

# Fredericton Fire Department

## Light Rescue

### Production Specification

**Contents**

LIABILITY INSURANCE ..... 5

INTERNET IN-PROCESS SITE ..... 5

VEHICLE STABILITY ..... 5

ROLLOVER STABILITY ..... 5

ROADABILITY ..... 6

SERVICEABILITY ..... 6

CONSTRUCTION DOCUMENTATION ..... 7

OPERATIONS AND SERVICE DOCUMENTATION ..... 8

NFPA REQUIRED DOCUMENTATION FORMAT - CD-ROM ..... 8

STATEMENT OF EXCEPTIONS ..... 9

CARRYING CAPACITY ..... 9

TESTING ..... 11

ROAD TEST ..... 11

LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST ..... 11

TEST SEQUENCE ..... 11

1. RESERVE CAPACITY TEST ..... 11

2. ALTERNATOR PERFORMANCE TEST ..... 12

TEST AT IDLE ..... 12

TEST AT FULL LOAD ..... 12

3. LOW VOLTAGE ALARM TEST ..... 12

LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST ..... 12

DOCUMENTATION ..... 12

UL 120/240 VAC CERTIFICATION ..... 13

DOCUMENTATION ..... 13

DIELECTRIC VOLTAGE WITHSTAND TEST ..... 14

PERFORMANCE BOND ..... 14

WARRANTY ..... 14

GENERAL LIMITED WARRANTY - ONE (1) YEAR ..... 14

LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS ..... 15

STRUCTURAL WARRANTY - TEN (10) YEARS ..... 15

PAINT LIMITED WARRANTY - TEN (10) YEARS ..... 15

GRAPHICS LIMITED WARRANTY ..... 15

CONSTRUCTION PERIOD ..... 15

OVERALL HEIGHT ..... 15

OVERALL LENGTH ..... 15

ENGINEERING SUPPORT AT PRE-CONSTRUCTION MEETING ..... 15

FINAL INSPECTION CONFERENCE ..... 16

DELIVERY AND DEMONSTRATION ..... 16

CAB CHASSIS SPECIFICATIONS ..... 17

2012 FORD F-550 CHASSIS 4X4 SD SUPER CAB 186" WB DRW XLT (X5H) ..... 17

POWERTRAIN ..... 17

STEERING AND SUSPENSION ..... 17

SAFETY ..... 17

COMFORT AND CONVENIENCE ..... 17

SEATING AND INTERIOR ..... 17

EXTERIOR FEATURES ..... 17

WARRANTY ..... 18

DIMENSIONS AND CAPACITIES ..... 18

REQUIRED ADDITIONS ..... 18

SELECTED OPTIONS ..... 18

PACKAGES ..... 18

POWERTRAIN ..... 19

WHEELS & TIRES ..... 19

# Fredericton Fire Department

## Light Rescue

### Production Specification

SEATS & SEAT TRIM .....	19
OTHER OPTIONS .....	19
CAB TO AXLE DIMESION .....	20
CHASSIS MODIFICATIONS .....	21
LUBRICATION AND TIRE DATA PLATE.....	21
VEHICLE DATA PLATE .....	21
OVERALL HEIGHT, LENGTH DATA PLATE (METRIC) .....	21
ACCIDENT PREVENTION.....	22
PERSONNEL CAPACITY.....	22
ACCIDENT PREVENTION.....	22
WEARING HELMET WARNING .....	22
FRONT BUMPER.....	22
FRONT BUMPER EXTENSION.....	22
BUMPER GRAVEL SHIELD.....	22
FRONT MOUNTED WINCH.....	22
FRONT TOW PROVISIONS .....	22
EXHAUST.....	23
RADIO/ANTENNA INSTALLATION .....	23
SEAT BELT COLOR.....	23
SEAT BELT WEB LENGTH - COMMERCIAL CAB .....	23
SEAT BELT/VDR SYSTEM.....	23
REAR CAB STORAGE MODULE .....	24
IGNITION KEY.....	24
SIX (6) – LED TIRE PRESSURE VISUAL INDICATORS .....	24
HELMET STORAGE.....	24
CAB MIRRORS, DRIVER ADJUSTABLE .....	24
ADD LOWER SECOND COLOR.....	24
PAINT DOOR JAMBS JOB COLOR .....	24
CHASSIS PAINT WARRANTY.....	25
CAB RUNNING BOARDS .....	25
STAINLESS STEEL WHEEL SIMULATOR KITS .....	25
MUDFLAPS .....	25
ROAD EMERGENCY SAFETY KIT .....	25
FUEL FILL .....	25
DEF FLUID FILL .....	25
BODY DESIGN.....	26
EXTERIOR ALUMINUM BODY.....	26
DRIP RAILS.....	27
ROOF CONSTRUCTION .....	27
BODY SUBFRAME.....	27
BODY MOUNTING.....	27
10" REAR STEP BUMPER.....	27
REAR TOW EYES.....	28
TRAILER HITCH.....	28
TRAILER ELECTRICAL RECEPTACLE .....	28
TRAILER AUXILIARY ELECTRICAL RECEPTACLE .....	28
GROUND LIGHTS.....	28
WHEEL WELL EXTERIOR PANEL.....	28
DIEFORMED BEADED EDGE BODY FENDERS .....	28
WHEEL WELL LINERS .....	28
SCBA CYLINDER COMPARTMENTS .....	29
BODY PAINT SPECIFICATIONS.....	29
BODY PAINT PREPARATION .....	29
PAINT PROCESS.....	29

# Fredericton Fire Department

## Light Rescue

### Production Specification

MACHINE POLISHED .....	29
PAINT - ENVIRONMENTAL IMPACT .....	30
PAINT FINISH - SINGLE COLOR .....	30
BODY UNDERCOATING .....	30
UNDERCOAT WARRANTY .....	30
PAINT WARRANTY .....	30
COMPARTMENT INTERIOR FINISH .....	30
REFLECTIVE STRIPE REQUIREMENTS .....	31
GRAPHICS PROOF .....	31
REFLECTIVE STRIPE - CAB SIDE .....	31
REFLECTIVE STRIPE - CAB FRONT .....	31
REFLECTIVE STRIPE - CAB DOOR INTERIOR.....	31
REFLECTIVE STRIPE - BODY SIDES .....	32
CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS .....	32
LETTERING.....	32
EXTERIOR COMPARTMENT DOORS.....	32
ROLL-UP DOOR CONSTRUCTION - AMDOR.....	32
BODY HEIGHT MEASUREMENTS .....	33
BODY WIDTH DIMENSIONS .....	33
STREETSIDE COMPARTMENT - FRONT (S1) .....	34
STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2).....	36
STREETSIDE COMPARTMENT - REAR (S3).....	37
CURBSIDE COMPARTMENT - FRONT (C1) .....	38
CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C2) .....	40
CURBSIDE COMPARTMENT - REAR (C3).....	41
REAR COMPARTMENT - CENTER (RC1).....	42
PLASTIC FLOOR AND SHELF TILE .....	44
FRONT GRAVEL GUARDS .....	44
LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC .....	44
12 VOLT MULTIPLEX CONTROL CENTER.....	47
WELDON CERTIFICATION .....	48
ROCKER SWITCH PANEL .....	48
CAB CONSOLE.....	48
BATTERY SYSTEM .....	49
BATTERY SWITCH.....	49
BATTERY SOLENOID.....	49
BATTERY CONDITIONER.....	49
SHORE POWER INLET .....	50
ENGINE COMPARTMENT LIGHT .....	50
MAP LIGHT .....	50
CAB SPOTLIGHT .....	50
CAB HAZARD WARNING LIGHT .....	51
BACK-UP ALARM .....	51
TAIL LIGHTS .....	51
MIDSHIP MARKER/TURN SIGNAL .....	51
MARKER LIGHTS .....	51
CAB STEP LIGHTS / GROUND LIGHTS.....	52
LICENSE PLATE LIGHT .....	52
ELECTRONIC SIREN.....	52
SIREN ACTIVATION .....	52
SIREN SPEAKER.....	52
SIDE SCENE LIGHTS .....	52
REAR SCENE LIGHTS .....	52
TRAFFIC DIRECTIONAL LIGHT.....	53

**Fredericton Fire Department**  
**Light Rescue**  
**Production Specification**

WARNING LIGHT PACKAGE ..... 53

UPPER LEVEL OPTICAL WARNING DEVICES ..... 54

GTT OPTICOM..... 54

LOWER LEVEL OPTICAL WARNING DEVICES ..... 55

LINE VOLTAGE ELECTRICAL SYSTEM..... 56

UNDERHOOD GENERATOR SYSTEM - (120 VAC) ..... 56

MANUALS AND SCHEMATICS ..... 56

ENGINE SPEED CONTROL ..... 56

LOADCENTER ..... 57

GENERATOR MONITORING PANEL..... 57

OUTLETS AND CIRCUITS..... 57

LINE VOLTAGE ELECTRICAL SYSTEM..... 57

GENERAL REQUIREMENTS..... 57

120/240 VAC SCENE LIGHTING..... 63

COMMAND LIGHT - KNIGHT TOWER w/ BACKLIGHT..... 63

RECESSED LIGHT TOWER ..... 64

EQUIPMENT PAYLOAD WEIGHT ALLOWANCE ..... 64

EQUIPMENT ..... 64

REMAINING NFPA MINOR EQUIPMENT BY PURCHASER..... 64

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **LIABILITY INSURANCE**

Bidder shall furnish with the bid a certificate of insurance for;

Workman's Compensation and Employer's Liability Insurance covering all employees.

General Liability each occurrence of \$1,000,000.00, General Aggregate of \$2,000,000.00 including Products Completed / Operations Aggregate.

Personal Injury of \$1,000,000.00, Fire damage of \$50,000.00 and Medical expense of \$10,000.00. Automobile liability of \$1,000,000.00 combined single limit (each accident), including any auto, all owned autos, scheduled autos, hired autos, non-owned autos, and garage liability.

Excess Umbrella Liability coverage of \$2,000,000.00 each occurrence, Aggregate of \$2,000,000.00.

All insurance policies must be;

- Maintained for the life of the contract,
- Must provide ten (10) days notice before cancellation,
- Must cover all operations of the contractor, or anyone employed by them.

#### **INTERNET IN-PROCESS SITE**

The Bidder shall post and maintain a website where the Fredericton Fire Department will be able to view digital images of their apparatus as its being manufactured. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of the apparatus.

#### **VEHICLE STABILITY**

##### **ROLLOVER STABILITY**

The apparatus shall meet the criteria defined below, or it shall be equipped with a stability control system defined below.

The apparatus shall meet the criteria defined in either of the following:

- 1) The apparatus shall remain stable to 26.5 degrees in both directions when tested on a tilt table in accordance with SAE J2180, *A Tilt Table Procedure for Measuring the Static Rollover Threshold for Heavy Trucks*.
- 2) The calculated or measured center of gravity (CG) shall be no higher than 80 percent of the rear axle track width.

Compliance shall be certified by testing, calculating, or measuring the apparatus or by comparing the apparatus to a compliant, substantially similar example apparatus and the certification shall be delivered with the fire apparatus.

The example apparatus shall be considered substantially similar if it includes a chassis with the same or higher CG height, the same or narrower rear axle track width, the same or greater water tank size and CG height, the same type of front and rear suspension and the same type and size of aerial device.

The apparatus shall be loaded with fuel, fire-fighting agents, hose, ladders, a weight of 250 lb in each seating position and weight equivalent to the Miscellaneous Equipment Allowance as defined in NFPA 1901, 2009 Edition, Table 12.1.2.

If the apparatus is designed to meet a specified higher equipment loading or larger hose bed capacity or to carry additional ground ladders, these greater loads shall be included in the testing, calculating or measuring.

The weight added to the fire apparatus for the purpose of test, calculation or measurement shall be distributed to approximate typical in-service use of the fire apparatus while not exceeding the manufacturer's published individual

# Fredericton Fire Department

## Light Rescue

### Production Specification

compartment weight ratings.

If the apparatus is equipped with a stability control system, the system shall have, at a minimum, a steering wheel position sensor, a vehicle yaw sensor, a lateral accelerometer and individual wheel brake controls.

#### **ROADABILITY**

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- 1) From a standing start, the apparatus shall be able to attain a speed of 35 mph (55 km/hr) within 25 seconds on a level road.
- 2) The apparatus shall be able to attain a minimum top speed of 50 mph (80 km/hr) on a level road.
- 3) The apparatus shall be able to maintain a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent.

The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (105 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal (4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (85 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

#### **SERVICEABILITY**

The fire apparatus shall be designed to allow the manufacturer's recommended routine maintenance checks of lubricant and fluid levels to be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **CONSTRUCTION DOCUMENTATION**

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

The manufacturers record of apparatus construction details, including the following information:

- 1) Owner's name and address
- 2) Apparatus manufacturer, model, and serial number
- 3) Chassis make, model, and serial number
  - a) GAWR of front and rear axles and GVWR
  - b) Front tire size and total rated capacity in pounds (kilograms)
  - c) Rear tire size and total rated capacity in pounds (kilograms)
  - d) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
  - e) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
  - f) Type of fuel and fuel tank capacity
  - g) Electrical system voltage and alternator output in amps
  - h) Battery make, model, and capacity in cold cranking amps (CCA)
  - i) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
- 4) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
- 5) Pump transmission make, model, serial number, and gear ratio
- 6) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
- 7) Water and Foam tank certified capacity in gallons or liters
- 8) Paint manufacturer and paint number(s)
- 9) Company name and signature of responsible company representative
- 10) If the apparatus is a mobile foam fire apparatus, the certification of foam tank capacity
- 11) Certification of compliance of the optical warning system
- 12) Siren manufacturer's certification of the siren
- 13) Written load analysis and results of the electrical system performance tests
- 14) Certification of slip resistance of all stepping, standing, and walking surfaces
- 15) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability
- 16) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions
- 17) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications
- 18) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed
- 19) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test
- 20) If the apparatus has a fire pump, the certification of inspection and test for the fire pump
- 21) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test
- 22) When the apparatus is equipped with a water tank, the certification of water tank capacity
- 23) If the apparatus has an aerial device, the certification of inspection and test for the aerial device
- 24) If the apparatus has an aerial device, all the technical information required for inspections to comply with NFPA 1911, Standard for the Inspection, Maintenance, Testing, and Retirement of In-Service Automotive Fire Apparatus
- 25) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy and the final installer's certification the foam proportioning system meets this standard
- 26) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests
- 27) If the apparatus has a line voltage power source, the certification of the test for the power source
- 28) If the apparatus is equipped with an air system, air tank certificates, the SCBA fill station certification, and the results of the testing of the air system installation
- 29) Any other required manufacturer test data or reports.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **OPERATIONS AND SERVICE DOCUMENTATION**

The Contractor shall deliver with the fire apparatus at least two (2) sets of complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof.

The Contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- 1) Manufacturer's name and address
- 2) Country of manufacture
- 3) Source for service and technical information
- 4) Parts replacement information
- 5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- 6) Wiring diagrams for low voltage and line voltage systems to include the following information:
  - j) Pictorial representations of circuit logic for all electrical components and wiring
  - k) Circuit identification
  - l) Connector pin identification
  - m) Zone location of electrical components
  - n) Safety interlocks
  - o) Alternator-battery power distribution circuits
  - p) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- 7) Lubrication charts
- 8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- 9) Precautions related to multiple configurations of aerial devices, if applicable
- 10) Instructions regarding the frequency and procedure for recommended maintenance
- 11) Overall apparatus operating instructions
- 12) Safety considerations
- 13) Limitations of use
- 14) Inspection procedures
- 15) Recommended service procedures
- 16) Troubleshooting guide
- 17) Apparatus body, chassis and other component manufacturer's warranties
- 18) Special data required by this standard
- 19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus

The Contractor shall deliver with the apparatus all manufacturer's operations and service documents supplied with components and equipment that are installed or supplied by the Contractor.

#### **NFPA REQUIRED DOCUMENTATION FORMAT - CD-ROM**

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a CD-ROM. These manuals shall be divided into sections for ease of reference. There shall be two (2) copies of the CD-ROM provided with the completed vehicle.



# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **STATEMENT OF EXCEPTIONS**

The Contractor shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- 20) A separate specification of the section of the applicable standard for which compliance is lacking
  - 1) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
  - 2) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance
  - 3) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to or at the time of delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

An apparatus that is delivered subject to a Statement of Exceptions other than a certification of full compliance shall not be placed in emergency service until the apparatus has been modified as necessary to accomplish full compliance with this standard.

#### **CARRYING CAPACITY**

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The Body Manufacturer shall establish the estimated in service weight during the design of the vehicle

The estimated in-service weight shall include the following:

- 4) The chassis, body and tank(s)
  - 1) Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
  - 2) Full water and other agent tanks
  - 3) \*250 lb (114 kg) in each seating position
  - 4) Fixed equipment such as pumps, aerial devices, generators, reels and air systems as installed
  - 5) Ground ladders, suction hose, designed hose load in their hose beds and on their reels
  - 6) An allowance for miscellaneous equipment that is the greatest of the values for type of vehicle per NFPA 1901, a Purchaser provided list of equipment to be carried with weights or a Purchaser specified miscellaneous equipment allowance.

The Body Manufacturer shall engineer and design the vehicle such that the completed unit, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

# Fredericton Fire Department

## Light Rescue

### Production Specification

A final Body Manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

Apparatus Type	Equip. Storage Area	Apparatus Size	Equipment Allowance	
			lb.	kg.
Special Service Fire Apparatus	Minimum of 120 cu ft (3.4 cu mt) of enclosed compartmentation.	10,000 lb to 15,000 lb (4,500 kg to 7,000 kg) GVWR	2,000	910
		15,001 lb to 20,000 lb (7,001 kg to 9,000 kg) GVWR	2,500	1,135
		20,001 lb to 30,000 lb (9,001 kg to 14,000 kg) GVWR	3,000	1,350
		30,001 lb to 40,000 lb (14,001 kg to 18,000 kg) GVWR	4,000	1,800
		40,001 lb to 50,000 lb (18,001 kg to 23,000 kg) GVWR	6,000	2,700
		50,001 lb to 60,000 lb (23,001 kg to 27,000 kg) GVWR	8,000	3,600
		60,001 lb and up (27,001 kg) GVWR	10,000	4,500

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **TESTING**

#### **ROAD TEST**

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the Body Manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

#### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (-18°C and 43°C).

#### **TEST SEQUENCE**

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for ten (10) minutes. Failure of any of these tests shall require a repeat of the sequence.

#### **1. RESERVE CAPACITY TEST**

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

# Fredericton Fire Department

## Light Rescue

### Production Specification

## **2. ALTERNATOR PERFORMANCE TEST**

### **TEST AT IDLE**

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

### **TEST AT FULL LOAD**

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

## **3. LOW VOLTAGE ALARM TEST**

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

## **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

### **DOCUMENTATION**

The manufacturer shall deliver the following with the fire apparatus:

- 7) Documentation of the electrical system performance tests
- 1) A written electrical load analysis, including the following:
  - 2) The nameplate rating of the alternator
  - q) The alternator rating
  - r) Each of the component loads specified that make up the minimum continuous electrical load
  - a) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
  - b) Each individual intermittent electrical load

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **UL 120/240 VAC CERTIFICATION**

The 120/240 volt electrical system shall be tested and certified by Underwriters Laboratories, to perform as listed below;

The prime mover shall be started from a cold start condition, and the unloaded voltage and frequency shall be recorded.

The line voltage electrical system shall be loaded to at least 100% of the continuous rated wattage stated on the power source specification label. Testing with a resistive load bank shall be permitted.

The power source shall be operated in the manner specified by the apparatus manufacturer as documented on instruction plates or in operation manuals. The power source shall be operated at a minimum of 100% of the continuous rated wattage as stated on the power source specification label for a minimum of two (2) hours.

The load shall be adjusted to maintain the output wattage at or above the continuous rated wattage during the entire 2-hour test.

The following conditions shall be recorded at least every 1/2 hour during the test:

- c) The power source output voltage, frequency and amperes
- d) The prime mover's oil pressure, water temperature and transmission temperature, if applicable
  - 1) The power source hydraulic fluid temperature, if applicable
  - 2) The ambient temperature and power source air inlet temperature

The following conditions shall be recorded once during the test for power sources driven by dedicated auxiliary internal combustion engines:

- 3) Altitude
- 4) Barometric pressure
- 1) Relative humidity

If the generator is driven by the chassis engine and the generator allows for operation at variable speeds, the chassis engine speed shall be reduced to the lowest rpm allowed for generator operation and the voltage and frequency shall be recorded.

The load shall be removed and the unloaded voltage and frequency shall be recorded.

Voltage shall be maintained within  $\pm 10\%$  of the voltage stated on the power source specification label during the entire test. Frequency shall be maintained within  $\pm 3$  Hz of the frequency stated on the power source specification label during the entire test.

The total continuous electrical loads, excluding those loads associated with the equipment defined in NFPA 22.15.7.3.11.2, shall be applied during the testing unless an auxiliary engine drives the power source.

If the apparatus is equipped with a fire pump, the 2-hour certification test of the power source shall be completed with the fire pump pumping at 100% capacity at 150 psi (1000 kPa) net pump pressure. The test shall be permitted to be run concurrently with the pump certification test.

#### **DOCUMENTATION**

The Body Manufacturer shall deliver the following with the fire apparatus:

The results of each test shall be recorded on an appropriate form and provided with the delivery of the fire apparatus.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **DIELECTRIC VOLTAGE WITHSTAND TEST**

The line voltage wiring and permanently connected devices and equipment shall be subjected to a dielectric voltage withstand test of 900 volts for one (1) minute. The testing shall be performed after all body work has been completed.

The test shall be conducted as follows:

- 2) Isolate the power source from the panel board and disconnect any solid state low voltage components
- 3) Connect one lead of the dielectric tester to all the hot and neutral buses tied together
- 1) Connect the other lead to the fire apparatus frame or body
- 2) Close any switches and circuit breakers in the circuit(s)
- 3) Apply the dielectric voltage for one (1) minute in accordance with the testing equipment manufacturer's instructions

The electrical polarity of all permanently wired equipment, cord reels and receptacles shall be tested to verify that wiring connections have been properly made.

Electrical continuity shall be verified from the chassis or body to all line voltage electrical enclosures, light housings, motor housings, light poles, switch boxes and receptacle ground connections that are accessible to fire fighters in normal operations.

If the apparatus is equipped with a transfer switch, it shall be tested to verify operation and that all non grounded conductors are switched.

Electrical light towers, floodlights, motors, fixed appliances and portable generators shall be operated at their full rating or capacity for 30 minutes to ensure proper operation.

#### **PERFORMANCE BOND**

The successful Bidder will be required to provide a performance bond in the amount of \$10,000.00. Performance bond shall be provided within two (2) weeks after notice of award.

The terms of the performance bond shall continue one (1) year after completion and delivery of the apparatus.

#### **WARRANTY**

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source and will deal directly with the Fredericton Fire Department on all warranty work.

#### **GENERAL LIMITED WARRANTY - ONE (1) YEAR**

The vehicle shall be free of defects in material and workmanship for a period of one (1) year or 24,000 miles (or 38,624 kilometers), whichever occurs first starting thirty (30) days after the original invoice date.

The Contractor must be the "single source" coordinator of all warranties on the vehicle.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS**

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles (or 96,561 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

#### **STRUCTURAL WARRANTY - TEN (10) YEARS**

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

#### **PAINT LIMITED WARRANTY - TEN (10) YEARS**

The body shall be free of bubbling or peeling as a result of a defect in the method of manufacture for a period of ten (10) years or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

#### **GRAPHICS LIMITED WARRANTY**

The 3M graphics installation shall be warranted for a period of two (2) years. The 3M materials installed on completed vehicle shall be warranted for seven (7) years. The 3M Diamond grade film (if specified) shall be warranted for ten (10) years.

#### **CONSTRUCTION PERIOD**

The completed vehicle shall be delivered within two hundred forty (240) days after receipt of a purchase order or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to Fredericton Fire Department as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

#### **OVERALL HEIGHT**

The overall height (OAH) of the vehicle shall be approximately 92" (7' - 8") from the ground. This measurement shall be taken on flat ground with the tires properly inflated, in the unloaded condition, at that highest point of the vehicle.

#### **OVERALL LENGTH**

The overall length (OAL) of the vehicle shall be approximately 310"(25' -10").

#### **ENGINEERING SUPPORT AT PRE-CONSTRUCTION MEETING**

The Contractor shall provide an engineer to be present at the pre-construction meeting held at the Fredericton Fire Department location. The engineer will address all engineering related questions for the truck as purchased and for all proposed changes.

The engineer will have the 2D AutoCAD electronic drawing on hand and be able to provide dimensional data for proposed changes and proposed layouts. This will help ensure that the final design matches the Fredericton Fire Department intentions to the maximum extent possible.

Inspection Trips, Delivery, Demonstration

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **FINAL INSPECTION CONFERENCE**

A final inspection conference shall be required, at the Contractor's factory for two (2) personnel from the Fredericton Fire Department to inspect the vehicle and construction details prior to shipment of the completed vehicle. This inspection shall take place after any specified striping and lettering is installed.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the final inspection conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

#### **DELIVERY AND DEMONSTRATION**

The Contractor shall be responsible for the delivery of the completed unit to the Fredericton Fire Department's location. On initial delivery of the apparatus, the Contractor shall supply a qualified representative to demonstrate the apparatus and provide initial instruction to representatives of the Fredericton Fire Department regarding the operation, care and maintenance of the apparatus and equipment supplied at Fredericton Fire Department location.

The Delivery Engineer shall set delivery and instruction schedule with the person appointed by Fredericton Fire Department.

After delivery of the apparatus, the Fredericton Fire Department shall be responsible for ongoing training of its personnel to proficiency regarding the proper and safe use of the apparatus and associated equipment.



# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **CAB CHASSIS SPECIFICATIONS**

#### **2012 FORD F-550 CHASSIS 4X4 SD SUPER CAB 186" WB DRW XLT (X5H)**

#### **POWERTRAIN**

Triton 6.8L V-10 SOHC SMPI 30 valve engine \* 155 amp HD alternator \* 750 amp 78 amp hours (Ah) HD battery with run down protection \* Engine block heater, transmission oil cooler \* 5-speed electronic SelectShift automatic transmission with overdrive, lock-up, driver selection \* Part-time four-wheel drive with manual transfer case shift, manual locking hubs \* Limited slip differential, driveline traction control \* 4.88 axle ratio \* Stainless steel exhaust

#### **STEERING AND SUSPENSION**

Hydraulic power-assist re-circulating ball steering \* 4-wheel disc brakes with front and rear vented discs \* Firm ride suspension \* Mono-beam non-independent front suspension \* Front anti-roll bar \* Front coil springs \* HD front shocks \* Rigid rear axle \* Rear leaf suspension \* Rear anti-roll bar \* HD rear leaf springs \* HD rear shocks \* Front and rear 19.5" x 6.00" argent steel wheels \* LT225/70SR19.5 BSW AS front and rear tires

#### **SAFETY**

4-wheel anti-lock braking system \* Daytime running lights \* Dual airbags, passenger side front-impact cancellable airbag, seat mounted driver and passenger side-impact airbags, Safety Canopy System curtain 1st and 2nd row overhead airbags \* Front height adjustable seatbelts \* SecuriLock immobilizer, panic alarm, security system

#### **COMFORT AND CONVENIENCE**

Air conditioning, underseat ducts \* AM/FM stereo, clock, seek-scan, in-dash mounted single CD, MP3 decoder, 4 speakers, fixed antenna \* Cruise control with steering wheel controls \* Power door locks with 2 stage unlock, keyfob (front doors) keyless entry \* 3 12V DC power outlets, retained accessory power \* Analog instrumentation display includes tachometer, oil pressure gauge, engine temperature gauge, transmission fluid temp gauge, engine hour meter, exterior temp, systems monitor, trip odometer \* Warning indicators include oil pressure, engine temperature, battery, lights on, key, low fuel, door ajar, brake fluid \* Steering wheel with tilt and telescopic adjustment \* Power front windows and vented rear windows with deep tint, driver 1-touch down \* Variable intermittent front windshield wipers \* Dual vanity mirrors \* Day-night rearview mirror \* Interior lights include dome light with fade, front reading lights, illuminated entry \* Full overhead console with storage, glove box, front and rear cupholders, instrument panel bin, 2 seat back storage pockets, driver and passenger door bins, locking 1st row underseat storage \* Upfitter switches

#### **SEATING AND INTERIOR**

Seating capacity of 6 \* 40-20-40 split-bench front seat with adjustable head restraints, centre armrest with storage \* 4-way adjustable driver seat includes lumbar support \* 4-way adjustable passenger seat \* 60-40 folding rear split-bench seat with fold-up cushion, 2 fixed rear head restraints \* Cloth faced front seats with cloth back material \* Cloth faced rear seats with carpet back material \* Full cloth headliner, full carpet floor covering with carpet front and rear floor mats, plastic/rubber gear shift knob, chrome interior accents

#### **EXTERIOR FEATURES**

Side impact beams, front license plate bracket, fully galvanized steel body material \* Black fender flares \* Black side window mouldings, black front windshield moulding \* Black door handles \* Chrome grille \* 4 doors with reverse opening rear driver's side door, reverse opening rear passenger's side door \* Trailer harness \* Driver and passenger power remote black heated convex spotter folding manual extendable trailer outside mirrors with turn signal indicators \* Front chrome bumper with front tow hooks \* Aero-composite halogen headlamps \* Additional exterior lights include cab clearance lights, underhood light, remote activated perimeter/approach lights \* Clearcoat monotone paint

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **WARRANTY**

Basic 36 month/37,283 miles \* Powertrain 60 month/62,139 miles \* Corrosion Perforation 60 month/unlimited mileage \* Roadside Assistance 60 month/62,139 miles \* Accessories 36 month/37,283 miles

#### **DIMENSIONS AND CAPACITIES**

Output 362 hp @ 4,750 rpm \* Torque 457 lb.-ft. @ 3,250 rpm \* 1st gear ratio 3.110 \* 2nd gear ratio 2.220 \* 3rd gear ratio 1.550 \* 4th gear ratio 1.000 \* 5th gear ratio 0.710 \* Reverse gear ratio 2.880 \* Curb weight 7,500 lbs. \* GVWR 18,000 lbs. \* Front GAWR Weight 6,000 lbs. \* Rear GAWR Weight 13,660 lbs. \* Payload 10,500 lbs. \* Front curb weight 4,299 lbs. \* Rear curb weight 3,201 lbs. \* Front axle capacity 7,000 lbs. \* Rear axle capacity 13,660 lbs. \* Front spring rating 6,000 lbs. \* Rear spring rating 13,660 lbs. \* Front tire/wheel capacity 7,500 lbs. \* Rear tire/wheel capacity 15,000 lbs. \* Towing capacity 16,000 lbs. \* 5th-wheel towing capacity 17,500 lbs. \* Front legroom 41.1 " \* Rear legroom 31.6 " \* Front headroom 40.7 " \* Rear headroom 38.1 " \* Front hiproom 67.6 " \* Rear hiproom 67.3 " \* Front shoulder room 68.0 " \* Rear shoulder room 68.1 " \* Passenger area volume 113.3 cu.ft. \* Length 271.5 " \* Body width 93.9 " \* Body height 80.5 " \* Wheelbase 186.0 " \* Cab to axle 84.0 " \* Axle to end of frame 47.6 " \* Front tread 74.8 " \* Rear tread 74.0 " \* Turning radius 26.2 ' \* Fuel tank 33.3 gal.

#### **REQUIRED ADDITIONS**

Additional Owner's manual \* Additional Engine Manual \* Optional Extended Warranty *Emergency vehicles are not eligible for ext. Warranties* \* Vinyl Floor Covering (BC3Z2613010AA) \* Freight to SVI Trucks, Loveland, CO \* Exhaust is specified to have discharge 1 foot forward of rear wheel. *If factory exhaust does not conform the body manufacturer (SVI Trucks) will be required to make specified modifications.* \* Front & Rear Wheels & Tires specifies LT225/70G19.5 BSW traction. Ford only provides 225/70RX19.5G BSW AS (All-Season). \* Ford only provides premium Ford only provides premium cloth cloth bucket seats bucket seats. The request specifies vinyl seating. The request specifies vinyl seating surfaces and seat backs. Any upgrade of seating surfaces and seat backs is the responsibility of SVI Trucks and shall be quoted by them based on local pricing. \* Ford only provides for carpeted floor coverings in the captains chair configuration. Carpet Delete options is only available in the 40/20/40 bench seat configuration. The floor covering for this configuration is quoted above and will require SVI to install said floor covering during the vehicle modification process.

#### **SELECTED OPTIONS**

4x4 SD Super Cab 186" WB DRW XLT (X5H)

#### **PACKAGES**

963A Order Code 963A

(99Y) Engine: 6.8L 3-Valve SOHC EFI Modular V10;(44T) Transmission: TorqShift 5-Speed Automatic w/OD: Includes tow haul mode.; (X8L) Limited Slip w/4.88Axle Ratio; (STDGV) GVWR: 8,165 kgs (18,000 lbs) Payload Package; (TFB) Tires: 225/70Rx19.5G BSWAS; (64Z) Wheels: 19.5" Argent Painted Steel (6); (3)Cloth 40/20/40 Split Bench Seat w/Recline : Includes fold-down centre armrest with 2 cup holders, lift up centre-seat with locking storage, power point and driver's side manual lumbar.; (585) Radio: AM/FM Stereo w/Single CD/MP3 Player : Includes digital clock,4-speakers and My Key.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **POWERTRAIN**

99T Engine: 6.7L 4V Diesel V8  
*200 Amp Extra Heavy Duty Alternator; (X4N) Limited Slip w/4.10 Axle Ratio; Dual 78 AH Batteries. Includes large plastic urea tank and exhaust brake (B20capability). Torque: 660 ft.lbs. @ 1600 rpm.*

44W Transmission: 6-Speed Automatic w/Select Shift  
*Includes tow haul mode.*

X8L Limited Slip w/4.88 Axle Ratio (w/99T/68M)

68M GVWR: 8,845 kgs (19,500 lbs) Payload

#### **WHEELS & TIRES**

TFB Tires: 225/70R19.5G BSW AS

64Z Wheels: 19.5" Argent Painted Steel (6)

#### **SEATS & SEAT TRIM**

2 Cloth Luxury Captain's Chairs  
*Flow-Through Centre Console w/Column Shifter :Includes 110 volt power point outlet and storage. Includes driver side manual lumbar.*

90D 6-Way Power Driver Seat Adjuster  
*Includes manual 2-way passenger adjust and 2-way manual lumbar on drivers side only.*

#### **OTHER OPTIONS**

PAINT Monotone Paint Application

186WB 186" Wheelbase/84" Cab to Axle

61J 6-Ton Hydraulic Jack

213 Electronic-Shift-On-The-Fly  
*Includes auto-manual-locking hubs and rotary control on instrument panel.*

54F Power Scope Trailer Tow Mirrors  
*Includes power telescoping, power-folding, power heated glass, heated convex spotter mirror and integrated clearance lights/turn signals.*

52B Trailer Brake Controller  
*Includes wiring from Trailer Tow Prep Package. Verified to be compatible with electronic actuated drum brakes only.*

585 Radio: AM/FM Stereo w/Single CD/MP3 Player  
*Includes digital clock, 4-speakers and My Key*

86S Low Deflection Package  
*Includes 2-inch spacer blocks. Recommended for rear-biased loading, such as wrecker/retriever applications.*

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### 67X Extra Heavy-Service Suspension Package

*Includes pre-selected extra heavy-service front springs(see Super Duty Supplemental Reference manual for springs/FGAWR of specific vehicle configurations).Recommended only on vehicles which will permanently utilize aftermarket equipment such as heavy duty winches, brush guards or other apparatus which loads the front axle to the specified Gross Axle Weight Rating(GAWR). NOTE 1: May result in a deterioration of ride quality. NOTE 2: Vehicle ride height will increase with the addition of this package.*

#### 535 High Capacity Trailer Tow Package

*Trailer brake controller not included. Includes upgraded rear-axle. Increases GCW from 26,000 lbs. to 35,000 lbs. NOTE 1: Salesperson's Portfolio or Trailer Towing Guide should be consulted for specific trailer towing or camper limits and corresponding required equipment, axle ratios and model availability. See Supplemental Reference Manual for vehicle height consideration.*

#### 153 Front License Plate Bracket (LPO)

*Standard in British Columbia, Manitoba, New Brunswick, Ontario and Saskatchewan.*

Interior Colours For : Primary w/XLT

2S Steel

Primary Colours For : Primary w/XLT

Z1 Oxford White

#### **CAB TO AXLE DIMESION**

Cab to axle will be 84".

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **CHASSIS MODIFICATIONS**

#### **LUBRICATION AND TIRE DATA PLATE**

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- 4) Engine oil
- 5) Engine coolant
  - Chassis transmission fluid
  - Pump transmission lubrication fluid . . (if applicable)
  - Pump priming system fluid, if applicable . . (if applicable)
  - Drive axle(s) lubrication fluid
  - Air conditioning refrigerant . . (if applicable)
  - Air conditioning lubrication oil . . (if applicable)
  - Power steering fluid
  - Cab tilt mechanism fluid . . (if applicable)
  - Transfer case fluid . . (if applicable)
  - Equipment rack fluid (if applicable)
  - CAFS air compressor system lubricant . . (if applicable)
  - Generator system lubricant . . (if applicable)
  - Front tire cold pressure
  - Rear tire cold pressure
  - Maximum tire speed ratings

#### **VEHICLE DATA PLATE**

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the;
  - Engine
  - Transmission
    - Air
    - Fuel
- Serial numbers for the;
  - Engine
  - Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

#### **OVERALL HEIGHT, LENGTH DATA PLATE (METRIC)**

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in meters, the length of the completed fire apparatus in meters and the GVWR in kilograms.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **ACCIDENT PREVENTION**

There shall be a placard in the cab seating area which reads, "ALL OCCUPANTS MUST BE SEATED AND BELTED WHEN THE APPARATUS IS IN MOTION".

#### **PERSONNEL CAPACITY**

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

#### **ACCIDENT PREVENTION**

If the rear bumper is 8" deep or more, there shall be a placard on the rear face of the body, in clear sight from the ground, which reads, "WARNING - DO NOT RIDE ON STEPS OR DECK AREAS WHILE THE APPARATUS IS IN MOTION. DEATH OR SERIOUS INJURY MAY RESULT".

#### **WEARING HELMET WARNING**

A label stating "DO NOT WEAR HELMET WHILE SEATED" shall be visible from each seating location.

#### **FRONT BUMPER**

The front bumper shall be as provided by the cab/chassis manufacturer. No other alternation or modifications are required.

#### **FRONT BUMPER EXTENSION**

The front bumper of the chassis shall be extended approximately 16" ahead of the cab using Junior I-beams.

The bumper mounting plate shall be welded to the Junior I-beam for mounting of the chassis bumper. After fabrication of the bumper extension, the panels shall be removed and the unit shall be primed and painted black.

#### **BUMPER GRAVEL SHIELD**

The front bumper extension shall have a 3/16" NFPA compliant aluminum tread plate gravel shield. The gravel shield shall cover the full width of the front bumper to the front of the cab and the full height of the bumper on each end.

#### **FRONT MOUNTED WINCH**

The bumper extension shall be equipped with a Warn M12000, 12 volt electric, 12,000 lb. capacity winch.

The control of the winch shall be with a plug-in remote control unit. The unit shall have 12' of control cable, with forward, neutral and reverse dead man type hand control.

The winch shall be equipped with 125' of 3/8" galvanized cable. The cable shall end with a clamped type loop and a drop forged heavy duty hook. The cable shall feed through a full captive type 4-way roller and guide assembly.

#### **FRONT TOW PROVISIONS**

The front tow provisions shall be supplied and installed by the cab/chassis manufacturer.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **EXHAUST**

The existing exhaust tailpipe shall be modified from the stock location by cutting the pipe and adding a connector and band clamp.

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the apparatus or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

#### **RADIO/ANTENNA INSTALLATION**

There shall be one (1) Fredericton Fire Department supplied radio(s) with antenna installed in the cab within easy reach of driver. The location of radio shall be determined by the Fredericton Fire Department at the pre-construction meeting.

Radio shall be installed per Manufacturer's requirements and wired for proper 12 volt power and ground.

#### **SEAT BELT COLOR**



Section 14.1.3.4 of the NFPA 1901 Standards, 2009 edition, requires all seat belt webbing in cab to be bright red or bright orange in color, and the buckle portion of the seat belt shall be mounted on a rigid or semi rigid stalk such that the buckle remains positioned in an accessible location.

#### **SEAT BELT WEB LENGTH - COMMERCIAL CAB**

Sections 14.1.3.2 and 14.1.3.3 of the NFPA 1901 standards, 2009 edition, require the effective seat belt web length for a Type 1 lap belt for pelvic restraint to be a minimum of 60", and a Type 2 pelvic and upper torso restraint-style seat belt assembly to be a minimum of 110".

The chassis seat belt web length as supplied by the commercial chassis manufacturer shall be compliant to NFPA Standards 14.1.3.2 and 14.1.3.3.

#### **SEAT BELT/VDR SYSTEM**



The specified Ford F550 4-Door cab/chassis will be shipped from Ford manufacturing plant, thru to Manning Equipment using Ford code 31M D9E. The completed system shall meet NFPA 1901 for seat belt monitoring, and seat belt length and color. System shall include;

- Five (5) Seat sensors (2 front, 3 rear)
- One (1) Interface module mounted under front dash
- One (1) Intermotive display (temporary mount for OEM to locate)
- One (1) Fire Research Inc. Vehicle Data Recorder (VDR), located behind rear seat
- One (1) Wireless interface module w/USB cable and CD Rom
- One (1) Wire harness kit
- Five (5) 110" red seat belts using OEM hardware

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **REAR CAB STORAGE MODULE**

A storage module shall be provided in the rear area of the extended cab. The module shall be designed to hold the following items while providing floor storage for one (1) set of bunker gear per side on the floor:

- One (1) "D" sized oxygen cylinder storage module. The module shall be capable of storing one (1) cylinder up to 6" diameter.
- Two (2) MSA SCBA air packs. The packs shall be secured to the module with two (2) Zico 1000 series KD-UH walkaway type SCBA air pack bracket(s) with high cycle coated spring clips and angled foot plate (CRS strap inc.). The air packs shall be accessible from the exterior of the apparatus.
- One (1) medical bag storage area(s). One (1) bag shall measure approximately 22.0"L x 14.0"W x 8.5"H.
- One (1) defibrillator storage area(s). The defibrillator shall measure approximately 14.0"L x 6.0"W x 14.0"H.
- One (1) oxygen bag storage area(s). The oxygen bag shall measure approximately 24.0"L x 15.0"W x 12.0"H.
- There shall be three (3) OnScene Solutions cargo straps provided to secure the stored equipment.

#### **IGNITION KEY**

If the vehicle is specified to have an ignition key it will be attached to steering column or dash with vinyl covered steel cable.

#### **SIX (6) – LED TIRE PRESSURE VISUAL INDICATORS**

Each tire shall be equipped with a VECSAFE heavy duty valve cap (or equal) LED indicator that indicates proper tire pressure.

#### **HELMET STORAGE**

No helmet storage is required in the in the cab driving or crew area.

#### **CAB MIRRORS, DRIVER ADJUSTABLE**

Section 14.3.5 of the NFPA 1901 Standards, 2009 edition, requires all primary rear view mirrors used by the driver to be adjustable from the driver's position.

#### **ADD LOWER SECOND COLOR**

The cab exterior (door jambs not painted unless specified otherwise) shall be re-painted with a second color over the main cab color from the bottom of the glass up over cab roof with PPG Delfleet Evolution paint.

Color: Red

Paint Number: FBCH-75280 to match DuPont N3240 Imron Elite RED

#### **PAINT DOOR JAMBS JOB COLOR**

Two (2) chassis door jambs will be painted to match the exterior color of the chassis.



# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **CHASSIS PAINT WARRANTY**

The portion of the cab re-painted shall be provided with a ten (10) year, non-prorated paint warranty to the original owner. The warranty shall be provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle.

#### **CAB RUNNING BOARDS**

The chassis shall be provided with running boards each side, below the cab doors. The running boards shall be constructed of aluminum 3003H-14 alloy NFPA nonskid compliant tread plate.

#### **STAINLESS STEEL WHEEL SIMULATOR KITS**

Front and rear stainless steel wheel simulator kits shall be provided.

The kits shall include American made RealWheels brand mirror finish, 304L grade, non-corrosive stainless steel Universal wheel simulators meeting D.O.T. certification standards. They shall simulate the look of polished aluminum wheels and come complete with stainless steel hub covers and lug nut covers.

All stainless steel simulators shall carry a lifetime warranty.

#### **MUDFLAPS**

There shall be rubber mudflaps furnished and installed behind each set of tires.

#### **ROAD EMERGENCY SAFETY KIT**

One (1) set of three (3) dual faced triangular warning flares with fold away base complete with storage case per DOT requirements shall be provided with the completed apparatus.

One (1) 2.5 lb. ABC type vehicle fire extinguisher with bracket per DOT requirements shall be provided with the completed apparatus.

#### **FUEL FILL**

There shall be one (1) fuel fill door located on the rear of the body streetside. The fill door shall be fabricated from brushed stainless steel. There shall be a permanent label with the text "DIESEL FUEL ONLY" located adjacent to the fuel fill access.

#### **DEF FLUID FILL**

There shall be one (1) DEF fluid fill located in the streetside over-wheel compartment, ahead of the rear axle. The fill guard shall have an open face and a permanent label with the text "DEF ONLY".

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **BODY DESIGN**

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the Fredericton Fire Department to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the Fredericton Fire Department from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

#### **EXTERIOR ALUMINUM BODY**

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 3/16" (.187) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas, No Exceptions.

The front and rear corners of body shall be formed as part of the front or rear body panels. This provides a stronger body corner and finished appearance. The use of extruded corners, or caps will not be acceptable, No Exceptions.

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

# Fredericton Fire Department

## Light Rescue

### Production Specification

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded and caulked to prevent moisture from entering the compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

Exterior compartments shall have louvers in lower back wall of compartment for ventilation.

#### **DRIP RAILS**

The body shall have drip rails over the side full height compartments. The drip rails shall be formed into the upper body panels providing a ridged lower panel and a flat upper body panel surface. The use of mechanically fastened, taped or glued on drip rails will not be acceptable, No Exceptions.

#### **ROOF CONSTRUCTION**

The roof shall be integral with the body and shall be all welded construction. The roof of the body shall not be less than 3/16" aluminum 3003H-14 alloy tread plate, fully and continuously welded. The roof shall be reinforced with 2" x 2" x 1/4" aluminum tubing running the full width of the body.

All seams in the roof area shall be welded to the radius and supports prior to paint to prevent entry of moisture. All roof seams shall be continuously welded.

A 2" formed radius shall be provided along the body sides. The use of extruded radius will not be acceptable, No Exceptions.

#### **BODY SUBFRAME**

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 4" x 1/4" aluminum tubes minimum, the same width as the chassis frame rails. Welded to this tubing shall be cross members of 2" x 4" x 1/4" aluminum. Smaller dimension, lighter gauge tubing or angle material subframe shall not be accepted.

These cross members shall extend the full width of the body to support the compartments. Cross members shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum cross members shall be located on 16" centers, or as necessary to support walkway or heavy equipment.

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.

#### **BODY MOUNTING**

For optimum chassis frame and body life, the body subframe shall be fastened to the chassis frame with a minimum of six (6) 1/2" x 2" strap mounts, welded to the body subframe. The straps shall be bolted to the chassis frame work utilizing 1/2" Grade 8 bolts.

#### **10" REAR STEP BUMPER**

The full width rear bumper shall be constructed from 2" x 2" x 1/4" aluminum tubing frame and covered with 3/16" NFPA compliant aluminum tread plate. The bumper shall extend from the rear vertical body panel 10" and provide a rear step with a minimum of 1/2" space at body for water drainage.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **REAR TOW EYES**

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below the apparatus body. The tow eyes shall be fabricated from 3/4" thick steel plate and shall have a black powder coat finish.

#### **TRAILER HITCH**

A Class III, 7,500 lbs. weight carrying capacity (gross trailer weight) rear hitch receiver shall be provided below the rear bumper. The receiver shall be attached to the apparatus body frame.

The hitch shall be complete with a 2" square receiver. Without the use of a "weight distribution" ball hitch the Class III receiver shall have a capacity of 5,000 lbs. gross trailer weight and a maximum tongue weight of 500 lbs.

A label shall be provided in a location in which it is visible to an operator making trailer connections. The label shall state the maximum GVWR and tongue weight of the trailer that can be safely towed with the hitch system.

Two (2) safety chain attachment points shall be provided near the hitch point for hitches designed to use safety chains, each designed with an ultimate strength of not less than the maximum GVWR specified on label.

#### **TRAILER ELECTRICAL RECEPTACLE**

For hydraulic brake equipped or electric brake equipped trailer towing capability, a primary electrical receptacle shall be provided near the hitch point and shall match the umbilical cable specified. Receptacle shall be a 7-Way Blade Type socket, the same as used on most Light Duty Trucks and RV's.

#### **TRAILER AUXILIARY ELECTRICAL RECEPTACLE**

An auxiliary electrical receptacle shall be provided near the hitch point and shall match the umbilical cable specified for optical warning lights. Receptacle shall be a 7-Way Pin Type Socket, ISO3731 compliant with a reverse ground terminal.

#### **GROUND LIGHTS**

Two (2) OnScene Solutions 9" LED Nightstik ground lights shall be mounted below the bumper.

There shall be two (2) OnScene Solutions 9" LED NightStik light(s) installed below bumper capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting shall be switchable but activated automatically when headlights are activated and vehicle park brake is set.

#### **WHEEL WELL EXTERIOR PANEL**

The exterior panel of the body wheel well enclosure shall be constructed from 1/8" aluminum smooth plate.

#### **DIEFORMED BEADED EDGE BODY FENDERS**

A die formed beaded edge shall be provided along the radius of the wheel well opening for a finished appearance.

#### **WHEEL WELL LINERS**

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will not accumulate dirt or water.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **SCBA CYLINDER COMPARTMENTS**

Two (2) SCBA cylinder storage compartments shall be provided, one (1) each side of the body in rear wheel well area. Each compartment shall have a brushed SST door assembly with a positive catch latch. Each compartment shall have a 8" diameter tube behind the wheel well panel attached to the door assembly. Each compartment shall allow the storage of an SCBA cylinder up to 7-3/4" in diameter. The door shall activate the "Hazard Warning Light" in the cab when not in the closed position.

#### **BODY PAINT SPECIFICATIONS**

##### **BODY PAINT PREPARATION**

After the body and components have been fabricated they shall be disassembled prior to painting so when the vehicle is complete there shall be finish paint beneath the removable components. The body shall be totally removed from chassis during the paint process to insure the entire unit is covered. The body and components shall be metal finished as follows to provide a superior substrate for painting.

The exterior body shall undergo a thorough cleaning process starting with a biodegradable phosphoric acid solution to begin the etching process followed by a complete clear water rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the metal surface for greater film adhesion. If the compartment interior is to be painted the interior shall be acid etched as described above then primed with an epoxy primer and all seams caulked.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

##### **PAINT PROCESS**

The paint process shall follow the strict standards set forth by PPG Industries guidelines. Painters applying PPG products will be PPG Certified Commercial Technicians, and re-certified every two (2) years.

The body shall go through an eight-stage paint process;

1. Clean bare metal using a solvent base wax & grease remover.
2. Finish all exterior body seams as necessary, followed by a thorough sanding of all bare metal to be painted.
3. Re-clean bare metal using a solvent base wax & grease remover.
4. Bare Metal Epoxy Primer Coat - PPG Delfleet® Evolution corrosion resistance epoxy primer to be applied at 1.0-2.0 mills DFT over clean abraded bare metal.
5. Primer Filler Coat - PPG Delfleet® Evolution urethane build primer to achieve total thickness of 3.0-6.0 mills DFT after sanding.
6. Base coat (Color) - PPG Delfleet® Evolution High Solids Polyurethane Base coat. Apply 1.0-3.0 mills DFT of base coat color to achieve full hiding.
7. Clear coat PPG Delfleet® Evolution polyurethane premium quality clear coat with improved mar resistant finish. The clear coat shall be applied to achieve a total dry film thickness of 2.0-3.0 mills.
8. Curing process of the painted body shall go through a force dry/bake cycle process. The painted components shall be baked 180 degrees for 2 hours to achieve a complete coating cure on the finished product.

##### **MACHINE POLISHED**

After the force dry/bake cycle and ample cool down time, the coated surface shall be sanded using 1,000, 1,500, and or 3,000 grit sandpaper to remove surface defects. In the final step, the surface shall be buffed then polished to an extra high gloss smooth finish. Total dry film thickness of paint will average between 8.0-12.0 mils.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **PAINT - ENVIRONMENTAL IMPACT**

The contractor shall meet or exceed all current State (his) regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. PPG Delfleet® Evolution paint shall be free of all heavy metal (lead & chromate) components. Paint emissions from sanding and painting shall be filtered and collected. All paint wastes shall be disposed of in an environmentally safe manner. Solvents used in cleanup operations shall be collected, sent off-site for distillation and returned for reuse.

#### **PAINT FINISH - SINGLE COLOR**

The body shall be painted with a single color of PPG Delfleet® Evolution paint per approved customer sprayout.

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, an isolation tape, or gasket shall be used to prevent damage to the finish painted surfaces. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nutserts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

Touch-up paint shall be provided with completed vehicle.

1. Paint Color: Red
2. Paint Number: PPG FBCH-75280 to match DuPont N3240 Imron Elite RED

#### **BODY UNDERCOATING**

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

#### **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

#### **PAINT WARRANTY**

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle.

#### **COMPARTMENT INTERIOR FINISH**

The compartment interiors shall be treated with phosphoric acid and then sprayed with an epoxy primer applied 1.0 mil thick. All body seams will be caulked with urethane seam sealer and painted with two (2) coats of textured Zolatone paint. Zolatone catalysts will be added to the Zolatone to help in resisting moisture and provide a more durable finish. Paint color shall be gray.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **REFLECTIVE STRIPE REQUIREMENTS**

##### Material

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retroreflection of 10 with observation angle of 0.2 degrees and entrance angle of -4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

##### Minimum Requirements

A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 4 in. (100 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

#### **GRAPHICS PROOF**

A color graphics proof of the reflective striping layout shall be provided for approval by Fredericton Fire Department prior to installation. The graphics proof shall be submitted to Fredericton Fire Department on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

#### **REFLECTIVE STRIPE - CAB SIDE**

The reflective stripe material shall be 4" wide, 3M Scotchcal 680 series.

1) This reflective stripe shall be gold in color.

#### **REFLECTIVE STRIPE - CAB FRONT**

The reflective stripe material shall be 4" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be gold in color.
- The word FIRE will be printed in the center of the stripe.

#### **REFLECTIVE STRIPE - CAB DOOR INTERIOR**

Any door of the apparatus designed to allow persons to enter or exit the apparatus shall have at least 96 in.2 (62,000 mm2) of retroreflective material affixed to the inside of the door.

The stripe material shall be 3M Scotchlite 680.

- This reflective stripe shall be white in color.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **REFLECTIVE STRIPE - BODY SIDES**

The reflective stripe material shall be 4" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be gold in color.

The stripe shall extend straight back from the chassis and then, ahead of the rear wheels, it shall form an "S" and then extend straight back to the rear of the body. The "S" portion of the stripe shall be shaded in the corners.

#### **CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS**

At least 50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width.

The rear side panels only of the body shall have a Chevron style reflective stripe layout, and cover as much of the rear side panels as possible. Chevron panels shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panels shall have a minimum 10 year warranty for material failure, and colorfastness.

The stripe material shall be 3M Diamond Grade.

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

#### **LETTERING**

No lettering shall be provided on the completed unit.

#### **EXTERIOR COMPARTMENT DOORS**

##### **ROLL-UP DOOR CONSTRUCTION - AMDOR**

The apparatus shall be equipped with Amdor brand exterior roll-up compartment doors. Amdor roll-up doors shall be complete with the following features;

- 1" aluminum double wall slats with continuous ball & socket hinge joint and recessed dual durometer slat seal
- Double wall reinforced bottom panel with stainless steel lift bar latching system
- Bottom panel flange with cut-outs for ease of access with gloved hands
- Reusable slat shoes with positive snap-in securement
- Smooth interior door curtain to prevent equipment hang-ups
- One-piece aluminum door track / side frame, top gutter with non-marring seal
- Non-marring recessed side seals with UV stabilizers to prevent warping
- Dual leg bottom seal, with all wear component material to be Type 6 Nylon

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.



# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **BODY HEIGHT MEASUREMENTS**

The vertical body dimensions shall be as follows:

##### AHEAD OF REAR AXLE

	<u>Description</u>	<u>Dimension</u>
A	Bottom of Subframe to Top of Body	59.0"
B	Bottom of Subframe to Bottom of Body	18.0"
C	Vertical Door Opening	
	-with roll-up door	55.5"
	-with hinged door	59.5"

##### ABOVE REAR AXLE

	<u>Description</u>	<u>Dimension</u>
D	Vertical Door Opening - Above Rear Wheel	
	-with roll-up door	32.0"
	-with hinged door	35.0"

##### BEHIND REAR AXLE

	<u>Description</u>	<u>Dimension</u>
E	Bottom of Subframe to Bottom of Body	15.0"
F	Vertical Door Opening	
	-with roll-up door	53.0"
	-with hinged door	57.0"

##### GENERAL

	<u>Description</u>	<u>Dimension</u>
G	Bottom or Drip Rail to Top of Body	13.5"

(Dimensions are generic and subject to change during the actual design process)

#### **BODY WIDTH DIMENSIONS**

The body shall be 96.0" wide, not including drip rail or non-permanent fixtures. Interior compartment depth dimensions shall be approximately:

<u>Area Description</u>	<u>Dimension</u>
Transverse Area above Subframe	91.0"
Compartment Depth below Subframe	21.0"

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **STREETSIDE COMPARTMENT - FRONT (S1)**

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.


#### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-trac for specified component installation.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 92" deep and as wide as the compartment layout or door opening permits, capable of extending out either side of the body located above the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed, 40% extended and 70% extended positions. Each tray top shall be fabricated from 3/16" 3003 aluminum sheet shall have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2". The transverse tray will be mounted on the top of the specified transverse module.
- There shall be one (1) transverse module fabricated from 3/16" (.188) 3003H-14 aluminum alloy smooth sheet. The storage module will be mounted on the upper floor area of the compartment. The module will be designed for the following long tools and equipment:
  - One (1) Fredericton Fire Department supplied stokes basket(s). The stokes basket(s) shall measure approximately 84.0"L x 24.0"W x 7.5"H.
  - Two (2) Fredericton Fire Department supplied backboard(s). The backboard(s) shall measure approximately 72.0"L x 16.0"W x 2.0"H.
  - There shall be two (2) OnScene Solutions cargo straps provided to secure the stored equipment.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.


# Fredericton Fire Department

## Light Rescue

### Production Specification

 One (1) Hannay ECR1616-17-18 electric cable reel(s) capable of storing 150' of 10/3 electric cable. Reel(s) shall be designed to hold 110% of the capacity of cord length, with fully enclosed 45 amp, three (3) conductor collector rings. Reel(s) shall be mounted to channel structure that allows for side-to-side adjustment of reel position.

- Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and not be more than 72 in. (1830 mm) above the operator's standing position, and shall be marked with a label indicating its function.
- A label shall be provided in a visible location adjacent to reel with following information: Current rating, Current type, Phase, Voltage, and Total cord length.
- The cable reel shall equipped with 150' of 10/3 SEOW black cable, a molded plastic ball clamp, and a single heavy duty L5-30 twist-lock female plug at the end.
- One (1) Akron model EJB, cast aluminum electrical power distribution box with yellow powder coat painted finish shall be provided. The power distribution box shall meet all requirements described in NFPA 1901. The power distribution box shall include:
  - A 12" pigtail that terminates in an L5-30 configuration to match the cable on the cord reel. The outlet configuration shall include:
    - One (1) 5-20 duplex straight-blade receptacle
    - One (1) 5-20 duplex straight-blade receptacle
    - One (1) L5-20 single twist lock receptacle
    - One (1) L5-20 single twist lock receptacle
  - One (1) Akron EJB treadplate vertical apparatus mounting bracket shall be provided.
  - The fairlead roller shall be mounted directly to the reel.
  - One (1) OnScene Solutions 63" LED Nightstik compartment light, vertically mounted.
  - The controls for the specified light tower(s).

 There shall be one (1) 120 volt outlet(s) located in this compartment on the forward wall unless noted otherwise.

- The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
- Outlet(s) shall be powered through the on-board generator system.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.
- The 12 volt electrical distribution panel shall be located in the streetside front lower compartment.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2)**

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

#### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-trac for specified component installation.



There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".



There shall be one (1) 250 lbs. slide out and down tray(s) with an OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will hold the tray in the closed position. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".

- The DEF fill shall be located on the forward wall of the compartment.
- One (1) OnScene Solutions 36" LED Nightstik compartment light, vertically mounted.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **STREETSIDE COMPARTMENT - REAR (S3)**

The interior useable compartment width shall be approximately 35.0" wide.

The compartment door opening shall be approximately 28.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

#### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-trac for specified component installation.
- There shall be two (2) slide-out smooth aluminum vertical tool board(s) approximately 20" deep. Each tool boards shall be fabricated of 3/16" (.188) aluminum 3003H-14 alloy smooth plate with double 90 degree formed edge to provide an easy grip handle. The top and bottom of tool board shall be provided with Accuride 9300 series slide tracks. Each board shall be rated for a maximum 200 lbs. evenly distributed load. Each tool board shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.
  - Each tool board shall be horizontally adjustable; mounted on aluminum shelf trac on compartment floor.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- One (1) OnScene Solutions 63" LED Nightstik compartment light, vertically mounted.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.
  - Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **CURBSIDE COMPARTMENT - FRONT (C1)**

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

#### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-trac for specified component installation.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 94" deep; capable of extending out either side of the body located above the level of the chassis frame rails. (Specified in opposite side compartment.)
- There shall be one (1) transverse module(s) which extends to the opposite side of the body. (Specified in opposite side compartment.)
  - There shall be two (2) OnScene Solutions cargo straps provided to secure the stored equipment.
- There shall be one (1) air bag storage module(s). The module shall be fabricated from 1/8" (.125) 3003H-14 aluminum alloy sheet. Circular notches shall be provided along the front edge to ease the access to the air bags. Each bay shall be sized to hold the air bag and a matching piece of plywood. The module shall be designed to store the following air bags:
  - One (1) 29.25" x 28.00" x 0.50"
  - One (1) 21.25" x 27.00" x 0.50"
  - One (1) 15.00" x 16.00" x 0.50"
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
  - One (1) OnScene Solutions 63" LED Nightstik compartment light, vertically mounted.
  - One (1) 120/240 VAC load center.

# Fredericton Fire Department

## Light Rescue

### Production Specification

- There shall be one (1) 120 volt outlet(s) located in this compartment on the forward wall unless noted otherwise.
- The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
- Outlet(s) shall be powered through the on-board generator system.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C2)**

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
  - There shall be NO keyed lock on this roll-up compartment door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

#### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-trac for specified component installation.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".
- There shall be one (1) 250 lbs. slide out and down tray(s) with an OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will hold the tray in the closed position. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".
- One (1) OnScene Solutions 36" LED Nightstik compartment light, vertically mounted.



# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **CURBSIDE COMPARTMENT - REAR (C3)**

The interior useable compartment width shall be approximately 35.0" wide.

The compartment door opening shall be approximately 28.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

#### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-trac for specified component installation.
- There shall be one (1) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- One (1) OnScene Solutions 63" LED Nightstik compartment light, vertically mounted.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **REAR COMPARTMENT - CENTER (RC1)**

The rear center compartment shall be closed to both side rear compartments.

The rear center compartment shall start at the top of the frame and be as high as the body permits.

The interior useable compartment width shall be approximately 41.0" wide.

The compartment door opening shall be approximately 34.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

#### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-trac for specified component installation.
- There shall be one (1) adjustable shelf/shelves approximately 34" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 31" deep (or as deep as possible) and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".



Two (2) Fredericton Fire Department supplied hydraulic hose reel(s) with electric rewind shall be installed. The rewind button for each reel shall be located adjacent to the reel it controls.

- The hydraulic reel shall be equipped with Fredericton Fire Department supplied hydraulic hose. Contractor shall provide plastic hose stop on hose end.
- Two (2) OnScene Solutions 63" LED Nightstik compartment lights, vertically mounted.
- One (1) Fredericton Fire Department supplied Genesis Mach III gas powered hydraulic power unit(s).

# Fredericton Fire Department

## Light Rescue

### Production Specification



Mounts will be supplied and installed for one (1) Fredericton Fire Department supplied Genesis 22-45 hydraulic ram(s).

- Mounts will be supplied and installed for one (1) Fredericton Fire Department supplied Genesis C236 hydraulic cutter(s).
- Mounts will be supplied and installed for one (1) Fredericton Fire Department supplied Genesis S49-XL hydraulic spreader(s).

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **PLASTIC FLOOR AND SHELF TILE**

All compartment floors, shelves, and trays shall be covered with Dri-Dek plastic interlocking grating.

- The plastic floor tile shall be red.
- The plastic edge trim shall be red.

#### **FRONT GRAVEL GUARDS**

Gravel guards shall be fabricated of tread plate aluminum to match the specified cab running boards. The gravel guards shall be installed on the front body corners and shall extend half way up the body and wrap around the corners to the front compartment door hinge on each side.

#### **LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC**

##### General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

##### Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125 % of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10 %. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

##### Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

# Fredericton Fire Department

## Light Rescue

### Production Specification

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage overcurrent protective devices. Such devices shall be readily accessible and protected against heat in excess of the overcurrent device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- SAE J156, *Fusible Links*
- SAE J553, *Circuit Breakers*
- SAE J554, *Electric Fuses (Cartridge Type)*
- SAE J1888, *High Current Time Lag Electric Fuses*
- SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125 % of maximum current for which the circuit is protected.

#### Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

#### Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- 1) The propulsion engine and transmission
- 2) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- 3) The radio(s) at a duty cycle of 10 percent transmit and 90 % receive (for calculation and testing purposes, a default value of 5 A continuous)
- 4) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
  - 1) The minimum optical warning system, where the apparatus is blocking the right-of way
  - 2) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
  - 3) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

# Fredericton Fire Department

## Light Rescue

### Production Specification

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

#### Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

#### Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

#### Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **12 VOLT MULTIPLEX CONTROL CENTER**

The apparatus shall be equipped with a Weldon V-MUX multiplexed 12 volt electrical system that will provide complete diagnostic capability, No Exception. The system shall have the capability of delivering multiple signals via a CAN bus, utilizing specifications set forth by SAE J1939. The system shall be node based to maximize stability so that failure of one node does not affect the operation of the other nodes. The system shall use shielded twisted-pair wire for transmission of system function signals. The shielded wire shall provide protection against EMI and RFI noise interruptions.

The multiplex system shall be responsible for providing power management functions as well as load shedding. The warning light system shall be controlled by the multiplex system. The system shall be capable of displaying text and/or graphic messages on a display module. The system shall be based on solid-state technology and shall include self-contained diagnostic indicators.

#### **Outputs:**

The outputs shall perform all the following items without added modules to perform any of the tasks;

1. **Load Shedding:** The system shall have the capability to load shed with 8 levels any output. This means you can specify which outputs (barring NFPA restrictions) you would like load shed. Level 1 12.9v, Level 2 12.5V, Level 3 - 12.1V, Level 4 - 11.7V, Level 5 11.3V, Level 6 10.9V, Level 7 10.5, Level 8 10.1. Unlike conventional load shedding devices you can assign a level to any or all outputs.
2. **Load Sequencing:** The system shall be able to sequence from 0 8 levels any output. With 0 being no delay and 1 being a 1 second delay, 2 being a 2 second delay and so on. Sequencing reduces the amount of voltage spikes and drops on your vehicle, and can help limit damage to your charging system.
3. **Output Device:** The system shall have solid-state output devices. Each solid-state output shall be a MOS-FET (Metal Oxide Semiconductor - Field Effect Transistors); MOS-FETs are solid-state devices with no moving parts to wear out. A typical relay when loaded to spec has a life of 100,000 cycles. The life of a FET is more than *100 times* that of a relay.
4. **Flashing Outputs:** The system shall be able to flash any output in either A or B phase, and logic is used to shut down needed outputs in park, or any one of several combined interlocks. The flash rate can be selected at either 80, 160 or 200 FPM. This means any light can be specified with a multiplex truck with no need to add flashers. Flashing outputs can also be used to warn of problems or other unique idea you may come up with.
5. **PWM:** The modules shall have the ability to PWM at some outputs so that a headlight PWM module is not needed.
6. **Diagnostics:** An output should be able to detect either a short or open circuit. The system should be able report in "real time" a text based message that points the maintenance person to a specific output.

#### **Inputs:**

1. The inputs shall have the ability to switch by a ground or vbatt signal.
2. The inputs shall be filtered for noise suppression via hardware and software so that RF or dirty power will not trick an input into changing its status.

#### **Auto-Throttle:**

The multiplex system shall be able to perform automatic high idle via a network gateway or by using an existing output on a module to provide the proper signals to an OEM Engine ECU. This task should be handled with existing inputs and outputs.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **Displays:**

Displays shall be able to provide real time information regarding load shedding and system status, such as network traffic/errors or shorts and open circuits.

#### **System Network:**

The multiplex system shall contain a Peer-to-Peer network. A Master Slave Type network is not suitable for this type of unit. A Peer-to-Peer network means that all the modules are equal on the network; a Master is not needed to tell other nodes when to talk, **No Exceptions.**

#### **System Reliability:**

The multiplex system shall be able to perform in extreme temperature conditions, from 40° to +85° C (-40° to +185° F.) The system shall be sealed against the environment, moisture, humidity, salt or fluids such as diesel fuel, motor oil or brake fluid. The enclosures shall be rugged to withstand being mounted in various locations or compartments around the vehicle. The modules shall be protected from over voltage and reverse polarity.

#### **WELDON CERTIFICATION**

A letter shall be provided with bid submittal that the Contractor has successfully completed the Weldon training requirements for Level 1 of the V-MUX Certified Supplier Program and is authorized to design, build, and service V-MUX electrical systems.

#### **ROCKER SWITCH PANEL**

The control of the 12 volt equipment installed on chassis and body shall be centrally located in the cab. The individual rocker style switches shall be located on a separate electrical panel, complete with backlit name tags describing function of each individual switch. The back lighting shall have two (2) levels of intensity, low level lights activated when the vehicle lights or ignition switch is turned "On", and high level lights activated when individual switch is turned "On". An internally lighted rocker switch shall be furnished to the left of specified emergency lighting switches, and identified as "MASTER EMERGENCY SWITCH".

Switch circuitry shall be on a printed circuit board. The lights shall be solid state type and have a 100,000 hour life span.

The rocker switch panel shall be located in the cab center console for all master switches and emergency light switches.

#### **CAB CONSOLE**

A center cab console shall be provided between the Driver's and Officer's seats. Console shall be as large as possible and fabricated of 1/8" smooth aluminum. A textured powder coat paint finish shall be provided for durability and finished appearance.

The rear portion of the console shall be provided with open top storage for notebooks or maps. Two (2) adjustable dividers shall be provided in the storage area. The forward portion of console shall be slanted for mounting of siren head, radio or 12 volt control panel, and etc, with easy access to both Driver and Officer.

The final design of console shall be determined by the Fredericton Fire Department at the pre-construction meeting.



# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **BATTERY SYSTEM**

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

A master load disconnect switch shall be provided between the starter solenoid(s) and the remainder of the electrical loads on the apparatus. The starter solenoids shall be connected directly to the batteries.

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

A green "battery on" pilot light that is visible from the driver's position shall be provided.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within 5 seconds.

#### **BATTERY SWITCH**

The chassis ignition key shall activate a heavy duty relay to provide 12 volt battery power to the vehicle. There shall be a green "BATTERY ON" pilot light that is visible from the driver's position.

#### **BATTERY SOLENOID**

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

#### **BATTERY CONDITIONER**

One (1) Kussmaul model Auto Charge 1000 single battery conditioner, with 120 VAC input and 15 amp, 12 volt output shall be provided. This system shall monitor the condition of batteries and provide an electrical current at variable rates to overcome battery failure. A display shall be provided with charge indicator, remote mounted. The conditioner shall be located in the body, on the upper S1/C1 compartment wall.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **SHORE POWER INLET**

One (1) Kussmaul 120 VAC, 20 amp Super Auto-Eject shore power inlet(s) shall be provided. The shore power connection shall automatically disengage from vehicle when chassis ignition is engaged.

The protective ground from the shoreline inlet shall be bonded to the vehicle frame.

1. The outlet cover shall be yellow.
2. The shore power inlet shall be located on the streetside front of body, outboard of the cab.

#### **ENGINE COMPARTMENT LIGHT**

There shall be one (1) light(s) mounted in the engine compartment with integral switch with a light output of at least 20 candlepower (250 lumens). The engine compartment light(s) shall operate only when the master battery switch is turned "On".

#### **MAP LIGHT**

There shall be one (1) 24" goose neck 12 volt map light(s) provided and installed on the front curbside corner of the cab console.

#### **CAB SPOTLIGHT**

There shall be one (1) Golight Radoray 2020 motorized spotlight(s) that operates via a wired dash mount controller with joystick and on/off button. The joystick controls the motorized 135 degree tilt of the spotlight and the motorized rotation of the light a full 370 degrees. The light continues to move while the joystick is pressed. Once any button is released, the spotlight remains locked in that position until the joystick is moved again. The dash controller also turns the light on and off, so no additional switches are required. The dash mounted remote control allows for fingertip operation and is hard wired to the searchlight.

The Radoray is mounted to the surface of vehicle via 4 screws and a rubber gasket for a quick, safe and secure attachment.

The Cr5 Pentabeam II technology combines a five-sided parabolic reflector with an axial filament Phillips H-9 bulb. This 5,000,000 Adjusted Retail Candle Power (400,000 Industrial Candlepower) configuration generates an extremely bright beam to penetrate dark spots, cast a broad spectral pattern and reach distances of 700 feet.

The light shall be located centered on the specified lightbar.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **CAB HAZARD WARNING LIGHT**

A red flashing or rotating light, located in the driving compartment, shall be illuminated automatically whenever the vehicles parking brake is not fully engaged and any of the following conditions exist:

- Any passenger or equipment compartment door is not closed.
- Any ladder or equipment rack is not in the stowed position.
- Stabilizer system is not in its stowed position.
- Powered light tower is not stowed.
- Any other device permanently attached to the apparatus is open, extended, or deployed in a manner that is likely to cause damage to the apparatus if the apparatus is moved.

Compartments and equipment meeting all of the following conditions shall be permitted to be exempt from being wired to the hazard light:

- The volume is less than or equal to 4 ft<sup>3</sup> (0.1 m<sup>3</sup>).
- The compartment has an opening less than or equal to 144 in.<sup>2</sup> (92,900 mm<sup>2</sup>).
- The open door does not extend sideways beyond the mirrors or up above the top of the fire apparatus.
- All equipment in the compartment is restrained so that nothing can fall out if the door is open while the apparatus is moving.
- Manually raised pole lights with an extension of less than 5 ft (1.5 m).

The hazard light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

An audible alarm shall be provided for the door ajar light.

#### **BACK-UP ALARM**

The body manufacturer shall furnish and install one (1) 107 dB(A) electronic back-up alarm. Back-up alarm to actuate automatically when the transmission gear selector is placed in reverse.

#### **TAIL LIGHTS**

Rear body tail lights shall be vertically mounted per Federal Motor Vehicle Safety Standards. The following lights shall be furnished:

- Two (2) Whelen amber LED 600 Series 60A00TAR turn signal lights
- Two (2) Whelen red LED 600 Series 60R00XRR stop/tail lights
- Two (2) Whelen LED 600 Series 60C00WCR maximum intensity back-up lights with clear lens

Each of the lights above shall be mounted in a 6EFLANGE, chrome finish bezel.

#### **MIDSHIP MARKER/TURN SIGNAL**

Two (2) Whelen LED midship body clearance marker/turn signal lights (T0A00MAR) shall be installed. There shall be one (1) light on each side of the body, in the wheel well, ahead of the rear axle. Both lights shall have an amber lens and operate with the chassis clearance marker and turn signals.

#### **MARKER LIGHTS**

The apparatus body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) regulations. All body clearance lights shall be Truck-Lite Model 18 LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **CAB STEP LIGHTS / GROUND LIGHTS**

There shall be two (2) OnScene Solutions 9" LED NightStik light(s) installed on the vehicle capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting designed to provide illumination on areas under the driver and crew riding area exits shall be switchable but activated automatically when the exit doors are opened.

#### **LICENSE PLATE LIGHT**

One (1) Arrow #437 chrome plated LED license plate light shall be installed on the rear of the body. License plate light shall be wired to the headlight circuit of chassis. A fastener system shall be provided for license plate installation.

#### **ELECTRONIC SIREN**

One (1) Federal EQ2B 200 watt, electronic siren/amplifier with digital output control head shall be provided. The siren control head shall be mounted within reach of the Driver.

There shall be a siren brake installed in the rocker switch control panel to activate the siren brake.

#### **SIREN ACTIVATION**

There shall be two (2) foot switches to activate the siren, one (1) for the officer and one (1) for the driver. The switches shall be mounted on the floor in a location to prevent accidental activation.

#### **SIREN SPEAKER**

One (1) Federal BP200-EF, 200 watt siren speaker shall be provided and recess mounted behind the front bumper.

- The siren speaker shall be located on the streetside of front bumper.

#### **SIDE SCENE LIGHTS**

There shall be four (4) Whelen 810 series (10" x 8") surface mounted Opti-Scene halogen lights (810CA0ZR) provided on the upper body. Light quantity shall be divided equally per side. Each light will have an 8-32 degree lens and chrome flange.

Two (2) switches shall be provided, one (1) for the streetside scene lights, and one (1) for the curbside scene lights.

The lights shall be switched at the 12 volt control panel in the cab.

#### **REAR SCENE LIGHTS**

Two (2) Whelen 900 series (9" x 7") recess mounted Opti-Scene halogen lights (90E000ZR) shall be provided on the upper rear body to light the work area immediately behind the vehicle to a level of at least 3 fc (30 lx) within a 10 ft x 10 ft (3 m x 3 m) square. Each light will have a 8-32 degree gradient lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **TRAFFIC DIRECTIONAL LIGHT**

One (1) Whelen TAL85, 47" eight (8) LED light, traffic directional warning device with 30' control cable shall be located on upper rear body. The control head shall be located in the cab within easy reach of Driver.

The traffic directional light shall be surface mounted on upper rear body.

#### **WARNING LIGHT PACKAGE**

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two separate signaling modes during emergency operations. One mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### UPPER LEVEL OPTICAL WARNING DEVICES

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

#### ZONE A - FRONT WARNING LIGHTS

There shall be one (1) Whelen Edge FN60QLED LED 60" lightbar permanently mounted to the cab roof.

The lightbar configuration (streetside to curbside) shall be:

<u>SECTION</u>	<u>INTERNAL COMPONENTS</u>	<u>LENS COLOR</u>
1	One (1) Red Linear LED - Side Facing	Clear
2	One (1) Red Corner LED	Clear
3	Clear Linear LED	Clear
4	Blank	Clear
5	Red Linear LED	Clear
6	Blank	Clear
7	Blank	Clear
8	Red Linear LED	Clear
9	Blank	Clear
10	Clear Linear LED	Clear
11	One (1) Red Corner LED	Clear
12	One (1) Red Linear LED - Side Facing	Clear

All clear lights shall shut down when the parking brake is set to comply with "Blocking" mode requirements as outlined in NFPA 1901.

The lightbar shall be separately switched at the 12 volt control panel in the cab.

The lightbar shall be supplied with LR11 halogen alley lights on each end and wired to come on with park brake switch.

#### GTT OPTICOM

One (1) GTT Opticom emitter light shall be provided inside specified light bar. The Opticom shall be activated with light bar and de-activated when the park brake is set and the vehicle is in blocking mode.

#### ZONES B AND D - SIDE WARNING LIGHTS

#### UPPER REAR CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### ZONE C - REAR WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

#### LOWER LEVEL OPTICAL WARNING DEVICES

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1220 mm) above level ground for small apparatus.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

#### ZONE A - FRONT WARNING LIGHTS

There shall be two (2) Whelen 700 series (7" x 3") red Linear Super-LED lights (70R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

#### ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

There shall be two (2) Whelen 700 series (7" x 3") red Linear Super-LED lights (70R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

#### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY WHEELWELL AREA)

There shall be two (2) Whelen 700 series (7" x 3") red Linear Super-LED lights (70R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

#### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Whelen 700 series (7" x 3") red Linear Super-LED lights (70R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

#### LINE VOLTAGE ELECTRICAL SYSTEM

##### UNDERHOOD GENERATOR SYSTEM - (120 VAC)

The vehicle shall be equipped with a Mobile Electric Power Solutions (MEPS), 7,500 watt (continuous), 120 volt single phase, 50 amp, 60 Hertz under hood electrical generator.

The generator shall be belt driven from the front of the engine and shall be capable of operating from engine idle to maximum engine RPM without affecting generator operation. It shall be mounted under the hood in the engine compartment with vehicle and engine specific mounting brackets.

The Alternator Control Unit (ACU) shall be mounted in a weather proof location, preferably in unusable space of body compartment. The generator control switch shall be mounted in the cab area near the Driver's seat for turning the generator system on and off. The generator system, when engaged, shall operate normally whether the vehicle is stationary or being driven (reduced load capacity). The generator system shall NOT produce any noise greater than the engine produces during normal operation. The unit shall produce AC current that is plus or minus 0.1 Hertz total frequency deviation, and has less than 3% total harmonic distortion.

The generator system shall NOT require any scheduled maintenance. Portable gasoline, or diesel generators, or hydraulic driven generators will NOT be an acceptable alternative to the MEPS generator system. NO Exceptions.

A voltmeter shall be provided at an operator's panel for any system of this type.

The belt drive system shall be rated to drive the generator or alternator at the nameplate rating.

Mounting Bracket: Mobile Electric Power, Ford

#### MANUALS AND SCHEMATICS

Two (2) complete manuals on parts list, maintenance, wiring schematics, hydraulic schematics, circuit boards, voltage regulator board and other components shall be provided on delivery.

#### ENGINE SPEED CONTROL

The apparatus shall be equipped with an InPower ETM, Electronic Throttle Module to maintain a stable cycle output from generator.

An interlock shall prevent the operation of the engine speed auxiliary control device unless the parking brake is engaged and the transmission is in neutral or park, or the parking brake is engaged and the engine is disengaged from the drive wheels.

The engine shall be prevented from regulating its own engine speed during times when engine rpm control is critical for consistent apparatus functions such as generator, water pump, or aerial operation.



# Fredericton Fire Department

## Light Rescue

### Production Specification

#### **LOADCENTER**

The loadcenter shall be a Cutler Hammer, BR Series, specifically designed for protection and distribution of 120/240 volt AC, such as lighting and small motor branch circuits. The loadcenter enclosure shall be made of 16 gauge galvanized sheet steel. The galvanized coating provides corrosion protection and as such does not require paint. All trims used on the BR Loadcenter shall be chromate sealed and finished with electro disposition epoxy paint (ASA61) which exceeds requirements for outdoor and indoor applications. A combination surface/flush cover with integral door shall be supplied.

The loadcenter shall be UL/CSA listed, **NO EXCEPTIONS** will be allowed.

#### **GENERATOR MONITORING PANEL**

To properly monitor the generator performance and load demand during operation, the generator installation shall be equipped with a full instrument monitor panel.

- Generator frequency in hertz
- Line 1 current in amperes
- Line 2 current in amperes
- Generator voltage in volts

The program shall support the accumulation of elapsed generator hours. Generator hours shall be displayed.

#### **OUTLETS AND CIRCUITS**

The generator and or shore power shall supply the 120/240 volt electrical equipment and outlets outlined below. Proper circuit protection shall be installed as noted:

Two (2) 120 volt exterior outlets, one (1) each side near rear wheel well area.

- The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).

#### **LINE VOLTAGE ELECTRICAL SYSTEM**

##### **GENERAL REQUIREMENTS**

##### Stability

Any fixed line voltage power source producing alternating current (ac) shall produce electric power at 60 Hz,  $\pm 3$  Hz when producing power at all levels between no load and full rated power. Any fixed line voltage power source shall produce electric power at the rated voltage  $\pm 10$  percent when producing power at all levels between no load and full rated power.

The maximum voltage supplied to portable equipment shall not exceed 275 volts to ground. Higher voltage shall be permitted only when used to operate fixed wired, permanently mounted equipment on the apparatus.

##### Conformance with National Electrical Code

All components, equipment, and installation procedures shall conform to *NFPA 70, National Electrical Code*, except where superseded by the requirements of this chapter. Where the requirements of this chapter differ from those in *NFPA 70*, the requirements in this chapter shall apply.

Where available, line voltage electrical system equipment and materials included on the apparatus shall be listed and used only in the manner for which they have been listed. All equipment and materials shall be installed in accordance with the manufacturer's instructions.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### Location Ratings

Any equipment used in a dry location shall be listed for dry locations. Any equipment used in a wet location shall be listed for wet locations.

Any equipment, except a PTO-driven generator, used in an underbody or under chassis location that is subject to road spray shall be either listed as Type 4 or mounted in an enclosure that is listed as Type 4.

If a PTO-driven generator is located in an underbody or under chassis location, the installation shall include a shield to prevent road spray from splashing directly on the generator.

#### Grounding

Grounding shall be in accordance with 250.34(A) and 250.34(B) of *NFPA 70*. Ungrounded systems shall not be used.

Only stranded or braided copper conductors shall be used for grounding and bonding.

The grounded current-carrying conductor (neutral) shall be insulated from the equipment-grounding conductors and from the equipment enclosures and other grounded parts.

The neutral conductor shall be colored white or gray in accordance with 200.6, "Means of Identifying Grounded Conductors," of *NFPA 70*.

Any bonding screws, straps, or buses in the distribution panel board or in other system components between the neutral and equipment-grounding conductor shall be removed and discarded.

#### Bonding

The neutral conductor of the power source shall be bonded to the vehicle frame. The neutral bonding connection shall occur only at the power source. In addition to the bonding required for the low voltage return current, each body and each driving or crew compartment enclosure shall be bonded to the vehicle frame by a copper conductor.

The conductor shall have a minimum amperage rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated amperage on the power source specification label.

A single conductor that is sized to meet the low voltage and line voltage requirements shall be permitted to be used.

#### Ground Fault Circuit Interrupters

In special service vehicles incorporating a lavatory, sink, toilet, shower, or tub, 120 V, 15 or 20 A receptacles within 6 ft (1.8 m) of these fixtures shall have ground fault circuit interrupter (GFCI) protection. GFCIs integrated into outlets or circuit breakers or as stand-alone devices shall be permitted to be used in situations.

#### Power Source General Requirements

All power source system mechanical and electrical components shall be sized to support the continuous duty nameplate rating of the power source.

The power source shall be shielded from contamination that would prevent the power source from operating within its design specifications.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### Power Source Rating

For power sources of 8 kW or larger, the power source manufacturer shall declare the continuous duty rating that the power source can provide when installed on fire apparatus according to the manufacturer's instructions and run at 120°F (49°C) air intake temperature at 2000 ft (600 m) above sea level.

The rating on the power source specification label shall not exceed the declared rating from the power source manufacturer.

Access shall be provided to permit both routine maintenance and removal of the power source for major servicing. The power source shall be located such that neither it nor its mounting brackets interfere with the routine maintenance of the fire apparatus.

#### Instrumentation

If the power source is rated at less than 3 kW, a "Power On" indicator shall be provided. If the power source is rated at 3 kW or more but less than 8 kW, a voltmeter shall be provided.

If the power source is rated at 8 kW or more, the following instrumentation shall be provided at an operator's panel:

- Voltmeter
- Current meters for each ungrounded leg
- Frequency (Hz) meter
- Power source hour meter

The instrumentation shall be permanently mounted at an operator's panel. The instruments shall be located in a plane facing the operator. Gauges, switches, or other instruments on this panel shall each have a label to indicate their function.

The instruments and other line voltage equipment and controls shall be protected from mechanical damage and not obstructed by tool mounting or equipment storage.

An instruction plate(s) that provides the operator with the essential power source operating instructions, including the power-up and power-down sequence, shall be permanently attached to the apparatus at any point where such operations can take place.

#### Operation

Provisions shall be made for placing the generator drive system in operation using controls and switches that are identified and within convenient reach of the operator.

Where the generator is driven by the chassis engine and engine compression brakes or engine exhaust brakes are furnished, they shall be automatically disengaged for generator operations.

Any control device used in the generator system power train between the engine and the generator shall be equipped with a means to prevent unintentional movement of the control device from its set position in the power generation mode.

If there is permanent wiring on the apparatus that is designed to be connected to the power source, a power source specification label that is permanently attached to the apparatus at the operator's control station shall provide the operator with the information required.

The power source, at any load, shall not produce a noise level that exceeds 90 dBA in any driving compartment, crew compartment, or onboard command area with windows and doors closed or at any operator's station on the apparatus.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### Power Supply Assembly

The conductors used in the power supply assembly between the output terminals of the power source and the main over current protection device shall not exceed 12 ft (4 m) in length.

All power supply assembly conductors, including neutral and grounding conductors, shall have an equivalent amperage rating and shall be sized to carry not less than 115 percent of the amperage of the nameplate current rating of the power source.

If the power supply assembly connects to the vibrating part of a generator (not a connection on the base), the conductors shall be flexible cord or other fine-stranded conductors enclosed in metallic or nonmetallic liquid tight flexible conduit rated for wet locations and temperatures not less than 194°F (90°C).

#### Overcurrent Protection

Manually resettable over current devices shall be installed to protect the line voltage electrical system components.

#### Power Source Protection

A main over current protection device shall be provided that is either incorporated in the power source or connected to the power source by a power supply assembly.

The size of the main over current protection device shall not exceed 100 percent of the rated amperage stated on the power source specification label or the rating of the next larger available size over current protection device, where so recommended by the power source manufacturer.

If the main over current protection device is subject to road spray, the unit shall be housed in a Type 4-rated enclosure.

#### Branch Circuit Overcurrent Protection

Over current protection devices shall be provided for each individual circuit and shall be sized at not less than 15 amps in accordance with 240.4, "Protection of Conductors," of *NFPA 70*.

Any panel board shall have a main breaker where the panel has six or more individual branch circuits or the power source is rated 8 kW or larger.

Each over current protection device shall be marked with a label to identify the function of the circuit it protects.

Dedicated circuits shall be provided for any large appliance or device (air conditioning units, large motors, etc.) that requires 60 percent or more of the rated capacity of the circuit to which it is connected, and that circuit shall serve no other purpose.

#### Panelboards

All fixed power sources shall be hardwired to a permanently mounted panel board unless one of the following conditions exists:

- 1) All line voltage power connections are made through receptacles on the power source and the receptacles are protected by integrated over current devices.
- 2) Only one circuit is hardwired to the power source, which is protected by an integrated over current device.

# Fredericton Fire Department

## Light Rescue

### Production Specification

The panel shall be visible and located so that there is unimpeded access to the panel board controls. All panel boards shall be designed for use in their intended location. The panel(s) shall be protected from mechanical damage, tool mounting, and equipment storage.

Where the power source is 120/240 V and 120 V loads are connected, the apparatus manufacturer or line voltage system installer shall consider load balancing to the extent that it is possible.

#### Wiring Methods

Fixed wiring systems shall be limited to the following:

- 1) Metallic or nonmetallic liquid tight flexible conduit rated at temperatures not less than 194°F (90°C) with stranded copper wire rated for wet locations and temperatures not less than 194°F (90°C)
- 2) Type SOW, SOOW, SEOW, or SEOOW flexible cord rated at 600 V and at temperatures not less than 194°F (90°C)

Electrical cord or conduit shall not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring and shall be arranged as follows:

- 1) Separated by a minimum distance of 12 in. (300 mm) from exhaust piping or shielded from such piping
- 2) Separated from fuel lines by a minimum distance of 6 in. (150 mm)

A means shall be provided to allow "flexing" between the driving and crew compartment, the body, and other areas or equipment whose movement would stress the wiring.

Electrical cord or conduit shall be supported within 6 in. (150 mm) of any junction box and at a minimum of every 24 in. (600 mm) of run.

Supports shall be made of nonmetallic materials or of corrosion-resistant or corrosion-protected metal. All supports shall be of a design that does not cut or abrade the conduit or cord and shall be mechanically fastened to the apparatus.

Only fittings and components listed for the type of cord or conduit being installed shall be used.

Splices shall be made only in a listed junction box.

#### Additional Requirements for Flexible Cord Installations

Where flexible cord is used in any location where it could be damaged, it shall be protected by installation in conduit, enclosures, or guards.

Where flexible cord penetrates a metal surface, rubber or plastic grommets or bushings shall be installed.

#### Wiring Identification

Each line voltage circuit originating from the main panel board shall be identified.

The wire or circuit identification either shall reference a wiring diagram or wire list or shall indicate the final termination point of the circuit.

Where pre-wiring for future power sources or devices exists, the un-terminated ends shall be marked with a label showing their wire size and intended function.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### Wiring System Components

Only stranded copper conductors with an insulation rated for temperatures of at least 194°F (90°C) and wet locations shall be used. Conductors in flexible cord shall be sized in accordance with Table 400.5(A) of *NFPA 70*. Conductors used in conduit shall be sized in accordance with 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*. Aluminum or copper-clad aluminum conductors shall not be used.

All boxes shall conform to and be mounted in accordance with Article 314, "Outlet, Device, Pull, and Junction Boxes; Conduit Bodies; Fittings; and Manholes," of *NFPA 70*. All boxes shall be accessible using ordinary hand tools. Boxes shall not be permitted behind welded or pop-riveted panels.

The maximum number of conductors permitted in any box shall be in accordance with 314.16, "Number of Conductors in Outlet, Device, and Junction Boxes, and Conduit Bodies," of *NFPA 70*.

All wiring connections and terminations shall provide a positive mechanical and electrical connection. Connectors shall be installed in accordance with the manufacturer's instructions. Wire nuts or insulation displacement and insulation piercing connectors shall not be used.

Each switch shall indicate the position of its contact points (i.e., open or closed) and shall be rated for the continuous operation of the load being controlled. All switches shall be marked with a label indicating the function of the switch. Circuit breakers used as switches shall be "switch rated" (SWD) or better. Switches shall simultaneously open all associated line voltage conductors. Switching of the neutral conductor alone shall not be permitted.

Line voltage circuits controlled by low voltage circuits shall be wired through properly rated relays in listed enclosures that control all non-grounded current-carrying conductors.

#### Receptacles and Inlet Devices

##### Wet and Dry Locations

All wet location receptacle outlets and inlet devices, including those on hardwired, remote power distribution boxes, shall be of the grounding type, provided with a wet location cover, and installed in accordance with Section 406.8, "Receptacles in Damp or Wet Locations," of *NFPA 70*.

All receptacles located in a wet location shall be not less than 24 in. (600 mm) from the ground. Receptacles on off road fire apparatus shall be a minimum of 30 in. (750 mm) from the ground. All receptacles located in a dry location shall be of the grounding type and shall be at least 12 in. (300 mm) above the interior floor height. No receptacle shall be installed in a face-up position.

The face of any wet location receptacle shall be installed in a plane from vertical to not more than 45 degrees off vertical.

##### Receptacle Label

Each receptacle shall be marked with a label indicating the nominal line voltage (120 volts or 240 volts) and the current rating in amps of the circuit. If the receptacle is DC or other than single phase, that information shall also be marked on the label.

All receptacles and electrical inlet devices shall be listed to UL 498, *Standard for Safety Attachment Plugs and Receptacles*, or other recognized performance standards.

Receptacles used for DC voltages shall be rated for DC service.

# Fredericton Fire Department

## Light Rescue

### Production Specification

#### Wiring Schematics

An "As-Built" Wiring diagrams for line voltage systems shall be provided to include the following information;

- 1) Pictorial representations of circuit logic for all electrical components and wiring
- 2) Circuit identification
- 3) Connector pin identification
- 4) Zone location of electrical components
- 5) Safety interlocks
- 6) Alternator–battery power distribution circuits
- 7) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems

#### **120/240 VAC SCENE LIGHTING**

##### **COMMAND LIGHT - KNIGHT TOWER w/ BACKLIGHT**

The apparatus shall be equipped with one (1) all-electric floodlight tower(s). The unit shall not require tapping into vehicle braking system to be operated, eliminating the chance for vehicle brake problems. Hydraulic or pneumatic type floodlights are not acceptable alternatives to the all-electric light tower specified. NO EXCEPTIONS.

The light tower shall have six (6) weatherproof, 650 watt, 120 volt quartz halogen lights. Light heads shall be mounted in three (3) pairs, giving two (2) vertical lines of three (3) when the lights are in the upright position. The light tower shall have slip-rings for a full 360 degree rotation and capable of rotating either direction from a stowed position, NO EXCEPTIONS.

The lower pair of light heads shall be capable of being rotated about a horizontal axis to provide light down on the vehicle or to the opposite side of the vehicle.

The light tower shall be capable of overhanging the side or back of the vehicle (depending on mounting location) to provide maximum illumination and a warming area adjacent to the vehicle, NO EXCEPTIONS.

Positioning of the light bank shall be accomplished with maintenance free, heavy duty 12 volt linear actuators.

The light tower shall be all aluminum construction, with stainless steel shafts and bronze bushings for long life and low maintenance.

Light tower shall be controlled with a hand-held umbilical line remote control. The storage station for the remote control unit shall be equipped with a button to activate the "Auto-Park" automatic nesting feature.

Command Light controls shall include:

- Three (3) switches, one (1) for each light bank.
- One (1) light bank rotation switch.
- One (1) switch for elevating lower stage.
- One (1) switch for elevating upper stage.
- One (1) light to indicate when light bank is out of roof nest position.
- One (1) light to indicate when light bank is rotated to proper nest position.
- One (1) back light rotation switch
- One (1) "On/Off" switch for the top mounted strobe (optional)

The controls shall be located per the itemized compartment list.

# Fredericton Fire Department

## Light Rescue

### Production Specification

The light tower shall have a full extension over 7' from mounted position and extend from nest position to full upright in 15 seconds. The overall size of nested light tower shall be approximately 23" wide x 47" long x 11 3/4" high, and weight approximately 120 lbs.

A flashing warning light shall be provided in cab, indicating when a light tower is not in nested position as required by NFPA 1901. The operational envelope of the mast shall be automatically illuminated whenever the mast assembly is being raised, lowered, or rotated as required by NFPA 1901.

The Command Light shall be covered by a five (5) year limited warranty from defects in materials and workmanship. An operation, maintenance, and parts manual shall be provided with the delivered apparatus.

#### **RECESSED LIGHT TOWER**

The specified light tower(s) shall be recessed into the roof of body to allow light tower(s) to be stowed below roof level. The floor and side walls of recessed area shall be fabricated as a separate module from 3/16" aluminum treadplate with an overlapping 3" flange around perimeter roof line. The recessed area shall be completely water tight. All electrical connections made to light tower shall be located on sidewalls for a water tight connection.

The recessed area shall have two (2) water drain holes (in opposite corners) with flexible 1" diameter hose routed to the area below the body.

#### **EQUIPMENT PAYLOAD WEIGHT ALLOWANCE**

In compliance with NFPA 1901 standards, the special service vehicle shall be designed for an equipment loading allowance of 2,500 lbs. of Fredericton Fire Department provided loose equipment based on a 15,001 - 20,000 pound gross vehicle weight rating.

#### **EQUIPMENT**

The following equipment shall be furnished with the completed special service vehicle;

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- There shall be two (2) NFPA approved aluminum wheel chocks provided for 32" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20 % grade, with the transmission in neutral, and the parking brake released.
  - The wheel chock(s) shall be shipped loose with the completed apparatus.
- Three (3) Streamlight Survivor LED, model # 90509, portable rechargeable flashlight(s) and charger(s) shall be provided. Each flashlight shall be orange in color. Each flashlight shall have a 12 volt DC fast charging station and mount. The flashlights shall be wired to battery direct unless otherwise specified by the customer.
  - The flashlight(s) shall be mounted on the completed unit in the lower area of compartment S1.

#### **REMAINING NFPA MINOR EQUIPMENT BY PURCHASER**

All other minor equipment not specified above, but required by NFPA 1901 before the unit is placed in service shall be supplied and mounted by Fredericton Fire Department.