

# GREELEY FIRE DEPT

SVI #930

Production Specs

## Table of Contents

<b>WEIGHT DISTRIBUTION</b> .....	9
<b>LOAD DISTRIBUTION</b> .....	9
The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C) .....	
<b>ROADABILITY</b> .....	9
<b>SERVICEABILITY</b> .....	10
<b>CONSTRUCTION DOCUMENTATION</b> .....	10
<b>OPERATIONS AND SERVICE DOCUMENTATION</b> .....	11
<b>NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVES</b> .....	12
<b>STATEMENT OF EXCEPTIONS</b> .....	12
<b>CARRYING CAPACITY</b> .....	12
<b>TESTING</b> .....	13
<b>ROAD TEST</b> .....	13
<b>LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST</b> .....	14
<b>TEST SEQUENCE</b> .....	14
<b>1. RESERVE CAPACITY TEST</b> .....	14
<b>2. ALTERNATOR PERFORMANCE TEST</b> .....	14
<b>TEST AT IDLE</b> .....	14
<b>TEST AT FULL LOAD</b> .....	14
<b>3. LOW VOLTAGE ALARM TEST</b> .....	15
<b>LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST</b> .....	15
<b>DOCUMENTATION</b> .....	15
<b>UL 120/240 VAC CERTIFICATION</b> .....	15
<b>DIELECTRIC VOLTAGE WITHSTAND TEST</b> .....	16
<b>UL PUMP CERTIFICATION</b> .....	17
<b>WARRANTY</b> .....	18

# GREELEY FIRE DEPT

SVI #930

## Production Specs

<b>GENERAL LIMITED WARRANTY - TWO (2) YEARS</b> .....	18
<b>LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS</b> .....	18
<b>STRUCTURAL WARRANTY - TEN (10) YEARS</b> .....	18
<b>UNDERCOAT WARRANTY</b> .....	18
<b>PAINT LIMITED WARRANTY - TEN (10) YEARS</b> .....	18
<b>GRAPHICS LIMITED WARRANTY</b> .....	19
<b>WATEROUS FIVE YEAR PUMP WARRANTY</b> .....	19
<b>STAINLESS STEEL PLUMBING WARRANTY</b> .....	19
<b>UPF POLY WATER TANK WARRANTY</b> .....	19
<b>CONSTRUCTION PERIOD</b> .....	19
<b>APPARATUS DELIVERY</b> .....	19
<b>CHASSIS MODIFICATIONS</b> .....	73
<b>LUBRICATION AND TIRE DATA PLATE</b> .....	73
<b>VEHICLE DATA PLATE</b> .....	73
<b>OVERALL HEIGHT, LENGTH DATA PLATE (US)</b> .....	74
A final stage manufacturer vehicle certification label shall be provided and installed in the driver cab door jamb area.....	74
<b>FRONT BUMPER</b> .....	74
<b>BUMPER GRAVELSHIELD</b> .....	75
<b>BUMPER PRE-CONNECT COMPARTMENT</b> .....	75
<b>AIR HORN(S)</b> .....	75
<b>FRONT TOW PROVISIONS</b> .....	75
<b>EXHAUST</b> .....	75
<b>MDT COMPUTER</b> .....	76
<b>RADIO/ANTENNA INSTALLATION</b> .....	76
<b>SEAT BELT COLOR</b> .....	76
<b>SEAT BELT WEB LENGTH - CUSTOM CAB</b> .....	76
<b>SEAT BELT / VDR SYSTEM - CUSTOM CAB</b> .....	76
<b>HELMET STORAGE</b> .....	77

# GREELEY FIRE DEPT

SVI #930

## Production Specs

<b>CAB CRASH TEST CERTIFICATION</b> .....	77
<b>CAB MIRRORS, DRIVER ADJUSTABLE</b> .....	77
<b>MUDFLAPS</b> .....	78
<b>AIR BRAKE SYSTEM QUICK BUILD-UP</b> .....	78
<b>CAB INTERIOR CABINET - CENTER REAR WALL</b> .....	78
<b>12 VDC ACCESSORY PLUG</b> .....	78
<b>FUEL FILL</b> .....	78
<b>MAP BOX</b> .....	79
<b>BODY DESIGN</b> .....	79
<b>EXTERIOR ALUMINUM BODY</b> .....	79
<b>ROOF CONSTRUCTION</b> .....	80
<b>BODY SUBFRAME</b> .....	80
<b>BODY MOUNTING</b> .....	81
<b>12" REAR STEP BUMPER</b> .....	81
<b>REAR TOW EYES</b> .....	81
<b>GROUND LIGHTS</b> .....	81
<b>WHEEL WELL EXTERIOR PANEL</b> .....	81
<b>STAINLESS STEEL BODY FENDERS</b> .....	82
<b>WHEEL WELL LINERS</b> .....	82
<b>SCBA CYLINDER COMPARTMENTS</b> .....	82
<b>BODY PAINT SPECIFICATIONS</b> .....	82
<b>BODY PAINT PREPARATION</b> .....	82
<b>PAINT PROCESS</b> .....	82
<b>BODY UNDERCOATING</b> .....	84
<b>UNDERCOAT WARRANTY</b> .....	84
<b>PAINT WARRANTY</b> .....	84
<b>COMPARTMENT INTERIOR FINISH</b> .....	84
<b>REFLECTIVE STRIPE REQUIREMENTS</b> .....	84
<b>REFLECTIVE STRIPE - CAB SIDE</b> .....	85

# GREELEY FIRE DEPT

SVI #930

Production Specs

REFLECTIVE STRIPE - CAB FRONT BUMPER.....	85
REFLECTIVE STRIPE - BODY SIDES.....	85
CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS.....	85
LETTERING.....	86
SIDE CAB DOOR LETTERING.....	86
FRONT OF CAB LETTERING.....	86
CUSTOM DOOR DECAL.....	87
EXTERIOR COMPARTMENT DOORS.....	87
HINGED DOOR CONSTRUCTION.....	87
ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM).....	87
BODY HEIGHT MEASUREMENTS.....	88
BODY WIDTH DIMENSIONS.....	89
STREETSIDE COMPARTMENT - FRONT (S1).....	89
COMPARTMENT LAYOUT.....	89
STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2).....	90
COMPARTMENT LAYOUT.....	90
STREETSIDE COMPARTMENT - REAR (S3).....	90
COMPARTMENT LAYOUT.....	91
CURBSIDE COMPARTMENT - FRONT (C1).....	91
COMPARTMENT LAYOUT.....	92
CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C2).....	92
COMPARTMENT LAYOUT.....	93
CURBSIDE COMPARTMENT - REAR (C3).....	93
COMPARTMENT LAYOUT.....	93
REAR COMPARTMENT - CENTER (RC1).....	94
COMPARTMENT LAYOUT.....	94
LADDER LIFT INTERLOCK.....	95
REAR BODY HANDRAILS.....	96
PUMP MODULE HANDRAILS.....	97

# GREELEY FIRE DEPT

SVI #930

Production Specs

FOLDING STEP(S).....	97
LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC.....	97
12 VOLT MULTIPLEX CONTROL CENTER .....	99
BATTERY SYSTEM.....	100
BATTERY SWITCH.....	101
BATTERY SOLENOID.....	101
BATTERY CONDITIONER.....	101
ENGINE COMPARTMENT LIGHT.....	101
REAR SCENE LIGHTS (BACK-UP LIGHTS).....	101
CAB HAZARD WARNING LIGHT .....	101
BACK-UP ALARM.....	102
TAIL LIGHTS.....	102
MIDSHIP MARKER/TURN SIGNAL.....	102
MARKER LIGHTS .....	102
CAB STEP LIGHTS / GROUND LIGHTS.....	102
LICENSE PLATE LIGHT .....	103
ELECTRONIC SIREN .....	103
SIREN SPEAKER.....	103
TRAFFIC ADVISOR LIGHTS .....	103
SETCOM INTERCOM SYSTEM.....	103
INTERCOM SYSTEM INSTALLATION .....	104
WARNING LIGHT PACKAGE.....	104
UPPER LEVEL OPTICAL WARNING DEVICES.....	105
GTT OPTICOM.....	106
LOWER LEVEL OPTICAL WARNING DEVICES.....	106
HYDRAULIC GENERATOR SYSTEM.....	107
GENERATOR MOUNTING .....	108
WARRANTY PERIOD.....	108
HYDRAULIC COMPONENTS .....	108

# GREELEY FIRE DEPT

SVI #930

Production Specs

<b>GENERATOR MOUNTING .....</b>	<b>108</b>
<b>MANUALS AND SCHEMATICS .....</b>	<b>108</b>
<b>POWER-TAKE-OFF GENERATOR DRIVE .....</b>	<b>109</b>
<b>LOADCENTER.....</b>	<b>109</b>
<b>GENERATOR MONITORING PANEL .....</b>	<b>109</b>
<b>SHORE POWER INLET - BATTERY CHARGER.....</b>	<b>110</b>
<b>OUTLETS AND CIRCUITS .....</b>	<b>110</b>
<b>LINE VOLTAGE ELECTRICAL SYSTEM.....</b>	<b>111</b>
<b>GENERAL REQUIREMENTS.....</b>	<b>111</b>
<b>120/240 VAC SCENE LIGHTING.....</b>	<b>117</b>
<b>FRONT CAB-MOUNTED SCENE LIGHT(S) .....</b>	<b>117</b>
<b>SIDE UPPER RECESSED SCENE LIGHTS.....</b>	<b>117</b>
<b>SIDE MOUNT PUMP MODULE .....</b>	<b>118</b>
<b>HEATER .....</b>	<b>119</b>
<b>WATEROUS CU FIRE PUMP .....</b>	<b>120</b>
<b>PUMP TRANSMISSION .....</b>	<b>121</b>
<b>WATEROUS FIVE YEAR PUMP WARRANTY .....</b>	<b>123</b>
<b>MANUFACTURER FIRE PUMP TEST .....</b>	<b>123</b>
<b>FIRE PUMP TEST LABEL .....</b>	<b>123</b>
<b>ALTITUDE REQUIREMENT .....</b>	<b>123</b>
<b>PUMP DRAIN CONTROL .....</b>	<b>123</b>
<b>ELECTRIC PRIMING PUMP CONTROL AT PUMP PANEL .....</b>	<b>123</b>
<b>PRIMER CONTROL .....</b>	<b>124</b>
<b>DISCHARGE RELIEF VALVE .....</b>	<b>124</b>
<b>6" SUCTION INLET - STREETSIDE .....</b>	<b>124</b>
<b>LONG SUCTION TUBE .....</b>	<b>124</b>
<b>SUCTION CAP .....</b>	<b>124</b>
<b>6" SUCTION INLET - CURBSIDE .....</b>	<b>124</b>
<b>LONG SUCTION TUBE .....</b>	<b>124</b>

# GREELEY FIRE DEPT

SVI #930

Production Specs

SUCTION CAP .....	124
HEAT EXCHANGER .....	125
INTAKE RELIEF VALVE .....	125
PLUMBING SPECIFICATIONS.....	125
STAINLESS STEEL INTAKE MANIFOLD .....	125
STAINLESS STEEL DISCHARGE MANIFOLD .....	125
STAINLESS STEEL PLUMBING WARRANTY .....	125
STREETSIDE INTAKE - 2-1/2" .....	127
TANK TO PUMP CHECK VALVE .....	127
TANK TO PUMP VALVE.....	127
DISCHARGES.....	128
FRONT DISCHARGE.....	128
STREETSIDE DISCHARGE .....	129
CURBSIDE DISCHARGE.....	130
MISCELLANEOUS DISCHARGE.....	131
HOSE BED DISCHARGE(S) .....	131
2" SPEED LAY(S) .....	131
DECK GUN .....	132
PUMP PANEL .....	133
PUMP PANEL LOCATION .....	134
PRESSURE GOVERNOR and ENGINE MONITORING DISPLAY .....	134
MASTER DISCHARGE GAUGE.....	135
MASTER INTAKE GAUGE.....	135
COLOR CODED LABELS .....	135
PUMP PANEL LIGHTING .....	135
PUMP PANEL AIR HORN SWITCH.....	135
TEST TAPS.....	135
WATER TANK LEVEL GAUGE.....	138
UPF POLY WATER TANK WARRANTY .....	139

# GREELEY FIRE DEPT

SVI #930

Production Specs

<b>HOSE BED STORAGE AREA .....</b>	<b>139</b>
<b>ALUMINUM HOSE BED COVER.....</b>	<b>140</b>
<b>EQUIPMENT PAYLOAD WEIGHT ALLOWANCE .....</b>	<b>140</b>
<b>EQUIPMENT.....</b>	<b>141</b>
<b>REMAINING NFPA MINOR EQUIPMENT BY PURCHASER .....</b>	<b>144</b>



# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **VEHICLE STABILITY SUPPLIED WITH CAB/CHASSIS**

The cab/chassis shall be equipped with a stability control system. The system shall have, at a minimum, a steering wheel position sensor, a vehicle yaw sensor, a lateral accelerometer and individual wheel brake controls.

### **WEIGHT DISTRIBUTION**

When the fire apparatus is loaded to its estimated in-service weight, the front-to-rear weight distribution shall be within the limits set by the chassis manufacturer.

The front axle loads shall not be less than the minimum axle loads specified by the chassis manufacturer under full load and all other loading conditions.

### **LOAD DISTRIBUTION**

The apparatus manufacturer shall calculate the load distribution for the apparatus, and that load distribution plan shall be delivered with the fire apparatus.

The manufacturer shall engineer the fire apparatus to comply with the gross axle weight ratings (GAWR), the overall gross vehicle weight rating (GVWR), and the chassis manufacturer's load balance guidelines.

The fire apparatus, when loaded to its estimated in service weight, shall have a side-to-side tire load variation of no more than 7 percent of the total tire load for that axle.

Each tire shall be equipped with a visual indicator or monitoring system that indicates tire pressure.

### **FIRE APPARATUS PERFORMANCE**

The fire apparatus shall meet the requirements of this standard at elevations of 2000 ft (600 m) above sea level.

The fire apparatus shall meet all the requirements of this standard while stationary on a grade of 10 percent in any direction.

The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C).

### **ROADABILITY**

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- 1) From a standing start, the apparatus shall be able to attain a speed of 35 mph (55 km/hr) within 25 seconds on a level road.
- 2) The apparatus shall be able to attain a minimum top speed of 50 mph (80 km/hr) on a level road.
- 3) The apparatus shall be able to maintain a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent.

The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (105 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal (4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (85 km/ hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

### **SERVICEABILITY**

The fire apparatus shall be designed to allow the manufacturer's recommended routine maintenance checks of lubricant and fluid levels to be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

### **CONSTRUCTION DOCUMENTATION**

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

The manufacturer's record of apparatus construction details, including the following information:

- 1) Owner's name and address
- 2) Apparatus manufacturer, model, and serial number
- 3) Chassis make, model, and serial number
  - a) GAWR of front and rear axles and GVWR
  - b) Front tire size and total rated capacity in pounds (kilograms)
  - c) Rear tire size and total rated capacity in pounds (kilograms)
  - d) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
  - e) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
  - f) Type of fuel and fuel tank capacity
  - g) Electrical system voltage and alternator output in amps
  - h) Battery make, model, and capacity in cold cranking amps (CCA)
  - i) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
- 4) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
- 5) Pump transmission make, model, serial number, and gear ratio
- 6) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
- 7) Water and Foam tank certified capacity in gallons or liters
- 8) Paint manufacturer and paint number(s)
- 9) Company name and signature of responsible company representative
- 10) If the apparatus is a mobile foam fire apparatus, the certification of foam tank capacity
- 11) Certification of compliance of the optical warning system
- 12) Siren manufacturer's certification of the siren
- 13) Written load analysis and results of the electrical system performance tests
- 14) Certification of slip resistance of all stepping, standing, and walking surfaces

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- 15) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability
- 16) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions
- 17) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications
- 18) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed
- 19) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test
- 20) If the apparatus has a fire pump, the certification of inspection and test for the fire pump
- 21) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test
- 22) When the apparatus is equipped with a water tank, the certification of water tank capacity
- 23) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy and the final installer's certification the foam proportioning system meets this standard
- 24) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests
- 25) If the apparatus has a line voltage power source, the certification of the test for the power source
- 26) If the apparatus is equipped with an air system, air tank certificates, the SCBA fill station certification, and the results of the testing of the air system installation
- 27) Any other required manufacturer test data or reports.

### **OPERATIONS AND SERVICE DOCUMENTATION**

The Contractor shall deliver with the fire apparatus at least five (5) sets of complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service and operations of the fire apparatus and all major components thereof.

The Contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- 1) Manufacturer's name and address
- 2) Country of manufacture
- 3) Source for service and technical information
- 4) Parts replacement information
- 5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- 6) Wiring diagrams for low voltage and line voltage systems to include the following information:
  - j) Pictorial representations of circuit logic for all electrical components and wiring
  - k) Circuit identification
  - l) Connector pin identification
  - m) Zone location of electrical components
  - n) Safety interlocks
  - o) Alternator-battery power distribution circuits
  - p) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- 7) Lubrication charts
- 8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- 9) Precautions related to multiple configurations of aerial devices, if applicable
- 10) Instructions regarding the frequency and procedure for recommended maintenance
- 11) Overall apparatus operating instructions
- 12) Safety considerations

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- 13) Limitations of use
- 14) Inspection procedures
- 15) Recommended service procedures
- 16) Troubleshooting guide
- 17) Apparatus body, chassis and other component manufacturer's warranties
- 18) Special data required by this standard
- 19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus

The Contractor shall deliver with the apparatus all manufacturers' operations and service documents supplied with components and equipment that are installed or supplied by the Contractor.

### **NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVES**

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a USB Flash Drive. These manuals shall be divided into sections for ease of reference. There shall be five (5) USB flash Drives provided with the completed vehicle.

### **STATEMENT OF EXCEPTIONS**

The Contractor shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- 1) A separate specification of the section of the applicable standard for which compliance is lacking
- 2) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
- 3) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance
- 4) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to or at the time of delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

An apparatus that is delivered subject to a Statement of Exceptions other than a certification of full compliance shall not be placed in emergency service until the apparatus has been modified as necessary to accomplish full compliance with this standard.

### **CARRYING CAPACITY**

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The Body Manufacturer shall establish the estimated in service weight during the design of the vehicle

The estimated in-service weight shall include the following:

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- 1) The chassis, body and tank(s)
- 2) Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
- 3) Full water and other agent tanks
- 4) \*250 lb (114 kg) in each seating position
- 5) Fixed equipment such as pumps, aerial devices, generators, reels and air systems as installed
- 6) Ground ladders, suction hose, designed hose load in their hose beds and on their reels
- 7) An allowance for miscellaneous equipment that is the greatest of the values for type of vehicle per NFPA 1901, a Purchaser provided list of equipment to be carried with weights or a Purchaser specified miscellaneous equipment allowance.

The Body Manufacturer shall engineer and design the vehicle such that the completed unit, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

A final Body Manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

		<b>Equipment Allowance</b>		
<b>Apparatus Type</b>	<b>Storage Areas</b>	<b>Apparatus Size</b>	<b>lb.</b>	<b>kg.</b>
Pumper Fire Apparatus	Equip. minimum of 40 cu ft (1.1 cu mt) of enclosed compartmentation.	Less than 250 cu ft ( 7 cu mt) compartment space	2,000	910
	Hose minimum of 30 cu ft (0.8 cu mt) for 2 1/2" (65 mm) or larger fire hose.	250 cu ft (7 cu mt) or more of compartment space	2,500	1,135
	(2) areas for pre-connects each minimum of 3.5 cu.ft. (0.1 cu.mt.) for 1 1/2" (38 mm) or larger fire hose.			
Compartment space for pumpers is calculated based on the inside dimensions of the enclosed compartment.				

### **TESTING**

#### **ROAD TEST**

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the Body Manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (-18°C and 43°C).

### **TEST SEQUENCE**

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for ten (10) minutes. Failure of any of these tests shall require a repeat of the sequence.

#### **1. RESERVE CAPACITY TEST**

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

#### **2. ALTERNATOR PERFORMANCE TEST**

##### **TEST AT IDLE**

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

##### **TEST AT FULL LOAD**

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's

# GREELEY FIRE DEPT

SVI #930

## Production Specs

governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

### **3. LOW VOLTAGE ALARM TEST**

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

#### **DOCUMENTATION**

The manufacturer shall deliver the following with the fire apparatus:

- 1) Documentation of the electrical system performance tests
- 2) A written electrical load analysis, including the following:
  - q) The nameplate rating of the alternator
  - r) The alternator rating
  - s) Each of the component loads specified that make up the minimum continuous electrical load
  - t) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
  - u) Each individual intermittent electrical load

#### **UL 120/240 VAC CERTIFICATION**

The 120/240 volt electrical system shall be third-party, independent, audit-certified through Underwriters Laboratory (UL) to the current edition of NFPA 1901 to perform as listed below;

The prime mover shall be started from a cold start condition, and the unloaded voltage and frequency shall be recorded.

The line voltage electrical system shall be loaded to at least 100% of the continuous rated wattage stated on the power source specification label. Testing with a resistive load bank shall be permitted.

The power source shall be operated in the manner specified by the apparatus manufacturer as documented on instruction plates or in operation manuals. The power source shall be operated at a minimum of 100% of the continuous rated wattage as stated on the power source specification label for a minimum of two (2) hours.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The load shall be adjusted to maintain the output wattage at or above the continuous rated wattage during the entire 2-hour test.

The following conditions shall be recorded at least every 1/2 hour during the test:

- 1) The power source output voltage, frequency and amperes
- 2) The prime mover's oil pressure, water temperature and transmission temperature, if applicable
- 3) The power source hydraulic fluid temperature, if applicable
- 4) The ambient temperature and power source air inlet temperature

The following conditions shall be recorded once during the test for power sources driven by dedicated auxiliary internal combustion engines:

- 1) Altitude
- 2) Barometric pressure
- 3) Relative humidity

If the generator is driven by the chassis engine and the generator allows for operation at variable speeds, the chassis engine speed shall be reduced to the lowest rpm allowed for generator operation and the voltage and frequency shall be recorded.

The load shall be removed and the unloaded voltage and frequency shall be recorded.

Voltage shall be maintained within  $\pm 10\%$  of the voltage stated on the power source specification label during the entire test. Frequency shall be maintained within  $\pm 3$  Hz of the frequency stated on the power source specification label during the entire test.

The total continuous electrical loads, excluding those loads associated with the equipment defined in NFPA 22.15.7.3.11.2, shall be applied during the testing unless an auxiliary engine drives the power source.

If the apparatus is equipped with a fire pump, the 2-hour certification test of the power source shall be completed with the fire pump pumping at 100% capacity at 150 psi (1000 kPa) net pump pressure. The test shall be permitted to be run concurrently with the pump certification test.

### **DOCUMENTATION**

The Body Manufacturer shall deliver the following with the fire apparatus:

The results of each test shall be recorded on an appropriate form and provided with the delivery of the fire apparatus.

### **DIELECTRIC VOLTAGE WITHSTAND TEST**

The line voltage wiring and permanently connected devices and equipment shall be subjected to a dielectric voltage withstand test of 900 volts for one (1) minute. The testing shall be performed after all body work has been completed.

The test shall be conducted as follows:

- 1) Isolate the power source from the panel board and disconnect any solid state low voltage components



# GREELEY FIRE DEPT

SVI #930

## Production Specs

- 2) Connect one lead of the dielectric tester to all the hot and neutral buses tied together
- 3) Connect the other lead to the fire apparatus frame or body
- 4) Close any switches and circuit breakers in the circuit(s)
- 5) Apply the dielectric voltage for one (1) minute in accordance with the testing equipment manufacturer's instructions

The electrical polarity of all permanently wired equipment, cord reels and receptacles shall be tested to verify that wiring connections have been properly made.

Electrical continuity shall be verified from the chassis or body to all line voltage electrical enclosures, light housings, motor housings, light poles, switch boxes and receptacle ground connections that are accessible to fire fighters in normal operations.

If the apparatus is equipped with a transfer switch, it shall be tested to verify operation and that all non grounded conductors are switched.

Electrical light towers, floodlights, motors, fixed appliances and portable generators shall be operated at their full rating or capacity for 30 minutes to ensure proper operation.

### **UL PUMP CERTIFICATION**

The apparatus upon completion shall be tested and certified by Underwriters Laboratories, Inc. (UL) The certification tests shall follow the guide lines outlined in NFPA 1901 "Standard for Fire Apparatus".

If the fire pump has a rated capacity of 750 gpm (3000 L/min) or greater, the pump shall be tested after the pump and all its associated piping and equipment have been installed on the apparatus.

The fire pump shall be tested and certified to perform as listed below;

- 100% of rated capacity at 100 psi (700 kPa) net pressure
- 70% of rated capacity at 150 psi (1,000 kPa) net pressure
- 50% of rated capacity at 200 psi (1,400 kPa) net pressure

The test shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming device tests, and the vacuum test.

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 500 psi (3,400 kPa).

The pump shall comply with the applicable requirements of "Standard for Fire Apparatus 1901, latest edition.

The pump shall be capable of producing fire streams that are free from objectionable pulsation under all normal operating conditions.

If the apparatus is equipped with a pump driven by the chassis engine designed for both stationary pumping and pump-and-roll, the test shall verify that the engine speed control at the pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the parking brake is off, and the pump shift status in the driving compartment is disengaged.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

(2) The chassis transmission is in any gear other than neutral, the parking brake is on, and the pump shift in the driving compartment is in the "Pump Engaged" or the "OK to Pump-and-Roll" position.

A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve.

### **WARRANTY**

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source and will deal directly with the Greeley Fire Department on all warranty work.

### **GENERAL LIMITED WARRANTY - TWO (2) YEARS**

The vehicle shall be free of defects in material and workmanship for a period of two (2) years or 36,000 miles (or 57,936 kilometers), whichever occurs first starting thirty (30) days after the original invoice date.

The Contractor must be the "single source" coordinator of all warranties on the vehicle.

### **LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS**

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles (or 96,561 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

### **STRUCTURAL WARRANTY - TEN (10) YEARS**

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

### **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

### **PAINT LIMITED WARRANTY - TEN (10) YEARS**

The body shall be free of bubbling or peeling as a result of a defect in the method of manufacture for a period of ten (10) years or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date. **Pro-rated warranties will not be acceptable.**

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **GRAPHICS LIMITED WARRANTY**

The 3M graphics installation shall be warranted for a period of two (2) years. The 3M materials installed on completed vehicle shall be warranted for seven (7) years. The 3M Diamond grade film (if specified) shall be warranted for ten (10) years.

### **WATEROUS FIVE YEAR PUMP WARRANTY**

The fire pump shall be warranted by Waterous for a period of five (5) years from the date of delivery to the Greeley Fire Department.

### **STAINLESS STEEL PLUMBING WARRANTY**

The stainless steel plumbing shall be free of defects in material and workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

The contractor shall supply details of their warranty information with their bid submission.

### **UPF POLY WATER TANK WARRANTY**

The UPF poly water tank shall be provided with a lifetime material and workmanship limited warranty. The manufacturer shall supply details of their warranty information with their bid submission.

### **CONSTRUCTION PERIOD**

The completed vehicle shall be delivered within three hundred sixty (360) days after receipt of a purchase order or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to Greeley Fire Department as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

### **OVERALL HEIGHT**

The overall height (OAH) of the vehicle shall not exceed 130" (10' - 10") from the ground. This measurement shall be taken on flat ground with the tires properly inflated, in the unloaded condition, at that highest point of the vehicle.

### **OVERALL LENGTH**

The overall length (OAL) of the vehicle shall not exceed 420" (35' - 0").

### **APPARATUS DELIVERY**

The Greeley Fire Department shall pick up finished apparatus at Contractor's facility. The Contractor shall be responsible for notifying the Greeley Fire Department a minimum of two (2) weeks prior to the completion of apparatus, so that the Greeley Fire Department has sufficient time to schedule pickup.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **CAB CHASSIS SPECIFICATION**

#### **MODEL**

The chassis shall be a Gladiator model. The cab and chassis shall include design considerations for multiple emergency vehicle applications, rapid transit and maneuverability. The chassis shall be manufactured for heavy duty service with the strength and capacity to support a fully laden apparatus, one hundred (100) percent of the time.

#### **MODEL YEAR**

The chassis shall have a vehicle identification number that reflects a 2016 model year.

#### **COUNTRY OF SERVICE**

The chassis shall be put in service in the country of United States of America (USA).

The chassis will meet applicable U.S.A. federal motor vehicle safety standards per CFR Title 49 Chapter V Part 571 as clarified in the incomplete vehicle book per CFR Title 49 Chapter V Part 568 Section 4 which accompanies each chassis. Spartan Chassis is not responsible for compliance to state, regional, or local regulations. Dealers should identify those regulations and order any necessary optional equipment from Spartan Chassis or their OEM needed to be in compliance with those regulations.

#### **APPARATUS TYPE**

The apparatus shall be a pumper vehicle designed for emergency service use which shall be equipped with a permanently mounted fire pump which has a minimum rated capacity of 750 gallons per minute (3000 L/min). The apparatus shall include a water tank and hose body whose primary purpose is to combat structural and associated fires.

#### **VEHICLE TYPE**

The chassis shall be manufactured for use as a straight truck type vehicle and designed for the installation of a permanently mounted apparatus behind the cab. The apparatus of the vehicle shall be supplied and installed by the apparatus manufacturer.

#### **AXLE CONFIGURATION**

The chassis shall feature a 4 x 2 axle configuration consisting of a single rear drive axle with a single front steer axle.

#### **GROSS AXLE WEIGHT RATINGS FRONT**

The front gross axle weight rating (GAWR) of the chassis shall be 22,800 pounds.

This front gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **GROSS AXLE WEIGHT RATINGS REAR**

The rear gross axle weight rating (GAWR) of the chassis shall be 24,000 pounds.

This rear gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

### **PUMP PROVISION**

The chassis shall include provisions to mount a drive line pump in the middle of the chassis, behind the cab, more commonly known as the midship location.

### **CAB STYLE**

The cab shall be a custom, fully enclosed, ELFD model with a 10.00 inch raised roof over the driver, officer, and crew area, designed and built specifically for use as an emergency response vehicle by a company specializing in cab and chassis design for all emergency response applications. The cab shall be designed for heavy-duty service utilizing superior strength and capacity for the application of protecting the occupants of the vehicle. This style of cab shall offer up to ten (10) seating positions.

The cab shall incorporate a fully enclosed design with side wall roof supports, allowing for a spacious cab area with no partition between the front and rear sections of the cab. To provide a superior finish by reducing welds that fatigue cab metal; the roof, the rear wall and side wall panels shall be assembled using a combination of welds and proven industrial adhesives designed specifically for aluminum fabrication for construction.

The cab shall be constructed using multiple aluminum extrusions in conjunction with aluminum plate, which shall provide proven strength and the truest, flattest body surfaces ensuring less expensive paint repairs if needed. All aluminum welding shall be completed to the American Welding Society and ANSI D1.2-96 requirements for structural welding of aluminum.

All interior and exterior seams shall be sealed for optimum noise reduction and to provide the most favorable efficiency for heating and cooling retention.

The cab shall be constructed of 5052-H32 corrosion resistant aluminum plate. The cab shall incorporate tongue and groove fitted 6061-T6 0.13 & 0.19 inch thick aluminum extrusions for extreme duty situations. A single formed, one (1) piece extrusion shall be used for the "A" pillar, adding strength and rigidity to the cab as well as additional roll-over protection. The cab side walls and lower roof skin shall be 0.13 inch thick; the rear wall and raised roof skins shall be 0.09 inch thick; the front cab structure shall be 0.19 inch thick.

The exterior width of the cab shall be 99.40 inches wide with a minimum interior width of 91.00 inches. The overall cab length shall be 151.10 inches with 74.00 inches from the centerline of the front of the axle to the back of the cab.

The cab interior shall be designed to afford the maximum usable interior space and attention to ergonomics with hip and legroom while seated which exceeds industry standards. The crew cab floor shall be flat across the entire walking area for ease of movement inside the cab.

The cab shall offer an interior height of 57.50 inches from the front floor to the headliner and a rear floor to headliner height of 65.00 inches in the raised roof area, at a minimum. The cab shall offer an interior measurement at the floor level from the rear of the engine tunnel to the rear wall of the cab of 69.88 inches. All

# GREELEY FIRE DEPT

SVI #930

## Production Specs

interior measurements shall include the area within the interior trimmed surfaces and not to any unfinished surface.

The cab shall include a driver and officer area with two (2) cab doors large enough for personnel in full firefighting gear. The front doors shall offer a clear opening of 40.25 inches wide X 53.50 inches high, from the cab floor to the top of the door opening. The cab shall also include a crew area with up to two (2) cab doors, also large enough for personnel in full firefighting gear. The rear doors shall offer a clear opening of 32.25 inches wide X 61.00 inches high, from the cab floor to the top of the door opening.

The cab shall incorporate a progressive two (2) step configuration from the ground to the cab floor at each door opening. The progressive steps are vertically staggered and extend the full width of each step well allowing personnel in full firefighting gear to enter and exit the cab easily and safely.

The first step for the driver and officer area shall measure approximately 11.50 inches deep X 31.13 inches wide. The intermediate step shall measure approximately 8.50 inches deep X 32.50 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 11.00 inches.

The first step for the crew area shall measure approximately 11.50 inches deep X 20.44 inches wide. The intermediate step shall measure approximately 10.25 inches deep X 22.75 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 12.80 inches.

### **OCCUPANT PROTECTION**

The vehicle shall include the Advanced Protection System™ (APS) which shall secure belted occupants and increase the survivable space within the cab. The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The system components shall include:

- Driver steering wheel airbag
- Driver dual knee air bags (patent pending) with energy management mounting (patent pending) and officer knee airbag.
- Large driver, officer, and crew area side curtain airbags
- APS advanced seat belt system - retractor pre-tensioners tighten the seat belts around the occupants, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries
- Heavy truck Restraints Control Module (RCM) - receives inputs from the outboard sensors, selectively deploys APS systems, and records sensory inputs immediately before and during a detected qualifying event
- Integrated outboard crash sensors mounted at the perimeter of the vehicle - detects a qualifying front or side impact event and monitors and communicates vehicle status and real time diagnostics of all critical subsystems to the RCM
- Fault-indicating Supplemental Restraint System (SRS) light on the driver's instrument panel

Frontal impact protection shall be provided by the outboard sensors and the RCM. In a qualifying front impact event the outboard sensors provide inputs to the RCM. The RCM activates the steering wheel airbag, driver side dual knee airbags (patent pending), officer side knee airbag, and advanced seat belts for each occupant in the cab.

The APS frontal impact system shall be independently tested to ensure occupant injury criteria does not exceed injury criteria defined in Federal Motor Vehicle Safety Standard (FMVSS) 208. Frontal impact into a rigid barrier at

# GREELEY FIRE DEPT

SVI #930

## Production Specs

25 mph shall be conducted by an independent third party test facility using belted 95<sup>th</sup> percentile Hybrid II test dummies.

Rollover, side impact, and ejection mitigation shall be provided by the outboard sensors and the RCM. In qualifying rollover or side impact events the outboard sensors provide inputs to the RCM. The RCM activates the side curtain airbags and advanced seat belts for each occupant in the cab. The RCM measures roll angle, lateral acceleration, and roll rate to determine if a rollover event or side impact event is imminent or occurring.

In the event of a qualifying offset or other non-frontal impact, the RCM shall determine and intelligently deploy the front impact protection system, the side impact protection system, or both front and side impact protection systems based on the inputs received from the outboard crash sensors.

The APS side impact system shall be independently tested to ensure occupant injury criteria does not exceed injury criteria defined in Federal Motor Vehicle Safety Standard (FMVSS) 214. Side impact from a moving barrier at 17 mph shall be conducted by an independent third party test facility using belted 50<sup>th</sup> percentile ES-2re test dummies.

### **CAB FRONT FASCIA**

The front cab fascia shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate which shall be an integral part of the cab.

The cab fascia will encompass the entire front of the aluminum cab structure from the bottom of the windshield to the bottom of the cab and shall be the "Classic" design.

The front cab fascia shall include two (2) molded plastic modules on each side accommodating a total of up to four (4) Hi/Low beam headlights and two (2) turn signal lights or up to four (4) warning lights. A chrome plated molded plastic bezel shall be provided on each side around each set of four lamps.

### **FRONT GRILLE**

The front cab fascia shall include a classic box style, 304 stainless steel front grille with a Spartan logo. The grille shall measure 55.45 inches wide at the top tapering to 50.00 inches wide at the bottom X 33.06 inches high X 1.50 inches deep. The grille shall include a minimum free air intake of 750.00 square inches.

### **CAB UNDERCOAT**

There shall be a rubberized undercoating applied to the underside of the cab that provides abrasion protection, sound deadening and corrosion protection.

### **CAB SIDE DRIP RAIL**

There shall be a drip rail along the top radius of each cab side. The drip rails shall help prevent water from the cab roof running down the cab side.

### **CAB PAINT EXTERIOR**

The cab shall be painted prior to the installation of glass accessories and all other cab trim to ensure complete paint coverage and the maximum in corrosion protection of all metal surfaces.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

All metal surfaces on the entire cab shall be ground by disc to remove any surface oxidation or surface debris which may hinder the paint adhesion. Once the surface is machine ground a high quality acid etching of base primer shall be applied. Upon the application of body fillers and their preparation, the cab shall be primed with a coating designed for corrosion resistance and surface paint adhesion. The maximum thickness of the primer coat shall be 2.00 mils.

The entire cab shall then be coated with an intermediate solid or epoxy surfacing agent that is designed to fill any minor surface defects, provide an adhesive bond between the primer and the paint and improve the color and gloss retention of the color. The finish to this procedure shall be a sanding of the cab with 360 grit paper followed by sealing the seams with SEM brand seam sealer.

The cab shall then be painted the specific color designated by the customer with an acrylic urethane type system designed to retain color and resist acid rain and most atmospheric chemicals found on the fire ground or emergency scene. The paint shall have a minimum thickness of 2.00 mils, followed by a clear top coat not to exceed 2.00 mils. The entire cab shall then be baked at 180 degrees for one (1) hour to speed the curing process of the coatings.

### **CAB PAINT MANUFACTURER**

The cab shall be painted with PPG Industries paint.

### **CAB PAINT PRIMARY/LOWER COLOR**

The lower paint color shall be PPG FBCH 911662 Red.

### **CAB PAINT WARRANTY**

The cab and chassis shall be covered by a limited manufacturer paint warranty which shall be in effect for ten (10) years from the first owner's date of purchase or in service or the first 100,000 actual miles, whichever occurs first.

### **CAB PAINT INTERIOR**

The visible interior cab structure surfaces shall be painted with a Zolatone #20-72 silver gray texture finish.

### **CAB ENTRY DOORS**

The cab shall include four (4) entry doors, two (2) front doors and two (2) crew doors designed for ease of entering and egress when outfitted with an SCBA. The doors shall be constructed of extruded aluminum with a nominal thickness of 0.13 inch. The exterior skins shall be constructed of 0.13 inch aluminum plate.

The doors shall include a double rolled style automotive rubber seal around the perimeter of each door frame and door edge which ensures a weather tight fit.

All door hinges shall be hidden within flush mounted cab doors for a pleasing smooth appearance and perfect fit along each side of the cab. Each door hinge shall be piano style with a 0.38 inch pin and shall be constructed of stainless steel.

### **CAB ENTRY DOOR TYPE**

All cab entry doors shall be full length in design to fully enclose the lower cab steps.



# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **CAB INSULATION**

The cab ceiling and walls shall include 1.00 inch thick foam insulation. The insulation shall act as a barrier absorbing noise as well as assisting in sustaining the desired climate within the cab interior.

### **LH EXTERIOR REAR COMPARTMENT**

The cab shall offer an exterior compartment on the left side of the cab behind the rear door. The compartment opening shall be 17.00 inches wide X 21.19 inches high. The compartment size shall be 17.34 inches wide X 21.19 inches high X 21.19 inches deep. The compartment shall have a 16.63 inch wide, 84.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a bright aluminum tread plate inner panel and a bent D-ring slam latch. The door shall open towards the rear of the cab. There shall be a switch to activate a light inside the compartment and the open compartment warning light in the cab in the event the door is left ajar.

### **LEFT HAND EXTERIOR REAR COMPARTMENT LIGHTING**

There shall be one (1) On-Scene brand Night Axe LED strip light installed to illuminate the exterior rear compartment on the left side of the cab. The strip light shall be 9.00 inches long and shall include six (6) bright white LEDs.

### **LH EXTERIOR COMPARTMENT INTERIOR FINISH**

The interior of the left hand exterior compartment shall have a Zolatone #20-72 silver gray texture finish.

### **RH EXTERIOR REAR COMPARTMENT**

The cab shall offer an exterior compartment on the right side of the cab behind the rear door. The compartment opening shall be 17.00 inches wide X 21.19 inches high. The compartment size shall be 17.34 inches wide X 21.19 inches high X 21.19 inches deep. The compartment shall have a 16.63 inch wide, 84.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a bright aluminum tread plate inner panel and a bent D-ring slam latch. The door shall open towards the rear of the cab. There shall be a switch to activate a light inside the compartment and the open compartment warning light in the cab in the event the door is left ajar.

### **RIGHT HAND EXTERIOR REAR COMPARTMENT LIGHTING**

There shall be one (1) On-Scene brand Night Axe LED strip light installed to illuminate the exterior rear compartment on the right side of the cab. The strip light shall be 9.00 inches in length and shall include six (6) bright white LEDs.

### **RH EXTERIOR COMPARTMENT INTERIOR FINISH**

The interior of the right hand exterior compartment shall have a Zolatone #20-72 silver gray texture finish.

### **CAB STRUCTURAL WARRANTY**

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN CHASSIS, INC. LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The cab structure shall be warranted for a period of ten (10) years or one hundred thousand (100,000) miles which ever may occur first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

### **CAB TEST INFORMATION**

The cab shall have successfully completed the preload side impact, static roof load application and frontal impact without encroachment to the occupant survival space when tested in accordance with Section 4 of SAE J2420 COE Frontal Strength Evaluation Dynamic Loading Heavy Trucks, Section 5 of SAE J2422 Cab Roof Strength Evaluation Quasi –Static Loading Heavy Trucks and ECE R29 Uniform Provisions Concerning the Approval of Vehicles with regard to the Protection of the Occupants of the Cab of a Commercial Vehicles Annex 3 Paragraph 5.

The above tests have been witnessed by and attested to by an independent third party. The test results were recorded using cameras, high speed imagers, accelerometers and strain gauges. Documentation of the testing shall be provided upon request.

### **ELECTRICAL SYSTEM**

The chassis shall include a single starting electrical system which shall include a 12 volt direct current Weldon brand of multiplexing system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be color coded and shall include the circuit number and function where possible. The wiring shall be protected by 275 degree Fahrenheit minimum high temperature flame retardant loom. All nodes and sealed Deutsch connectors shall be waterproof.

### **APPARATUS WIRING PROVISION**

An apparatus wiring panel shall be installed in the center dash area behind the rocker switch panel which shall include eight (8) open circuits consisting of three (3) 20 amp, one (1) 30 amp, three (3) 10 amp, and one (1) 15 amp circuit, with relays and breakers with trigger wires which shall be routed to the rocker switch panel.

### **MULTIPLEX DISPLAY**

The multiplex electrical system shall include a Weldon Vista IV Touchscreen display which shall be located on the left side of the dash in the switch panel. The Touchscreen display shall feature a full color LCD screen. The display shall include a message bar displaying the time of day, and important messages requiring acknowledgement by the user. There shall be virtual controls for the on-board diagnostics. The display screen shall be video ready for back- up cameras, thermal cameras, and DVD. A DIN type input connector ready for GPS interfacing shall be incorporated into the back of the display.

The Touchscreen display shall measure approximately 6.25 inches wide x 3.38 inches in height. The display shall offer varying fonts and background colors. The display shall be fully programmable to the needs of the customer and shall offer virtually infinite flexibility for screen configuration options.

### **DATA RECORDING SYSTEM**

The chassis shall have a Weldon Vehicle Data Recorder (VDR) system installed. The system shall be designed to meet NFPA 1901 and shall be integrated with the Weldon Multiplex electrical system. The following information shall be recorded:

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- Vehicle Speed
- Acceleration
- Deceleration
- Engine Speed
- Engine Throttle Position
- ABS Event
- Seat Occupied Status
- Seat Belt Status
- Master Optical Warning Device Switch Position
- Time
- Date

Each portion of the data shall be recorded at the specified intervals and stored for the specified length of time to meet NFPA 1901 guidelines and shall be retrievable by connecting a laptop computer to the VDR system.

### **ACCESSORY POWER**

The electrical distribution panel shall include two (2) power studs. The studs shall be size #10 and each of the power studs shall be circuit protected with a fuse of the specified amperage. One (1) power stud shall be capable of carrying up to a 40 amp battery direct load. One (1) power stud shall be capable of carrying up to a 15 amp ignition switched load. The two (2) power studs shall share one (1) #10 ground stud. A 225 amp battery direct power and ground stud shall be provided and installed on the chassis near the left hand battery box for OEM body connections.

### **EXTERIOR ELECTRICAL TERMINAL COATING**

All terminals exposed to the elements will be sprayed with a high visibility protective rubberized coating to prevent corrosion.

### **ENGINE**

The chassis engine shall be a Cummins ISX15 engine. The ISX15 engine shall be an in-line six (6) cylinder, four cycle diesel powered engine. The engine shall offer a rating of 550 horse power at 1800 RPM and shall be governed at 2100 RPM. The torque rating shall feature 1850 foot pounds of torque at 1200 RPM with 912 cubic inches (14.9 liter) of displacement.

The ISX15 engine shall feature a VGT™ Turbocharger, a high pressure common rail fuel system, fully integrated electronic controls with an electronic governor, and shall be EPA certified to meet the 2013 emissions standards using cooled exhaust gas recirculation and selective catalytic reduction technology.

The engine shall include an engine mounted combination full flow/by-pass oil filter with replaceable spin on cartridge for use with the engine lubrication system. The engine shall include Citgo brand Citgard 500, or equivalent SAE 15W40 CJ4 low ash engine oil which shall be utilized for proper engine lubrication.

A wiring harness shall be supplied ending at the back of the cab. The harness shall include a connector which shall allow an optional harness for the pump panel. The included circuits shall be provided for a tachometer, oil pressure, engine temperature, hand throttle, high idle and a PSG system. A circuit for J1939 data link shall also be provided at the back of the cab.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **CAB ENGINE TUNNEL**

The cab interior shall include an integrated engine tunnel constructed of 5052-H32 Marine Grade 0.19 of an inch thick aluminum alloy plate. The tunnel shall be a maximum of 46.50 inches wide X 29.00 inches high.

### **DIESEL PARTICULATE FILTER CONTROLS**

There shall be two (2) controls for the diesel particulate filter. One (1) control shall be for regeneration and one (1) control shall be for regeneration inhibit.

### **ENGINE PROGRAMMING HIGH IDLE SPEED**

The engine high idle control shall maintain the engine idle at approximately 1250 RPM when engaged.

### **ENGINE HIGH IDLE CONTROL**

The vehicle shall be equipped with an automatic high-idle speed control. It shall be pre-set so when activated, it will operate the engine at the appropriate RPM to increase alternator output. This device shall operate only when the master switch is activated and the transmission is in neutral with the parking brake set. The device shall disengage when the operator depresses the brake pedal, or the transmission is placed in gear, and shall be available to manually or automatically re-engage when the brake is released, or when the transmission is placed in neutral. There shall be an indicator on the Vista display and control screen for the high idle speed control.

### **ENGINE PROGRAMMING ROAD SPEED GOVERNOR**

The engine shall include programming which will govern the top speed of the vehicle.

### **AUXILIARY ENGINE BRAKE**

A compression brake, for the six (6) cylinder engine shall be provided. A cutout relay shall be installed to disable the compression brake when in pump mode or when an ABS event occurs. The engine compression brake shall activate upon 0% accelerator when in operation mode and actuate the vehicle's brake lights.

The engine shall utilize a variable geometry turbo (VGT) as an integrated auxiliary engine brake to offer a variable rate of exhaust flow, which when activated in conjunction with the compression brake shall enhance the engine's compression braking capabilities.

### **AUXILIARY ENGINE BRAKE CONTROL**

An engine compression brake control device shall be included. The electronic control device shall monitor various conditions and shall activate the engine brake only if all of the following conditions are simultaneously detected:

- A valid gear ratio is detected.
- The driver has requested or enabled engine compression brake operation.
- The throttle is at a minimum engine speed position.
- The electronic controller is not presently attempting to execute an electronically controlled final drive gear shift.

The compression brake shall be controlled via an off/low/high virtual button through the Vista display and control screen. The multiplex system shall remember and default to the last engine brake control setting when the vehicle is shut off and re-started.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **FLUID FILLS**

The engine oil, coolant, transmission, and power steering fluid fills shall be located under the cab. The engine tunnel shall include an access door to allow for engine oil and power steering fluid visual checks. The windshield washer fill shall be accessible through the front left side mid step.

### **ENGINE DRAIN PLUG**

The engine shall include an original equipment manufacturer installed magnetic oil drain plug.

### **ENGINE WARRANTY**

The Cummins engine shall be warranted for a period of five (5) years or 100,000 miles, whichever occurs first.

### **REMOTE THROTTLE HARNESS**

An apparatus interface wiring harness for the engine shall be supplied with the chassis. The harness shall include a connector for connection to the chassis harness which shall terminate in the left frame rail behind the cab for reconnection by the apparatus builder. The harness shall contain connectors for a FRC Pump Boss pressure governor and a multiplexed gauge. Separate circuits shall be included for pump controls, "Pump Engaged" and "OK to Pump" indicator lights, open compartment ground, start signal, park brake ground, ignition signal, master power, customer ignition, air horn solenoid switch, high idle switch and high idle indication light. The harness shall be designed for a side mount pump panel.

An apparatus interface wiring harness shall also be included which shall be wired to the cab harness interface connectors and shall incorporate circuits with relays to control pump functions. This harness shall control the inputs for the transmission lock up circuits, governor/hand throttle controls and dash display which shall incorporate "Pump Engaged" and "OK to Pump" indicator lights. The harness shall contain circuits for the apparatus builder to wire in a pump switch.

### **ENGINE PROGRAMMING REMOTE THROTTLE**

The engine ECM (Electronic Control Module) discreet wire remote throttle circuit shall be turned off for use with a J1939 based pump controller or when the discreet wire remote throttle controls are not required.

### **ENGINE PROGRAMMING IDLE SPEED**

The engine low idle speed will be programmed at 700 rpm.

### **ENGINE FAN DRIVE**

The engine cooling system fan shall incorporate a thermostatically controlled, Horton clutched type fan drive. The clutch fan shall automatically engage in pump mode.

When the clutched fan is disengaged it shall facilitate improved vehicle performance, cab heating in cold climates, and fuel economy. The fan clutch design shall be fail safe so that if the clutch drive fails the fan shall engage to prevent engine overheating due to the fan clutch failure.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **ENGINE COOLING SYSTEM**

There shall be a heavy-duty aluminum cooling system designed to meet the demands of the emergency response industry. The cooling system shall have the capacity to keep the engine properly cooled under all conditions of road and pumping operations. The cooling system shall be designed and tested to meet or exceed the requirements specified by the engine and transmission manufacturer and all EPA requirements. The complete cooling system shall be mounted to isolate the entire system from vibration or stress. The individual cores of the cooling system shall be mounted in a manner to allow expansion and contraction at various rates without inducing stress into the adjoining cores.

The cooling system shall be comprised of a charge air cooler to radiator serial flow package that provides the maximum cooling capacity for the specified engine as well as serviceability. The main components shall include a surge tank, a charge air cooler bolted to the front of the radiator, recirculation shields, a shroud, a fan, and required tubing.

The radiator shall be a down-flow design constructed with aluminum cores, plastic end tanks, and a steel frame. The radiator shall be equipped with a drain cock to drain the coolant for serviceability.

The cooling system shall include a one piece injected molded polymer eleven (11) blade fan with a fiberglass fan shroud.

The cooling system shall be equipped with a surge tank that is capable of removing entrained air from the system. The surge tank shall be equipped with a low coolant probe and sight glass to monitor the level of the coolant. The surge tank shall have a dual seal cap that meets the engine manufacturer's pressure requirements, and allows for expansion and recovery of coolant into a separate integral expansion chamber.

All radiator tubes shall be formed from aluminized steel tubing. Recirculation shields shall be installed where required to prevent heated air from reentering the cooling package and affecting performance.

The charge air cooler shall be a cross-flow design constructed completely of aluminum with cast tanks. All charge air cooler tubes shall be formed from aluminized steel tubing and installed with silicone hump hoses and stainless steel "constant torque" style clamps meeting the engine manufacturer's requirements.

### **ENGINE COOLING SYSTEM PROTECTION**

The engine cooling system shall include a recirculation shield designed to act as a light duty skid plate below the radiator to provide additional protection for the engine cooling system from light impacts, stones, and road debris. The skid plate shall be painted to match the frame color.

### **ENGINE COOLANT**

The cooling package shall include Extended Life Coolant (ELC). The use of ELC provides longer intervals between coolant changes over standard coolants providing improved performance. The coolant shall contain a 50/50 mix of ethylene glycol and de-ionized water to keep the coolant from freezing to a temperature of -34 degrees Fahrenheit.

Proposals offering supplemental coolant additives (SCA) shall not be considered, as this is part of the extended life coolant makeup.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **ENGINE COOLANT FILTER**

An engine coolant filter with a shut-off valve for the inlet and outlet shall be installed on the chassis. The location of the filter shall allow for easy maintenance.

Proposals offering engines equipped with coolant filters shall be supplied with standard non-chemical type particulate filters.

### **ELECTRONIC COOLANT LEVEL INDICATOR**

The instrument panel shall feature a low engine coolant indicator light which shall be located in the center of the instrument panel. An audible tone alarm shall also be provided to warn of a low coolant incident.

### **ENGINE PUMP HEAT EXCHANGER**

A single bundle type coolant to water heat exchanger shall be installed between the engine and the radiator. The heat exchanger shall be designed to prohibit water from the pump from coming in contact with the engine coolant. This shall allow the use of water from the discharge side of the pump to assist in cooling the engine.

### **COOLANT HOSES**

The cooling system hoses shall be silicone heater hose with rubber hoses in the cab interior. The radiator hoses shall be formed silicone coolant hoses with formed aluminized steel tubing. All heater hose, silicone coolant hose, and tubing shall be secured with stainless steel constant torque band clamps.

### **ENGINE AIR INTAKE**

The engine air intake system shall include an ember separator air intake filter which shall be located in the front of the cab behind the right hand side fascia. This filter shall protect the downstream air filter from embers using a combination of unique flat and crimped metal screens constructed into a corrosion resistant steel frame. This multilayered screen shall be designed to trap embers or allow them to burn out before passing through the pack, while creating only minimal air flow restriction through the system. Periodic cleaning or replacement of the screen shall be all that is required after installation.

The engine shall also include an air intake filter which shall be bolted to the frame and located under the front of the cab on the right hand side. The system shall utilize a replaceable dry type filter which ensures dust and debris remains safely contained inside the housing during operation via leak-tight seals. The service cover shall be located on the bottom of the housing, eliminating the chance of contaminating the air intake system during air filter service.

The air flow distribution and dust loading shall be uniform throughout the high-performance filter element, which shall result in pressure differential for improved horsepower and fuel economy. The air intake ember separator shall be mounted within easy access via a hinged panel behind the right hand side headlight module. The air intake system shall include a restriction indicator light in the warning light cluster on the instrument panel, which shall activate when the air cleaner element requires replacement.

### **AIR INTAKE PROTECTION**

A light duty skid plate shall be supplied for the engine air intake system below the right front side of the cab. The skid plate shall provide protection for the air intake system from light impacts, stones, and road debris.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **ENGINE EXHAUST SYSTEM**

The exhaust system shall include a diesel particulate filter (DPF), a diesel oxidation catalyst, and a selective catalytic reduction (SCR) catalyst to meet current EPA standards. The selective catalytic reduction catalyst utilizes a diesel exhaust fluid solution consisting of urea and purified water to convert NOx into nitrogen, water, and trace amounts of carbon dioxide. The solution shall be injected into the system through the decomposition tube between the DPF and SCR.

The system shall utilize 0.07 inch thick stainless steel exhaust tubing between the engine turbo and the DPF. Zero leak clamps seal all system joints between the turbo and DPF.

The DPF, the decomposition tube, and the SCR canister through the end of the tailpipe shall be connected with zero leak clamps. The discharge shall terminate horizontally on the right side of the vehicle ahead of the rear tires.

The exhaust system shall be mounted below the frame in the outboard position with the SCR canister in line rearward of the DPF.

### **DIESEL EXHAUST FLUID TANK**

The exhaust system shall include a molded cross linked polyethylene tank for Diesel Exhaust Fluid (DEF). The tank shall have a capacity of six (6) usable gallons and shall be mounted on the left hand side of the chassis frame behind the batteries below the frame.

The DEF tank shall be designed with capacity for expansion in case of fluid freezing. Engine coolant, which shall be thermostatically controlled, shall be run through lines in the tank to help prevent the DEF from freezing and to provide a means of thawing the fluid if it should become frozen.

The tank fill tube shall be routed under the rear of the cab with the fill neck and splash guard accessible in the top rear step.

### **ENGINE EXHAUST ACCESSORIES**

An exhaust temperature mitigation device shall be shipped loose for installation by the body manufacturer on the vehicle. The temperature mitigation device shall lower the temperature of the exhaust by combining ambient air with the exhaust gasses at the exhaust outlet.

### **ENGINE EXHAUST WRAP**

The exhaust tubing between the engine turbo and the diesel particulate filter (DPF) shall be wrapped with a thermal cover in order to retain the necessary heat for DPF regeneration. The exhaust wrap shall also help protect surrounding components from radiant heat which can be transferred from the exhaust.

### **TRANSMISSION**

The drive train shall include an Allison model EVS 4000 torque converting, automatic transmission which shall include electronic controls and an output retarder. The transmission shall feature two (2) 10-bolt PTO pads located on the converter housing.



# GREELEY FIRE DEPT

SVI #930

## Production Specs

The transmission shall include two (2) internal oil filters which shall offer Castrol TranSynd™ synthetic TES 295 transmission fluid which shall be utilized in the lubrication of the EVS transmission. An electronic oil level sensor shall be included with the readout located in the shift selector.

The transmission gear ratios shall be:

1st	3.51:1
2nd	1.91:1
3rd	1.43:1
4th	1.00:1
5th	0.74:1
6th	0.64:1 (if applicable)
Rev	4.80:1

### **TRANSMISSION MODE PROGRAMMING**

The transmission, upon start-up, will automatically select a four (4) speed operation. The fifth speed over drive shall be available with the activation of the mode button on the shifting pad.

### **TRANSMISSION FEATURE PROGRAMMING**

The Allison Gen V-E transmission EVS group package number 127 shall contain the 198 vocational package in consideration of the duty of this apparatus as a pumper. This package shall incorporate an automatic neutral with selector override. This feature commands the transmission to neutral when the park brake is applied, regardless of drive range requested on the shift selector. This requires re-selecting drive range to shift out of neutral for the override.

This package shall be coupled with the use of a split shaft PTO and incorporate pumping circuits. These circuits shall be used allowing the vehicle to operate in the fourth range lockup while operating the pump mode due to the 1 to 1 ratio through the transmission, therefore the output speed of the engine is the input speed to the pump. The pump output can be easily calculated by using this input speed and the drive ratio of the pump itself to rate the gallons of water the pump can provide.

A transmission interface connector shall be provided in the cab. This package shall contain the following input/output circuits to the transmission control module. The Gen V-E transmission shall include prognostic diagnostic capabilities. These capabilities shall include the monitoring of the fluid life, filter change indication, and transmission clutch maintenance.

<u>Function ID</u>	<u>Description</u>	<u>Wire assignment</u>
Inputs		
C	PTO Request	142
J	Fire Truck Pump Mode (4th Lockup)	122 / 123
Outputs		
C	Range Indicator	145 (4th)
G	PTO Enable Output	130
	Signal Return	103

### **ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR**

The transmission fluid shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal.

# GREELEY FIRE DEPT

SVI #930

Production Specs

## **TRANSMISSION SHIFT SELECTOR**

An Allison pressure sensitive range selector touch pad shall be provided and located to the right of the driver within clear view and easy reach. The shift selector shall have a graphical Vacuum Florescent Display (VFD) capable of displaying two lines of text. The shift selector shall provide mode indication and a prognostic indicator (wrench symbol) on the digital display. The prognostics monitor various operating parameters and shall alert you when a specific maintenance function is required.

## **TRANSMISSION RETARDER CONTROL**

The Allison transmission retarder shall be engaged with the first one-third at 0% throttle and the remaining two-thirds shall be modulated by brake pedal actuation. The system shall include a retarder on/off rocker switch mounted on the dash. The engagement of the retarder shall activate the brake lights. The retarder shall be inactive during pump mode.

## **TRANSMISSION RETARDER CAPACITY LEVEL**

The transmission retarder shall be programmed so the maximum retardation shall be at the high capacity level.

## **TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE**

When the auxiliary brake is engaged, the transmission shall automatically shift to second gear to decrease the rate of speed assisting the secondary braking system and slowing the vehicle.

## **TRANSMISSION COOLING SYSTEM**

The transmission shall include a water to oil cooler system located in the cooling loop between the radiator and the engine. The transmission cooling system shall meet all transmission manufacturer requirements. The transmission cooling system shall feature continuous flow of engine bypass water to maintain uninterrupted transmission cooling.

## **TRANSMISSION DRAIN PLUG**

The transmission shall include an original equipment manufacturer installed magnetic transmission fluid drain plug.

## **TRANSMISSION WARRANTY**

The Allison EVS series transmission shall be warranted for a period of five (5) years with unlimited mileage. Parts and labor shall be included in the warranty.

## **LH PTO**

A PTO shall be installed on the transmission by the OEM.

## **LH PTO MODEL**

A ten (10) bolt Chelsea model 859-XGFJP-B5XV heavy duty transmission driven PTO shall be installed. The clutched shifted PTO is designed specifically for the Allison world transmission and provides torque ranges from 250 to 335 lb. ft.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### PTO LOCATION

The transmission shall have two (2) power take off (PTO) mounting locations, one (1) in the 8:00 o'clock position and one (1) in the 1:00 o'clock position.

### DRIVELINE

All drivelines shall be heavy duty metal tube and equipped with Spicer 1810 series universal joints. The shafts shall be dynamically balanced prior to installation to alleviate future vibration. In areas of the driveline where a slip shaft is required, the splined slip joint shall be coated with Glide Coat®.

### DRIVELINE GUARDS

One (1) driveline guard loop shall be provided and installed to support the driveline shaft for routine maintenance and in the event of a driveline component failure.

### MIDSHIP PUMP / GEARBOX

A temporary jackshaft driveline shall be installed by the chassis manufacturer to accommodate the mid-ship split shaft pump as specified by the apparatus manufacturer.

### MIDSHIP PUMP / GEARBOX MODEL

The midship pump/gearbox provisions shall be for a Waterous CMUC20 pump.

### MIDSHIP PUMP GEARBOX DROP

The Waterous pump gearbox shall have a "C" (medium length) drop length.

### MIDSHIP PUMP RATIO

The ratio for the midship pump shall be 2.27:1.

### MIDSHIP PUMP LOCATION C/L SUCTION TO C/L REAR AXLE

The midship pump shall be located so the dimension from the centerline of the suction to the centerline of the rear axle is 95.00 inches.

### PUMP SHIFT CONTROLS

One (1) air pump shift control panel shall be mounted in the lower left section of the center dash panel. The following shall be provided on the panel: a three (3) position control lever; an engraved PUMP ENGAGED identification light; and an engraved OK TO PUMP identification light. The pump shift control panel shall be black with a yellow border outline and shall include pump instructions. An instruction plate describing the transmission shift selector position used for pumping shall be provided and located so it can be read from the driver's position per NFPA 16.10.1.3. **The pump mode shall be selected when the control lever is in the "DOWN" position and road mode shall be selected when the control lever is in the "UP" position.**

The control lever center position shall exhaust air from both pump and road sides of the pump gear box shift cylinder.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **PUMP SHIFT CONTROL PLUMBING**

Air connections shall be provided from the air supply tank to the pump shift control valve and from the pump shift control valve to the frame mounted bracket. The frame mounted bracket shall include labeling identifying the pump and road connection points with threaded 0.38 NPT fittings for attaching the customer installed pump. The air supply shall be pressure protected from service brake system.

### **FUEL FILTER/WATER SEPARATOR**

The fuel system shall have a Racor S3238 fuel filter/water separator as a primary filter. The fuel filter shall have a drain valve and a see through cover to allow visual inspection of fuel and filter condition. The Racor S3238 shall be a 10 micron filter capable of handling a maximum flow rate of 150 gallons per hour.

A secondary fuel filter shall be included as approved by the engine manufacturer.

An instrument panel lamp and audible alarm which indicates when water is present in the fuel-water separator shall also be included.

### **FUEL LINES**

The fuel system supply and return lines installed from the fuel tank to the engine shall be black textile braided lines which are reinforced with braided high tensile steel wire. The fuel lines shall be connected with reusable steel fittings.

### **FUEL SHUTOFF VALVE**

A fuel shutoff valve shall be installed in the fuel draw line at the primary fuel filter to allow the fuel filter to be changed without loss of fuel to the fuel pump.

A second fuel shutoff valve shall be installed in the fuel draw line, near the fuel tank to allow maintenance to be performed with minimal loss of fuel.

### **ELECTRIC FUEL PRIMER**

Integral to the engine assembly is an electric lift pump that serves the purpose of pre-filter fuel priming.

### **FUEL COOLER**

An aluminum cross flow air to fuel cooler shall be provided to lower fuel temperature allowing the vehicle to operate at higher ambient temperatures. The fuel cooler shall be located above the fuel tank.

### **FUEL TANK**

The fuel tank shall have a capacity of sixty-eight (68) gallons and shall measure 35.00 inches in width X 17.00 inches in height X 29.00 inches in length. The baffled tank shall be made of 14 gauge aluminized steel. The exterior of the tank shall be painted with a PRP Corsol™ black anti-corrosive exterior metal treatment finish. This results in a tank which offers the internal and external corrosion resistance.

The tank shall have a vent port to facilitate venting to the top of the fill neck for rapid filling without "blow-back" and a roll over ball check vent for temperature related fuel expansion and draw.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The tank is designed with dual draw tubes and sender flanges. The tank shall have 2.00 inch NPT fill ports for right or left hand fill. A 0.50 inch NPT drain plug shall be centered in the bottom of the tank.

The fuel tank shall be mounted below the frame, behind the rear axle. Two (2) three-piece strap hanger assemblies with "U" straps bolted midway on the fuel tank front and rear shall be utilized to allow the tank to be easily lowered and removed for service purposes. Rubber isolating pads shall be provided between the tank and the upper tank mounting brackets. Strap mounting studs through the rail, hidden behind the body shall not be acceptable.

### **FUEL TANK MATERIAL AND FINISH**

The fuel tank shall be constructed of 14 gauge aluminized steel. The exterior of the fuel tank shall be painted to match the frame color.

### **FUEL TANK STRAP MATERIAL**

The fuel tank straps shall be constructed of ASTM A-36 steel.

### **FUEL TANK FILL PORT**

The fuel tank fill ports shall be provided with two (2) left fill ports located one (1) in the forward position and one (1) in the middle position and the right fill port located in the middle position of the fuel tank.

### **FUEL TANK DRAIN PLUG**

A 0.5 inch NPT drain plug shall be centered in the bottom of the fuel tank.

### **FRONT AXLE**

The front axle shall include an independent front suspension (IFS) offering superior ride and improved handling.

The suspension shall utilize fully independent double wishbone arms with carrier and kingpin for optimized scrub radius. Air springs are tuned for ride and help reduce suspension weight. The IFS reduces turn radius with improved wheel cut over beam axles. The hydraulic damper shall feature rebound control to ensure the maximum load stability and superior driver comfort. The IFS system shall improve handling and offer better braking because of improved ground to tire ratio. This design shall allow for independent adjustment of the vehicle's alignment settings. The IFS shall include an auxiliary transverse leaf spring.

Proposals offering independent front axles comprised of torsion bar style suspensions shall not be considered.

### **FRONT AXLE WARRANTY**

The front axle shall be warranted by Tuthill for three (3) years or 150,000 miles, which ever comes first. Details of the Tuthill warranty are provided on the PDF document attached to this option.

### **FRONT WHEEL BEARING LUBRICATION**

The front axle wheel bearings shall be lubricated with oil. The oil level can be visually checked via clear inspection windows in the front axle hubs.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **FRONT SHOCK ABSORBERS**

Two (2) Koni shock absorbers shall be provided and installed as part of the front suspension system. The Koni shock absorbers shall be adjustable, providing as much or as little compensation as needed. Each shock shall deliver improved road handling and durability.

### **FRONT SUSPENSION**

The chassis shall include an independent front suspension (IFS) system. The known advantages of IFS systems can be improved handling and better braking due to the increase in tire surface to ground contact area. The suspension travel of the IFS shall be approximately 6.50 inches, providing 3.00 inches bounce and 3.50 inches rebound of the suspension. The IFS front axle shall be rated between 21,000 and 24,000 pounds.

### **STEERING COLUMN/ WHEEL**

The cab shall include a Douglas Autotech steering column which shall include a seven (7) position tilt, a 2.25 inch telescopic adjustment, and an 18.00 inch, four (4) spoke steering wheel located at the driver's position. The steering wheel shall be covered with black polyurethane foam padding.

The steering column shall contain a horn button, self-canceling turn signal switch, four-way hazard switch and headlamp dimmer switch.

### **ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR**

The power steering fluid shall be monitored electronically and shall send a signal to activate an audible alarm and visual warning in the instrument panel when fluid level falls below normal.

### **POWER STEERING PUMP**

The hydraulic power steering pump shall be a TRW PS and shall be gear driven from the engine. The pump shall be a balanced, positive displacement, sliding vane type.

### **FRONT AXLE CRAMP ANGLE**

The chassis shall have a front axle cramp angle of 48-degrees to the left and right.

### **POWER STEERING GEAR**

The power steering gear shall be a TRW model TAS 85/RCS 85.

### **CHASSIS ALIGNMENT**

The chassis frame rails shall be measured to insure the length is correct and cross checked to make sure they run parallel and are square to each other. The front and rear axles shall be laser aligned. The front tires and wheels shall be aligned and toe-in set on the front tires by the chassis manufacturer.

### **REAR AXLE**

The rear axle shall be a Meritor model RS-23-186 single drive axle. The axle shall include precision forged, single reduction differential gearing, and shall have a fire service rated capacity of 24,000 pounds.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The axle shall be built of superior construction and quality components to provide the rugged dependability needed to stand up to the fire industry's demands. The axle shall include rectangular shaped, hot-formed housing with a standard wall thickness of 0.50 of an inch for extra strength and rigidity and a rigid differential case for high axle strength and reduced maintenance.

The axle shall have heavy-duty Hypoid gearing for longer life, greater strength and quieter operation. Industry-standard wheel ends for compatibility with both disc and drum brakes, and unitized oil seal technology to keep lubricant in and help prevent contaminant damage will be used.

### **REAR AXLE DIFFERENTIAL LUBRICATION**

The rear axle differential shall be lubricated with oil.

### **REAR AXLE WARRANTY**

The rear axle shall be warranted by Meritor for two (2) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

### **REAR WHEEL BEARING LUBRICATION**

The rear axle wheel bearings shall be lubricated with oil.

### **VEHICLE TOP SPEED**

The top speed of the vehicle shall be approximately 68 MPH +/-2 MPH at governed engine RPM.

### **REAR SUSPENSION**

The single rear axle shall feature a Hendrickson Firemaax™ air suspension. The suspension shall include two optimized air springs mounted to cast structural trailing arms, a transverse cross beam for increased roll stability and two heavy duty shock absorbers. Dual air height control valves shall be installed to ensure equal frame height on both sides of the vehicle regardless of the load. Axle alignment is maintained using two eccentric bushings at each frame bracket.

The rear suspension capacity shall be rated at 24,000 pounds.

### **REAR SHOCK ABSORBERS**

Shock absorbers shall be supplied by the suspension manufacturer and installed on the rear axle suspension.

### **FRONT TIRE**

The front tires shall be Michelin 425/65R22.5 "L" tubeless radial XFE regional tread.

The front tire stamped load capacity shall be 22,800 pounds per axle with a speed rating of 65 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Tire Intermittent Service Rating load capacity shall be 24,400 pounds per axle with a speed rating of up to 75 miles per hour when properly inflated to 120 pounds per square inch. The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to one (1) hour of loaded travel with a one (1) hour cool down prior to another loaded run.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **REAR TIRE**

The rear tires shall be Michelin 11R-22.5 16PR "H" tubeless radial XDN2 all-weather tread designed for exceptional traction and mileage.

The rear tire stamped load capacity shall be 24,020 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Tire Intermittent Service Rating load capacity shall be 24,820 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch. The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to one (1) hour of loaded travel with a one (1) hour cool down prior to another loaded run.

### **REAR AXLE RATIO**

The rear axle ratio shall be 4.89:1.

### **TIRE PRESSURE INDICATOR**

There shall be a voucher provided with the chassis for a pop up style tire pressure indicator at each tire valve stem. The indicator shall provide visual indication of pressure in the specific tire.

The tire pressure indicators shall be redeemed upon the vehicle manufacturer's receipt of the voucher for installation by the customer.

### **FRONT WHEEL**

The front wheels shall be Alcoa hub piloted, 22.50 inch X 12.25 inch LvL One™ polished aluminum wheels. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts. The wheels shall feature one-piece forged strength and shall include Alcoa's Dura-Bright® finish with XBR technology as an integral part of the wheel surface. Alcoa Dura-Bright® wheels keep their shine without polishing. Brake dust, grime and road debris are easily removed by simply cleaning the wheels with soap and water.

### **REAR WHEEL**

The rear wheels shall be Alcoa hub piloted, 22.50 inch X 8.25 inch LvL One™ aluminum wheels with a polished outer surface and Alcoa Dura-Bright® wheel treatment with XBR® technology as an integral part of the wheel. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

### **WHEEL TRIM**

The front wheels shall include stainless steel lug nut covers and stainless steel baby moons shipped loose with the chassis for installation by the apparatus builder. The baby moons shall have cutouts for oil seal viewing when applicable.

The rear wheels shall include stainless steel lug nut covers and band mounted spring clip stainless steel high hats shipped loose with the chassis for installation by the apparatus builder.



# GREELEY FIRE DEPT

SVI #930

## Production Specs

The lug nut covers, baby moons, and high hats shall be RealWheels® brand constructed of 304L grade, non-corrosive stainless steel with a mirror finish. Each wheel trim component shall meet D.O.T. certification.

### **TIRE CHAINS**

Insta-Chains, six (6) strand automatic ice chains shall be installed on the rear axle of the chassis to provide instant traction on ice and snow at speeds below 35 MPH.

### **TIRE CHAINS ACTIVATION**

The tire chain system shall be activated by a virtual button on the Vista display and control screen. The virtual button shall display "Active" when the tire chains are engaged. The tire chains shall be interlocked with the transmission and shall engage only if the vehicle is traveling 30 MPH or less. After traveling over 30 MPH, the vehicle must be reduced to a speed below 5 MPH for the tire chains to be engaged or re-engaged. The virtual button, once the vehicle reaches 35 MPH shall be reset to "Inactive". The vehicle must then reduce to a speed below 5 MPH to enable the tire chains virtual button.

### **BRAKE SYSTEM**

A rapid build-up air brake system shall be provided. The air brakes shall include a two (2) air tank, three (3) reservoir system with a total of 4152 cubic inch of air capacity. A floor mounted treadle valve shall be mounted inside the cab for graduated control of applying and releasing the brakes. An inversion valve shall be installed to provide a service brake application in the unlikely event of primary air supply loss. All air reservoirs provided on the chassis shall be labeled for identification.

The rear axle spring brakes shall automatically apply in any situation when the air pressure falls below 25 PSI and shall include a mechanical means for releasing the spring brakes when necessary. An audible alarm shall designate when the system air pressure is below 60 PSI.

A four (4) sensor, four (4) modulator anti-lock braking system (ABS) shall be installed on the front and rear axles in order to prevent the brakes from locking or skidding while braking during hard stops or on icy or wet surfaces. This in turn shall allow the driver to maintain steering control under heavy braking and in most instances, shorten the braking distance. The electronic monitoring system shall incorporate diagonal circuitry which shall monitor wheel speed during braking through a sensor and tone ring on each wheel. A dash mounted ABS lamp shall be provided to notify the driver of a system malfunction. The ABS system shall automatically disengage the auxiliary braking system device when required. The speedometer screen shall be capable of reporting all active defaults using PID/SID and FMI standards.

Additional safety shall be accommodated through Automatic Traction Control (ATC) which shall be installed on the single rear axle. The ATC system shall apply the ABS when the drive wheels loose traction. The system shall scale the electronic engine throttle back to prevent wheel spin while accelerating on ice or wet surfaces.

A momentary rocker style switch shall be provided and properly labeled "mud/snow". When the switch is pressed once, the system shall allow a momentary wheel slip to obtain traction under extreme mud and snow conditions. During this condition the ATC light and the light on the rocker switch shall blink continuously notifying the driver of activation. Pressing the switch again shall deactivate the mud/snow feature.

The Electronic Stability Control (ESC) unit is a functional extension of the electronic braking system. It is able to detect any skidding of the vehicle about its vertical axis as well as any rollover tendency. The control unit comprises an angular-speed sensor that measures the vehicle's motion about the vertical axis, caused, for instance, by cornering or by skidding on a slippery road surface. An acceleration sensor measures the vehicle's

# GREELEY FIRE DEPT

SVI #930

## Production Specs

lateral acceleration. The Controller Area Network (CAN) bus provides information on the steering angle. On the basis of lateral acceleration and steering angle, an integrated microcontroller calculates a theoretical angular speed for the stable vehicle condition.

### **FRONT BRAKES**

The front brakes shall be Knorr/Bremse SN7 disc brakes with 17.00 inch vented rotors.

### **REAR BRAKES**

The rear brakes shall be Meritor EX225 Disc Plus disc brakes with 17.00 inch vented rotors.

### **PARK BRAKE**

Upon application of the push-pull valve in the cab, the rear brakes will engage via mechanical spring force. This is accomplished by dual chamber rear brakes, satisfying the FMVSS parking brake requirements.

### **PARK BRAKE CONTROL**

A Meritor-Wabco manual hand control push-pull style valve shall operate the parking brake system. The control shall be yellow in color.

The parking brake actuation valve shall be mounted 6.00 inches to the left of center of the dash within easy access of the driver. A guard shall be installed over the parking brake control to prevent accidental application or release.

### **AIR DRYER**

The brake system shall include a Bendix AD-9 fully self contained air dryer which shall not require an extra purge tank or additional valves. The AD-9 system shall include a spin-off desiccant filter with a 12-volt, 75-watt thermostatically controlled heating element. The air dryer shall feature 3.9 pounds of premium, high crush strength desiccant which shall be produced with a composition that shall be more effective and longer lasting than other desiccants. It shall also offer protection against contamination and desiccant breakdown. The air dryer shall be mounted behind the battery box on the left hand side.

### **FRONT BRAKE CHAMBERS**

The front brakes shall be provided with type 24 brake chambers as supplied with the independent front suspension axle.

### **REAR BRAKE CHAMBERS**

The rear axle shall include TSE 24/30 H.O.T. (High Output Technology) brake chambers shall convert the energy of compressed air into mechanical force and motion. This shall actuate the brake camshaft, which in turn shall operate the foundational brake mechanism forcing the brake pads against the brake rotor.

### **AIR COMPRESSOR**

The air compressor provided for the engine shall be a Wabco® SS318 single cylinder pass-through drive type compressor which shall be capable of producing 18.7 CFM at 1200 engine RPMs. The air compressor shall feature a higher delivery efficiency translating to more air delivery per horsepower absorbed. The compressor

# GREELEY FIRE DEPT

SVI #930

## Production Specs

shall include an aluminum cylinder head which shall improve cooling, reduce weight and decrease carbon formation. Superior piston and bore finishing technology shall reduce oil consumption and significantly increasing the system component life.

### **AIR GOVERNOR**

An air governor shall be provided to control the cut-in and cut-out pressures of the engine mounted air compressor. The governor shall be calibrated to meet FMVSS requirements. The air governor shall be located on the air dryer bracket on the left frame rail behind the battery box.

### **AUXILIARY AIR RESERVOIR**

One (1) auxiliary air reservoir with a 2084 cubic inch capacity shall be installed on the chassis to act as an additional reserve supply to the air system for air horn, air tool, or other non-service brake use. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

### **MOISTURE EJECTORS**

An automatic moisture ejector with a manual drain provision shall be installed on the wet tank of the air supply system. Manual pet-cock type drain valves shall be installed on all remaining reservoirs of the air supply system.

### **AIR SUPPLY LINES**

The air system on the chassis shall be plumbed with black textile braid covered high tensile steel reinforced wire braided hose with steel reusable fittings. All drop hoses shall be fiber reinforced neoprene covered hose.

### **AIR TANK SPACERS**

There shall be spacers included with the air tank mounting. The spacers shall move the air tanks 1.50 inches inward towards the center of the chassis. This shall provide clearance between the air tanks and the frame for body U-bolt clearance.

### **WHEELBASE**

The chassis wheelbase shall be 212.00 inches.

### **REAR OVERHANG**

The chassis rear overhang shall be 78.00 inches.

### **FRAME**

The frame shall consist of double rails running parallel to each other with cross members forming a ladder style frame. The frame rails shall be formed in the shape of a "C" channel, with the outer rail measuring 10.25 inches high X 3.50 inches deep upper and lower flanges X 0.38 inches thick with an inner channel of 9.44 inches high X 3.13 inches deep and 0.38 inches thick. Each rail shall be constructed of 110,000 psi minimum yield high strength low alloy steel. Each double rail section shall be rated by a Resistance Bending Moment (RBM) minimum of 3,213,100 inch pounds and have a minimum section modulus of 29.21 cubic inches. The frame shall measure 35.00 inches in width.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

Proposals calculating the frame strength using the "box method" shall not be considered.

Proposals including heat treated rails shall not be considered. Heat treating frame rails produces rails that are not uniform in their mechanical properties throughout the length of the rail. Rails made of high strength, low alloy steel are already at the required yield strength prior to forming the rail.

A minimum of seven (7) fully gusseted 0.25 inch thick cross members shall be installed. The inclusion of the body mounting, or bumper mounting shall not be considered as a cross member. The cross members shall be attached using zinc coated grade 8 fasteners. The bolt heads shall be flanged type, held in place by distorted thread flanged lock nuts. Each cross member shall be mounted to the frame rails utilizing a minimum of 0.25 inch thick gusset reinforcement plates at all corners balancing the area of force throughout the entire frame.

Any proposals not including additional reinforcement for each cross member shall not be considered.

All relief areas shall be cut in with a minimum 2.00 inch radius at intersection points with the edges ground to a smooth finish to prevent a stress concentration point.

The frame and cross members shall carry a lifetime warranty to the original purchaser. A copy of the frame warranty shall be made available upon request.

Proposals offering warranties for frames not including cross members shall not be considered.

### **FRAME WARRANTY**

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN CHASSIS, INC. LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The frame and cross members shall carry a limited lifetime warranty to the original purchaser. The warranty period shall commence on the date the vehicle is delivered to the first end user.

### **FRAME CLEAR AREA**

The chassis frame shall be left clear of chassis mounted components inside or outside the frame rails within the first 30.00 inches behind the cab to allow space for OEM installed components. Cross members may be installed in the clear area if required for proper frame or driveline configuration.

### **FRAME PAINT**

The frame shall be powder coated black prior to any attachment of components.

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 shall not have a fail of more than ten (10) squares. The pencil hardness test per ASTM D3363 shall have a final post-curved pencil hardness of H-2H. The direct impact resistance test per ASTM D2794 shall have an impact resistance of 120.00 inches per pound at 2 mils.

Any proposals offering painted frame with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **FRONT BUMPER**

The chassis shall be equipped with a severe duty front bumper constructed from structural steel channel. The bumper material shall be 0.38 thick ASTM A36 steel which shall measure 12.00 inches high with a 3.05 inch flange and shall be 104.50 inches wide with angled front corners.

The bumper shall be primed and painted as specified.

### **FRONT BUMPER EXTENSION LENGTH**

The front bumper shall be extended approximately 21.00 inches ahead of the cab.

### **FRONT BUMPER EXTENSION FRAME WIDTH**

The front bumper extension frame shall feature an overall width of 48.25 inches.

### **FRONT BUMPER PAINT**

The front bumper shall be painted the same as the lower cab color.

### **FRONT BUMPER APRON**

The 21.00 inch extended front bumper shall include an apron constructed of 0.19 inch thick embossed aluminum tread plate.

The apron shall be installed between the bumper and the front face of the cab affixed using stainless steel bolts attaching the apron to the top bumper flange.

### **MECHANICAL SIREN**

The front bumper shall include an electro mechanical Federal Q2B™ siren, which shall be streamlined, chrome-plated and shall produce 123 decibels of sound at 10.00 feet. The Q2B™ siren produces a distinctive warning sound that is recognizable at long distances. A unique clutch design provides a longer coast down sound while reducing the amp draw to 100 amps. The siren shall measure 10.50 inches wide X 10.00 inches high X 14.00 inches deep. The siren shall include a pedestal mount to surface mount on a horizontal surface.

### **MECHANICAL SIREN LOCATION**

The siren shall be pedestal mounted on the bumper apron on the furthest outboard section of the bumper on the driver side.

### **AIR HORN**

The front bumper shall include two (2) Hadley brand E-Tone air horns which shall measure 21.00 inches long with a 6.00 inch round flare. The air horns shall be trumpet style with a chrome finish on the exterior and a painted finish deep inside the trumpet.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **AIR HORN LOCATION**

The air horns shall be recess mounted in the front bumper face on the right side of the bumper in the inboard and outboard positions relative to the right hand frame rail.

### **AIR HORN RESERVOIR**

One (1) air reservoir, with a 1200 cubic inch capacity, shall be installed on the chassis to act as a supply tank for operating air horns. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

### **ELECTRONIC SIREN SPEAKER**

There shall be two (2) Whelen Engineering Inc. model SA314A, 100 watt speakers provided. Each speaker shall measure 6.40 inches tall X 6.17 inches wide X 3.14 inches deep. Each speaker shall have a natural cast aluminum finish and shall be installed using a polished aluminum trim ring.

### **ELECTRONIC SIREN SPEAKER LOCATION**

The two (2) electronic siren speakers shall be located on the front bumper face between the frame rails in the right and left side outboard positions.

### **FRONT BUMPER TOW EYES**

The bumper shall include two (2) chrome plated tow eyes shall be installed through the front bumper. The eyes shall be fabricated from 0.75 inch thick #1020 ASTM-A36 hot rolled steel. The inside diameter of the eye shall be 2.00 inches and include a chamfered edge.

### **CAB TILT SYSTEM**

The entire cab shall be capable of tilting approximately 45-degrees to allow for easy maintenance of the engine and transmission. The cab tilt pump assembly shall be located on the right side of the chassis above the battery box.

The electric-over-hydraulic lift system shall include an ignition interlock and red cab lock down indicator lamp on the tilt control which shall illuminate when holding the "Down" button to indicate safe road operation.

It shall be necessary to activate the master battery switch and set the parking brake in order to tilt the cab. As a third precaution the ignition switch must be turned off to complete the cab tilt interlock safety circuit.

Two (2) spring-loaded hydraulic hold down hooks located outboard of the frame shall be installed to hold the cab securely to the frame. Once the hold-down hooks are set in place, it shall take the application of pressure from the hydraulic cab tilt lift pump to release the hooks.

Two (2) cab tilt cylinders shall be provided with velocity fuses in each cylinder port. The cab tilt pivots shall be 1.90 inch ball and be anchored to frame brackets with 1.25 inch diameter studs.

A steel safety channel assembly, painted safety yellow shall be installed on the right side cab lift cylinder to prevent accidental cab lowering. The safety channel assembly shall fall over the lift cylinder when the cab is in the fully tilted position. A cable release system shall also be provided to retract the safety channel assembly from the lift cylinder to allow the lowering of the cab.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **CAB TILT AUXILIARY PUMP**

A manual cab tilt pump module shall be attached to the cab tilt pump housing.

### **CAB TILT LIMIT SWITCH**

A cab tilt limit switch shall be installed. The switch will effectively limit the travel of the cab when being tilted. The limit adjustment of the switch shall be preset by the chassis manufacturer to prevent damage to the cab or any bumper mounted option mounted in the cab tilt arc. Further adjustment to the limit by the apparatus manufacturer shall be available to accommodate additional equipment.

### **CAB TILT CONTROL RECEPTACLE**

The cab tilt control cable shall include a receptacle which shall be temporarily located on the right hand chassis rail rear of the cab to provide a place to plug in the cab tilt remote control pendant. The tilt pump shall include 8.00 feet of cable with a six (6) pin Deutsch receptacle with a cap.

The remote control pendant shall include 20.00 feet of cable with a mating Deutsch connector. The remote control pendant shall be shipped loose with the chassis.

### **CAB TILT LOCK DOWN INDICATOR**

The cab dash shall include a message located within the dual air pressure gauge which shall alert the driver when the cab is unlocked and ajar. The alert message shall cease to be displayed when the cab is in the fully lowered position and the hold down hooks are secured and locked to the cab mounts.

In addition to the alert message an audible alarm shall sound when the cab is unlocked and ajar and the parking brake is released.

### **CAB WINDSHIELD**

The cab windshield shall have a surface area of 2969.88 square inches and be of a two (2) piece wraparound design for maximum visibility.

The glass utilized for the windshield shall include standard automotive tint. The left and right windshield shall be fully interchangeable thereby minimizing stocking and replacement costs.

Each windshield shall be installed using black self locking window rubber.

### **GLASS FRONT DOOR**

The front cab doors shall include a window which is 27.00 inches in width X 26.00 inches in height. These windows shall have the capability to roll down completely into the door housing. This shall be accomplished using electric actuation. The left and right front door windows shall be controlled using a switch on each respective side inner door panel. The driver's door shall include a switch for each powered door window in the cab.

There shall be an irregular shaped fixed window which shall measure 2.50 inches wide at the top, 8.00 inches wide at the bottom X 26.00 inches in height, more commonly known as "cozy glass" ahead of the front door roll down windows.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The windows shall be mounted within the frame of the front doors trimmed with a black anodized ring on the exterior.

### **GLASS TINT FRONT DOOR**

The windows located in the left and right front doors shall have a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

### **GLASS REAR DOOR RH**

The rear right hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the inner door panel and on the driver's control panel.

### **GLASS TINT REAR DOOR RIGHT HAND**

The window located in the right hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

### **GLASS REAR DOOR LH**

The rear left hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the inner door panel and on the driver's control panel.

### **GLASS TINT REAR DOOR LEFT HAND**

The window located in the left hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

### **GLASS SIDE MID RH**

The cab shall include a window on the right side behind the front and ahead of the crew door which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

### **GLASS TINT SIDE MID RIGHT HAND**

The window located on the right hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

### **GLASS SIDE MID LH**

The cab shall include a window on the left side behind the front door and ahead of the crew door and above the wheel well which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.



# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **GLASS TINT SIDE MID LEFT HAND**

The window located on the left hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

### **CLIMATE CONTROL**

The cab shall be equipped with a ceiling mounted combination defrost / heating and air-conditioning system mounted above the engine tunnel in a central location.

The system shall offer sixteen (16) adjustable louvers. Six (6) of the louvers shall face forward towards the windshield, offering 45,000 BTU of heat at 320 CFM for defrosting. The system shall include six (6) rearward facing louvers to direct air for the crew area and four (4) for driver and officer comfort. The HVAC system shall be designed to produce 60,000 BTU of heat and 32,000 BTU of cooling. The HVAC cover shall be made of aluminum which shall be coated with a customer specified interior paint, or protective coating.

All defrost/heating systems shall be plumbed with one (1) seasonal shut-off valve at the front corner on the right side of the cab.

The air conditioner lines shall be a mixture of custom bent zinc coated steel fittings and Aero-quip GH 134 flexible hose with Aero-Quip EZ-Clip fittings.

### **CLIMATE CONTROL DRAIN**

The climate control system shall include a venturi pump for water management. The venturi pump drain shall remove condensation from the air conditioning system.

### **CLIMATE CONTROL ACTIVATION**

The heating, defrosting, and air conditioning controls shall be located on the center switch panel in the lower center section, in a position easily accessible to the driver and officer. The climate control shall be activated by a rotary switch.

### **HVAC OVERHEAD COVER PAINT**

The overhead HVAC cover shall be painted with a Zolatone #20-72 silver gray texture finish.

### **AUXILIARY CLIMATE CONTROL FRONT UNDERSEAT**

Two (2) 13,500 BTU heaters shall be provided and installed in the face of the seat riser storage area for the left and right front seats, one (1) each side. The fan controls shall be located on the Vista display and control screen(s).

The auxiliary heater system hoses shall be silicone with stainless steel constant torque clamps approved for use with silicone hose. The auxiliary heater system shall include one (1) seasonal shut-off valve. The valve shall be supplied at the front of the right hand corner of the cab. The cab must be tilted to access the shut-off valve.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **HEATER HOSE INSULATION**

The heater hoses leading from the engine to the cab shall include a foam insulation wrap which runs the length of the hose improving heating in extreme cold climates. The heater hoses which shall be routed inside the cab shall not be insulated.

### **A/C CONDENSER LOCATION**

A roof mounted A/C condenser shall be installed centered on the cab forward of the raised roof against the slope rise.

### **A/C COMPRESSOR**

The air-conditioning compressor shall be a belt driven, engine mounted, open type compressor that shall be capable of producing a minimum of 32,000 BTU at 1500 engine RPMs. The compressor shall utilize R-134A refrigerant and PAG oil.

### **UNDER CAB INSULATION**

The underside of the cab tunnel surrounding the engine shall be lined with multi-layer insulation, engineered for application inside diesel engine compartments.

The insulation shall act as a noise barrier, absorbing noise thus keeping the decibel level in the cab well within NFPA recommendations. As an additional benefit, the insulation shall assist in sustaining the desired temperature within the cab interior.

The engine tunnel insulation shall measure approximately 0.75 inch thick including a vertically lapped polyester fiber layer, a 1.0 lb/ft<sup>2</sup> PVC barrier layer, an open cell foam layer, and a moisture and heat reflective foil facing reinforced with a woven fiberglass layer. The foil surface acts as protection against moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.

The insulation shall be cut precisely to fit each section and sealed for additional heat and sound deflection. The insulation shall be held in place by 3 mils of acrylic pressure sensitive adhesive and aluminum pins with hard hat, hold in place fastening heads.

### **INTERIOR TRIM FLOOR**

The floor of the cab shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive and aluminum trim molding. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.

### **INTERIOR TRIM**

The cab interior shall include trim on the front ceiling, rear crew ceiling, and the cab walls. It shall be easily removable to assist in maintenance. The trim shall be constructed of insulated vinyl over a hard board backing.

### **REAR WALL INTERIOR TRIM**

The rear wall of the cab shall be trimmed with vinyl.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **HEADER TRIM**

The cab interior shall feature header trim over the driver and officer dash constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum.

### **TRIM CENTER DASH**

The main center dash area shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate. There shall be four (4) holes located on the top of the dash near each outer edge of the electrical access cover for ventilation.

### **TRIM LH DASH**

The left hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate for a perfect fit around the instrument panel. For increased occupant protection the extreme duty left hand dash utilizes patent pending break away technology to reduce rigidity in the event of a frontal crash. The left hand dash shall offer lower vertical surface area to the left and right of the steering column to accommodate control panels.

### **TRIM RH DASH**

The right hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate and shall include a glove compartment with a hinged door and a Mobile Data Terminal (MDT) provision. The glove compartment size will measure 14.00 inches wide X 6.38 inches high X 5.88 inches deep. The MDT provision shall be provided above the glove compartment.

### **TRIM RH DASH ACCESSORIES**

The Mobile Data Terminal (MDT) provision on the right hand dash shall be provided with a slide-out tray. The MDT slide-out tray shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate. The mounting surface of the tray measures 12.50 inches wide X 10.75 inches deep which shall allow for the mounting of a MDT with the added luxury of sliding it toward the officer as much as 11.00 inches.

### **ENGINE TUNNEL TRIM**

The cab engine tunnel shall be covered with a multi-layer mat consisting of 0.25 inch closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The mat shall be held in place by pressure sensitive adhesive. The engine tunnel mat shall be trimmed with anodized aluminum stair nosing trim for an aesthetically pleasing appearance.

The cab engine tunnel shall include a hinged aluminum access hatch with flush latches. The access hatch shall allow access to the engine compartment to check fluids.

### **POWER POINT DASH MOUNT**

The cab shall include one (1) 12 volt cigarette lighter type receptacle in the cab dash electrical panel to provide a power source for 12 volt electrical equipment. The cab shall also include two (2) universal serial bus (USB) charging receptacles in the cab dash electrical panel to provide a power source for USB chargeable electrical equipment. Each USB port shall be capable of a 5 Volt-500 milliampere output. The receptacles shall be wired to be live with the battery master switch.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **STEP TRIM**

Each cab entry door shall include a three step entry. The first step closest to the ground shall be constructed of 14 gauge 304 stainless steel with indented perforations. The perforations shall allow water and other debris to flow through rather than becoming trapped within the stepping surface. The stainless steel material shall have a number 7 mirror finish. The lower step shall be mounted to a frame which is integral with the construction of the cab for rigidity and strength. The middle step shall be integral with the cab construction and shall be trimmed in 0.08 inch thick 3003-H22 embossed aluminum tread plate.

### **UNDER CAB ACCESS DOOR**

The cab shall include an aluminum access door in the left crew step riser painted to match the cab interior paint with a push and turn latch. The under cab access door shall provide access to the diesel exhaust fluid fill.

### **INTERIOR DOOR TRIM**

The interior trim on the doors of the cab shall consist of an aluminum panel constructed of Marine Grade 5052-H32 0.13 of an inch thick aluminum plate. The door panels shall include a painted finish.

### **DOOR TRIM KICKPLATE**

The inner door panels shall include an aluminum tread kick plate which shall be fastened to the lower portion of the door panels.

### **DOOR TRIM CUSTOMER NAMEPLATE**

The interior door trim on the front doors shall include a customer nameplate which states the vehicle was custom built for their Department.

### **CAB DOOR TRIM REFLECTIVE**

The interior of each door shall include high visibility reflective tape. A white reflective tape shall be provided vertically along the rear outer edge of the door. The lowest portion of each door skin shall include a reflective tape chevron with red and white stripes and a Spartan logo. The chevron tape shall measure 6.00 inches in height.

### **INTERIOR GRAB HANDLE "A" PILLAR**

There shall be two (2) rubber covered 11.00 inch grab handles installed inside the cab, one on each "A" post at the left and right door openings. The left handle shall be located 7.88 inches above the bottom of the door window opening and the right handle shall be located 2.88 inches above the bottom of the door window opening. The handles shall assist personnel in entering and exiting the cab.

### **INTERIOR GRAB HANDLE FRONT DOOR**

Each front door shall include one (1) ergonomically contoured 9.00 inch cast aluminum handle mounted horizontally on the interior door panels. The handles shall feature a textured black powder coat finish to assist personnel entering and exiting the cab.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **INTERIOR GRAB HANDLE REAR DOOR**

A black powder coated cast aluminum assist handle shall be provided on the inside of each rear crew door. A 30.00 inch long handle shall extend horizontally the width of the window just above the window sill. The handle shall assist personnel in exiting and entering the cab.

### **INTERIOR SOFT TRIM COLOR**

The cab interior soft trim surfaces shall be gray in color.

### **INTERIOR TRIM SUNVISOR**

The header shall include two (2) sun visors, one each side forward of the driver and officer seating positions above the windshield. Each sun visor shall be constructed of Masonite and covered with padded vinyl trim.

### **INTERIOR FLOOR MAT COLOR**

The cab interior floor mat shall be gray in color.

### **CAB PAINT INTERIOR DOOR TRIM**

The inner door panel surfaces shall be painted with Zolatone #20-72 silver gray texture finish.

### **HEADER TRIM INTERIOR PAINT**

The metal surfaces in the header area shall be coated with Zolatone #20-72 silver gray texture finish.

### **TRIM CENTER DASH INTERIOR PAINT**

The entire center dash shall be coated with Zolatone #20-72 silver gray texture finish. Any accessory pods attached to the dash shall also be painted this color.

### **TRIM LH DASH INTERIOR PAINT**

The left hand dash shall be painted with a Zolatone #20-72 silver gray texture finish.

### **TRIM RIGHT HAND DASH INTERIOR PAINT**

The right hand dash shall be painted with Zolatone #20-72 silver gray texture finish.

### **RIGHT HAND DASH ACCESSORIES INTERIOR PAINT**

The right hand dash accessories shall be painted with Zolatone #20-72 silver gray texture finish.

### **DASH PANEL GROUP**

The main center dash area shall include three (3) removable panels located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **SWITCHES CENTER PANEL**

The center dash panel shall include six (6) switch positions in the upper left portion of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

### **SWITCHES LEFT PANEL**

The left dash panel shall include four (4) switches. There shall be three (3) across the top of the panel with one (1) below. Two (2) of the top row of switches shall be rocker type and the left one (1) shall be the windshield wiper/washer control switch. The lower switch shall be a rocker type switch.

A rocker switch with a blank legend installed directly above shall be provided for any position not designated by a specific option. The non-designated switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

### **SWITCHES RIGHT PANEL**

The right dash panel shall include three (3) rocker switch positions in the upper right hand portion of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

### **SEAT BELT WARNING**

A Weldon seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the cab. The system shall provide a visual warning indicator in the Vista display and control screen(s), an indicator light in the instrument panel, and an audible alarm.

The warning system shall activate when any seat is occupied with a minimum of 60 pounds, the corresponding seat belt remains unfastened, and the park brake is released. The warning system shall also activate when any seat is occupied, the corresponding seat belt was fastened in an incorrect sequence, and the park brake is released. Once activated, the visual indicators and audible alarm shall remain active until all occupied seats have the seat belts fastened.

### **SEAT MATERIAL**

The seats shall include a covering of high strength, wear resistant fabric made of durable ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Common trade names for this material are Imperial 1200 and Durawear.

### **SEAT COLOR**

All seats supplied with the chassis shall be gray in color. All seats shall include red seat belts.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **SEAT BACK LOGO**

The seat backs shall include the logo for the OEM body manufacturer. The logo shall be centered on the standard headrest of the seat back and on the left side of a split headrest.

### **SEAT DRIVER**

The driver's seat shall be an H.O. Bostrom Sierra model seat with air suspension. The four-way seat shall feature 3.00 inch vertical travel air suspension and manual fore and aft adjustment with 5.00 inches of travel. The suspension control shall be located on the seat below the left front corner of the bottom cushion. The seat shall also feature integral springs to isolate shock.

The seat position shall include a three-point shoulder harness with lap belt and an automatic retractor attached to the cab. The buckle portion of the seat belt shall be mounted on a semi-rigid stalk extending from the seat base within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 37.00 inches measured with the seat suspension height adjusted to the upper limit of its travel.

This model of seat shall have successfully completed the static load tests set forth by FMVSS 207, 209, and 210 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity.

The materials used in construction of the seat shall also have successfully completed testing with regard to the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which dictates the allowable burning rate of materials in the occupant compartments of motor vehicles.

### **SEAT BACK DRIVER**

The driver's seat shall feature a two (2) way adjustable lumbar support and offer an infinite fully reclining adjustable titling seat back. The seat back shall also feature a contoured head rest.

### **SEAT MOUNTING DRIVER**

The driver's seat shall be installed in an ergonomic position in relation to the cab dash.

### **OCCUPANT PROTECTION DRIVER**

The driver's position shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The driver's seating area APS shall include:

- Advanced seat belt system - retractor pre-tensioner tightens the seat belt around the driver, securing the occupant in the seat and the load limiter plays out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.
- Large side curtain airbag - protects the driver's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection

# GREELEY FIRE DEPT

SVI #930

## Production Specs

mitigation protection to the driver in a qualifying event by covering the window and the upper portion of the door.

- Dual knee airbags (patent pending) with energy management mounting (patent pending) - protects the driver's lower body from dangerous surface contact injuries, acceleration injuries, and from intrusion as well as locks the lower body in place so the upper body shall be slowed by the load limiting seat belt.

Steering wheel airbag - protects the driver's head, neck, and upper torso from contact injuries, acceleration injuries, and contact points with intrusive surfaces as a result of a collision.

### **SEAT OFFICER**

The officer's seat shall be an H.O. Bostrom Firefighter Sierra model seat. The seat shall feature six-way electric positioning. The six (6) positions shall include up and down, fore and aft and front and rear tilt. The seat shall also feature integral springs to isolate shock.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt, automatic retractor and buckle as an integral part of the seat assembly.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches measured with the seat height adjusted to the lowest position of travel.

This model of seat shall have successfully completed the static load tests by FMVSS 207, 209, 210 and 302 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

### **SEAT BACK OFFICER**

The officer's seat shall feature a SecureAll™ SCBA locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

### **SEAT MOUNTING OFFICER**

The officer's seat shall be installed in an ergonomic position in relation to the cab dash.



# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **OCCUPANT PROTECTION OFFICER**

The officer's position shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The officer's seating area APS shall include:

- Advanced seat belt system - retractor pre-tensioner tightens the seat belt around the officer, securing the occupant in the seat and the load limiter plays out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.
- Large side curtain airbag - protects the officer's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to the officer in a qualifying event by covering the window and the upper portion of the door.

Knee airbags - protects the officer's lower body from dangerous surface contact injuries, acceleration injuries, and from contact points with intrusive surfaces as a result of a collision as well as locks the lower body in place so the upper body shall be slowed by the load limiting seat belt.

### **POWER SEAT WIRING**

The power seat or seats installed in the cab shall be wired directly to battery power.

### **SEAT BELT ORIENTATION CREW**

The crew position seat belts shall follow the standard orientation which extends from the outboard shoulder extending to the inboard hip.

### **SEAT REAR FACING OUTER LOCATION**

The crew area shall include two (2) rear facing crew seats, which include one (1) located directly behind the left side front seat and one (1) located directly behind the right side front seat.

### **SEAT CREW REAR FACING OUTER**

The crew area shall include a seat in the rear facing outboard position which shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have

# GREELEY FIRE DEPT

SVI #930

## Production Specs

successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

### **SEAT BACK REAR FACING OUTER**

The rear facing outboard seat shall feature a Bostrom SecureAll™ self contained breathing apparatus (SCBA) locking system which shall store most U.S. and International SCBA brands and bottle sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the center of the bottom seat cushion for easy access and to eliminate hooking the release handle with clothing or other equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

### **SEAT MOUNTING REAR FACING OUTER**

The rear facing outer seats shall offer special mounting positions which shall be 2.00 inches towards the rear wall offering additional space between the front seats and the outer rear facing seats.

### **OCCUPANT PROTECTION RFO**

The rear facing outer seat position(s) shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

Each rear facing outer seating position APS shall include:

- APS advanced seat belt system - retractor pre-tensioners tighten the seat belts around each occupant, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.

Side curtain airbag - protects each occupant's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to each occupant in a qualifying event by covering the windows and walls adjacent to each seating position with an airbag custom designed for each cab configuration.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **SEAT FRAME REAR FACING CENTER**

The rear facing center seating shall include a seat frame which is located and installed behind the engine tunnel. The seat frame shall measure 46.15 inches wide X 12.00 inches high X 15.88 inches deep. The seat frame shall be constructed of 0.19 inch thick Marine Grade 5052-H32 smooth aluminum plate. The seat box shall be painted with the same color as the remaining interior.

### **SEAT FRAME REAR FACING CENTER STORAGE ACCESS**

The rear facing center seat frame shall include a storage access opening which shall measure 32.00 inches wide X 8.75 inches high to allow access within the seat frame for storage. A solid access door which shall measure 34.00 inches wide X 11.12 inches high shall be provided at the opening.

### **CAB FRONT UNDERSEAT STORAGE ACCESS**

The left and right under seat storage areas shall have a vented aluminum hinged door with non-locking latch.

### **SEAT COMPARTMENT DOOR FINISH**

All underseat storage compartment access doors shall have a Zolatone #20-72 silver gray texture.

### **WINDSHIELD WIPER SYSTEM**

The cab shall include a dual arm wiper system which shall clear the windshield of water, ice and debris. There shall be two (2) windshield wipers which shall be affixed to a radial wet arm. The system shall include a single motor which shall initiate the arm in which both the left hand and right hand windshield wipers are attached, initiating a back and forth motion for each wiper. The wiper motor shall be activated by an intermittent wiper control located within easy reach of the driver's position.

### **ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR**

The windshield washer fluid level shall be monitored electronically. When the washer fluid level becomes low the yellow "Check Message Center" indicator light on the instrument panel shall illuminate and the message center in the dual air pressure gauge shall display a "Check Washer Fluid Level" message.

### **CAB DOOR HARDWARE**

The cab entry doors shall be equipped with exterior pull handles, suitable for use while wearing firefighter gloves. The handles shall be made of a fiber reinforced plastic composite with a black matt finish.

The interior exit door handles shall be flush paddle type with a black finish, which are incorporated into the upper door panel.

All cab entry doors shall include locks which are keyed alike. The door locks shall be designed to prevent accidental lockout.

### **DOOR LOCKS**

The cab entry doors shall include a Controller Area Network (CAN) based electronic door lock system which shall include one (1) external keypad located on the left side next to the front grab. There shall be one (1) red rocker switch provided on the inside of each front cab entry door to actuate the cab door locks. Each door lock may also

# GREELEY FIRE DEPT

SVI #930

## Production Specs

be manually actuated from the inside of the cab by means of a red knob located on the paddle handle of the respective door. The electronic door lock system shall include four (4) key fobs for actuation with buttons for cab entry door locks and for compartment door locks.

When the doors are unlocked using the external keypad or the key fobs the interior dome lights shall illuminate and remain on for a period of twenty (20) seconds. The interior dome safety feature shall require the interior lighting power to be battery direct.

Wiring shall also be provided for up to four (4) exterior cab compartments and up to four (4) body compartments.

### **DOOR LOCK LH REAR CAB COMPARTMENT**

The left hand side rear compartment shall feature a power door lock actuator.

### **DOOR LOCK RH REAR CAB COMPARTMENT**

The right hand side rear compartment shall feature a power door lock actuator.

### **POWER DOOR LOCK COMPARTMENT ACTIVATION**

The power door lock feature shall include activation for exterior compartment door locks through the key fob, keypads and through a virtual switch on the multiplex display.

### **GRAB HANDLES**

The cab shall include one (1) 18.00 inch three-piece knurled aluminum, anti-slip exterior assist handle, installed behind each cab door. The assist handle shall be made of extruded aluminum with a knurled finish to enable non-slip assistance with a gloved hand.

### **REAR VIEW MIRRORS**

The cab exterior shall include Ramco bus style mirrors, one (1) mounted on the drivers' door and one (1) mounted on the right front cab corner radius below the windshield.

The left side mirror shall be model CRM-310-1750-TPCHR. The mirror head shall be injection molded chrome plated ABS plastic that measures 9.50 inches wide X 17.50 inches high and is mounted with a polished die-cast aluminum arm.

The right side mirror shall be model CRM-310-1752-A8-TPCHR. The mirror head shall be injection molded chrome plated ABS plastic that measures 9.50 inches wide X 17.50 inches high and is mounted with a 17.00 inch long polished cast aluminum arm.

Both the flat and convex mirrors shall be heated and remote controlled. The mirror control switches shall be located within easy reach of the driver. The mirrors shall be manufactured using the finest quality non-glare glass and shall feature a rigid mounting thereby reducing vibration. The mirrors shall be corrosion free under all weather conditions.

### **REARVIEW MIRROR HEAT SWITCH**

The heat for the rearview mirrors shall be controlled through a virtual button on the Vista display and control screen.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **EXTERIOR TRIM REAR CORNER**

There shall be mirror finish stainless steel scuff plates on the outside corners at the back of the cab. The stainless steel plate shall be affixed to the cab using two sided adhesive tape.

### **TRIM ROOF**

The raised portion of the cab roof shall include 3003-H22 bright aluminum embossed tread plate which is 0.08 inches thick. This plate shall be intended for reinforcement value and shall start at the rear edge of the roof extending to the radius at the forward end of the raised roof, and shall be the full width of the flat portion of the roof left to right.

The tread plate shall be held in place using stainless steel fasteners and shall be sealed with silver silicone caulk around the perimeter of the tread plate and at each mounting screw.

### **CAB FENDER**

Full width wheel well liners shall be installed on the extruded cab to limit road splash and enable easier cleaning. Each two-piece liner shall consist of an inner liner 16.00 inches wide made of vacuum formed ABS composite and an outer fenderette 3.50 inches wide made of 14 gauge 304 polished stainless steel.

### **MUD FLAPS FRONT**

The front wheel wells shall have mud flaps installed on them. The mud flaps shall extend from the outer edge of the wheel well to the inner edge of the wheel well to provide additional protection from road spray.

### **CAB EXTERIOR FRONT & SIDE EMBLEMS**

The cab shall include three (3) Spartan Chassis emblems. There shall be one (1) for the front air intake grille and two (2) emblems with integrated model nameplates for the exterior sides of the cab shipped loose for installation by the body manufacturer.

### **CAB EXTERIOR MODEL NAMEPLATE**

The cab shall include custom "Gladiator Advanced Protection System" nameplates integrated into the side emblem.

### **IGNITION**

A master battery system with a keyless start ignition system shall be provided. Each system shall be controlled by a one-quarter turn Cole Hersee switch, both of which shall be mounted to the left of the steering wheel on the dash. A chrome push type starter button shall be provided adjacent to the master battery and ignition switches.

Each switch shall illuminate a green LED indicator light on the dash when the respective switch is placed in the "ON" position.

The starter button shall only operate when both the master battery and ignition switches are in the "ON" position.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **BATTERY**

The single start electrical system shall include six (6) Harris BCI 31 950 CCA batteries with a 210 minute reserve capacity and 4/0 welding type dual path starter cables per SAE J541.

### **BATTERY TRAY**

The batteries shall be installed within two (2) steel battery trays located on the left side and right side of the chassis, securely bolted to the frame rails. The battery trays shall be coated with the same material as the frame.

The battery trays shall include drain holes in the bottom for sufficient drainage of water. A durable, non-conducting, interlocking mat made by Dri-Dek shall be installed in the bottom of the trays to allow for air flow and help prevent moisture build up. The batteries shall be held in place by non-conducting phenolic resin hold down boards.

### **BATTERY BOX COVER**

Each battery box shall include a steel cover which protects the top of the batteries. Each cover shall include flush latches which shall keep the cover secure as well as a black powder coated handle for convenience when opening.

### **BATTERY CABLE**

The starting system shall include cables which shall be protected by 275 degree F. minimum high temperature flame retardant loom, sealed at the ends with heat shrink and sealant.

### **BATTERY JUMPER STUD**

The starting system shall include battery jumper studs. These studs shall be located in the forward most portion of the driver's side lower step. The studs shall allow the vehicle to be jump started, charged, or the cab to be raised in an emergency in the event of battery failure.

### **ALTERNATOR**

The charging system shall include a 320 amp Leece-Neville 12 volt alternator. The alternator shall include a self-exciting integral regulator.

### **BATTERY CONDITIONER**

A Kussmaul 1200 Pump Plus battery conditioner shall be supplied. The battery conditioner shall be mounted in the cab in the LH rear facing outer seating position.

### **BATTERY CONDITIONER DISPLAY**

A Kussmaul battery conditioner display shall be supplied. The battery conditioner display shall be mounted in the cab, viewable through the cab mid side window behind the left front door.

### **AUXILIARY AIR COMPRESSOR**

A Kussmaul Pump 12V HP air compressor shall be supplied. The air compressor shall be installed behind the driver's seat. The air compressor shall be plumbed to the air brake system to maintain air pressure.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **ELECTRICAL INLET**

A Kussmaul 20 amp super auto-eject electrical receptacle shall be supplied. It shall automatically eject the plug when the starter button is depressed.

A single item or an addition of multiple items must not exceed the rating of the electric inlet that it's connected to.

#### **Amp Draw Reference List:**

*Kussmaul 1000 Charger - 3.5 Amps*

*Kussmaul 1200 Charger - 10 Amps*

*Kussmaul 35/10 Charger - 10 Amps*

*1000W Engine Heater - 8.33 Amps*

*1500W Engine Heater - 12.5 Amps*

*120V Air Compressor - 4.2 Amps*

### **ELECTRICAL INLET LOCATION**

An electrical inlet shall be installed on the left hand side of cab over the wheel well.

### **ELECTRICAL INLET CONNECTION**

The electrical inlet shall be connected to the battery conditioner.

### **ELECTRICAL INLET COLOR**

The electrical inlet connection shall include a gray cover.

### **HEADLIGHTS**

The cab front shall include four (4) rectangular LED headlamps with separate high and low beams mounted in bright chrome bezels.

### **FRONT TURN SIGNALS**

The front fascia shall include two (2) Whelen model 600 4.00 inch X 6.00 inch programmable amber LED turn signals which shall be installed in the outboard position.

### **HEADLIGHT LOCATION**

The headlights shall be located on the front fascia of the cab directly below the front warning lights.

### **SIDE TURN/MARKER LIGHTS**

The sides of the cab shall include two (2) LED round side marker lights which shall be provided just behind the front cab radius corners.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **MARKER AND ICC LIGHTS**

In accordance with FMVSS, there shall be five (5) LED cab marker lamps designating identification, center and clearance provided. These lights shall be installed on the face of the cab within full view of other vehicles from ground level.

### **HEADLIGHT AND MARKER LIGHT ACTIVATION**

The headlights and marker lights shall be controlled via a virtual button on the Vista display. There shall be a virtual dimmer control on the Vista display to adjust the brightness of the dash lights. The headlamps shall be equipped with the "Daytime Running" light feature, which shall illuminate the headlights to 80% brilliance when the battery master switch is in the "On" position and the parking brake is released.

### **GROUND LIGHTS**

Each door shall include an NFPA compliant LED ground light mounted to the underside of the cab step below each door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life. The ground lighting shall be activated by the opening of the door on the respective cab side, when the parking brake is set and through a virtual button on the Vista display and control screen.

### **LOWER CAB STEP LIGHTS**

The middle step located at each door shall include a recess mounted 4.00 inch round LED light which shall activate with the opening of the respective door.

### **INTERMEDIATE STEP LIGHTS**

The intermediate step well area at each door shall include an LED light within a chrome housing. The Egress step lights shall provide visibility to the step well area for the first step exiting the vehicle. The Egress step lights shall activate with Entry step lighting.

### **ENGINE COMPARTMENT LIGHT**

There shall be an LED NFPA compliant light mounted under the engine tunnel for area work lighting on the engine. The light shall include a polycarbonate lens, a housing which is vibration welded and a bulb which shall be shock mounted for extended life. The light shall activate automatically when the cab is tilted.

### **FRONT SCENE LIGHTS**

The front of the cab shall include two (2) Fire Research Spectra model, universal mount scene lights installed on the brow of the cab.

The lamphead shall have sixty (60) ultra-bright white LEDs, 48 for flood lighting and 12 to provide a spot light beam pattern. It shall operate at 240 volts AC, draw 1 amp, and generate 20,000 lumens of light. The lamphead shall have a unique lens that directs flood lighting onto the work area and focuses the spot light beam into the distance. The lamphead shall be no more than 6" high by 14" wide by 4 3/4" deep. The lamphead and mounting arm shall be powder coated.



# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **FRONT SCENE LIGHTS ACTIVATION**

The front scene lighting shall be pre-wired to be activated by the OEM.

### **FRONT SCENE LIGHT LOCATION**

There shall be two (2) scene lights mounted to the front brow of the cab inboard of the outer front marker lights. Each light shall be angled outboard 15-degrees.

### **INTERIOR OVERHEAD LIGHTS**

The cab shall include a two-section, red and clear Weldon LED dome lamp located over each door. The dome lamps shall be rectangular in shape and shall measure approximately 7.00 inches in length X 3.00 inches in width with a black colored bezel. The clear portion of each lamp shall be activated by opening the respective door and via the multiplex display and both the red and clear portion can be activated by individual push lenses on each lamp.

An additional two-section, red and clear Weldon LED dome lamp shall be provided over the engine tunnel which can be activated by individual switches on the lamp.

### **DO NOT MOVE APPARATUS LIGHT**

The front headliner of the cab shall include a flashing red Whelen 500 Series 5mm LED light clearly labeled "Do Not Move Apparatus". In addition to the flashing red light, an audible alarm shall be included which shall sound while the light is activated.

The flashing red light shall be 5.40 inches long X 1.70 inches wide X 0.90 inches high and shall be located centered left to right for greatest visibility.

The light and alarm shall be interlocked for activation when either a cab door is not firmly closed or an apparatus compartment door is not closed, and the parking brake is released.

### **MASTER WARNING SWITCH**

A master switch shall be included, as a virtual button on the Vista display and control screen which shall be labeled "E Master" for identification. The button shall feature control over all devices wired through it. Any warning device switches left in the "ON" position when the master switch is activated shall automatically power up.

### **HEADLIGHT FLASHER**

An alternating high beam headlight flashing system shall be installed into the high beam headlight circuit which shall allow the high beams to flash alternately from left to right.

Deliberate operator selection of high beams will override the flashing function until low beams are again selected. Per NFPA, these clear flashing lights will also be disabled "On Scene" when the park brake is applied.

### **HEADLIGHT FLASHER SWITCH**

The flashing headlights shall be activated through a virtual button on the Vista display and control screen.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **INBOARD FRONT WARNING LIGHTS**

The cab front fascia shall include two (2) Whelen 600 series Super LED front warning lights in the left and right inboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel.

### **INBOARD FRONT WARNING LIGHTS COLOR**

The warning lights mounted on the cab front fascia in the inboard positions shall be red.

### **FRONT WARNING SWITCH**

The front warning lights shall be controlled through a virtual control on the Vista display and control screen. This switch shall be clearly labeled for identification.

### **INTERSECTION WARNING LIGHTS**

The chassis shall include two (2) Whelen 600 series Super LED intersection warning lights, one (1) each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

### **INTERSECTION WARNING LIGHTS COLOR**

The intersection lights shall be red.

### **INTERSECTION WARNING LIGHTS LOCATION**

The intersection lights shall be mounted on the side of the bumper in the rearward position.

### **SIDE WARNING LIGHTS**

The cab sides shall include two (2) Whelen 600 series Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the sides of the cab within a chrome bezel.

### **SIDE WARNING LIGHTS COLOR**

The warning lights located on the side of the cab shall be red.

### **SIDE WARNING LIGHTS LOCATION**

The warning lights on the side of the cab shall be mounted over the front wheel well directly over the center of the front axle.

### **SIDE AND INTERSECTION WARNING SWITCH**

The side warning lights shall be controlled through a virtual button on the Vista display and control screen. This button shall be clearly labeled for identification.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **MARS WARNING LIGHTS**

The cab front shall include a Mars 888 model TB8-L1-P/C LED warning light featuring a gimbal mounted oscillating lamp.

The stainless steel light head shall be 7.00 inches in diameter and shall generate a "figure eight" pattern which is clearly visible even in adverse conditions. The light shall be pedestal mounted top center above the grill on an aluminum bracket painted cab color.

The lens shall be clear in color.

### **MARS WARNING LIGHT SWITCH**

The Mars front warning light(s) shall be separately controlled through a virtual button on the Vista display and control panel.

### **INTERIOR DOOR OPEN WARNING LIGHTS**

The interior of each door shall include one (1) red 4.00 inch diameter Truck-Lite LED warning light located on the door panel. Each light shall activate with a flashing pattern when the door is in the open position to serve as a warning to oncoming traffic.

### **SIREN CONTROL HEAD**

A Whelen 295SLSA1 electronic siren control head with hard wired microphone shall be provided in lower right section of the center panel. The siren shall offer a selectable 100 or 200-watt output, radio broadcast, public address, and seventeen (17) Scan-Lock siren tones and hands free operation which shall allow the operator to turn the siren on and off from the steering wheel horn ring if a horn/siren selector switch option is also selected. The siren circuitry shall be placed behind the rocker switch panels under the electrical cover with a 30 inch loop for the OEM to route as desired.

### **HORN BUTTON SELECTOR SWITCH**

A virtual button on the Vista display and control screen shall be provided to allow control of the electric horn or the air horn from the steering wheel horn button. The horn button selection shall default to the air horn each time the Vista screen power is cycled off and on. The electric horn shall sound when the selector switch is in either position to meet FMCSA requirements.

### **AIR HORN ACTIVATION**

The air horn activation shall be accomplished through the steering wheel button for the driver and by two (2) lanyard cables, one (1) on the left hand side accessible to the driver and one (1) on the right hand side accessible to the officer. An air horn activation circuit shall be provided to the chassis harness pump panel harness connector.

### **MECHANICAL SIREN ACTIVATION**

The mechanical siren shall be actuated by a Linemaster model SP491-S81 foot switch mounted in the front section of the cab for use by the officer. A red momentary siren brake rocker switch shall be provided in the switch panel on the dash.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The siren shall only be active when master warning switch is on to prevent accidental engagement.

### **BACK-UP ALARM**

An ECCO model 575 backup alarm shall be installed at the rear of the chassis with an output level of 107 dB. The alarm shall automatically activate when the transmission is placed in reverse. A virtual button shall be provided on the Vista display and control screen to disable the backup alarm.

### **INSTRUMENTATION**

An ergonomically designed instrument panel shall be provided. Each gauge shall be backlit with LED lamps. Stepper motor movements shall drive all gauges. The instrumentation system shall be multiplexed and shall receive ABS, engine, and transmission information over the J1939 data bus to reduce redundant sensors and wiring.

The instrument panel shall contain the following gauges:

One (1) electronic speedometer shall be included. The primary scale on the speedometer shall read from 0 to 100 MPH, and the secondary scale on the speedometer shall read from 0 to 160 KM/H.

One (1) electronic tachometer shall be included. The scale on the tachometer shall read from 0 to 3000 RPM.

One (1) two-movement gauge displaying primary system, and secondary system air volumes and integral LCD odometer/trip odometer shall be included on the lower portion of the LCD. The scale on the air pressure gauges shall read from 0 to 150 pounds per square inch (PSI). The air pressure scales shall be linear to operate with an accuracy of 1 degree of the measured data with a red indication zone on the gauge showing critical levels of air pressure. A red indicator light in the gauge shall indicate a low air pressure, as well as a message on the LCD screen. The odometer shall display up to 9,999,999.9 miles. The trip odometer shall display 9,999.9 miles. The LCD shall display Transmission Temperature in degrees Fahrenheit on the upper portion of the LCD. The LCD screen shall also be capable of displaying certain diagnostic functions.

One (1) four-movement gauge displaying engine oil pressure, coolant temperature, fuel level, voltmeter, and an \*indicator bar displaying Diesel Exhaust Fluid (DEF) LED bar shall be included. The scale on the engine oil pressure gauge shall read from 0 to 120 pounds per square inch (PSI). The engine oil pressure scale shall be linear to operate with an accuracy of 1 degree of the measured. A red indicator light in the gauge shall indicate a low engine oil pressure, as well as a message on the LCD screen. The scale on the coolant temperature gauge shall read from 100 to 250 degrees Fahrenheit (F). The coolant temperature scale shall be linear to operate with an accuracy of 1 degree of the measured data with a red indication zone on the gauge showing critical levels of air pressure. A red indicator light in the gauge shall indicate high coolant temperature, as well as a message on the LCD screen. The scale on the fuel level gauge shall read from empty to full as a percentage of fuel remaining. An amber indicator light shall indicate low fuel at 25% tank level. The scale on the voltmeter shall read from 10 to 16 volts with a red indication zone on the gauge showing critical levels of battery voltage. A red indicator light shall indicate high or low system voltage, as well as a message on the LCD screen. The scale on the DEF LED bar will consist of four (4) LEDs displaying levels in increments of 25% of useable DEF in green. Upon decreasing levels, the indicator bar will change colors to notify the driver of decreasing levels of DEF and action will be required. An amber indicator light shall indicate low levels of DEF, as well as a message on the LCD screen and an audible alarm.

The instrument panel shall include a light bar that contains the following LED indicator lights and produce the following audible alarms in applicable configurations:

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **RED LAMPS**

Stop Engine-indicates critical engine fault  
Air Filter Restricted-indicates excessive engine air intake restriction  
Park Brake-indicates parking brake is set  
Seat Belt Indicator-indicates when a seat is occupied and corresponding seat belt remains unfastened  
Low Coolant-indicates engine coolant is required

### **AMBER LAMPS**

MIL-indicates an engine emission control system fault  
Check Engine-indicates engine fault  
Check Trans-indicates transmission fault  
High Transmission Temperature-indicates excessive transmission oil temperature  
ABS-indicates anti-lock brake system fault  
HEST-indicates a high exhaust system temperature  
Water in Fuel-indicates presence of water in fuel filter  
\*DPF-indicates a restriction of the diesel particulate filter  
\*Regen Inhibit-indicates regeneration has been postponed due to user interaction  
Range Inhibit-indicates a transmission operation is prevented and requested shift request may not occur.  
\*SRS-indicates a problem in the supplemental restraint system  
Check Message-Turn Signal On  
Check Message-Door Ajar  
Check Message-Cab Ajar  
\*Check Message-ESC Active  
\*Check Message-DPF Regen Active  
Check Message-No Engine Data  
Check Message-No Transmission Data  
Check Message-No ABS Data  
Check Message-No Data All Communication With The Vehicle Systems Has Been Lost  
Check Message-Check Engine Oil Level  
Check Message-Check Washer Fluid Level  
Check Message-Check Power Steering Fluid Level  
Check Message-Low Transmission Fluid Level  
Check Message-Check Coolant Level

### **GREEN LAMPS**

Left and Right turn signal indicators  
\*ATC-indicates low wheel traction for automatic traction control equipped vehicles, also indicates mud/snow mode is active for ATC system  
High Idle-indicates engine high idle is active.  
Cruise Control-indicates cruise control is active  
OK to Pump-indicates the pump engage conditions have been met  
Pump Engaged-indicates the pump is currently in use  
Auxiliary Brake-indicates secondary braking device is active

### **BLUE LAMP**

High Beam Indicator

### **WHITE LAMP**

Wait to Start-indicates active engine air preheat cycle

# GREELEY FIRE DEPT

SVI #930

Production Specs

## **AUDIBLE ALARMS FROM GAUGE PACKAGE**

High Trans Temp  
High or Low Voltage  
Check Engine  
Check Transmission  
Stop Engine  
Low Air Pressure  
Fuel Low  
Water in Fuel  
\*ESC  
High Coolant Temperature  
Low Engine Oil Pressure  
Low Coolant Level  
\*Low DEF Level  
Air Filter Restricted  
Extended Left and Right Turn Remaining On  
Cab Ajar  
Door Ajar  
ABS System Fault  
Seatbelt Indicator

## **EXTERNAL AUDIBLE ALARM**

Air Filter  
Cab Ajar  
Door Ajar  
Check Engine  
Stop Engine  
Low Air Pressure  
Low Engine Oil Pressure  
Water in Fuel  
\*Low DEF  
ABS System Fault  
Seatbelt Indicator  
\*Items marked with an asterisk are provided only in applicable configurations.

## **LCD MESSAGES**

Transmission Temperature  
Battery Voltage  
Engine Hours  
Vehicle Speed  
Engine RPMs  
Fuel Level  
DEF Level  
Engine Oil Pressure  
Ammeter (If quipped)  
Auxiliary Ammeter (If quipped)  
Engine Coolant Temp  
Primary System Air Pressure  
Secondary System Air Pressure  
Turbo Boost Pressure  
Exhaust Temperature

# GREELEY FIRE DEPT

SVI #930

## Production Specs

Engine Load  
Engine Torque  
Instant Fuel Economy  
Average Fuel Economy

### **BACKLIGHTING COLOR**

The instrumentation gauges and the switch panel legends shall be backlit using red LED backlighting.

### **AUXILIARY SPEEDOMETER**

The dash shall include an auxiliary analog speedometer.

### **AIR RESTRICTION GAUGE**

The instrument panel shall include an Engineered Products air cleaner restriction gauge.

### **RADIO**

A Jensen radio with weather band, AM/FM stereo receiver, compact disc (CD) player, and four (4) speakers shall be installed in the cab. The radio shall include rear RCA input pigtail connector, satellite radio capability, and a covered front auxiliary mini stereo input with iPod ready USB jack. The CD player shall be compatible with CD-R, CD-RW and MP3 format discs. The radio shall be installed in the right hand overhead position. The speakers shall be installed inside the cab with two (2) speakers recessed within the headliner of the front of the cab just behind the windshield and two (2) speakers on the upper rear wall of the cab.

### **AM/FM ANTENNA**

A small antenna shall be located on the right hand side of the cab roof for AM/FM and weather band reception.

### **CAB EXTERIOR PROTECTION**

The cab face shall have a removable plastic film installed over the painted surfaces to protect the paint finish during transport to the body manufacturer.

### **FIRE EXTINGUISHER**

A 2.50 pound D.O.T approved fire extinguisher with BC rating shall be shipped loose with the cab.

### **ROAD SAFETY KIT**

The cab and chassis shall include one (1) emergency road safety triangle kit.

### **DOOR KEYS**

The cab and chassis shall include a total of four (4) door keys for the manual door locks.

### **DIAGNOSTIC SOFTWARE OCCUPANT PROTECTION**

Diagnostic software for the Spartan Advanced Protection System shall be available for free download from the Spartan Chassis website to Spartan authorized OEMs, dealers and service centers, as well as the vehicle owner.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The software has been validated to be compatible with the following RP1210 interface adapters:

- Dearborn Group DPA4 Plus
- Noregon Systems JPRO® DLA+
- Cummins INLINE5
- Cummins INLINE6
- NexIQ™ USB-Link™

The software and adapter utilize the SAE J1939-13 heavy duty nine (9) pin connector which is located below the driver's side dash to the left of the steering column.

### **WARRANTY**

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN CHASSIS, INC. LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The chassis manufacturer shall provide a limited parts and labor warranty to the original purchaser of the custom built cab and chassis for a period of twenty-four (24) months, or the first 36,000 miles, whichever occurs first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

### **CAB AND CHASSIS LABELING LANGUAGE**

The cab and chassis shall include the applicable caution, warning, and safety notice labels with text to be written in English.

### **CHASSIS OPERATION MANUAL**

There shall be four (4) complete sets of chassis operation manuals provided with the chassis. Two (2) sets shall be printed hard copies and two (2) sets shall be digital copies. Each manual shall include a parts list specific to the chassis model.

### **ENGINE AND TRANSMISSION OPERATION MANUALS**

The following manuals specific to the engine and transmission models ordered will be included with the chassis in the ship loose items:

- (2) Hard copies of the Engine Operation and Maintenance manual with CD
- (2) Digital copies of the Transmission Operator's manual
- (2) Digital copies of the Engine Owner's manual



# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **CAB/CHASSIS AS BUILT WIRING DIAGRAMS**

The cab and chassis shall include four (4) complete sets of wiring schematics and option wiring diagrams. Two (2) sets shall be printed hard copies and two (2) sets shall be digital copies.

### Weights

F Axle: 17,157

R Axle: 5,030

### **CAB TO AXLE DIMENSION**

Cab to axle will be 138".

### **CHASSIS MODIFICATIONS**

### **LUBRICATION AND TIRE DATA PLATE**

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid . . (if applicable)
- Pump priming system fluid, if applicable . . (if applicable)
- Drive axle(s) lubrication fluid
- Air conditioning refrigerant . . (if applicable)
- Air conditioning lubrication oil . . (if applicable)
- Power steering fluid
- Cab tilt mechanism fluid . . (if applicable)
- Transfer case fluid . . (if applicable)
- Equipment rack fluid (if applicable)
- CAFS air compressor system lubricant . . (if applicable)
- Generator system lubricant . . (if applicable)
- Front tire cold pressure
- Rear tire cold pressure
- Maximum tire speed ratings

### **VEHICLE DATA PLATE**

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the;
  - Engine
  - Transmission
  - Air
  - Fuel

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- Serial numbers for the;
  - Engine
  - Transmission
- Delivered Weights of the Front and Rear Axles
  - Paint Brand and Code(s)
  - Sales Order Number

### **OVERALL HEIGHT, LENGTH DATA PLATE (US)**

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in feet and inches, the length of the completed fire apparatus in feet and inches, and the GVWR in pounds.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

### **ACCIDENT PREVENTION**

There shall be a placard in the cab seating area which reads, "**ALL OCCUPANTS MUST BE SEATED AND BELTED WHEN THE APPARATUS IS IN MOTION**".

### **PERSONNEL CAPACITY**

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

### **ACCIDENT PREVENTION**

If the rear bumper is 8" deep or more, there shall be a placard on the rear face of the body, in clear sight from the ground, which reads, "**WARNING - DO NOT RIDE ON STEPS OR DECK AREAS WHILE THE APPARATUS IS IN MOTION. DEATH OR SERIOUS INJURY MAY RESULT**".

### **WEARING HELMET WARNING**

A label stating "**DO NOT WEAR HELMET WHILE SEATED**" shall be visible from each seating location.

### **FINAL STAGE MANUFACTURER VEHICLE CERTIFICATION**

A final stage manufacturer vehicle certification label shall be provided and installed in the driver cab door jamb area.

### **FRONT BUMPER**

The front bumper shall be as provided by the cab/chassis manufacturer. No other alteration or modifications are required.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **BUMPER GRAVELSHIELD**

The bumper extension gravel shield shall be provided by the cab/chassis manufacturer.

### **BUMPER PRE-CONNECT COMPARTMENT**

The center bumper extension shall have one (1) fire hose pre-connect compartment. The compartment shall be as large as room allows and capable of holding a minimum of 150' of 1-3/4" double jacket structural fire fighting hose and nozzle. Compartment door shall be 1/8" NFPA compliant aluminum tread plate with stainless steel hinge wrapped with vinyl and chrome push release type latches. The compartment door shall have a gas shock type hold open device. This compartment shall not be watertight but shall include a compartment drain.

The pre-connected swivel line shall be provided on inside back wall of compartment with swivel facing upward.

If the bumper compartment is greater than 4 cu.ft. in volume and has an opening greater than 144 sq.in. it shall have sufficient compartment lighting to provide a minimum of 2 fc (20 lx) at any location on the floor of the compartment without any equipment in the compartment. There shall be one (1) 9" OnScene LED type ground light mounted below the bumper.

A flashing warning light signal shall be provided indicating when a compartment door is not in a closed position as required by NFPA 1901.

### **AIR HORN(S)**

The air horn(s) shall be supplied and installed by the cab/chassis manufacturer.

### **FRONT TOW PROVISIONS**

The front tow provisions shall be supplied and installed by the cab/chassis manufacturer.

### **AIR INTAKE SYSTEM**

An air filter shall be provided in the engine's air intake system.

Air inlet restrictions shall not exceed the engine manufacturer's recommendations.

The air inlet shall be equipped with a means of separating water and burning embers from the air intake system.

This requirement shall be permitted to be achieved by either of the following methods:

- Provision of a device such that burning particulate matter larger than 0.039 in. (1.0 mm) in diameter cannot reach the air filter element.
- 1. Provision of a multi screen ember separator capable of meeting the test requirements defined in the Parker Hannafin, Racor Division, publication LF 1093-90, *Ember Separation Test Procedure*, or an equivalent test.

### **EXHAUST**

The exhaust system shall be as provided by cab/chassis manufacturer. The tailpipe may require some modifications for proper ground clearances and fit with body.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the vehicle or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position or entry doors on body.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

### **COMPUTER MOUNT**

A Havis Shields DS-PAN-111-2 computer mount, with power supply with locking mount shall be provided and mounted for included Panasonic Toughbook computer on officer dash area slide-out tray.

### **MDT COMPUTER**

There shall be one (1) Panasonic Toughbook CF-31WBLEHLM provided and installed to work in conjunction with all mobile communication devices on the apparatus. (Panasonic Toughbook 31 with Win7, Intel Core i5-3340M- Windows 7 Pro/8 Pro down. 5GHz, vPro, 13.1" XGA Touch, 320 GB (7200rpm), 4GB, Intel Wi-Fi a/b/g/n, TPM, Bluetooth, Dual Pass (Upper: WWAN/Lower: Selectable, Verizon 4G LTE, GPS, Emissive Backlit Keyboard).

The MDT shall be mounted to the specified slide tray on officer side dash.

### **RADIO/ANTENNA INSTALLATION**

A Greeley Fire Department supplied Motorola TOTA 4-channel mobile radio shall be installed and wired into the intercom system. Radio head location shall be officer side engine tunnel panel.

Radio(s) shall be installed per manufacturers' requirements and wired for proper 12 volt power and ground.

Cummins Program annual Prescription for current Laptop

### **SEAT BELT COLOR**

Section 14.1.3.4 of the NFPA 1901 Standards, 2009 edition, requires all seat belt webbing in cab to be bright red or bright orange in color, and the buckle portion of the seat belt shall be mounted on a rigid or semi rigid stalk such that the buckle remains positioned in an accessible location.

### **SEAT BELT WEB LENGTH - CUSTOM CAB**

Sections 14.1.3.2 and 14.1.3.3 of the NFPA 1901 standards, 2009 edition, require the effective seat belt web length for a Type 1 lap belt for pelvic restraint to be a minimum of 60", and a Type 2 pelvic and upper torso restraint-style seat belt assembly to be a minimum of 110".

The chassis seat belt web length as supplied by the custom chassis manufacturer shall be compliant to NFPA Standards 14.1.3.2 and 14.1.3.3.

### **SEAT BELT / VDR SYSTEM - CUSTOM CAB**

The seat belt warning and vehicle data recorder systems shall be provided by the cab/chassis manufacturer.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **KNOX BOX**

There shall be {qty} SVI supplied and installed Knox Box. The Knox Box shall be located on the forward engine tunnel within easy reach of the officer.

The Knox Box shall be a model #2650 without a strobe, and wired for proper master switched 12 volt power and ground.

**NOTE: Knox Box shall be mounted facing the Officers and tilted up at a 45 degree angle for ease of using the keypad.**

### **KNOX MED-VAULT 2**

A Knox Med-Vault 2, (no WiFi), shall be provided and installed in the rear curbside EMS compartment on upper adjustable shelf. Greeley must complete Knox forms and authorize, or provide a key for SVI to open and install.

### **HELMET STORAGE**

No helmet storage is required in the cab driving area.

### **CAB CRASH TEST CERTIFICATION**

A cab crash test certification from the fire apparatus manufacturer shall be provided with the equipment. A copy of this certification shall be included with the bid.

**NOTE:** There shall be no exception to any portion of the cab integrity certification requirements. Nonconformance shall lead to immediate rejection of bid.

The certification shall state that the cab does meet or exceed the requirements below:

2. European Occupant Protection Standard ECE Regulation No. 29.
  - 1) SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks.

### **CAB MIRRORS, DRIVER ADJUSTABLE**

Section 14.3.5 of the NFPA 1901 Standards, 2009 edition, requires all primary rear view mirrors used by the driver to be adjustable from the driver's position.

### **STREETSIDE ELFD STORAGE COMPARTMENT**

Storage shall be provided for two (2) backboards with dimensions of 72" x 17" x 2-1/2" on left side of streetside ELFD cab door.

There shall be one (1) slide-out smooth aluminum vertical tool board located on right side wall approximately 24" deep. Tool board vertical exterior edge shall have a double 90 degree formed edge to provide an easy grip handle. The top and bottom of tool board(s) shall be provided with Accuride 9300 series slide tracks. Each board shall be rated for a maximum 200 lbs. evenly distributed load. Each tool board shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.

A small shelf shall be installed onto the bottom of the toolboard on the rearward side. Shelf to be made as wide as space permits.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **MUDFLAPS**

There shall be 1/4" rubber mudflaps provided and installed behind each set of tires to prevent throwing road debris and lower road spray.

### **AIR BRAKE SYSTEM QUICK BUILD-UP**

There shall be one (1) Milton male quick connector type air shoreline inlet to provide air to the chassis air tanks from an external source compressed air shoreline hookup in order to maintain full operating air pressure while the vehicle is not running. Air inlet shall be located near driver's door. The female end of the connector shall be supplied by the Greeley Fire Department.

The quick buildup system shall provide sufficient air pressure so that the apparatus has no brake drag and is able to stop under the intended operating conditions following the 60-second buildup time.

### **CAB INTERIOR CABINET - CENTER REAR WALL**

There shall be one (1) full height and full width cabinet located on rear cab wall. The cabinet shall be fabricated from 1/8" smooth aluminum, and shall have two (2) 31" door opening wide ROM un-painted roll-up doors, one (1) offset to curbside, and one (1) in center.

The cabinet shall be finished with a matching Zolatone paint matching interior cab paint. The cabinet shall be full cab width x full cab interior height x 18" deep. The cabinet will have a bolt-in dividing wall to allow storage of 72" backboards, and one (1) full height slideout toolboard for FD tools from streetside exterior ELFD compartment.

### **12 VDC ACCESSORY PLUG**

There shall be three (3) 12 volt accessory plug(s) furnished and installed in the cabinet area. The location of accessory plugs shall be located in the center compartment.

- 2) There shall be two (2) OnScene Solutions LED Night Axe(s) mounted vertically inside the cabinet. The LED Night Axe(s) shall be a 54" section
- There shall be four (4) vertically adjustable shelves, two (2) in each of the above cabinets with a 1.0" vertical lip (flush with Dri-Dek).
- There shall be one (1) 120 volt outlet(s) located inside this cabinet. The location of outlet(s) shall be located in the center compartment.
  - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
- There shall be one (1) 120 volt outlet strip(s) approximately 4' long with straight blade household type outlets provided with this outlet. Strip shall be located in the center compartment.
  - Outlet(s) shall be powered through the on-board shore power system.

### **FUEL FILL**

There shall be one (1) fuel fill door located in the streetside exterior wheel well panel, behind the rear axle. The fill door shall be fabricated from brushed stainless steel. There shall be a permanent label with the text "DIESEL FUEL ONLY" located adjacent to the fuel fill access.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **MAP BOX**

A map box shall be provided in the cab with an open top. The map box shall be securely fastened to the cab interior per NFPA 1901 standards. It shall be fabricated of 1/8" smooth aluminum and painted with a black or gray textured powder coat paint finish for durability and finished appearance.

The map box shall be designed to hold four (4) 1-1/2" 3-ring binders with an open storage area in center, and two (2) slots for holding gloves. Match previous job #915.

### **BODY DESIGN**

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the Greeley Fire Department to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the Greeley Fire Department from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

### **EXTERIOR ALUMINUM BODY**

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 3/16" (.187) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas, No Exceptions.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The front and rear corners of body shall be formed as part of the front or rear body panels. This provides a stronger body corner and finished appearance. The use of extruded corners, or caps will not be acceptable, No Exceptions.

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded and caulked to prevent moisture from entering the compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

### **DRIP RAILS**

The body shall have drip rails over the side full height compartments. The drip rails shall be formed into the upper body panels providing a ridged lower panel and a flat upper body panel surface. The use of mechanically fastened, taped or glued on drip rails will not be acceptable, No Exceptions.

### **ROOF CONSTRUCTION**

The roof shall be integral with the body and shall be all welded construction. The roof of the body shall not be less than 3/16" aluminum 3003H-14 alloy tread plate, fully and continuously welded. The roof shall be reinforced with 2" x 2" x 1/4" aluminum tubing running the full width of the body.

All seams in the roof area shall be welded to the radius and supports prior to paint to prevent entry of moisture. All roof seams shall be continuously welded.

A 2" formed radius shall be provided along the body sides. The use of extruded radius will not be acceptable, No Exceptions.

### **BODY SUBFRAME**

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.



# GREELEY FIRE DEPT

SVI #930

## Production Specs

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 4" x 1/4" aluminum tubes minimum, the same width as the chassis frame rails. Welded to this tubing shall be cross members of 2" x 4" x 1/4" aluminum. Smaller dimension, lighter gauge tubing or angle material subframe shall not be accepted.

These cross members shall extend the full width of the body to support the compartments. Cross members shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum cross members shall be located on 16" centers, or as necessary to support walkway or heavy equipment.

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.

### **BODY MOUNTING**

The body subframe shall be fastened to the chassis frame with a minimum of four (4) spring loaded body mounts. Each mount shall be configured using a two-piece encapsulated slide bracket. The two (2) brackets shall be fabricated of heavy duty 1/4" thick steel and shall have a powder coat finish to prevent any corrosion. Each mounting assembly shall utilize two (2) 3/4" diameter x 6" long grade 8 bolts and two (2) heavy duty springs. The assembly design shall allow the body and subframe to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall eliminate any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement will not be acceptable.

### **12" REAR STEP BUMPER**

The full width rear bumper shall be constructed from 2" x 2" x 1/4" aluminum tubing frame and covered with 3/16" NFPA compliant aluminum tread plate. The bumper shall extend from the rear vertical body panel 12" and provide a rear step with a minimum of 1/2" space at body for water drainage.

### **REAR TOW EYES**

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below the apparatus body. The tow eyes shall be fabricated from 3/4" thick steel plate and shall have a black powder coat finish.

### **GROUND LIGHTS**

There shall be two (2) OnScene 9" Night Axe LED lights installed below bumper capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting shall be switchable but activated automatically when the vehicle park brake is set.

### **WHEEL WELL EXTERIOR PANEL**

The exterior panel of the body wheel well enclosure shall be constructed from 3/16" smooth aluminum panels.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **STAINLESS STEEL BODY FENDERS**

The body wheel well openings shall be provided with round radius, polished stainless steel fenderettes. The fenderettes shall be bolted and easily replaceable if damaged. The fenderettes shall be installed using a rubber gasket to reduce buildup of moisture and/or debris.

### **WHEEL WELL LINERS**

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will not accumulate dirt or water.

### **SCBA CYLINDER COMPARTMENTS**

There shall be three (3) SCBA cylinder storage compartments located, two (2) on the curbside, and one (1) on the streetside of rear wheel well area. Each compartment shall be capable of storing two (2) SCBA cylinders (60 min cylinders). Each compartment shall have a vertically hinged door with a positive catch latch installed and painted primary lower body color. Each compartment shall allow the storage of an SCBA cylinder or a fire extinguisher up to 7-3/4" in diameter and 24" deep. The door shall activate the "Hazard Warning Light" in the cab when not in the closed position.

### **BODY PAINT SPECIFICATIONS**

#### **BODY PAINT PREPARATION**

After the body and components have been fabricated they shall be disassembled so when vehicle is complete there shall be finish paint beneath the removable components. The body shall be removed from chassis during the paint process to insure proper paint coverage. The body and components shall be metal finished as follows to provide a superior substrate for painting.

The exterior (and interior, if painted) body shall undergo a thorough cleaning process starting with a biodegradable phosphoric acid solution to begin the etching process followed by a complete clear water rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the metal surface for greater film adhesion.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

#### **PAINT PROCESS**

The paint process shall follow the strict standards set forth by PPG Industries guidelines. Painters applying PPG products will be PPG Certified Commercial Technicians, and re-certified every two (2) years. The body shall go through the following paint process;

- Clean bare metal with a wax and grease remover using low lint rags.
- 1) Inspect, straighten, and hammer high points, grind all seams, sharp edges, and welds. DA sand entire paintable surfaces using 24-180 grit dry paper. Plastic fill all low spots and DA sand fill areas using 36-180 grit dry paper. Apply pinhole filler and DA sand areas using 80-180 grit dry paper.
- 2) Re-clean bare metal using a wax and grease remover and low lint rags.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- 3) Within 24 hours, a PPG Delfleet® epoxy color primer with proper hardener for corrosion resistance using a pressure pot spray gun and applying 2-5 full wet coats or 1.5-8.0 dry mils max. achieving full hiding and allow to air dry 60 minutes @ 70°F or bake for 45 minutes @ 140°F degree.
- 4) Inspect, putty fill, and dry guild coat entire body surface and DA sand using 180-400 grit dry paper.
- 5) Re-clean bare metal using a wax and grease remover using low lint rags.
- 6) A PPG Delfleet® primer sealer with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 1 full wet coat or 1.0-2.0 dry mils achieving full hiding and allow to flash off in spray booth for minimum of 60 minutes @ 70°F.
- 7) A PPG Delfleet® FBCH basecoat (color) with proper hardener and dry additive shall then be sprayed using a pressure pot set @ 45-60 PSI and achieving full hiding or 1.5-2.0 wet mils and allow to flash off in spray booth 45-60 minutes before applying clearcoat.
- 8) A PPG Delfleet® clearcoat with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 2-3 full wet coats or 5.0 wet mils for a uniform gloss and allow to flash off in spray booth 10 minutes and bake for 120-140 minutes @ 125°F (surface temp.).
- 9) After cooling, DA sand heavy orange peel or runs using 1000 grit dry sand paper and final DA sand using 1500-2000 grit dry sand paper. Wipe off all surfaces to remove dust and debris. Buff unit as needed using 3M rubbing compound and a white wool pad and inspect until all sand scratches are removed.
- 10) Polish as needed using 3M Perfect-It-Polish and a black foam pad, repeat as necessary and inspect until all sand scratches are removed.

### **PAINT - ENVIRONMENTAL IMPACT**

The contractor shall meet or exceed all current State (his) regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. PPG Delfleet® Evolution paint shall be free of all heavy metal (lead & chromate) components. Paint emissions from sanding and painting shall be filtered and collected. All paint wastes shall be disposed of in an environmentally safe manner. Solvents used in cleanup operations shall be collected, sent off-site for distillation and returned for reuse.

### **PAINT FINISH - SINGLE COLOR**

The body shall be painted with a single color of PPG Delfleet® Evolution per Greeley Fire Department approved paint spray out provided.

A small touch-up bottle of paint shall be provided with completed vehicle.

### **FASTENERS**

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, a mylar isolation tape, or gasket shall be used to prevent damage to the finish painted surface. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nutserts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

### **ELECTROLYSIS CORROSION CONTROL**

The vehicle shall be assembled using ECK brand or similar corrosion control compound on all high corrosion potential areas.

ECK protects aluminum and stainless steel against electrolytic reaction, isolates dissimilar metals and gives bedding protection for hardware and fasteners. ECK contains anti-seizing lubricant for threads. ECK is dielectric and perfect for use with electrical connectors.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

11) Paint Color: Match cab/chassis supplied paint color.

### **BODY UNDERCOATING**

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

### **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

### **PAINT WARRANTY**

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle. **Pro-rated warranties will not be acceptable.**

### **COMPARTMENT INTERIOR FINISH**

The compartment interior paintable surfaces shall be prepared and DA sanded using 80-120 grit dry paper and cleaned with a wax and grease remover. A PPG Delfleet® primer topcoat of either a solids epoxy primer or an etch primer shall be applied.

A PPG Delfleet® color primer with proper hardener and thinner mix shall then be sprayed using a pressure pot spray gun and applying 2 wet coats achieving full hiding on entire compartment surface and allow to air dry for 30 minutes @ 70°F before applying texture coat.

A PPG Delfleet® F3985 White/F3986 Gray top coat/texture coat with proper hardener and dry additive shall then be sprayed using a pressure pot and reducing the atomizing air pressure and turn fan pattern all the way in on the gun. Apply the first color texture coat as needed and allow to air dry @ 70°F over night before assembly and 7 days before putting into full service.

### **REFLECTIVE STRIPE REQUIREMENTS**

#### Material

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retroreflection of 10 with observation angle of 0.2 degrees and entrance angle of -4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

#### Minimum Requirements

# GREELEY FIRE DEPT

SVI #930

## Production Specs

A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 4 in. (100 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

### **GRAPHICS PROOF**

A color graphics proof of the reflective striping layout shall be provided for approval by Greeley Fire Department prior to installation. The graphics proof shall be submitted to Greeley Fire Department on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

### **REFLECTIVE STRIPE - CAB SIDE**

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be black in color.

### **REFLECTIVE STRIPE - CAB FRONT BUMPER**

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be black in color.

### **REFLECTIVE STRIPE - BODY SIDES**

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be black in color.

The stripe shall remain in a straight line from the front of the front of cab to the rear body.

### **CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS**

At least 50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width.

The rear side panels of the body on each side of a rear stairway or compartment shall have a chevron style reflective stripe, extending from bumper height up to side compartment drip rail height. Each chevron panel shall be a full sheet and shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panel shall have a minimum 10 year warranty for material failure, and colorfastness.

The stripe material shall be 3M Diamond Grade.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

### **CAB STRIPE - 22K GOLD LEAF**

The cab shall have a 1/2" wide 22K gold leaf stripe provided on each side of cab on the two-tone cab paint line. Stripe shall have a black outline.

### **LOWER BODY STRIPE - 22K GOLD LEAF**

The body shall have a 1/2" wide 22K gold leaf stripe provided on each side of lower doors or body, and lower door or body above wheel well. Stripe shall have a black outline.

### **LETTERING**

#### **GRAPHICS PROOF**

A color graphics proof of the lettering layout shall be provided for approval by Greeley Fire Department prior to installation. The graphics proof shall be submitted to Greeley Fire Department on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

The following lettering shall be provided and installed on the completed unit as follows;

#### **SIDE CAB DOOR LETTERING**

There shall be fourteen (14) 4" high 22K Gold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

"GREELEY" - Arched above door emblem on front cab doors.

There shall be twelve (12) 3" high 22K Gold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

"ENGINE" - Arched on rear crew doors.

There shall be two (2) 6" high 22K Gold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

" 2 " - Rear crew doors each side (unit number)

#### **FRONT OF CAB LETTERING**

There shall be four (4) 3" high 22K Gold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

"E2" Located on each side front of cab below windshield.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **CUSTOM DOOR DECAL**

One (1) custom designed Maltese designs using 3M Scotchcal reflective material and 22k Gold Leaf sealed in a clear 3M laminate film shall be provided and located on front cab doors. The exact design and/or artwork shall match current Greeley Fire Department vehicles.

### **EXTERIOR COMPARTMENT DOORS**

#### **HINGED DOOR CONSTRUCTION**

The exterior compartment doors shall be custom manufactured and built for each compartment. The compartment doors must be able to withstand years of rugged service and wear. For this reason, the compartment door design, metal thickness, and attachments must be strictly adhered to.

The compartment doors shall be all aluminum 3003H-14 alloy construction. The exterior panel shall be of 1/8" thickness smooth plate aluminum and the interior panel shall be of 1/8" thickness smooth plate aluminum. Lighter gauge material will NOT BE ACCEPTABLE in these areas. The double panel doors shall be 1-3/4" thick to completely enclose the door latching assembly. Doors shall have drain hole openings for drainage and ventilation.

The doors shall be flush mounted so that the outer surface is in line with the side body surface. Lap or bevel type constructed doors, doors framed with extrusions, or doors requiring rubber bumpers to prevent unnecessary contact are NOT ACCEPTABLE.

Compartment door openings shall be sealed with closed cell automotive type rubber molding to provide a weather resistant seal around door. In addition, rubber molding shall be provided along hinge to prevent moisture entry. Open cell foam type rubber moldings are NOT ACCEPTABLE.

Hinged compartment doors shall have 14 gauge stainless steel hinge, with 1/4" stainless steel pin. The hinge shall be bolted to the door and body with stainless steel machine screws. A polyester barrier film gasket shall be placed between stainless steel hinge and any dissimilar metals as necessary.

Drip rails shall be installed above all compartment door openings. Drip rails shall be completely removable for easy replacement if necessary.

Each door shall be capable of being opened or closed without unlatching. Door checks shall be bolted to the upper compartment door header and the box pan of the door. Door checks that require unlatching by hand will NOT BE ACCEPTABLE.

The door handle type and door check type of hinged compartment doors shall be as specified with each door.

#### **ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM)**

The apparatus shall be equipped with Robinson ROM Series III roll-up exterior compartment doors. Robinson roll-up doors shall be complete with the following features;

- Doors shall be front roll with drum positioned at upper front portion of compartment to afford maximum clearances and head room for mounting equipment to ceiling of compartment

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- There shall be a non-abrasive side brush seals
- Every slat must have interlocking end shoes to prevent slat from moving side-to-side and binding the door
- Between each slat must be a co-extruded PVC inner seal to prevent metal-to-metal contact and to repel moisture. This inner seal is not visible to detract from appearance of door
- Slat are to have interlocking joints with a folding locking flange to provide security and prevent penetration by sharp objects
- Slat to be double-wall extrusion 1.366" high by .315" thick. Exterior surface to be flat and interior surface to be concave to prevent loose equipment from interfering with door operation
- Latch system to be a full width one piece lift bar operable by one hand
- A 2" wide finger pull integrated into bottom rail extrusion for easy one hand opening and closing
- Clip system that connects the curtain slats to the operator drum which allows for easy tension adjustment without tools
- Each roll-up door shall have a 4" diameter counterbalance operator drum to assist in lifting the door.
- Track shall be one-piece aluminum that has an attaching flange and finishing flange incorporated into its design
- Drip rail will have specially designed seal that prevents the seal from scratching the door
- Bottom rail extrusion must have smooth back to prevent loose equipment from jamming the door
- Bottom rail to have "V" shaped double seal to prevent water and debris from entering the compartment
- Standard replacement parts to be shipped from the United States and available in as little as 48 hours
- Will be free from manufacturing defects for a period of up to 7 years from date of purchase provided that the Product is used under conditions of normal use, that regular periodic maintenance and service is performed and that the product was installed in accordance with R•O•M's instructions.

Each roll-up door framework shall decrease the compartment door opening by approximately 2.25" and 4.5" in height for standard bottom rail and 6.0" in height for tall bottom rail option.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.

### **BODY HEIGHT MEASUREMENTS**

The vertical pumper body dimensions shall be as follows:

#### AHEAD OF REAR AXLE

	<u>Description</u>	<u>Dimension</u>
A	Bottom of Subframe to Top of Body	57.5"
B	Bottom of Subframe to Bottom of Body	22.5"
C	Vertical Door Opening -with hinged door	61.5"

#### ABOVE REAR AXLE

	<u>Description</u>	<u>Dimension</u>
D	Vertical Door Opening - Above Rear Wheel -with hinged door	28.0"

#### BEHIND REAR AXLE

	<u>Description</u>	<u>Dimension</u>
E	Bottom of Subframe to Bottom of Body	20.0"
F	Vertical Door Opening	



# GREELEY FIRE DEPT

SVI #930

## Production Specs

-with hinged door

59.5"

### GENERAL

	<u>Description</u>	<u>Dimension</u>
G	Bottom of Drip Rail to Top of Body	13.5" (min.)

(Dimensions are generic and subject to change during the actual design process)

### BODY WIDTH DIMENSIONS

The pumper body shall be 100.0" wide, not including drip rail or non-permanent fixtures. Interior compartment depth dimensions shall be approximately:

<u>Area Description</u>	<u>Dimension</u>
Transverse Area above Subframe (If Specified)	95.0"
Compartment Depth above Subframe	14.0" or 24.0" (depending on water tank configuration)
Compartment Depth below Subframe	24.5"

### STREETSIDE COMPARTMENT - FRONT (S1)

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

- This compartment shall have vertically hinged box pan style doors fabricated of 1/8" thick smooth aluminum. The inner liner of the door shall be 1/8" thick smooth aluminum with an unpainted finish. The door exterior shall be painted job color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The hinged door(s) shall have a stainless steel 6" offset bent D-ring non-locking handle. A gasket shall be placed between handle and door. Door latches shall be a two-point rotary slam, double-catch latch, recessed inside the double panel door with striker plate.
- The hinged door(s) shall have a pneumatic cylinder to hold door in the open and closed positions. Each door shall be capable of being closed without unlatching. Door checks shall be bolted to the compartment door header and the box pan of the door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- There shall be one (1) adjustable shelf/shelves approximately 12" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.
- There shall be one (1) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
- The side walls of compartment shall be PAC Trac 7000 extrusion with the tracks in a horizontal orientation.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- One (1) 120/240 VAC load center located in upper left compartment.
- The 12 volt electrical distribution panel shall be located in the upper right compartment.

### **STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2)**

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

- This compartment shall have a horizontally hinged, lift-up style box pan door fabricated of 1/8" thick smooth aluminum. The inner liner of the door shall be 1/8" thick smooth aluminum with an unpainted finish. The door exterior shall be painted job color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The hinged door(s) shall have a stainless steel 6" offset bent D-ring non-locking handle. A gasket shall be placed between handle and door. Door latches shall be a two-point rotary slam, double-catch latch, recessed inside the double panel door with striker plate.
- The hinged door(s) shall have a pneumatic cylinder to hold door in the open and closed positions. Each door shall be capable of being closed without unlatching. Door checks shall be bolted to the compartment door header and the box pan of the door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- The back wall and both side walls of compartment shall be PAC Trac 7000 extrusion with the tracks in a horizontal orientation.
- Two (2) OnScene 36" Access LED compartment lights, vertically mounted.

### **STREETSIDE COMPARTMENT - REAR (S3)**

The interior useable compartment width shall be approximately 49.0" wide.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The compartment door opening shall be approximately 42.0" wide.

- This compartment shall have vertically hinged box pan style doors fabricated of 1/8" thick smooth aluminum. The inner liner of the door shall be 1/8" thick smooth aluminum with an unpainted finish. The door exterior shall be painted job color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The hinged door(s) shall have a stainless steel 6" offset bent D-ring non-locking handle. A gasket shall be placed between handle and door. Door latches shall be a two-point rotary slam, double-catch latch, recessed inside the double panel door with striker plate.
- The hinged door(s) shall have a pneumatic cylinder to hold door in the open and closed positions. Each door shall be capable of being closed without unlatching. Door checks shall be bolted to the compartment door header and the box pan of the door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
- A hose hanger bar capable of holding 300' of double jacket 1-3/4" hose and two (2) nozzles shall be provided with a 3" retaining lip and located in in upper center of compartment 15" from ceiling.
- The side walls of compartment shall be PAC Trac 7000 extrusion with the tracks in a horizontal orientation.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

### **CURBSIDE COMPARTMENT - FRONT (C1)**

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

- This compartment shall have vertically hinged box pan style doors fabricated of 1/8" thick smooth aluminum. The inner liner of the door shall be 1/8" thick smooth aluminum with an unpainted finish. The door exterior shall be painted job color.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The hinged door(s) shall have a stainless steel 6" offset bent D-ring non-locking handle. A gasket shall be placed between handle and door. Door latches shall be a two-point rotary slam, double-catch latch, recessed inside the double panel door with striker plate.
- The hinged door(s) shall have a pneumatic cylinder to hold door in the open and closed positions. Each door shall be capable of being closed without unlatching. Door checks shall be bolted to the compartment door header and the box pan of the door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf/shelves approximately 12" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.
- There shall be one (1) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- The cab tilt control pendant.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

### **CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C2)**

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

- This compartment shall have a horizontally hinged, lift-up style box pan door fabricated of 1/8" thick smooth aluminum. The inner liner of the door shall be 1/8" thick smooth aluminum with an unpainted finish. The door exterior shall be painted job color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The hinged door(s) shall have a stainless steel 6" offset bent D-ring non-locking handle. A gasket shall be placed between handle and door. Door latches shall be a two-point rotary slam, double-catch latch, recessed inside the double panel door with striker plate.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- The hinged door(s) shall have a pneumatic cylinder to hold door in the open and closed positions. Each door shall be capable of being closed without unlatching. Door checks shall be bolted to the compartment door header and the box pan of the door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- The back wall and both side walls of compartment shall be PAC Trac 7000 extrusion with the tracks in a horizontal orientation.
- Two (2) OnScene 36" Access LED compartment lights, vertically mounted.

### **CURBSIDE COMPARTMENT - REAR (C3)**

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

- This compartment shall have vertically hinged box pan style doors fabricated of 1/8" thick smooth aluminum. The inner liner of the door shall be 1/8" thick smooth aluminum with an unpainted finish. The door exterior shall be painted job color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The hinged door(s) shall have a stainless steel 6" offset bent D-ring non-locking handle. A gasket shall be placed between handle and door. Door latches shall be a two-point rotary slam, double-catch latch, recessed inside the double panel door with striker plate.
- The hinged door(s) shall have a pneumatic cylinder to hold door in the open and closed positions. Each door shall be capable of being closed without unlatching. Door checks shall be bolted to the compartment door header and the box pan of the door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf/shelves approximately 12" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- There shall be two (2) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions. Specified Super Vac gas and electric fans to be located on this tray.
- Specified model 13 Little Giant ladder will be mounted horizontally on upper rear wall.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- Four (4) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment to vent gas fumes to outside.

### **REAR COMPARTMENT - CENTER (RC1)**

The rear center compartment shall start at the top of the body sub-frame and be as high as the side compartments, unless specified otherwise. There shall also be a compartment below the frame, as wide as the chassis frame rails permit.

The interior useable compartment width shall be approximately 41.0" wide x 26" deep.

The compartment door opening shall be approximately 34.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the

# GREELEY FIRE DEPT

SVI #930

## Production Specs

slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions. For Greeley Fire Department TNT tools (see photos in file for layout).

- Access shall be provided through floor to fuel sender on fuel tank.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.

### **PLASTIC FLOOR AND SHELF TILE**

All compartment floors, shelves, and trays shall be covered with Dri-Dek plastic interlocking grating.

- The plastic floor tile shall be black.
- The plastic edge trim shall be black.

### **LADDER LIFT SYSTEM, CURBSIDE**

A Ziamatic 12 VDC, 125 amp OALS (Outside Arm Ladder System) model OALS-1200 with dual 8" stroke hydraulic cylinders that mount on end walls of body (requires 8" D x 11.5" W on inside wall, and 5" W x 4.5" D on outside wall) designed to carry specified ladders and equipment shall be provided. 2" x 4" heavy wall booms connect hydraulic cylinders to rack with bronze bearings for years of trouble free service. Pneumatic power clamps shall lock booms in the stored position. Hydraulic power unit shall be set at 1,500 PSI for up, to 2,500 PSI for down cycle. System meets NFPA standard and has been cycle tested for over more than 6,000 operating cycles.

The lift system shall be electro-hydraulic with built-in electric safety latches and audible warning alarm when in operation. Access shall still be provided to compartments with system in lowered position. Flashing lights on ends shall produce a visual signal when the system is out of the stored position. A flashing warning light signal shall be provided indicating when a ladder rack is not in a stowed position as required by NFPA 1901.

The ladder control panel shall be located on curbside pump panel. The ladder lift system shall be designed to store the specified ladder compliment specified. The lift system rear arm may require to be modified to allow for unobstructed view of warning lights from rear of apparatus.

### **LADDER LIFT INTERLOCK**

An interlock circuit shall be included on the ladder lift system to prevent the lift from raising if a specified hose bed or compartment doors are in the open position.

Storage shall be provided for the following;

- One (1) 24' 2-section ladder(s). Manufacturer, model number of the ladder shall be provided in equipment section of specification, or at pre-construction meeting when provided by Greeley Fire Department.
- One (1) 14' roof ladder(s). Manufacturer, model number of the ladder shall be provided in equipment section of specification, or at pre-construction meeting when provided by Greeley Fire Department.
- One (1) 10' length of hard suction hose. Hard suction hose(s) shall be supplied by contractor with completed unit. See equipment section. The support trough shall be made full length so the hose does not sag.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **COMPARTMENT - STREETSIDE REAR**

Located in lower notch area of "T" tank shall be additional storage of long equipment. The compartment shall be integral with the body construction, and will not be bolted or added on modules.

Access to the compartment shall be from a rear facing compartment door. Door shall be fabricated from 3/16" smooth aluminum with full length 14 gauge stainless steel hinge, with 1/4" stainless steel pin, and a lift-turn style latch. A polyester barrier film gasket shall be placed between stainless steel hinge and any dissimilar metals as necessary to prevent corrosion. Door shall overlap body surface to prevent entry of moisture and sealed with automotive type rubber molding to provide a weather resistant seal.

Devices to secure equipment, compartment dividers, or UHMW plastic angles, or sheeting will be used for storage of specified equipment as required to prevent damage to equipment.

The compartment will be designed to store the following equipment:

- One (1) 10' folding ladder (see equipt. list for make/model).
- One (1) pike pole(s). Manufacturer, model number of the pike pole shall be provided in equipment section of specification, or at pre-construction meeting when provided by Greeley Fire Department.

### **SIDE BODY PROTECTION - RUB RAIL**

OnScene Solutions rub rails shall be provided below the compartment door openings on both the streetside and curbside.

The rub rail shall be fabricated from 6063 extruded aluminum, measuring approximately 2-3/4" high x 1-3/8" thick with tapered aluminum end caps. The rub rail shall be bolted to the body using stainless steel bolts and 1-1/2" diameter x 5/8" thick rubber mount isolators to prevent damage to the body.

The rails shall incorporate LED clearance marker lighting recessed into the rail fascia to avoid damage to the light in case of impact. The rub rail shall have an accessory mounting track integrated into the backside of the rail to allow mounting of accessories such as ground lighting.

3M™ Diamond Grade™ Conspicuity striping shall be provided in the rub rail. The striping shall be red in color.

### **FRONT PROTECTION PANELS**

To protect areas subject to intensive wear, scuffing or abuse, protection panels shall be installed on the front vertical body panels and wrapped around to the front compartment door opening. The protection panels shall be fabricated from 20 gauge brushed stainless steel.

### **REAR BODY HANDRAILS**

There shall be two (2) 24" vertical handrails on the rear of the body. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.



# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **PUMP MODULE HANDRAILS**

There shall be two (2) 24" handrails, one (1) each side of pump module for access to upper dunnage area. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

There shall also be (1) additional 7" chrome grab handle positioned at about a 45 degree angle on the top front corner of the body on the streetside for grabbing on to when accessing the folding steps.

### **FOLDING STEP(S)**

There shall be five (5) Cast Products polished cast aluminum folding step(s) provided and installed on completed vehicle. Each step shall be heavy duty with stainless steel spring and textured step surface meeting NFPA standards. Each step will include integrated upper and lower LED lights.

Three (3) steps shall be located on the front of the body on streetside for use in accessing the upper dunnage area, and two (2) steps each side of rear compartment door for use in accessing the hose bed area.

### **LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC**

#### General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

#### Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125 % of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10 %. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

#### Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be

# GREELEY FIRE DEPT

SVI #930

## Production Specs

permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage overcurrent protective devices. Such devices shall be readily accessible and protected against heat in excess of the overcurrent device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- SAE J156, *Fusible Links*
- 1) SAE J553, *Circuit Breakers*
- 2) SAE J554, *Electric Fuses (Cartridge Type)*
- 3) SAE J1888, *High Current Time Lag Electric Fuses*
- 4) SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125 % of maximum current for which the circuit is protected.

### Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

### Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- 5) The propulsion engine and transmission
- 1) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- 2) The radio(s) at a duty cycle of 10 percent transmit and 90 % receive (for calculation and testing purposes, a

# GREELEY FIRE DEPT

SVI #930

## Production Specs

default value of 5 A continuous)

- 3) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- 4) The minimum optical warning system, where the apparatus is blocking the right-of way
- 5) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- 6) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

### Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

### Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

### Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

## **12 VOLT MULTIPLEX CONTROL CENTER**

The apparatus shall be equipped with a Weldon V-MUX multiplexed 12 volt electrical system that will provide complete diagnostic capability, No Exception. The system shall have the capability of delivering multiple signals via a CAN bus, utilizing specifications set forth by SAE J1939. The system shall be node based to maximize stability so that failure of one node does not affect the operation of the other nodes. The system shall use shielded twisted-pair wire for transmission of system function signals. The shielded wire shall provide protection against EMI and RFI noise interruptions.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The multiplex system shall be responsible for providing power management functions as well as load shedding. The warning light system shall be controlled by the multiplex system. The system shall be capable of displaying text and/or graphic messages on a display module. The system shall be based on solid-state technology and shall include self-contained diagnostic indicators.

### **WELDON CERTIFICATION**

A letter shall be provided with bid submittal that the Contractor has successfully completed the Weldon training requirements for Level 1 of the V-MUX Certified Supplier Program and is authorized to design, build, and service V-MUX electrical systems.

The apparatus shall be equipped with a Weldon V-MUX multiplexed 12 volt electrical system that will provide complete diagnostic capability, No Exception. The system shall have the capability of delivering multiple signals via a CAN bus, utilizing specifications set forth by SAE J1939. The system shall be node based to maximize stability so that failure of one node does not affect the operation of the other nodes. The system shall use shielded twisted-pair wire for transmission of system function signals. The shielded wire shall provide protection against EMI and RFI noise interruptions.

The multiplex system shall be responsible for providing power management functions as well as load shedding. The warning light system shall be controlled by the multiplex system. The system shall be capable of displaying text and/or graphic messages on a display module. The system shall be based on solid-state technology and shall include self-contained diagnostic indicators.

### **BATTERY SYSTEM**

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

A master load disconnect switch shall be provided between the starter solenoid(s) and the remainder of the electrical loads on the apparatus. The starter solenoids shall be connected directly to the batteries.

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not

# GREELEY FIRE DEPT

SVI #930

## Production Specs

through the master load disconnect switch.

A green "battery on" pilot light that is visible from the driver's position shall be provided.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within five (5) seconds.

### **BATTERY SWITCH**

One (1) battery "On/Off" switch in cab located within easy reach of Driver with green "BATTERY ON" pilot light that is visible from the driver's position shall be provided. The switch and pilot light shall be supplied and installed by the cab/chassis manufacturer.

### **BATTERY SOLENOID**

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

### **BATTERY CONDITIONER**

The battery conditioner shall be supplied and installed by the cab chassis manufacturer.

### **ENGINE COMPARTMENT LIGHT**

Engine compartment light(s) shall be supplied and installed by the cab chassis manufacturer.

### **REAR SCENE LIGHTS (BACK-UP LIGHTS)**

There shall be a switch on the left side rear to convert backup lights and rear step lights to scene lights during night operations. The switch shall be of momentary style and shall be connected to a bi-stable relay, allowing multiple switching locations. The scene/reverse lights shall automatically shut off when the parking brake is disengaged.

### **CAB HAZARD WARNING LIGHT**

A red flashing or rotating light, located in the driving compartment. The light shall be furnished by the cab/chassis manufacturer. The light shall be illuminated automatically whenever the vehicles parking brake is not fully engaged and any of the following conditions exist:

- 7) Any passenger or equipment compartment door is not closed.
  - Any ladder or equipment rack is not in the stowed position.
  - Stabilizer system is not in its stowed position.
  - Powered light tower is not stowed.
  - Any other device permanently attached to the apparatus is open, extended, or deployed in a manner that is likely to cause damage to the apparatus if the apparatus is moved.

Compartments and equipment meeting all of the following conditions shall be permitted to be exempt from being wired to the hazard light:

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- The volume is less than or equal to 4 ft<sup>3</sup> (0.1 m<sup>3</sup>).
- The compartment has an opening less than or equal to 144 in.<sup>2</sup> (92,900 mm<sup>2</sup>).
- The open door does not extend sideways beyond the mirrors or up above the top of the fire apparatus.
- All equipment in the compartment is restrained so that nothing can fall out if the door is open while the apparatus is moving.
- Manually raised pole lights with an extension of less than 5 ft (1.5 m).

The hazard light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

### **BACK-UP ALARM**

An electronic back-up alarm shall be supplied and installed by the cab/chassis manufacturer. The back-up alarm shall actuate automatically when the transmission gear selector is placed in reverse.

### **TAIL LIGHTS**

Rear body tail lights shall be vertically mounted and located per Federal Motor Vehicle Safety Standards, FMVSS and Canadian Motor Vehicle Safety Standards CMVSS. The following lights shall be furnished;

- Two (2) Whelen amber LED 600 Series 60A00TAR turn signal lights
- Two (2) Whelen red LED 600 Series 60BTT stop/tail lights
- Two (2) Whelen LED 600 Series 60C00WCR maximum intensity back-up lights with clear lens

Each of the lights above shall be mounted in a 6EFLANGE, chrome finish bezel.

### **MIDSHIP MARKER/TURN SIGNAL**

Two (2) Whelen model T0A00MAR 2" round amber LED midship body clearance marker/turn signal lights shall be provided and installed, one (1) light on each side of the body, in forward wheel well of rear axle. Midship marker/turn lights shall be wired to the headlight circuit of the chassis.

### **MARKER LIGHTS**

The body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) and Canadian Motor Vehicle Safety Standards (CMVSS) regulations. All body clearance lights shall be Truck-Lite Model 18 LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

### **CAB STEP LIGHTS / GROUND LIGHTS**

The step lights and/or ground lights shall be supplied and installed by the cab/chassis manufacturer. Light(s) shall be capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting designed to provide illumination on areas under the driver and crew riding area exits shall be switchable but activated automatically when the exit doors are opened.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **LICENSE PLATE LIGHT**

One (1) Arrow #437 chrome plated LED license plate light shall be installed on the rear of the body. License plate light shall be wired to the headlight circuit of chassis. A fastener system shall be provided for license plate installation.

### **ELECTRONIC SIREN**

The siren control head shall be supplied and installed by the cab/chassis manufacturer. Siren power shall be wired through the master warning light switch.

### **SIREN SPEAKER**

The siren speaker(s) shall be supplied and installed by the cab/chassis manufacturer.

### **REAR SCENE LIGHTS**

Two (2) Fire Research Spectra model SPA900-Q70 LED lights shall provided on the upper rear body to light the work area immediately behind the vehicle to a level of at least 3 fc (30 lx) within a 10 ft x 10 ft (3 m x 3 m) square. The lights shall be mounted with four (4) screws to a flat surface. It shall be 6 3/4" high by 9" wide and have a profile of less than 1 3/4" beyond the mounting surface. Wiring shall extend from a weatherproof strain relief at the rear of the lamphead.

Each light shall have twenty-four (24) white LEDs. It shall operate at 12/24 volts DC, draw 6/3 amps and generate 7000 lumens of light. The lens shall redirect the light along the vehicle and out onto the working area. The lamphead housing shall be aluminum with a chrome colored bezel.

The lights shall be switched at the Vista display in the cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

### **TRAFFIC ADVISOR LIGHTS**

The Traffic Advisor shall be comprised of eight (8) Whelen 500 Series TIR6 Super LED lights, individually mounted with chrome bezels to the rear face of the vehicle and evenly distributed, if split by a hose bed, or walkway.

The lights shall be amber with a clear lens and controlled by the multiplexing system and provide Left Arrow, Right Arrow, Center Out and Wig-Wag patterns. The wig-wag light pattern shall be activated with the E-Master and can be switched to the other patterns at anytime through the "TRAFFIC ADVISOR" menu on the Vista Screen.

In addition the left and right light shall indicate with the left and right turn lights.

### **SETCOM INTERCOM SYSTEM**

The following Setcom wireless intercom system shall be provided and installed to improve the safety of firefighters and rescue professionals through enhanced communication and hearing protection. System shall have the following major components as minimum;

# GREELEY FIRE DEPT

SVI #930

## Production Specs

Provide total of four (4) position Setcom intercom system with capabilities of radio transmit at driver and officer positions.

- 1 - IM-900, Master Station
- 1 - RC-18MU4, Radio Cable
- 1 - RIM-9000-BAL, Radio Interface Module
- 2 - CSB-900W3 kit, Wireless Headset w/base
- 1 - JS-900-20, Jumpseat Station, 20' Cable
- 2 - CSB-901W3-3 Kit, Wireless Headset w/base
- 4 - 25-0735-10, Adaptor Cable

The Motorola radio and the AM/FM radio shall be integrated into the intercom system.

### **INTERCOM SYSTEM INSTALLATION**

The above listed intercom system shall be installed in the cab locations as follows;

#### **Front of Cab**

- Driver's – Mounted above the right shoulder position on ceiling.
- Officer's – Mounted above the left shoulder position on ceiling.

#### **Rear Crew Area**

- Driver's side rear facing – Above the right shoulder on the wall or ceiling.
- Driver's side rear facing center – Above the left shoulder on the ceiling.
- Officer's side rear facing – Above the left shoulder on the wall or ceiling.
- Officer's side rear facing center – Above the right shoulder on the ceiling.
- Driver's side forward facing – Above the right shoulder on the rear wall or ceiling.
- Driver's side forward facing center – Above the left shoulder on the rear wall or ceiling.
- Officer's side forward facing – Above the left shoulder on the rear wall or ceiling.
- Officer's side forward facing center – Above the right shoulder on the rear wall or ceiling.

### **WARNING LIGHT PACKAGE**

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four (4) warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four (4) zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.



# GREELEY FIRE DEPT

SVI #930

## Production Specs

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two (2) separate signaling modes during emergency operations. One (1) mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One (1) mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two (2) signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

### **UPPER LEVEL OPTICAL WARNING DEVICES**

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

### **ZONE A - FRONT WARNING LIGHTS**

There shall be one (1) Whelen Edge FN72QLED LED 72" lightbar permanently mounted to the cab roof.

The lightbar configuration (streetside to curbside) shall be:

<u>SECTION</u>	<u>INTERNAL COMPONENTS</u>	<u>LENS COLOR</u>
1	Red Side Linear LED	Clear
2	Red Front Corner Linear LED	Clear
3	Blank	Clear
4	Clear Linear LED	Clear
5	Blank	Clear
6	Red Linear LED	Clear
7	Blank (Opticom if specified)	Clear
8	Blank (Opticom if specified)	Clear
9	Red Linear LED	Clear
10	Blank	Clear
11	Clear Linear LED	Clear

# GREELEY FIRE DEPT

SVI #930

## Production Specs

12	Blank	Clear
13	Red Front Corner Linear LED	Clear
14	Red Side Linear LED	Clear

All clear lights shall shut down when the parking brake is set to comply with "Blocking" mode requirements as outlined in NFPA 1901.

### SHOP NOTES

Add MK8H lightbar mount on Wecad program if there is a brow light on cab

The lightbar shall be separately switched at the vista display in the cab.

### **GTT OPTICOM**

A GTT 795H Opticom emitter light shall be provided inside specified light bar. The Opticom option may replace specified light(s) in specified light bar. The Opticom shall be activated with light bar and de-activated when the park brake is set and the vehicle is in blocking mode.

### SHOP NOTES

792H

### **ZONES B AND D - SIDE WARNING LIGHTS**

#### **UPPER REAR CORNER WARNING LIGHTS**

There shall be two (2) Whelen Engineering L31 series LED beacons (L31HRFN) provided on the rear of the body, one (1) each side in the upper corners. The beacons shall have red lenses.

The lights shall be switched at the Vista display in the cab.

### **LOWER LEVEL OPTICAL WARNING DEVICES**

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1220 mm) above level ground for small apparatus.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

### **ZONE A - FRONT WARNING LIGHTS**

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the Vista display in the cab.

### ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the Vista display in the cab.

### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY WHEELWELL AREA)

There shall be two (2) Whelen 500 series (5" x 2") TIR6 Super-LED lights (50R03ZRR) provided, one (1) each side. Each light shall have a red lens and chrome finished flange.

The lights shall be switched at the Vista display in the cab.

### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the Vista display in the cab.

### ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the Vista display in the cab.

## LINE VOLTAGE ELECTRICAL SYSTEM

### HYDRAULIC GENERATOR SYSTEM

A Harrison HydraGen model 15.0MPC-16D, hydraulic driven generator set shall be installed on the vehicle. The generator shall be rated at 15,000 watts at 120/240 VAC, 125/62 amps, single phase. Current frequency shall be stable at 60 hertz.

A means shall be provided to activate the hydraulic generator system.

If the hydraulic generator system is not capable of output as stated on the power source specification label at all engine speeds, an automatic engine speed control system shall be provided.

If the vehicle is equipped with a fire pump driven by the chassis engine, the generator shall be capable of output as stated on the power source specification label with the engine at idle.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **GENERATOR BONDING**

A minimum of four (4) 16" x 2 gauge copper ground straps shall be bolted to body sub-frame and chassis sub-frame for proper bonding of high voltage system. The conductor shall have a minimum amperage rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated amperage on the power source specification label.

### **GENERATOR MOUNTING**

The hydraulic generator module shall contain all system components necessary to comprise a complete hydraulic generating system. The components shall be grouped and assembled into a compact modular unit.

The generator unit shall be modular, packaged with a heavy steel protective frame. All connections to the module (both hydraulic and electrical) shall be easily removable for easy removal of unit from compartment.

Hydraulic oil reservoir and filter shall be easily accessible with adequate clearance to facilitate oil filling and filter changing.

### **WARRANTY PERIOD**

Provided such goods are operated and maintained in accordance with Harrison's written instructions, Harrison warrants that the MPC series hydraulic generators shall be free from defects in material and workmanship for a period of two (2) years or two thousand (2,000) hours, whichever comes first, from the date of delivery to the first purchaser.

### **HYDRAULIC COMPONENTS**

A hydraulic system filter and strainer shall be provided and shall be located in a readily accessible area.

Hydraulic hose shall meet the hydraulic pump manufacturer's recommendations for pressure, size, vacuum, and abrasion resistance. Hydraulic fittings shall meet the hydraulic pump manufacturer's recommendations for pressure, size, and the type of hose used.

Where the hydraulic hose comes into contact with other surfaces, the hose shall be protected from chafing.

The generator shall be engaged at the driver and officer 12 volt control panels in the cab.

### **GENERATOR MOUNTING**

The generator shall be mounted in an upper dunnage area or roof compartment on rubber vibration isolators. The compartment shall be reinforced and ventilated where necessary to hold weight and provide cooling air for the generator. A valve shall be provided on the generator oil drain outlet and piped to underside of generator compartment with flexible hose and plug. The drain shall be located where easily accessible for generator service.

### **MANUALS AND SCHEMATICS**

Two (2) complete manuals on parts list, maintenance, wiring schematics, hydraulic schematics, circuit boards, voltage regulator board and other components shall be provided on delivery.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### POWER-TAKE-OFF GENERATOR DRIVE

There shall be a "Hot Shift" power-take-off (PTO) installed on the transmission PTO opening of the chassis. The "Hot Shift" PTO is provided to allow the engagement of the PTO at higher engine RPM speeds. The PTO output shall be connected to the generator through hollow tube type driveline with heavy duty universals.

The engagement of the PTO shall be in the chassis cab with a rocker switch and red pilot light to note engagement of the PTO or via the V-Mux screen if so equipped.

The power supply to the PTO engagement control shall be wired to the parking brake and a neutral position transmission switch to prevent engagement unless the vehicle is stopped and transmission has been placed in neutral.

The installation of the engine, transmission, driven accessories (power takeoffs (PTO), etc.) shall meet the engine and transmission manufacturers' installation recommendations for the service intended.

Model part number shall be Chelsea 859XJFJP-B5XV, 123% Ratio.

### LOADCENTER

The loadcenter shall be a Cutler Hammer, BR Series, specifically designed for protection and distribution of 120/240 volt AC, such as lighting and small motor branch circuits. The loadcenter enclosure shall be made of 16 gauge galvanized sheet steel. The galvanized coating provides corrosion protection and as such does not require paint. All trims used on the BR Loadcenter shall be chromate sealed and finished with electro disposition epoxy paint (ASA61) which exceeds requirements for outdoor and indoor applications. A combination surface/flush cover with integral door shall be supplied.

The loadcenter shall be UL/CSA listed, **NO EXCEPTIONS** will be allowed.

### GENERATOR MONITORING PANEL

To properly monitor the generator performance and load demand during operation, the generator installation shall be equipped with a full instrument monitor panel.

This unit shall be a Fire Research FROG-D model FDA100 generator display kit to monitor a single phase, 50/60 Hz, generator. The kit shall include a display module, voltage transformer, two (2) current transformers, and cables. The display module shall consolidate five (5) generator monitoring instruments into one device. The display case shall be waterproof and have dimensions not to exceed 4 1/4" high by 4 1/4" wide by 3 1/4" deep.

The following continuous displays shall be provided with super bright LED digits more than 1/2" high:

- Generator frequency in hertz
- Line 1 current in amperes
- Line 2 current in amperes
- Generator voltage in volts

The program shall support the accumulation of elapsed generator hours and the monitoring of hydraulic oil temperature. Generator hours and oil temperature shall be displayed at the push of a button. Audible warning alarm outputs are provided for generator overload, over/under voltage fluctuations, and high oil temperature.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### SHORE POWER INLET - BATTERY CHARGER

The above mentioned shore power inlet, and battery conditioner shall be specified in the 12 volt section.

### OUTLETS AND CIRCUITS

The generator and or shore power shall supply the 120/240 volt electrical equipment and outlets outlined below. Proper circuit protection shall be installed as noted:

- One (1) Hannay ECR1618-17-18 electric cable reel(s) capable of storing 200' of 10/3 electric cable. Reel(s) shall be designed to hold 110% of the capacity of cord length, with fully enclosed 45 amp, three (3) conductor collector rings. Reel shall be located in upper dunnage area and spool out of upper streetside pump panel area.
  - Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and not be more than 72 in. (1830 mm) above the operator's standing position, and shall be marked with a label indicating its function.
  - A label shall be provided in a visible location adjacent to reel with following information: Current rating, Current type, Phase, Voltage, and Total cord length.
  - The cable reel shall equipped with 200' of 10/3 SEOW yellow cable, a molded plastic ball clamp, and a single heavy duty L5-30 twist-lock female plug at the end.
- One (1) Akron model EJB series, cast aluminum electrical power distribution box with yellow powder coat painted finish shall be provided. The power distribution box shall meet all requirements described in NFPA 1901. The power distribution box shall include the following outlets mounted on a backlit face plate;
  - The electric junction box shall be direct wired to cable on the cord reel. The outlet configuration shall include:
    - One (1) 120 VAC, 5-20 duplex straight-blade receptacle
    - One (1) 120 VAC, 5-20 duplex straight-blade receptacle
    - One (1) 120 VAC, 5-20 duplex straight-blade receptacle
    - One (1) 120 VAC, 5-20 GFCI duplex straight-blade receptacle wired to protect all outlets in box.
  - One (1) Akron formed aluminum treadplate vertical mounting bracket shall be provided for specified power distribution box. Box to be located on upper streetside dunnage area similar to current pumpers.
- The fairlead roller shall be mounted to side of dunnage areas and the cord shall pass through the wall and the fairlead to match existing pumpers.

# GREELEY FIRE DEPT

SVI #930

Production Specs

## LINE VOLTAGE ELECTRICAL SYSTEM

### GENERAL REQUIREMENTS

#### Stability

Any fixed line voltage power source producing alternating current (ac) shall produce electric power at 60 Hz,  $\pm 3$  Hz when producing power at all levels between no load and full rated power. Any fixed line voltage power source shall produce electric power at the rated voltage  $\pm 10$  percent when producing power at all levels between no load and full rated power.

The maximum voltage supplied to portable equipment shall not exceed 275 volts to ground. Higher voltage shall be permitted only when used to operate fixed wired, permanently mounted equipment on the apparatus.

#### Conformance with National Electrical Code

All components, equipment, and installation procedures shall conform to *NFPA 70, National Electrical Code*, except where superseded by the requirements of this chapter. Where the requirements of this chapter differ from those in *NFPA 70*, the requirements in this chapter shall apply.

Where available, line voltage electrical system equipment and materials included on the apparatus shall be listed and used only in the manner for which they have been listed. All equipment and materials shall be installed in accordance with the manufacturer's instructions.

#### Location Ratings

Any equipment used in a dry location shall be listed for dry locations. Any equipment used in a wet location shall be listed for wet locations.

Any equipment, except a PTO-driven generator, used in an underbody or under chassis location that is subject to road spray shall be either listed as Type 4 or mounted in an enclosure that is listed as Type 4.

If a PTO-driven generator is located in an underbody or under chassis location, the installation shall include a shield to prevent road spray from splashing directly on the generator.

#### Grounding

Grounding shall be in accordance with 250.34(A) and 250.34(B) of *NFPA 70*. Ungrounded systems shall not be used.

Only stranded or braided copper conductors shall be used for grounding and bonding.

The grounded current-carrying conductor (neutral) shall be insulated from the equipment-grounding conductors and from the equipment enclosures and other grounded parts.

The neutral conductor shall be colored white or gray in accordance with 200.6, "Means of Identifying Grounded

# GREELEY FIRE DEPT

SVI #930

## Production Specs

Conductors,” of *NFPA 70*.

Any bonding screws, straps, or buses in the distribution panel board or in other system components between the neutral and equipment-grounding conductor shall be removed and discarded.

### Bonding

The neutral conductor of the power source shall be bonded to the vehicle frame. The neutral bonding connection shall occur only at the power source. In addition to the bonding required for the low voltage return current, each body and each driving or crew compartment enclosure shall be bonded to the vehicle frame by a copper conductor.

The conductor shall have a minimum amperage rating, as defined in 310.15, “Ampacities for Conductors Rated 0–2000 Volts,” of *NFPA 70*, of 115 percent of the rated amperage on the power source specification label.

A single conductor that is sized to meet the low voltage and line voltage requirements shall be permitted to be used.

### Ground Fault Circuit Interrupters

In special service vehicles incorporating a lavatory, sink, toilet, shower, or tub, 120 V, 15 or 20 A receptacles within 6 ft (1.8 m) of these fixtures shall have ground fault circuit interrupter (GFCI) protection. GFCIs integrated into outlets or circuit breakers or as stand-alone devices shall be permitted to be used in situations.

### Power Source General Requirements

All power source system mechanical and electrical components shall be sized to support the continuous duty nameplate rating of the power source.

The power source shall be shielded from contamination that would prevent the power source from operating within its design specifications.

### Power Source Rating

For power sources of 8 kW or larger, the power source manufacturer shall declare the continuous duty rating that the power source can provide when installed on fire apparatus according to the manufacturer’s instructions and run at 120°F (49°C) air intake temperature at 2000 ft (600 m) above sea level.

The rating on the power source specification label shall not exceed the declared rating from the power source manufacturer.

Access shall be provided to permit both routine maintenance and removal of the power source for major servicing. The power source shall be located such that neither it nor its mounting brackets interfere with the routine maintenance of the fire apparatus.

### Instrumentation

If the power source is rated at less than 3 kW, a “Power On” indicator shall be provided. If the power source is rated at 3 kW or more but less than 8 kW, a voltmeter shall be provided.

If the power source is rated at 8 kW or more, the following instrumentation shall be provided at an operator’s



# GREELEY FIRE DEPT

SVI #930

## Production Specs

panel:

- Voltmeter
- 1) Current meters for each ungrounded leg
- 2) Frequency (Hz) meter
- 3) Power source hour meter

The instrumentation shall be permanently mounted at an operator's panel. The instruments shall be located in a plane facing the operator. Gauges, switches, or other instruments on this panel shall each have a label to indicate their function.

The instruments and other line voltage equipment and controls shall be protected from mechanical damage and not obstructed by tool mounting or equipment storage.

An instruction plate(s) that provides the operator with the essential power source operating instructions, including the power-up and power-down sequence, shall be permanently attached to the apparatus at any point where such operations can take place.

### Operation

Provisions shall be made for placing the generator drive system in operation using controls and switches that are identified and within convenient reach of the operator.

Where the generator is driven by the chassis engine and engine compression brakes or engine exhaust brakes are furnished, they shall be automatically disengaged for generator operations.

Any control device used in the generator system power train between the engine and the generator shall be equipped with a means to prevent unintentional movement of the control device from its set position in the power generation mode.

If there is permanent wiring on the apparatus that is designed to be connected to the power source, a power source specification label that is permanently attached to the apparatus at the operator's control station shall provide the operator with the information required.

The power source, at any load, shall not produce a noise level that exceeds 90 dBA in any driving compartment, crew compartment, or onboard command area with windows and doors closed or at any operator's station on the apparatus.

### Power Supply Assembly

The conductors used in the power supply assembly between the output terminals of the power source and the main over current protection device shall not exceed 12 ft (4 m) in length.

All power supply assembly conductors, including neutral and grounding conductors, shall have an equivalent ampere rating and shall be sized to carry not less than 115 percent of the ampere of the nameplate current rating of the power source.

If the power supply assembly connects to the vibrating part of a generator (not a connection on the base), the conductors shall be flexible cord or other fine-stranded conductors enclosed in metallic or nonmetallic liquid tight flexible conduit rated for wet locations and temperatures not less than 194°F (90°C).

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### Overcurrent Protection

Manually resettable over current devices shall be installed to protect the line voltage electrical system components.

### Power Source Protection

A main over current protection device shall be provided that is either incorporated in the power source or connected to the power source by a power supply assembly.

The size of the main over current protection device shall not exceed 100 percent of the rated amperage stated on the power source specification label or the rating of the next larger available size over current protection device, where so recommended by the power source manufacturer.

If the main over current protection device is subject to road spray, the unit shall be housed in a Type 4-rated enclosure.

### Branch Circuit Overcurrent Protection

Over current protection devices shall be provided for each individual circuit and shall be sized at not less than 15 amps in accordance with 240.4, "Protection of Conductors," of *NFPA 70*.

Any panel board shall have a main breaker where the panel has six or more individual branch circuits or the power source is rated 8 kW or larger.

Each over current protection device shall be marked with a label to identify the function of the circuit it protects.

Dedicated circuits shall be provided for any large appliance or device (air conditioning units, large motors, etc.) that requires 60 percent or more of the rated capacity of the circuit to which it is connected, and that circuit shall serve no other purpose.

### Panelboards

All fixed power sources shall be hardwired to a permanently mounted panel board unless one of the following conditions exists:

- 4) All line voltage power connections are made through receptacles on the power source and the receptacles are protected by integrated over current devices.
- 1) Only one circuit is hardwired to the power source, which is protected by an integrated over current device.

The panel shall be visible and located so that there is unimpeded access to the panel board controls. All panel boards shall be designed for use in their intended location. The panel(s) shall be protected from mechanical damage, tool mounting, and equipment storage.

Where the power source is 120/240 V and 120 V loads are connected, the apparatus manufacturer or line voltage system installer shall consider load balancing to the extent that it is possible.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### Wiring Methods

Fixed wiring systems shall be limited to the following:

- 2) Metallic or nonmetallic liquid tight flexible conduit rated at temperatures not less than 194°F (90°C) with stranded copper wire rated for wet locations and temperatures not less than 194°F (90°C)
- 1) Type SOW, SOOW, SEOW, or SEOOW flexible cord rated at 600 V and at temperatures not less than 194°F (90°C)

Electrical cord or conduit shall not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring and shall be arranged as follows:

- 2) Separated by a minimum distance of 12 in. (300 mm) from exhaust piping or shielded from such piping
- 1) Separated from fuel lines by a minimum distance of 6 in. (150 mm)

A means shall be provided to allow “flexing” between the driving and crew compartment, the body, and other areas or equipment whose movement would stress the wiring.

Electrical cord or conduit shall be supported within 6 in. (150 mm) of any junction box and at a minimum of every 24 in. (600 mm) of run.

Supports shall be made of nonmetallic materials or of corrosion-resistant or corrosion-protected metal. All supports shall be of a design that does not cut or abrade the conduit or cord and shall be mechanically fastened to the apparatus.

Only fittings and components listed for the type of cord or conduit being installed shall be used.

Splices shall be made only in a listed junction box.

### Additional Requirements for Flexible Cord Installations

Where flexible cord is used in any location where it could be damaged, it shall be protected by installation in conduit, enclosures, or guards.

Where flexible cord penetrates a metal surface, rubber or plastic grommets or bushings shall be installed.

### Wiring Identification

Each line voltage circuit originating from the main panel board shall be identified.

The wire or circuit identification either shall reference a wiring diagram or wire list or shall indicate the final termination point of the circuit.

Where prewiring for future power sources or devices exists, the un-terminated ends shall be marked with a label showing their wire size and intended function.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### Wiring System Components

Only stranded copper conductors with an insulation rated for temperatures of at least 194°F (90°C) and wet locations shall be used. Conductors in flexible cord shall be sized in accordance with Table 400.5(A) of *NFPA 70*. Conductors used in conduit shall be sized in accordance with 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*. Aluminum or copper-clad aluminum conductors shall not be used.

All boxes shall conform to and be mounted in accordance with Article 314, "Outlet, Device, Pull, and Junction Boxes; Conduit Bodies; Fittings; and Manholes," of *NFPA 70*. All boxes shall be accessible using ordinary hand tools. Boxes shall not be permitted behind welded or pop-riveted panels.

The maximum number of conductors permitted in any box shall be in accordance with 314.16, "Number of Conductors in Outlet, Device, and Junction Boxes, and Conduit Bodies," of *NFPA 70*.

All wiring connections and terminations shall provide a positive mechanical and electrical connection. Connectors shall be installed in accordance with the manufacturer's instructions. Wire nuts or insulation displacement and insulation piercing connectors shall not be used.

Each switch shall indicate the position of its contact points (i.e., open or closed) and shall be rated for the continuous operation of the load being controlled. All switches shall be marked with a label indicating the function of the switch. Circuit breakers used as switches shall be "switch rated" (SWD) or better. Switches shall simultaneously open all associated line voltage conductors. Switching of the neutral conductor alone shall not be permitted.

Line voltage circuits controlled by low voltage circuits shall be wired through properly rated relays in listed enclosures that control all non-grounded current-carrying conductors.

### Receptacles and Inlet Devices

#### Wet and Dry Locations

All wet location receptacle outlets and inlet devices, including those on hardwired, remote power distribution boxes, shall be of the grounding type, provided with a wet location cover, and installed in accordance with Section 406.8, "Receptacles in Damp or Wet Locations," of *NFPA 70*.

All receptacles located in a wet location shall be not less than 24 in. (600 mm) from the ground. Receptacles on off road fire apparatus shall be a minimum of 30 in. (750 mm) from the ground. All receptacles located in a dry location shall be of the grounding type and shall be at least 12 in. (300 mm) above the interior floor height. No receptacle shall be installed in a face-up position.

The face of any wet location receptacle shall be installed in a plane from vertical to not more than 45 degrees off vertical.

#### Receptacle Label

Each receptacle shall be marked with a label indicating the nominal line voltage (120 volts or 240 volts) and the current rating in amps of the circuit. If the receptacle is DC or other than single phase, that information shall also be marked on the label.

All receptacles and electrical inlet devices shall be listed to UL 498, *Standard for Safety Attachment Plugs and Receptacles*, or other recognized performance standards.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

Receptacles used for DC voltages shall be rated for DC service.

### Wiring Schematics

An "As-Built" Wiring diagrams for line voltage systems shall be provided to include the following information;

- 2) Pictorial representations of circuit logic for all electrical components and wiring
  - (a) Circuit identification
  - (b) Connector pin identification
  - (c) Zone location of electrical components
  - (d) Safety interlocks
  - (e) Alternator–battery power distribution circuits
  - (f) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems

### **120/240 VAC SCENE LIGHTING**

#### **FRONT CAB-MOUNTED SCENE LIGHT(S)**

Floodlight(s) shall be provided on the front of the cab by the cab/chassis manufacturer. Each light shall be mounted in a brow-style mounting flange with a lens or a means for preventing damage from water spray and listed for wet location usage.

Each light shall be wired directly to the electrical generator system with Carflex conduit and stranded copper wire. The floodlights shall be protected with circuit breakers rated at the proper amperage and wire size.

- (g) The above lights shall be controlled by one (1) rocker switch(es). The rocker switch(es) shall be located in the cab within reach of the Driver and/or Officer.

#### **SIDE UPPER RECESSED SCENE LIGHTS**

Four (4) Fire Research Spectra LED Scene Light model SPA100-J20 lamphead shall be provided. The lamphead mounting arm shall terminate in 3/4" NPT threads. Wiring shall extend from the lamphead mounting arm bottom.

The lamphead shall have sixty (60) ultra-bright white LEDs, 48 for flood lighting and 12 to provide a spot light beam pattern. It shall operate at 240 volts AC, draw 1 amp, and generate 20,000 lumens of light. The lamphead shall have a unique lens that directs flood lighting onto the work area and focuses the spot light beam into the distance. The lamphead angle of elevation shall be adjustable at a pivot in the mounting arm and the position locked with a round knurled locking knob. The lamphead shall be no more than 5 3/8" high by 14" wide by 3 3/4" deep and have a heat resistant handle. The lamphead and mounting arm shall be powder coated. The LED scene light shall be for fire service use.

#### SHOP NOTES

Make: Fire Research

Model: Spectra

PN: SPA260-J15

- (h) The above lights shall be controlled by two (2) rocker switch(es). The rocker switch(es) shall be located in the cab within reach of the Driver and/or Officer.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **SIDE MOUNT PUMP MODULE**

The side mount pump enclosure shall be removable and supported from the chassis frame rails with spring type body mounts. This enclosure shall allow independent flexing of the pump enclosure from the body and allow for quick removal. The support structure shall be constructed of extruded aluminum tubing and angle.

All pump suction and discharge controls are to be mounted on the driver side pump operator's panel so as to permit operation of the pump from a central location. The fire pump, valves and controls shall be accessible for service and maintenance as required by applicable sections of NFPA standards.

The "master" gauges shall be suitably enclosed and mounted on a full pump compartment width "hinged" gauge panel constructed of the same material as the pump operators control panel, allowing access to the backside of all gauges and gauge lines. The individual gauges shall be mounted inline with the control handle or adjacent to the control handle. Panel is to include a stainless steel piano hinge, flush mounted chrome plated trigger latch, and stainless steel cable end stops. Electrical wiring and all gauge lines shall be properly tie wrapped to prevent kinking or cutting of the lines when the panel is opened.

The following controls and equipment shall be provided on the pump panel or within the pump enclosure:

- Electric primer.
- Pump and plumbing area service lights.
  - 1) Pressure control device and throttle control.
  - 2) Fire pump and engine instruments.
  - 3) Pump intakes and discharge controls.
  - 4) Master intake and discharge gauges.
  - 5) Tank fill control.
  - 6) Tank suction control.
  - 7) Water tank level gauge.
  - 8) Pump panel lights.

### **PUMP MODULE SERVICE ACCESS**

The front of pump module shall have a large removable service access door. The door shall be easily removable with lift/turn style latches. Door shall be fabricated from 1/8" treadplate aluminum.

### **PUMP MODULE DUNNAGE AREA**

There shall be an open dunnage area located directly above the pump panels to store miscellaneous Greeley Fire Department supplied equipment. The interior dunnage area side walls shall be fabricated from 1/8" aluminum tread plate, and the walking surface shall be fabricated from 3/16" aluminum NFPA compliant tread plate.

### **PUMP PANEL - SIDE MOUNT**

The pump operator's panel, along with the lower streetside and curbside pump panels shall be constructed of smooth plate aluminum with powder coated paint finish, fastened to the pump enclosure with 1/4" stainless steel bolts.

The instrument area shall have a stainless steel continuous hinge that shall swing towards the front of the module for easy access to gauges.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **STREETSIDE PUMP PANEL - BOLTED**

The streetside pump panel shall be fastened to the pump enclosure with 1/4" stainless steel bolts and nutserts.

### **CURBSIDE PUMP PANEL - BOLTED**

The curbside pump panel shall be fastened to the pump enclosure with 1/4" stainless steel bolts and nutserts.

### **HEATER**

The apparatus shall be provided with one (1) 35,000 BTU hot water type heater(s). The heater(s) shall be connected to the chassis engine cooling system and have three-speed, 12 volt blower. The cooling system lines shall be insulated and be provided with shut-off valves to isolate system, if required.

### **STREETSIDE RUNNING BOARD - SIDE MOUNT PANEL**

The streetside pump panel shall be equipped with a side running board. The running board shall extend along the width of the pump module.

The running board stepping surface shall be constructed of aluminum NFPA compliant tread plate, bolted in place with stainless steel fasteners.

The running board shall contain a hose well with a minimum of 9" width designed to carry 50' of 3.0" hose with hold down provisions.

9) One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.

### **CURBSIDE RUNNING BOARD - SIDE MOUNT PANEL**

The curbside pump panel shall be equipped with a side running board. The running board shall extend along the width of the pump module.

The running board stepping surface shall be constructed of aluminum NFPA compliant tread plate, bolted in place with stainless steel fasteners.

10) One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.

### **PUMP MODULE FINISH**

The upper exterior front, rear, and sides above pump panels shall be constructed of 1/8" treadplate aluminum and will not require any paint.

### **SPEED LAY**

The specified pump module shall have two (2) speed lay(s) located in pump module, or per the itemized compartment list. The speed lay(s) shall be transverse of the pump module or body with access from either side.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **SPEED LAY CONSTRUCTION**

Removable speed lay hose tray(s) shall be formed from 3/16" smooth aluminum with hand hold cut-outs on each end and additional slotted openings along length to allow for water drainage and ventilation. The design of each speed lay(s) shall be constructed to allow a double stack width of each hose size specified.

Stainless steel rollers or Delron blocks shall be provided at each end of the speed lay(s) to assist in deployment and re-loading of fire hose.

Each speed lay(s) shall have two (2) OnScene 9" LED lights provided, one (1) each end to light the interior speed lay hose bed area.

Each speed lay swivel elbow shall be connected to discharge valve with a Class 1 high pressure flex hose with stainless steel couplings.

Each end of hose bed shall have a black nylon style webbing cover. The covers will be mechanically fastened at the top of the hose bed and the bottom edges will be secured using elastic cord and shoulder bolts.

### **WATEROUS CU FIRE PUMP**

A mid-ship mounted Waterous CU series full body fire pump shall be provided. The pump shall comply with all applicable requirements of the latest standards for automotive fire apparatus of the National Fire Protection Association, NFPA 1901, and shall have a rated capacity of 1,500 GPM (6,000 LPM) to 2,250 GPM (9,000 LPM) depending on final configuration.

### **WATEROUS PUMP ANODES**

There shall be two (2) anodes provided with the fire pump. One (1) anode shall be installed in the left steamer port and one (1) shall be installed in the right steamer port.

### **IMPELLERS**

The pump impellers shall be bronze, specifically designed for the fire service and accurately balanced for vibration free running. The stripping edges shall be located on opposite sides of the impellers to reduce shaft deflection.

The impeller shaft shall be stainless steel, accurately ground to size and supported at each end by oil or grease lubricated anti-friction ball bearings for rigid, precise support. The bearings used on the impeller shaft shall be automotive type bearings, easily cross-referenced and readily available at normal parts or bearing stores.

### **FLAME PLATED IMPELLER HUBS**

The impeller hubs shall be flame plated with tungsten carbide to a hardness approximately twice that of tool steel to assure maximum pump life and efficiency. During the flame plating process the base metal shall not be allowed to exceed a temperature of 300 degrees Fahrenheit to prevent altering the metallurgical properties of the impeller material

### **IMPELLER WEAR RINGS**



# GREELEY FIRE DEPT

SVI #930

## Production Specs

The pump shall be equipped with replaceable bronze wear rings for increased pump life and minimum maintenance cost. The wear rings shall be designed to fit into a groove in the face of the impeller hubs forming a labyrinth that, as the clearance increases with age, directs water from the discharge side in several directions eventually exiting outward, away from the eye of the impeller hub.

### **PUMP CASING**

The pump casing shall be cast as two (2) horizontally split pieces. The casing shall be made of high tensile, close-grained gray iron with a minimum tensile strength of 40,000 PSI.

### **PUMP MANUAL**

Two (2) Pump Operation & Maintenance manual(s) shall be supplied at the time of delivery.

### **PAINT FINISH**

The paint finish will be red primer from pump manufacturer.

### **PUMP TRANSMISSION**

The pump transmission shall be of the latest design, incorporating a high strength involute tooth-form Morse Hy-Vo chain capable of operating at high speeds while providing smooth and quiet transmission of power. Drive and driven sprockets shall be made of alloy steel with teeth of an involute form. Driveline shafts shall be made from alloy steel forgings, hardened and ground to size. Deep groove, anti-friction ball bearings shall be used throughout the pump transmission. The pump shift engagement shall be accomplished by a free sliding collar that uses an internal locking mechanism to insure that the collar will stay in road or pump position.

Primary lubrication for the pump transmission bearings, sprockets and chain shall be provided by a splash system. A supplementary pressure system shall also be employed which shall include a strainer, an oil circulation pump driven by the impeller shaft, and a spray bar inside the case to apply oil to the inside of the chain just before it engages the driven sprocket.

The pump and transmission shall be easily separable. A two-piece shaft shall be splined allowing for individual repair of either the pump or transmission, to keep down time to a minimum.

All driveline components shall have a torque rating equal to or greater than the final net engine torque.

### **PUMP LUBRICATION**

Grease zerk(s) shall be installed in a convenient location and connected to the pump lubrication points by copper tubing.

### **AIR OPERATED PUMP SHIFT**

The pump shift actuating mechanism shall be air operated from a valve provided by cab/chassis manufacturer in cab identified as "PUMP SHIFT". Full instructions for shifting the pump shall be inscribed on the valve plate.

Two (2) green indicator lights shall be supplied in the chassis cab. One (1) light shall be energized when the chassis transmission is in neutral and shall be labeled "OK TO PUMP", the second light shall engage when the pump drive (PTO) has been engaged and shall be labeled "PUMP ENGAGED".

# GREELEY FIRE DEPT

SVI #930

## Production Specs

One (1) green indicator light shall be supplied at the Pump Operator's panel adjacent to the engine hand throttle. The green light shall be energized when both the chassis transmission is in neutral and the pump drive (PTO) has been engaged. Green light shall be labeled "OK TO PUMP".

### **PUMP SHIFT MANUAL OVERRIDE**

A manual pump shift override system shall be provided should a problem develop in the chassis air brake system. Controls for the override shall be located at the lower right hand corner of the left side pump panel. A "MANUAL PUMP SHIFT" label shall be provided near the pump shift controls.

### **PAINT FINISH**

The paint finish will be red primer from pump manufacturer.

### **PUMP DRIVELINE**

The pump transmission driveline shall be supplied with 1810 series yokes and bearings to match the cab chass driveline.

### **MECHANICAL SEALS**

The pump shall be equipped with self-adjusting, maintenance free mechanical shaft seals that shall not require manual adjustment. These seals shall be designed in a manner such that they shall remain functional enough to permit continued use of the pump in the unlikely event of a seal failure.

### **TWO-STAGE FIRE PUMP**

The pump shall be a Waterous CMUC20 two-stage centrifugal class "A" rated fire pump, designed specifically for the fire service.

### **TWO-STAGE TRANSFER VALVE**

The transfer valve shall be of the latest ball type design. The valve shall be all bronze construction and incorporate a hydraulically balanced seal to minimize leakage around the ball and assure maximum pump efficiency. The transfer valve shall operate smoothly without sticking, even when it is exposed to sandy or dirty water.

The transfer valve shall be operated by an electric actuator that will be controlled by a switch on the pump operator's panel. There shall be two (2) indicator lights to show when the pump is operating in pressure or volume mode.

### **1/2" PUMP COOLER LINE**

There shall be a 1/2" line installed from the discharge side of the pump to the water tank. The line shall be used to cool the pump during long periods of pumping when water is not being discharged. The pump cooler shall be controlled with a quarter-turn ball valve on operators panel, and shall be clearly labeled "Pump Cooler".

### **PUMP COOLER CHECK VALVE**

There shall be a check valve installed in the pump cooler line to prevent tank water from back flowing into the pump when it is not in use.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **WATEROUS FIVE YEAR PUMP WARRANTY**

The fire pump shall be warranted by Waterous for a period of five (5) years from the date of delivery to the Greeley Fire Department.

### **MANUFACTURER FIRE PUMP TEST**

The pump shall undergo a manufacturer's test per applicable sections of NFPA 1901 standards, prior to delivery of the completed apparatus.

The test shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming device tests, and the vacuum test.

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 500 psi (3400 kPa) for a minimum for 10 min. The pump shall be fully tested at the pump manufacturer's factory to the performance specifications as outlined by applicable NFPA 1901 standards.

The results of this test shall be furnished with the vehicle on delivery.

### **FIRE PUMP TEST LABEL**

A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve

The pump shall comply with the applicable requirements of "Standard for Fire Apparatus 1901, latest edition.

The pump shall be capable of producing fire streams that are free from objectionable pulsation under all normal operating conditions.

### **ALTITUDE REQUIREMENT**

The apparatus shall be designed to meet the specified rating at 5,000 feet (1,525 meters) altitude.

### **PUMP DRAIN VALVE**

A manifold drain valve assembly shall be supplied. This drain shall provide the capability to drain the entire pump by pulling a single control. The valve assembly shall consist of a stainless steel plunger in a bronze body with multiple ports.

### **PUMP DRAIN CONTROL**

The pump drain shall be controlled at the pump operator's panel and identified as "Pump Drain". The control shall be provided in the form of a "T" handle control that is easily actuated with a gloved hand.

### **ELECTRIC PRIMING PUMP CONTROL AT PUMP PANEL**

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The Waterous priming system shall include an oil-free rotary vane priming pump rigidly attached to the pump transmission and activated by a vacuum-activated priming (VAP) valve. Valve actuation may be accomplished while the main pump is in operation, if necessary to assure a complete prime.

The primer shall be capable of priming the pump through a 20' section of suction hose with a 10' lift within 30 seconds for pumps less than 1,500 gpm, and 45 seconds for pumps 1,500 gpm and larger.

### **PRIMER CONTROL**

The priming system shall be controlled at the pump operator's panel. The control shall be provided in the form of a momentary push button that is easily actuated with a gloved hand.

### **DISCHARGE RELIEF VALVE**

The discharge pressure relief shall be controlled by the electronic engine controlled device as specified.

### **6" SUCTION INLET - STREETSIDE**

One (1) 6" (150 mm) ungated suction intake shall be installed on the streetside pump panel to supply the fire pump from an external water supply. The threads shall be 6" NH male threads.

The intake shall be provided with a removable screen.

### **LONG SUCTION TUBE**

The specified pump intake shall be provided with a long suction tube. Suction tube shall have built-in zinc anode protection and multiple suction flanges per pump configuration.

### **SUCTION CAP**

The suction inlet shall be equipped with a 6" NH chrome plated, long handled, cap capable of withstanding 500 psi.

### **6" SUCTION INLET - CURBSIDE**

One (1) 6" (150 mm) ungated suction intake shall be installed on the curbside pump panel to supply the fire pump from an external water supply. The threads shall be 6" NH male threads.

The intake shall be provided with a removable screen.

### **LONG SUCTION TUBE**

The specified pump intake shall be provided with a long suction tube. Suction tube shall have built-in zinc anode protection and multiple suction flanges per pump configuration.

### **SUCTION CAP**

The suction inlet shall be equipped with a 6" NH chrome plated, long handled, cap capable of withstanding 500 psi.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **HEAT EXCHANGER**

A heat exchanger shall be provided on the pump driving engine cooling system that uses water from the discharge side of the pump to cool the engine coolant through the use of a closed heat exchanger. The water from the pump and the engine coolant shall not be intermixed. This cooling system shall be controlled by a 1/4 turn valve on the pump operator's panel.

### **INTAKE RELIEF VALVE**

There shall be an Akron model 59 intake relief valve factory set to 125 PSI installed on the suction side of the pump. The system shall be controlled by an adjustable valve and designed to prevent vibration from altering the setting of the valve. Provisions for adjusting or servicing the valve {will/shall} be provided. The relief outlet shall be directed below the pump with the discharge terminating in a 2-1/2" NSTM connection. The discharge shall be away from the pump operator and labeled "DO NOT CAP".

### **PLUMBING SPECIFICATIONS**

The fire pump plumbing system shall be of rigid or flexible piping with stainless steel fittings. Victaulic couplings shall be installed to permit flexing of the plumbing system and allow for quick removal of piping or valves for service. Flexible hose couplings shall be threaded stainless steel or Victaulic connections.

The fire pump and plumbing shall be hydrostatically tested in compliance to applicable sections of NFPA standards, with test results submit with the delivery documentation.

### **STAINLESS STEEL INTAKE MANIFOLD**

The suction manifold assembly shall be fabricated with Schedule #10 type 304 stainless steel. All threaded fittings shall be a minimum of Schedule 10 stainless steel. The suction manifold assembly shall have radiused sweep elbows to minimize water turbulence into the suction volute.

The suction manifold shall be welded and pressure tested prior to installation. The stainless steel manifold assembly shall be attached to the pump intake volute with a heavy-duty, flexible Victaulic coupling.

### **STAINLESS STEEL DISCHARGE MANIFOLD**

The discharge manifold assembly shall be fabricated with Schedule #10 type 304 stainless steel. All threaded fittings shall be a minimum of Schedule 10 stainless steel. The discharge manifold assembly shall have radiused sweep elbows to minimize water turbulence into the discharge header.

The manifold shall be welded and pressure tested prior to installation. The stainless steel manifold assembly shall be attached to the pump intake volute with a heavy-duty, flexible Victaulic coupling.

### **STAINLESS STEEL PLUMBING WARRANTY**

The stainless steel plumbing shall be free of defects in material and workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

The contractor shall supply details of their warranty information with their bid submission.

### **INTAKES**

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The pump shall have a sufficient number and size of intakes to perform the apparatus pump system certification test. The intakes shall have male National Hose Threads (NST) if the apparatus is to be used in the United States.

If the couplings on the suction hose carried on the apparatus are of a different size from that of the pump intake(s) or have means of hose attachment other than that provided on the intake(s), an adapter(s) shall be provided to allow connection of the suction hose to the pump intake(s).

A sign shall be provided on the pump operator's panel that states the following:

**WARNING:** Death or serious injury might occur if proper operating procedures are not followed. The pump operator as well as individuals connecting supply or discharge hoses to the apparatus must be familiar with water hydraulics hazards and component limitations.

Each intake shall have a removable or accessible strainer inside the connection. The strainer(s) shall restrict spherical debris that is too large to pass through the pump.

At least one valved intake shall be provided that can be controlled from the pump operator's position. The valve and piping shall be a minimum 2-1/2 in. (65 mm) nominal size.

If the intake is 2-1/2 in. (65 mm) nominal size, the intake shall be equipped with a female swivel coupling with NH threads. Any 3 in. (75 mm) or larger intake valve except the tank-to-pump intake valve shall be a slow-operating valve.

Each valved intake shall be equipped with a bleeder valve having a minimum 3/4 in. (19 mm) pipe thread connection to bleed off air or water. The bleeder valve shall be operational without the operator having to get under the apparatus. If a valved appliance is attached to an intake, it shall be equipped with a 3/4 in. (19 mm) bleeder valve on each intake. Bleeder valves for valved intakes 4 in. (100 mm) and larger not located at the pump operator's panel shall be located where the bleeder valve controls are visible and operationally functional while the operator remains stationary at the valved intake position.

Each valved intake having a connection size larger than 3 in. (75 mm) shall be equipped with an adjustable automatic pressure relief device installed on the supply side of the valve to bleed off pressure from a hose connected to the valved intake.

All intakes shall be provided with caps or closures capable of withstanding a hydrostatic gauge pressure of 500 psi (3400 kPa). Intakes having male threads shall be equipped with caps; intakes having female threads shall be equipped with plugs. Where adapters for special threads or other means for hose attachment are provided on the intakes, closures shall be provided for the adapters in lieu of caps or plugs. Caps or closures for intake connections smaller than 4 in. (100 mm) shall remain secured to the apparatus when removed from the connection.

If the suction inlets are to be equipped with a valve, siamese, or adapter that will remain in place while the apparatus is in motion, that valve, siamese, or adapter shall not project beyond the apparatus running board. The purchaser shall specify if any valve, siamese, or adapter is to be permanently installed on an intake and identify the brand and model of such item.

The completed apparatus shall have the following intake(s);

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **STREETSIDE INTAKE - 2-1/2"**

There shall be one (1) 2-1/2" (65 mm) gated intake(s) located on pump panel. Each intake shall include:

- One (1) Akron Brass 8800 series, manual type 2-1/2" (65 mm) valve(s). Each valve shall be equipped with a brass type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a handle for direct valve operation through panel.
- Each intake shall have a 2-1/2" (65 mm) NSTF chrome swivel adapter with strainer provided.
  - The specified adapter shall be provided with a 2-1/2" (65 mm) NSTM chrome plated plug with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.

### **CURBSIDE INTAKE - 2-1/2"**

There shall be one (1) 2-1/2" (65 mm) gated intake(s) located on pump panel. Each intake shall include:

- One (1) Akron Brass 8800 series, manual type 2-1/2" (65 mm) valve(s). Each valve shall be equipped with a brass type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a handle for direct valve operation through panel.
- Each intake shall have a 2-1/2" (65 mm) NSTF chrome swivel adapter with strainer provided.
  - The specified adapter shall be provided with a 2-1/2" (65 mm) NSTM chrome plated plug with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.

### **TANK TO PUMP CHECK VALVE**

There shall be a check valve between the pump suction and the booster tank valve. The check valve shall eliminate back flow into the water tank when the pump is connected to a pressurized source.

### **TANK TO PUMP VALVE**

A 4" (100 mm) full flow ball valve shall be installed between the fire pump and the water tank. The connection between the tank and the pump shall be capable of the flow recommendations as set forth in the latest edition of NFPA 1901. The valve shall be flanged to bolt directly to the pump and shall incorporate a chromium plated bronze ball. The remaining internal moving parts shall be stainless steel for years of dependable service. A non collapsible flexible hose shall be incorporated into the tank to pump plumbing to allow movement in the line as the chassis flexes to avoid damage during normal road operation.

The tank to pump valve shall be controlled from the pump operator's panel.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
- An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.

### **DISCHARGES**

A minimum of two 2-1/2 in. (65 mm) outlets shall be provided on any pump rated at 750 gpm (3000 L/min) or greater, and a minimum of one 2-1/2 in. (65 mm) outlet shall be provided on any pump rated at less than 750 gpm (3000 L/min).

All 1-1/2" (65 mm) or larger discharge outlet connections shall be equipped with male National Hose Threads (NST). Adapters with special threads or other means for hose attachment shall be permitted to be attached to any outlets.

The piping and valves supplying any preconnected 1-1/2 in. (38 mm), 1-3/4 in. (45 mm), or 2 in. (52 mm) hose line, including the piping to the preconnected hose storage areas shall be at least 2 in. (52 mm) in size.

All discharge outlet connections, except connections to which a hose will be preconnected, shall be equipped with caps or closures capable of withstanding a hydrostatic gauge pressure of 100 psi (700 kPa) over the maximum pump close-off pressure or 500 psi (3400 kPa), whichever is greater.

Where adapters are provided on the discharge outlet connections, the closures shall fit on the adapters.

Caps or closures for outlet connections smaller than 4 in. (100 mm) shall remain secured to the apparatus when removed from the connection.

Each discharge outlet shall be equipped with a valve that can be opened and closed smoothly at pump discharge gauge pressures of 250 psi (1700 kPa).

The flow-regulating element of each valve shall not change its position under any condition of operation that involves discharge pressures to the maximum pressure of the pump; the means to prevent a change in position shall be incorporated in the operating mechanism and shall be permitted to be manually or automatically controlled.

Any 3 in. (75 mm) or larger discharge valve shall be a slow-operating valve.

All 1-1/2 in. (38 mm) or larger discharge outlets shall be equipped with a drain or bleeder valve having a minimum 3/4 in. (19 mm) pipe thread connection for draining or bleeding off pressure from a hose connected to the outlet.

Any 2 in. (52 mm) or larger discharge outlet that is located more than 42 in. (1070 mm) off the ground to which hose is to be connected and that is not in a hose storage area shall be supplied with a sweep elbow of at least 30 degrees downward.

The completed apparatus shall have the following discharge(s);

### **FRONT DISCHARGE**



# GREELEY FIRE DEPT

SVI #930

## Production Specs

There shall be one (1) 2" (52 mm) gated discharge(s) located on pump panel. Each discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8600 series, actuated type 2" (52 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
  - An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.
- There shall be a 2" (52 mm) VFC x 1-1/2" (38 mm) NSTM chrome plated 90 degree swivel elbow provided for each discharge.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- One (1) Fire Research Insight model FPA402 combination digital flowmeter and pressure indicator kit(s) with blue backlighting and color coded bezel shall be provided. The kit shall include a flowmeter/pressure display module, paddlewheel flow sensor, flow sensor housing with a mount for proper sized plumbing, pressure sensor, and interconnecting J1939 data link cable.

### **STREETSIDE DISCHARGE**

There shall be two (2) 2-1/2" (65 mm) gated discharge(s) located on pump panel. Each discharge shall include:

- Two (2) of the discharge(s) shall flow water only.
- Two (2) Akron Brass 8600 series, actuated type 2-1/2" (65 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
  - An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated 30 degree downsweep elbow provided.
  - The specified elbow shall be provided with a 2-1/2" (65 mm) NSTF chrome plated cap with chain.
- Two (2) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- Two (2) Fire Research Insight model FPA402 combination digital flowmeter and pressure indicator kit(s) with blue backlighting and color coded bezel shall be provided. The kit shall include a flowmeter/pressure display

# GREELEY FIRE DEPT

SVI #930

## Production Specs

module, paddlewheel flow sensor, flow sensor housing with a mount for proper sized plumbing, pressure sensor, and interconnecting J1939 data link cable.

### **CURBSIDE DISCHARGE**

There shall be one (1) 2-1/2" (65 mm) gated discharge(s) located on pump panel. Each discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8600 series, actuated type 2-1/2" (65 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
  - An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated 30 degree downsweep elbow provided.
  - The specified elbow shall be provided with a 2-1/2" (65 mm) NSTF chrome plated cap with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- One (1) Fire Research Insight model FPA402 combination digital flowmeter and pressure indicator kit(s) with blue backlighting and color coded bezel shall be provided. The kit shall include a flowmeter/pressure display module, paddlewheel flow sensor, flow sensor housing with a mount for proper sized plumbing, pressure sensor, and interconnecting J1939 data link cable.

There shall be one (1) 4" (100 mm) gated discharge(s) located on pump panel. Each discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8600 series slow-operating, actuated type 4" (100 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
  - An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.
- Each discharge shall have a 4" (100 mm) rocker lug NSTF swivel x 5" (125 mm) Storz hardcoat finish 30 degree downsweep elbow provided.
  - The specified elbow shall be provided with a 5" (125 mm) Storz cap hardcoat finish with chain.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- One (1) Fire Research Insight model FPA402 combination digital flowmeter and pressure indicator kit(s) with blue backlighting and color coded bezel shall be provided. The kit shall include a flowmeter/pressure display module, paddlewheel flow sensor, flow sensor housing with a mount for proper sized plumbing, pressure sensor, and interconnecting J1939 data link cable.

### **MISCELLANEOUS DISCHARGE**

#### **HOSE BED DISCHARGE(S)**

There shall be two (2) 2-1/2" (65 mm) gated discharge(s) located in the hose bed area. Each discharge shall include:

- Two (2) of the discharge(s) shall flow water only.
- Two (2) Akron Brass 8600 series, actuated type 2-1/2" (65 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
  - An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.
- There shall be a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated long adapter provided for hose bed discharge(s).
- Two (2) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- Two (2) Fire Research Insight model FPA402 combination digital flowmeter and pressure indicator kit(s) with blue backlighting and color coded bezel shall be provided. The kit shall include a flowmeter/pressure display module, paddlewheel flow sensor, flow sensor housing with a mount for proper sized plumbing, pressure sensor, and interconnecting J1939 data link cable.

#### **2" SPEED LAY(S)**

There shall be two (2) 2" speed lay(s) located in pump module, or per the itemized compartment list. The speedlay(s) shall be transverse of the pump module or body with access from either side.

Each speed lay shall have a minimum storage capacity of 200' of 1-3/4" double jacket hose and nozzle.

- Two (2) of the discharge(s) shall flow water only.
- Two (2) Akron Brass 8600 series, actuated type 2" (52 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

- Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
- An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.
- There shall be a 2" (52 mm) VFC x 1-1/2" (38 mm) NSTM chrome plated 90 degree swivel elbow provided for each discharge. The elbow shall have the shortest size available so as not to hang down into the speedlay bed.
- Two (2) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- Two (2) Fire Research Insight model FPA402 combination digital flowmeter and pressure indicator kit(s) with blue backlighting and color coded bezel shall be provided. The kit shall include a flowmeter/pressure display module, paddlewheel flow sensor, flow sensor housing with a mount for proper sized plumbing, pressure sensor, and interconnecting J1939 data link cable.

### **DECK GUN**

There shall be one (1) 3" (75 mm) gated discharge located on the upper deck above the pump compartment, offset to streetside. Piping shall rise high enough for a mounted deluge gun to be operated in a 360 degree circle to a lower angle of 15 degrees without being impeded by any part of the apparatus or equipment.

The discharge plumbing shall terminate as required by deck gun model. The discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8600 series slow-operating, actuated type 3" (75 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
  - An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- One (1) Fire Research Insight model FPA402 combination digital flowmeter and pressure indicator kit(s) with blue backlighting and color coded bezel shall be provided. The kit shall include a flowmeter/pressure display module, paddlewheel flow sensor, flow sensor housing with a mount for proper sized plumbing, pressure sensor, and interconnecting J1939 data link cable.

### **DECK GUN MONITOR**

An Akron Apollo Hi-Riser model 3433 lift-off style deck monitor with 1,250 GPM capacity, manually controlled deck gun shall be provided with ability to rise over obstacles on top of the apparatus. To elevate pull a pin and

# GREELEY FIRE DEPT

SVI #930

## Production Specs

raise the discharge 24" above the deck. Hi-Riser also rotates easily down to a low profile position for portable operation and comes complete with automatic drain valve. The deck gun shall have the following features;

- 360° rotation when mounted in the deck mode, 180° in the portable mode
- Vertical travel from 90° above to 45° below horizontal, with built-in 35° safety stop
- 3" waterway with cast-in turning vanes for efficient flow
- Direct mount - a combination 3" NPT female and 3" flange
- Can be used in portable mode with standard Apollo ground bases

### **TELESCOPING WATERWAY**

No deck gun riser shall be provided on completed unit.

### **DECK GUN STOW LIGHT**

The specified deck gun shall be provided with a deck gun stow light and wired to cab hazard warning light in cab.

### **MASTER STREAM TIP**

The specified deck gun shall be provide with an Akron Akromatic model 5160 Pyrolite automatic, master stream tip capable of flowing 1,250 GPM.

### **STACKED TIPS**

The specified deck gun shall be provide with an Akron model 2499 Pyrolite quad stacked deluge tips, and an Akron model 3488 Pyrolite, 3-1/2" F x 3" M cast discharge pipe.

### **GROUND BASE**

The specified deck gun shall be provide with an Akron dual 2-1/2" inlet ground base.

There shall be an 8" spacer installed on the ground base to raise up the deck gun in the portable position.

### **TANK FILL VALVE**

There shall be one (1) 2" (52 mm) tank fill valve plumbed with 2" plumbing from the pump to the tank. Installation shall be completed with 2" rubber hose and stainless steel hose couplings. The tank fill valve shall be controlled from the operator's control panel.

- One (1) Akron Brass 8800 series, manual type 2" (52 mm) valve(s). Each valve shall be equipped with a brass type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a handle for direct valve operation through panel.

### **PUMP PANEL**

The side mount pump controls shall be mounted on an aluminum control panel which shall have a black powdercoat painted finish. The panel shall be hinged, or bolted in place allowing it to be easily removed to gain access to plumbing components.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The driverside panel will be a split design with valve controls on one section and valve intake and discharges on lower section.

### **PUMP PANEL LOCATION**

The pump control panel shall be side mounted.

The pump panel shall include the following items;

### **ENGINE GAUGES**

The cab/chassis engine gauges shall be provided with the specified pump pressure governor system.

### **PRESSURE GOVERNOR and ENGINE MONITORING DISPLAY**

A Fire Research PumpBoss series PBA400-A00 pressure governor and monitoring display kit shall be installed. The kit shall include a control module, intake pressure sensor, discharge pressure sensor, and cables. The control module case shall be waterproof and have dimensions not to exceed 6 3/4" high by 4 5/8". The control knob shall be 2" in diameter with no mechanical stops, have a serrated grip, and a red idle push button in the center. It shall not extend more than 1 3/4" from the front of the control module. Inputs for monitored engine information shall be from a J1939 databus or independent sensors. Outputs for engine control shall be on the J1939 databus or engine specific wiring. Inputs from the pump discharge and intake pressure sensors shall be electrical.

The following continuous displays shall be provided:

- Engine RPM; shown with four daylight bright LED digits more than 1/2" high
- Check engine and stop engine warning LEDs
- Engine oil pressure; shown on a dual color (green/red) LED bar graph display
- Engine coolant temperature; shown on a dual color (green/red) LED bar graph display
- Transmission Temperature: shown on a dual color (green/red) LED bar graph display
- Battery voltage; shown on a dual color (green/red) LED bar graph display
- Pressure and RPM operating mode LEDs
- Pressure / RPM setting; shown on a dot matrix message display
- Throttle ready LED.

A dot-matrix message display shall show diagnostic and warning messages as they occur. It shall show monitored apparatus information, stored data, and program options when selected by the operator. All LED intensity shall be automatically adjusted for day and night time operation.

The program shall store the accumulated operating hours for the pump and engine to be displayed with the push of a button. It shall monitor inputs and support audible and visual warning alarms for the following conditions:

• High Battery Voltage	• Low Engine Oil Pressure
• Low Battery Voltage (Engine Off)	• High Engine Coolant Temperature
• Low Battery Voltage (Engine Running)	• Out of Water (visual alarm only)
• High Transmission Temperature	• No Engine Response (visual alarm only).

# GREELEY FIRE DEPT

SVI #930

## Production Specs

The program features shall be accessed via push buttons located on the front of the control module. There shall be a USB port located at the rear of the control module to upload future firmware enhancements.

The governor shall operate in two control modes, pressure and RPM. No discharge pressure or engine RPM variation shall occur when switching between modes. A throttle ready LED shall light when the interlock signal is recognized. The governor shall start in pressure mode and set the engine RPM to idle. In pressure mode the governor shall automatically regulate the discharge pressure at the level set by the operator. In RPM mode the governor shall maintain the engine RPM at the level set by the operator except in the event of a discharge pressure increase. The governor shall limit a discharge pressure increase in RPM mode to a maximum of 30 psi. Other safety features shall include recognition of no water conditions with an automatic programmed response and a push button to return the engine to idle.

The pressure governor and monitoring pressure display shall be programmed at installation for a specific engine.

### **MASTER DISCHARGE GAUGE**

There shall be one (1) Innovative Controls/NoShok 4" liquid filled gauge to display the Master Discharge Pressure. Gauge shall be labeled "MASTER DISCHARGE".

### **MASTER INTAKE GAUGE**

There shall be one (1) Innovative Controls/NoShok 4" liquid filled gauge to display the Master Intake Pressure. Gauge shall be labeled "MASTER INTAKE".

- This gauge(s) shall have a white background with black text.
- The above gauge(s) shall have a range from -30" to 600 PSI.

### **COLOR CODED LABELS**

The pump panel shall have Innovative Controls Inc. color coded die cast zinc, chrome plated bezels with plastic labels inserts for each intake, discharge, master gauges, and drain. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

### **PUMP PANEL LIGHTING**

All gauges and controls on the pump operator's panel shall be adequately illuminated by a full panel width shielded light assembly with full width OnScene Solutions LED light (each panel, if equipped). The light shall be activated by a weather-proof type switch on the pump operator's panel as well as automatically when pump is engaged. This switch shall also activate any area step lighting.

### **PUMP PANEL AIR HORN SWITCH**

A switch to activate the cab/chassis air horn(s) shall be provided on pump panel. Switch shall be constantly illuminated and labeled.

### **TEST TAPS**

Test taps for pump intake and pump pressure shall be provided on the pump instrument panel and be properly labeled.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **DIGITAL FLOWMETER REMOTE**

A Fire Research Insight model DFA400-000 digital flowmeter remote display module shall be installed and used to total all discharge flows. The flowmeter case shall be waterproof, manufactured of anodized machined aluminum, and have dimensions not to exceed 3 1/4" high by 3 1/4" wide by 2 1/2" deep. It shall have an LED display with super bright digits more than 1/2" high.

The remote display shall receive input information over a datalink from a Fire Research Insight primary display. It shall mirror the primary display or be programmable for summing and accumulating functions. A 10' cable shall be provided to connect the datalink. The remote indicator shall have the same program as the primary so that the two indicators are interchangeable.

### **POLY WATER TANK**

The water tank capacity shall be approximately 500 US gallon or 416 Imperial gallons. Certification of the tank capacity shall be recorded on the manufacturer's record of construction and shall be provided to the purchaser upon delivery of the apparatus.

### **CONSTRUCTION**

The tank must be designed and fabricated by a tank manufacturer that is ISO 9001:2008 certified. The ISO certification must be to the current standard in effect at the time of the design and fabrication of the tank.

The water tank shall be of a specific configuration and designed to be completely independent of the body and compartments. Joints and seams shall be fused using nitrogen gas as required and tested for maximum strength and integrity. The tank construction shall include PolyProSeal™ technology wherein a sealant shall be installed between the plastic components prior to being fusion welded. This sealing method will provide a liquid barrier offering leak protection in the event of a weld compromise. The top of the booster tank is fitted with removable lifting assembly designed to facilitate tank removal. The transverse and longitudinal swash partitions shall be manufactured of a minimum of 3/8" PT3™ polypropylene. All partitions shall be equipped with vent and air holes to permit movement of air and water between compartments. The partitions shall be designed to provide maximum water flow. All swash partitions interlock with one another and are completely fused to each other as well as to the walls of the tank. All partitions and spacing shall comply with NFPA 1901. The walls shall be welded to the floor of the tank providing maximum strength as part of the tank's unique Full Floor Design™. Tolerances in design allow for a maximum variation of 1/8" on all dimensions.

### **WATER FILL TOWER AND COVER**

The tank shall have a combination vent and manual fill tower. The fill tower shall be constructed of 1/2" PT3™ polypropylene and shall be a minimum dimension of 8" x 8" outer perimeter. The fill tower shall be blue in color indicating that it is a water-only fill tower. The tower shall be located in the left front corner of the tank unless otherwise specified by the tank manufacturer to the purchaser. The tower shall have a 1/4" thick removable polypropylene screen and a PT3™ polypropylene hinged cover. The capacity of the tank shall be engraved on the top of the fill tower lid. Inside the fill tower there shall be a combination vent/overflow pipe. The vent overflow shall be a minimum of schedule 40 polypropylene pipe with a minimum I.D. of 4" that is designed to run through the tank, and shall be piped to discharge water behind the rear wheels as required in NFPA 1901 so as to not interfere with rear tire traction.

The tank cover shall be constructed of 1/2" thick PT3™ polypropylene and UV stabilized, to incorporate a multi-piece locking design, which allows for individual removal and inspection if necessary. The tank cover(s) shall be



# GREELEY FIRE DEPT

SVI #930

## Production Specs

flush or recessed 3/8" from the top of the tank and shall be fused to the tank walls and longitudinal partitions for maximum integrity. Each one of the covers shall have hold downs consisting of 2" minimum polypropylene dowels spaced a maximum of 40" apart. These dowels shall extend through the covers and will assist in keeping the covers rigid under fast filling conditions. A minimum of two lifting dowels shall accommodate the necessary lifting hardware.

### **SUMP**

There shall be one (1) sump standard per tank. The sump shall be constructed of a minimum of 1/2" PT3™ polypropylene and be located in the left front quarter of the tank, unless specified otherwise. On all tanks that require a front suction, a 3" schedule 40 polypropylene pipe shall be installed that will incorporate a dip tube from the front of the tank to the sump location. The sump shall have a minimum 3" N.P.T. threaded outlet on the bottom for a drain plug per NFPA. This shall be used as a combination clean-out and drain. All tanks shall have an anti-swirl plate located approximately 3" above the inside floor.

# GREELEY FIRE DEPT

SVI #930

## Production Specs

### **OUTLETS**

There will be two (2) standard tank outlets: one for the tank-to-pump suction line, which shall be sized to provide adequate water flow to the pump; and, one for tank fill line, which shall be sized according to the NFPA minimum size chart for booster tanks. All tank fill couplings shall be backed with flow deflectors to break up the stream of water entering the tank, and be capable of withstanding sustained fill rates of up to 1000 G.P.M. The addition of rear suction fittings, nurse valve fittings, dump valve fittings, and through-the-tank sleeves to accommodate rear discharge piping must be specified. All auxiliary outlets and inlets must meet all NFPA guidelines in effect at the time of manufacture.

### **MOUNTING**

The tank shall rest on the body cross members in conjunction with such additional cross members, spaced at a distance that would not allow for more than 530 square inches of unsupported area under the tank floor. In cases where overall height of the tank exceeds 40 inches, cross member spacing must be decreased to allow for not more than 400 square inches of unsupported area.

The tank must be isolated from the cross members through the use of hard rubber strips with a minimum thickness and width dimension of 1/4" x 1" and a Shore A Hardness of approximately 60 durometer. The rubber must be installed so it will not become dislodged during normal operation of the vehicle. Additionally, the tank must be supported around the entire bottom outside perimeter and captured both in the front and rear as well as side to side to prevent tank from shifting during vehicle operation.

A picture frame type cradle mount with a minimum of 2" x 2" x 1/4" mild steel, stainless steel, or aluminum angle shall be provided or the use of corner angles having a minimum dimension of 4" x 4" x 1/4" by 6" high are permitted for the purpose of capturing the tank.

Although the tank is designed on a free floating suspension principle, it is required that the tank have adequate vertical hold down restraints to minimize movement during vehicle operation. If proper retention has not been incorporated into the apparatus hose floor structure, an optional mounting restraint system shall be located on top of the tank, half way between the front and the rear on each side of the tank. These stops can be constructed of steel, stainless steel or aluminum angle having minimum dimensions of 3" x 3" x 1/4" and shall be approximately 6" to 12" long. These brackets must incorporate rubber isolating pads with a minimum thickness of 1/4" inch and a hardness of 60 durometer affixed on the underside of the angle. The angle should then be bolted to the body side walls of the vehicle while extending down to rest on the top outside edge of the upper side wall of the tank. Hose beds floors must be so designed that the floor slat supports extend full width from side wall to side wall and are not permitted to drop off the edge of the tank or in any way come in contact with the individual covers where a puncture could occur. Tank top must be capable of supporting loads up to 200 lbs per sq. foot when evenly distributed. Other equipment such as generators, portable pumps, etc. must not be mounted directly to the tank top unless provisions have been designed into the Poly-Tank® III for that purpose. The tank shall be completely removable without disturbing or dismantling the apparatus structure.

### **CENTER OF GRAVITY**

A center of gravity calculation shall be determined for each tank and provided as requested in order to provide the apparatus manufacturer with the necessary data to design and certify the apparatus with respect to the NFPA requirements regarding rollover stability.

### **WATER TANK LEVEL GAUGE**

# GREELEY FIRE DEPT

SVI #930

## Production Specs

There shall be one (1) Fire Research TankVision model WLA200-A00 tank indicator level gauge(s) provided. The kit shall include an electronic indicator module, a pressure sensor, and a 10' sensor cable. The indicator shall show the volume of water in the tank on nine (9) easy to see super bright LEDs. A wide view lens over the LEDs shall provide for a viewing angle of 180 degrees. The indicator case shall be waterproof, manufactured of aluminum, and have a distinctive blue label.

The program features shall be accessed from the front of the indicator module. The program shall support self-diagnostics capabilities, self-calibration, and a datalink to connect remote indicators. Low water warnings shall include flashing LEDs at 1/4 tank, down chasing LEDs when the tank is almost empty, and an output for an audio alarm.

The indicator shall receive an input signal from an electronic pressure sensor. The sensor shall be mounted from the outside of the water tank near the bottom. No probe shall place on the interior of the tank. Wiring shall be weather resistant and have automotive type plug-in connectors.

### UPF POLY WATER TANK WARRANTY

The UPF poly water tank shall be provided with a lifetime material and workmanship limited warranty. The manufacturer shall supply details of their warranty information with their bid submission.

### HOSE BED STORAGE AREA

Hose bed storage area shall be located over water tank and body, and shall exit at the rear of the apparatus. The interior of storage area shall be free from all projections such as nuts, sharp angles, or brackets that may damage equipment.

Hose bed shall be **minumum of 10' deep**, and laid out as follows;

- Far Left Side: 200' of 3" Pre-connect (single stack) for a Blitz Fire monitor on rear body.
- Left Side: 750' of 2-1/2" (flat)
- Left Center: 750' of 2-1/2" (flat)
- Right Center: 1,000' of 5" supply hose (flat)
- Far Right: 300' of 2-1/2" Pre-connect (flat)

Additional hose storage will be as follows:

- Front Bumper: 150' of 1-3/4" in a flat or triple flat load
- Crosslays: (2) 200' of 1-3/4" Pre-connect, each

### ALUMINUM HOSE BED DECKING

The hose bed deck shall be constructed from 3" x 3/4" hollow aluminum extrusions welded into a one-piece grid to allow ventilation and water drainage. The extrusions shall have a radiused ribbed top surface. The deck will be completely removable for easy access to the booster tank. The booster tank fill tower shall be protected as necessary to prevent damage from equipment located in the storage area.

### WALKWAY/STEP LIGHTS

# GREELEY FIRE DEPT

SVI #930

## Production Specs

There shall be four (4) OnScene Solutions Rough-Service 9" LED lights provided to illuminate the walkway or step area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

Lighting shall provide illumination at a minimum level of 2 fc (20 lx) on all work surfaces, steps, and walkways. Lighting shall be switchable but activated automatically when the vehicle park brake is set.

### **FILL TOWER PROTECTION**

The fill tower(s) shall be boxed in with an aluminum panel for protection from damage.

### **HOSE BED DIVIDER(S)**

Four (4) adjustable aluminum hose bed partition(s) shall be provided in the hose storage area. The partition(s) shall be 3/16" smooth aluminum with split aluminum tubing welded to the top and rear edges.

### **ALUMINUM HOSE BED COVER**

A two-section hose bed cover shall be provided. Each door shall be fabricated from 1/8" NFPA aluminum treadplate with formed hat sections for bracing. Doors shall be hinged along each side of the hose body using stainless steel piano hinge. The top surface of each section shall slant down with the highest point in the center of the hose bed area and shall be supported from underneath by at least one (1) adjustable hose bed divider.

Each section shall be constructed to support the weight of a person (300 lbs).

Each section shall utilize pneumatic cylinders to assist with opening and closing. There shall be one (1) 24" vertical handrail on each door to assist in raising and lowering hose bed door. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

Each door shall have a horizontally mounted On Scene LED light on the underside of the door that will be automatically activated when the door is opened and wired to the compartment door ajar warning light provided in cab.

A vinyl hose bed flap shall be provided attached to each door and extend downward to bottom of hose bed to protect hose and equipment from weather and dust. The center where both doors come together shall have a Velcro seam to join two-pieces of vinyl together. Bottom of each flap shall be weighted for quick deployment of hose. Vinyl color shall be color coordinated with upper vehicle colors unless specified otherwise.

### **HOSE BED FULL WIDTH EXTENSION**

A full width, bolt-on type hose bed extension step shall be provided. Step shall be fabricated from 3/16" NFPA compliant treadplate aluminum with side gusset supports to body. The specified center rear marker lights shall be located on rear facing edge. The underside of step shall have a 36" OnScene LED light to light the bumper or compartment area below.

### **EQUIPMENT PAYLOAD WEIGHT ALLOWANCE**

# GREELEY FIRE DEPT

SVI #930

## Production Specs

In compliance with NFPA 1901 standards, the pumper shall be designed for an equipment loading allowance of 2,500 lbs. of Greeley Fire Department provided equipment based on the body having more than 250 cu. ft. of storage space.

### **EQUIPMENT**

The following equipment shall be furnished with the completed pumper vehicle;

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- Three (3) Eagle Attack, Glow Bumper Fahrenheit Thermal Imaging Camera(s) with TAC mode model #TIP2BBKYL203B1, and Accy Kit1 shall be provided. One (1) unit to be installed on engine tunnel on driverside and two (2) units shipped loose.
- There shall be two (2) Zico SAC-44-E NFPA approved folding aluminum wheel chocks provided for 44" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20 % grade, with the transmission in neutral, and the parking brake released.
  - **The wheel chock(s) shall be mounted to the underside of the lower adjustable shelf located in the S1 compartment..**
- One (1) Duo-Safety 900-A series 24' 2-section extension ladder(s) shall be provided with the completed unit.
  - The ladder(s) shall be mounted on specified ladder rack.
- One (1) Duo-Safety 775A series 14' aluminum roof ladder(s) shall be provided with the completed unit.
  - The ladder(s) shall be mounted on specified ladder rack.
- One (1) Duo-Safety 585-A 10' aluminum folding ladder(s) shall be provided with the completed unit.
  - The ladder(s) shall be located in specified ladder compartment.
- One (1) Nupla 8' Trash/Arson hook with fiberglass handle shall be provided with the completed unit.
  - The above specified pike pole will have a D handle attached
  - The trash hook(s) shall be mounted on the curbside rear wall of cab.
  - A stainless steel scuffplate shall be installed onto the back wall of the cab where the trash hook head comes in contact with the cab to prevent any paint damage.
- One (1) Duo-Safety 10' fiberglass pike pole(s) shall be provided with the completed unit.
  - The above specified pike pole will not have a D handle attached
  - The pike pole(s) shall be mounted in rear compartment with folding ladder.
- Four (4) Streamlight Fire Vulcan C4 LED flashlight(s) with shoulder strap shall be provided with 80,000 candela and 3 hour run time. Each flashlight shall be yellow in color and have a 12 volt DC charger and

# GREELEY FIRE DEPT

SVI #930

## Production Specs

vehicle mount kit. Each flashlight shall have an LED spotlight style bulbs and reflectors. The flashlight(s) shall be wired to battery direct unless otherwise specified by Greeley Fire Department.

- Four (4) flashlight(s) shall be mounted, three (3) in rear cab crew area on rear of engine tunnel, and one (1) for driver inside rear streetside crew door on rear cabinet face.
- One (1) Kochek 6.0" x 10' clear PVC flexible suction hose(s) shall be provided with completed unit. The hose shall have light weight Storz couplings provided.
  - The suction hose(s) shall be mounted on the specified ladder rack.
- One (1) 6" NST low level jet siphon to match hard suction hose provided shall be provided and stored in Compt. RC1.
- One (1) Task Force Tips 500 GPM manual Blitzfire monitor model XXC-52 with automatic nozzle, stream straightener, 3- stacked tips, 2-1/2" inlet, and apparatus mount shall be provided with completed unit.
  - The above specified fire adapter/appliance shall be mounted on the completed unit, located on the streetside rear of the body and shall be preconnected to the far left 3" preconnect. A protective vinyl bag cover shall be provided to protect monitor from elements.
- One (1) Akron Brass 448 wrench holder with two (2) style 46 spanners, and one (1) Akron Brass SS-MP Super Spanners set with four (4) SS-525 spanner wrenches, shall be provided with completed unit.
  - The above specified wrench holder(s) shall be mounted on the completed unit, locations as per the Greeley Fire Department.

**Nozzle, Adapters, Valves, Extinguishers, Tools:**

	Qty.	Part Number	List	Cost Ea.	Ext. Cost
One (1) 2.5" NS Bresnan Cellar nozzle	1	193-6			
One (1) 2.5" to 1.5" NS brass fire hose reducer (chrome)	1	37R2515C			
Three (3) 2.5" to 1.5" gated wye	3	22K15025			
Two (2) 2.5" NS double female adapters	2	35R2525			
Two (2) 2.5" NS double male adapters	2	36R2525			
One (1) 2.5" Iron Pipe thread to 1.5" NS thread adapter	1	37R25N15			
One (1) 1.5" F to 2.5" M NS thread hose increaser adapter	1	37R1525			
One (1) Elkhart Universal Hose Adapter part #435	1	435			
One (1) 1.5" NS to garden hose adapter	1	37R15G			
Two (2) Task Force Tips BIV Ball Intake Valves model # AB1ST-NX. Threads shall be NH 6-4.	2	AB1ST-NX			
Two (2) Akron adjustable Style 15 hydrant wrenches	2	15			
One (1) 3" Cooper Hose Jacket	1	773			
One (1) Multi-Purpose ABC rated 40 pound extinguisher	1				
One (1) Amerex 6 liter K-class extinguisher	1	B260			
One (1) 2A10BC Dry Chemical extinguisher	1				

# GREELEY FIRE DEPT

SVI #930

## Production Specs

One (1) 2.5 gallon pressurized water extinguisher	1			
One (1) Three-foot (3') 1.5" NS piercing nozzle (125 gpm)	1	Akron 1088		
One (1) Elkhart Brass 2.5" inline gauge model #228A	1	228-A-2.5		
One (1) Elkhart Brass 2.5" inline drain elbow model 105A	1	105A		
One (1) FG Six pound pick-head fire axe	1	Darley #J745		
Two (2) FG Six pound flat-head fire axes	2	Darley #370		
One (1) 30" Halligan Pro-bar (dropped forged, single piece)	1	Probar		
One (1) Three foot (3') D-handled closet hook	1	Nupla 35577		
One (1) Super Vac gasoline-powered blower model #718G4-H (6.5 hp Honda GX motor)	1	718G4-H		
One (1) Super-Vac 16" electric box fan	1	P164S		
One (1) Little Giant Type 1A Classic ladder	1	Model 13		
One (1) Elkhart Brass 285 hose clamp with mounting bracket	1	286/285-MB		
One (1) 6" NH thread to Storz hydrant adapter (6" rigid female x 5" Storz)	1	S37S56		
<b>Hand-line Nozzles:</b>				
Eleven (11) Elkhart 1.5" body with full ball-valve	11	B-375-GA		
Two (2) 2.5" Elkhart body with full ball-valve	2	DB-375-GA		
Two (2) 1 1/8" Elkhart smooth-bore tip with stream straightner.	2	187-A-1 1/8		
Five (7) Chief fog tips rated at 125 gpm @ 75 psi. (green)	7	4000-14		
Two (2) Chief fog tips rated at 175 gpm @ 75 psi. (orange)	2	4000-24		
One (1) 15/16" Elkhart smooth-bore tip with stream straightner	1	187-A-15/16		
Eight (8) Pac Trac Model #1001 Hookloks	8	1001		
Eight (8) Pac Trac Model #1004-Y Handleloks	8	1004-Y		
Two (2) Pac Trac Model # 1009 Tool Hanger	2	1009		
One (1) Pac Trac Model # K5003 IronsLok	1	K5003		
Six (6) Elkhart Brass Model # 653 Tri-Lock Nozzle Holder	6	653		
<b>Hose:</b>				
Ten (10) one-hundred foot lengths of five-inch supply hose with Storz couplings (yellow)	10	RC5078		
One (1) twenty-five (25) foot section of five-inch supply hose with Storz couplings (yellow)	1	RC5078-2		
One (1) one-hundred foot section of 2.0" light-weight high-rise attack hose with 1.5" NS couplings (x=specify color-no additional cost)	1	DJP2015-X		
Eight (8) fifty-foot sections of 1.75" double jacket attack hose with 1.5" NS couplings (-2=white / color additional cost)	8	DJ175151-2		

# GREELEY FIRE DEPT

SVI #930

## Production Specs

Three (3) fifty-foot sections of 1.5" rubber attack hose with 1.5" NS couplings (x=specify color no additional cost)	3	RC15151-X			
Thirty (30) fifty-foot sections of 2.5" double-jacket attack hose with 2.5" NS couplings (-2=white / color additional cost)	30	DJ25251-2			
Six (6) fifty-foot lengths of 3.0" double-jacket attack/supply hose with 2.5" NS couplings (-2=white / color additional cost)	6	DJ30251-2			

### **REMAINING NFPA MINOR EQUIPMENT BY PURCHASER**

All other minor equipment not specified above, but required by NFPA 1901 for special service vehicles, section 10.5.1 shall be supplied and mounted by Greeley Fire Department before the unit is placed in emergency service.