

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

Table of Contents

INTERNET IN-PROCESS SITE	18
ROADABILITY.....	18
SERVICEABILITY	18
OPERATIONS AND SERVICE DOCUMENTATION	20
NFPA REQUIRED DOCUMENTATION FORMAT - CD-ROM.....	20
STATEMENT OF EXCEPTIONS	21
CARRYING CAPACITY	21
TESTING.....	22
ROAD TEST	22
LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST	23
TEST SEQUENCE	23
1. RESERVE CAPACITY TEST	23
2. ALTERNATOR PERFORMANCE TEST	23
TEST AT IDLE.....	23
TEST AT FULL LOAD	23
LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST	24
DOCUMENTATION	24
DOCUMENTATION	26
DIELECTRIC VOLTAGE WITHSTAND TEST	26
PERFORMANCE BOND.....	27
WARRANTY.....	27
GENERAL LIMITED WARRANTY - ONE (1) YEAR	28
LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS	28
STRUCTURAL WARRANTY - TEN (10) YEARS	28
PAINT LIMITED WARRANTY - TEN (10) YEARS.....	28
GRAPHICS LIMITED WARRANTY	28
CONSTRUCTION PERIOD	28
OVERALL HEIGHT.....	28

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

OVERALL LENGTH.....	29
OVERALL WIDTH	29
ENGINEERING SUPPORT AT PRE-CONSTRUCTION MEETING.....	29
DELIVERY AND DEMONSTRATION.....	29
CHASSIS SPECIFICATION.....	29
MODEL	29
MODEL YEAR.....	29
COUNTRY OF SERVICE	30
APPARATUS TYPE	30
VEHICLE TYPE	30
AXLE CONFIGURATION.....	30
GROSS AXLE WEIGHT RATINGS FRONT	30
GROSS AXLE WEIGHT RATINGS REAR.....	30
CAB STYLE.....	31
CAB FRONT FASCIA.....	32
FRONT GRILLE	32
CAB UNDERCOAT	32
CAB SIDE DRIP RAIL	32
CAB PAINT EXTERIOR	33
CAB PAINT MANUFACTURER	33
CAB PAINT PRIMARY/LOWER COLOR	33
CAB PAINT SECONDARY/UPPER COLOR.....	33
CAB PAINT EXTERIOR BREAKLINE.....	33
CAB PAINT PINSTRIPE.....	33
CAB PAINT WARRANTY	34
CAB PAINT INTERIOR.....	34
CAB ENTRY DOORS.....	34
CAB ENTRY DOOR TYPE.....	34
LH EXTERIOR REAR COMPARTMENT.....	34

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

LEFT HAND EXTERIOR REAR COMPARTMENT LIGHTING	34
LH EXTERIOR COMPARTMENT INTERIOR FINISH	34
RH EXTERIOR REAR COMPARTMENT	35
RIGHT HAND EXTERIOR REAR COMPARTMENT LIGHTING	35
RH EXTERIOR COMPARTMENT INTERIOR FINISH.....	35
REAR CAB WALL CUTOUT.....	35
CAB STRUCTURAL WARRANTY.....	35
CAB TEST INFORMATION	35
ELECTRICAL SYSTEM.....	36
APPARATUS WIRING PROVISION	36
LOAD MANAGEMENT SYSTEM.....	36
DATA RECORDING SYSTEM	36
ACCESSORY POWER DISTRIBUTION PANEL.....	37
ACCESSORY POWER	37
AUXILIARY ACCESSORY POWER	37
EXTERIOR ELECTRICAL TERMINAL COATING.....	37
ENGINE.....	37
CAB ENGINE TUNNEL.....	38
DIESEL PARTICULATE FILTER CONTROLS.....	38
ENGINE PROGRAMMING HIGH IDLE SPEED.....	38
ENGINE HIGH IDLE CONTROL.....	38
ENGINE PROGRAMMING ROAD SPEED GOVERNOR.....	38
AUXILIARY ENGINE BRAKE	38
AUXILIARY ENGINE BRAKE CONTROL.....	38
ELECTRONIC ENGINE OIL LEVEL INDICATOR	39
FLUID FILLS.....	39
ENGINE DRAIN PLUG.....	39
ENGINE WARRANTY	39
ENGINE PROGRAMMING REMOTE THROTTLE.....	39

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ENGINE PROGRAMMING IDLE SPEED	39
ENGINE FAN DRIVE.....	39
ENGINE COOLING SYSTEM	40
ENGINE COOLING SYSTEM PROTECTION	40
ENGINE COOLANT	40
ELECTRONIC COOLANT LEVEL INDICATOR	40
COOLANT HOSES	41
ENGINE AIR INTAKE.....	41
ENGINE EXHAUST SYSTEM	41
DIESEL EXHAUST FLUID TANK	42
ENGINE EXHAUST WRAP	42
TRANSMISSION	42
TRANSMISSION MODE PROGRAMMING	42
TRANSMISSION FEATURE PROGRAMMING	43
TRANSMISSION SHIFT SELECTOR	43
ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR.....	43
TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE	43
TRANSMISSION COOLING SYSTEM	43
TRANSMISSION DRAIN PLUG	43
TRANSMISSION WARRANTY.....	44
PTO PROGRAMMING	44
PTO CONTROL	44
DRIVELINE	44
FUEL FILTER/WATER SEPARATOR	44
FUEL LINES.....	44
FUEL SHUTOFF VALVE	45
FUEL COOLER	45
FUEL TANK.....	45
FUEL TANK FILL PORT.....	45

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

FUEL TANK SERVICEABILITY PROVISIONS.....	45
FRONT AXLE	46
FRONT AXLE WARRANTY.....	46
FRONT WHEEL BEARING LUBRICATION	46
FRONT SHOCK ABSORBERS	46
FRONT SUSPENSION.....	46
STEERING COLUMN/ WHEEL.....	47
POWER STEERING PUMP	47
ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR	47
FRONT AXLE CRAMP ANGLE.....	47
POWER STEERING GEAR	47
CHASSIS ALIGNMENT	47
REAR AXLE	48
REAR AXLE DIFFERENTIAL LUBRICATION	48
REAR AXLE WARRANTY	48
REAR WHEEL BEARING LUBRICATION	48
REAR AXLE DIFFERENTIAL CONTROL.....	48
VEHICLE TOP SPEED	48
REAR SUSPENSION	48
FRONT TIRE	49
REAR TIRE	49
REAR AXLE RATIO	49
TIRE PRESSURE INDICATOR.....	49
FRONT WHEEL.....	49
REAR WHEEL	50
WHEEL GUARDS	50
BRAKE SYSTEM	50
FRONT BRAKES.....	51
REAR BRAKES.....	51

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

PARK BRAKE	51
PARK BRAKE CONTROL.....	51
REAR BRAKE SLACK ADJUSTERS	51
REAR BRAKE DUST SHIELDS.....	51
AIR DRYER	51
FRONT BRAKE CHAMBERS	51
REAR BRAKE CHAMBERS	52
AIR COMPRESSOR	52
AIR GOVERNOR	52
MOISTURE EJECTORS	52
AIR SUPPLY LINES	52
AIR INLET CONNECTION	52
AIR INLET LOCATION	52
PLUMBING AIR INLET CONNECTION	53
AIR INLET SHUTOFF VALVE.....	53
AIR INLET/ OUTLET FITTING TYPE	53
AIR TANK SPACERS	53
REAR AIR TANK MOUNTING.....	53
WHEELBASE.....	53
REAR OVERHANG	53
FRAME.....	54
FRAME WARRANTY.....	54
FRAME PAINT	54
FRONT BUMPER	55
FRONT BUMPER EXTENSION LENGTH.....	55
FRONT BUMPER EXTENSION FRAME WIDTH.....	55
FRONT BUMPER PAINT	55
FRONT BUMPER APRON	55
MECHANICAL SIREN	55

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

MECHANICAL SIREN LOCATION	55
AIR HORN	55
AIR HORN LOCATION	56
AIR HORN RESERVOIR	56
FRONT BUMPER TOW EYES.....	56
CAB TILT SYSTEM.....	56
CAB TILT LIMIT SWITCH.....	56
CAB TILT CONTROL RECEPTACLE.....	57
CAB WINDSHIELD	57
GLASS FRONT DOOR	57
GLASS TINT FRONT DOOR	57
GLASS REAR DOOR RH	57
GLASS TINT REAR DOOR RIGHT HAND.....	57
GLASS REAR DOOR LH	58
GLASS TINT REAR DOOR LEFT HAND.....	58
GLASS SIDE MID RH.....	58
GLASS TINT SIDE MID RIGHT HAND	58
GLASS SIDE MID LH	58
GLASS TINT SIDE MID LEFT HAND	58
GLASS UPPER SIDE REAR DOOR	58
GLASS TINT UPPER SIDE REAR DOOR.....	59
CLIMATE CONTROL	59
CLIMATE CONTROL DRAIN	59
CLIMATE CONTROL ACTIVATION	59
HVAC OVERHEAD COVER PAINT	59
A/C CONDENSER LOCATION.....	59
A/C COMPRESSOR.....	59
CAB CIRCULATION FANS FRONT	60
CAB INSULATION	60

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

UNDER CAB INSULATION	60
INTERIOR TRIM FLOOR.....	60
INTERIOR TRIM VINYL	60
REAR WALL INTERIOR TRIM	61
HEADER TRIM.....	61
TRIM CENTER DASH	61
TRIM LH DASH	61
TRIM RH DASH	61
ENGINE TUNNEL TRIM	61
POWER POINT DASH MOUNT	61
STEP TRIM	62
STEP TRIM KICKPLATE	62
UNDER CAB ACCESS DOOR	62
INTERIOR DOOR TRIM.....	62
DOOR TRIM KICKPLATE	62
DOOR TRIM CUSTOMER NAMEPLATE.....	62
CAB DOOR TRIM REFLECTIVE	62
INTERIOR GRAB HANDLE "A" PILLAR	63
INTERIOR GRAB HANDLE FRONT DOOR.....	63
INTERIOR GRAB HANDLE REAR DOOR	63
INTERIOR TRIM VINYL COLOR	63
INTERIOR TRIM SUNVISOR.....	63
INTERIOR FLOOR MAT COLOR.....	63
CAB PAINT INTERIOR DOOR TRIM.....	63
HEADER TRIM INTERIOR PAINT.....	63
TRIM CENTER DASH INTERIOR PAINT	64
TRIM LH DASH INTERIOR PAINT.....	64
TRIM RIGHT HAND DASH INTERIOR PAINT	64
REAR WALL INTERIOR PAINT.....	64

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

DASH PANEL GROUP	64
SWITCHES CENTER PANEL.....	64
SWITCHES LEFT PANEL.....	64
SWITCHES RIGHT PANEL	65
SEAT BELT WARNING	65
SEAT MATERIAL.....	65
SEAT COLOR	65
SEAT BACK LOGO.....	65
SEAT DRIVER.....	66
SEAT BACK DRIVER	66
SEAT MOUNTING DRIVER	66
SEAT OFFICER	66
SEAT BACK OFFICER	67
SEAT MOUNTING OFFICER.....	67
SEAT REAR FACING OUTER LOCATION.....	67
SEAT CREW REAR FACING OUTER.....	67
SEAT BACK REAR FACING OUTER	68
SEAT MOUNTING REAR FACING OUTER	68
SEAT BELT ORIENTATION CREW.....	68
SEAT FORWARD FACING OUTER LOCATION	68
SEAT CREW FORWARD FACING OUTER	69
SEAT BACK FORWARD FACING OUTER	69
SEAT MOUNTING FORWARD FACING OUTER.....	69
SEAT FRAME FORWARD FACING.....	70
SEAT FRAME FORWARD FACING STORAGE ACCESS	70
SEAT FRAME EXTERIOR REAR COMPARTMENT ACCESS	70
CAB FRONT UNDERSEAT STORAGE ACCESS.....	70
SEAT COMPARTMENT DOOR FINISH.....	70
WINDSHIELD WIPER SYSTEM	70

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR.....	70
CAB DOOR HARDWARE.....	71
DOOR LOCKS	71
DOOR LOCK LH REAR CAB COMPARTMENT.....	71
DOOR LOCK RH REAR CAB COMPARTMENT	71
GRAB HANDLES	71
REARVIEW MIRRORS.....	72
REARVIEW MIRROR HEAT SWITCH	72
TRIM LOWER SIDE	72
CAB FENDER.....	72
MUD FLAPS FRONT	72
CAB EXTERIOR FRONT & SIDE EMBLEMS.....	72
CAB EXTERIOR MODEL NAMEPLATE	73
IGNITION	73
BATTERY	73
BATTERY TRAY.....	73
BATTERY BOX COVER	73
BATTERY CABLE.....	73
BATTERY JUMPER STUD	74
ALTERNATOR.....	74
STARTER MOTOR	74
BATTERY CONDITIONER.....	74
BATTERY CONDITIONER DISPLAY	74
ELECTRICAL INLET.....	74
ELECTRICAL INLET LOCATION.....	74
ELECTRICAL INLET CONNECTION	75
ELECTRICAL INLET COLOR	75
HEADLIGHTS.....	75
FRONT TURN SIGNALS.....	75

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

HEADLIGHT LOCATION.....	75
SIDE TURN/MARKER LIGHTS	75
MARKER AND ICC LIGHTS.....	75
HEADLIGHT AND MARKER LIGHT ACTIVATION	75
GROUND LIGHTS	76
STEP LIGHTS	76
ENGINE COMPARTMENT LIGHT	76
FRONT SCENE LIGHTS.....	76
FRONT SCENE LIGHT LOCATION.....	76
FRONT SCENE LIGHTS ACTIVATION.....	76
SIDE SCENE LIGHTS.....	76
SIDE SCENE LIGHT LOCATION.....	77
SIDE SCENE ACTIVATION	77
INTERIOR OVERHEAD LIGHTS.....	77
MAP LIGHTS	77
DO NOT MOVE APPARATUS LIGHT	77
MASTER WARNING SWITCH	77
HEADLIGHT FLASHER.....	78
HEADLIGHT FLASHER SWITCH.....	78
INBOARD FRONT WARNING LIGHTS	78
INBOARD FRONT WARNING LIGHTS COLOR	78
FRONT WARNING SWITCH.....	78
INTERSECTION WARNING LIGHTS.....	78
INTERSECTION WARNING LIGHTS COLOR.....	78
INTERSECTION WARNING LIGHTS LOCATION	78
SIDE WARNING LIGHTS	79
SIDE WARNING LIGHTS COLOR	79
SIDE WARNING LIGHTS LOCATION	79
SIDE AND INTERSECTOR WARNING SWITCH	79

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

LIGHTBAR PROVISION	79
CAB FRONT LIGHTBAR.....	79
LIGHTBAR SWITCH	79
HORN BUTTON SELECTOR SWITCH.....	79
AIR HORN ACTIVATION	80
MECHANICAL SIREN ACTIVATION	80
BACK-UP ALARM	80
INSTRUMENTATION	80
RED LAMPS.....	81
AMBER LAMPS	81
GREEN LAMPS	81
BLUE LAMPS.....	82
CONSTANT AUDIBLE ALARMS FROM GAUGE PACKAGE	82
OSCILLATING AUDIBLE ALARMS FROM GAUGE PACKAGE.....	82
BACKLIGHTING COLOR.....	82
CAB EXTERIOR PROTECTION	82
FIRE EXTINGUISHER.....	82
ROAD SAFETY KIT	82
DOOR KEYS.....	83
WARRANTY.....	83
OPERATION MANUAL	83
ENGINE AND TRANSMISSION OPERATION MANUALS.....	83
AS BUILT WIRING DIAGRAMS	83
PAINT CONFIRMATION	83
CAB TO AXLE DIMESION.....	83
CHASSIS MODIFICATIONS	84
LUBRICATION AND TIRE DATA PLATE	84
VEHICLE DATA PLATE	84
OVERALL HEIGHT, LENGTH DATA PLATE (US).....	85

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ACCIDENT PREVENTION	85
PERSONNEL CAPACITY	85
ACCIDENT PREVENTION	85
WEARING HELMET WARNING.....	85
FRONT BUMPER	85
EXHAUST SYSTEM (VERTICAL).....	86
THREE (3) ANTENNA RAIL	86
HUB AND NUT COVERS	86
MUDFLAPS	86
CAB INTERIOR CABINET - CURBSIDE OVERHEAD	87
CAB INTERIOR CABINET - STREETSIDE OVERHEAD	87
CAB INTERIOR CABINET - OVERHEAD	88
FUEL FILL	88
BODY DESIGN	89
EXTERIOR STAINLESS STEEL BODY	90
DRIP RAILS.....	90
ROOF CONSTRUCTION	90
BODY SUBFRAME	91
BODY MOUNTING	91
12" REAR STEP BUMPER	91
REAR TOW EYES	91
GROUND LIGHTS	92
WHEEL WELL EXTERIOR PANEL.....	92
STAINLESS STEEL BODY FENDERS.....	92
WHEEL WELL LINERS	92
BODY PAINT SPECIFICATIONS	92
BODY PAINT PREPARATION	92
PAINT PROCESS	93
MACHINE POLISHED.....	93

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

PAINT - ENVIRONMENTAL IMPACT	93
PAINT FINISH - SINGLE COLOR	93
BODY UNDERCOATING.....	94
UNDERCOAT WARRANTY	94
PAINT WARRANTY.....	94
COMPARTMENT INTERIOR FINISH	94
REFLECTIVE STRIPE REQUIREMENTS.....	94
REFLECTIVE STRIPE - CAB SIDE	95
REFLECTIVE STRIPE - CAB FRONT	95
REFLECTIVE STRIPE - BODY SIDES.....	95
CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS.....	96
LETTERING.....	96
SIDE CAB DOOR LETTERING	96
UPPER BODY SIDE LETTERING.....	96
CUSTOM DECAL LOGO - 12" -18"	97
EXTERIOR COMPARTMENT DOORS.....	97
ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM).....	97
BODY HEIGHT MEASUREMENTS	98
FIVE (5) UPPER BODY COMPARTMENTS (OPEN).....	99
UPPER BODY WALKWAY	99
WALKWAY/STEP LIGHTS	100
ACCESS LADDER	100
WALKWAY/STEP LIGHTS	100
ROOF ACCESS HANDRAIL	100
BODY WIDTH DIMENSIONS.....	101
STREETSIDE COMPARTMENT - FRONT (S1).....	102
COMPARTMENT LAYOUT	102
STREETSIDE COMPARTMENT - AHEAD OF REAR WHEELS (S2)	104
COMPARTMENT LAYOUT	104

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S3).....	107
COMPARTMENT LAYOUT	107
STREETSIDE COMPARTMENT - REAR (S4)	109
COMPARTMENT LAYOUT	109
CURBSIDE COMPARTMENT - FRONT (C1)	111
COMPARTMENT LAYOUT	111
CURBSIDE COMPARTMENT - AHEAD OF REAR WHEEL (C2)	113
COMPARTMENT LAYOUT	113
CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C3)	116
COMPARTMENT LAYOUT	116
CURBSIDE COMPARTMENT - REAR (C4).....	117
COMPARTMENT LAYOUT	117
REAR COMPARTMENT - CENTER (RC1)	119
COMPARTMENT LAYOUT	119
PLASTIC FLOOR AND SHELF TILE	122
SIDE BODY PROTECTION - RUB RAIL	122
WALK-IN INTERIOR FINISH DETAILS	122
DESK, CABINET, CONSOLE FINISH	122
CAB/BODY WALK-THROUGH CONNECTION.....	123
CUT OUT IN REAR CAB WALL	123
INTERIOR SPECIFICATIONS.....	123
INTERIOR INSULATION	123
INTERIOR FINISH	123
INTERIOR WALKWAY SIDE WALLS.....	124
INTERIOR WALKWAY FLOOR.....	124
INTERIOR SUB-FLOOR	124
AIR CONDITIONER - HEATER	124
STREETSIDE INTERIOR AREA (IS1)	125
INTERIOR CABINET – ABOVE DECK	125

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

FLIP-UP SEAT	125
CURBSIDE INTERIOR AREA (IC1)	125
INTERIOR CABINET – ABOVE DECK	125
GALLEY REFRIGERATOR.....	126
LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC.....	126
12 VOLT DIAGNOSTIC RELAY CONTROL CENTER.....	128
ROCKER SWITCH PANEL	129
ELECTRICAL SYSTEM MANAGER.....	129
BATTERY SYSTEM	129
BATTERY SWITCH	130
BATTERY SOLENOID	130
INTERIOR LED LIGHTS.....	130
TAIL LIGHTS	130
MIDSHIP MARKER/TURN SIGNAL.....	130
MARKER LIGHTS	131
SIDE SCENE LIGHTS - LED	131
REAR SCENE LIGHTS - LED	131
TRAFFIC DIRECTIONAL LIGHT	131
WARNING LIGHT PACKAGE	132
UPPER LEVEL OPTICAL WARNING DEVICES.....	132
LOWER LEVEL OPTICAL WARNING DEVICES	133
LINE VOLTAGE ELECTRICAL SYSTEM	135
HYDRAULIC GENERATOR SYSTEM.....	135
GENERATOR MOUNTING	135
WARRANTY PERIOD	135
HYDRAULIC COMPONENTS	135
GENERATOR MOUNTING	136
MANUALS AND SCHEMATICS.....	136
POWER-TAKE-OFF GENERATOR DRIVE	136

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

GENERATOR MONITORING PANEL	136
CIRCUIT BREAKER BOX	137
LINE VOLTAGE ELECTRICAL SYSTEM	137
GENERAL REQUIREMENTS	137
120/240 VAC SCENE LIGHTING	143
COMMAND LIGHT TOWER w/ BACKLIGHT	143
LIGHT TOWER TREE LIMB GUARD.....	144
HYDRAULIC RESCUE SYSTEM.....	144
Intent.....	144
Scope and General Description.....	144
Compliance to NFPA Standards	145
Performance	145
Variable Engine Speed Compatibility.....	145
Hydraulic Pumps	145
Hydraulic Fluid Reservoir	145
Hydraulic Fluid Filtration.....	146
Hydraulic Fluid Cooling Systems	146
Hydraulic System Plumbing, Hoses, and Fittings	146
Valve Plate Assembly	147
Control Valve Assembly	147
High Pressure Intensifier.....	147
Electrical Control System	147
“On-Off” Control	148
Hydraulic Rescue Tool System Materials and Hoses	148
Hydraulic Tool System Installation and Testing	148
EQUIPMENT PAYLOAD WEIGHT ALLOWANCE	148
EQUIPMENT	148
REMAINING NFPA MINOR EQUIPMENT BY PURCHASER.....	149

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

INTERNET IN-PROCESS SITE

The Bidder shall post and maintain a website where the Hilton-Parma Fire District will be able to view digital images of their apparatus as its being manufactured. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of the apparatus.

ROADABILITY

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- 1) From a standing start, the apparatus shall be able to attain a speed of 35 mph (55 km/hr) within 25 seconds on a level road.
- 2) The apparatus shall be able to attain a minimum top speed of 50 mph (80 km/hr) on a level road.
- 3) The apparatus shall be able to maintain a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent.

The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (105 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal (4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (85 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

SERVICEABILITY

The fire apparatus shall be designed to allow the manufacturer's recommended routine maintenance checks of lubricant and fluid levels to be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

CONSTRUCTION DOCUMENTATION

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

The manufacturers record of apparatus construction details, including the following information:

- 1) Owner's name and address
- 2) Apparatus manufacturer, model, and serial number
- 3) Chassis make, model, and serial number
 - a) GAWR of front and rear axles and GVWR
 - b) Front tire size and total rated capacity in pounds (kilograms)
 - c) Rear tire size and total rated capacity in pounds (kilograms)
 - d) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
 - e) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
 - f) Type of fuel and fuel tank capacity
 - g) Electrical system voltage and alternator output in amps
 - h) Battery make, model, and capacity in cold cranking amps (CCA)
 - i) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
- 4) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
- 5) Pump transmission make, model, serial number, and gear ratio
- 6) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
- 7) Water and Foam tank certified capacity in gallons or liters
- 8) Paint manufacturer and paint number(s)
- 9) Company name and signature of responsible company representative
- 10) If the apparatus is a mobile foam fire apparatus, the certification of foam tank capacity
- 11) Certification of compliance of the optical warning system
- 12) Siren manufacturer's certification of the siren
- 13) Written load analysis and results of the electrical system performance tests
- 14) Certification of slip resistance of all stepping, standing, and walking surfaces
- 15) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability
- 16) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions
- 17) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications
- 18) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed
- 19) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test
- 20) If the apparatus has a fire pump, the certification of inspection and test for the fire pump
- 21) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test
- 22) When the apparatus is equipped with a water tank, the certification of water tank capacity
- 23) If the apparatus has an aerial device, the certification of inspection and test for the aerial device
- 24) If the apparatus has an aerial device, all the technical information required for inspections to comply with NFPA 1911, Standard for the Inspection, Maintenance, Testing, and Retirement of In-Service Automotive Fire Apparatus
- 25) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy and the final installer's certification the foam proportioning system meets this standard
- 26) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests
- 27) If the apparatus has a line voltage power source, the certification of the test for the power source
- 28) If the apparatus is equipped with an air system, air tank certificates, the SCBA fill station certification, and the results of the testing of the air system installation
- 29) Any other required manufacturer test data or reports.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

OPERATIONS AND SERVICE DOCUMENTATION

The Contractor shall deliver with the fire apparatus at least two (2) sets of complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof.

The Contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- 1) Manufacturer's name and address
- 2) Country of manufacture
- 3) Source for service and technical information
- 4) Parts replacement information
- 5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- 6) Wiring diagrams for low voltage and line voltage systems to include the following information:
- 7) Pictorial representations of circuit logic for all electrical components and wiring
 - a. Circuit identification
 - b. Connector pin identification
 - c. Zone location of electrical components
 - d. Safety interlocks
 - e. Alternator–battery power distribution circuits
 - f. Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- 8) Lubrication charts
- 9) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- 10) Precautions related to multiple configurations of aerial devices, if applicable
- 11) Instructions regarding the frequency and procedure for recommended maintenance
- 12) Overall apparatus operating instructions
- 13) Safety considerations
- 14) Limitations of use
- 15) Inspection procedures
- 16) Recommended service procedures
- 17) Troubleshooting guide
- 18) Apparatus body, chassis and other component manufacturer's warranties
- 19) Special data required by this standard
- 20) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus

The Contractor shall deliver with the apparatus all manufacturer's operations and service documents supplied with components and equipment that are installed or supplied by the Contractor.

NFPA REQUIRED DOCUMENTATION FORMAT - CD-ROM

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a CD-ROM. These manuals shall be divided into sections for ease of reference. There shall be two (2) copies of the CD-ROM provided with the completed vehicle.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

STATEMENT OF EXCEPTIONS

The Contractor shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- 1) A separate specification of the section of the applicable standard for which compliance is lacking
- 2) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
- 3) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance
- 4) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to or at the time of delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

An apparatus that is delivered subject to a Statement of Exceptions other than a certification of full compliance shall not be placed in emergency service until the apparatus has been modified as necessary to accomplish full compliance with this standard.

CARRYING CAPACITY

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The Body Manufacturer shall establish the estimated in service weight during the design of the vehicle

The estimated in-service weight shall include the following:

- 1) The chassis, body and tank(s)
- 2) Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
- 3) Full water and other agent tanks
- 4) *250 lb (114 kg) in each seating position
- 5) Fixed equipment such as pumps, aerial devices, generators, reels and air systems as installed
- 6) Ground ladders, suction hose, designed hose load in their hose beds and on their reels
- 7) An allowance for miscellaneous equipment that is the greatest of the values for type of vehicle per NFPA 1901, a Purchaser provided list of equipment to be carried with weights or a Purchaser specified miscellaneous equipment allowance.

The Body Manufacturer shall engineer and design the vehicle such that the completed unit, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

A final Body Manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

Apparatus Type	Equip. Storage Area	Apparatus Size	Equipment Allowance	
			lb.	kg.
Special Service Fire Apparatus	Minimum of 120 cu ft (3.4 cu mt) of enclosed compartmentation.	10,000 lb to 15,000 lb (4,500 kg to 7,000 kg) GVWR	2,000	910
		15,001 lb to 20,000 lb (7,001 kg to 9,000 kg) GVWR	2,500	1,135
		20,001 lb to 30,000 lb (9,001 kg to 14,000 kg) GVWR	3,000	1,350
		30,001 lb to 40,000 lb (14,001 kg to 18,000 kg) GVWR	4,000	1,800
		40,001 lb to 50,000 lb (18,001 kg to 23,000 kg) GVWR	6,000	2,700
		50,001 lb to 60,000 lb (23,001 kg to 27,000 kg) GVWR	8,000	3,600
		60,001 lb and up (27,001 kg) GVWR	10,000	4,500

TESTING

ROAD TEST

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the Body Manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (-18°C and 43°C).

TEST SEQUENCE

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for ten (10) minutes. Failure of any of these tests shall require a repeat of the sequence.

1. RESERVE CAPACITY TEST

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

2. ALTERNATOR PERFORMANCE TEST

TEST AT IDLE

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

TEST AT FULL LOAD

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

3. LOW VOLTAGE ALARM TEST

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST

DOCUMENTATION

The manufacturer shall deliver the following with the fire apparatus:

- 1) Documentation of the electrical system performance tests
- 2) A written electrical load analysis, including the following:
 - a. The nameplate rating of the alternator
 - b. The alternator rating
 - c. Each of the component loads specified that make up the minimum continuous electrical load
 - d. Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
 - e. Each individual intermittent electrical load

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

UL 120/240 VAC CERTIFICATION

The 120/240 volt electrical system shall be tested and certified by Underwriters Laboratories, to perform as listed below;

The prime mover shall be started from a cold start condition, and the unloaded voltage and frequency shall be recorded.

The line voltage electrical system shall be loaded to at least 100% of the continuous rated wattage stated on the power source specification label. Testing with a resistive load bank shall be permitted.

The power source shall be operated in the manner specified by the apparatus manufacturer as documented on instruction plates or in operation manuals. The power source shall be operated at a minimum of 100% of the continuous rated wattage as stated on the power source specification label for a minimum of two (2) hours.

The load shall be adjusted to maintain the output wattage at or above the continuous rated wattage during the entire 2-hour test.

The following conditions shall be recorded at least every 1/2 hour during the test:

- The power source output voltage, frequency and amperes
- The prime mover's oil pressure, water temperature and transmission temperature, if applicable
- The power source hydraulic fluid temperature, if applicable
- The ambient temperature and power source air inlet temperature

The following conditions shall be recorded once during the test for power sources driven by dedicated auxiliary internal combustion engines:

- Altitude
- Barometric pressure
- Relative humidity

If the generator is driven by the chassis engine and the generator allows for operation at variable speeds, the chassis engine speed shall be reduced to the lowest rpm allowed for generator operation and the voltage and frequency shall be recorded.

The load shall be removed and the unloaded voltage and frequency shall be recorded.

Voltage shall be maintained within $\pm 10\%$ of the voltage stated on the power source specification label during the entire test. Frequency shall be maintained within ± 3 Hz of the frequency stated on the power source specification label during the entire test.

The total continuous electrical loads, excluding those loads associated with the equipment defined in NFPA 22.15.7.3.11.2, shall be applied during the testing unless an auxiliary engine drives the power source.

If the apparatus is equipped with a fire pump, the 2-hour certification test of the power source shall be completed with the fire pump pumping at 100% capacity at 150 psi (1000 kPa) net pump pressure. The test shall be permitted to be run concurrently with the pump certification test.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

DOCUMENTATION

The Body Manufacturer shall deliver the following with the fire apparatus:

The results of each test shall be recorded on an appropriate form and provided with the delivery of the fire apparatus.

DIELECTRIC VOLTAGE WITHSTAND TEST

The line voltage wiring and permanently connected devices and equipment shall be subjected to a dielectric voltage withstand test of 900 volts for one (1) minute. The testing shall be performed after all body work has been completed.

The test shall be conducted as follows:

- 1) Isolate the power source from the panel board and disconnect any solid state low voltage components
- 2) Connect one lead of the dielectric tester to all the hot and neutral buses tied together
- 3) Connect the other lead to the fire apparatus frame or body
- 4) Close any switches and circuit breakers in the circuit(s)
- 5) Apply the dielectric voltage for one (1) minute in accordance with the testing equipment manufacturer's instructions

The electrical polarity of all permanently wired equipment, cord reels and receptacles shall be tested to verify that wiring connections have been properly made.

Electrical continuity shall be verified from the chassis or body to all line voltage electrical enclosures, light housings, motor housings, light poles, switch boxes and receptacle ground connections that are accessible to fire fighters in normal operations.

If the apparatus is equipped with a transfer switch, it shall be tested to verify operation and that all non grounded conductors are switched.

Electrical light towers, floodlights, motors, fixed appliances and portable generators shall be operated at their full rating or capacity for 30 minutes to ensure proper operation.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

BID BOND AND/OR SECURITY

Each bid must be accompanied by a bid bond in the amount of 10% of the maximum amount of the bid or in lieu thereof, a deposit of cash or, certified check payable to Hilton-ParmaFire District in an amount equal to 10% of the maximum amount of the bid, to assure the Hilton-ParmaFire District of the adherence of the Bidder to their bid and the execution of the contract, if their bid is accepted.

Within ten (10) days after the opening of bids, the deposits of all but the three (3) lowest responsible Bidders who comply with these specifications will be returned.

Within ten (10) days after the award of the contract, if an award is made, the deposits of the remaining two (2) unsuccessful Bidders will be returned, or if all bids are rejected, the deposits of said three (3) lowest Bidders will be returned.

Within ten (10) days after the execution of the contract and acceptance of the Bidder's bond by the Hilton-ParmaFire District, the deposit of the successful Bidder will be returned.

No plea of mistake in such accepted bid shall be available to the Bidder for the recovery of their deposit or as a defense to any action based upon such accepted bid.

PERFORMANCE BOND

The successful Bidder will be required to provide a 100% performance bond in the amount equivalent to the total amount of its bid including any additional options that may have been given. Performance bond shall be provided within two (2) weeks after notice of award.

If the Bidder to whom the contract is awarded, refuses or neglects to execute or fails to furnish the required 100% performance bond within two (2) weeks after notice, the amount of his deposit may be forfeited and retained by the Hilton-ParmaFire District as liquidated damages.

The terms of the performance bond shall continue one (1) year after completion and delivery of the apparatus.

WARRANTY

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source and will deal directly with the Hilton-ParmaFire District on all warranty work.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

GENERAL LIMITED WARRANTY - ONE (1) YEAR

The vehicle shall be free of defects in material and workmanship for a period of one (1) year or 12,000 miles, whichever occurs first starting thirty (30) days after the original invoice date.

The Contractor must be the "single source" coordinator of all warranties on the vehicle.

LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles, whichever occurs first, starting thirty (30) days after the original invoice date.

STRUCTURAL WARRANTY - TEN (10) YEARS

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles whichever occurs first, starting thirty (30) days after the original invoice date.

PAINT LIMITED WARRANTY - TEN (10) YEARS

The body shall be free of bubbling or peeling as a result of a defect in the method of manufacture for a period of ten (10) years or 100,000 miles whichever occurs first, starting thirty (30) days after the original invoice date.

GRAPHICS LIMITED WARRANTY

The 3M graphics installation shall be warranted for a period of two (2) years. The 3M materials installed on completed vehicle shall be warranted for seven (7) years. The 3M Diamond grade film (if specified) shall be warranted for ten (10) years.

CONSTRUCTION PERIOD

The completed vehicle shall be delivered within three hundred sixty (360) days after receipt of a purchase order or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to Hilton-ParmaFire District as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

OVERALL HEIGHT

The overall height (OAH) of the vehicle shall be approximately 144" (12' - 0") from the ground. This measurement shall be taken on flat ground with the tires properly inflated, in the unloaded condition, at that highest point of the vehicle.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

OVERALL LENGTH

The overall length (OAL) of the vehicle shall be approximately 436" (36' - 4").

OVERALL WIDTH

The overall width (OAW) of the body at drip rails shall be 102" (8' - 6"), and body shall be 100" (8' - 4").

ENGINEERING SUPPORT AT PRE-CONSTRUCTION MEETING

The Contractor shall provide an engineer to be present at the pre-construction meeting held at the factory location. The engineer will address all engineering related questions for the truck as purchased and for all proposed changes.

The engineer will have the 2D and/or 3D AutoCAD electronic drawings projected on screen and be able to provide dimensional data for proposed changes and proposed layouts. This will help ensure that the final design matches the Hilton-ParmaFire District intentions to the maximum extent possible.

DELIVERY AND DEMONSTRATION

The Contractor shall be responsible for the delivery of the completed unit to the Hilton-ParmaFire District's location. On initial delivery of the apparatus, the Contractor shall supply a qualified representative to demonstrate the apparatus and provide initial instruction to representatives of the Hilton-ParmaFire District regarding the operation, care and maintenance of the apparatus and equipment supplied at Hilton-ParmaFire District location.

The Delivery Engineer shall set delivery and instruction schedule with the person appointed by Hilton-ParmaFire District.

After delivery of the apparatus, the Hilton-ParmaFire District shall be responsible for ongoing training of its personnel to proficiency regarding the proper and safe use of the apparatus and associated equipment.

CHASSIS SPECIFICATION

MODEL

The chassis shall be a Metro Star model. The cab and chassis shall include design considerations for multiple emergency vehicle applications, rapid transit and maneuverability. The chassis shall be manufactured for heavy duty service with the strength and capacity to support a fully laden apparatus, one hundred (100) percent of the time.

MODEL YEAR

The chassis shall have a vehicle identification number that reflects a 2012 model year.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

COUNTRY OF SERVICE

The chassis shall be put in service in the country of United States of America (USA).

The chassis will meet applicable U.S.A. federal motor vehicle safety standards per CFR Title 49 Chapter V Part 571 as clarified in the incomplete vehicle book per CFR Title 49 Chapter V Part 568 Section 4 which accompanies each chassis. Spartan Chassis is not responsible for compliance to state, regional, or local regulations. Dealers should identify those regulations and order any necessary optional equipment from Spartan Chassis or their OEM needed to be in compliance with those regulations.

APPARATUS TYPE

The apparatus shall be a rescue vehicle designed for emergency service use which shall include the functions of a multipurpose vehicle which primarily provides support services at emergency scenes.

VEHICLE TYPE

The chassis shall be manufactured for use as a straight truck type vehicle and designed for the installation of a permanently mounted apparatus behind the cab. The apparatus of the vehicle shall be supplied and installed by the apparatus manufacturer.

AXLE CONFIGURATION

The chassis shall feature a 4 x 2 axle configuration consisting of a single rear drive axle with a single front steer axle.

GROSS AXLE WEIGHT RATINGS FRONT

The front gross axle weight rating (GAWR) of the chassis shall be 22,800 pounds.

This front gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

GROSS AXLE WEIGHT RATINGS REAR

The rear gross axle weight rating (GAWR) of the chassis shall be 27,000 pounds.

This rear gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

CAB STYLE

The cab shall be a custom, fully enclosed, ELFD model with a 24.00 inch raised roof over the driver, officer, and crew area, designed and built specifically for use as an emergency response vehicle by a company specializing in cab and chassis design for all emergency response applications. The cab shall be designed for heavy-duty service utilizing superior strength and capacity for the application of protecting the occupants of the vehicle. This style of cab shall offer up to ten (10) seating positions.

The cab shall incorporate a fully enclosed design with side wall roof supports, allowing for a spacious cab area with no partition between the front and rear sections of the cab. To provide a superior finish by reducing welds that fatigue cab metal; the roof, the rear wall and side wall panels shall be assembled using a combination of welds and proven industrial adhesives designed specifically for aluminum fabrication for construction.

The cab shall be constructed using multiple aluminum extrusions in conjunction with aluminum plate, which shall provide proven strength and the truest, flattest body surfaces ensuring less expensive paint repairs if needed. All aluminum welding shall be completed to the American Welding Society and ANSI D1.2-96 requirements for structural welding of aluminum.

All interior and exterior seams shall be sealed for optimum noise reduction and to provide the most favorable efficiency for heating and cooling retention.

The cab shall be constructed of 5052-H32 corrosion resistant aluminum plate. The cab shall incorporate tongue and groove fitted 6061-T6 0.13 & 0.19 inch thick aluminum extrusions for extreme duty situations. A single formed, one (1) piece extrusion shall be used for the "A" pillar, adding strength and rigidity to the cab as well as additional roll-over protection. The cab side walls and lower roof skin shall be 0.13 inch thick; the rear wall and raised roof skins shall be 0.09 inch thick; the front cab structure shall be 0.19 inch thick.

The exterior width of the cab shall be 94.00 inches wide with a minimum interior width of 88.00 inches. The overall cab length shall be 151.10 inches with 74.00 inches from the centerline of the front of the axle to the back of the cab.

The cab interior shall be designed to afford the maximum usable interior space and attention to ergonomics with hip and legroom while seated which exceeds industry standards. The crew cab floor shall be flat across the entire walking area for ease of movement inside the cab.

The cab shall offer an interior height of 57.50 inches from the front floor to the headliner and a rear floor to headliner height of 79.00 inches in the raised roof area, at a minimum. The cab shall offer an interior measurement at the floor level from the rear of the engine tunnel to the rear wall of the cab of 69.88 inches. All interior measurements shall include the area within the interior trimmed surfaces and not to any unfinished surface.

The cab shall include a driver and officer area with two (2) cab doors large enough for personnel in full firefighting gear. The front doors shall offer a clear opening of 40.25 inches wide X 53.50 inches high, from the cab floor to the top of the door opening. The cab shall also include a crew area with up to two (2) cab doors, also large enough for personnel in full firefighting gear. The rear doors shall offer a clear opening of 32.25 inches wide X 71.00 inches high, from the cab floor to the top of the door opening.

The cab shall incorporate a progressive two (2) step configuration from the ground to the cab floor at each door opening. The progressive steps are vertically staggered and extend the full width of each step well allowing personnel in full firefighting gear to enter and exit the cab easily and safely.

The first step for the driver and officer area shall measure approximately 11.50 inches deep X 31.50 inches wide. The intermediate step shall measure approximately 8.50 inches deep X 33.00 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 11.00 inches.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

The first step for the crew area shall measure approximately 11.50 inches deep X 21.50 inches wide. The intermediate step shall measure approximately 10.25 inches deep X 22.50 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 12.50 inches.

CAB FRONT FASCIA

The front cab fascia shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate which shall be an integral part of the cab.

The cab fascia will encompass the entire front of the aluminum cab structure from the bottom of the windshield to the bottom of the cab and shall be the "Classic" design.

The front cab fascia shall include two (2) molded plastic modules on each side accommodating a total of up to four (4) Hi/Low beam headlights and two (2) turn signal lights or up to four (4) warning lights. A chrome plated molded plastic bezel shall be provided on each side around each set of four lamps.

FRONT GRILLE

The front cab fascia shall include a classic box style, 304 stainless steel front grille with a Spartan logo. The grille shall measure 44.45 inches wide at the top tapering to 39.30 inches wide at the bottom X 33.50 inches high X 1.50 inches deep. The grille shall include a minimum free air intake of 632.90 square inches.

CAB UNDERCOAT

There shall be a rubberized undercoating applied to the underside of the cab that provides abrasion protection, sound deadening and corrosion protection.

CAB SIDE DRIP RAIL

There shall be a drip rail along the top radius of each cab side. The drip rails shall help prevent water from the cab roof running down the cab side.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CAB PAINT EXTERIOR

The cab shall be painted prior to the installation of glass accessories and all other cab trim to ensure complete paint coverage and the maximum in corrosion protection of all metal surfaces.

All metal surfaces on the entire cab shall be ground by disc to remove any surface oxidation or surface debris which may hinder the paint adhesion. Once the surface is machine ground a high quality acid etching of base primer shall be applied. Upon the application of body fillers and their preparation, the cab shall be primed with a coating designed for corrosion resistance and surface paint adhesion. The maximum thickness of the primer coat shall be 2.00 mils.

The entire cab shall then be coated with an intermediate solid or epoxy surfacing agent that is designed to fill any minor surface defects, provide an adhesive bond between the primer and the paint and improve the color and gloss retention of the color. The finish to this procedure shall be a sanding of the cab with 360 grit paper, the seams shall be sealed with SEM brand seam sealer and painted with two (2) to four (4) coats of an acrylic urethane type system designed to retain color and resist acid rain and most atmospheric chemicals found on the fire ground or emergency scene.

The cab shall then be painted with the upper and lower colors specifically designated by the customer with a minimum thickness of two 2.00 mils of paint, followed by a clear top coat not to exceed 2.00 mils. The entire cab shall then be baked at 180 degrees for one (1) hour to speed the curing process of the coatings.

CAB PAINT MANUFACTURER

The cab shall be painted with PPG Industries paint.

CAB PAINT PRIMARY/LOWER COLOR

The lower paint color shall be PPG FBCH 934007 red.

CAB PAINT SECONDARY/UPPER COLOR

The secondary/upper paint color shall be PPG FBCH 902547 cream.

CAB PAINT EXTERIOR BREAKLINE

The upper and lower paint shall meet at a breakline on the cab which shall be located approximately 1.00 inch below the door windows on each side of the cab. The breakline shall curve down at the front cab corners to approximately 5.00 inches below the windshields on the front of the cab.

CAB PAINT PINSTRIPE

A 0.50 inch wide gold reflective tape with black borders shall be applied on the break line between the two different colored surfaces.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CAB PAINT WARRANTY

The cab and chassis shall be covered by a limited manufacturer paint warranty which shall be in effect for ten (10) years from the first owner's date of purchase or in service or the first 100,000 actual miles, whichever occurs first.

CAB PAINT INTERIOR

The visible interior cab structure surfaces shall be painted with a Zolatone #20-72 silver gray texture finish.

CAB ENTRY DOORS

The cab shall include four (4) entry doors, two (2) front doors and two (2) crew doors designed for ease of entering and egress when outfitted with an SCBA. The doors shall be constructed of extruded aluminum with a nominal thickness of 0.13 inch. The exterior skins shall be constructed of 0.13 inch aluminum plate.

The doors shall include a double rolled style automotive rubber seal around the perimeter of each door frame and door edge which ensures a weather tight fit.

All door hinges shall be hidden within flush mounted cab doors for a pleasing smooth appearance and perfect fit along each side of the cab. Each door hinge shall be piano style with a 0.38 inch pin and shall be constructed of stainless steel.

CAB ENTRY DOOR TYPE

All cab entry doors shall be full length in design to fully enclose the lower cab steps.

LH EXTERIOR REAR COMPARTMENT

The cab shall offer an exterior compartment on the left side of the cab behind the rear door. The compartment opening shall be 17.00 inches wide X 31.19 inches high. The compartment size shall be 17.34 inches wide X 31.19 inches high X 21.19 inches deep. The compartment shall have a 16.63 inch wide, 32.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a bright aluminum tread plate inner panel and a bent D-ring slam latch. There shall be a switch to activate a light inside the compartment and the open compartment warning light in the cab in the event the door is left ajar.

LEFT HAND EXTERIOR REAR COMPARTMENT LIGHTING

There shall be one (1) SoundOff Signal brand LED strip light installed to illuminate the exterior rear compartment on the left side of the cab. The strip light shall be 21.00 inches long and shall include six (6) bright white Gen3 LEDs.

LH EXTERIOR COMPARTMENT INTERIOR FINISH

The interior of the left hand exterior compartment shall have a DA sanded finish.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

RH EXTERIOR REAR COMPARTMENT

The cab shall offer an exterior compartment on the right side of the cab behind the rear door. The compartment opening shall be 17.00 inches wide X 31.19 inches high. The compartment size shall be 17.34 inches wide X 31.19 inches high X 21.19 inches deep. The compartment shall have a 16.63 inch wide, 32.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a bright aluminum tread plate inner panel and a bent D-ring slam latch. There shall be a switch to activate a light inside the compartment and the open compartment warning light in the cab in the event the door is left ajar.

RIGHT HAND EXTERIOR REAR COMPARTMENT LIGHTING

There shall be one (1) SoundOff Signal brand LED strip light installed to illuminate the exterior rear compartment on the right side of the cab. The strip light shall be 21.00 inches long and shall include six (6) bright white Gen3.

RH EXTERIOR COMPARTMENT INTERIOR FINISH

The interior of the right hand exterior compartment shall have a DA sanded finish.

REAR CAB WALL CUTOUT

The rear wall of the cab shall include a cut out which measures 24.00 inches wide X 76.50 inches tall to accommodate a walk through application.

CAB STRUCTURAL WARRANTY

The cab structure shall be warranted for a period of ten (10) years or one hundred thousand (100,000) miles which ever may occur first. Warranty conditions may apply and shall be listed in the detailed warranty document that shall be provided upon request.

CAB TEST INFORMATION

The cab shall have successfully completed the preload side impact, static roof load application and frontal impact without encroachment to the occupant survival space when tested in accordance with Section 4 of SAE J2420 COE Frontal Strength Evaluation Dynamic Loading Heavy Trucks, Section 5 of SAE J2422 Cab Roof Strength Evaluation Quasi –Static Loading Heavy Trucks and ECE R29 Uniform Provisions Concerning the Approval of Vehicles with regard to the Protection of the Occupants of the Cab of a Commercial Vehicles Annex 3 Paragraph 5.

The above tests have been witnessed by and attested to by an independent third party. The test results were recorded using cameras, high speed imagers, accelerometers and strain gauges. Documentation of the testing shall be provided upon request.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ELECTRICAL SYSTEM

The chassis shall include a single starting electrical system which shall include a 12 volt direct current system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be color coded and shall include the circuit number and function where possible. The wiring shall be protected by 275 degree Fahrenheit minimum high temperature flame retardant loom.

APPARATUS WIRING PROVISION

An apparatus wiring panel shall be installed in the center dash area behind the rocker switch panel which shall include eight (8) open circuits consisting of three (3) 20 amp, one (1) 30 amp, three (3) 10 amp, and one (1) 15 amp circuit, with relays and breakers with trigger wires which shall be routed to the rocker switch panel.

LOAD MANAGEMENT SYSTEM

The apparatus shall be equipped with a Class 1 Total System Manager (TSM) for performing electrical load management. The TSM shall have sixteen (16) programmable outputs to supply warning and load switching requirements. Outputs one (1) through twelve (12) shall be independently programmable to activate during the scene mode, the response mode, or both. These outputs can also be programmed to activate with the ignition or master warning switch, or to sequence and shed along with the priority. Output thirteen (13) shall be designated to activate a fast idle system. Output fourteen (14) shall provide a low voltage warning for an isolated battery. Output fifteen (15) is a user configurable output and shall be programmable for activating between 10.50 and 15.00 volts. Output sixteen (16) shall provide a low voltage alarm that activates at the NFPA required 11.80 volts. The TSM shall have a digital display to indicate system voltage in normal operation mode and also indicate the output configuration during programming mode. The TSM shall be protected against reverse polarity and shorted outputs and be enclosed in a metal enclosure to enhance EMI/RFI protection.

DATA RECORDING SYSTEM

The chassis shall have a Class One Vehicle Data Recorder (VDR) system installed. The system shall be designed to meet NFPA 1901. The following information shall be recorded:

- Vehicle Speed
- Acceleration
- Deceleration
- Engine Speed
- Engine Throttle Position
- ABS Event
- Seat Occupied Status
- Seat Belt Status
- Master Optical Warning Device Switch Position
- Time
- Date

Each portion of the data shall be recorded at the specified intervals and stored for the specified length of time to meet NFPA 1901 guidelines and shall be retrievable by connecting a laptop computer to the VDR system. The laptop connection shall be a panel mounted female type B USB connection point, remotely mounted in the left side foot well of the cab.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ACCESSORY POWER DISTRIBUTION PANEL

An accessory power distribution panel shall be installed behind the officers' seat. The panel shall feature ten (10) blade type fuses protected by a 40 amp fuse. The panel shall be capable of carrying up to a maximum 40 amp battery direct load.

ACCESSORY POWER

The electrical distribution panel shall include two (2) power studs. The studs shall be size #10 and each of the power studs shall be circuit protected with a fuse of the specified amperage. One (1) power stud shall be capable of carrying up to a 40 amp battery direct load. One (1) power stud shall be capable of carrying up to a 15 amp ignition switched load. The two (2) power studs shall share one (1) #10 ground stud.

AUXILIARY ACCESSORY POWER

An auxiliary set of power and ground studs shall be provided and installed behind the electrical center cover with a 40 amp breaker. The studs shall be 0.38 inch diameter and capable of carrying up to a 40 amp load switched with the master power switch.

EXTERIOR ELECTRICAL TERMINAL COATING

All terminals exposed to the elements will be sprayed with a high visibility protective rubberized coating to prevent corrosion.

ENGINE

The chassis engine shall be a Cummins ISC8.3 engine. The ISC8.3 engine shall be an in-line six (6) cylinder, four cycle diesel powered engine. The engine shall offer a rating of 380 horse power at 2000 RPM and shall be governed at 2200 RPM. The torque rating shall feature 1050 foot pounds of torque at 1400 RPM with 506 cubic inches (8.3 liter) of displacement.

The ISC8.3 engine shall feature a VGT™ Turbocharger, a high pressure common rail fuel system, fully integrated electronic controls with an electronic governor, and shall be EPA certified to meet the 2010 emissions standards using cooled exhaust gas recirculation and selective catalytic reduction technology.

The engine shall include an engine mounted combination full flow/by-pass oil filter with replaceable spin on cartridge for use with the engine lubrication system. The engine shall include Citgard brand Citgard 500, or equivalent SAE 15W40 CJ4 low ash engine oil which shall be utilized for proper engine lubrication.

A wiring harness shall be supplied ending at the back of the cab. The harness shall include a connector which shall allow an optional harness for the pump panel. The included circuits shall be provided for a tachometer, oil pressure, engine temperature, hand throttle, high idle and a PSG system. A circuit for J1939 data link shall also be provided at the back of the cab.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CAB ENGINE TUNNEL

The cab interior shall include an integrated engine tunnel constructed of 5052-H32 Marine Grade, 0.19 of an inch thick aluminum. The tunnel shall be a maximum of 41.50 inches wide X 25.50 inches high.

DIESEL PARTICULATE FILTER CONTROLS

There shall be two (2) controls for the diesel particulate filter. One (1) control shall be for regeneration and one (1) control shall be for regeneration inhibit.

ENGINE PROGRAMMING HIGH IDLE SPEED

The engine high idle control shall maintain the engine idle at approximately 1250 RPM when engaged.

ENGINE HIGH IDLE CONTROL

The vehicle shall be equipped with an automatic high-idle speed control which shall be pre-set to operate when the engine is at a specified RPM to increase alternator output. This device shall operate only when the master switch is activated and the transmission is in neutral with the parking brake set. The device shall disengage when the operator depresses the brake pedal, or the transmission is placed in gear, and shall automatically re-engage when the brake is released, or when the transmission is placed in neutral.

ENGINE PROGRAMMING ROAD SPEED GOVERNOR

The engine shall include programming which will govern the top speed of the vehicle.

AUXILIARY ENGINE BRAKE

A compression brake, for the six (6) cylinder engine shall be provided. A cutout relay shall be installed to disable the compression brake when in pump mode or when an ABS event occurs. The engine compression brake shall activate upon 0% accelerator when in operation mode and actuate the vehicle's brake lights.

The engine shall utilize a variable geometry turbo (VGT) as an integrated auxiliary engine brake to offer a variable rate of exhaust flow, which when activated in conjunction with the compression brake shall enhance the engine's compression braking capabilities.

AUXILIARY ENGINE BRAKE CONTROL

An engine compression brake control device shall be included. The electronic control device shall monitor various conditions and shall activate the engine brake only if all of the following conditions are simultaneously detected:

- A valid gear ratio is detected.
- The driver has requested or enabled engine compression brake operation.
- The throttle is at a minimum engine speed position.
- The electronic controller is not presently attempting to execute an electronically controlled final drive gear shift.

The compression brake shall be controlled through an on/off switch and a low/medium/high selector switch.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ELECTRONIC ENGINE OIL LEVEL INDICATOR

The engine oil shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal. The warning shall activate in a low oil situation upon turning on the master battery and ignition switches without the engine running.

FLUID FILLS

The engine oil, coolant, transmission, and power steering fluid fills shall be located under the cab. The windshield washer fill shall be accessible through the front left side mid step.

ENGINE DRAIN PLUG

The engine shall include an original equipment manufacturer installed oil drain plug.

ENGINE WARRANTY

The Cummins engine shall be warranted for a period of five (5) years or 100,000 miles, whichever occurs first.

ENGINE PROGRAMMING REMOTE THROTTLE

The engine ECM (Electronic Control Module) discreet wire remote throttle circuit shall be turned off for use with a J1939 based pump controller or when the discreet wire remote throttle controls are not required.

ENGINE PROGRAMMING IDLE SPEED

The engine low idle speed will be programmed at 700 rpm.

ENGINE FAN DRIVE

The engine cooling system fan shall incorporate a thermostatically controlled, Horton clutched type fan drive.

When the clutched fan is disengaged it shall facilitate improved vehicle performance, cab heating in cold climates, and fuel economy. The fan clutch design shall be fail safe so that if the clutch drive fails the fan shall engage to prevent engine overheating due to the fan clutch failure.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ENGINE COOLING SYSTEM

There shall be a heavy-duty aluminum cooling system designed to meet the demands of the emergency response industry. The cooling system shall have the capacity to keep the engine properly cooled under all conditions of road and pumping operations. The cooling system shall be designed and tested to meet or exceed the requirements specified by the engine and transmission manufacturer and all EPA requirements. The complete cooling system shall be mounted to isolate the entire system from vibration or stress. The individual cores of the cooling system shall be mounted in a manner to allow expansion and contraction at various rates without inducing stress into the adjoining cores.

The cooling system shall utilize a charge air cooler to radiator serial flow package that provides the maximum cooling capacity for the specified engine as well as serviceability. The main components shall include a surge tank, an air to air charge air cooler bolted to the front of the radiator, recirculation shields, a shroud, a fan, and required tubing.

The radiator shall be a down-flow design constructed with aluminum cores, plastic end tanks, and a steel frame. The radiator shall be equipped with a drain cock to drain the coolant for serviceability.

The cooling system shall include a one piece injection molded polymer eleven (11) blade fan with a fiberglass fan shroud.

The cooling system shall be equipped with a surge tank that is capable of removing entrained air from the system. The surge tank shall be equipped with a low coolant probe and sight glass to monitor the level of the coolant. The surge tank shall have a dual seal cap that meets the engine manufacturer's pressure requirements, and allows for expansion and recovery of coolant into a separate integral expansion chamber.

All radiator tubes shall be formed from aluminized steel tubing. Recirculation shields shall be installed where required to prevent heated air from reentering the cooling package and affecting performance.

The charge air cooler shall be a cross-flow design constructed completely of aluminum with cast tanks. All charge air cooler tubes shall be formed from aluminized steel tubing and installed with silicone hump hoses and stainless steel "constant torque" style clamps meeting the engine manufacturer's requirements.

ENGINE COOLING SYSTEM PROTECTION

The engine cooling system shall include a recirculation shield designed to act as a light duty skid plate below the radiator to provide additional protection for the engine cooling system from light impacts, stones, and road debris.

ENGINE COOLANT

The cooling package shall include Extended Life Coolant (ELC). The use of ELC provides longer intervals between coolant changes over standard coolants providing improved performance. The coolant shall contain a 50/50 mix of ethylene glycol and de-ionized water to keep the coolant from freezing to a temperature of -34 degrees Fahrenheit.

Proposals offering supplemental coolant additives (SCA) shall not be considered, as this is part of the extended life coolant makeup.

ELECTRONIC COOLANT LEVEL INDICATOR

The instrument panel shall feature a low engine coolant indicator light which shall be located in the center of the instrument panel. An audible tone alarm shall also be provided to warn of a low coolant incident.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

COOLANT HOSES

The cooling system hoses shall be silicone heater hose with rubber hoses in the cab interior. The radiator hoses shall be formed silicone coolant hoses with formed aluminized steel tubing. All heater hose, silicone coolant hose, and tubing shall be secured with stainless steel constant torque band clamps.

ENGINE AIR INTAKE

The engine air intake system shall include an ember separator air intake filter which shall be located in the front of the cab behind the right hand side fascia. This filter shall protect the downstream air filter from embers using a combination of unique flat and crimped metal screens constructed into a corrosion resistant steel frame. This multilayered screen shall be designed to trap embers or allow them to burn out before passing through the pack, while creating only minimal air flow restriction through the system. Periodic cleaning or replacement of the screen shall be all that is required after installation.

The engine shall also include an air intake filter which shall be bolted to the frame and located under the front of the cab on the right hand side. The dry type filter shall ensure dust and debris safely contained inside the disposable housing, eliminating the chance of contaminating the air intake system during air filter service via a leak-tight seal.

The air flow distribution and dust loading shall be uniform throughout the high-performance filter cone pack, which shall result in pressure differential for improved horsepower and fuel economy. The air intake shall be mounted within easy access via a hinged panel behind the right hand side headlight module. The air intake system shall include a restriction indicator light in the warning light cluster on the instrument panel, which shall activate when the air cleaner element requires replacement.

ENGINE EXHAUST SYSTEM

The exhaust system shall include a diesel particulate filter (DPF), a diesel oxidation catalyst, and a selective catalytic reduction catalyst (SCR) to meet current EPA standards. The selective catalytic reduction catalyst utilizes a diesel exhaust fluid solution consisting of urea and purified water to convert NO_x into nitrogen, water, and trace amounts of carbon dioxide. The solution shall be injected into the system through the decomposition tube between the DPF and SCR.

The system shall utilize 0.07 inch thick stainless steel exhaust tubing between the engine turbo and the DPF. Zero leak clamps seal all system joints between the turbo and DPF.

The DPF, the decomposition tube, and the SCR canister through the end of the tailpipe shall be connected with zero leak clamps. The discharge shall terminate horizontally on the right side of the vehicle ahead of the rear tires.

The exhaust system shall be mounted below the frame in the inboard position with the SCR canister in line rearward of the DPF.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

DIESEL EXHAUST FLUID TANK

The exhaust system shall include a molded cross linked polyethylene tank for Diesel Exhaust Fluid (DEF). The tank shall have a capacity of six (6) usable gallons and shall be mounted on the left hand side of the chassis frame behind the batteries below the frame.

The DEF tank shall be designed with capacity for expansion in case of fluid freezing. Engine coolant, which shall be thermostatically controlled, shall be run through lines in the tank to help prevent the DEF from freezing and to provide a means of thawing the fluid if it should become frozen.

The tank fill tube shall be routed under the rear of the cab with the fill neck and splash guard accessible in the top rear step.

ENGINE EXHAUST WRAP

The exhaust tubing between the engine turbo and the diesel particulate filter (DPF) shall be wrapped with a thermal cover in order to retain the necessary heat for DPF regeneration. The exhaust wrap shall also help protect surrounding components from radiant heat which can be transferred from the exhaust.

TRANSMISSION

The drive train shall include an Allison model EVS 3000 torque converting, automatic transmission which shall include electronic controls. The transmission shall feature two (2) 10-bolt PTO pads located on the converter housing.

The transmission shall include two (2) internal oil filters and Castrol TranSynd™ synthetic TES 295 transmission fluid which shall be utilized in the lubrication of the EVS transmission. An electronic oil level sensor shall be included with the readout located in the shift selector.

The transmission gear ratios shall be:

1st	3.49:1
2nd	1.86:1
3rd	1.41:1
4th	1.00:1
5th	0.75:1
6th	0.65:1 (if applicable)
Rev	5.03:1

TRANSMISSION MODE PROGRAMMING

The transmission, upon start-up, will select a six (6) speed operation without the need to press the mode button.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

TRANSMISSION FEATURE PROGRAMMING

The Allison Gen IV-E EVS group package number 127 shall contain the 199 vocational package in consideration of the duty of this apparatus for rescue. This package shall incorporate an automatic neutral with selector override. This feature commands the transmission to neutral when the park brake is applied, regardless of drive range requested on the shift selector. This requires re-selecting drive range to shift out of neutral for the override.

An eight (8) pin Delphi connector will be provided next to the steering column connector. This will contain the following input/output circuits to the transmission control module. The Gen IV-E transmission shall include prognostic diagnostic capabilities. These capabilities shall include the monitoring of the fluid life, filter change indication, and transmission clutch maintenance.

Function ID	Description	Wire assignment
C	PTO Request	143
F	Aux. Function Range Inhibit (Special)	101/142
G	PTO Enable Output (See Input Function C)	130
S	Neutral Indicator for PTO	145
	Signal Return	103

TRANSMISSION SHIFT SELECTOR

An Allison pressure sensitive range selector touch pad shall be provided and located to the right of the driver within clear view and easy reach. The shift selector shall provide a prognostic indicator (wrench symbol) on the digital display between the selected and attained indicators. The prognostics monitor various operating parameters to determine and shall alert you when a specific maintenance function is required.

ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR

The transmission fluid shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal.

TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE

When the auxiliary brake is engaged, the transmission shall automatically shift to second gear to decrease the rate of speed assisting the secondary braking system and slowing the vehicle.

TRANSMISSION COOLING SYSTEM

The transmission shall include a water to oil cooler system located in the cooling loop between the radiator and the engine. The transmission cooling system shall meet all transmission manufacturer requirements. The transmission cooling system shall feature continuous flow of engine bypass water to maintain uninterrupted transmission cooling.

TRANSMISSION DRAIN PLUG

The transmission shall include an original equipment manufacturer installed oil drain plug.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

TRANSMISSION WARRANTY

The Allison EVS series transmission shall be warranted for a period of five (5) years with unlimited mileage. Parts and labor shall be included in the warranty.

PTO PROGRAMMING

The power take off shall be programmed for operator control such that it shall only engage at or below 900 RPM and operate in a range up to 4000 RPM. The PTO programming shall provide for automatic disengagement set at a specified engine speed of 4000 RPM which shall protect equipment driven from the power take off.

PTO CONTROL

A pre-wire shall be provided for a customer mounted left hand power take off which shall be controlled by the transmission. The power take off shall be activated by a locking on/off rocker switch which contains an integral light which shall illuminate upon a positive engagement of the power take off. This switch shall be located on dash.

Required operating conditions for enabling this function are:

- Throttle position is low
 - Engine speed is within customer modifiable constant limits
 - Output speed is within customer modifiable constant limits
- Park brake set

DRIVELINE

All drivelines shall be heavy duty metal tube and equipped with Spicer 1710 series universal joints. The shafts shall be dynamically balanced prior to installation to alleviate future vibration. In areas of the driveline where a slip shaft is required, the splined slip joint shall be coated with Glide Coat[®].

FUEL FILTER/WATER SEPARATOR

The fuel system shall have a Fleetguard FS1003 fuel filter/water separator as a primary filter. The fuel filter shall have a drain valve.

A water in fuel sensor shall be provided and wired to an instrument panel lamp and audible alarm to indicate when water is present in the fuel/water separator.

A secondary fuel filter shall be included as approved by the engine manufacturer.

FUEL LINES

The fuel system supply and return lines installed from the fuel tank to the engine shall be black textile braided lines which are reinforced with braided high tensile steel wire. The fuel lines shall be connected with reusable steel fittings.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

FUEL SHUTOFF VALVE

A fuel shutoff valve shall be installed in the fuel draw line at the primary fuel filter to allow the fuel filter to be changed without loss of fuel to the fuel pump.

FUEL COOLER

An aluminum cross flow air to fuel cooler shall be provided to lower fuel temperature allowing the vehicle to operate at higher ambient temperatures. The fuel cooler shall be located behind the rear axle.

FUEL TANK

The fuel tank shall have a capacity of sixty-eight (68) gallons and shall measure 35.00 inches in width X 17.00 inches in height X 29.00 inches in length. The baffled tank shall be made of 14 gauge aluminized steel. The exterior of the tank shall be painted with a PRP Corsol™ black anti-corrosive exterior metal treatment finish. This results in a tank which offers the internal and external corrosion resistance. In addition, the exterior of the fuel tank shall be coated with Spar-Liner spray on protective coating.

The tank shall have a vent port to facilitate venting to the top of the fill neck for rapid filling without "blow-back" and a roll over ball check vent for temperature related fuel expansion and draw.

The tank is designed with dual draw tubes and sender flanges. The tank shall have 2.00 inch NPT fill ports for right or left hand fill. A 0.50 inch NPT drain plug shall be centered in the bottom of the tank.

The fuel tank shall be mounted below the frame, behind the rear axle. Two (2) three-piece strap hanger assemblies with "U" straps bolted midway on the fuel tank front and rear shall be utilized to allow the tank to be easily lowered and removed for service purposes. Rubber isolating pads shall be provided between the tank and the upper tank mounting brackets. Strap mounting studs through the rail, hidden behind the body shall not be acceptable.

FUEL TANK FILL PORT

The fuel tank fill ports shall be provided with two (2) left fill ports located one (1) in the forward position and one (1) in the middle position and the right fill port located in the middle position of the fuel tank.

FUEL TANK SERVICEABILITY PROVISIONS

The chassis fuel lines shall have additional length provided so the tank can be easily lowered and removed for service purposes. The additional 8.00 feet of length shall be located above the fuel tank and shall be coiled and secured. The fuel line fittings shall be pointed towards the right side (curbside) of the chassis.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

FRONT AXLE

The front axle shall be a Meritor Easy Steer Non drive front axle, model number MFS-23. The axle shall include a 3.74 inch drop and a 71.00 inch king pin intersection (KPI). The axle shall include a conventional style hub with a standard knuckle. The weight capacity for the axle shall be rated to 23,000 pounds. This rating shall require special approvals from the wheel manufacturers.

FRONT AXLE WARRANTY

The front axle shall be warranted by Meritor for two (2) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

FRONT WHEEL BEARING LUBRICATION

The front axle wheel bearings shall be lubricated with oil. The oil level can be visually checked via clear inspection windows in the front axle hubs.

FRONT SHOCK ABSORBERS

Two (2) Bilstein inert, nitrogen gas filled shock absorbers shall be provided and installed as part of the front suspension system. The shocks shall be a monotubular design and fabricated using a special extrusion method, utilizing a single blank of steel without a welded seam, achieving an extremely tight peak-to-valley tolerance and maintains consistent wall thickness. The monotubular design shall provide superior strength while maximizing heat dissipation and shock life.

The ride afforded through the use of a gas shock is more consistent and shall not deteriorate with heat, the same way a conventional oil filled hydraulic shock would.

The Bilstein front shocks shall include a digressive working piston assembly allowing independent tuning of the compression and rebound damping forces to provide optimum ride and comfort without compromise. The working piston design shall feature fewer parts than most conventional twin tube and "road sensing" shock designs and shall contribute to the durability and long life of the Bilstein shock absorbers.

Proposals offering the use of conventional twin tube or "road sensing" designed shocks shall not be considered.

FRONT SUSPENSION

The front suspension shall include a ten (10) leaf spring pack in which the longest leaf measures 53.38 inch long and 4.00 inches wide. The springs shall be shot peened for long life and include a military double wrapped front eye. The springs shall be bolted in place with M20 10.9 bolts and have replaceable rubber bushings in the spring eyes. The spring capacity shall be rated at 23,000 pounds.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

STEERING COLUMN/ WHEEL

The cab shall include a Douglas Autotech steering column which shall include a seven (7) position tilt, a 2.25 inch telescopic adjustment, and an 18.00 inch, two (2) spoke steering wheel located at the driver's position. The steering wheel shall be covered with black polyurethane foam padding.

The steering column shall contain a horn button, self-canceling turn signal switch, four-way hazard switch and headlamp dimmer switch.

POWER STEERING PUMP

The hydraulic power steering pump shall be a TRW PS and shall be gear driven from the engine. The pump shall be a balanced, positive displacement, sliding vane type.

ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR

The power steering fluid shall be monitored electronically and shall send a signal to activate an audible alarm and visual warning in the instrument panel when fluid level falls below normal.

FRONT AXLE CRAMP ANGLE

The chassis shall have a front axle cramp angle of 48-degrees to the left and 44-degrees to the right.

POWER STEERING GEAR

The power steering gear shall be a TRW model TAS 85 with an assist cylinder.

CHASSIS ALIGNMENT

The chassis frame rails shall be measured to insure the length is correct and cross checked to make sure they run parallel and are square to each other. The front and rear axles shall be laser aligned. The front tires and wheels shall be aligned and toe-in set on the front tires by the chassis manufacturer.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

REAR AXLE

The rear axle shall be a Meritor model RS-25-160 single drive axle. The axle shall include precision forged, single reduction differential gearing, and shall have a fire service rated capacity of 27,000 pounds.

The axle shall be built of superior construction and quality components to provide the rugged dependability needed to stand up to the fire industry's demands. The axle shall include rectangular shaped, hot-formed housing with a standard wall thickness of 0.63 of an inch for extra strength and rigidity and a rigid differential case for high axle strength and reduced maintenance.

The axle shall have heavy-duty Hypoid gearing for longer life, greater strength and quieter operation. Industry-standard wheel ends for compatibility with both disc and drum brakes, and unitized oil seal technology to keep lubricant in and help prevent contaminant damage will be used.

REAR AXLE DIFFERENTIAL LUBRICATION

The rear axle differential shall be lubricated with oil.

REAR AXLE WARRANTY

The rear axle shall be warranted by Meritor for two (2) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

REAR WHEEL BEARING LUBRICATION

The rear axle wheel bearings shall be lubricated with oil.

REAR AXLE DIFFERENTIAL CONTROL

A driver controlled differential lock shall be installed on the rear axle. This feature shall allow the main differential to be locked and unlocked when encountering poor road or highway conditions, where maximum traction is needed, for use at speeds no greater than 25 MPH. The differential lock shall be controlled by a locking rocker switch on the switch panel. The light on the switch shall illuminate with positive engagement of the differential control.

VEHICLE TOP SPEED

The top speed of the vehicle shall be approximately 68 MPH +/-2 MPH at governed engine RPM.

REAR SUSPENSION

The single rear axle shall feature a Reyco 79KB vari-rate, self-leveling captive slipper type conventional multi-leaf spring suspension, with 57.50 inch X 3.00 inch springs. One (1) adjustable and one (1) fixed torque rod shall be provided.

The rear suspension capacity shall be rated from 21,000 to 31,500 pounds.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

FRONT TIRE

The front tires shall be Michelin 425/65R22.5 "L" tubeless radial XFE regional tread.

The front tire stamped load capacity shall be 22,800 pounds per axle with a speed rating of 65 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Tire Intermittent Service Rating load capacity shall be 24,400 pounds per axle with a speed rating of up to 75 miles per hour when properly inflated to 120 pounds per square inch. The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to one (1) hour of loaded travel with a one (1) hour cool down prior to another loaded run.

REAR TIRE

The rear tires shall be Michelin 12R-22.5 16PR "H" tubeless radial XDS regional tread.

The rear tire stamped load capacity shall be 27,120 pounds per axle with a speed rating of 65 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Tire Intermittent Service Rating load capacity shall be 28,880 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch. The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to one (1) hour of loaded travel with a one (1) hour cool down prior to another loaded run.

REAR AXLE RATIO

The rear axle ratio shall be 5.63:1.

TIRE PRESSURE INDICATOR

There shall be a voucher provided with the chassis for a dial style tire pressure indicator at the front and rear tire valve stem. The indicator shall provide visual indication of pressure in the specific tire.

The tire pressure indicators shall be redeemed upon the vehicle manufacturer's receipt of the voucher for installation by the customer.

FRONT WHEEL

The front wheels shall be Alcoa hub piloted, 22.50 inch X 12.25 inch LvL One™ polished aluminum wheels. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts. The wheels shall feature one-piece forged strength and a polished finish that lasts.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

REAR WHEEL

The rear wheels shall be Alcoa hub piloted, heavy duty, 22.50 inch X 9.00 inch aluminum wheels. Each wheel shall have a polished aluminum finish. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

WHEEL GUARDS

The rear dual wheels shall include a plastic isolator approximately 0.04" thick installed between the inner and outer wheel to help prevent corrosion caused by metal to metal contact.

BRAKE SYSTEM

A rapid build-up air brake system shall be provided. The air brakes shall include a two (2) air tank, three (3) reservoir system with a total of 4152 cubic inch of air capacity. A floor mounted treadle valve shall be mounted inside the cab for graduated control of applying and releasing the brakes. An inversion valve shall be installed to provide a service brake application in the unlikely event of primary air supply loss. All air reservoirs provided on the chassis shall be labeled for identification.

The rear axle spring brakes shall automatically apply in any situation when the air pressure falls below 25 PSI and shall include a mechanical means for releasing the spring brakes when necessary. An audible alarm shall designate when the system air pressure is below 60 PSI.

A four (4) sensor, four (4) modulator anti-lock braking system (ABS) shall be installed on the front and rear axles in order to prevent the brakes from locking or skidding while braking during hard stops or on icy or wet surfaces. This in turn shall allow the driver to maintain steering control under heavy braking and in most instances, shorten the braking distance. The electronic monitoring system shall incorporate diagonal circuitry which shall monitor wheel speed during braking through a sensor and tone ring on each wheel. A dash mounted ABS lamp shall be provided to notify the driver of a system malfunction. The ABS system shall automatically disengage the auxiliary braking system device when required. The speedometer screen shall be capable of reporting all active defaults using PID/SID and FMI standards.

Additional safety shall be accommodated through Automatic Traction Control (ATC) which shall be installed on the single rear axle. The ATC system shall apply the ABS when the drive wheels loose traction. The system shall scale the electronic engine throttle back to prevent wheel spin while accelerating on ice or wet surfaces.

A momentary rocker style switch shall be provided and properly labeled "mud/snow". When the switch is pressed once, the system shall allow a momentary wheel slip to obtain traction under extreme mud and snow conditions. During this condition the ATC light and the light on the rocker switch shall blink continuously notifying the driver of activation. Pressing the switch again shall deactivate the mud/snow feature.

The Electronic Stability Control (ESC) unit is a functional extension of the electronic braking system. It is able to detect any skidding of the vehicle about its vertical axis as well as any rollover tendency. The control unit comprises an angular-speed sensor that measures the vehicle's motion about the vertical axis, caused, for instance, by cornering or by skidding on a slippery road surface. An acceleration sensor measures the vehicle's lateral acceleration. The Controller Area Network (CAN) bus provides information on the steering angle. On the basis of lateral acceleration and steering angle, an integrated microcontroller calculates a theoretical angular speed for the stable vehicle condition.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

FRONT BRAKES

The front brakes shall be Meritor EX225 Disc Plus disc brakes with 17.00 inch vented rotors.

REAR BRAKES

The rear brakes shall be Meritor 16.50 inch X 7.00 inch S-cam drum type. The brakes shall feature a cast iron shoe.

PARK BRAKE

Upon application of the push-pull valve in the cab, the rear brakes will engage via mechanical spring force. This is accomplished by dual chamber rear brakes, satisfying the FMVSS parking brake requirements.

PARK BRAKE CONTROL

A Meritor-Wabco manual hand control push-pull style valve shall operate the parking brake system. The control shall be yellow in color.

The parking brake actuation valve shall be mounted on the left hand dash to the right of the steering column within easy reach of the driver.

REAR BRAKE SLACK ADJUSTERS

The rear brakes shall include Meritor automatic slack adjusters installed on the axle which features a simple, durable design offering reduced weight. The automatic slack adjusters shall feature a manual adjusting nut which cannot inadvertently be backed off and threaded grease fittings for easy serviceability.

REAR BRAKE DUST SHIELDS

The rear brakes shall be equipped with brake dust shields.

AIR DRYER

The brake system shall include a Wabco System Saver 1200 air dryer with an integral 100 watt heater with a Metri-Pack sealed connector. The air dryer incorporates an internal turbo cutoff valve that closes the path between the air compressor and air dryer purge valve during the compressor "unload" cycle. The turbo cutoff valve allows purging of moisture and contaminants without the loss of turbo boost pressure. The air dryer shall be located on the right hand frame rail forward of the front wheel behind the right hand cab step.

FRONT BRAKE CHAMBERS

The front brakes shall be provided with MGM type 24 long stroke brake chambers.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

REAR BRAKE CHAMBERS

The rear axle shall include TSE 30/36 brake chambers which shall convert the energy of compressed air into mechanical force and motion. This shall actuate the brake camshaft, which in turn shall operate the foundational brake mechanism forcing the brake shoes against the brake drum. The TSE Type 36 brake chamber has a 36.00 square inch effective area.

AIR COMPRESSOR

The air compressor provided for the engine shall be a Wabco® SS318 single cylinder pass-through drive type compressor which shall be capable of producing 18.7 CFM at 1200 engine RPMs. The air compressor shall feature a higher delivery efficiency translating to more air delivery per horsepower absorbed. The compressor shall include an aluminum cylinder head which shall improve cooling, reduce weight and decrease carbon formation. Superior piston and bore finishing technology shall reduce oil consumption and significantly increasing the system component life.

AIR GOVERNOR

An air governor shall be provided to control the cut-in and cut-out pressures of the engine mounted air compressor. The governor shall be calibrated to meet FMVSS requirements. The air governor shall be mounted to the right frame rail.

MOISTURE EJECTORS

Manual pet-cock type drain valves shall be installed on all reservoirs of the air supply system.

AIR SUPPLY LINES

The air system on the chassis shall be plumbed with color coded reinforced nylon tubing air lines. The primary (rear) brake line shall be green, the secondary (front) brake line red, the parking brake line orange and the auxiliary (outlet) will be blue.

Brass compression type fittings shall be used on the nylon tubing. All drop hoses shall include fiber reinforced neoprene covered hoses.

AIR INLET CONNECTION

An air connection for the shoreline air inlet shall be supplied.

AIR INLET LOCATION

The air inlet shall be installed in the left hand side middle front step in the forward position.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

PLUMBING AIR INLET CONNECTION

The air inlet connector shall be plumbed to the air system with a check valve to prevent air from escaping through the inlet connector.

AIR INLET SHUTOFF VALVE

The air inlet shall include a 1/4 turn shutoff valve which shall terminate the air supply between the inlet connection and the tank.

AIR INLET/ OUTLET FITTING TYPE

The air connector supplied shall be a 0.25 inch size Tru-Flate Interchange style manual connection which is compatible with Milton 'T' style, Myers 0.25 inch Automotive style and Parker 0.25 inch 10 Series connectors.

AIR TANK SPACERS

There shall be spacers included with the air tank mounting. The spacers shall move the air tanks 1.50 inches inward towards the center of the chassis. This shall provide clearance between the air tanks and the frame for body U-bolt clearance.

REAR AIR TANK MOUNTING

If a combination of wheel base, air tank quantity, or other requirements necessitate the location of one or more air tanks to be mounted rear of the fuel tank, these tank(s) will be mounted perpendicular to frame.

WHEELBASE

The chassis wheelbase shall be 222.00 inches.

REAR OVERHANG

The chassis rear overhang shall be 94.00 inches.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

FRAME

The frame shall consist of double rails running parallel to each other with cross members forming a ladder style frame. The frame rails shall be formed in the shape of a "C" channel, with the outer rail measuring 10.25 inches high X 3.50 inches deep upper and lower flanges X 0.38 inches thick with an inner channel of 9.44 inches high X 3.13 inches deep and 0.38 inches thick. Each rail shall be constructed of 110,000 psi minimum yield high strength low alloy steel. Each double rail section shall be rated by a Resistance Bending Moment (RBM) minimum of 3,213,100 inch pounds and have a minimum section modulus of 29.21 cubic inches. The frame shall measure 35.00 inches in width.

Proposals calculating the frame strength using the "box method" shall not be considered.

Proposals including heat treated rails shall not be considered. Heat treating frame rails produces rails that are not uniform in their mechanical properties throughout the length of the rail. Rails made of high strength, low alloy steel are already at the required yield strength prior to forming the rail.

A minimum of seven (7) fully gusseted 0.25 inch thick cross members shall be installed. The inclusion of the body mounting, or bumper mounting shall not be considered as a cross member. The cross members shall be attached using zinc coated grade 8 fasteners. The bolt heads shall be flanged type, held in place by distorted thread flanged lock nuts. Each cross member shall be mounted to the frame rails utilizing a minimum of 0.25 inch thick gusset reinforcement plates at all corners balancing the area of force throughout the entire frame.

Any proposals not including additional reinforcement for each cross member shall not be considered.

All relief areas shall be cut in with a minimum 2.00 inch radius at intersection points with the edges ground to a smooth finish to prevent a stress concentration point.

The frame and cross members shall carry a lifetime warranty to the original purchaser. A copy of the frame warranty shall be made available upon request.

Proposals offering warranties for frames not including cross members shall not be considered.

FRAME WARRANTY

The frame and cross members shall carry a limited lifetime warranty to the original purchaser. The warranty shall include conditional items listed in the detailed warranty document which shall be provided upon request.

FRAME PAINT

The frame shall be powder coated black prior to any attachment of components.

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 shall not have a fail of more than ten (10) squares. The pencil hardness test per ASTM D3363 shall have a final post-curved pencil hardness of H-2H. The direct impact resistance test per ASTM D2794 shall have an impact resistance of 120.00 inches per pound at 2 mils.

Any proposals offering painted frame with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

The chassis under carriage consisting of frame, axles, driveline running gear, air tanks and other chassis mounted components shall be painted with gloss black paint. Paint shall be applied prior to airline and electrical wiring installation.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

FRONT BUMPER

The chassis shall be equipped with a severe duty front bumper constructed from structural steel channel. The bumper material shall be 0.38 thick ASTM A36 steel which shall measure 12.00 inches high with a 3.05 inch flange and shall be 99.00 inches wide with angled front corners.

The bumper shall be primed and painted as specified.

FRONT BUMPER EXTENSION LENGTH

The front bumper shall be extended approximately 12.50 inches ahead of the cab.

FRONT BUMPER EXTENSION FRAME WIDTH

The front bumper extension frame shall feature an overall width of 48.25 inches.

FRONT BUMPER PAINT

The front bumper shall be painted the same as the lower cab color.

FRONT BUMPER APRON

The 12.50 inch extended front bumper shall include an apron constructed of 0.19 inch thick embossed aluminum tread plate.

The apron shall be installed between the bumper and the front face of the cab affixed using stainless steel bolts attaching the apron to the top bumper flange.

MECHANICAL SIREN

The front bumper shall include an electro mechanical Federal Q2B™ siren, which shall be streamlined, chrome-plated and shall produce 123 decibels of sound at 10.00 feet. The Q2B™ siren produces a distinctive warning sound that is recognizable at long distances. A unique clutch design provides a longer coast down sound while reducing the amp draw to 100 amps. The siren shall measure 10.50 inches wide X 10.00 inches high X 14.00 inches deep.

MECHANICAL SIREN LOCATION

The siren shall be recess mounted in the center on the front fascia of the bumper between the frame rails.

AIR HORN

The front bumper shall include two (2) Hadley brand E-Tone air horns which shall measure 21.00 inches long with a 6.00 inch round flare. The air horns shall be trumpet style with a chrome finish on the exterior and a painted finish deep inside the trumpet.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

AIR HORN LOCATION

The air horns shall be recess mounted in the front bumper face, one (1) on the right side of the bumper in the inboard position relative to the right hand frame rail and one (1) on the left side of the bumper in the inboard position relative to the left hand frame rail.

AIR HORN RESERVOIR

One (1) air reservoir, with a 1200 cubic inch capacity, shall be installed on the chassis to act as a supply tank for operating air horns. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

FRONT BUMPER TOW EYES

The bumper shall include two (2) painted tow eyes which shall be installed below the front bumper. The tow eyes shall be fabricated from 0.75 inch thick #1020 ASTM-36 hot rolled steel. The inside diameter of the eye shall be 2.00 inches and include a chamfered edge. The tow eyes shall be painted to match the front bumper.

CAB TILT SYSTEM

The entire cab shall be capable of tilting approximately 45-degrees to allow for easy maintenance of the engine and transmission. The cab tilt pump assembly shall be located on the right side of the chassis above the battery box.

The electric-over-hydraulic lift system shall include an ignition interlock and red cab lock down indicator lamp on the tilt control which shall illuminate when holding the "Down" button to indicate safe road operation.

It shall be necessary to activate the master battery switch and set the parking brake in order to tilt the cab. As a third precaution the ignition switch must be turned off to complete the cab tilt interlock safety circuit.

Two (2) spring-loaded hydraulic hold down hooks located outboard of the frame shall be installed to hold the cab securely to the frame. Once the hold-down hooks are set in place, it shall take the application of pressure from the hydraulic cab tilt lift pump to release the hooks.

Two (2) cab tilt cylinders shall be provided with velocity fuses in each cylinder port. The cab tilt pivots shall be 1.90 inch ball and be anchored to frame brackets with 1.25 inch diameter studs.

A steel safety channel assembly shall be installed on the right side cab lift cylinder to prevent accidental cab lowering. The safety channel assembly shall fall over the lift cylinder when the cab is in the fully tilted position. A cable release system shall also be provided to retract the safety channel assembly from the lift cylinder to allow the lowering of the cab.

CAB TILT LIMIT SWITCH

A cab tilt limit switch shall be installed. The switch will effectively limit the travel of the cab when being tilted. The final adjustment of the switch shall be performed by the apparatus manufacturer to prevent damage to the cab or any bumper mounted option mounted in the cab tilt arc.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CAB TILT CONTROL RECEPTACLE

The cab tilt control cable shall include a receptacle which shall be temporarily located on the right hand chassis rail rear of the cab to provide a place to plug in the cab tilt remote control pendant. The tilt pump shall include 8.00 feet of cable with a six (6) pin Deutsch receptacle with a cap.

The remote control pendant shall include 20.00 feet of cable with a mating Deutsch connector. The remote control pendant shall be shipped loose with the chassis.

CAB WINDSHIELD

The cab windshield shall have a surface area of 2825.00 square inches and be of a two (2) piece wraparound design for maximum visibility.

The glass utilized for the windshield shall include standard automotive tint. The left and right windshield shall be fully interchangeable thereby minimizing stocking and replacement costs.

Each windshield shall be installed using black self locking window rubber.

GLASS FRONT DOOR

The front cab doors shall include a window which is 27.00 inches in width X 26.00 inches in height. These windows shall have the capability to roll down completely into the door housing. This shall be accomplished manually utilizing a crank style handle on the inside of the door. A reinforced window regulator assembly shall be provided for severe duty use.

There shall be an irregular shaped fixed window which shall measure 2.50 inches wide at the top, 8.00 inches wide at the bottom X 26.00 inches in height, more commonly known as "cozy glass" ahead of the front door roll down windows.

The windows shall be mounted within the frame of the front doors trimmed with a black anodized ring on the exterior.

GLASS TINT FRONT DOOR

The windows located in the left and right front doors shall have a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS REAR DOOR RH

The rear right hand side door shall include a window which is 27.00 inches in width X 26.00 inches in height. This window shall roll up and down manually utilizing a crank style handle on the inside of the door. A reinforced window regulator assembly shall be provided for severe duty use.

GLASS TINT REAR DOOR RIGHT HAND

The window located in the right hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

GLASS REAR DOOR LH

The rear left hand side door shall include a window which is 27.00 inches in width X 26.00 inches in height. This window shall roll up and down manually utilizing a crank style handle on the inside of the door. A reinforced window regulator assembly shall be provided for severe duty use.

GLASS TINT REAR DOOR LEFT HAND

The window located in the left hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS SIDE MID RH

The cab shall include a window on the right side behind the front and ahead of the crew door which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID RIGHT HAND

The window located on the right hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS SIDE MID LH

The cab shall include a window on the left side behind the front door and ahead of the crew door and above the wheel well which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID LEFT HAND

The window located on the left hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS UPPER SIDE REAR DOOR

Windows shall be provided in the upper portion of each rear door of the raised roof cab. Each window shall measure 27.00 inches wide X 14.00 inches high and be installed above the lower door window. The windows shall be rectangular in shape and fixed within this space. The windows shall be mounted using black self-locking window rubber.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

GLASS TINT UPPER SIDE REAR DOOR

The window located in the upper section of the rear crew doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

CLIMATE CONTROL

The cab shall be equipped with a ceiling mounted combination defrost / heating and air-conditioning system mounted above the engine tunnel in a central location.

The system shall offer sixteen (16) adjustable louvers. Six (6) of the louvers shall face forward towards the windshield, offering 45,000 BTU of heat at 320 CFM for defrosting. The system shall include six (6) rearward facing louvers to direct air for the crew area and four (4) for driver and officer comfort. The HVAC system shall be designed to produce 60,000 BTU of heat and 32,000 BTU of cooling. The HVAC cover shall be made of aluminum which shall be coated with a customer specified interior paint, or protective coating.

All defrost/heating systems shall be plumbed with one (1) seasonal shut-off valve at the front corner on the right side of the cab.

The air conditioner lines shall be a mixture of custom bent zinc coated steel fittings and Aero-quip GH 134 flexible hose with Aero-Quip EZ-Clip fittings.

CLIMATE CONTROL DRAIN

The climate control system shall include a gravity drain for water management. The gravity drain shall remove condensation from the air conditioning system without additional mechanical assistance.

CLIMATE CONTROL ACTIVATION

The heating, defrosting and air conditioning controls shall be on the dash next to driver panel, in a position which is easily accessible to the driver. The climate control shall be activated by a rotary switch.

HVAC OVERHEAD COVER PAINT

The overhead HVAC cover shall be painted with a Zolatone #20-72 silver gray texture finish.

A/C CONDENSER LOCATION

A roof mounted A/C condenser shall be installed centered on the cab forward of the raised roof against the slope rise.

A/C COMPRESSOR

The air-conditioning compressor shall be a belt driven, engine mounted, open type compressor that shall be capable of producing a minimum of 32,000 BTU at 1500 engine RPMs. The compressor shall utilize R-134A refrigerant and PAG oil.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CAB CIRCULATION FANS FRONT

The cab shall include two (2) all metal 6.00 inch air circulation fans installed in the outer front cab corners. Each fan shall be controlled by an individual toggle switch on each fan. The fans can be used to help defog the windshield or to increase air circulation for passenger comfort.

CAB INSULATION

The cab ceiling and walls shall include 1.00 inch thick foam insulation. The insulation shall act as a barrier absorbing noise as well as assisting in sustaining the desired climate within the cab interior.

UNDER CAB INSULATION

The underside of the cab tunnel surrounding the engine shall be lined with multi-layer insulation, engineered for application inside diesel engine compartments.

The insulation shall act as a noise barrier, absorbing noise thus keeping the decibel level in the cab well within NFPA recommendations. As an additional benefit, the insulation shall assist in sustaining the desired temperature within the cab interior.

The engine tunnel insulation shall measure approximately 0.75 inch thick including a vertically lapped polyester fiber layer, a 1.0 lb/ft² PVC barrier layer, an open cell foam layer, and a moisture and heat reflective foil facing reinforced with a woven fiberglass layer. The foil surface acts as protection against moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.

The insulation shall be cut precisely to fit each section and sealed for additional heat and sound deflection. The insulation shall be held in place by 3 mils of acrylic pressure sensitive adhesive and aluminum pins with hard hat, hold in place fastening heads.

INTERIOR TRIM FLOOR

The floor of the cab shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive and aluminum trim molding. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.

INTERIOR TRIM VINYL

The cab interior shall include trim on the front ceiling and rear crew ceiling, . The cab side walls shall have aluminum panels covering cab cavities, making smooth sidewall surfaces. It shall be easily removable to assist in maintenance. The trim shall be constructed of insulated vinyl over a hard board backing.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

REAR WALL INTERIOR TRIM

The rear wall of the cab shall be trimmed with aluminum sheet metal coated with a customer specified interior paint or protective coating.

HEADER TRIM

The cab interior shall feature header trim over the driver and officer dash constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum.

TRIM CENTER DASH

The main center dash area shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate. There shall be four (4) holes located on the top of the dash near each outer edge of the electrical access cover for ventilation.

TRIM LH DASH

The left hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate for a perfect fit around the instrument panel and the lower control panels to the left and right of the steering column.

TRIM RH DASH

The right hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate and shall include a glove compartment with a hinged door and a Mobile Data Terminal (MDT) provision. The glove compartment size will measure 14.00 inches wide X 6.38 inches high X 5.88 inches deep. The MDT provision shall be provided above the glove compartment.

ENGINE TUNNEL TRIM

The cab engine tunnel shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive.

The cab engine tunnel shall have an overlay of 3003-H22 aluminum plate with a Zolatone finish, colored to match the cab paint interior finish color scheme. The engine tunnel top, rear slope sections to floor will have the aluminum cover. The cover will wrap around the edges of the top to avoid a sharp edge on corners. The aluminum plate shall be held down with screws. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention

POWER POINT DASH MOUNT

The cab interior shall include three (3) 12 volt cigarette lighter type receptacles in the cab dash switch panel to provide a power source for 12 volt electrical equipment. The receptacles shall be wired battery direct.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

STEP TRIM

Each cab entry door shall include a three step entry. The first step closest to the ground shall be constructed of 14 gauge 304 stainless steel with indented perforations. The perforations shall allow water and other debris to flow through rather than becoming trapped within the stepping surface. The stainless steel material shall have a number 7 mirror finish. The lower step shall be mounted to a frame which is integral with the construction of the cab for rigidity and strength. The middle step shall be integral with the cab construction and shall be trimmed in 0.08 inch thick 3003-H22 embossed aluminum tread plate.

STEP TRIM KICKPLATE

The cab steps shall include a kick plate in the rise of each step. The risers shall be trimmed in 3003-H22 bright aluminum tread-plate which is 0.07 inch thick.

UNDER CAB ACCESS DOOR

The cab shall include an aluminum access door in the left crew step riser painted to match the cab interior paint with a push and turn latch. The under cab access door shall provide access to the diesel exhaust fluid fill.

INTERIOR DOOR TRIM

The interior trim on the doors of the cab shall consist of an aluminum panel constructed of Marine Grade 5052-H32 0.13 of an inch thick aluminum plate. The door panels shall include a painted finish.

DOOR TRIM KICKPLATE

The inner door panels shall include an aluminum tread kick plate which shall be fastened to the lower portion of the door panels.

DOOR TRIM CUSTOMER NAMEPLATE

The interior door trim on the front doors shall include a customer nameplate which states the vehicle was custom built for their Department.

CAB DOOR TRIM REFLECTIVE

The interior of each door shall include high visibility reflective tape. A white reflective tape 1.00 inch in width shall be provided vertically along the outer rear edge of the door.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

INTERIOR GRAB HANDLE "A" PILLAR

There shall be two (2) rubber covered 11.00 inch grab handles installed inside the cab, one on each "A" post at the left and right door openings. The left handle shall be located 7.88 inches above the bottom of the door window opening and the right handle shall be located 2.88 inches above the bottom of the door window opening. The handles shall assist personnel in entering and exiting the cab.

INTERIOR GRAB HANDLE FRONT DOOR

Each front door shall include one (1) ergonomically contoured 9.00 inch cast aluminum handle mounted horizontally on the interior door panels. The handles shall feature a textured black powder coat finish to assist personnel entering and exiting the cab.

INTERIOR GRAB HANDLE REAR DOOR

A black powder coated cast aluminum assist handle shall be provided on the inside of each rear crew door. A 30.00 inch long handle shall extend horizontally the width of the window just above the window sill. The handle shall assist personnel in exiting and entering the cab.

INTERIOR TRIM VINYL COLOR

The cab interior vinyl trim surfaces shall be gray in color.

INTERIOR TRIM SUNVISOR

The header shall include two (2) sun visors, one each side forward of the driver and officer seating positions above the windshield. Each sun visor shall be constructed of Masonite and covered with padded vinyl trim.

INTERIOR FLOOR MAT COLOR

The cab interior floor mat shall be black in color.

CAB PAINT INTERIOR DOOR TRIM

The inner door panel surfaces shall be painted with Zolatone #20-72 silver gray texture finish.

HEADER TRIM INTERIOR PAINT

The metal surfaces in the header area shall be coated with Zolatone #20-72 silver gray texture finish.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

TRIM CENTER DASH INTERIOR PAINT

The entire center dash shall be coated with Zolatone #20-72 silver gray texture finish. Any accessory pods attached to the dash shall also be painted this color.

TRIM LH DASH INTERIOR PAINT

The left hand dash shall be painted with a Zolatone #20-72 silver gray texture finish.

TRIM RIGHT HAND DASH INTERIOR PAINT

The right hand dash shall be painted with Zolatone #20-72 silver gray texture finish.

REAR WALL INTERIOR PAINT

The rear wall of the cab shall be trimmed with aluminum sheet metal coated with a Zolatone #20-72 silver gray texture finish.

DASH PANEL GROUP

The main center dash area shall include three (3) removable panels located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer.

SWITCHES CENTER PANEL

The center dash panel shall include eighteen (18) rocker switch positions in a twelve (12) over six (6) configuration in the left portion of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SWITCHES LEFT PANEL

The left dash panel shall include thirteen (13) switches. There shall be six (6) switches across the top of the panel and seven (7) across the bottom of the panel. Five (5) of the top row of switches shall be rocker type and the left one (1) shall be the headlight switch. Five (5) of the lower row of switches shall be rocker type and the left two (2) shall be the windshield wiper/washer control switch and instrument lamp dimmer switch.

A rocker switch with a blank legend installed directly above shall be provided for any position not designated by a specific option. The non-designated switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

SWITCHES RIGHT PANEL

The right dash panel shall six (6) rocker switch positions in a three (3) over three (3) switch configuration.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SEAT BELT WARNING

A Class One seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the cab. The system shall activate an indicator light in the instrument panel, a digital seat position indicator with a seat position legend in the switch panel, and an audible alarm.

The warning system shall activate when any seat is occupied with a minimum of 60 pounds, the corresponding seat belt remains unfastened, and the park brake is released. The warning system shall also activate when any seat is occupied, the corresponding seat belt was fastened in an incorrect sequence, and the park brake is released. Once activated, the visual indicators and audible alarm shall remain active until all occupied seats have the seat belts fastened.

SEAT MATERIAL

The seats shall include a covering of high strength, wear resistant fabric made of durable ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Common trade names for this material are Imperial 1200 and Durawear.

SEAT COLOR

All seats supplied with the chassis shall be black in color. All seats shall include red seat belts.

SEAT BACK LOGO

The seat backs shall include the logo for the OEM body manufacturer. The logo shall be centered on the standard headrest of the seat back and on the left side of a split headrest.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

SEAT DRIVER

The driver's seat shall be an H.O. Bostrom Sierra model seat with air suspension. The four-way seat shall feature 3.00 inch vertical travel air suspension and manual fore and aft adjustment with 5.00 inches of travel. The suspension control shall be located on the seat below the left front corner of the bottom cushion. The seat shall also feature integral springs to isolate shock.

The seat position shall include a three-point shoulder harness with lap belt and an automatic retractor attached to the cab. The buckle portion of the seat belt shall be mounted on a semi-rigid stalk extending from the seat base within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 37.00 inches measured with the seat suspension height adjusted to the upper limit of its travel.

This model of seat shall have successfully completed the static load tests set forth by FMVSS 207, 209, and 210 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity.

The materials used in construction of the seat shall also have successfully completed testing with regard to the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which dictates the allowable burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK DRIVER

The driver's seat shall feature a two (2) way adjustable lumbar support and offer an infinite fully reclining adjustable titling seat back. The seat back shall also feature a contoured head rest.

SEAT MOUNTING DRIVER

The driver's seat shall be installed in an ergonomic position in relation to the cab dash.

SEAT OFFICER

The officer's seat shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion. The seat shall be a non-adjustable type seat.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

SEAT BACK OFFICER

The officer's seat shall feature a SecureAll™ SCBA locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

SEAT MOUNTING OFFICER

The officer's seat shall be installed in an ergonomic position in relation to the cab dash.

SEAT REAR FACING OUTER LOCATION

The crew area shall include two (2) rear facing crew seats, which include one (1) located directly behind the left side front seat and one (1) located directly behind the right side front seat.

SEAT CREW REAR FACING OUTER

The crew area shall include a seat in the rear facing outboard position which shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion. The seat and cushion shall be spring load hinged and compact in design for additional room and shall remain in the stored position until occupied.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

SEAT BACK REAR FACING OUTER

The rear facing outboard seat shall feature a Bostrom SecureAll™ self contained breathing apparatus (SCBA) locking system which shall store most U.S. and International SCBA brands and bottle sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the center of the bottom seat cushion for easy access and to eliminate hooking the release handle with clothing or other equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

SEAT MOUNTING REAR FACING OUTER

The rear facing outer seats shall offer special mounting positions which shall be 2.00 inches towards the rear wall offering additional space between the front seats and the outer rear facing seats.

SEAT BELT ORIENTATION CREW

The crew position seat belts shall follow the standard orientation which extends from the outboard shoulder extending to the inboard hip.

SEAT FORWARD FACING OUTER LOCATION

The crew area shall include two (2) forward facing outboard seats, which include one (1) located next to the outer wall of the cab on the left side of the cab and one (1) located next to the outer wall on the right side of the cab.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

SEAT CREW FORWARD FACING OUTER

The crew area shall include a seat in the forward facing outer position which shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat back and cushion. The bottom cushion shall be hinged and compact in design for additional room and shall remain in the stored position until occupied.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK FORWARD FACING OUTER

The forward facing outboard seat shall feature a SecureAll™ self contained breathing apparatus (SCBA) locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

SEAT MOUNTING FORWARD FACING OUTER

The forward facing outer seat shall be mounted in the furthest outboard position facing the front of the cab.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

SEAT FRAME FORWARD FACING

The forward facing outboard seating positions shall include individual enclosed seat frames for each position located and installed at the outer rear wall positions. The seat frames shall measure 28 inches wide X 12.38 inches high X 22.00 inches deep. The seat frames shall be constructed of Marine Grade 5052-H32 0.19 inch thick aluminum plate. The seat frames shall be painted with the same color as the remaining interior

SEAT FRAME FORWARD FACING STORAGE ACCESS

There shall be two (2) access points to the storage area centered on the front of the seat frame. Each access point shall be covered by a hinged door to allow access for storage in the seat box.

SEAT FRAME EXTERIOR REAR COMPARTMENT ACCESS

The seat frame shall be open to the exterior rear compartment on both the right hand side and the left hand side. This shall allow interior access to the left and right exterior rear compartments.

CAB FRONT UNDERSEAT STORAGE ACCESS

The left and right under seat storage areas shall have a solid aluminum hinged door with non-locking latch.

SEAT COMPARTMENT DOOR FINISH

All underseat storage compartment access doors shall have a Zolatone #20-72 silver gray texture.

WINDSHIELD WIPER SYSTEM

The cab shall include a dual arm wiper system which shall clear the windshield of water, ice and debris. There shall be two (2) windshield wipers which shall be affixed to a radial wet arm. The system shall include a single motor which shall initiate the arm in which both the left hand and right hand windshield wipers are attached, initiating a back and forth motion for each wiper. The wiper motor shall be activated by an intermittent wiper control located within easy reach of the driver's position.

ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR

The windshield washer fluid level shall be monitored electronically. When the washer fluid level becomes low the yellow "Check Message Center" indicator light on the instrument panel shall illuminate and the message center in the dual air pressure gauge shall display a "Check Washer Fluid Level" message.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CAB DOOR HARDWARE

The cab entry doors shall be equipped with exterior pull handles, suitable for use while wearing firefighter gloves. The handles shall be made of aluminum with a chrome plated finish.

The interior exit door handles shall be flush paddle type with a black finish, which are incorporated into the upper door panel.

All cab entry doors shall include locks which are keyed alike. The door locks shall be designed to prevent accidental lockout.

The exterior pull handles shall include a scuff plate behind the handle constructed of polished stainless steel to help protect the cab finish.

DOOR LOCKS

Each cab entry door shall include a manually operated door lock. The each door lock may be actuated from the inside of the cab by means of a red knob located on the paddle handle of the respective door or by using a TriMark key from the exterior. The door locks are designed to prevent accidental lock out.

DOOR LOCK LH REAR CAB COMPARTMENT

The left hand side rear compartment shall feature a manual door lock.

DOOR LOCK RH REAR CAB COMPARTMENT

The right hand side rear compartment shall feature a manual door lock.

GRAB HANDLES

The cab shall include one (1) 18.00 inch knurled, anti-slip, one-piece exterior assist handle behind each cab door. The grab handle shall be made of 14 gauge 304- stainless steel and be 1.25 inch diameter to enable non-slip assistance with a gloved hand.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

REARVIEW MIRRORS

Retrac Aerodynamic West Coast style single vision mirror heads model 613285 shall be provided and installed on each of the front cab doors.

The mirrors shall be mounted via 1.00 inch diameter tubular stainless steel arms to provide a rigid mounting to reduce mirror vibration.

The mirrors shall measure 8.00 inches wide X 19.00 inches high and shall include an 8.00 inch convex mirrors with a stainless steel back, model 980-4, installed below the flat glass to provide a wider field of vision. The flat mirrors shall be motorized with remote horizontal and vertical adjustment. The control switches shall be mounted within easy reach of the driver. The convex mirrors shall be manually adjustable. The flat mirror glass shall be heated for defrosting in severe cold weather conditions.

The mirror backs shall be constructed of vacuum formed chrome plated ABS plastic housings that are corrosion resistant and shall include an amber marker light. The mirrors shall be manufactured with the finest quality non-glare glass.

REARVIEW MIRROR HEAT SWITCH

The heat for the rearview mirrors shall be controlled through a rocker switch on the dash in the switch panel.

TRIM LOWER SIDE

A stainless steel trim band, 10.00 inches high, with upper and lower black and chrome trim moldings, shall be installed on the lower exterior sides of the cab and doors. The trim shall be installed so that the top edge approximately 1.00 inch below the top of the front bumper, and shall be affixed without holes and fasteners.

CAB FENDER

Full width wheel well liners shall be installed on the extruded cab to limit road splash and enable easier cleaning. Each two-piece liner shall consist of an inner liner 16.00 inches wide made of vacuum formed ABS composite and an outer fenderette 3.50 inches wide made of 14 gauge 304 polished stainless steel.

MUD FLAPS FRONT

The front wheel wells shall have mud flaps installed on them.

CAB EXTERIOR FRONT & SIDE EMBLEMS

The cab shall include three (3) Spartan emblems. There shall be one (1) for the front air intake grille and two (2) for the exterior sides of the cab shipped loose with the chassis for installation by the body manufacturer.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CAB EXTERIOR MODEL NAMEPLATE

The cab shall include custom "Metro Star" nameplates on the front driver and officer side doors.

IGNITION

A master battery system with a keyless start ignition system shall be provided. Each system shall be controlled by a one-quarter turn Cole Hersee switch, both of which shall be mounted to the left of the steering wheel on the dash. A chrome push type starter button shall be provided adjacent to the master battery and ignition switches.

Each switch shall illuminate a green LED indicator light on the dash when the respective switch is placed in the "ON" position.

The starter button shall only operate when both the master battery and ignition switches are in the "ON" position.

BATTERY

The single start electrical system shall include six (6) Harris BCI 31 950 CCA batteries with a 210 minute reserve capacity and 4/0 welding type dual path starter cables per SAE J541. The cables shall have encapsulated ends with heat shrink and sealant.

BATTERY TRAY

The batteries shall be installed within two (2) steel battery trays located on the left side and right side of the chassis, securely bolted to the frame rails. The battery trays shall be coated with the same material as the frame.

The battery trays shall include drain holes in the bottom for sufficient drainage of water. A durable, non-conducting, interlocking mat made by Dri-Dek shall be installed in the bottom of the trays to allow for air flow and help prevent moisture build up. The batteries shall be held in place by non-conducting phenolic resin hold down boards.

BATTERY BOX COVER

Each battery box shall include a steel cover which protects the top of the batteries. Each cover shall include flush latches which shall keep the cover secure as well as a black powder coated handle for convenience when opening.

BATTERY CABLE

The starting system shall include cables which shall be protected by 275 degree F. minimum high temperature flame retardant loom, sealed and encapsulated at the ends with heat shrink and sealant.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

BATTERY JUMPER STUD

The starting system shall include battery jumper studs. These studs shall be located in the forward most portion of the driver's side lower step. The studs shall allow the vehicle to be jump started, charged, or the cab to be raised in an emergency in the event of battery failure.

ALTERNATOR

The charging system shall include a 320 amp Leece-Neville 12 volt alternator. The alternator shall include a self-exciting integral regulator.

STARTER MOTOR

The single start electrical system shall include a Delco brand starter motor.

BATTERY CONDITIONER

A Kussmaul 1200 battery conditioner shall be supplied. The battery conditioner shall be mounted in the cab behind the driver's seat.

BATTERY CONDITIONER DISPLAY

A Kussmaul battery conditioner display shall be supplied. The battery conditioner display shall be mounted in the cab, viewable through the cab mid side window behind the left front door.

ELECTRICAL INLET

A Kussmaul 20 amp electrical receptacle shall be supplied.

A single item or an addition of multiple items must not exceed the rating of the electric inlet that it's connected to.

Amp Draw Reference List:

Kussmaul 1000 Charger - 3.5 Amps

Kussmaul 1200 Charger - 10 Amps

Kussmaul 35/10 Charger - 10 Amps

1000W Engine Heater - 8.33 Amps

1500W Engine Heater - 12.5 Amps

120V Air Compressor - 4.2 Amps

ELECTRICAL INLET LOCATION

An electrical inlet shall be installed in the left hand side middle front step in the mid rear position.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ELECTRICAL INLET CONNECTION

The electrical inlet shall be connected to the battery conditioner.

ELECTRICAL INLET COLOR

The electrical inlet connection shall include a yellow cover.

HEADLIGHTS

The cab front shall include four (4) rectangular LED headlamps with separate high and low beams mounted in bright chrome bezels.

FRONT TURN SIGNALS

The front fascia shall include two (2) Whelen model 600 4.00 inch X 6.00 inch programmable LED amber turn signals which shall be installed in a chrome bezel outboard of the front warning and headlamps.

HEADLIGHT LOCATION

The headlights shall be located on the front fascia of the cab directly below the front warning lights.

SIDE TURN/MARKER LIGHTS

The sides of the cab shall include two (2) LED round side marker lights which shall be provided just behind the front cab radius corners.

MARKER AND ICC LIGHTS

In accordance with FMVSS, there shall be five (5) LED cab marker lamps designating identification, center and clearance provided. These lights shall be installed on the face of the cab within full view of other vehicles from ground level.

HEADLIGHT AND MARKER LIGHT ACTIVATION

The headlights and marker lights shall be controlled through a rocker switch within easy reach of the driver. There shall be a dimmer switch within easy reach of the driver to adjust the brightness of the dash lights. The headlamps shall be equipped with the "Daytime Running" light feature, which shall illuminate the headlights to 80% brilliance when the battery master switch is in the "On" position and the parking brake is released.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

GROUND LIGHTS

Each door shall include an LED NFPA compliant ground light mounted to the under side of the cab step below each door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life. The ground lighting shall be activated by the opening of the respective door as well as being activated when the parking brake is set.

STEP LIGHTS

The middle step located at each door shall include a recess mounted 4.00 inch round LED light which shall activate with the opening of the respective door.

ENGINE COMPARTMENT LIGHT

There shall be an incandescent NFPA compliant light mounted under the engine tunnel for area work lighting on the engine. The light shall include a polycarbonate lens, a housing which is vibration welded and a bulb which shall be shock mounted for extended life. The light shall activate automatically when the cab is tilted.

FRONT SCENE LIGHTS

The front of the cab shall include two (2) Whelen Pioneer model PCP2 contour roof mount scene lights installed on the brow of the cab.

Each lamp head shall have two (2) 12 volt high intensity LED panels. One side of each lamp head shall include a flood light and the other side shall include an 8-degree spotlight. The spotlight portion of each lamp shall be mounted in the outboard position. Each lamp head shall draw 12.0 amps and generate 14,000 lumens total. Each lamp head shall measure 4.25 inches in height X 14.00 inches in width. The lamp heads shall be powder coated white.

FRONT SCENE LIGHT LOCATION

There shall be two (2) scene lights mounted to the front brow of the cab inboard of the outer front marker lights.

FRONT SCENE LIGHTS ACTIVATION

The front scene lighting shall be activated by a rocker switch labeled "Brow Lights".

SIDE SCENE LIGHTS

The cab shall include two (2) Whelen model Pioneer PFA2 semi-recess mount lights installed one (1) on each side of the cab.

Each lamp head shall have two (2) 12 volt high intensity LED panels at 70 watts total. Each light shall draw 6.0 amps and generate 6000 lumens. Each LED panel shall be mounted at a 15-degree downward angle within the semi-recess housing. Each lamp head shall be no more than 4.25 inches in height X 14.00 inches in width. The lamp heads shall be powder coated white with a chrome trim ring.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

SIDE SCENE LIGHT LOCATION

The scene lighting located on the left and right sides of the cab shall be mounted rearward of the cab "B" pillar in the 20.00 inch raised roof portion of the cab between the front and rear crew doors.

SIDE SCENE ACTIVATION

The scene lights shall be activated by two (2) rocker switches located in the switch panel, one (1) for each light, and by opening the respective side cab doors.

INTERIOR OVERHEAD LIGHTS

The cab shall include a two-section Weldon incandescent dome lamp with a red and clear lens located over each door. The dome lamps shall be rectangular in shape and shall measure approximately 9.50 inches in length X 5.00 inches in width with a black colored bezel. The clear portion of each lamp shall be activated by opening the respective door and both the red and clear portions can be activated by individual switches on each lamp.

An additional two-section Weldon incandescent red and clear lamp shall be provided over the engine tunnel which can be activated by individual switches on the lamp.

MAP LIGHTS

A Roxter gooseneck style map light shall be provided. The light shall have a clear bulb and a control switch on the base. The light shall be located high on the right hand side cab "A" pillar above the dash in a location that does not interfere with entering or exiting the cab.

DO NOT MOVE APPARATUS LIGHT

The front headliner of the cab shall include a flashing red light clearly labeled "Do Not Move Apparatus". In addition to the flashing red light, an audible alarm shall be included which shall sound while the light is activated.

The flashing red light shall be 6.00 inches long X 2.50 inches wide X 1.75 inches high and shall be located centered left to right for greatest visibility.

The light and alarm shall be interlocked for activation when either a cab door is not firmly closed or an apparatus compartment door is not closed, and the parking brake is released.

MASTER WARNING SWITCH

A master switch shall be included in the main rocker switch panel. The switch shall be a rocker type, red in color and labeled "Master" for identification. The switch shall feature control over all devices wired through it. Any warning device switch left in the "ON" position shall automatically power up when the master switch is activated.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

HEADLIGHT FLASHER

An alternating high beam headlight flashing system shall be installed into the high beam headlight circuit which shall allow the high beams to flash alternately from left to right.

Deliberate operator selection of high beams will override the flashing function until low beams are again selected. Per NFPA, these clear flashing lights will also be disabled "On Scene" when the park brake is applied.

HEADLIGHT FLASHER SWITCH

The flashing headlights shall be activated through a rocker switch on the switch panel. The rocker switch shall be clearly labeled for identification.

INBOARD FRONT WARNING LIGHTS

The cab front fascia shall include two (2) Whelen 600 series Super LED front warning lights in the left and right inboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel.

INBOARD FRONT WARNING LIGHTS COLOR

The warning lights mounted on the cab front fascia in the inboard positions shall be red with a clear lens.

FRONT WARNING SWITCH

The front warning lights shall be controlled via rocker switch on the panel. This switch shall be clearly labeled for identification.

INTERSECTION WARNING LIGHTS

The chassis shall include two (2) Whelen 600 series Super LED intersection warning lights, one (1) each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

INTERSECTION WARNING LIGHTS COLOR

The intersection lights shall be red with a clear lens.

INTERSECTION WARNING LIGHTS LOCATION

The intersection lights shall be mounted on the side of the cab on the front radius.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

SIDE WARNING LIGHTS

The cab sides shall include two (2) Whelen 600 series Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the sides of the cab within a chrome bezel.

SIDE WARNING LIGHTS COLOR

The warning lights located on the side of the cab shall be red with clear lens.

SIDE WARNING LIGHTS LOCATION

The warning lights on the side of the cab shall be mounted over the front wheel well directly over the center of the front axle.

SIDE AND INTERSECTOR WARNING SWITCH

The side and intersector warning lights shall be controlled by a rocker switch on the switch panel. This switch shall be clearly labeled for identification.

LIGHTBAR PROVISION

There shall be one (1) light bar installed on the cab roof. The light bar shall be provided and installed by Spartan Chassis. The light bar installation shall include mounting and wiring to a control switch on the cab dash.

CAB FRONT LIGHTBAR

The lightbar provisions shall be for one (1) Whelen brand Freedom FN72QLED lightbar mounted centered on the front of the cab roof. The lightbar shall be 72.00 inches in length. The lightbar shall feature twelve (12) red LED lights and two (2) clear LED lights. The clear lights shall be disabled with park brake engaged. The cable shall exit the lightbar on the right side of the cab.

LIGHTBAR SWITCH

The light bar shall be controlled by a rocker switch located on the switch panel. This switch shall be clearly labeled for identification.

HORN BUTTON SELECTOR SWITCH

A rocker switch shall be installed in the switch panel between the driver and officer to allow control of either the electric horn or the air horn from the steering wheel horn button. The electric horn shall sound by default when the selector switch is in either position to meet FMCSA requirements.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

AIR HORN ACTIVATION

The air horn activation shall be accomplished by the steering wheel horn button for the driver and two (2) Linemaster model SP491-S81 foot switches, one (1) on the left hand side accessible to the driver and one (1) on the right hand side accessible to the officer. An air horn activation circuit shall be provided to the chassis harness pump panel harness connector.

MECHANICAL SIREN ACTIVATION

The mechanical siren shall be actuated by a Linemaster model SP491-S81 foot switch mounted in the front section of the cab for use by the driver and a black push button in the switch panel on the dash. Two (2) red momentary siren brake rocker switches shall be provided in the switch panel on the dash.

The siren shall only be active when master warning switch is on to prevent accidental engagement.

BACK-UP ALARM

An ECCO model 575 backup alarm shall be installed at the rear of the chassis with an output level of 107 dB. The alarm shall automatically activate when the transmission is placed in reverse.

INSTRUMENTATION

An ergonomically designed instrument panel shall be provided. Each gauge shall be backlit with LED lamps. Stepper motor movements shall drive all gauges. The instrumentation system shall be multiplexed and shall receive ABS, engine, and transmission information over the J1939 data bus to reduce redundant sensors and wiring.

The instrument panel shall contain the following gauges:

One (1) electronic speedometer shall be included. The primary scale on the speedometer shall read from 0 to 100 MPH, and the secondary scale on the speedometer shall read from 0 to 160 KM/H.

One (1) electronic tachometer shall be included. The scale on the tachometer shall read from 0 to 3000 RPM.

One (1) two-movement gauge displaying primary system, and secondary system air volumes and integral LCD odometer/trip odometer shall be included on the lower portion of the LCD. The scale on the air pressure gauges shall read from 0 to 150 pounds per square inch (PSI). The air pressure scales shall be linear to operate with an accuracy of 1 degree of the measured data with a red indication zone on the gauge showing critical levels of air pressure. A red indicator light in the gauge shall indicate a low air pressure, as well as a message on the LCD screen. The odometer shall display up to 9,999,999.9 miles. The trip odometer shall display 9,999.9 miles. The LCD shall display Transmission Temperature in degrees Fahrenheit on the upper portion of the LCD. The LCD screen shall also be capable of displaying certain diagnostic functions.

One (1) four-movement gauge displaying engine oil pressure, coolant temperature, fuel level, voltmeter, and an indicator bar displaying Diesel Exhaust Fluid (DEF) LED bar shall be included. The scale on the engine oil pressure gauge shall read from 0 to 120 pounds per square inch (PSI). The engine oil pressure scale shall be linear to operate with an accuracy of 1 degree of the measured. A red indicator light in the gauge shall indicate a low engine oil pressure, as well as a message on the LCD screen. The scale on the coolant temperature gauge shall read from 100 to 250 degrees Fahrenheit (F). The coolant temperature scale shall be linear to operate with an accuracy of 1 degree of the measured data with a red indication zone on the gauge showing critical levels of air pressure. A red indicator light in the gauge shall indicate high coolant temperature, as well as a message on the LCD screen. The scale on the fuel level gauge shall read

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

from empty to full as a percentage of fuel remaining. An amber indicator light shall indicate low fuel at 25% tank level. The scale on the voltmeter shall read from 10 to 16 volts with a red indication zone on the gauge showing critical levels of battery voltage. A red indicator light shall indicate high or low system voltage, as well as a message on the LCD screen. The scale on the DEF LED bar will consist of four (4) LEDs displaying levels in increments of 25% of useable DEF in green. Upon decreasing levels, the indicator bar will change colors to notify the driver of decreasing levels of DEF and action will be required. An amber indicator light shall indicate low levels of DEF, as well as a message on the LCD screen and an audible alarm.

The instrument panel shall include a light bar that will contain the following LED indicator lights:

RED LAMPS

Low Primary Air Pressure (located in gauge)
Low Secondary Air Pressure (located in gauge)
Stop Engine-indicates critical engine fault
Air Filter Restricted-indicates excessive engine air intake restriction
Park Brake-indicates parking brake is set
Seat Belt Indicator-indicates when a seat is occupied and corresponding seat belt remains unfastened
Volts-indicates high or low system voltage (located in gauge)
Low Oil Pressure-indicates low engine oil pressure (located in gauge)
High Coolant Temperature-indicates excessive engine coolant temperature (located in gauge)
DEF Level Bar-DEF level is at critically low level (located in gauge)

AMBER LAMPS

MIL-indicates an engine emission control system fault
Check Engine-indicates engine fault
Check Trans-indicates transmission fault
High Transmission Temperature-indicates excessive transmission oil temperature
ABS-indicates anti-lock brake system fault
Wait to Start-indicates active engine air preheat cycle
HEST-indicates a high exhaust system temperature
Water in Fuel-indicates presence of water in fuel filter
DPF-indicates a restriction of the diesel particulate filter
Regen Inhibit-indicates regeneration has been postponed due to user interaction
Range Inhibit-indicates a transmission operation is prevented and requested shift request may not occur.
SRS-indicates a problem in the RollTek supplemental restraint system
Low Fuel-indicates low fuel, (located in gauge)
DEF-indicates a low level of DEF fluid (located in gauge)
DEF Level Bar-DEF level is at a low level (located in gauge)

GREEN LAMPS

Left and Right turn signal indicators
ATC-indicates low wheel traction for automatic traction control equipped vehicles, also indicates mud/snow mode is active for ATC system
High Idle-indicates engine high idle is active.
Cruise Control-indicates cruise control is active
OK to Pump-indicates the pump engage conditions have been met
Pump Engaged-indicates the pump is currently in use
Auxiliary Brake-indicates secondary braking device is active
DEF Level Bar-indicates useable levels of DEF: 25%, 50%, 75%, 100% (located in gauge)

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

BLUE LAMPS

High Beam Indicator

CONSTANT AUDIBLE ALARMS FROM GAUGE PACKAGE

High Trans Temp
High or Low Voltage
Seatbelt
Check Engine
Check Transmission
Stop Engine
Low Air Pressure
Fuel Low
Water in Fuel
ESC
High Coolant Temperature
Low Engine Oil Pressure
Low Coolant Level
Low DEF Level

OSCILLATING AUDIBLE ALARMS FROM GAUGE PACKAGE

Air Filter
Extended Left and Right Turn remaining on
Cab Ajar
Door Ajar
Low Oil Level

BACKLIGHTING COLOR

The instrumentation gauges and the switch panel legends shall be backlit using red LED backlighting.

CAB EXTERIOR PROTECTION

The cab face shall have a removable plastic film installed over the painted surfaces to protect the paint finish during transport to the body manufacturer.

FIRE EXTINGUISHER

A 2.50 pound D.O.T approved fire extinguisher with BC rating shall be shipped loose with the cab.

ROAD SAFETY KIT

The cab and chassis shall include one (1) emergency road safety triangle kit.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

DOOR KEYS

The cab and chassis shall include a total of four (4) door keys for the manual door locks.

WARRANTY

The chassis manufacturer shall provide a limited parts and labor warranty to the original purchaser of the custom built cab and chassis for a period of twelve (12) months, or the first 24,000 miles, whichever occurs first. The warranty period shall commence on the date the vehicle is delivered to the end user. The warranty shall include conditional items listed in the detailed warranty document which shall be provided upon request.

OPERATION MANUAL

There shall be two (2) digital copies of the chassis operation manual provided with the chassis. The digital data shall include a parts list specific to the chassis model.

ENGINE AND TRANSMISSION OPERATION MANUALS

There shall be one (1) printed hard copy set of the engine operation manual and one (1) printed hard copy set of the transmission operation manual specific to the model ordered included with the chassis in the ship loose items.

AS BUILT WIRING DIAGRAMS

The cab and chassis shall include one (1) digital copy of wiring schematics and option wiring diagrams.

PAINT CONFIRMATION

There shall be a paint confirmation letter sent to the body manufacturer with paint spray outs to confirm the cab primary paint color or primary and secondary paint color as specified by the paint options.

CAB TO AXLE DIMESION

Cab to axle will be 148".

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CHASSIS MODIFICATIONS

LUBRICATION AND TIRE DATA PLATE

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid . . (if applicable)
- Pump priming system fluid, if applicable . . (if applicable)
- Drive axle(s) lubrication fluid
- Air conditioning refrigerant . . (if applicable)
- Air conditioning lubrication oil . . (if applicable)
- Power steering fluid
- Cab tilt mechanism fluid . . (if applicable)
- Transfer case fluid . . (if applicable)
- Equipment rack fluid (if applicable)
- CAFS air compressor system lubricant . . (if applicable)
- Generator system lubricant . . (if applicable)
- Front tire cold pressure
- Rear tire cold pressure
- Maximum tire speed ratings

VEHICLE DATA PLATE

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the;
 - Engine
 - Transmission
 - Air
 - Fuel
- Serial numbers for the
 - Engine
 - Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

OVERALL HEIGHT, LENGTH DATA PLATE (US)

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in feet and inches, the length of the completed fire apparatus in feet and inches and the GVWR in pounds.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

ACCIDENT PREVENTION

There shall be a placard in the cab seating area which reads, "ALL OCCUPANTS MUST BE SEATED AND BELTED WHEN THE APPARATUS IS IN MOTION".

PERSONNEL CAPACITY

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

ACCIDENT PREVENTION

If the rear bumper is 8" deep or more, there shall be a placard on the rear face of the body, in clear sight from the ground, which reads, "WARNING - DO NOT RIDE ON STEPS OR DECK AREAS WHILE THE APPARATUS IS IN MOTION. DEATH OR SERIOUS INJURY MAY RESULT".

WEARING HELMET WARNING

A label stating "DO NOT WEAR HELMET WHILE SEATED" shall be visible from each seating location.

FRONT BUMPER

The front bumper shall be as provided by the cab/chassis manufacturer. No other alternation or modifications are required.

BUMPER GUARDS

Two (2) black rubber bumper guards shall be provided on front face of front bumper, one each side of specified mechanical siren.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

EXHAUST SYSTEM (VERTICAL)

The existing exhaust tailpipe shall be modified to a vertical exhaust pipe, extending above the body height.

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the apparatus or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

EXHAUST ADAPTER

The vehicle vertical exhaust shall be provided with a MagneGrip VSR (Vertical Stack Rail) adapter.

SHOP NOTES

Engineering to look at the overall height of the magna grip exhaust relative to the overall height requirement for this vehicle.

THREE (3) ANTENNA RAIL

One (1) radio antenna rail(s) shall be provided and installed on roof of vehicle. Each rail shall be constructed of aluminum, forming a two piece box design. The top section shall be removable for easy access to the individual antenna wiring. Three (3) antenna bases shall be provided and installed in each rail. Each antenna base shall include enough cable to reach radio location plus a service loop of at least 3' of LMR195 flexible communications cable. The antenna wiring shall enter the vehicle roof at a single point under the end of the rail. The end of each radio antenna shall be routed to radio mounting locations, or as determined by the Hilton-ParmaFire District.

Due to the various configurations of antenna whips, the contractor shall provide the antenna base only, and Hilton-ParmaFire District shall provide the antenna whip.

SHOP NOTES

Terminate Antenna Wires behind cab dash area

HUB AND NUT COVERS

Front and rear wheels shall be provided with stainless steel hub caps and wheel nut covers.

MUDFLAPS

There shall be rubber mudflaps furnished and installed behind each set of tires.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

CAB INTERIOR CABINET - CURBSIDE OVERHEAD

There shall be one (1) overhead cabinet(s) provided on interior. Cabinet(s) shall be constructed of 1/8" smooth finish aluminum, and painted with a dark gray hammer tone powder coat paint finish for a hard durable surface. Each cabinet shall be approximately 14" high x 14" deep, length to best fit the designated area.

- There shall be one (1) 120 volt outlet(s) located inside this cabinet against the back wall unless noted otherwise.
SHOP NOTES
locate in upper rear corner
 - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
 - Outlet(s) shall be powered by both the on-board generator and shore power system through a relay system.
- The above cabinet(s) shall have lift-up type door(s) with dry-erase outer surface.
- One (1) 12 volt terminal block(s) installed to provide 12 VDC power for equipment supplied by the Hilton-ParmaFire District.
SHOP NOTES
To be located in rear wall overhead cabinet - next to 120 volt outlet. To be wired battery direct.

CAB INTERIOR CABINET - STREETSIDE OVERHEAD

There shall be one (1) overhead cabinet(s) provided on interior. Cabinet(s) shall be constructed of 1/8" smooth finish aluminum, and painted with a dark gray hammer tone powder coat paint finish for a hard durable surface. Each cabinet shall be approximately 14" high x 14" deep, length to best fit the designated area.

- There shall be one (1) 120 volt outlet(s) located inside this cabinet against the back wall unless noted otherwise.
SHOP NOTES
locate in upper rear corner
 - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
 - Outlet(s) shall be powered by both the on-board generator and shore power system through a relay system.
- The above cabinet(s) shall have lift-up type door(s) with dry-erase outer surface.
- One (1) 12 volt terminal block(s) installed to provide 12 VDC power for equipment supplied by the Hilton-ParmaFire District.
SHOP NOTES
To be located in rear wall overhead cabinet - next to 120 volt outlet. To be wired battery direct.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CAB INTERIOR CABINET - OVERHEAD

There shall be two (2) overhead cabinet(s) provided on interior. Cabinet(s) shall be constructed of 1/8" smooth finish aluminum, and painted with a dark gray hammer tone powder coat paint finish for a hard durable surface. Each cabinet shall be approximately 14" high x 14" deep x 26" wide.

- Cargo netting of 1-1/2" nylon webbing provided at cabinet opening with easy release automotive style latches at top and sides.

CAB INTERIOR 120V OULETS

- There shall be one (1) 120 volt outlet(s) located behind driver's seat.
 - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R) 4 gang outlet.
 - Outlet(s) shall be powered by both the on-board generator and shore power system through a relay system.
- There shall be one (1) 120 volt outlet(s) located behind officer's seat.
 - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R) 4 gang outlet.
 - Outlet(s) shall be powered by both the on-board generator and shore power system through a relay system.

FUEL FILL

There shall be one (1) fuel fill door located in the streetside exterior wheel well panel, behind the rear axle. The fill door shall be fabricated from brushed stainless steel. There shall be a permanent label with the text "DIESEL FUEL ONLY" located adjacent to the fuel fill access.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

BODY DESIGN

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the Hilton-ParmaFire District to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the Hilton-ParmaFire District from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

EXTERIOR STAINLESS STEEL BODY

The fabrication of the body shall be completed using 12 gauge type #304 stainless steel. This shall include the compartment front panels, vertical side sheets, side upper roll-over panels, rear panels and compartment door frames. All non-structural exterior body panels and all compartment floors shall be constructed with not less than 12 gauge type #304 stainless steel. Interior compartment dividing walls shall be constructed with not less than 14 gauge type #304 stainless steel. Lighter gauge sheet metal will not be acceptable in these areas.

The front and rear corners of body shall be formed as part of the front or rear body panels. This provides a stronger body corner and finished appearance. The use of extruded corners, or caps will not be acceptable, No Exceptions.

Each compartment door frame opening shall be fabricated of formed "C" channel approx. 4" wide x 3" deep. The encapsulated channel design shall provide the maximum strength in the body structure. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be pre-formed, then positioned in body and welded into final position. All compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All seams in sheet metal below frame, and around the rear wheel well area shall be welded continuous to prevent moisture from entering compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel fasteners shall be used in mounting exterior trim, hardware and equipment.

Exterior compartments shall have louvers in lower back wall of compartment for ventilation.

DRIP RAILS

The body shall have drip rails over the side full height compartments. The drip rails shall be formed into the upper body panels providing a ridged lower panel and a flat upper body panel surface. The use of mechanically fastened, taped or glued on drip rails will not be acceptable, No Exceptions.

ROOF CONSTRUCTION

The roof shall be integral with the body and shall be all welded construction. The roof shall be constructed from 3/16" (.188) aluminum 3003H-14 alloy treadplate and supported with 2" x 2" x 1/4" tubing running the full width of the body. The supports shall be welded in place on approximate 16" centers.

All seams in the roof area shall be welded to the radius and supports prior to paint to prevent entry of moisture. All roof seams shall be continuously welded.

A 2" formed radius shall be provided along the body sides. The use of extrusions will not be acceptable, No Exceptions.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

BODY SUBFRAME

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

The body subframe shall be constructed from stainless steel tubing. The subframe shall consist of two (2) 2" x 4" x 11 gauge type #304 stainless steel tubes running the full length of the body and spaced the same width as the chassis frame rails. Welded to the two (2) stringers shall be 2" x 4" x 11 gauge type #304 stainless steel tubing cross members. These cross members shall extend the full width of the body to support the compartments. Cross members shall be located at front and rear of body, below compartment divider walls, and in front and rear of wheel well opening. Additional stainless steel cross members shall be located on 16" centers, or as necessary to support walkways or heavy equipment.

The compartment area behind the rear axle may be supported by a drop frame fabricated of the same 2" x 4" x 11 gauge stainless steel tube and the main stringers. Any such rear drop frame shall be constructed using a minimum of four (4) vertical drop tubes, welded to the main subframe. In areas where heavy equipment shall be mounted, drop frame support shall be constructed with 2" x 4" x 11 gauge stainless steel tube. All drop frame structures must be welded directly to the body subframe to allow the body to be a completely separate structure from the chassis.

To form the frame, the tubing shall be welded at each joint using a wire feed MIG welders with ER308 stainless steel welding wire.

BODY MOUNTING

The body subframe shall be fastened to the chassis frame with a minimum of six (6) spring loaded body mounts. Each mount shall be configured using a two-piece encapsulated slide bracket. The two (2) brackets shall be fabricated of heavy duty 1/4" thick steel and shall have a powder coat finish to prevent any corrosion. Each mounting assembly shall utilize two (2) 3/4" diameter x 6" long grade 8 bolts and two (2) heavy duty springs. The assembly design shall allow the body and subframe to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall eliminate any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement will not be acceptable.

12" REAR STEP BUMPER

The full width rear bumper shall be constructed from 2" x 2 x 11 gauge stainless steel tubing frame and covered with 3/16" NFPA compliant aluminum tread plate. The bumper shall extend from the rear vertical body panel 12" and provide a rear step with a minimum of 1/2" space at body for water drainage.

REAR TOW EYES

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below the apparatus body. The tow eyes shall be fabricated from 3/4" thick steel plate and shall have a black powder coat finish.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

GROUND LIGHTS

There shall be two (2) OnScene 9" Premium LED light(s) installed below bumper capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting shall be switchable but activated automatically when the vehicle park brake is set.

WHEEL WELL EXTERIOR PANEL

The exterior panel of the body wheel well shall be constructed from not less than 12 gauge type #304 smooth stainless steel.

STAINLESS STEEL BODY FENDERS

The body wheel well openings shall be provided with round radius, polished stainless steel fenderettes. The fenderettes shall be bolted and easily replaceable if damaged. The fenderettes shall be installed using a rubber gasket to reduce buildup of moisture and/or debris.

WHEEL WELL LINERS

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will not accumulate dirt or water.

BODY PAINT SPECIFICATIONS

BODY PAINT PREPARATION

After the body and components have been fabricated they shall be disassembled prior to painting so when the vehicle is complete there shall be finish paint beneath the removable components. The body shall be totally removed from chassis during the paint process to insure the entire unit is covered. The body and components shall be metal finished as follows to provide a superior substrate for painting.

The exterior body shall undergo a thorough cleaning process starting with a biodegradable phosphoric acid solution to begin the etching process followed by a complete clear water rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the metal surface for greater film adhesion. If the compartment interior is to be painted the interior shall be acid etched as described above then primed with an epoxy primer and all seams caulked.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

PAINT PROCESS

The paint process shall follow the strict standards set forth by PPG Industries guidelines. Painters applying PPG products will be PPG Certified Commercial Technicians, and re-certified every two (2) years.

The body shall go through an eight-stage paint process;

- 1) Clean bare metal using a solvent base wax & grease remover.
- 2) Finish all exterior body seams as necessary, followed by a thorough sanding of all bare metal to be painted.
- 3) Re-clean bare metal using a solvent base wax & grease remover.
- 4) Bare Metal Epoxy Primer Coat - PPG Delfleet® Evolution corrosion resistance epoxy primer to be applied at 1.0-2.0 mills DFT over clean abraded bare metal.
- 5) Primer Filler Coat - PPG Delfleet® Evolution urethane build primer to achieve total thickness of 3.0-6.0 mills DFT after sanding.
- 6) Base coat (Color) - PPG Delfleet® Evolution High Solids Polyurethane Base coat. Apply 1.0-3.0 mills DFT of base coat color to achieve full hiding.
- 7) Clear coat PPG Delfleet® Evolution polyurethane premium quality clear coat with improved mar resistant finish. The clear coat shall be applied to achieve a total dry film thickness of 2.0-3.0 mills.
- 8) Curing process of the painted body shall go through a force dry/bake cycle process. The painted components shall be baked 180 degrees for 2 hours to achieve a complete coating cure on the finished product.

MACHINE POLISHED

After the force dry/bake cycle and ample cool down time, the coated surface shall be sanded using 1,000, 1,500, and or 3,000 grit sandpaper to remove surface defects. In the final step, the surface shall be buffed then polished to an extra high gloss smooth finish. Total dry film thickness of paint will average between 8.0-12.0 mills.

PAINT - ENVIRONMENTAL IMPACT

The contractor shall meet or exceed all current State (his) regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. PPG Delfleet® Evolution paint shall be free of all heavy metal (lead & chromate) components. Paint emissions from sanding and painting shall be filtered and collected. All paint wastes shall be disposed of in an environmentally safe manner. Solvents used in cleanup operations shall be collected, sent off-site for distillation and returned for reuse.

PAINT FINISH - SINGLE COLOR

The body shall be painted with a single color of PPG Delfleet® Evolution paint per approved customer sprayout.

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, an isolation tape, or gasket shall be used to prevent damage to the finish painted surfaces. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nutserts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

Touch-up paint shall be provided with completed vehicle.

- Paint Color: Match cab/chassis supplied paint color.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

BODY UNDERCOATING

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

UNDERCOAT WARRANTY

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

PAINT WARRANTY

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle.

COMPARTMENT INTERIOR FINISH

The interior of all exterior body compartments shall be a "Maintenance Free" smooth unpainted finish. All body seams shall be finished with a caulk sealant for both appearance and moisture protection.

REFLECTIVE STRIPE REQUIREMENTS

Material

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retroreflection of 10 with observation angle of 0.2 degrees and entrance angle of -4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

Minimum Requirements

A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 4 in. (100 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

GRAPHICS PROOF

A color graphics proof of the reflective striping layout shall be provided for approval by Hilton-ParmaFire District prior to installation. The graphics proof shall be submitted to Hilton-ParmaFire District on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

REFLECTIVE STRIPE - CAB SIDE

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

There shall be a 1" Scotchcal reflective stripe located 1" above and a second 1" Scotchcal reflective stripe located 1" below the main stripe.

- This reflective stripe shall be white in color.

REFLECTIVE STRIPE - CAB FRONT

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

There shall be a 1" Scotchcal reflective stripe located 1" above and a second 1" Scotchcal reflective stripe located 1" below the main stripe.

- This reflective stripe shall be white in color.

REFLECTIVE STRIPE - BODY SIDES

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

There shall be a 1" Scotchcal reflective stripe located 1" above and a second 1" Scotchcal reflective stripe located 1" below the main stripe.

- This reflective stripe shall be white in color.

The stripe shall extend from the chassis to the body where it will angle up and then extend straight back to the rear of the body.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS

At least 50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width.

The rear side panels only of the body shall have a Chevron style reflective stripe layout, and cover as much of the rear side panels as possible. Chevron panels shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panels shall have a minimum 10 year warranty for material failure, and colorfastness.

The stripe material shall be 3M Diamond Grade.

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

LETTERING

GRAPHICS PROOF

A color graphics proof of the lettering layout shall be provided for approval by Hilton-ParmaFire District prior to installation. The graphics proof shall be submitted to Hilton-ParmaFire District on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

The following lettering shall be provided and installed on the completed unit as follows;

SIDE CAB DOOR LETTERING

There shall be eighteen (18) 5" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

Final design and layout shall be determined prior to construction.

There shall be fifty four (54) 3" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

Final design and layout shall be determined prior to construction.

UPPER BODY SIDE LETTERING

There shall be forty eight (48) 8" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

Final design and layout shall be determined prior to construction.

There shall be three (3) 12" high reflective letters furnished and installed on the vehicle.

- This reflective lettering shall be black in color.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

CUSTOM DECAL LOGO - 12" -18"

Two (2) custom designed 12" - 18" Scotchal type retroreflective logo shall be provided and located on the completed vehicle. The exact design and/or artwork shall be provided by the Hilton-ParmaFire District prior to construction.

Two (2) copy of the above custom logo shall be provided and located on the completed vehicle as directed by Hilton-ParmaFire District.

EXTERIOR COMPARTMENT DOORS

ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM)

The apparatus shall be equipped with Robinson ROM Series III roll-up exterior compartment doors. Robinson roll-up doors shall be complete with the following features;

- Doors shall be front roll with drum positioned at upper front portion of compartment to afford maximum clearances and head room for mounting equipment to ceiling of compartment
- There shall be a non-abrasive side brush seals
- Every slat must have interlocking end shoes to prevent slat from moving side-to-side and binding the door
- Between each slat must be a co-extruded PVC inner seal to prevent metal-to-metal contact and to repel moisture. This inner seal is not visible to detract from appearance of door
- Slat are to have interlocking joints with a folding locking flange to provide security and prevent penetration by sharp objects
- Slat to be double-wall extrusion 1.366" high by .315" thick. Exterior surface to be flat and interior surface to be concave to prevent loose equipment from interfering with door operation
- Latch system to be a full width one piece lift bar operable by one (1) hand
- A 2" wide finger pull integrated into the bottom rail extrusion for easy one (1) hand opening and closing
- Clip system that connects the curtain slats to the operator drum which allows for easy tension adjustment without tools
- Each roll-up door shall have a 4" diameter counterbalance operator drum to assist in lifting the door.
- Track shall be one-piece aluminum that has an attaching flange and finishing flange incorporated into its design
- Drip rail will have specially designed seal that prevents the seal from scratching the door
- Bottom rail extrusion must have smooth back to prevent loose equipment from jamming the door
- Bottom rail to have "V" shaped double seal to prevent water and debris from entering the compartment
- Standard replacement parts to be shipped from the United States and available in as little as 48 hours

Each shutter door shall decrease the compartment door frame opening approximately 2.00" in width and approximately 4.50" in height for the bottom section of door assembly.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

BODY HEIGHT MEASUREMENTS

The vertical body dimensions shall be as follows:

AHEAD OF REAR AXLE

	<u>Description</u>	<u>Dimension</u>
A	Bottom of Subframe to Top of Body	89.0"
B	Bottom of Subframe to Bottom of Body	25.0"
C	Vertical Door Opening	
	-with roll-up door	67.5"
	-with hinged door	71.5"

ABOVE REAR AXLE

	<u>Description</u>	<u>Dimension</u>
D	Vertical Door Opening - Above Rear Wheel	
	-with roll-up door	34.0"
	-with hinged door	37.0"

BEHIND REAR AXLE

	<u>Description</u>	<u>Dimension</u>
E	Bottom of Subframe to Bottom of Body	20.0"
F	Vertical Door Opening	
	-with roll-up door	62.0"
	-with hinged door	66.0"

GENERAL

	<u>Description</u>	<u>Dimension</u>
G	Bottom of Drip Rail to Top of Body	38.5"

(Dimensions are generic and subject to change during the actual design process)

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

FIVE (5) UPPER BODY COMPARTMENTS (OPEN)

The forward transverse compartment shall be 90.0" long x 27.0" wide x 33.5" deep. There shall be four (4) compartments parallel to the sides of the body, two (2) on each side. The streetside rear and curbside forward compartment shall be approximately 70.0" long x 27.0" wide x 33.5" deep. The streetside forward and curbside rear compartment shall be approximately 42.0" long x 27.0" wide x 33.5" deep. The side compartments shall be open under each door sill to allow for long equipment. Each compartment shall be integral with the body construction, and will not be bolted or add-on modules. The outside walls of each compartment will be double walled to prevent equipment from denting the outside painted surface.

Each compartment shall have a lift-up type compartment door hinged on the outboard side. Each door shall be fabricated from 3/16" aluminum tread plate. Each door shall have two (2) pneumatic type cylinders, one (1) at each end, attached to cast aluminum brackets mounted to the interior surface of the door to hold the door in both the opened and closed positions. Each door shall be mounted using 16" long, equally spaced, 14 gauge stainless steel hinges, with 1/4" stainless steel pin. A polyester barrier film gasket shall be placed between stainless steel hinge and the body mounting surface as necessary to prevent corrosion caused by dissimilar metals.

Each compartment door shall overlap a 2" vertical lip on the body roof to prevent entry of moisture and sealed with automotive type rubber molding to provide a weather resistant seal.

Each roof compartment door shall have a chrome 7" handle bolted to center of each door.

Each compartment shall have a 13/16" drain hole located in floor of compartment with a 1" flexible drain tube that terminates below body.

Each compartment shall have a horizontally mounted OnScene Solutions LED Night Stik on the underside of the door. The light will be automatically activated by a gravity-driven, sealed, ball-style tilt switch mounted to one of the pneumatic cylinders and also wired to the NFPA required hazard warning light in cab.

- One (1) Grainger model 1NNF7 or equal, 240 VAC, 3.1 HP electric powered air compressor with 20 gallon storage tank shall be located in this compartment. One (1) 240 VAC twist lock receptacle with switch shall be provided on wall within easy reach of operator for turning the compressor ON/OFF.

Results of the NFPA required utility air system test shall be provided with delivered vehicle.

UPPER BODY WALKWAY

A 34" wide, upper body walkway shall be provided at the center of body and recessed into the roof structure. The walkway shall be fabricated from NFPA compliant 3/16" aluminum tread plate with continuously welded seams to prevent moisture penetration into apparatus body, No Exceptions. The walkway shall be supported with 2" x 2" x 1/4" aluminum tubing on 14" - 22" centers.

13/16" drains shall be installed at front of walkway connected to 1" flexible drain tubes that will terminate below the body.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

WALKWAY/STEP LIGHTS

There shall be three (3) OnScene Solutions 9" LED NightStik lights provided to illuminate the walkway or step area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in a ball burnished cast aluminum housing to protect against damage from personnel or equipment.

Lighting shall provide illumination at a minimum level of 2 fc (20 lx) on all work surfaces, steps, and walkways. Lighting shall be switchable but activated automatically when the vehicle park brake is set.

ACCESS LADDER

The top of the body shall be accessible from the ground by a folding ladder. The ladder design shall have a main ladder section, bolt on upper hand rail section and a folding lower step section for better angle of departure. Ladder stores in a folded position and then pulls out to a comfortable climbing angle. The ladder shall be parallel to the body when in the stored position.

Each cast aluminum step shall be 4-1/2" deep x 16" wide. Hand railing shall be 2-1/8" oval shaped aluminum tubing with a ribbed gripping surface.

The ladder shall be wired to the door ajar warning light in cab to warn the driver that the ladder is in the down position. Ladder shall be mounted to body with stainless steel bolts.

Ladder shall be located on rear curbside of the body.

WALKWAY/STEP LIGHTS

There shall be two (2) OnScene Solutions 9" LED NightStik lights provided to illuminate the walkway or step area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in a ball burnished cast aluminum housing to protect against damage from personnel or equipment.

Lighting shall provide illumination at a minimum level of 2 fc (20 lx) on all work surfaces, steps, and walkways. Lighting shall be switchable but activated automatically when the vehicle park brake is set.

ROOF ACCESS HANDRAIL

There shall be one (1) handrail mounted on top of body to assist in roof access. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

BODY WIDTH DIMENSIONS

The body shall be 100.0" wide, not including drip rail or non-permanent fixtures. Interior compartment depth dimensions shall be:

<u>Area Description</u>	<u>Dimension</u>
Transverse Area:	95.5"
- Above Top of Subframe	
Compartment Depth:	24.5"
- Below Top of Subframe	
- Ahead of Rear Axle	
Compartment Depth:	23.5"
- Below Top of Subframe	(Eng. Note)
- Behind the Rear Axle	

(Dimensions are generic and subject to change during the actual design process)

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

STREETSIDE COMPARTMENT - FRONT (S1)

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted stainless steel Uni-Strut for specified component installation.
- There shall be one (1) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
 - There shall be one (1) vertical partition(s) installed on tray dividing the tray into left and right sides. Each vertical partition shall be horizontally adjustable; mounted on aluminum shelf trac on tray floor.
 - The above specified fire extinguisher(s) shall be installed on the completed unit, location to be determined by the Hilton-ParmaFire District.
- There shall be three (3) Zico 1000 series KD-UH walkaway type SCBA air pack bracket(s) with high cycle coated spring clips and angled foot plate (no CRS strap inc.).
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

- Two (2) OnScene Solutions 63" LED Nightstik compartment lights, vertically mounted.
- One (1) 12 volt terminal block(s) installed to provide 12 VDC power for equipment supplied by the Hilton-ParmaFire District. Exact location shall be determined at the pre-construction meeting.
- The controls for the specified light tower(s).
- One (1) OnScene 9" LED ground light shall be provided below the body.
- The 12 volt electrical distribution panel shall be located in the streetside front lower compartment.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

STREETSIDE COMPARTMENT - AHEAD OF REAR WHEELS (S2)

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted stainless steel Uni-Strut for specified component installation.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 94" deep and as wide as the compartment layout or door opening permits, capable of extending out either side of the body located above the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed, 40% extended and 70% extended positions. Each tray top shall be fabricated from 3/16" 3003 aluminum sheet shall have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".
 - The above specified ventilation fan(s) shall be installed on completed unit using mounting brackets and/or straps, location to be determined by the Hilton-ParmaFire District.
SHOP NOTES
Mounting Only - Fans are not provided
- There shall be one (1) slide-out smooth aluminum vertical tool board(s) approximately 24" deep. Each tool board(s) vertical exterior edge shall have a double 90 degree formed edge to provide an easy grip handle. The top and bottom of tool board(s) shall be provided with Accuride 9300 series slide tracks. Each board shall be rated for a maximum 200 lbs. evenly distributed load. Each tool board shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.
 - The tool board material shall be PAC Trac double face 7040 extrusion with the tracks in a horizontal orientation.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

- Each tool board will be bolted to compartment floor.
- There shall be one (1) vertical compartment partition dividing the compartment into left and right sides.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- One (1) Hannay ECR1618-17-18 240 volt electric cable reel(s) capable of storing 200' of 10/4 electric cable. Reel(s) shall be designed to hold 110% of the capacity of cord length, with fully enclosed 60 amp, four (4) conductor collector rings. Reel(s) shall be mounted to channel structure that allows for side-to-side adjustment of reel position.
 - Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and not be more than 72 in. (1830 mm) above the operator's standing position, and shall be marked with a label indicating its function.
 - A label shall be provided in a visible location adjacent to reel with following information: Current rating, Current type, Phase, Voltage, and Total cord length.
 - The electric cord reel shall equipped with 200' of 10/4 SEOW yellow cord, a molded plastic ball clamp, and a single heavy duty L14-30 twist-lock female plug.
- One (1) Akron model EJB electrical junction box with yellow powder coat finish. The power distribution box shall meet all requirements described in NFPA Section 22.12.8. The junction box shall include:
 - A 12" pigtail that terminates in an L14-30 configuration to match the cable on the cord reel. The outlet configuration shall include:
 - One (1) 5-20 duplex straight-blade receptacle
 - One (1) 5-20 duplex straight-blade receptacle
 - One (1) 5-20 duplex straight-blade receptacle
 - One (1) 5-20 duplex straight-blade receptacle
 - One (1) EJB vertical apparatus mounting bracket - treadplate
 - The fairlead roller shall be mounted directly to the reel.
- Two (2) OnScene Solutions 63" LED Nightstik compartment lights, vertically mounted.
- One (1) OnScene 36" Premium LED compartment light, horizontally mounted at the top of the compartment toward the door opening.
- There shall be one (1) 120 volt outlet(s) located in this compartment on the forward wall unless noted otherwise.
- The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
SHOP NOTES
Outlet and power strip to be located on transverse tray
- There shall be one (1) 120 volt outlet strip(s) approximately 2' long with straight blade household type outlets provided

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

with this outlet. Exact mounting location shall be specified by the Hilton-ParmaFire District at the pre-construction meeting.

SHOP NOTES

Outlet and power strip to be located on transverse tray

- Outlet(s) shall be powered by both the on-board generator and shore power system through a relay system.
- One (1) OnScene 9" LED ground light shall be provided below the body.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S3)

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

SHOP NOTES

Add 2" lower stainless Door threshold guard under the door opening to prevent paint chips

COMPARTMENT LAYOUT

- There shall be vertically mounted stainless steel Uni-Strut for specified component installation.
- There shall be one (1) transverse module fabricated from 3/16" (.188) 3003H-14 aluminum alloy smooth sheet. The module will be designed for the following long tools and equipment:
 - The list of items to be stored in the transverse module shall be determined at the pre-construction meeting.
 - Four (4) Hilton-ParmaFire District supplied pike pole(s). Manufacturer, model number and dimensions of the pike pole(s) shall be provided during the pre-construction meeting.
 - SHOP NOTES
 - For Fire Hooks Unlimited "New York Hooks" Without DRing Handles, (2) to come out street side and (2) to come out Curbside
 - One (1) Hilton-ParmaFire District supplied stokes basket(s). Manufacturer, model number and dimensions of the stokes basket(s) shall be provided during the pre-construction meeting.
 - SHOP NOTES
 - Stokes Basket Dimension is 84"X13"X34

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

- One (1) Hilton-ParmaFire District supplied Ice Board. Manufacturer, model number and dimensions of the scoop shall be provided during the pre-construction meeting.
 - SHOP NOTES
 - Ice Board Dimension is 75 X 8 X 24

- Two (2) Hilton-ParmaFire District supplied backboard(s). Manufacturer, model number and dimensions of the backboard(s) shall be provided during the pre-construction meeting.
 - SHOP NOTES
 - Backboard 72 X 16.5 X 2.5

- One (1) Hilton-ParmaFire District supplied Appliance Dolly. Manufacturer, model number and dimensions to be provided during the pre-construction meeting.
 - SHOP NOTES
 - Dolly Dimension is 61 X 13 X 24

- One (1) Hilton-ParmaFire District supplied Little Giant ladder(s). Manufacturer, model number and dimensions of the ladder(s) shall be provided during the pre-construction meeting.
 - SHOP NOTES
 - Little Giant 56 X 8 X 24

- Two (2) OnScene Solutions 36" LED Nightstik compartment lights, vertically mounted.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

STREETSIDE COMPARTMENT - REAR (S4)

The interior useable compartment width shall be approximately 64.0" wide.

The compartment door opening shall be approximately 57.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted stainless steel Uni-Strut for specified component installation.
- There shall be two (2) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges

SHOP NOTES

Located directly above tool cabinet.

- There shall be two (2) slide-out smooth aluminum vertical tool board(s) approximately 24" deep. Each tool boards shall be fabricated of 3/16" (.188) aluminum 3003H-14 alloy smooth plate with double 90 degree formed edge to provide an easy grip handle. The top and bottom of tool board shall be provided with Accuride 9300 series slide tracks. Each board shall be rated for a maximum 200 lbs. evenly distributed load. Each tool board shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.
 - The tool board material shall be PAC Trac double face 7040 extrusion with the tracks in a horizontal orientation.
- Specified tool boards shall be provided with aluminum tool trays at lower edge.
 - Each tool board shall be horizontally adjustable; mounted on aluminum shelf trac on compartment floor.
- There shall be one (1) vertical compartment partition dividing the compartment into left and right sides.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

- One (1) Lista ST Series 8 drawer cabinet shall be provided, 41.5" high x 28-1/4" wide x 22-1/2' deep. The cabinet shall have eight (8) individual locking drawers.
- There shall be two (2) removable plastic tool box(s) with hand holes for carrying. Each tool box shall be fabricated from 1/2" (.50) textured finish polypropylene sheet.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- Two (2) OnScene Solutions 63" LED Nightstik compartment lights, vertically mounted.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CURBSIDE COMPARTMENT - FRONT (C1)

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted stainless steel Uni-Strut for specified component installation.
- There shall be two (2) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
 - The portable generator(s) shall be mounted on the completed unit, locations as per the Hilton-ParmaFire District.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- Two (2) OnScene Solutions 63" LED Nightstik compartment lights, vertically mounted.
- The cab tilt control pendant.
- There shall be one (1) 240 volt outlet(s) located in this compartment mounted on the forward wall unless noted otherwise.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

- The outlet receptacle(s) shall be 30 amp, twist-lock (NEMA L6-30R).
SHOP NOTES
Locate low on forward wall
- Outlet(s) shall be powered through the on-board generator system.
- One (1) OnScene 9" LED ground light shall be provided below the body.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CURBSIDE COMPARTMENT - AHEAD OF REAR WHEEL (C2)

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted stainless steel Uni-Strut for specified component installation.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 94" deep; capable of extending out either side of the body located above the level of the chassis frame rails. (Specified in opposite side compartment.)
- There shall be one (1) slide-out smooth aluminum vertical tool board(s) approximately 24" deep. Each tool board(s) vertical exterior edge shall have a double 90 degree formed edge to provide an easy grip handle. The top and bottom of tool board(s) shall be provided with Accuride 9300 series slide tracks. Each board shall be rated for a maximum 200 lbs. evenly distributed load. Each tool board shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.
 - The tool board material shall be PAC Trac double face 7040 extrusion with the tracks in a horizontal orientation.
 - Each tool board will be bolted to compartment floor.
- There shall be two (2) vertical compartment partition dividing the compartment into left and right sides.
- There shall be one (1) SCBA cylinder storage module for 6" OD (maximum) SCBA bottles. The module shall have an exterior shell fabricated from 1/8" (.125) 3003H-14 aluminum alloy sheet. The module shall have a 2" slope, front to back to prevent cylinders from sliding out. The SCBA cylinder storage tubing shall be fabricated from PVC pipe to prevent damage or abrasion to cylinders. In addition there shall be rubber matting provided in the base of each storage tube for bottle protection and to prevent slipping.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

SHOP NOTES

Brand: _____

Diameter: _____ " (must be less than 5.625")

Length: _____ " (with valve)

- The SCBA cylinder storage module shall be capable of storing eighteen (18) SCBA cylinders up to 6" diameter.
SHOP NOTES
Lower compartment, cylinders 22" long.

- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.

SHOP NOTES

partial

- One (1) Hannay ECR1618-17-18 240 volt electric cable reel(s) capable of storing 200' of 10/4 electric cable. Reel(s) shall be designed to hold 110% of the capacity of cord length, with fully enclosed 60 amp, four (4) conductor collector rings. Reel(s) shall be mounted to channel structure that allows for side-to-side adjustment of reel position.
 - Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and not be more than 72 in. (1830 mm) above the operator's standing position, and shall be marked with a label indicating its function.
 - A label shall be provided in a visible location adjacent to reel with following information: Current rating, Current type, Phase, Voltage, and Total cord length.
 - The electric cord reel shall equipped with 200' of 10/4 SEOW yellow cord, a molded plastic ball clamp, and a single heavy duty L14-30 twist-lock female plug.
- One (1) Akron model EJB electrical junction box with yellow powder coat finish. The power distribution box shall meet all requirements described in NFPA Section 22.12.8. The junction box shall include:
 - A 12" pigtail that terminates in an L14-30 configuration to match the cable on the cord reel. The outlet configuration shall include:
 - One (1) 5-20 duplex straight-blade receptacle
 - One (1) 5-20 duplex straight-blade receptacle
 - One (1) 5-20 duplex straight-blade receptacle
 - One (1) 5-20 duplex straight-blade receptacle
 - One (1) EJB vertical apparatus mounting bracket - treadplate
 - The fairlead roller shall be mounted directly to the reel.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

- Two (2) OnScene Solutions 63" LED Nightstik compartment lights, vertically mounted.
- There shall be one (1) 120 volt outlet(s) located in this compartment on the forward wall unless noted otherwise.
 - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
SHOP NOTES
locate on lower forward wall
 - Outlet(s) shall be powered by both the on-board generator and shore power system through a relay system.
- One (1) OnScene 9" LED ground light shall be provided below the body.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C3)

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

SHOP NOTES

Add 2" lower stainless Door threshold guard under the door opening to prevent paint chips

COMPARTMENT LAYOUT

- There shall be vertically mounted stainless steel Uni-Strut for specified component installation.
- There shall be one (1) transverse module(s) which extends to the opposite side of the body. (Specified in opposite side compartment.)
- Two (2) OnScene Solutions 36" LED Nightstik compartment lights, vertically mounted.
- One (1) 12 volt terminal block(s) installed to provide 12 VDC power for equipment supplied by the Hilton-ParmaFire District. Exact location shall be determined at the pre-construction meeting.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CURBSIDE COMPARTMENT - REAR (C4)

The interior useable compartment width shall be approximately 64.0" wide.

The compartment door opening shall be approximately 57.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be one (1) Hilton-ParmaFire District supplied radio(s) with antenna installed in this compartment.
 - Radio shall be installed per Manufacturer's requirements and wired for proper 12 volt power and ground.
- **SHOP NOTES**
Run antenna above body walk in area
- There shall be vertically mounted stainless steel Uni-Strut for specified component installation.
- Base of compartment shall be provided bolted floor with slope towards rear of compartment for customer cribbing storage.
- There shall be one (1) vertical compartment partition dividing the compartment into left and right sides.
- There shall be one (1) 70" deep module fabricated from 3/16" (.188) 3003H-14 aluminum alloy smooth sheet. The module will be designed for the following long tools and equipment:
 - The list of items to be stored in the transverse module shall be determined at the pre-construction meeting.
 - Eight (8) Hilton-ParmaFire District supplied 4 X4's.
 - There shall be one (1) OnScene Solutions cargo straps provided to secure the stored equipment.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

- There shall be one (1) air bag storage module(s). The module shall be fabricated from 1/8" (.125) 3003H-14 aluminum alloy sheet. Circular notches shall be provided along the front edge to ease the access to the air bags. Each bay shall be sized to hold the air bag and a matching piece of plywood. The make, model and exact dimensions of the air bags shall be provided during the pre-construction meeting.
 - There shall be four (4) OnScene Solutions cargo straps provided to secure the stored equipment.
 - Cargo netting of 1-1/2" nylon webbing provided at cabinet opening with easy release automotive style latches at top and sides.
- SHOP NOTES
Cribbing Area.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) OnScene Solutions 63" LED Nightstik compartment lights, vertically mounted.
- One (1) OnScene 9" LED ground light shall be provided below the body.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

REAR COMPARTMENT - CENTER (RC1)

The rear center compartment shall be closed to both side rear compartments.

The rear center compartment shall start at the bottom of the body and shall be as high as the body permits.

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum shelf-trac for specified component installation.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 24" deep and as wide as the compartment layout or door opening permits located below the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 60" deep and as wide as the compartment layout or door opening permits located above the body subframe and shall be vertically adjustable in height. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification



- Three (3) Hannay EF2022-14-16 hydraulic hose reel(s) capable of storing 200' of dual line hydraulic hose. The rewind button for each reel shall be located adjacent to the reel it controls.
 - The hydraulic reel shall be equipped with 150' of Parker hydraulic hose. The hose shall be Red in color and approved for Amkus Rescue tool application.
SHOP NOTES
Make the color of the hydraulic line the color of the switch on the Ultimate System
 - The hydraulic reel shall connect to the hydraulic pump with two (2) 60' Parker pigtails. The hoses shall be Red in color.
 - The hydraulic reel shall be equipped with 150' of Parker hydraulic hose. The hose shall be Black in color and approved for Amkus Rescue tool application.
SHOP NOTES
Make the color of the hydraulic line the color of the switch on the Ultimate System
 - The hydraulic reel shall connect to the hydraulic pump with two (2) 60' parker pigtails. The hoses shall be Black in color.
 - The hydraulic reel shall be equipped with 150' of Parker hydraulic hose. The hose shall be Yellow in color and approved for Amkus Rescue tool application.
SHOP NOTES
Make the color of the hydraulic line the color of the switch on the Ultimate System
 - The hydraulic reel shall connect to the hydraulic pump with two (2) 60' Parker pigtails. The hoses shall be Yellow in color.
 - The fairlead roller shall be mounted directly to the reel.
- One (1) Hannay EF1520-17-18 low pressure air hose reel(s) capable of storing 200' of low pressure air hose. The rewind button for each reel shall be located adjacent to the reel it controls.
 - The hose reel shall equipped with 200' of 3/8 low pressure air hose. Molded plastic ball clamp shall be provided on the hose to stop it at the 4-way roller. The hose shall be Green in color.
 - The air supply shall be from the utility air compressor.
 - A reel shut-off valve, pressure regulator, and 0-150 psi gauge shall be provided on an aluminum control panel next to the air reel.
 - A on/off switch shall be provided in compartment to power specified utility air compressor.
Specified generator will be required to be energized prior to air compressor operation.
 - The fairlead roller shall be mounted directly to the reel.
- A multi fairlead extendable type rollers assembly shall be provided that allows hoses or cords to be extended away from compartment door edges, slide trays, or shelving that may result in wear damage.
- Two (2) OnScene 63" Premium LED compartment lights, vertically mounted.
- Specified Amkus Ultimate system user controls shall be located in comaprtnent.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

- One (1) Hilton-ParmaFire District supplied gas powered hydraulic power unit(s).
- Mounts will be supplied and installed for three (3) Hilton-ParmaFire District supplied hydraulic ram(s).
SHOP NOTES
Make: Amkus Model: AMK-20R, (2) AMK-40R
Mount on lower tray
- Mounts will be supplied and installed for one (1) Hilton-ParmaFire District supplied hydraulic cutter(s).
SHOP NOTES
Make: Amkus Model: AMK-22
Mount on top tray
- Mounts will be supplied and installed for one (1) Hilton-ParmaFire District supplied hydraulic spreader(s).
SHOP NOTES
Make: Amkus Model: AMK-30CRT
Mount on top tray
- Mounts will be supplied and installed for one (1) Hilton-ParmaFire District supplied hydraulic combination tool(s).
SHOP NOTES
Make: Amkus Model: AMK-25CD
Mount on top tray

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

PLASTIC FLOOR AND SHELF TILE

All compartment floors, shelves, and trays shall be covered with Dri-Dek plastic interlocking grating.

- The plastic floor tile shall be black.
- The plastic edge trim shall be black.

SIDE BODY PROTECTION - RUB RAIL

OnScene Solutions rub rails shall be provided below the compartment door openings on both the streetside and curbside.

The rub rail shall be fabricated from 6063 extruded aluminum, measuring approximately 2-3/4" high x 1-3/8" thick with tapered aluminum end caps. The rub rail shall be bolted to the body using stainless steel bolts and 1-1/2" diameter x 5/8" thick rubber mount isolators to prevent damage to the body.

The rails shall incorporate LED clearance marker lighting recessed into the rail fascia to avoid damage to the light in case of impact. The rub rail shall have an accessory mounting track integrated into the backside of the rail to allow mounting of accessories such as ground lighting.

WALK-IN INTERIOR FINISH DETAILS

DESK, CABINET, CONSOLE FINISH

All specified interior desks, cabinets, overhead cabinets, or consoles shall be fabricated from formed 1/8" 3003 H14 alloy smooth aluminum. After fabrication is completed they shall be painted with a hammer tone powder coat paint finish for a hard durable surface. Paint color shall be gray.

The use of wood materials or laminated surfaces in the construction of desks, cabinets, overhead cabinets, or consoles will not be allowed. There will be **No Exceptions** allowed on specified ruggedized finish.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

CAB/BODY WALK-THROUGH CONNECTION

The front center of the rescue body shall be interconnected with the rear crew area of custom cab through a weather tight walk-through opening. The opening shall be designed to allow the custom cab to tilt forward without disconnecting an attached type seal between the cab and body. The opening shall be approximately 24" wide x 70" high (sized to match the cutout in the rear wall of the cab).

The front of the body shall be cut out to match the cab opening. Additional reinforcements with metal angle or tubing shall be provided to back of cab or front of body, if necessary so that the walk-through opening weakens neither the cab nor body integrity.

The connection shall be weather resistant, yet provide the cab and body to move independent of each other. A flexible 3" rubber weather strip shall be attached to a stainless steel sheet metal frame around the perimeter of the opening in the back wall of the cab. A drip rail shall be provided on front of body above the opening to channel water to both sides of opening. Stainless steel scuff panels shall be provided on back of cab where the rubber seal on body comes in contact with cab.

A formed metal frame shall be bolted to the front of the body. The body-mounted frame shall be provided where the rubber seal comes into contact with the body. The framework shall be painted to match the body color.

The base of the opening shall be covered with a 3/16" aluminum tread plate full width panel, which will overlap from the cab to body so that the rubber seal can not be damaged.

Full width padded foam cushion head bumpers shall be provided on both sides of opening. Head bumpers shall be covered with matching interior vinyl and bolted to each side of walk-through.

CUT OUT IN REAR CAB WALL

The rear wall of the custom cab shall be cut out 24" wide for walk-thru application. The height of the cutout shall be determined by the cab structure in the rear wall and the roof. The opening shall be completed by the custom cab/chassis manufacturer to assure proper cab structural integrity and completed final interior finish.

SHOP NOTES

Cab Body Opening to be as high as Spartan opening and to be as wide if not wider than the Spartan Opening

INTERIOR SPECIFICATIONS

INTERIOR INSULATION

Following the sheet metal fabrication the roof area, upper exterior walls and the entry door of the apparatus body shall be insulated with 1-1/2" rigid polyurethane foam insulation. This insulation shall be the type that will not absorb moisture, move once in place or deteriorate. Mat type fiberglass or spray in foam insulation is not acceptable.

INTERIOR FINISH

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

The interior of the apparatus body shall have a fully maintenance free and durable finish. The interior finish shall be installed on the ceiling, front wall, and interior side walls from top of exterior compartments to ceiling height.

The exposed interior finish shall be smooth stainless steel, mill or cabinet finish.

SHOP NOTES

All Interior walls to be Stainless - Floor to be tread plate with 4" Kick plate all the way around - Ceiling to be FRP

INTERIOR WALKWAY SIDE WALLS

Walkway side walls from floor level to approximately 4" high shall be aluminum tread plate panels.

INTERIOR WALKWAY FLOOR

The NFPA compliant 3/16" aluminum tread plate walkway floor shall be installed above the barrier, with a 2" high vertical break on each side of the floor panel to form a watertight splash and kickboard along the walkway sides.

The walkway floor area continuously welded at all cross seams to provide a watertight finish, so that a water hose may be used to flush-out walkway area.

INTERIOR SUB-FLOOR

Above the body subframe shall be an isolation sheet that shall prevent outside elements from permeating the full length sound and thermal barrier of 3/4" thick air core plastic. The sheet shall be fabricated from the same type of material as is used in the subframe. The isolation sheet shall be flanged on both sides with a 1" high vertical break.

AIR CONDITIONER - HEATER

One (1) Dometic Penguin, model 641835 low profile, 120 VAC, 60 cycle, single phase air conditioner(s) shall be provided and installed on the body roof. The unit shall be a roof top contemporary contoured integral evaporator/condenser type with built-in heating elements.

Each unit shall be rated at minimum of 13,500 BTU cooling capacity with a heating element rated at 5,600 BTU.

A three-speed fan shall supply a maximum/minimum of 335/250 cfm air flow capacity.

The roof mounted air conditioner shall be approximately 9.5" high x 29" wide x 40" long and weigh approximately 96 pounds.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

STREETSIDE INTERIOR AREA (IS1)

INTERIOR CABINET – ABOVE DECK

There shall be one (1) cabinet(s) provided on interior above the interior deck surface formed by exterior compartment ceilings. Cabinet(s) shall be framed in from the top of the interior deck surface to the ceiling of the walk-in area. Each cabinet shall be approximately 42" wide x 16" deep.

SHOP NOTES

This will be a wide cabinet 82" long - similar to Syracuse Rescue Compartment IC5 - there will be a center piece for strength but the shelves will be full length.

- The above cabinet(s) shall have an open front face (no door).
- Cargo netting of 1-1/2" nylon webbing provided at cabinet opening with easy release automotive style latches at top and sides.
- There shall be two (2) vertically adjustable shelves in each of the above cabinets.

FLIP-UP SEAT

There shall be a bench seat sized for three (3) person/people. The seat bottom cushion shall be notched into exterior side compartments approximately 8". The cushion shall be approximately 3" thick with a wood platform for stability. The cushion shall be covered with Duraware heavy duty fabric material. This seat shall not include seat belts and therefore will not be considered a riding position.

SHOP NOTES

~82" long. This will be a fold up bench (No seat box or under storage required)

CURBSIDE INTERIOR AREA (IC1)

INTERIOR CABINET – ABOVE DECK

There shall be one (1) cabinet(s) provided on interior above the interior deck surface formed by exterior compartment ceilings. Cabinet(s) shall be framed in from the top of the interior deck surface to the ceiling of the walk-in area. Each cabinet shall be approximately (insert actual dimensions).

- There shall be vertically mounted aluminum shelf-trac for specified component installation.
- The above cabinet(s) shall have an open front face (no door).
- Cargo netting of 1-1/2" nylon webbing provided at cabinet opening with easy release automotive style latches at top and sides.
- There shall be two (2) vertically adjustable shelves in each of the above cabinets.
- One (1) 120/240 VAC load center.
SHOP NOTES
This will be on the back wall
- One (1) 12 volt terminal block(s) installed to provide 12 VDC power for equipment supplied by the Hilton-ParmaFire District. Exact location shall be determined at the pre-construction meeting.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

GALLEY REFRIGERATOR

There shall be one (1) Norcold DE-0041R 120VAC/12VDC refrigerator/freezer(s) furnished and installed in the galley. The unit shall be a flush mount style box with Body Manufacturer fabricated custom enclosure. Each refrigerator shall operate from 12 volt or 120 volt power. The built-in dimensions are 30-7/8" high x 23-1/4" wide x 23-1/2" deep.

- There shall be one (1) 120 volt outlet(s) located in the walk-in area of the body.
 - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
 - Outlet(s) shall be powered through the on-board generator system.

LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC

General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125 % of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10 %. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage overcurrent protective devices. Such devices shall be readily accessible and protected against heat in excess of the overcurrent device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- SAE J156, *Fusible Links*
- SAE J553, *Circuit Breakers*
- SAE J554, *Electric Fuses (Cartridge Type)*
- SAE J1888, *High Current Time Lag Electric Fuses*
- SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125 % of maximum current for which the circuit is protected.

Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- 1) The propulsion engine and transmission
- 2) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- 3) The radio(s) at a duty cycle of 10 percent transmit and 90 % receive (for calculation and testing purposes, a default value of 5 A continuous)
- 4) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- 5) The minimum optical warning system, where the apparatus is blocking the right-of way

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

- 6) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- 7) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

12 VOLT DIAGNOSTIC RELAY CONTROL CENTER

The 12 volt power distribution shall be conveniently located with easy access for service. All relays and circuit breakers shall be plug-in type allowing for removal for repairs without necessitating soldering or tools. The sockets mounts for both the relays and circuit breakers shall be of a design that permits the use of standard automotive type components.

The 12 volt distribution panel shall utilize printed circuit boards mounted in high strength enclosure. Each printed circuit board shall be provided with twelve (12) heavy duty independent switching relays. Each relay shall have the ability to be configured either normally open or normally closed and be protected by a 20 amp automatic reset breaker. Each circuit will be provided with a LED for visual diagnostic.

Power distribution panel shall be located in apparatus body within a protected enclosure with removable or hinged cover.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ROCKER SWITCH PANEL

The 12 volt control switch panel shall be supplied and installed by the cab/chassis manufacturer.

ELECTRICAL SYSTEM MANAGER

The chassis shall contain an electrical system manager for:

- Monitoring chassis battery voltage
- Shedding pre-determined electrical circuits
- Sequencing pre-determined electrical circuits
- Automatically controlling chassis engine fast-idle
- Monitor master switch and parking brake applications
- Automatically control warning light modes ("Calling-For" and "Blocking Right of Way")
- Provide low voltage alarm
- Programmable control circuits
- Remote system status indicator panel

System manager shall perform all electrical functions required by current NFPA 1901 Standards.

The electrical system manager shall be supplied and installed by the cab/chassis manufacturer.

BATTERY SYSTEM

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

A master load disconnect switch shall be provided between the starter solenoid(s) and the remainder of the electrical loads on the apparatus. The starter solenoids shall be connected directly to the batteries.

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

A green "battery on" pilot light that is visible from the driver's position shall be provided.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within five (5) seconds.

BATTERY SWITCH

One (1) battery "On/Off" switch in cab located within easy reach of Driver with green "BATTERY ON" pilot light that is visible from the driver's position shall be provided. The switch and pilot light shall be supplied and installed by the cab/chassis manufacturer.

BATTERY SOLENOID

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

INTERIOR LED LIGHTS

Two (2) OnScene Solution model #70156, 10" x 10" x 7/8", 10-30 VDC, surface mount dual red and white LED light(s) with clear lens shall be provided throughout the vehicle. Each light shall be individually switched with a high/low intensity setting switchable at the entry door(s). In addition light(s) will be capable of a five (5) second delay after switching off.

TAIL LIGHTS

Rear body tail lights shall be vertically mounted per Federal Motor Vehicle Safety Standards. The following lights shall be furnished:

- Two (2) Whelen amber LED 600 Series 60A00TAR turn signal lights
- Two (2) Whelen red LED 600 Series 60R00XRR stop/tail lights
- Two (2) Whelen LED 600 Series 60C00WCR maximum intensity back-up lights with clear lens

Each of the lights above shall be mounted in a 6EFLANGE, chrome finish bezel.

MIDSHIP MARKER/TURN SIGNAL

Two (2) Whelen LED midship body clearance marker/turn signal lights (T0A00MAR) shall be installed. There shall be one (1) light on each side of the body, in the wheel well, ahead of the rear axle. Both lights shall have an amber lens and operate with the chassis clearance marker and turn signals.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

MARKER LIGHTS

The apparatus body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) regulations. All body clearance lights shall be Truck-Lite Model 18 LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

Floodlight(s) shall be provided on the front of the cab by the cab/chassis manufacturer. Scene lights shall be provided with a lens or a means for preventing damage from water spray and shall be listed for wet location usage.

Each light shall be wired directly to the 12 VDC electrical system with stranded copper wire. The floodlights shall be protected with circuit breakers rated at the proper amperage and wire size.

SIDE SCENE LIGHTS - LED

There shall be four (4) Whelen Pioneer Plus model PFP2 with dual Panel Super LED lights on the upper body sides. Light quantity shall be divided equally per side. Lights shall be 12 VDC, 12 amp, 150 watt, with 14,000 useable lumens.

Each light shall be mounted in PBA203 mounting bracket, semi recessed into the apparatus body with chrome trim ring housing. The light mounts will provide either a straight out, 0 degree or a 15 degree downward angle.

The lights shall be switched at the 12 volt control panel in the cab.

REAR SCENE LIGHTS - LED

Two (2) Whelen Pioneer Plus model PFP2 with dual panel Super LED lights on the upper rear body, one (1) each side. Lights shall be 12 VDC, 12 amp, 150 watt, with 14,000 useable lumens.

Each light shall be mounted in PBA203 mounting bracket, semi recessed into the apparatus body with chrome trim ring housing. The light mounts will provide either a straight out, 0 degree or a 15 degree downward angle.

SHOP NOTES

Tie Curbside rear scene light into ladder so that when ladder is deployed - that scene light turns off

The lights shall be switched at the 12 volt control panel in the cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

TRAFFIC DIRECTIONAL LIGHT

One (1) Whelen TAL85, 47" eight (8) LED light, traffic directional warning device with 30' control cable shall be located on upper rear body. The control head shall be located in the cab within easy reach of Driver.

The traffic directional light shall be surface mounted on upper rear body.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

WARNING LIGHT PACKAGE

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two separate signaling modes during emergency operations. One mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

UPPER LEVEL OPTICAL WARNING DEVICES

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

ZONE A - FRONT WARNING LIGHTS

The light bar shall be supplied and installed by the cab/chassis manufacturer.

The lightbar shall be separately switched at the 12 volt control panel in the cab.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ZONES B AND D - SIDE WARNING LIGHTS

UPPER REAR CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FCR) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

UPPER FORWARD CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FCR) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

ZONE C - REAR WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FCR) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

LOWER LEVEL OPTICAL WARNING DEVICES

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1220 mm) above level ground for small apparatus.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

ZONE A - FRONT WARNING LIGHTS

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the 12 volt control panel in the cab.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the 12 volt control panel in the cab.

ZONES B AND D - BODY INTERSECTOR LIGHT (BODY WHEELWELL AREA)

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FCR) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FCR) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FCR) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

LINE VOLTAGE ELECTRICAL SYSTEM

HYDRAULIC GENERATOR SYSTEM

A Harrison HydraGen model 30.0MPC-16D, hydraulic driven generator set shall be installed on the vehicle. The generator shall be rated at 30,000 watts at 120/240 VAC, 250/125 amps, single phase. Current frequency shall be stable at 60 hertz.

A means shall be provided to activate the hydraulic generator system.

If the hydraulic generator system is not capable of output as stated on the power source specification label at all engine speeds, an automatic engine speed control system shall be provided.

If the vehicle is equipped with a fire pump driven by the chassis engine, the generator shall be capable of output as stated on the power source specification label with the engine at idle.

GENERATOR MOUNTING

The hydraulic generator module shall contain all system components necessary to comprise a complete hydraulic generating system. The components shall be grouped and assembled into a compact modular unit.

The generator unit shall be modular, packaged with a heavy steel protective frame. All connections to the module (both hydraulic and electrical) shall be easily removable for easy removal of unit from compartment.

Hydraulic oil reservoir and filter shall be easily accessible with adequate clearance to facilitate oil filling and filter changing.

WARRANTY PERIOD

Provided such goods are operated and maintained in accordance with Harrison's written instructions, Harrison warrants that the MPC series hydraulic generators shall be free from defects in material and workmanship for a period of two (2) years or two thousand (2,000) hours, whichever comes first, from the date of delivery to the first purchaser.

HYDRAULIC COMPONENTS

A hydraulic system filter and strainer shall be provided and shall be located in a readily accessible area.

Hydraulic hose shall meet the hydraulic pump manufacturer's recommendations for pressure, size, vacuum, and abrasion resistance. Hydraulic fittings shall meet the hydraulic pump manufacturer's recommendations for pressure, size, and the type of hose used.

Where the hydraulic hose comes into contact with other surfaces, the hose shall be protected from chafing.

SHOP NOTES

Incorporated into Amkus hydraulic system.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

GENERATOR MOUNTING

The generator shall be mounted in an upper roof compartment on rubber vibration isolators. The compartment shall be reinforced where necessary to hold weight of generator. A valve shall be provided on the generator oil drain outlet and piped to underside of generator compartment with flexible hose and plug. The drain shall be located where easily accessible for generator service.

MANUALS AND SCHEMATICS

Two (2) complete manuals on parts list, maintenance, wiring schematics, hydraulic schematics, circuit boards, voltage regulator board and other components shall be provided on delivery.

POWER-TAKE-OFF GENERATOR DRIVE

There shall be a "Hot Shift" power-take-off (PTO) installed on the transmission PTO opening of the chassis. The "Hot Shift" PTO is provided to allow the engagement of the PTO at higher engine RPM speeds. The PTO output shall be connected to the generator through hollow tube type driveline with heavy duty universals.

The engagement of the PTO shall be in the chassis cab with a rocker switch and red pilot light to note engagement of the PTO.

The power supply to the PTO engagement control shall be wired to the parking brake and a neutral position transmission switch to prevent engagement unless the vehicle is stopped and transmission has been placed in neutral.

The installation of the engine, transmission, driven accessories (power takeoffs (PTO), etc.) shall meet the engine and transmission manufacturers' installation recommendations for the service intended.

SHOP NOTES

Verify with Amkus engineering prior to purchasing

Model part number shall be Chelsea 277XMFJPB5XD, 129% Ratio.

GENERATOR MONITORING PANEL

To properly monitor the generator performance and load demand during operation, the generator installation shall be equipped with a full instrument monitor panel.

- Generator frequency in hertz
- Line 1 current in amperes
- Line 2 current in amperes
- Generator voltage in volts

The program shall support the accumulation of elapsed generator hours. Generator hours shall be displayed.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

CIRCUIT BREAKER BOX

There shall be a Newmar 120/240 VAC distribution/breaker panel provided on completed vehicle. All circuit breakers shall be rated to the wire size and load demand.

There shall be color coded LED indicator lights provided to indicate the status of each branch breaker.

Each individual switch and all meters shall be back lit for identification in low light situations.

The panel shall have four (4) meters:

- One (1) to monitor frequency
- One (1) to monitor line voltage
- One (1) to monitor load current (amps)
- One (1) hour meter to register genset run time

Each circuit breaker shall be hydraulic/magnetic trip free style with a manual reset.

The Newmar panel shall also control the manual switch over from shore to generator power.

The entire panel shall be mounted via a piano style hinge that allows the front panel to open for access to the breakers.

LINE VOLTAGE ELECTRICAL SYSTEM

GENERAL REQUIREMENTS

Stability

Any fixed line voltage power source producing alternating current (ac) shall produce electric power at 60 Hz, ± 3 Hz when producing power at all levels between no load and full rated power. Any fixed line voltage power source shall produce electric power at the rated voltage ± 10 percent when producing power at all levels between no load and full rated power.

The maximum voltage supplied to portable equipment shall not exceed 275 volts to ground. Higher voltage shall be permitted only when used to operate fixed wired, permanently mounted equipment on the apparatus.

Conformance with National Electrical Code

All components, equipment, and installation procedures shall conform to *NFPA 70, National Electrical Code*, except where superseded by the requirements of this chapter. Where the requirements of this chapter differ from those in *NFPA 70*, the requirements in this chapter shall apply.

Where available, line voltage electrical system equipment and materials included on the apparatus shall be listed and used only in the manner for which they have been listed. All equipment and materials shall be installed in accordance with the manufacturer's instructions.

Location Ratings

Any equipment used in a dry location shall be listed for dry locations. Any equipment used in a wet location shall be listed for wet locations.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

Any equipment, except a PTO-driven generator, used in an underbody or under chassis location that is subject to road spray shall be either listed as Type 4 or mounted in an enclosure that is listed as Type 4.

If a PTO-driven generator is located in an underbody or under chassis location, the installation shall include a shield to prevent road spray from splashing directly on the generator.

Grounding

Grounding shall be in accordance with 250.34(A) and 250.34(B) of *NFPA 70*. Ungrounded systems shall not be used.

Only stranded or braided copper conductors shall be used for grounding and bonding.

The grounded current-carrying conductor (neutral) shall be insulated from the equipment-grounding conductors and from the equipment enclosures and other grounded parts.

The neutral conductor shall be colored white or gray in accordance with 200.6, "Means of Identifying Grounded Conductors," of *NFPA 70*.

Any bonding screws, straps, or buses in the distribution panel board or in other system components between the neutral and equipment-grounding conductor shall be removed and discarded.

Bonding

The neutral conductor of the power source shall be bonded to the vehicle frame. The neutral bonding connection shall occur only at the power source. In addition to the bonding required for the low voltage return current, each body and each driving or crew compartment enclosure shall be bonded to the vehicle frame by a copper conductor.

The conductor shall have a minimum amperage rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated amperage on the power source specification label.

A single conductor that is sized to meet the low voltage and line voltage requirements shall be permitted to be used.

Ground Fault Circuit Interrupters

In special service vehicles incorporating a lavatory, sink, toilet, shower, or tub, 120 V, 15 or 20 A receptacles within 6 ft (1.8 m) of these fixtures shall have ground fault circuit interrupter (GFCI) protection. GFCIs integrated into outlets or circuit breakers or as stand-alone devices shall be permitted to be used in situations.

Power Source General Requirements

All power source system mechanical and electrical components shall be sized to support the continuous duty nameplate rating of the power source.

The power source shall be shielded from contamination that would prevent the power source from operating within its design specifications.

Power Source Rating

For power sources of 8 kW or larger, the power source manufacturer shall declare the continuous duty rating that the power source can provide when installed on fire apparatus according to the manufacturer's instructions and run at 120°F (49°C) air intake temperature at 2000 ft (600 m) above sea level.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

The rating on the power source specification label shall not exceed the declared rating from the power source manufacturer.

Access shall be provided to permit both routine maintenance and removal of the power source for major servicing. The power source shall be located such that neither it nor its mounting brackets interfere with the routine maintenance of the fire apparatus.

Instrumentation

If the power source is rated at less than 3 kW, a "Power On" indicator shall be provided. If the power source is rated at 3 kW or more but less than 8 kW, a voltmeter shall be provided.

If the power source is rated at 8 kW or more, the following instrumentation shall be provided at an operator's panel:

- Voltmeter
- Current meters for each ungrounded leg
- Frequency (Hz) meter
- Power source hour meter

The instrumentation shall be permanently mounted at an operator's panel. The instruments shall be located in a plane facing the operator. Gauges, switches, or other instruments on this panel shall each have a label to indicate their function.

The instruments and other line voltage equipment and controls shall be protected from mechanical damage and not obstructed by tool mounting or equipment storage.

An instruction plate(s) that provides the operator with the essential power source operating instructions, including the power-up and power-down sequence, shall be permanently attached to the apparatus at any point where such operations can take place.

Operation

Provisions shall be made for placing the generator drive system in operation using controls and switches that are identified and within convenient reach of the operator.

Where the generator is driven by the chassis engine and engine compression brakes or engine exhaust brakes are furnished, they shall be automatically disengaged for generator operations.

Any control device used in the generator system power train between the engine and the generator shall be equipped with a means to prevent unintentional movement of the control device from its set position in the power generation mode.

If there is permanent wiring on the apparatus that is designed to be connected to the power source, a power source specification label that is permanently attached to the apparatus at the operator's control station shall provide the operator with the information required.

The power source, at any load, shall not produce a noise level that exceeds 90 dBA in any driving compartment, crew compartment, or onboard command area with windows and doors closed or at any operator's station on the apparatus.

Power Supply Assembly

The conductors used in the power supply assembly between the output terminals of the power source and the main over current protection device shall not exceed 12 ft (4 m) in length.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

All power supply assembly conductors, including neutral and grounding conductors, shall have an equivalent amperage rating and shall be sized to carry not less than 115 percent of the amperage of the nameplate current rating of the power source.

If the power supply assembly connects to the vibrating part of a generator (not a connection on the base), the conductors shall be flexible cord or other fine-stranded conductors enclosed in metallic or nonmetallic liquid tight flexible conduit rated for wet locations and temperatures not less than 194°F (90°C).

Overcurrent Protection

Manually resettable over current devices shall be installed to protect the line voltage electrical system components.

Power Source Protection

A main over current protection device shall be provided that is either incorporated in the power source or connected to the power source by a power supply assembly.

The size of the main over current protection device shall not exceed 100 percent of the rated amperage stated on the power source specification label or the rating of the next larger available size over current protection device, where so recommended by the power source manufacturer.

If the main over current protection device is subject to road spray, the unit shall be housed in a Type 4-rated enclosure.

Branch Circuit Overcurrent Protection

Over current protection devices shall be provided for each individual circuit and shall be sized at not less than 15 amps in accordance with 240.4, "Protection of Conductors," of *NFPA 70*.

Any panel board shall have a main breaker where the panel has six or more individual branch circuits or the power source is rated 8 kW or larger.

Each over current protection device shall be marked with a label to identify the function of the circuit it protects.

Dedicated circuits shall be provided for any large appliance or device (air conditioning units, large motors, etc.) that requires 60 percent or more of the rated capacity of the circuit to which it is connected, and that circuit shall serve no other purpose.

Panelboards

All fixed power sources shall be hardwired to a permanently mounted panel board unless one of the following conditions exists:

- 1) All line voltage power connections are made through receptacles on the power source and the receptacles are protected by integrated over current devices.
- 2) Only one circuit is hardwired to the power source, which is protected by an integrated over current device.

The panel shall be visible and located so that there is unimpeded access to the panel board controls. All panel boards shall be designed for use in their intended location. The panel(s) shall be protected from mechanical damage, tool mounting, and equipment storage.

Where the power source is 120/240 V and 120 V loads are connected, the apparatus manufacturer or line voltage system installer shall consider load balancing to the extent that it is possible.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

Wiring Methods

Fixed wiring systems shall be limited to the following:

- 1) Metallic or nonmetallic liquid tight flexible conduit rated at temperatures not less than 194°F (90°C) with stranded copper wire rated for wet locations and temperatures not less than 194°F (90°C)
- 2) Type SOW, SOOW, SEOW, or SEOOW flexible cord rated at 600 V and at temperatures not less than 194°F (90°C)

Electrical cord or conduit shall not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring and shall be arranged as follows:

- 1) Separated by a minimum distance of 12 in. (300 mm) from exhaust piping or shielded from such piping
- 2) Separated from fuel lines by a minimum distance of 6 in. (150 mm)

A means shall be provided to allow "flexing" between the driving and crew compartment, the body, and other areas or equipment whose movement would stress the wiring.

Electrical cord or conduit shall be supported within 6 in. (150 mm) of any junction box and at a minimum of every 24 in. (600 mm) of run.

Supports shall be made of nonmetallic materials or of corrosion-resistant or corrosion-protected metal. All supports shall be of a design that does not cut or abrade the conduit or cord and shall be mechanically fastened to the apparatus.

Only fittings and components listed for the type of cord or conduit being installed shall be used.

Splices shall be made only in a listed junction box.

Additional Requirements for Flexible Cord Installations

Where flexible cord is used in any location where it could be damaged, it shall be protected by installation in conduit, enclosures, or guards.

Where flexible cord penetrates a metal surface, rubber or plastic grommets or bushings shall be installed.

Wiring Identification

Each line voltage circuit originating from the main panel board shall be identified.

The wire or circuit identification either shall reference a wiring diagram or wire list or shall indicate the final termination point of the circuit.

Where prewiring for future power sources or devices exists, the un-terminated ends shall be marked with a label showing their wire size and intended function.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

Wiring System Components

Only stranded copper conductors with an insulation rated for temperatures of at least 194°F (90°C) and wet locations shall be used. Conductors in flexible cord shall be sized in accordance with Table 400.5(A) of *NFPA 70*. Conductors used in conduit shall be sized in accordance with 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*. Aluminum or copper-clad aluminum conductors shall not be used.

All boxes shall conform to and be mounted in accordance with Article 314, "Outlet, Device, Pull, and Junction Boxes; Conduit Bodies; Fittings; and Manholes," of *NFPA 70*. All boxes shall be accessible using ordinary hand tools. Boxes shall not be permitted behind welded or pop-riveted panels.

The maximum number of conductors permitted in any box shall be in accordance with 314.16, "Number of Conductors in Outlet, Device, and Junction Boxes, and Conduit Bodies," of *NFPA 70*.

All wiring connections and terminations shall provide a positive mechanical and electrical connection. Connectors shall be installed in accordance with the manufacturer's instructions. Wire nuts or insulation displacement and insulation piercing connectors shall not be used.

Each switch shall indicate the position of its contact points (i.e., open or closed) and shall be rated for the continuous operation of the load being controlled. All switches shall be marked with a label indicating the function of the switch. Circuit breakers used as switches shall be "switch rated" (SWD) or better. Switches shall simultaneously open all associated line voltage conductors. Switching of the neutral conductor alone shall not be permitted.

Line voltage circuits controlled by low voltage circuits shall be wired through properly rated relays in listed enclosures that control all non-grounded current-carrying conductors.

Receptacles and Inlet Devices

Wet and Dry Locations

All wet location receptacle outlets and inlet devices, including those on hardwired, remote power distribution boxes, shall be of the grounding type, provided with a wet location cover, and installed in accordance with Section 406.8, "Receptacles in Damp or Wet Locations," of *NFPA 70*.

All receptacles located in a wet location shall be not less than 24 in. (600 mm) from the ground. Receptacles on off road fire apparatus shall be a minimum of 30 in. (750 mm) from the ground. All receptacles located in a dry location shall be of the grounding type and shall be at least 12 in. (300 mm) above the interior floor height. No receptacle shall be installed in a face-up position.

The face of any wet location receptacle shall be installed in a plane from vertical to not more than 45 degrees off vertical.

Receptacle Label

Each receptacle shall be marked with a label indicating the nominal line voltage (120 volts or 240 volts) and the current rating in amps of the circuit. If the receptacle is DC or other than single phase, that information shall also be marked on the label.

All receptacles and electrical inlet devices shall be listed to UL 498, *Standard for Safety Attachment Plugs and Receptacles*, or other recognized performance standards.

Receptacles used for DC voltages shall be rated for DC service.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

Wiring Schematics

An "As-Built" Wiring diagrams for line voltage systems shall be provided to include the following information;

- 1) Pictorial representations of circuit logic for all electrical components and wiring
- 2) Circuit identification
- 3) Connector pin identification
- 4) Zone location of electrical components
- 5) Safety interlocks
- 6) Alternator–battery power distribution circuits
- 7) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems

120/240 VAC SCENE LIGHTING

COMMAND LIGHT TOWER w/ BACKLIGHT

The apparatus shall be equipped with one (1) all electric Command Light(s). The unit shall not require tapping into vehicle braking system to be operated, eliminating the chance for vehicle brake problems. Hydraulic or pneumatic type floodlights are not acceptable alternatives to the all electric light tower specified.

The light bank shall have six (6) Whelen Pioneer, 120 volt LED lights. Light heads shall be mounted in three (3) pairs, giving two (2) vertical lines of three (3) when the lights are in the upright position.

The lower pair of light heads shall be capable of being rotated about a horizontal axis to provide light down on the vehicle or to the opposite side of the vehicle.

Power for light bank shall be transmitted through power collecting rings thus allowing 360+ degrees rotation in either direction.

Positioning of the light bank shall be accomplished with maintenance free, heavy duty 12 volt linear actuators.

The Command Light assembly shall be all aluminum construction, with stainless steel shafts and bronze bushings for long life and low maintenance.

Light tower shall be controlled with a hand-held umbilical line remote control. Command Light to be equipped with "Auto-Park" automatic nesting feature.

Command Light controls shall feature:

- Three (3) switches, one (1) for each light bank
- One (1) light bank rotation switch
- One (1) switch for elevating lower stage
- One (1) switch for elevating upper stage
- One (1) indicator light to indicate when light bank is out of roof nest position
- One (1) indicator light to indicate when light bank is rotated to proper nest position
- One (1) back light rotation switch

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

Command Light controls shall be located per the itemized compartment list.

The light tower shall have a full extension of 10' - 6" from mounted position and shall extend from nested position to full upright in under 20 seconds.

The overall size of the nested light tower shall be approximately 43" wide x 73" long x 12" high, and weigh approximately 310 lbs.

A flashing warning light shall be provided in cab, indicating when a light tower is not in nested position as required by NFPA 1901. The operational envelope of the mast shall be automatically illuminated whenever the mast assembly is being raised, lowered, or rotated as required by NFPA 1901.

The Command Light shall be covered by a five (5) year limited warranty from defects in materials and workmanship. An operation, maintenance, and parts manual shall be provided with the delivered apparatus.

SHOP NOTES

Lt cost per KS 3/16/2012.

The light tower shall be mounted to roof of the custom cab which shall be reinforced as necessary to support weight of the light tower.

LIGHT TOWER TREE LIMB GUARD

A 1/8" aluminum tread plate tree limb guard shall be provided for the specified light tower.

HYDRAULIC RESCUE SYSTEM

One (1) Amkus "Ultimate" PTO driven HRT system shall be provided and installed on vehicle. System components shall be mounted per manufacturer specifications with proper valving located at each HRT hose reel location.

Intent

It is the purpose and intent of these specifications to describe a chassis mounted central hydraulic drive system designed and engineered specifically for the simultaneous operation of high pressure rescue tool supply circuits and low pressure hydraulic system. Under these specifications and contract, body and tool manufacturers shall provide associated drive components and control systems required for complete operation of such systems.

Any and all parts or accessories not specifically mentioned herein but necessary to furnish a complete unit shall be supplied by the body manufacturer. The following specifications indicate the minimum requirements including all parts, accessories, equipment and safety features, whether mentioned herein or not.

Scope and General Description

The apparatus shall be equipped with an on-board AMKUS Ultimate hydraulic rescue tool system capable of powering specified tool circuits and powering the specified low pressure hydraulic system on an individual or simultaneous basis. The system shall be designed for 10,500 PSI nominal operating pressure and shall be compatible with AMKUS hydraulic oil.

The primary hydraulic pump system shall include, but not be limited to, a power take(PTO), hydraulic pump, hydraulic control valve assembly, reservoir, filtration system, hydraulic oil cooler, and electrical control system. This system shall

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

provide all necessary hydraulic requirements and controls to properly operate the secondary stage high-pressure intensifiers. All system component flow rates and pressure requirements shall be balanced and matched so that volumetric and overall efficiency is maximized at times of simultaneous component operation.

Compliance to NFPA Standards

All system components shall meet or exceed pressure drop, flow velocity, maximum operating pressure and torque safety margin factors as recommended by NFPA, JIC, SAE, and ISO standards organizations. The furnished hydraulic rescue portable and fixed rescue equipment shall be in full compliance to applicable NFPA standards.

Performance

The hydraulic system shall be designed to provide near-constant hydraulic flow up to the maximum operating pressure of 10,500 PSI for each hydraulically independent tool circuit and allowing the low-pressure hydraulic system to operate a full rated capacity. The operating conditions, such as tool force, tool direction, or hose length, of any circuit shall not affect the performance of any of the other circuits or the low-pressure hydraulic system operations .

Variable Engine Speed Compatibility

The fixed hydraulic rescue tool system shall be capable of providing constant output at variable engine speeds. The engine RPM range shall be subject to many variable factors such as other hydraulically driven equipment and fire pump. The exact operating RPM shall be determined prior to installation by engineering and shall be subject to available horsepower, gearing and other critical design factors.

Hydraulic Pumps

The hydraulic pumps shall be AMKUS model K3-80/80-K and shall be driveshaft driven from an OEM provided Chelsea or Muncie hot shift clutch-shift power take-off mounted on side of transmission. The pumps shall be piggy-backed to drive the hydraulic rescue tool system and hydraulic driven generator. The PTO system and installation shall be in compliance with applicable NFPA 1901 standards for similar applications.

A locking toggle PTO switch shall be provided on the cab dash to engage the system. A green indicator light shall be provided adjacent to the switch to indicate system engagement.

The engagement switch and indicating light shall be labeled "HRT SYSTEM". NFPA required interlocks shall be provided to prevent engagement unless the transmission is in neutral, the parking brake is set and the engine is at idle.

Hydraulic Fluid Reservoir

A 35-gallon AMKUS Model HRG-120 hydraulic fluid reservoir shall be provided for the tool system and hydraulic generator system. The reservoir shall be constructed of a minimum of eight (8) gauge steel and a minimum of two internal flow baffles for proper oil circulation. A 3/4" IPT drain boss and plug and clean out/ strainer access cover shall be installed. All return lines shall be discharged hydraulic fluid directly into tank, through filter assembly, not less than six (6) inches below normal operating fluid level. Volumetric capacity of reservoir shall be such as to provide for proper flow velocity, cooling and deaeration of oil. Assembly shall be flex mounted if attached to chassis frame rail.

The reservoir shall also be equipped with dual suctions, combination pressurized fluid filler assembly with removable five hundred micron strainer, combination fluid level, sight gauge and thermometer, cooling system temperature control switch .

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

Hydraulic Fluid Filtration

The hydraulic system shall be equipped with fluid filters on the return lines and high pressure filters on the discharge side of the tool and low-pressure hydraulic system. The hydraulic system shall be provided with suction side strainers. The hydraulic system shall include a spin on cartridge, suction line filter with a minimum of ten (10) micron filtering capacity. Filter flow capacity shall provide for minimum restriction of return flow. Filter assembly shall include an integral 15 PSI bypass valve and be equipped with a filter condition indicating device. Note: a pressure gauge shall not be acceptable. Top mounted inside tank, cartridge insert return filters shall be provided.

The hydraulic filters and strainers shall be equipped with shut-off valves or provisions to prevent loss of hydraulic fluid from the system during changing of such devices. The installer shall provide adequate clearance and accessibility for filter maintenance, as well as hydraulic oil filling and drainage.

Hydraulic Fluid Cooling Systems

A high capacity air to hydraulic fluid coolers shall be installed to cool hydraulic fluid for the tool system and low pressure hydraulic system. A second high capacity air to hydraulic fluid coolers shall be installed to cool hydraulic fluid for the generator system. The cooler systems shall be of sufficient BTU per hour cooling capacity to provide for a maximum system oil temperature of ambient air plus 30 degrees Fahrenheit when all component systems are in simultaneous and continuous operation. Cooling system core shall be of sufficient flow capacity so that pressure drop across cooler headers (inlet to outlet) does not exceed 30 PSI at required flow. Pressure and flow bypass valving shall be provided to prevent over pressurization of assembly.

Integrally mounted 12-volt electric or hydraulic motor driven fan assemblies of required CFM flow capacity shall provide airflow. Mounting of cooling systems requiring airflow supply provided by chassis engine cooling system fan is not acceptable. Fan motor shall be thermostatically controlled to provide for a minimum operating oil temperature of 90 degrees Fahrenheit and maximum as stated. The cooling system shall provide for automatic on/off control of fan with hydraulic system engagement or shutdown (operator control not required).

The cooler flow core and fan drive assemblies shall be independently flex cushion mounted and located on chassis to provide for minimum airflow restriction and shall not be effected by engine heat or exhaust system heat inclusion.

Hydraulic System Plumbing, Hoses, and Fittings

The hydraulic system for the tool system and low pressure hydraulic system shall be equipped with high pressure hydraulic hoses rated at 125% of working pressure of the designed system. The hoses shall be installed with sweep-type low friction loss corrosion resistant female swivel connections. The hoses shall be installed with mechanical and abrasion protection coverings and clamps.

All hydraulic hoses shall meet or exceed the following specifications: Each hose assembly (hose with hose end fittings), except for pump section hose, shall be fitted with JIC 37 degree swivel fittings located at each point of hose and component connection. All pressure line hoses shall comply with SAE 100 R9 specifications. Suction line hose shall be a minimum of 2" nominal inside diameter and comply with requirements under SAE 100 R4. All hydraulic hoses shall be fully installed and ready for operation.

All fittings and adaptors to be of the steel type designed for hydraulic system use. All pipe thread fittings are to be coated with liquid Teflon pipe sealer before assembly. Use of Teflon tape shall not be acceptable. Hydraulic quick check disconnect fittings of the valved type as manufactured by Parker Hannifin Corporation or approved equal shall be installed in the main pressure inlet section and outlet work ports of the valve assembly for diagnostic testing.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

Valve Plate Assembly

The tool system shall be provided with a complete valve plate mounting assembly. The compact assembly shall incorporate valve controls, intensifiers, and requirement equipment. The unit shall include Amkus valve plate assemblies; including tubing fittings check valves to pre-assemble valve, and intensifier skid unit.

Control Valve Assembly

The system shall be provided with a three (3) tool Amkus control valve assembly. All required hydraulic control functions of the intensifier drive circuits shall be supplied within a single multi closed center control valve assembly. Assembly shall be of the modular integrated, screw in cartridge valve/manifold circuit design having stackable control sections for each drive circuit, and shall be designed to provide for additional drive circuit installations with only minor system modification.

The valve assembly shall consist of control sections for intensifier operation. Each section of the assembly shall be fully post pressure compensated to provide proper flow and pressure regulation to each drive circuit independent of the operating requirements of other circuits in simultaneous operation. Each section, when stacked to make a complete assembly, shall provide all pressure inlet, tank return, load sense network, drive circuit porting, and control functions required.

Each of the intensifier control sections shall provide electric solenoid operated on control, automatic pressure sequenced dual set flow controls with fully adjustable flow and pressure settings and intensifier pre-charge control valving. The regulated flow output shall be post (after directional valve) pressure compensated by means of cartridge valve assembly and shall have internal load sense logic network controls required.

High Pressure Intensifier

The secondary oil supply system shall be driven by the primary pump and control valve central hydraulic system and shall consist of three (3) Amkus high pressure oil to oil type intensifiers. Each intensifier shall consist of an axial piston motor drive group with a direct interconnecting axial rotational force plate ramp supplying force and drive requirements of the axial piston high pressure pump group.

The intensification pressure ratio shall be approximately 4:1 and be capable of developing a continuous intensified flow up to a maximum normal operating pressure of 12,500 PSI. The flow transmission factor shall be approximately 0.21:1 with a normal primary system drive flow rate of 7.5 GPM. Intensified (secondary oil supply output) flow rate shall be automatic high/low flow sequence controlled by system pressure/force requirements and shall be fully adjustable to supply a wide range of tool operating cycle speeds and high/low step-down initiation pressures.

Each intensifier shall be a single unitized assembly consisting of the motor drive and high pressure pump piston rotational groups, internal fill and output valving on each pump piston, internal high pressure piston precharge fill network, high pressure system adjustable relief valve, reverse connection protection valving, case over pressurization protection and all required intensifier component parts. Intensifiers of the motor/pump close coupled type or of the reciprocating differential area piston type are not acceptable. This unit shall be designed to supply a smooth, uninterrupted intensified oil flow output for rapid cycle operational speeds and predictable force characteristics of the rescue tool.

Electrical Control System

An Amkus Model EDP (Electric Distribution Panel), 12-volt relay power distribution system, shall provide the control of the three (3) tool hydraulic system electrical valves, auxiliary power system, and components. All relays and control system switching circuits shall be fused and arc suppression protected.

The installer or chassis manufacturer shall provide an electronic controlled variable set constant speed engine governor control system. Unit shall be set to automatically raise and hold constant the engine RPM required for proper hydraulic pump output to ensure intensifier drive output as the number of circuits and their loads change. Control module for governor shall be chassis mounted in a readily accessible location.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue Production Specification

"On-Off" Control

The main control panel shall be equipped with an AMKUS RMC-400, "on-off" switch for tool operation. The switch shall be labeled on instructions intended use and function.

Hydraulic Rescue Tool System Materials and Hoses

The installer of the system shall provide all necessary materials and equipment to comply with installation requirements of the tool manufacturer. The hydraulically driven hydraulic tool system shall be equipped with high pressure hydraulic hoses rated at 125% of working pressure of the designed system. The hoses shall be installed with sweep-type low friction loss corrosion resistant female swivel connections. The hoses shall be installed with mechanical and abrasion protection coverings and clamps.

All hydraulic hoses shall meet or exceed the following specifications:

Each hose assembly (hose and fittings) except for pump section hose, shall be fitted with JIC 37 degree swivel fittings located at each point of hose and component connection.

All pressure line hoses shall comply with SAE 100 R9 specifications.

All hydraulic hoses shall be fully installed and ready for operation.

Hydraulic Tool System Installation and Testing

The on-board hydraulic tool system shall be installed as per rescue tool manufacturers instructions. The system shall be factory tested in compliance to applicable NFPA standards.

SHOP NOTES

Customer supplied.

EQUIPMENT PAYLOAD WEIGHT ALLOWANCE

In compliance with NFPA 1901 standards, the special service vehicle shall be designed for an equipment loading allowance of 8,000 lbs. of Hilton-ParmaFire District provided loose equipment based on a 50,001 - 60,000 pound gross vehicle weight rating.

EQUIPMENT

The following equipment shall be furnished with the completed special service vehicle;

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- There shall be two (2) NFPA approved folding aluminum wheel chocks provided for 44" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20 % grade, with the transmission in neutral, and the parking brake released.
 - The wheel chock(s) shall be shipped loose with the completed apparatus.
- Two (2) Streamlight LiteBox Vehicle Mounting Systems shall be provided. Each flashlight shall be orange in color. Each flashlight shall have a 12 volt DC charger and vehicle mount kit. Each flashlight shall have a 20 watt spotlight style bulb and reflector. The flashlights shall be wired to battery direct unless otherwise specified by the customer.
 - The above specified flashlight(s) shall be shipped loose with the completed unit.

HILTON-PARMA FIRE DISTRICT

SVI #849

Heavy Rescue

Production Specification

REMAINING NFPA MINOR EQUIPMENT BY PURCHASER

All other minor equipment not specified above, but required by NFPA 1901 before the unit is placed in service shall be supplied and mounted by Hilton-ParmaFire District.