

# Life Safety Systems

## SVI Emergency Vehicles

### INTERNET IN-PROCESS SITE

The Bidder shall post and maintain a website where the Life Safety Systems will be able to view digital images of their apparatus as its being manufactured. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of the apparatus.

### CONSTRUCTION DOCUMENTATION

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

- (1) The manufacturers record of apparatus construction details, including the following information:
  - (a) Owner's name and address
  - (b) Apparatus manufacturer, model, and serial number
  - (c) Chassis make, model, and serial number
  - (d) GAWR of front and rear axles and GVWR
  - (e) Front tire size and total rated capacity in pounds (kilograms)
  - (f) Rear tire size and total rated capacity in pounds (kilograms)
  - (g) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
  - (h) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
  - (i) Type of fuel and fuel tank capacity
  - (j) Electrical system voltage and alternator output in amps
  - (k) Battery make, model, and capacity in cold cranking amps (CCA)
  - (l) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
  - (m) Ratios of all driving axles
  - (n) Maximum governed road speed
  - (o) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
  - (p) Pump transmission make, model, serial number, and gear ratio
  - (q) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
  - (r) Water and Foam tank certified capacity in gallons or liters
  - (s) Paint manufacturer and paint number(s)
  - (t) Company name and signature of responsible company representative
  - (u) Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall fire apparatus (with the water tank full but without personnel, equipment, and hose)
- (2) Certification of compliance of the optical warning system
- (3) Siren manufacturer's certification of the siren
- (4) Written load analysis and results of the electrical system performance tests
- (5) Certification of slip resistance of all stepping, standing, and walking surfaces
- (6) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability
- (7) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions
- (8) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications
- (9) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed
- (10) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test
- (11) If the apparatus has a fire pump, the certification of inspection and test for the fire pump
- (12) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test

# Life Safety Systems

## SVI Emergency Vehicles

- (13) When the apparatus is equipped with a water tank, the certification of water tank capacity
- (14) If the apparatus has an aerial device, the certification of inspection and test for the aerial device
- (15) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy and the final installer's certification the foam proportioning system meets this standard
- (16) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests
- (17) If the apparatus has a line voltage power source, the certification of the test for the power source
- (18) If the apparatus is equipped with an air system, air tank certificates, the SCBA fill station certification (see 24.9.7), and the results of the testing of the air system installation
- (19) Any other required manufacturer test data or reports

### **OPERATIONS AND SERVICE DOCUMENTATION**

The contractor shall deliver with the fire apparatus at least two (2) sets of complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof.

The contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- (1) Manufacturer's name and address
- (2) Country of manufacture
- (3) Source for service and technical information
- (4) Parts replacement information
- (5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- (6) Wiring diagrams for low voltage and line voltage systems to include the following information:
  - (a) Pictorial representations of circuit logic for all electrical components and wiring
  - (b) Circuit identification
  - (c) Connector pin identification
  - (d) Zone location of electrical components
  - (e) Safety interlocks
  - (f) Alternator–battery power distribution circuits
  - (g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- (7) Lubrication charts
- (8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- (9) Precautions related to multiple configurations of aerial devices, if applicable
- (10) Instructions regarding the frequency and procedure for recommended maintenance
- (11) Overall apparatus operating instructions
- (12) Safety considerations
- (13) Limitations of use
- (14) Inspection procedures
- (15) Recommended service procedures
- (16) Troubleshooting guide
- (17) Apparatus body, chassis, and other component manufacturer's warranties
- (18) Special data required by this standard
- (19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus

The contractor shall deliver with the apparatus all manufacturers' operations and service documents supplied with components and equipment that are installed or supplied by the contractor.

# Life Safety Systems

## SVI Emergency Vehicles

### **NFPA REQUIRED DOCUMENTATION FORMAT - CD-ROM**

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a CD-ROM. These manuals shall be divided into sections for ease of reference. There shall be two (2) copies of the CD-ROM provided with the completed vehicle.

### **CARRYING CAPACITY**

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The Body Manufacturer shall establish the estimated in-service weight during the design of the vehicle

The estimated in-service weight shall include the following:

- (1) The chassis, body, and tank(s)
- (2) Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
- (3) Full water and other agent tanks
- (4) \*250 lb (114 kg) in each seating position
- (5) Fixed equipment such as pumps, aerial devices, generators, reels, and air systems as installed
- (6) Ground ladders, suction hose, designed hose load in their hose beds and on their reels
- (7) An allowance for miscellaneous equipment that is the greatest of the values for type of vehicle per NFPA 1901, a Purchaser provided list of equipment to be carried with weights, or a Purchaser specified miscellaneous equipment allowance.

The Body Manufacturer shall engineer and design the vehicle such that the completed unit, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

A final Body Manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

		<b>Equipment Allowance</b>		
<b>Apparatus Type</b>	<b>Equipt. Storage Area</b>	<b>Apparatus Size</b>	<b>lb.</b>	<b>kg.</b>
Special Service Fire Apparatus	Minimum of 120 cu ft (3.4 cu mt) of enclosed compartmentation.	15,001 lb to 20,000 lb (7,001 kg to 9,000 kg) GVWR	2,500	1,135

# Life Safety Systems

## SVI Emergency Vehicles

### **TESTING**

#### **ROAD TEST**

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial, or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil, or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil, or grease.

# Life Safety Systems

## SVI Emergency Vehicles

### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (-18°C and 43°C).

### **TEST SEQUENCE**

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for 10 minutes. Failure of any of these tests shall require a repeat of the sequence.

#### **1. RESERVE CAPACITY TEST**

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off, and the minimum continuous electrical load shall be activated for 10 minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

#### **2. ALTERNATOR PERFORMANCE TEST**

##### **TEST AT IDLE**

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

##### **TEST AT FULL LOAD**

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of 2 hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

#### **3. LOW VOLTAGE ALARM TEST**

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system, or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

# Life Safety Systems

## SVI Emergency Vehicles

### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

#### **DOCUMENTATION**

The manufacturer shall deliver the following with the fire apparatus:

- (1) Documentation of the electrical system performance tests
- (2) A written electrical load analysis, including the following:
  - (a) The nameplate rating of the alternator
  - (b) The alternator rating
  - (c) Each of the component loads specified that make up the minimum continuous electrical load
  - (d) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
  - (e) Each individual intermittent electrical load.

# Life Safety Systems

## SVI Emergency Vehicles

### **UL 120/240 VAC CERTIFICATION**

The 120/240 volt electrical system shall be tested and certified by Underwriters Laboratories, to perform as listed below;

The prime mover shall be started from a cold start condition, and the unloaded voltage and frequency shall be recorded.

The line voltage electrical system shall be loaded to at least 100 % of the continuous rated wattage stated on the power source specification label. Testing with a resistive load bank shall be permitted.

The power source shall be operated in the manner specified by the apparatus manufacturer as documented on instruction plates or in operation manuals. The power source shall be operated at a minimum of 100 % of the continuous rated wattage as stated on the power source specification label for a minimum of 2 hours.

The load shall be adjusted to maintain the output wattage at or above the continuous rated wattage during the entire 2-hour test.

The following conditions shall be recorded at least every 1/2 hour during the test:

- (1) The power source output voltage, frequency, and amperes
- (2) The prime mover's oil pressure, water temperature, and transmission temperature, if applicable
- (3) The power source hydraulic fluid temperature, if applicable
- (4) The ambient temperature and power source air inlet temperature

The following conditions shall be recorded once during the test for power sources driven by dedicated auxiliary internal combustion engines:

- (1) Altitude
- (2) Barometric pressure
- (3) Relative humidity

If the generator is driven by the chassis engine and the generator allows for operation at variable speeds, the chassis engine speed shall be reduced to the lowest rpm allowed for generator operation and the voltage and frequency shall be recorded.

The load shall be removed, and the unloaded voltage and frequency shall be recorded.

Voltage shall be maintained within  $\pm 10$  % of the voltage stated on the power source specification label during the entire test. Frequency shall be maintained within  $\pm 3$  Hz of the frequency stated on the power source specification label during the entire test.

The total continuous electrical loads, excluding those loads associated with the equipment defined in NFPA 22.15.7.3.11.2, shall be applied during the testing unless an auxiliary engine drives the power source.

If the apparatus is equipped with a fire pump, the 2-hour certification test of the power source shall be completed with the fire pump pumping at 100 % capacity at 150 psi (1000 kPa) net pump pressure. The test shall be permitted to be run concurrently with the pump certification test.

# Life Safety Systems

## SVI Emergency Vehicles

### **DOCUMENTATION**

The manufacturer shall deliver the following with the fire apparatus:

- (1) The results of each test shall be recorded on an appropriate form and provided with the delivery of the fire apparatus.

### **DIELECTRIC VOLTAGE WITHSTAND TEST**

The line voltage wiring and permanently connected devices and equipment shall be subjected to a dielectric voltage withstand test of 900 volts for 1 minute. The testing shall be performed after all body work has been completed.

The test shall be conducted as follows:

- (1) Isolate the power source from the panel board and disconnect any solid state low voltage components.
- (2) Connect one lead of the dielectric tester to all the hot and neutral buses tied together.
- (3) Connect the other lead to the fire apparatus frame or body.
- (4) Close any switches and circuit breakers in the circuit(s).
- (5) Apply the dielectric voltage for 1 minute in accordance with the testing equipment manufacturer's instructions.

The electrical polarity of all permanently wired equipment, cord reels, and receptacles shall be tested to verify that wiring connections have been properly made.

Electrical continuity shall be verified from the chassis or body to all line voltage electrical enclosures, light housings, motor housings, light poles, switch boxes, and receptacle ground connections that are accessible to fire fighters in normal operations.

If the apparatus is equipped with a transfer switch, it shall be tested to verify operation and that all non grounded conductors are switched.

Electrical light towers, floodlights, motors, fixed appliances, and portable generators shall be operated at their full rating or capacity for 30 minutes to ensure proper operation.

# Life Safety Systems

## SVI Emergency Vehicles

### **WARRANTY**

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material, and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials, and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source, and will deal directly with the Life Safety Systems on all warranty work.

### **GENERAL LIMITED WARRANTY - ONE (1) YEAR**

The vehicle shall be free of defects in material and workmanship for a period of one (1) year or 12,000 miles, whichever occurs first starting thirty (30) days after the original invoice date.

The contractor must be the "single source" coordinator of all warranties on the vehicle.

### **LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS**

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles, whichever occurs first, starting thirty (30) days after the original invoice date.

### **STRUCTURAL WARRANTY - TEN (10) YEARS**

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles whichever occurs first, starting thirty (30) days after the original invoice date.

### **PAINT LIMITED WARRANTY - TEN (10) YEARS**

The body shall be free of bubbling, or peeling as a result of a defect in the method of manufacture for a period of ten (10) years, or 100,000 miles whichever occurs first, starting thirty (30) days after the original invoice date.

### **CONSTRUCTION PERIOD**

The completed vehicle shall be delivered within two hundred (200) days after receipt of a purchase order, or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to Life Safety Systems as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

### **OVERALL HEIGHT**

The overall height (OAH) of the vehicle shall be approximately 110" (9' - 2") from the ground. This measurement shall be taken on flat ground with the tires properly inflated, in the unloaded condition, at that highest point of the vehicle.

### **OVERALL LENGTH**

The overall length (OAL) of the vehicle shall be approximately 330" ( 27' - 6" ).

# Life Safety Systems

## SVI Emergency Vehicles

### **CAB CHASSIS SPECIFICATIONS**

MANUFACTURER: Ford

Model: 2011 F550 Super Duty, 4-Door, 4 x 4

G.V.W.R.: 17,950 lbs.

Wheelbase: 200" Cab to axle: 84"

#### FRONT AXLE:

Rating: 7,000 lbs.

Type: Dana mono beam drive axle, or equal

Shocks: Heavy duty

Front Springs: Single stage, Constant rate, 6,500 lb. capacity

Steering: Power

#### REAR AXLE:

Rating: 13,660 lbs.

Type: Dana or equal full floating with 4.10 ratio, Limited-slip, and Stabilizer bar

Rear Springs: Two-stage, 13,660 lb. capacity

Shocks: Heavy duty

#### BRAKES:

Type: Four-wheel power disc brakes with ABS system

Parking Brake: Cable actuation, foot operated, hand release

#### TIRES AND WHEELS:

Front Tires: (2) LT225/70R 19.5, max traction

Rear Tires: (4) LT225/70R 19.5, max traction

Wheels: 19.5", 10-hole steel disc

Spare: (1) LT225/70R 19.5, all terrain tread, (1) steel disc wheel

# Life Safety Systems

## SVI Emergency Vehicles

### **CHASSIS SPECIFICATIONS**

#### FRAME:

Type: Single channel

Rating: 36,000 PSI steel, 10.1 section modulus

#### ENGINE:

Manufacturer: Ford

Model: 6.7 L Power Stroke Turbo Diesel

Rating: 350 GHP @ 3,300 RPM, 650 GT @ 2,000 RPM

Engine Equipment: Heavy duty dry type air cleaner, fuel filter, horizontal muffler and exhaust, block heater.

#### TRANSMISSION:

Manufacturer: Ford Torque Shift

Type: Automatic

Speeds: 6-speed forward with overdrive  
1-speed reverse

Transfer Case: New Venture or equal, Hi/Lo, manual hubs, with fuel tank skid plate

#### ELECTRICAL:

Alternator: 150 amp

Battery: Dual maintenance free 78 amp/hr, 750 CCA each

#### FUEL TANK:

Size: 40 total gallons

Location: Mid ship mounted aft of rear axle

# Life Safety Systems

## SVI Emergency Vehicles

### **CAB SPECIFICATIONS**

Cab Type: Standard cab with Ambulance Prep Package, XL trim interior

Cab Equipment: Heater and defroster, air conditioning, dome light, sun visor, electric horn, all clearance lights and identification lights required by State and Federal Department of Transportation and all standard equipment, Speed control, Tilt steering wheel, Power door locks, Power windows, AM/FM/CD stereo/clock, Driver/passenger air bag SRS system.

Cab Instruments and Gauge: Fuel, Odometer, Tachometer, Engine oil pressure, Engine water temperature, Volt meter, Auxiliary idle control.

Seats: Front high back cloth bucket seats with 3-point seat belts, Rear bench seat with outer 3-point, and center lap seat belts.

Cab Mirrors: Door mounted telescopic, powered adjustable black camper tow mirrors

Cab Glass: Tinted solar glass

Bumper: Chrome plated

Windshield Wipers: 2-speed electric with washers

Cab Color: Ford Red

Cab Interior Color: Medium Flint

Floor Mats: Rubber floor mats in lieu of carpet

### **CAB/CHASSIS PREPAYMENT**

The specified cab/chassis shall be prepaid by Life Safety Systems within 30 days of invoice. Life Safety Systems understands that if payment is made after 30 days, additional interest charges may apply.

# Life Safety Systems

## SVI Emergency Vehicles

### **CHASSIS MODIFICATIONS**

#### **LUBRICATION AND TIRE DATA PLATE**

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid . . (if applicable)
- Pump priming system fluid, if applicable . . (if applicable)
- Drive axle(s) lubrication fluid
- Air conditioning refrigerant . . (if applicable)
- Air conditioning lubrication oil . . (if applicable)
- Power steering fluid
- Cab tilt mechanism fluid . . (if applicable)
- Transfer case fluid . . (if applicable)
- Equipment rack fluid (if applicable)
- CAFS air compressor system lubricant . . (if applicable)
- Generator system lubricant . . (if applicable)
- Front tire cold pressure
- Rear tire cold pressure
- Maximum tire speed ratings

#### **VEHICLE DATA PLATE**

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the
  - Engine
  - Transmission
  - Air
  - Fuel
- Serial numbers for the
  - Engine
  - Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

#### **OVERALL HEIGHT, LENGTH DATA PLATE (METRIC)**

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in meters, the length of the completed fire apparatus in meters, and the GVWR in kilograms.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

# Life Safety Systems

## SVI Emergency Vehicles

### **ACCIDENT PREVENTION**

There shall be a placard in the cab seating area which reads, "ALL OCCUPANTS MUST BE SEATED AND BELTED WHEN THE APPARATUS IS IN MOTION".

### **PERSONNEL CAPACITY**

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

### **ACCIDENT PREVENTION**

If the rear bumper is 8" deep or more, there shall be a placard on the rear face of the body, in clear sight from the ground, which reads, "WARNING - DO NOT RIDE ON STEPS OR DECK AREAS WHILE THE APPARATUS IS IN MOTION. DEATH OR SERIOUS INJURY MAY RESULT".

### **WEARING HELMET WARNING**

A label stating "DO NOT WEAR HELMET WHILE SEATED" shall be visible from each seating location.

### **FRONT BUMPER**

The front bumper shall be as provided by the cab/chassis manufacturer. No other alternation or modifications are required.

### **RAMSEY WRAP AROUND GRILLE GUARD**

There shall be a Ramsey "Wrap Around" grille guard assembly provided and installed on the front of the chassis cab grille area. The "Grille Guard" shall be black in color and shall have mounting provisions for a Ramsey winch.

### **FRONT MOUNTED WINCH**

The front bumper extension shall be provided with a heavy duty winch installation. The winch shall be a Ramsey RE-12000R, 12 volt electric, 12,000 lb. capacity winch.

The winch shall be equipped with 100' of 3/8" galvanized cable.

A 25' remote control shall be provided with the assembly that permits the Operator to stand at a safe operating distance from the cable and winch.

The cable shall end with a clamp type loop and a drop forged heavy duty hook. The cable shall feed through a full captive type 4-way roller and guide assembly.

### **FRONT TOW PROVISIONS**

The front tow provisions shall be supplied and installed by the cab/chassis manufacturer.

# Life Safety Systems

## SVI Emergency Vehicles

### **EXHAUST**

The exhaust system shall be as provided by cab/chassis manufacturer. No other alternation or modifications are required.

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the apparatus or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

### **RADIO/ANTENNA INSTALLATION**

There shall be one (1) Life Safety Systems supplied radio(s) with antenna installed in the cab within easy reach of driver. The location of radio shall be determined by the Life Safety Systems at the pre-construction meeting.

Radio shall be installed per manufacturers requirements and wired for proper 12 volt power and ground.

### **12 VDC ACCESSORY PLUG**

There shall be two (2) 12 volt accessory plug(s) furnished and installed in center console.

### **DRIVERS SEAT**

The drivers seat shall be either modified to accept an SCBA cylinder or changed to a fixed position SCBA type high back seat with lap/shoulder safety belt and retractor. A cavity type cover will be provided to cover opening when seat is not being used with SCBA cylinder.

No SCBA bracket is required, only an opening to accept cylinder while donned by driver.

### **SEAT BELT COLOR AND MOUNTING**

Section 14.1.3.4 of the NFPA 1901 Standards, 2009 edition, requires all seat belt webbing in cab to be bright red or bright orange in color, and the buckle portion of the seat belt shall be mounted on a rigid or semi rigid stalk such that the buckle remains positioned in an accessible location.

Per Life Safety Systems specification for a commercial chassis, this emergency vehicle may not have the required seat belt webbing colors or buckle in an accessible locatiobn. These belts may not provide visibility to driver that seat belts are on or buckle is easily accessible. This specifications for an emergency fire apparatus for these seat belts shall be non-compliant to NFPA 1901 standards, effective at the time of the bid opening.

# Life Safety Systems

## SVI Emergency Vehicles

### **SEAT BELT WEB LENGTH - COMMERCIAL CAB**

Sections 14.1.3.2 and 14.1.3.3 of the NFPA 1901 standards, 2009 edition, require the effective seat belt web length for a Type 1 lap belt for pelvic restraint to be a minimum of 60", and a Type 2 pelvic and upper torso restraint-style seat belt assembly to be a minimum of 110".

The chassis seat belt web length as supplied by the commercial chassis manufacturer shall be compliant to NFPA Standards 14.1.3.2 and 14.1.3.3.

Per Life Safety Systems specification for a commercial chassis, this emergency vehicle may not have seat belts of this required length. These belts may not provide sufficient length for large firefighters in bunker gear. This specification for an emergency fire apparatus for these seat belts shall be non-compliant to NFPA 1901 standards, effective at the time of the bid opening.

### **SEAT BELT MONITORING SYSTEM - COMMERCIAL CAB**

Section 14.1.3.10 of the NFPA 1901 Standards, 2009 edition, requires that a seat belt warning system be provided. The seat belt warning device is intended to assist the driver or officer in determining whether all occupants are seated and belted before the vehicle is driven.

Per Life Safety Systems specification for a commercial chassis, this emergency vehicle may not have a seat belt monitoring system. Without this device, the driver must manually determine that all occupants are seated and belted before the apparatus is placed in motion. This specification for an emergency fire apparatus for the seat belt monitoring system shall be non-compliant to NFPA 1901 standards, effective at the time of the bid opening.

### **IGNITION KEY**

The ignition key will be attached to steering column or dash with vinyl covered steel cable.

### **SIX (6) - TIRE PRESSURE VISUAL INDICATORS**

Each tire shall be equipped with an Accu-Pressure Safety Cap (or equal) visual indicator that indicates proper tire pressure.

### **CAB TESTING CERTIFICATION**

As per NFPA 14.3.2, cabs on apparatus with a GVWR greater than 26,000 lb. (11,800 kg) shall meet the requirements of one of the following sets of standards:

- 1) European Occupant Protection Standard ECE Regulation No. 29.
- 2) SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks.

A copy of this certification shall be included with the bid.

NOTE: There shall be no exception to any portion of the cab integrity certification requirements. Nonconformance shall lead to immediate rejection of bid.

### **CAB MIRRORS, DRIVER ADJUSTABLE**

Section 14.3.5 of the NFPA 1901 Standards, 2009 edition, requires all primary rear view mirrors used by the driver to be adjustable from the driver's position.

# Life Safety Systems

## SVI Emergency Vehicles

### **CAB PAINT**

The finish paint and color as provided from the cab/chassis manufacturer shall be provided. Cab shall not be repainted.

(Note: Most departments do NOT find that the fleet paint finish from a commercial cab/chassis manufacturer is acceptable. The Body Builder will NOT be responsible for paint quality and finish issues.)

### **REAR CAB WINDOW**

The rear cab window shall be removed and replaced with a welded in steel panel.

### **CAB RUNNING BOARDS**

The chassis shall be provided with running boards each side, below the cab doors. The running boards shall constructed of aluminum 3003H-14 alloy NFPA nonskid compliant tread plate.

### **STAINLESS STEEL WHEEL SIMULATOR KITS**

Front and rear stainless steel wheel simulator kits shall be provided.

The kits shall include American made RealWheels brand mirror finish, 304L grade, non-corrosive stainless steel Universal wheel simulators meeting D.O.T. certification standards. They shall simulate the look of polished aluminum wheels and come complete with stainless steel hub covers and lug nut covers.

All stainless steel simulators shall carry a lifetime warranty.

### **MUDFLAPS**

There shall be rubber mudflaps furnished and installed behind each set of tires.

### **ROAD EMERGENCY SAFETY KIT**

One (1) set of three dual faced triangular warning flares with fold away base complete with storage case per DOT requirements shall be provided with the completed apparatus.

One (1) 2.5 lb. ABC type vehicle fire extinguisher with bracket shall be provided and mounted in the cab or the front streetside compartment.

### **FUEL FILL**

There shall be one (1) Cast Products fuel fill door located on the rear panel of the body. The fill door shall have a spring-loaded hinged door and a permanent label with the text "DIESEL FUEL ONLY".

# Life Safety Systems

## SVI Emergency Vehicles

### **BODY DESIGN**

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the Life Safety Systems to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the Life Safety Systems from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

# Life Safety Systems

## SVI Emergency Vehicles

### **EXTERIOR ALUMINUM BODY**

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 3/16" (.187) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas.

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded continuous to prevent moisture from entering compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

Exterior compartments shall have louvers in lower back wall of compartment for ventilation.

### **ROOF CONSTRUCTION**

The roof shall be integral with the body and shall be all welded construction. The roof of the body shall not be less than 3/16" aluminum 3003H-14 alloy NFPA nonskid compliant tread plate, fully and continuously welded. The roof shall be reinforced with 2" x 2" x 1/4" aluminum tubing running the full width of the body. A 2" rounded radius shall be provided along the body sides.

### **DECON PALLET STORAGE**

An open compartment shall be provided between the recessed light tower and rear of body recessed into roof approximately 8" x 49" wide x 61" deep. A 2" vertical lip shall be provided along floor to hold decon pallets in place (24" x 48" x 1 3/4" each). Eight (8) Austin Hardware #B23SS stainless steel tie-downs will be provided around perimeter of rear recess area to secure pallets into storage area.

# Life Safety Systems

## SVI Emergency Vehicles

### **BODY SUBFRAME**

To assure proper body alignment and clearance, the body subframe shall be constructed directly on the chassis.

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 4" x 1/4" aluminum tubes minimum, the same width as the chassis frame rails. Welded to this tubing shall be crossmembers of 2" x 4" x 1/4" aluminum. Smaller dimension, lighter gauge tubing or angle material subframe shall not be accepted.

These crossmembers shall extend the full width of the body to support the compartments. Crossmembers shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum crossmembers shall be located as necessary to support walkways or heavy equipment.

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.

### **BODY MOUNTING**

For optimum chassis frame and body life, the body subframe shall be fastened to the chassis frame with a minimum of six (6) 1/2" x 2" strap mounts, welded to the body subframe. The straps shall be bolted to the chassis frame work utilizing 1/2" Grade 8 bolts.

### **14" REAR STEP BUMPER**

The full width rear bumper shall be constructed from 2" x 2" x 1/4" aluminum tubing frame and covered with 3/16" NFPA compliant aluminum tread plate. The bumper shall extend from the rear vertical body panel 14" and provide a rear step with a minimum of 1/2" space at body for water drainage.

### **REAR TOW EYES**

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below the apparatus body. The tow eyes shall be fabricated from 3/4" thick steel plate and shall have a black powder coat finish.

### **TRAILER HITCH**

A Class III, 7,500 lbs. weight carrying capacity (gross trailer weight) rear hitch receiver shall be provided below the rear bumper. The receiver shall be attached to the apparatus body frame.

The hitch shall be complete with a 2" square receiver. Without the use of a "weight distribution" ball hitch the Class III receiver shall have a capacity of 5,000 lbs. gross trailer weight.

A label shall be provided in a location in which it is visible to an operator making trailer connections. The label shall state the maximum GVWR and tongue weight of the trailer that can be safely towed with the hitch system.

Two (2) safety chain attachment points shall be provided near the hitch point for hitches designed to use safety chains, each designed with an ultimate strength of not less than the maximum GVWR specified on label.

# Life Safety Systems

## SVI Emergency Vehicles

### **TRAILER ELECTRICAL RECEPTACLE**

For hydraulic brake equipped or electric brake equipped trailer towing capability, a primary electrical receptacle shall be provided near the hitch point and shall match the umbilical cable specified.

### **TRUCK AUXILIARY ELECTRICAL RECEPTACLE**

An auxiliary electrical receptacle shall be provided near the hitch point and shall match the umbilical cable specified for optical warning lights.

### **WHEEL WELL EXTERIOR PANEL**

The exterior panel of the body wheel well enclosure shall be constructed from 1/8" aluminum smooth plate.

### **DIEFORMED BEADED EDGE BODY FENDERS**

A die formed beaded edge shall be provided along the radius of the wheel well opening for a finished appearance.

### **WHEEL WELL LINERS**

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will not accumulate dirt or water.

### **SCBA BOTTLE COMPARTMENTS**

There shall be four (4) SCBA compartments located adjacent to the rear wheels. There shall be two (2) on each side of the apparatus body. Each compartment shall have a Cast Products aluminum door assembly with a positive catch latch. Each compartment shall have a 8" diameter aluminum tube behind the wheel well panel, attached to the Cast Products door assembly. The door shall activate the "Hazard Warning Light" in the cab when not in the closed position.

# Life Safety Systems

## SVI Emergency Vehicles

### **ALUMINUM BODY PAINT SPECIFICATIONS**

#### **BODY PAINT PREPARATION**

After the body and components have been fabricated they shall be disassembled prior to painting so when the vehicle is complete there shall be finish paint beneath the removable components. The body shall be totally removed from chassis during the paint process to insure the entire unit is covered. The body and components shall be metal finished as follows to provide a superior substrate for painting.

The exterior body shall undergo a thorough cleaning process starting with a biodegradable phosphoric acid solution to begin the etching process followed by a complete clear water rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the metal surface for greater film adhesion. If the compartment interior is to be painted the interior shall be acid etched as described above then primed with an epoxy primer and all seams caulked.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

#### **PAINT PROCESS**

The paint process shall follow the strict standards set forth by PPG Industries guidelines. Painters applying PPG products will be PPG Certified Commercial Technicians, and re-certified every two (2) years.

The body shall go through an eight-stage paint process;

1. Clean bare metal using a solvent base wax & grease remover.
2. Finish all exterior body seams as necessary, followed by a thorough sanding of all bare metal to be painted.
3. Re-clean bare metal using a solvent base wax & grease remover.
4. Bare Metal Epoxy Primer Coat - PPG Delfleet® Evolution corrosion resistance epoxy primer to be applied at 1.0-2.0 mills DFT over clean abraded bare metal.
5. Primer Filler Coat - PPG Delfleet® Evolution urethane build primer to achieve total thickness of 3.0-6.0 mills DFT after sanding.
6. Base coat (Color) - PPG Delfleet® Evolution High Solids Polyurethane Base coat. Apply 1.0-3.0 mills DFT of base coat color to achieve full hiding.
7. Clear coat PPG Delfleet® Evolution polyurethane premium quality clear coat with improved mar resistant finish. The clear coat shall be applied to achieve a total dry film thickness of 2.0-3.0 mills.
8. Curing process of the painted body shall go through a force dry/bake cycle process. The painted components shall be baked 180 degrees for 2 hours to achieve a complete coating cure on the finished product.

#### **MACHINE POLISHED**

After the force dry/bake cycle and ample cool down time, the coated surface shall be sanded using 1,000, 1,500, and or 3,000 grit sandpaper to remove surface defects. In the final step, the surface shall be buffed then polished to an extra high gloss smooth finish. Total dry film thickness of paint will average between 8.0-12.0 mils.

#### **PAINT - ENVIRONMENTAL IMPACT**

The contractor shall meet or exceed all current State (his) regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. PPG Delfleet® Evolution paint shall be free of all heavy metal (lead & chromate) components. Paint emissions from sanding and painting shall be filtered and collected. All paint wastes shall be disposed of in an environmentally safe manner. Solvents used in cleanup operations shall be collected, sent off-site for distillation and returned for reuse.

# Life Safety Systems

## SVI Emergency Vehicles

### **PAINT FINISH - SINGLE COLOR**

The body shall be painted with a single color of PPG Delfleet® Evolution paint as described above.

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, an isolation tape, or gasket shall be used to prevent damage to the finish painted surfaces. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nutserts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

Touch-up paint shall be provided with completed vehicle.

- Paint Color: Match cab/chassis supplied paint color.

### **BODY UNDERCOATING**

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

### **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

### **PAINT WARRANTY**

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle.

### **COMPARTMENT INTERIOR FINISH**

The interior of all exterior body compartments shall be a "Maintenance Free" smooth unpainted finish. All body seams shall be finished with a caulk sealant for both appearance and moisture protection.

# Life Safety Systems

## SVI Emergency Vehicles

### **REFLECTIVE STRIPE**

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retroreflection of 10 with observation angle of 0.2 degrees and entrance angle of -4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

### **REFLECTIVE STRIPE - CAB SIDE**

A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side.

The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 6 in. (152 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

- The stripe material shall be 3M Diamond Grade.
- This reflective stripe shall be white in color.

### **REFLECTIVE STRIPE - CAB FRONT**

A reflective stripe shall be affixed to the front of cab. The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 6 in. (152 mm) wide retroreflective stripe(s) shall be affixed to at least 25 percent of the width of the front of the apparatus.

- The stripe material shall be 3M Scotchlite Diamond Grade.
- This reflective stripe shall be white in color.

### **REFLECTIVE STRIPE - CAB DOOR INTERIOR**

Any door of the apparatus designed to allow persons to enter or exit the apparatus shall have at least 96 in.2 (62,000 mm2) of retroreflective material affixed to the inside of the door.

- The stripe material shall be 3M Scotchlite 680.
- This reflective stripe shall be white in color.

# Life Safety Systems

## SVI Emergency Vehicles

### **REFLECTIVE STRIPE - BODY SIDES**

A 6" minimum reflective stripe shall be affixed to the sides of the body.

- The stripe material shall be 3M Diamond Grade.
- This reflective stripe shall be white in color.

The stripe shall extend straight back from the chassis and then, ahead of the rear wheels, it shall form a "Z" and then extend straight back to the rear of the body.

### **CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS**

At least 50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width.

The rear side panels only of the body shall have a Chevron style reflective stripe layout, and cover as much of the rear side panels as possible. Chevron panels shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panels shall have a minimum 10 year warranty for material failure, and colorfastness.

- The stripe material shall be 3M Diamond Grade.

All retroreflective materials required shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

- This reflective Chevron stripe shall alternate red and yellow in color.

# Life Safety Systems

## SVI Emergency Vehicles

### **LETTERING**

The following lettering shall be furnished and installed on the completed unit:

#### **SIDE CAB DOOR LETTERING**

##### **UPPER BODY SIDE LETTERING**

There shall be thirty four (34) 4" high letters furnished and installed on the vehicle.

Lettering shall be; "TERRORISM RESPONSE"

- This reflective lettering shall be yellow in color.

There shall be fifty four (54) 4" high reflective letters furnished and installed on the vehicle.

Lettering shall be; NUCLEAR - BIOLOGICAL - CHEMICAL

- This reflective lettering shall be yellow in color.

##### **REAR BODY LETTERING**

There shall be twenty six (26) 5" high reflective letters furnished and installed on the vehicle.

Lettering shall be; NUCLEAR - "N" is 5 1/2" high; "uclear is 4" high  
BIOLOGICAL - "B" is 5 1/2" high; "iological" is 4" high  
CHEMICAL - "C" is 5 1/2" high; "hemical" is 4" high

- This reflective lettering shall be yellow in color.

There shall be twelve (12) 3" high reflective letters furnished and installed on the vehicle.

"RESPONSE TEAM" - Centered on top of reflective stripe.

- This reflective lettering color shall be black in color.

##### **FRONT OF CAB LETTERING**

# Life Safety Systems

## SVI Emergency Vehicles

### **EXTERIOR COMPARTMENT DOORS**

#### **ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM)**

The apparatus shall be equipped with Robinson Series III roll-up exterior compartment doors. Robinson roll-up doors shall be complete with the following features;

- Doors shall be front roll with drum positioned at upper front portion of compartment to afford maximum clearances and head room for mounting equipment to ceiling of compartment
- There shall be a non-abrasive side brush seals
- Magnetic door ajar system must be integrated in lift bar handle and the retainer block to signal open door. No mechanical switches or switches interior to the compartment shall be used
- Every slat must have interlocking end shoes to prevent slat from moving side-to-side and binding the door
- Between each slat must be a co-extruded PVC inner seal to prevent metal-to-metal contact and to repel moisture. This inner seal is not visible to detract from appearance of door
- Slat are to have interlocking joints with a folding locking flange to provide security and prevent penetration by sharp objects
- Slat to be double-wall extrusion 1.366" high by .315" thick. Exterior surface to be flat and interior surface to be concave to prevent loose equipment from interfering with door operation
- Latch system to be a full width one piece lift bar operable by one (1) hand
- A 2" wide finger pull integrated into the bottom rail extrusion for easy one (1) hand opening and closing
- Clip system that connects the curtain slats to the operator drum which allows for easy tension adjustment without tools
- Each roll-up door shall have a 4" diameter counterbalance operator drum to assist in lifting the door.
- Track shall be one-piece aluminum that has an attaching flange and finishing flange incorporated into its design
- Drip rail will have specially designed seal that prevents the seal from scratching the door
- Bottom rail extrusion must have smooth back to prevent loose equipment from jamming the door
- Bottom rail to have "V" shaped double seal to prevent water and debris from entering the compartment
- Standard replacement parts to be shipped from the United States and available in as little as 48 hours

Each shutter door shall decrease the compartment door frame opening approximately 2.00" in width and approximately 4.50" in height for the bottom section of door assembly.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.

# Life Safety Systems

## SVI Emergency Vehicles

### **BODY HEIGHT MEASUREMENTS**

The vertical body dimensions shall be as follows:

#### **AHEAD OF REAR AXLE**

	<u>Description</u>	<u>Dimension</u>
A	Bottom of Subframe to Top of Body	69.0"
B	Bottom of Subframe to Bottom of Body	18.0"
C	Vertical Door Opening	
	-with roll-up door	60.5"
	-with hinged door	64.5"

#### **ABOVE REAR AXLE**

	<u>Description</u>	<u>Dimension</u>
D	Vertical Door Opening - Above Rear Wheel	
	-with roll-up door	37.0"
	-with hinged door	40.0"

#### **BEHIND REAR AXLE**

	<u>Description</u>	<u>Dimension</u>
E	Bottom of Subframe to Bottom of Body	15.0"
F	Vertical Door Opening	
	-with roll-up door	58.0"
	-with hinged door	62.0"

#### **GENERAL**

	<u>Description</u>	<u>Dimension</u>
G	Bottom or Drip Rail to Top of Body	18.5"

(Dimensions are generic and subject to change during the actual design process)

### **BODY WIDTH DIMENSIONS**

The body shall be 96.0" wide, not including drip rail or non-permanent fixtures. Interior compartment depth dimensions shall be:

<u>Area Description</u>	<u>Dimension</u>
Transverse Area:	91.5"
- Above Top of Subframe	
Compartment Depth:	21.5"
- Below Top of Subframe	
- Ahead of Rear Axle	
Compartment Depth:	20.0"
- Below Top of Subframe	
- Behind the Rear Axle	

(Dimensions are generic and subject to change during the actual design process)

# Life Safety Systems

## SVI Emergency Vehicles

### **STREETSIDE COMPARTMENT - FRONT (S1)**

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have a Robinson roll-up door.

- The roll-up door shall have an un-painted satin aluminum finish on the door slats and the door trim components.
- A keyed cylinder lock shall be provided in the bottom portion of the roll-up door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT COMPONENTS

- There shall be vertically mounted aluminum shelf trac for shelving installation.
- Storage location on floor for portable shower (45" x 45" x 45", Weight: 215 lbs.)
- There shall be one (1) vertical compartment partition dividing compartment into left and right sides bolted in place 47" in from the inside of S1 closed door.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- One (1) vertically mounted OnScene Solutions LED Nightstik.
- The controls for the specified light tower(s).
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in lower compartment.
- The 12 volt electrical distribution panel shall be located in the streetside front lower compartment.

# Life Safety Systems

## SVI Emergency Vehicles

### **STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2)**

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

This compartment shall have a Robinson roll-up door.

- The roll-up door shall have an un-painted satin aluminum finish on the door slats and the door trim components.
- A keyed cylinder lock shall be provided in the bottom portion of the roll-up door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT COMPONENTS

- There shall be vertically mounted aluminum shelf trac for shelving installation.
- There shall be one (1) adjustable shelf/shelves approximately 46" deep.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with a SlideMaster base approximately 94" deep and as wide as the compartment layout or door opening permits, capable of extending out either side of the body located above the level of the chassis frame rails.
- One (1) vertically mounted OnScene Solutions LED Nightstik.

# Life Safety Systems

## SVI Emergency Vehicles

### **STREETSIDE COMPARTMENT - REAR (S3)**

The interior useable compartment width shall be approximately 35.0" wide.

The compartment door opening shall be approximately 28.0" wide.

This compartment shall have a Robinson roll-up door.

- The roll-up door shall have an un-painted satin aluminum finish on the door slats and the door trim components.
- A keyed cylinder lock shall be provided in the bottom portion of the roll-up door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT COMPONENTS

- There shall be vertically mounted aluminum shelf trac for shelving installation.
- There shall be two (2) adjustable shelf/shelves approximately 19" deep.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- One (1) vertically mounted OnScene Solutions LED Nightstik.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in lower compartment.

# Life Safety Systems

## SVI Emergency Vehicles

### **CURBSIDE COMPARTMENT - FRONT (C1)**

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have a Robinson roll-up door.

- The roll-up door shall have an un-painted satin aluminum finish on the door slats and the door trim components.
- A keyed cylinder lock shall be provided in the bottom portion of the roll-up door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT COMPONENTS

- There shall be vertically mounted aluminum shelf trac for shelving installation.
- The water heater will be stored on floor of this compartment. The water heater is 28" W x 36" L x 34" H, and weighs 285 lbs. Wheel stops will be bolted to floor, and tie-down loops will be provided in Uni-Strut tracks on compartment walls.
- An aluminum ramp shall be provided for loading and un-loading the portable hot water heater. Ramp shall be stored along front wall of compartment, and be as long as possible.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- One (1) vertically mounted OnScene Solutions LED Nightstik.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in lower compartment.

# Life Safety Systems

## SVI Emergency Vehicles

### **CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C2)**

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

This compartment shall have a Robinson roll-up door.

- The roll-up door shall have an un-painted satin aluminum finish on the door slats and the door trim components.
- A keyed cylinder lock shall be provided in the bottom portion of the roll-up door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT COMPONENTS

- There shall be vertically mounted aluminum shelf trac for shelving installation.
- There shall be one (1) adjustable shelf/shelves approximately 46" deep.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 94" deep, capable of extending out either side of the body located above the level of the chassis frame rails. (Specified in opposite side compartment.)
- One (1) vertically mounted OnScene Solutions LED Nightstik.

# Life Safety Systems

## SVI Emergency Vehicles

### **CURBSIDE COMPARTMENT - REAR (C3)**

The interior useable compartment width shall be approximately 35.0" wide.

The compartment door opening shall be approximately 28.0" wide.

This compartment shall have a Robinson roll-up door.

- The roll-up door shall have an un-painted satin aluminum finish on the door slats and the door trim components.
- A keyed cylinder lock shall be provided in the bottom portion of the roll-up door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT COMPONENTS

- There shall be vertically mounted aluminum shelf trac for shelving installation.
- There shall be two (2) adjustable shelf/shelves approximately 19" deep.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- One (1) vertically mounted OnScene Solutions LED Nightstik.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in lower compartment.

# Life Safety Systems

## SVI Emergency Vehicles

### **REAR COMPARTMENT - CENTER (R1)**

The rear center compartment shall start at the top of the frame and be as high as the body permits.

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

This compartment shall have a Robinson roll-up door.

- The roll-up door shall have an un-painted satin aluminum finish on the door slats and the door trim components.
- A keyed cylinder lock shall be provided in the bottom portion of the roll-up door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT COMPONENTS

- There shall be vertically mounted aluminum shelf trac for shelving installation.
- There shall be one (1) adjustable shelf/shelves approximately 34" deep on left side of partition.
- There shall be one (1) slide-out smooth aluminum vertical tool board(s) approximately 34" deep and shall be located above the level of the chassis frame rails.
  - The tool board(s) will be bolted to compartment floor.
- There shall be one (1) vertical compartment partition located approximately 18" from left wall of compartment.
- There shall be four (4) Zico ULLH walkaway type SCBA air pack bracket(s) with "V" type clip and strap assembly to hold SCBA in place.
- One (1) Hannay ECR1616-17-18 cable reel(s) capable of storing 150' of 10/4 electric cord. The rewind switch shall be located adjacent to the reel it controls.
  - The electric cord reel shall equipped with 150' of 10/4 SEOW black cable, a molded plastic ball clamp, and a single heavy duty L14-30 twist-lock female plug.
  - One (1) Akron model EJB electrical junction box with yellow powder coat finish. The junction box shall include:
    - A 12" pigtail that terminates in an L14-30 configuration to match the cable on the cord reel. The outlet configuration shall include:
      - One (1) L5-15 single twist lock receptacle
      - One (1) L5-20 single twist lock receptacle
      - One (1) L6-20 single twist lock receptacle
      - One (1) L6-20 single twist lock receptacle
  - One (1) EJB vertical apparatus mounting bracket - treadplate
- Two (2) vertically mounted OnScene Solutions LED Nightstiks.

# Life Safety Systems

## SVI Emergency Vehicles

### **PLASTIC FLOOR AND SHELF TILE**

All compartment floors, shelves, and trays shall be covered with Dri-Dek plastic interlocking grating.

- The plastic floor tile shall be black.
- The plastic edge trim shall be black.

### **REAR BODY HANDRAILS**

There shall be two (2) vertical handrails on the rear of the body. Handrails shall be NFPA compliant 1-1/4" extruded aluminum tubing with chrome plated end stanchions.

### **FOLDING STEP(S)**

There shall be four (4) NFPA approved folding step(s) furnished and installed on front curbside of body for access to roof area. Each step shall be cast aluminum with heavy duty stainless steel spring and textured step surface.

### **CAB FILTRATION/PRESSURIZATION SYSTEM**

A Life Safety System provided Hunter air filtration and pressurization unit shall be installed on the forward roof area of body and connected to rear of cab with 5" diameter flexible hose. The system operates on a 24 volt system and will be connected to the specified power supply system.

The controls for the Hunter filtration system will be located on driver side of the center console.

The cab will be sealed as thoroughly as possible to achieve at least 2 1/2" of water pressure @ 200 cfm. Known areas to be sealed or disabled are as follows;

- Remove vac/blower assembly and seal fresh air intake.
- Disable re-circulation door (remove linkage).
- Disable blower motor (remove fuse).
- Sealant applied around all grommets and pass throughs on fire wall.
- Seal around door handles and mirrors.
- A second bulb seal may be required for all cab doors (no silicone type seal material). Further test to be determined if this is necessary.
- One door extractor on rear wall of cab to be completely sealed. The second extractor location will be used for the inbound air supply (5" dia. hose) from Hunter air unit. Hoses will be protected from possible damage or crushing.

Further tests will be conducted to determine other areas that may need to be sealed.

# Life Safety Systems

## SVI Emergency Vehicles

### **POWER SUPPLY**

The apparatus shall be equipped with one (1) 24 volt power supply to operate the above Hunter system.

All wiring for the power supply installation shall be enclosed in Carflex flexible moisture resistant conduit. All wire shall be stranded copper type, and sized to load and circuit breaker rating.

### **WEATHER STATION**

An LSS supplied Columbia weather station shall be installed. The display shall be located in center cab console or dash area.

Removable telescopic pole mount to be located on front face of body on streetside. A cable connector with cover shall be located adjacent to pole mounting location.

# Life Safety Systems

## SVI Emergency Vehicles

### **COMPARTMENT COMPONENTS DESCRIPTIONS**

All interior compartment components shall be fabricated as follows:

#### **ADJUSTABLE SHELVING HARDWARE**

Adjustable shelving hardware shall be provided indicated in the numbered compartment list.

The shelving hardware shall include a minimum of four (4) aluminum shelf tracs mounted vertically on compartment side walls or vertical partitions. There shall be one (1) cast aluminum shelf bracket per vertical shelf trac to mount each shelf, tray, or adjustable storage module. Shelving hardware shall be of heavy duty quality with unlimited vertical adjustment settings.

#### **ADJUSTABLE SHELF/SHELVES**

Adjustable shelf/shelves shall be provided in exterior compartment as indicated in the numbered compartment list.

Shelves shall be fabricated from 3/16" (.188) aluminum 3003H-14 alloy smooth plate with a 2" vertical flange along the front and rear edges. Shelves shall be designed to be used with flanges either in the upward position to hold various equipment on shelf, or in the downward position for sweep-out shelf surface.

All shelves shall be fully adjustable, from top to bottom of the compartment. There shall be at least four (4) vertical mounting channels and shelving hardware, two (2) each side of compartment. Shelving hardware shall be of heavy duty quality with unlimited vertical adjustment settings.

#### **HEAVY DUTY SLIDE-OUT EQUIPMENT TRAYS - (1,000 LB.CAPACITY)**

Heavy duty slide-out equipment tray(s) shall be provided in exterior compartment as indicated in the numbered compartment list.

Trays shall be fabricated from 3/16" (.188) aluminum 3003H-14 alloy smooth plate. Trays shall be built with a 4" high vertical lip with welded corners to form a box type tray surface. Tray shall be mounted on a SlideMaster 3-rail heavy duty structural steel frame with twelve (12) sealed 1,000 lbs. static load ball bearings. The slide-out tray shall be rated for a maximum 1,000 lbs. evenly distributed load.

The tray shall be locked in its stored position as well as at 50%, and 100% of extension for loading or as a stationary work surface.

#### **SLIDE-OUT TOOL BOARD (SMOOTH ALUMINUM)**

Slide-out tool board(s) shall be provided in the exterior compartment as indicated in the numbered compartment list.

Tool boards shall be fabricated of 3/16" (.188) aluminum 3003H-14 alloy smooth plate with double flange at the outer edge to provide an easy grip handle. The top and bottom of tool board shall be provided with Accuride 502 series slide tracks. The length shall be per numbered compartment list and the extension shall be 100% of the slide length. Slide tracks shall be constructed from formed steel with ball bearings in triple track rails. The board shall be rated for a maximum 200 lbs. evenly distributed load.

Tool board(s) shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.

# Life Safety Systems

## SVI Emergency Vehicles

### **WALKAWAY SCBA BRACKET**

Ziamatic walkaway type SCBA air pack bracket(s) shall be provided and located per the numbered compartment list.

SCBA brackets shall be Ziamatic ULLH type "Load & Lock" type walkaway brackets complying with the current NFPA 1901 standard. Bracket shall consist of backplate, short footplate, two (2) non-mar double-coated seats, and our "Load & Lock" adjustable strap assembly. The backplate and footplate are black thermoplastic coated for years of trouble-free service.

One size fits all U.S. made 30 to 60 minute rated self-contained breathing apparatus.

### **COMPARTMENT LIGHTING**

Each enclosed equipment compartment greater than 4 ft<sup>3</sup> (0.1 m<sup>3</sup>) in volume and having an opening greater than 144 in.<sup>2</sup> (92,900 mm<sup>2</sup>) shall have sufficient compartment lighting to provide a minimum of 2 fc (20 lx) at any location on the floor of the compartment without any shelves, dividers, or equipment in the compartment.

Compartments such as ladder tunnels, pike pole storage tubes, or underbody compartments designed around the volumetric requirements of specific equipment that can be removed without the use of article illumination shall not be required to have compartment lighting.

All compartments shall be equipped with OnScene Nightstik LED lights with the following minimum light requirements;

- Full Height Compartments, 63" Section (42 LED's)
- Wheel well Compartments, 36" Section (24 LED's)
- Rear Rescue Compartment, 63" Section (42 LED's)
- Low Compartments, 18" Section (12 LED's), Vertical
- Low Compartments, 36" Section (24 LED's), Horizontal

The OnScene Nightstik lights shall be rated at 100,000 hours of service and shall be provided with a 5 year free replacement warranty.

# Life Safety Systems

## SVI Emergency Vehicles

### ELECTRIC CORD REEL

Electric cord reel(s) shall be provided in exterior compartment as indicated in the numbered compartment list.

The 240 volt cord reel(s) shall be Hannay with electric rewind, equipped with fully enclosed 45 amp, four (4) conductor collector rings.

The 12 volt reel rewind system shall be directly wired to the chassis battery system with heavy duty stranded copper wire, with guarded finger type rewind button located within easy reach of the operator.

Each reel shall have a Hannay 4-way roller assembly to permit cable to feed directly off the reel and away from compartment. Plastic roller assemblies are not acceptable.

The wiring from the generator system shall be through Carflex electrical weatherproof conduit, with stranded copper wiring. The wiring shall terminate in a sealed conduit box at the reel with mechanical type connectors for quick removal of wiring.

### Cord Reel General Requirements

All permanently mounted cord reels shall be rated for continuous duty and installed to be accessible for removal, cord access, maintenance, and servicing.

The power rewind cord reel spool area shall be visible to the operator during the rewind operation, or the reel spool shall be encapsulated to prevent cord from spooling off the reel.

Rollers or guides shall be provided, where required, to prevent damage to the cord at reel spools or compartment openings.

### Rewind Provision

Power rewind type reels shall have the control in a position where the operator can observe the rewinding operation. If a reel is in an enclosure or out of direct view, the cord entry point to the enclosure shall be visible to the operator of the reel control.

The rewind control or crank shall not be more than 72 in. (1830 mm) above the operator's standing position. The rewind control shall be marked with a label indicating its function and shall be guarded to prevent accidental operation.

### Cord

The reel shall be designed to hold 110 percent of the capacity needed for the intended cord length.

The wire size shall be in accordance with *NFPA 70*, Table 400.5(A), but in no case shall it be smaller than 12AWG. Electrical cord shall be Type SEOW, Type SOOW, or Type STOOW.

A label that indicates the following information shall be provided in a visible location adjacent to any permanently connected reel:

- (1) Current rating
- (2) Current type
- (3) Phase
- (4) Voltage
- (5) Total cord length

# Life Safety Systems

## SVI Emergency Vehicles

### **POWER DISTRIBUTION BOX**

Where a power distribution box is hardwired to the end of a cord that is stored on a fixed cord reel or other fixed storage means, the following requirements shall apply;

The remote power distribution box shall be listed for use in a wet location.

The distribution box shall be as follows:

- (1) Protected from corrosion
- (2) capable of being carried with a gloved hand
- (3) Designed to keep the exterior electrical components above 2 in. (51 mm) of standing water

Inlets, receptacles, circuit breakers, or GFCI devices shall not be mounted on the top surface of the horizontal plane.

Branch circuit breakers shall be installed in the remote power distribution box if the overcurrent device protecting the feed cord to the box is too large to protect the wiring supplying the devices plugged onto the distribution box.

Remote power distribution boxes shall have a light on the box to indicate the power is on. The light shall be visible in a 360 degree plane from a minimum of 200 ft (60 m) in complete darkness. The light shall be mechanically protected to prevent damage.

The hardwired portable cord connection to the box shall have strain relief and meet the intended usage requirements.

### **STEP / GROUND LIGHTS**

Step and ground lights shall be OnScene Solutions 9" LED Nightstik and be placed at any entry door and step where personnel climb on or descend from the apparatus to ground level. OnScene LED lights shall have 6 LED lights per 9" light, and shall be rated at 100,000 hours of service. On Scene Solutions LED lights shall have a 5 year free replacement warranty.

All of the required step and ground lights shall be activated when the parking brake is set.

# Life Safety Systems

## SVI Emergency Vehicles

### LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC

#### General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

#### Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125 % of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10 %. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

# Life Safety Systems

## SVI Emergency Vehicles

### Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage overcurrent protective devices. Such devices shall be readily accessible and protected against heat in excess of the overcurrent device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- (1) SAE J156, *Fusible Links*
- (2) SAE J553, *Circuit Breakers*
- (3) SAE J554, *Electric Fuses (Cartridge Type)*
- (4) SAE J1888, *High Current Time Lag Electric Fuses*
- (5) SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125 % of maximum current for which the circuit is protected.

### Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

# Life Safety Systems

## SVI Emergency Vehicles

### Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- (1) The propulsion engine and transmission
- (2) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- (3) The radio(s) at a duty cycle of 10 percent transmit and 90 % receive (for calculation and testing purposes, a default value of 5 A continuous)
- (4) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- (5) The minimum optical warning system, where the apparatus is blocking the right-of way
- (6) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- (7) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

### Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

### Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

### Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

# Life Safety Systems

## SVI Emergency Vehicles

### **12 VOLT DIAGNOSTIC RELAY CONTROL CENTER**

The 12 volt power distribution shall be conveniently located with easy access for service. All relays and circuit breakers shall be plug-in type allowing for removal for repairs without necessitating soldering or tools. The sockets mounts for both the relays and circuit breakers shall be of a design that permits the use of standard automotive type components.

The 12 volt distribution panel shall utilize printed circuit boards mounted in high strength enclosure. Each printed circuit board shall be provided with twelve (12) heavy duty independent switching relays. Each relay shall have the ability to be configured either normally open or normally closed and be protected by a 20 amp automatic reset breaker. Each circuit will be provided with a LED for visual diagnostic.

Power distribution panel shall be located in apparatus body within a protected enclosure with removable or hinged cover.

- The 12 volt electrical distribution panel shall be located in the streetside front lower compartment.

### **ROCKER SWITCH PANEL**

The control of the 12 volt equipment installed on chassis and body shall be centrally located in the cab. The individual rocker style switches shall be located on a separate electrical panel, complete with backlit name tags describing function of each individual switch. The back lighting shall have two (2) levels of intensity, low level lights activated when the vehicle lights or ignition switch is turned "On", and high level lights activated when individual switch is turned "On". An internally lighted rocker switch shall be furnished to the left of specified emergency lighting switches, and identified as "MASTER EMERGENCY SWITCH".

Switch circuitry shall be on a printed circuit board. The lights shall be solid state type and have a 100,000 hour life span.

The rocker switch panel shall be located in the cab center console for all master switches and emergency light switches.

### **CAB CONSOLE**

A center cab console shall be provided between the Driver's and Officer's seats. Console shall be as large as possible and fabricated of 1/8" smooth aluminum. A textured powder coat paint finish shall be provided for durability and finished appearance.

The rear portion of the console shall be provided with open top storage for notebooks or maps. Two (2) adjustable dividers shall be provided in the storage area. The forward portion of console shall be slanted for mounting of siren head, radio or 12 volt control panel, and etc, with easy access to both Driver and Officer.

The final design of console shall be determined by the Life Safety Systems at the pre-construction meeting.

### **COMPUTER MOUNTING**

A JottoDesk model F700 pedistal computer mount shall be provided adjacent to cab center console for access by passenger position.

# Life Safety Systems

## SVI Emergency Vehicles

### **ELECTRICAL SYSTEM MANAGER**

#### **LOAD MANAGEMENT**

If the total continuous electrical load exceeds the minimum continuous electrical output rating of the installed alternator(s), an automatic electrical load management system shall be required. The minimum continuous electrical loads shall not be subject to automatic load management.

The apparatus 12 volt electrical system shall be provided with a system manager for:

- Monitoring chassis battery voltage
- Shedding pre-determined electrical circuits
- Sequencing pre-determined electrical circuits
- Automatically controlling chassis engine fast-idle
- Monitor master switch and parking brake applications
- Automatically control warning light modes ("Calling-For" and "Blocking Right of Way")
- Provide low voltage alarm
- Programmable control circuits
- Remote system status indicator panel

System manager shall perform all electrical functions required by current NFPA 1901 Standards.

#### **BATTERY MONITORING**

The system manager shall monitor the vehicle battery voltage. When electrical loads exceed the alternator output and the voltage drops, the load manager shall start shutting down electrical outputs. The system shall shut down only as many outputs required to maintain the system voltage. A special indicator to show different states of the electrical system by flashing at rate proportional to the battery discharge.

#### **LOAD SEQUENCING AND SHEDDING**

The system shall be capable of sequentially switching and shedding 12 volt loads. The Master light switch starts the sequential switch when it is turned "On". Likewise turning the Master Switch "Off" will sequentially de-energize the loads.

# Life Safety Systems

## SVI Emergency Vehicles

### **BATTERY SYSTEM**

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

A master load disconnect switch shall be provided between the starter solenoid(s) and the remainder of the electrical loads on the apparatus. The starter solenoids shall be connected directly to the batteries.

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

A green "battery on" pilot light that is visible from the driver's position shall be provided.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within 5 seconds.

### **BATTERY SWITCH**

The chassis ignition key shall activate a heavy duty relay to provide 12 volt battery power to the vehicle. There shall be a green "BATTERY ON" pilot light that is visible from the driver's position.

### **BATTERY SOLENOID**

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

- Two (2) 12 volt terminal block(s) installed to provide 12 VDC power for equipment supplied by the Life Safety Systems. Exact location shall be determined at the pre-construction meeting.

### **ENGINE COMPARTMENT LIGHT**

There shall be one (1) light(s) mounted in the engine compartment with integral switch with a light output of at least 20 candlepower (250 lumens). The engine compartment light(s) shall operate only when the master battery switch is turned "On".

# Life Safety Systems

## SVI Emergency Vehicles

### **MAP LIGHT**

There shall be one (1) 24" goose neck 12 volt map light(s) provided and installed on the officer side dash area.

### **CAB DOME LIGHTS**

There shall be one (1) Truck-Lite model #80354, 7" diameter halogen dome light(s) provided with red lens and switch on light for cab 12 VDC interior lighting.

### **CAB SPOTLIGHT**

There shall be one (1) Collins Dynamics #750 Pulsar hand held spotlight furnished and installed. Location of each spotlight shall be determined by the Life Safety Systems at the pre-construction meeting.

### **CAB HAZARD WARNING LIGHT**

A red flashing or rotating light, located in the driving compartment, shall be illuminated automatically whenever the vehicles parking brake is not fully engaged and any of the following conditions exist:

- Any passenger or equipment compartment door is not closed.
- Any ladder or equipment rack is not in the stowed position.
- Stabilizer system is not in its stowed position.
- Powered light tower is not stowed.
- Any other device permanently attached to the apparatus is open, extended, or deployed in a manner that is likely to cause damage to the apparatus if the apparatus is moved.

Compartments and equipment meeting all of the following conditions shall be permitted to be exempt from being wired to the hazard light:

- The volume is less than or equal to 4 ft<sup>3</sup> (0.1 m<sup>3</sup>).
- The compartment has an opening less than or equal to 144 in.<sup>2</sup> (92,900 mm<sup>2</sup>).
- The open door does not extend sideways beyond the mirrors or up above the top of the fire apparatus.
- All equipment in the compartment is restrained so that nothing can fall out if the door is open while the apparatus is moving.
- Manually raised pole lights with an extension of less than 5 ft (1.5 m).

The hazard light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

An audible alarm shall be provided for the door ajar light.

### **BACK-UP ALARM**

The body manufacturer shall furnish and install one (1) 107 dB(A) electronic back-up alarm. Back-up alarm to actuate automatically when the transmission gear selector is placed in reverse.

# Life Safety Systems

## SVI Emergency Vehicles

### **TAIL LIGHTS**

Rear body tail lights shall be vertically mounted per Federal Motor Vehicle Safety Standards. The following lights shall be furnished:

- Two (2) Whelen amber LED 600 Series 60A00TAR turn signal lights
- Two (2) Whelen red LED 600 Series 60R00XRR stop/tail lights
- Two (2) Whelen halogen 600 Series 60J000CR back-up lights with clear lens
- Two (2) Whelen warning lights as detailed in the warning light section

Two (2) Whelen CAST-4V, 4-light polished aluminum bezels shall be provided, one (1) each side vertically mounted on the rear of the apparatus body for the above tail lights.

### **MIDSHIP MARKER/TURN SIGNAL**

Two (2) Whelen LED midship body clearance marker/turn signal lights (T0A00MAR) shall be installed. There shall be one (1) light on each side of the body, in the wheel well, ahead of the rear axle. Both lights shall have an amber lens and operate with the chassis clearance marker and turn signals.

### **MARKER LIGHTS**

The apparatus body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) regulations. All body clearance lights shall be LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

### **LICENSE PLATE LIGHT**

One (1) Arrow #437 chrome plated license plate light shall be installed on the rear of the apparatus body. License plate light shall be wired to the headlight circuit of chassis. A fastener system shall be provided for license plate installation.

### **ELECTRONIC SIREN**

One (1) Whelen model 295SLSA1 electronic siren control with standard hard wired microphone and user programmable siren tones. Siren to be installed in cab within easy access of Driver.

### **SIREN SPEAKERS**

Two (2) Cast Products Inc. model SAP/D 4302 100 watt siren speaker shall be provided, one (1) streetside and one (1) curbside.

### **SIDE SCENE LIGHTS**

There shall be four (4) Whelen 810 series (10" x 8") surface mounted Opti-Scene halogen lights (810CA0ZR) provided on the upper body. Each light will have a 8-32 degree lens and chrome flange. They will be equally divided between the curbside and streetside.

Two (2) switches shall be provided, one (1) for the streetside scene lights, and one (1) for the curbside scene lights.

The lights shall be switched at the 12 volt control panel in the cab.

# Life Safety Systems

## SVI Emergency Vehicles

### **REAR SCENE LIGHTS**

Two (2) Whelen 900 series (9" x 7") recess mounted Opti-Scene halogen lights (90E000ZR) shall be provided on the upper rear body to light the work area immediately behind the vehicle to a level of at least 3 fc (30 lx) within a 10 ft x 10 ft (3 m x 3 m) square. Each light will have a 8-32 degree gradient lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

### **TRAFFIC DIRECTIONAL LIGHT**

One (1) Whelen TAL85, 47" eight (8) LED light, traffic directional warning device with 30' control cable shall be located on upper rear body. The control head shall be located in the cab within easy reach of Driver.

- The traffic directional light shall be surface mounted on upper rear body.

# Life Safety Systems

## SVI Emergency Vehicles

### **WARNING LIGHT PACKAGE**

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two separate signaling modes during emergency operations. One mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

# Life Safety Systems

## SVI Emergency Vehicles

### UPPER LEVEL OPTICAL WARNING DEVICES

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

### ZONE A - FRONT WARNING LIGHTS

There shall be one (1) Whelen Edge FN60QLED LED 60" lightbar permanently mounted to the cab roof.

The lightbar configuration (streetside to curbside) shall be:

<u>SECTION</u>	<u>INTERNAL COMPONENTS</u>	<u>LENS COLOR</u>
1	One (1) Red Linear LED - Side Facing	Clear
2	One (1) Red Corner LED	Clear
3	Clear Linear LED	Clear
4	Blank	Clear
5	Red Linear LED	Clear
6	Blank	Clear
7	Blank	Clear
8	Red Linear LED	Clear
9	Blank	Clear
10	Clear Linear LED	Clear
11	One (1) Red Corner LED	Clear
12	One (1) Red Linear LED - Side Facing	Clear

All clear lights shall shut down when the parking brake is set to comply with "Blocking" mode requirements as outlined in NFPA 1901.

The lightbar shall be separately switched at the 12 volt control panel in the cab.

# Life Safety Systems

## SVI Emergency Vehicles

### ZONES B AND D - SIDE WARNING LIGHTS

#### UPPER REAR CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

#### UPPER FORWARD CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

### ZONE C - REAR WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

# Life Safety Systems

## SVI Emergency Vehicles

### LOWER LEVEL OPTICAL WARNING DEVICES

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1220 mm) above level ground for small apparatus.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

### ZONE A - FRONT WARNING LIGHTS

There shall be two (2) Whelen 400 series (4" x 3") red Linear Super-LED lights (40R02ZRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

### ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

There shall be two (2) Whelen 400 series (4" x 3") red Linear Super-LED lights (40R02ZRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY WHEELWELL AREA)

There shall be two (2) Whelen 400 series (4" x 3") red Linear Super-LED lights (40R02ZRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Whelen 400 series (4" x 3") red Linear Super-LED lights (40R02ZRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

### ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

# Life Safety Systems

## SVI Emergency Vehicles

### **LINE VOLTAGE ELECTRICAL SYSTEM**

#### **UNDERHOOD GENERATOR SYSTEM - (120 VAC)**

The vehicle shall be equipped with a Mobile Electric Power Solutions (MEPS), 5,000 watt (continuous), 120 volt single phase, 42 amp, 60 Hertz under hood electrical generator.

The generator shall be belt driven from the front of the engine and shall be capable of operating from engine idle to maximum engine RPM without affecting generator operation. It shall be mounted under the hood in the engine compartment with vehicle and engine specific mounting brackets.

The Alternator Control Unit (ACU) shall be mounted in a weather proof location, preferably in unusable space of body compartment. The generator control switch shall be mounted in the cab area near the Driver's seat for turning the generator system on and off. The generator system, when engaged, shall operate normally whether the vehicle is stationary or being driven (reduced load capacity). The generator system shall NOT produce any noise greater than the engine produces during normal operation. The unit shall produce AC current that is plus or minus 0.1 Hertz total frequency deviation, and has less than 3% total harmonic distortion.

The generator system shall NOT require any scheduled maintenance. Portable gasoline, or diesel generators, or hydraulic driven generators will NOT be an acceptable alternative to the MEPS generator system. NO Exceptions.

A voltmeter shall be provided at an operator's panel for any system of this type.

The belt drive system shall be rated to drive the generator or alternator at the nameplate rating.

Mounting Bracket: Mobile Electric Power, Ford

### **MANUALS AND SCHEMATICS**

Two (2) complete manuals on parts list, maintenance, wiring schematics, hydraulic schematics, circuit boards, voltage regulator board and other components shall be provided on delivery.

### **ENGINE SPEED CONTROL**

The apparatus shall be equipped with an InPower ETM, Electronic Throttle Module to maintain a stable cycle output from generator.

An interlock shall prevent the operation of the engine speed auxiliary control device unless the parking brake is engaged and the transmission is in neutral or park, or the parking brake is engaged and the engine is disengaged from the drive wheels.

The engine shall be prevented from regulating its own engine speed during times when engine rpm control is critical for consistent apparatus functions such as generator, water pump, or aerial operation.

# Life Safety Systems

## SVI Emergency Vehicles

### **GENERATOR MONITORING PANEL**

To properly monitor the generator performance and load demand during operation, the generator installation shall be equipped with a full instrument monitor panel.

This unit shall be manufactured by FRC model FROG-D and mounted next to the circuit breaker panel. This generator output display shall consolidate five (5) generator monitoring instruments into one device. The display case shall be waterproof and have dimensions not to exceed 4 1/4" high by 4 1/4" wide by 3 1/4" deep.

The following continuous displays shall be provided with super bright LED digits more than 1/2" high:

- Generator frequency in hertz
- Line 1 current in amperes
- Line 2 current in amperes
- Generator voltage in volts

The program shall support the accumulation of elapsed generator hours. Generator hours shall be displayed at the push of a button.

### **LOADCENTER**

The loadcenter shall be a Cutler Hammer, BR Series, specifically designed for protection and distribution of 120/240 volt AC, such as lighting and small motor branch circuits. The loadcenter enclosure shall be made of 16 gauge galvanized sheet steel. The galvanized coating provides corrosion protection and as such does not require paint. All trims used on the BR Loadcenter shall be chromate sealed and finished with electro disposition epoxy paint (ASA61) which exceeds requirements for outdoor and indoor applications. A combination surface/flush cover with integral door shall be supplied.

The loadcenter shall be UL/CSA listed, **NO EXCEPTIONS** will be allowed.

### **OUTLETS AND CIRCUITS**

The generator and or shore power shall supply the 120/240 volt electrical equipment and outlets outlined below. Proper circuit protection shall be installed as noted:

- Two (2) 240 volt exterior outlets, one (1) each side near rear wheel well area.
  - The outlet receptacles shall be supplied by LSS.
- Two (2) 120 volt exterior outlets, one (1) each side rear of body.
  - The outlet receptacle shall be 20 amp, twist-lock (NEMA L5-20R).

# Life Safety Systems

## SVI Emergency Vehicles

### LINE VOLTAGE ELECTRICAL SYSTEM

#### GENERAL REQUIREMENTS

##### Stability

Any fixed line voltage power source producing alternating current (ac) shall produce electric power at 60 Hz,  $\pm 3$  Hz when producing power at all levels between no load and full rated power. Any fixed line voltage power source shall produce electric power at the rated voltage  $\pm 10$  percent when producing power at all levels between no load and full rated power.

The maximum voltage supplied to portable equipment shall not exceed 275 volts to ground. Higher voltage shall be permitted only when used to operate fixed wired, permanently mounted equipment on the apparatus.

##### Conformance with National Electrical Code

All components, equipment, and installation procedures shall conform to *NFPA 70, National Electrical Code*, except where superseded by the requirements of this chapter. Where the requirements of this chapter differ from those in *NFPA 70*, the requirements in this chapter shall apply.

Where available, line voltage electrical system equipment and materials included on the apparatus shall be listed and used only in the manner for which they have been listed. All equipment and materials shall be installed in accordance with the manufacturer's instructions.

##### Location Ratings

Any equipment used in a dry location shall be listed for dry locations. Any equipment used in a wet location shall be listed for wet locations.

Any equipment, except a PTO-driven generator, used in an underbody or under chassis location that is subject to road spray shall be either listed as Type 4 or mounted in an enclosure that is listed as Type 4.

If a PTO-driven generator is located in an underbody or under chassis location, the installation shall include a shield to prevent road spray from splashing directly on the generator.

##### Grounding

Grounding shall be in accordance with 250.34(A) and 250.34(B) of *NFPA 70*. Ungrounded systems shall not be used.

Only stranded or braided copper conductors shall be used for grounding and bonding.

The grounded current-carrying conductor (neutral) shall be insulated from the equipment-grounding conductors and from the equipment enclosures and other grounded parts.

The neutral conductor shall be colored white or gray in accordance with 200.6, "Means of Identifying Grounded Conductors," of *NFPA 70*.

Any bonding screws, straps, or buses in the distribution panelboard or in other system components between the neutral and equipment-grounding conductor shall be removed and discarded.

# Life Safety Systems

## SVI Emergency Vehicles

### Bonding

The neutral conductor of the power source shall be bonded to the vehicle frame. The neutral bonding connection shall occur only at the power source. In addition to the bonding required for the low voltage return current, each body and each driving or crew compartment enclosure shall be bonded to the vehicle frame by a copper conductor.

The conductor shall have a minimum ampere rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated ampere on the power source specification label.

A single conductor that is sized to meet the low voltage and line voltage requirements shall be permitted to be used.

### Ground Fault Circuit Interrupters

In special service vehicles incorporating a lavatory, sink, toilet, shower, or tub, 120 V, 15 or 20 A receptacles within 6 ft (1.8 m) of these fixtures shall have ground fault circuit interrupter (GFCI) protection. GFCIs integrated into outlets or circuit breakers or as stand-alone devices shall be permitted to be used in situations.

### Power Source General Requirements

All power source system mechanical and electrical components shall be sized to support the continuous duty nameplate rating of the power source.

The power source shall be shielded from contamination that would prevent the power source from operating within its design specifications.

### Power Source Rating

For power sources of 8 kW or larger, the power source manufacturer shall declare the continuous duty rating that the power source can provide when installed on fire apparatus according to the manufacturer's instructions and run at 120°F (49°C) air intake temperature at 2000 ft (600 m) above sea level.

The rating on the power source specification label shall not exceed the declared rating from the power source manufacturer.

Access shall be provided to permit both routine maintenance and removal of the power source for major servicing. The power source shall be located such that neither it nor its mounting brackets interfere with the routine maintenance of the fire apparatus.

# Life Safety Systems

## SVI Emergency Vehicles

### Instrumentation

If the power source is rated at less than 3 kW, a “Power On” indicator shall be provided. If the power source is rated at 3 kW or more but less than 8 kW, a voltmeter shall be provided.

If the power source is rated at 8 kW or more, the following instrumentation shall be provided at an operator’s panel:

- (1) Voltmeter
- (2) Current meters for each ungrounded leg
- (3) Frequency (Hz) meter
- (4) Power source hour meter

The instrumentation shall be permanently mounted at an operator’s panel. The instruments shall be located in a plane facing the operator. Gauges, switches, or other instruments on this panel shall each have a label to indicate their function.

The instruments and other line voltage equipment and controls shall be protected from mechanical damage and not obstructed by tool mounting or equipment storage.

An instruction plate(s) that provides the operator with the essential power source operating instructions, including the power-up and power-down sequence, shall be permanently attached to the apparatus at any point where such operations can take place.

### Operation

Provisions shall be made for placing the generator drive system in operation using controls and switches that are identified and within convenient reach of the operator.

Where the generator is driven by the chassis engine and engine compression brakes or engine exhaust brakes are furnished, they shall be automatically disengaged for generator operations.

Any control device used in the generator system power train between the engine and the generator shall be equipped with a means to prevent unintentional movement of the control device from its set position in the power generation mode.

If there is permanent wiring on the apparatus that is designed to be connected to the power source, a power source specification label that is permanently attached to the apparatus at the operator’s control station shall provide the operator with the information required.

The power source, at any load, shall not produce a noise level that exceeds 90 dBA in any driving compartment, crew compartment, or onboard command area with windows and doors closed or at any operator’s station on the apparatus.

# Life Safety Systems

## SVI Emergency Vehicles

### Power Supply Assembly

The conductors used in the power supply assembly between the output terminals of the power source and the main overcurrent protection device shall not exceed 12 ft (4 m) in length.

All power supply assembly conductors, including neutral and grounding conductors, shall have an equivalent ampere rating and shall be sized to carry not less than 115 percent of the ampere rating of the nameplate current rating of the power source.

If the power supply assembly connects to the vibrating part of a generator (not a connection on the base), the conductors shall be flexible cord or other fine-stranded conductors enclosed in metallic or nonmetallic liquid tight flexible conduit rated for wet locations and temperatures not less than 194°F (90°C).

### Overcurrent Protection

Manually resettable overcurrent devices shall be installed to protect the line voltage electrical system components.

### Power Source Protection

A main overcurrent protection device shall be provided that is either incorporated in the power source or connected to the power source by a power supply assembly.

The size of the main overcurrent protection device shall not exceed 100 percent of the rated ampere rating stated on the power source specification label or the rating of the next larger available size overcurrent protection device, where so recommended by the power source manufacturer.

If the main overcurrent protection device is subject to road spray, the unit shall be housed in a Type 4-rated enclosure.

### Branch Circuit Overcurrent Protection

Overcurrent protection devices shall be provided for each individual circuit and shall be sized at not less than 15 amps in accordance with 240.4, "Protection of Conductors," of *NFPA 70*.

Any panelboard shall have a main breaker where the panel has six or more individual branch circuits or the power source is rated 8 kW or larger.

Each overcurrent protection device shall be marked with a label to identify the function of the circuit it protects.

Dedicated circuits shall be provided for any large appliance or device (air conditioning units, large motors, etc.) that requires 60 percent or more of the rated capacity of the circuit to which it is connected, and that circuit shall serve no other purpose.

# Life Safety Systems

## SVI Emergency Vehicles

### Panelboards

All fixed power sources shall be hardwired to a permanently mounted panelboard unless one of the following conditions exists:

- (1) All line voltage power connections are made through receptacles on the power source and the receptacles are protected by integrated overcurrent devices.
- (2) Only one circuit is hardwired to the power source, which is protected by an integrated overcurrent device.

The panel shall be visible and located so that there is unimpeded access to the panelboard controls. All panelboards shall be designed for use in their intended location. The panel(s) shall be protected from mechanical damage, tool mounting, and equipment storage.

Where the power source is 120/240 V and 120 V loads are connected, the apparatus manufacturer or line voltage system installer shall consider load balancing to the extent that it is possible.

### Wiring Methods

Fixed wiring systems shall be limited to the following:

- (1) Metallic or nonmetallic liquid tight flexible conduit rated at temperatures not less than 194°F (90°C) with stranded copper wire rated for wet locations and temperatures not less than 194°F (90°C)
- (2) Type SOW, SOOW, SEOW, or SEOOW flexible cord rated at 600 V and at temperatures not less than 194°F (90°C)

Electrical cord or conduit shall not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring and shall be arranged as follows:

- (1) Separated by a minimum distance of 12 in. (300 mm) from exhaust piping or shielded from such piping
- (2) Separated from fuel lines by a minimum distance of 6 in. (150 mm)

A means shall be provided to allow "flexing" between the driving and crew compartment, the body, and other areas or equipment whose movement would stress the wiring.

Electrical cord or conduit shall be supported within 6 in. (150 mm) of any junction box and at a minimum of every 24 in. (600 mm) of run.

Supports shall be made of nonmetallic materials or of corrosion-resistant or corrosion-protected metal. All supports shall be of a design that does not cut or abrade the conduit or cord and shall be mechanically fastened to the apparatus.

Only fittings and components listed for the type of cord or conduit being installed shall be used.

Splices shall be made only in a listed junction box.

### Additional Requirements for Flexible Cord Installations

Where flexible cord is used in any location where it could be damaged, it shall be protected by installation in conduit, enclosures, or guards.

Where flexible cord penetrates a metal surface, rubber or plastic grommets or bushings shall be installed.

# Life Safety Systems

## SVI Emergency Vehicles

### Wiring Identification

Each line voltage circuit originating from the main panelboard shall be identified.

The wire or circuit identification either shall reference a wiring diagram or wire list or shall indicate the final termination point of the circuit.

Where prewiring for future power sources or devices exists, the un-terminated ends shall be marked with a label showing their wire size and intended function.

### Wiring System Components

Only stranded copper conductors with an insulation rated for temperatures of at least 194°F (90°C) and wet locations shall be used. Conductors in flexible cord shall be sized in accordance with Table 400.5(A) of *NFPA 70*. Conductors used in conduit shall be sized in accordance with 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*. Aluminum or copper-clad aluminum conductors shall not be used.

All boxes shall conform to and be mounted in accordance with Article 314, "Outlet, Device, Pull, and Junction Boxes; Conduit Bodies; Fittings; and Manholes," of *NFPA 70*. All boxes shall be accessible using ordinary hand tools. Boxes shall not be permitted behind welded or pop-riveted panels.

The maximum number of conductors permitted in any box shall be in accordance with 314.16, "Number of Conductors in Outlet, Device, and Junction Boxes, and Conduit Bodies," of *NFPA 70*.

All wiring connections and terminations shall provide a positive mechanical and electrical connection. Connectors shall be installed in accordance with the manufacturer's instructions. Wire nuts or insulation displacement and insulation piercing connectors shall not be used.

Each switch shall indicate the position of its contact points (i.e., open or closed) and shall be rated for the continuous operation of the load being controlled. All switches shall be marked with a label indicating the function of the switch. Circuit breakers used as switches shall be "switch rated" (SWD) or better. Switches shall simultaneously open all associated line voltage conductors. Switching of the neutral conductor alone shall not be permitted.

Line voltage circuits controlled by low voltage circuits shall be wired through properly rated relays in listed enclosures that control all non-grounded current-carrying conductors.

### Receptacles and Inlet Devices

#### Wet and Dry Locations

All wet location receptacle outlets and inlet devices, including those on hardwired, remote power distribution boxes, shall be of the grounding type, provided with a wet location cover, and installed in accordance with Section 406.8, "Receptacles in Damp or Wet Locations," of *NFPA 70*.

All receptacles located in a wet location shall be not less than 24 in. (600 mm) from the ground. Receptacles on off road fire apparatus shall be a minimum of 30 in. (750 mm) from the ground. All receptacles located in a dry location shall be of the grounding type and shall be at least 12 in. (300 mm) above the interior floor height. No receptacle shall be installed in a face-up position.

The face of any wet location receptacle shall be installed in a plane from vertical to not more than 45 degrees off vertical.

# Life Safety Systems

## SVI Emergency Vehicles

### Receptacle Label

Each receptacle shall be marked with a label indicating the nominal line voltage (120 volts or 240 volts) and the current rating in amps of the circuit. If the receptacle is DC or other than single phase, that information shall also be marked on the label.

All receptacles and electrical inlet devices shall be listed to UL 498, *Standard for Safety Attachment Plugs and Receptacles*, or other recognized performance standards.

Receptacles used for DC voltages shall be rated for DC service.

### Wiring Schematics

An "As-Built" Wiring diagrams for line voltage systems shall be provided to include the following information;

- (a) Pictorial representations of circuit logic for all electrical components and wiring
- (b) Circuit identification
- (c) Connector pin identification
- (d) Zone location of electrical components
- (e) Safety interlocks
- (f) Alternator–battery power distribution circuits
- (g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems

# Life Safety Systems

## SVI Emergency Vehicles

### **120/240 VAC SCENE LIGHTING**

Two (2) Fire Research Focus, model FCA656-S75, tripod telescopic light shall be provided. The light pole shall be anodized aluminum and have a knurled twist lock mechanism to secure the extension pole in position. The extension pole shall extend 28" and rotate 360 degrees. An internal brake shall slow the extension pole during lowering. The outer pole shall be a grooved aluminum extrusion. The folding legs shall be anodized aluminum tubing with plastic endcaps. The fully extended tripod system shall exceed a height of 8' and be less than 5' when collapsed. Wiring shall extend from the pole bottom with a 4' retractile cord.

The lamphead shall have one (1) quartz halogen 750 watt 120 volt bulb. The bulb shall draw 6.3 amps and generate 19,600 lumens. The bulb shall be accessible through the front. The lamphead shall direct 50 percent of the light onto the action area while providing 50 percent to illuminate the working area. The lamphead angle of elevation shall be adjustable at a pivot in the mounting arm and the position locked with a round knurled locking knob. The lamphead shall incorporate heat-dissipating fins and be no more than 5" deep by 3 3/8" high by 10" wide. Scene lights shall be provided with a lens or a means for preventing damage from water spray and shall be listed for wet location usage.

A weatherproof on-off toggle switch shall be mounted in a switchbox below the lamphead. A wire guard shall be furnished to protect the lamphead glass.

A tripod truck mount bracket set shall be provided for each light. Each set shall include a lower base plate, an upper lock with a quick release spring loaded locking pin, and a shim set.

# Life Safety Systems

## SVI Emergency Vehicles

### **COMMAND LIGHT - KNIGHT TOWER**

The apparatus shall be equipped with one (1) all-electric floodlight tower(s). The unit shall not require tapping into vehicle braking system to be operated, eliminating the chance for vehicle brake problems. Hydraulic or pneumatic type floodlights are not acceptable alternatives to the all-electric light tower specified. NO EXCEPTIONS.

The light tower shall have six (6) weatherproof, 500 watt, 120 volt quartz halogen lights. Light heads shall be mounted in three (3) pairs, giving two (2) vertical lines of three (3) when the lights are in the upright position. The light tower shall have slip-rings for a full 360 degree rotation and capable of rotating either direction from a stowed position, NO EXCEPTIONS.

The light tower shall be capable of overhanging the side or back of the vehicle (depending on mounting location) to provide maximum illumination and a warning area adjacent to the vehicle, NO EXCEPTIONS. Positioning of the light bank shall be accomplished with maintenance free, heavy duty 12 volt linear actuators.

The light tower shall be all aluminum construction, with stainless steel shafts and bronze bushings for long life and low maintenance.

Light tower shall be controlled with a hand-held umbilical line remote control. The storage station for the remote control unit shall be equipped with a button to activate the "Auto-Park" automatic nesting feature.

Command Light controls shall include:

- Three (3) switches, one (1) for each light bank.
- One (1) light bank rotation switch.
- One (1) switch for elevating lower stage.
- One (1) switch for elevating upper stage.
- One (1) light to indicate when light bank is out of roof nest position.
- One (1) light to indicate when light bank is rotated to proper nest position.
- One (1) "On/Off" switch for the top mounted strobe (optional)

The controls shall be located per the itemized compartment list.

The light tower shall have a full extension over 7' from mounted position and extend from nest position to full upright in 15 seconds. The overall size of nested light tower shall be approximately 23" wide x 47" long x 11 3/4" high, and weight approximately 120 lbs.

A flashing warning light shall be provided in cab, indicating when a light tower is not in nested position as required by NFPA 1901. The operational envelope of the mast shall be automatically illuminated whenever the mast assembly is being raised, lowered, or rotated as required by NFPA 1901.

The Command Light shall be covered by a one (1) year limited warranty from defects in materials and workmanship. An operation, maintenance, and parts manual shall be provided with the delivered apparatus.

The floodlight tower shall have a strobe indicator located on the top of the upper section.

The lens color for the strobe light shall be green.

The specified light tower(s) shall be recessed into the roof of the apparatus body. The recessed area shall have two (2) water drain holes (in opposite corners) with flexible 1" diameter hose routed to the area below the body.

# Life Safety Systems

## SVI Emergency Vehicles

### **EQUIPMENT PAYLOAD WEIGHT ALLOWANCE**

In compliance with NFPA 1901 standards, the special service vehicle shall be designed for an equipment loading allowance of 2,500 lbs. of Life Safety Systems provided loose equipment based on a 15,001 - 20,000 pound gross vehicle weight rating.

### **EQUIPMENT**

The following equipment shall be furnished with the completed special service vehicle;

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- There shall be two (2) NFPA approved aluminum wheel chocks provided for 32" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20 % grade, with the transmission in neutral, and the parking brake released.
  - The wheel chock(s) shall be mounted on the apparatus, location as per the Life Safety Systems.

### **REMAINING NFPA MINOR EQUIPMENT BY PURCHASER**

All other minor equipment not specified above, but required by NFPA 1901 before the unit is placed in service shall be supplied and mounted by Life Safety Systems.



# Change Order #1

Customer: Life Safety Systems  
 Dealer: Life Safety Systems

Date: 5/25/2010  
 SVI #: 783

## Change Order Description Pre Paint Changes

**Based on the following changes/modifications to the specification, ( 14 ) days will be added to the quoted delivery time.**

Review each item for change description and price. Check the appropriate response for each item, sign and date form at bottom, and fax completed form to SVI Trucks at (970) 667-3343.

Prices shown above are per unit (ea truck) prices unless otherwise noted. All work to be performed under same terms and conditions as specified in original contract unless otherwise stipulated. Change Order documentation will override specification in cases of conflicting documentation.

Item #	Spec Section	Item Description	Unit Cost (In US \$)	Change Accepted?
1	Compartment RC1	Delete Sliding Tool Board With Zico Airpack Brackets	\$0.00	<input checked="" type="checkbox"/> YES
2	Compartment RC1	Delete Vertical Partion Wall	\$0.00	<input checked="" type="checkbox"/> YES
3	Compartment RC1	Add vertical shelf trac to the curbside wall	\$0.00	<input checked="" type="checkbox"/> YES
4	Compartment RC1	Delete the (2) Half width Shelves in this compartment and add (2) full width adjustable shelves	\$317.00	<input checked="" type="checkbox"/> YES
5	Exterior Comaprment	Install pinned LIP ANTI-ROLL feature in all compartment locations. Make it a removable system Total of (7).	\$677.00	<input checked="" type="checkbox"/> YES
6	Compartment s S1/C1	RAMP. Install index pins to eliminate potential for ramp falling. Use same index pin holes for equipment lip in this compartment.	\$0.00	<input checked="" type="checkbox"/> YES
7	Body	Install two (2) grab handles on top of front of body to assist at ladder. One on front of body to right, and one on curbside. Keep path clear so a person can climb ladder, access roof.	\$310.00	<input checked="" type="checkbox"/> YES
8	Cab	Delete SCBA Driers Seat - Leave the Seat Stock Seat	(\$1,107.00)	<input checked="" type="checkbox"/> YES
9	Cab/Body	Make bottom and perhaps second lowest ladder step smaller. Must be able to clear door when opened.	\$0.00	<input checked="" type="checkbox"/> YES
Change Order Total:			<b>\$197.00</b>	<input checked="" type="checkbox"/>

Authorized Customer Signature:	<div style="border: 2px solid green; border-radius: 15px; padding: 10px; background-color: #e0f0e0;"> <p><b>APPROVED</b>  <i>By Ryan Wells at 11:50 am, Jun 23, 2010</i></p> </div>	Date Accepted:
Authorized Dealer Signature:		Date Accepted:



# Change Order #2

Customer: **Life Safety Systems**  
 Dealer: **Life Safety Systems**

Date: 6/22/2010  
 SVI #: **783**

**Change Order Description**  
**Generator Change**

**Based on the following changes/modifications to the specification, ( 10 ) days will be added to the quoted delivery time.**

Review each item for change description and price. Check the appropriate response for each item, sign and date form at bottom, and fax completed form to SVI Trucks at (970) 667-3343.

Prices shown above are per unit (ea truck) prices unless otherwise noted. All work to be performed under same terms and conditions as specified in original contract unless otherwise stipulated. Change Order documentation will override specification in cases of conflicting documentation.

Item #	Spec Section	Item Description	Unit Cost (In US \$)	Change Accepted?
<b>1</b>	120 Volt System	Change Genertao from belt Driven to an Onan CMQD 5000 Diesel Generator	\$0.00	<input checked="" type="checkbox"/> <b>YES</b>
Change Order Total:			<b>\$0.00</b>	<input checked="" type="checkbox"/>

Authorized Customer Signature:	Date Accepted:
<div style="border: 1px solid green; border-radius: 10px; padding: 10px; display: inline-block;"> <p align="center"><b>APPROVED</b>  <i>By Ryan Wells at 11:51 am, Jun 23, 2010</i></p> </div>	
Authorized Dealer Signature:	Date Accepted:
Authorized SVI Signature:	Date Accepted:

*This change order is not valid until signed by all parties listed above.*