

Surprise Fire Dept  
Surprise, AZ

# **SURPRISE FIRE DEPT**

**Surprise, AZ**

**Job #929**

**Production Specs  
For Ladder Tender**

# Surprise Fire Dept

## Surprise, AZ

### Table of Contents

<b>SURPRISE FIRE DEPT</b>	1
<b>Surprise, AZ</b>	1
<b>Job #929</b>	1
<b>Production Specs</b>	1
<b>For Ladder Tender</b>	1
<b>LIABILITY INSURANCE</b>	9
<b>INTERNET IN-PROCESS SITE</b>	9
The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C).	10
<b>ROADABILITY</b>	10
<b>SERVICEABILITY</b>	10
<b>CONSTRUCTION DOCUMENTATION</b>	10
<b>OPERATIONS AND SERVICE DOCUMENTATION</b>	11
<b>NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE</b>	12
<b>STATEMENT OF EXCEPTIONS</b>	12
<b>CARRYING CAPACITY</b>	13
<b>TESTING</b>	14
<b>ROAD TEST</b>	14
<b>LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST</b>	14
<b>TEST SEQUENCE</b>	14
<b>1. RESERVE CAPACITY TEST</b>	14
<b>2. ALTERNATOR PERFORMANCE TEST</b>	15
<b>TEST AT IDLE</b>	15
<b>TEST AT FULL LOAD</b>	15
<b>3. LOW VOLTAGE ALARM TEST</b>	15
<b>LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST</b>	15
<b>DOCUMENTATION</b>	15

# Surprise Fire Dept

## Surprise, AZ

<b>UL 120/240 VAC CERTIFICATION .....</b>	<b>16</b>
<b>DIELECTRIC VOLTAGE WITHSTAND TEST .....</b>	<b>17</b>
<b>MANUFACTURER PUMP CERTIFICATION .....</b>	<b>17</b>
<b>PERFORMANCE BOND .....</b>	<b>18</b>
<b>WARRANTY .....</b>	<b>18</b>
<b>GENERAL LIMITED WARRANTY - TWO (2) YEARS .....</b>	<b>19</b>
<b>LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS .....</b>	<b>19</b>
<b>STRUCTURAL WARRANTY - TEN (10) YEARS .....</b>	<b>19</b>
<b>UNDERCOAT WARRANTY .....</b>	<b>19</b>
<b>PAINT LIMITED WARRANTY - TEN (10) YEARS .....</b>	<b>19</b>
<b>GRAPHICS LIMITED WARRANTY .....</b>	<b>19</b>
<b>WATEROUS FIVE YEAR PUMP WARRANTY .....</b>	<b>19</b>
<b>STAINLESS STEEL PLUMBING WARRANTY .....</b>	<b>19</b>
<b>CONSTRUCTION PERIOD .....</b>	<b>20</b>
<b>OVERALL HEIGHT REQUIREMENT .....</b>	<b>20</b>
<b>OVERALL LENGTH REQUIREMENT .....</b>	<b>20</b>
<b>OVERALL WIDTH .....</b>	<b>20</b>
<b>PRE-CONSTRUCTION CONFERENCE .....</b>	<b>20</b>
<b>EQUIPMENT MOUNTING CONFERENCE .....</b>	<b>20</b>
<b>FINAL INSPECTION CONFERENCE .....</b>	<b>21</b>
<b>DELIVERY AND DEMONSTRATION .....</b>	<b>21</b>
<b>CAB/CHASSIS PREPAYMENT .....</b>	<b>71</b>
<b>CHASSIS MODIFICATIONS .....</b>	<b>71</b>
<b>LUBRICATION AND TIRE DATA PLATE .....</b>	<b>71</b>
<b>VEHICLE DATA PLATE .....</b>	<b>71</b>
<b>OVERALL HEIGHT, LENGTH DATA PLATE (US) .....</b>	<b>72</b>
A final stage manufacturer vehicle certification label shall be provided and installed in the driver cab door jamb area.....	72
<b>FRONT BUMPER .....</b>	<b>73</b>

# Surprise Fire Dept

## Surprise, AZ

BUMPER GRAVEL SHIELD .....	73
AIR HORN(S) .....	73
MOTOR DRIVEN SIREN .....	73
SIREN ACTIVATION .....	73
AIR HORN / ELECTRIC HORN SWITCH .....	73
FRONT TOW PROVISIONS .....	73
EXHAUST DIVERTER .....	74
DOCKING STATION INSTALLATION .....	74
12 VDC FUSE BLOCK .....	74
FIVE (5) POSITION ANTENNA RAIL .....	74
PAINT ANTENNA RAIL .....	75
MAP BOX.....	75
HUB AND NUT COVERS .....	77
MUDFLAPS .....	77
ELECTRIC DOOR LOCK INTERFACE .....	77
ROAD EMERGENCY SAFETY KIT.....	77
FUEL FILL.....	77
FUEL FILL.....	78
BODY DESIGN.....	78
EXTERIOR ALUMINUM BODY.....	78
ROOF CONSTRUCTION.....	79
BODY SUBFRAME .....	79
BODY MOUNTING .....	80
14" REAR STEP BUMPER.....	80
REAR TOW EYES .....	80
GROUND LIGHTS .....	80
WHEEL WELL EXTERIOR PANEL.....	81
STAINLESS STEEL BODY FENDERS .....	81
WHEEL WELL LINERS.....	81

# Surprise Fire Dept

## Surprise, AZ

SCBA CYLINDER COMPARTMENTS .....	81
BODY UNDERCOATING .....	82
UNDERCOAT WARRANTY .....	82
PAINT WARRANTY .....	82
COMPARTMENT INTERIOR FINISH .....	82
REFLECTIVE STRIPE REQUIREMENTS .....	82
REFLECTIVE STRIPE - CAB SIDE .....	83
REFLECTIVE STRIPE - CAB FRONT .....	83
REFLECTIVE STRIPE - CAB DOOR INTERIOR .....	83
REFLECTIVE STRIPE - BODY SIDES .....	83
CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS .....	83
LETTERING .....	84
SIDE CAB DOOR LETTERING .....	84
UPPER BODY SIDE LETTERING .....	84
REAR BODY LETTERING .....	84
FRONT OF CAB LETTERING .....	84
EXTERIOR COMPARTMENT DOORS .....	85
ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM) .....	85
BODY HEIGHT MEASUREMENTS .....	86
BODY WIDTH DIMENSIONS .....	88
STREETSIDE COMPARTMENT - FRONT (S1) .....	88
COMPARTMENT LAYOUT .....	89
STREETSIDE COMPARTMENT - AHEAD OF REAR WHEELS (S2) .....	90
COMPARTMENT LAYOUT .....	90
STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S3) .....	92
COMPARTMENT LAYOUT .....	92
STREETSIDE COMPARTMENT - REAR (S4) .....	93
COMPARTMENT LAYOUT .....	93
CURBSIDE COMPARTMENT - FRONT (C1) .....	94

# Surprise Fire Dept

## Surprise, AZ

COMPARTMENT LAYOUT.....	95
CURBSIDE COMPARTMENT - AHEAD OF REAR WHEEL (C2).....	96
COMPARTMENT LAYOUT.....	97
12 VDC ACCESSORY PLUG.....	97
CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C3).....	98
COMPARTMENT LAYOUT.....	99
CURBSIDE COMPARTMENT - REAR (C4) .....	99
COMPARTMENT LAYOUT.....	100
REAR COMPARTMENT - CENTER (RC1).....	100
COMPARTMENT LAYOUT.....	101
FOLDING STEP.....	104
LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC.....	104
12 VOLT MULTIPLEX CONTROL CENTER .....	107
BATTERY SYSTEM.....	108
BATTERY SWITCH.....	108
BATTERY SOLENOID.....	109
BATTERY CONDITIONER.....	109
ENGINE COMPARTMENT LIGHT.....	109
REAR SCENE LIGHTS (BACK-UP LIGHTS).....	109
CAB SPOTLIGHT.....	109
CAB HAZARD WARNING LIGHT .....	109
BACK-UP ALARM.....	110
REAR VIEW CAMERA .....	110
TAIL LIGHTS.....	110
MIDSHIP MARKER/TURN SIGNAL .....	110
MARKER LIGHTS .....	110
CAB STEP LIGHTS / GROUND LIGHTS.....	110
LICENSE PLATE LIGHT .....	111
ELECTRONIC SIREN .....	111

# Surprise Fire Dept

## Surprise, AZ

<b>SIREN SPEAKER .....</b>	<b>111</b>
<b>SIDE SCENE LIGHTS.....</b>	<b>111</b>
<b>REAR SCENE LIGHTS.....</b>	<b>112</b>
<b>DAVID CLARK INTERCOM SYSTEM .....</b>	<b>112</b>
<b>INTERCOM SYSTEM INSTALLATION .....</b>	<b>112</b>
<b>WARNING LIGHT PACKAGE .....</b>	<b>113</b>
<b>UPPER LEVEL OPTICAL WARNING DEVICES .....</b>	<b>113</b>
<b>TOMARE TRAFFIC EMITTER .....</b>	<b>114</b>
<b>LOWER LEVEL OPTICAL WARNING DEVICES.....</b>	<b>115</b>
<b>HYDRAULIC GENERATOR SYSTEM .....</b>	<b>117</b>
<b>GENERATOR MOUNTING .....</b>	<b>117</b>
<b>WARRANTY PERIOD .....</b>	<b>117</b>
<b>HYDRAULIC COMPONENTS .....</b>	<b>118</b>
<b>GENERATOR MOUNTING .....</b>	<b>118</b>
<b>MANUALS AND SCHEMATICS .....</b>	<b>118</b>
<b>POWER-TAKE-OFF GENERATOR DRIVE .....</b>	<b>118</b>
<b>LOADCENTER.....</b>	<b>118</b>
<b>GENERATOR MONITORING PANEL .....</b>	<b>119</b>
<b>SHORE POWER INLET - BATTERY CHARGER.....</b>	<b>119</b>
<b>OUTLETS AND CIRCUITS .....</b>	<b>119</b>
<b>LINE VOLTAGE ELECTRICAL SYSTEM .....</b>	<b>120</b>
<b>GENERAL REQUIREMENTS.....</b>	<b>120</b>
<b>120/240 VAC SCENE LIGHTING.....</b>	<b>126</b>
<b>FRONT CAB-MOUNTED SCENE LIGHT(S) .....</b>	<b>126</b>
<b>LIGHT TOWER.....</b>	<b>126</b>
<b>Light Tower Paint .....</b>	<b>127</b>
<b>WATEROUS CL 500 GPM SINGLE STAGE FIRE PUMP .....</b>	<b>128</b>
<b>PUMP DRIVE SYSTEM .....</b>	<b>129</b>
<b>WATEROUS FIVE YEAR PUMP WARRANTY .....</b>	<b>129</b>

# Surprise Fire Dept

## Surprise, AZ

MANUFACTURER FIRE PUMP TEST .....	129
FIRE PUMP TEST LABEL .....	130
ALTITUDE REQUIREMENT .....	130
PUMP DRAIN CONTROL .....	130
DISCHARGE RELIEF VALVE .....	130
HEAT EXCHANGER .....	130
INTAKE RELIEF VALVE .....	131
PLUMBING SPECIFICATIONS .....	131
STAINLESS STEEL INTAKE MANIFOLD .....	131
STAINLESS STEEL DISCHARGE MANIFOLD .....	131
STAINLESS STEEL PLUMBING WARRANTY .....	131
STREETSIDE INTAKE - 3-1/2" .....	132
TANK TO PUMP CHECK VALVE .....	133
TANK TO PUMP VALVE .....	133
DISCHARGES .....	133
STREETSIDE DISCHARGE .....	134
MISCELLANEOUS DISCHARGE .....	135
2" SPEED LAY(S) .....	135
PUMP PANEL .....	136
PUMP PANEL LOCATION .....	136
PUMP PANEL ACCESS .....	136
PRESSURE GOVENOR .....	137
MASTER DISCHARGE GAUGE .....	137
MASTER INTAKE GAUGE .....	137
PUMP SAFETY AND TEST LABELS .....	137
COLOR CODED LABELS .....	137
PUMP PANEL LIGHTING .....	138
PUMP PANEL AIR HORN SWITCH .....	138
TEST TAPS .....	138



# Surprise Fire Dept

## Surprise, AZ

<b>WATER TANK LEVEL GAUGE .....</b>	<b>140</b>
<b>UPF POLY WATER TANK WARRANTY .....</b>	<b>140</b>
<b>HOSE BED STORAGE AREA .....</b>	<b>140</b>
<b>ALUMINUM HOSE BED DECKING .....</b>	<b>140</b>
<b>ALUMINUM HOSE BED COVER.....</b>	<b>141</b>
<b>EQUIPMENT PAYLOAD WEIGHT ALLOWANCE .....</b>	<b>142</b>
<b>EQUIPMENT.....</b>	<b>142</b>
<b>REMAINING NFPA MINOR EQUIPMENT BY PURCHASER .....</b>	<b>143</b>

### **LIABILITY INSURANCE**

The manufacturer shall furnish with the bid a certificate of insurance for;

Workman's Compensation and Employer's Liability Insurance covering for all employees.

General Liability (each occurrence) of \$1,000,000.00. General Aggregate coverage of \$2,000,000.00. Products Completed / Operations Aggregate coverage of \$2,000,000.00. Medical Expense coverage of \$5,000 (any one person). Personal Injury of \$1,000,000.00.

Automobile liability of \$1,000,000.00 combined single limit (each accident), including any auto, all owned autos, scheduled autos, hired autos, non-owned autos, and garage liability.

Excess Umbrella Liability coverage of \$4,000,000.00 each occurrence, Aggregate of \$4,000,000.00.  
Garage Keepers Liability coverage of \$4,500,000.00 combined limit.

All insurance policies must be;

- Maintained for the life of the contract,
- Must provide ten (10) days notice before cancellation,
- Must cover all operations of the contractor, or anyone employed by them.

### **INTERNET IN-PROCESS SITE**

The manufacturer shall post and maintain a website where the Surprise Fire Department will be able to view digital images of their apparatus as its being built. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of unit.

### **VEHICLE STABILITY SUPPLIED WITH CAB/CHASSIS**

The cab/chassis shall be equipped with a stability control system. The system shall have, at a minimum, a steering wheel position sensor, a vehicle yaw sensor, a lateral accelerometer and individual wheel brake controls.

# Surprise Fire Dept

## Surprise, AZ

### **FIRE APPARATUS PERFORMANCE**

The fire apparatus shall meet the requirements of this standard at elevations of 2000 ft (600 m) above sea level.

The fire apparatus shall meet all the requirements of this standard while stationary on a grade of 10 percent in any direction.

The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C).

### **ROADABILITY**

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- 1) From a standing start, the apparatus shall be able to attain a speed of 35 mph (55 km/hr) within 25 seconds on a level road.
- 2) The apparatus shall be able to attain a minimum top speed of 50 mph (80 km/hr) on a level road.
- 3) The apparatus shall be able to maintain a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent.

The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (105 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal (4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (85 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

### **SERVICEABILITY**

The fire apparatus shall be designed to allow the manufacturer's recommended routine maintenance checks of lubricant and fluid levels to be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

### **CONSTRUCTION DOCUMENTATION**

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

The manufacturers record of apparatus construction details, including the following information:

- 1) Owner's name and address
- 2) Apparatus manufacturer, model, and serial number

# Surprise Fire Dept

## Surprise, AZ

- 3) Chassis make, model, and serial number
  - a) GAWR of front and rear axles and GVWR
  - b) Front tire size and total rated capacity in pounds (kilograms)
  - c) Rear tire size and total rated capacity in pounds (kilograms)
  - d) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
  - e) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
  - f) Type of fuel and fuel tank capacity
  - g) Electrical system voltage and alternator output in amps
  - h) Battery make, model, and capacity in cold cranking amps (CCA)
  - i) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
- 4) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
- 5) Pump transmission make, model, serial number, and gear ratio
- 6) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
- 7) Water and Foam tank certified capacity in gallons or liters
- 8) Paint manufacturer and paint number(s)
- 9) Company name and signature of responsible company representative
- 10) If the apparatus is a mobile foam fire apparatus, the certification of foam tank capacity
- 11) Certification of compliance of the optical warning system
- 12) Siren manufacturer's certification of the siren
- 13) Written load analysis and results of the electrical system performance tests
- 14) Certification of slip resistance of all stepping, standing, and walking surfaces
- 15) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability
- 16) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions
- 17) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications
- 18) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed
- 19) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test
- 20) If the apparatus has a fire pump, the certification of inspection and test for the fire pump
- 21) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test
- 22) When the apparatus is equipped with a water tank, the certification of water tank capacity
- 23) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy and the final installer's certification the foam proportioning system meets this standard
- 24) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests
- 25) If the apparatus has a line voltage power source, the certification of the test for the power source
- 26) If the apparatus is equipped with an air system, air tank certificates, the SCBA fill station certification, and the results of the testing of the air system installation
- 27) Any other required manufacturer test data or reports.

### **OPERATIONS AND SERVICE DOCUMENTATION**

The Contractor shall deliver with the fire apparatus at least two (2) sets of complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all

# Surprise Fire Dept

## Surprise, AZ

major components thereof.

The Contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- 1) Manufacturer's name and address
- 2) Country of manufacture
- 3) Source for service and technical information
- 4) Parts replacement information
- 5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- 6) Wiring diagrams for low voltage and line voltage systems to include the following information:
  - j) Pictorial representations of circuit logic for all electrical components and wiring
  - k) Circuit identification
  - l) Connector pin identification
  - m) Zone location of electrical components
  - n) Safety interlocks
  - o) Alternator-battery power distribution circuits
  - p) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- 7) Lubrication charts
- 8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- 9) Precautions related to multiple configurations of aerial devices, if applicable
- 10) Instructions regarding the frequency and procedure for recommended maintenance
- 11) Overall apparatus operating instructions
- 12) Safety considerations
- 13) Limitations of use
- 14) Inspection procedures
- 15) Recommended service procedures
- 16) Troubleshooting guide
- 17) Apparatus body, chassis and other component manufacturer's warranties
- 18) Special data required by this standard
- 19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus

The Contractor shall deliver with the apparatus all manufacturer's operations and service documents supplied with components and equipment that are installed or supplied by the Contractor.

### **NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE**

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a USB Flash Drive. These manuals shall be divided into sections for ease of reference. There shall be two (2) USB flash drives provided with the completed vehicle.

### **STATEMENT OF EXCEPTIONS**

The Contractor shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- 1) A separate specification of the section of the applicable standard for which compliance is lacking

# Surprise Fire Dept

## Surprise, AZ

- 2) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
- 3) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance
- 4) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to or at the time of delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

An apparatus that is delivered subject to a Statement of Exceptions other than a certification of full compliance shall not be placed in emergency service until the apparatus has been modified as necessary to accomplish full compliance with this standard.

### **CARRYING CAPACITY**

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The Body Manufacturer shall establish the estimated in service weight during the design of the vehicle

The estimated in-service weight shall include the following:

- 1) The chassis, body and tank(s)
- 2) Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
- 3) Full water and other agent tanks
- 4) \*250 lb (114 kg) in each seating position
- 5) Fixed equipment such as pumps, aerial devices, generators, reels and air systems as installed
- 6) Ground ladders, suction hose, designed hose load in their hose beds and on their reels
- 7) An allowance for miscellaneous equipment that is the greatest of the values for type of vehicle per NFPA 1901, a Purchaser provided list of equipment to be carried with weights or a Purchaser specified miscellaneous equipment allowance.

The Body Manufacturer shall engineer and design the vehicle such that the completed unit, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

A final Body Manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

Apparatus Type	Storage Areas	Apparatus Size	Equipment Allowance	
			lb.	kg.
Initial Attack Fire Apparatus	Equip. minimum of 22 cu ft (0.62 cu mt) of enclosed compartmentation.	10,000 lb to 15,000 lb (4,500 kg to 7,000 kg) GVWR	900	410
	Hose minimum of 10 cu ft (0.3 cu mt) for 2 1/2" (65 mm) or larger fire hose.	15,001 lb to 20,000 lb (7,001 kg to 9,000 kg) GVWR	1,500	680
	(2) areas for pre-connects	20,001 lb and up	2,000	910

# Surprise Fire Dept

## Surprise, AZ

	each minimum of 3.5 cu ft (0.1 cu mt) for 1 1/2" (38 mm) or larger fire hose.	(9,001 kg) GVWR		
--	---	-----------------	--	--

### **TESTING**

#### **ROAD TEST**

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the Body Manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

#### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (−18°C and 43°C).

#### **TEST SEQUENCE**

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for ten (10) minutes. Failure of any of these tests shall require a repeat of the sequence.

##### **1. RESERVE CAPACITY TEST**

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes.

# Surprise Fire Dept

## Surprise, AZ

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

### **2. ALTERNATOR PERFORMANCE TEST**

#### **TEST AT IDLE**

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

#### **TEST AT FULL LOAD**

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

### **3. LOW VOLTAGE ALARM TEST**

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

#### **DOCUMENTATION**

The manufacturer shall deliver the following with the fire apparatus:

- 1) Documentation of the electrical system performance tests
- 2) A written electrical load analysis, including the following:
  - q) The nameplate rating of the alternator
  - r) The alternator rating
  - s) Each of the component loads specified that make up the minimum continuous electrical load
  - t) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load

# Surprise Fire Dept

## Surprise, AZ

- u) Each individual intermittent electrical load

### **UL 120/240 VAC CERTIFICATION**

The 120/240 volt electrical system shall be third-party, independent, audit-certified through Underwriters Laboratory (UL) to the current edition of NFPA 1901 to perform as listed below;

The prime mover shall be started from a cold start condition, and the unloaded voltage and frequency shall be recorded.

The line voltage electrical system shall be loaded to at least 100% of the continuous rated wattage stated on the power source specification label. Testing with a resistive load bank shall be permitted.

The power source shall be operated in the manner specified by the apparatus manufacturer as documented on instruction plates or in operation manuals. The power source shall be operated at a minimum of 100% of the continuous rated wattage as stated on the power source specification label for a minimum of two (2) hours.

The load shall be adjusted to maintain the output wattage at or above the continuous rated wattage during the entire 2-hour test.

The following conditions shall be recorded at least every 1/2 hour during the test:

- 1) The power source output voltage, frequency and amperes
- 2) The prime mover's oil pressure, water temperature and transmission temperature, if applicable
- 3) The power source hydraulic fluid temperature, if applicable
- 4) The ambient temperature and power source air inlet temperature

The following conditions shall be recorded once during the test for power sources driven by dedicated auxiliary internal combustion engines:

- 1) Altitude
- 2) Barometric pressure
- 3) Relative humidity

If the generator is driven by the chassis engine and the generator allows for operation at variable speeds, the chassis engine speed shall be reduced to the lowest rpm allowed for generator operation and the voltage and frequency shall be recorded.

The load shall be removed and the unloaded voltage and frequency shall be recorded.

Voltage shall be maintained within  $\pm 10\%$  of the voltage stated on the power source specification label during the entire test. Frequency shall be maintained within  $\pm 3$  Hz of the frequency stated on the power source specification label during the entire test.

The total continuous electrical loads, excluding those loads associated with the equipment defined in NFPA 22.15.7.3.11.2, shall be applied during the testing unless an auxiliary engine drives the power source.

If the apparatus is equipped with a fire pump, the 2-hour certification test of the power source shall be completed with the fire pump pumping at 100% capacity at 150 psi (1000 kPa) net pump pressure. The test shall be permitted to be run concurrently with the pump certification test.



# Surprise Fire Dept

## Surprise, AZ

### **DOCUMENTATION**

The Body Manufacturer shall deliver the following with the fire apparatus:

The results of each test shall be recorded on an appropriate form and provided with the delivery of the fire apparatus.

### **DIELECTRIC VOLTAGE WITHSTAND TEST**

The line voltage wiring and permanently connected devices and equipment shall be subjected to a dielectric voltage withstand test of 900 volts for one (1) minute. The testing shall be performed after all body work has been completed.

The test shall be conducted as follows:

- 1) Isolate the power source from the panel board and disconnect any solid state low voltage components
- 2) Connect one lead of the dielectric tester to all the hot and neutral buses tied together
- 3) Connect the other lead to the fire apparatus frame or body
- 4) Close any switches and circuit breakers in the circuit(s)
- 5) Apply the dielectric voltage for one (1) minute in accordance with the testing equipment manufacturer's instructions

The electrical polarity of all permanently wired equipment, cord reels and receptacles shall be tested to verify that wiring connections have been properly made.

Electrical continuity shall be verified from the chassis or body to all line voltage electrical enclosures, light housings, motor housings, light poles, switch boxes and receptacle ground connections that are accessible to fire fighters in normal operations.

If the apparatus is equipped with a transfer switch, it shall be tested to verify operation and that all non grounded conductors are switched.

Electrical light towers, floodlights, motors, fixed appliances and portable generators shall be operated at their full rating or capacity for 30 minutes to ensure proper operation.

### **MANUFACTURER PUMP CERTIFICATION**

The apparatus upon completion shall be tested and certified by the manufacturer. The certification tests shall follow the guide lines outlined in NFPA 1901 "Standard for Fire Apparatus".

If the fire pump has a rated capacity of less than 750 gpm (3000 L/min), the pump shall be tested after the pump and all its associated piping and equipment have been installed on the apparatus.

The fire pump shall be tested and results certified to perform as listed below;

- 100% of rated capacity at 150 psi (1,000 kPa) net pressure
- 70% of rated capacity at 200 psi (1,400 kPa) net pressure
- 50% of rated capacity at 250 psi (1,700 kPa) net pressure

The test shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming device tests, and the vacuum test.

# Surprise Fire Dept

## Surprise, AZ

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 500 psi (3,400 kPa).

The pump shall comply with the applicable requirements of "Standard for Fire Apparatus 1901, latest edition.

The pump shall be capable of producing fire streams that are free from objectionable pulsation under all normal operating conditions.

If the apparatus is equipped with a pump driven by the chassis engine designed for both stationary pumping and pump-and-roll, the test shall verify that the engine speed control at the pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the parking brake is off, and the pump shift status in the driving compartment is disengaged.
- (2) The chassis transmission is in any gear other than neutral, the parking brake is on, and the pump shift in the driving compartment is in the "Pump Engaged" or the "OK to Pump-and-Roll" position.

A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve.

### **PERFORMANCE BOND**

The successful Bidder will be required to provide a 100% performance bond in the amount equivalent to the total amount of its bid including any additional options that may have been given. Performance bond shall be provided within two (2) weeks after notice of award.

If the Bidder to whom the contract is awarded, refuses or neglects to execute or fails to furnish the required 100% performance bond within two (2) weeks after notice, the amount of his deposit may be forfeited and retained by the Surprise Fire Department as liquidated damages.

The terms of the performance bond shall continue one (1) year after completion and delivery of the apparatus. The balance of any warranty, if greater than 12 months, shall continue to be guaranteed solely by Contractor.

### **WARRANTY**

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source and will deal directly with the Surprise Fire Department on all warranty work.

# Surprise Fire Dept

## Surprise, AZ

### **GENERAL LIMITED WARRANTY - TWO (2) YEARS**

The vehicle shall be free of defects in material and workmanship for a period of two (2) years or 36,000 miles (or 57,936 kilometers), whichever occurs first starting thirty (30) days after the original invoice date.

The Contractor must be the "single source" coordinator of all warranties on the vehicle.

### **LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS**

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles (or 96,561 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

### **STRUCTURAL WARRANTY - TEN (10) YEARS**

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

### **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

### **PAINT LIMITED WARRANTY - TEN (10) YEARS**

The body shall be free of bubbling or peeling as a result of a defect in the method of manufacture for a period of ten (10) years or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date. **Pro-rated warranties will not be acceptable.**

### **GRAPHICS LIMITED WARRANTY**

The 3M graphics installation shall be warranted for a period of two (2) years. The 3M materials installed on completed vehicle shall be warranted for seven (7) years. The 3M Diamond grade film (if specified) shall be warranted for ten (10) years.

### **WATEROUS FIVE YEAR PUMP WARRANTY**

The fire pump shall be warranted by Waterous for a period of five (5) years from the date of delivery to the Surprise Fire Department.

### **STAINLESS STEEL PLUMBING WARRANTY**

The stainless steel plumbing shall be free of defects in material and workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

# Surprise Fire Dept

## Surprise, AZ

The contractor shall supply details of their warranty information with their bid submission.

### **CONSTRUCTION PERIOD**

The completed vehicle shall be delivered within three hundred thirty (330) days after receipt of a purchase order or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to Surprise Fire Department as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

### **OVERALL HEIGHT REQUIREMENT**

There is no overall height (OAH) restriction for this vehicle.

### **OVERALL LENGTH REQUIREMENT**

There is no overall length (OAL) restriction for this vehicle.

### **OVERALL WIDTH**

The overall width (OAW) of the body at drip rails shall be 102" (8' - 6"), and body shall be 100" (8' - 4").

### **ANGLE OF APPROACH**

The angle of approach for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

### **ANGLE OF DEPARTURE**

The angle of departure for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

Dealer Commission

### **PRE-CONSTRUCTION CONFERENCE**

A pre-construction conference shall be required at the Contractor's factory for three (3) personnel from the Surprise Fire Department to finalize all construction details prior to manufacturing.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the pre-construction conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

### **EQUIPMENT MOUNTING CONFERENCE**

An equipment mounting conference shall be required at the Contractor's factory for two (2) personnel from the Surprise Fire Department to inspect the vehicle and construction details prior to the painting process.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the pre-paint conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

# Surprise Fire Dept

## Surprise, AZ

### **FINAL INSPECTION CONFERENCE**

A final inspection conference shall be required at the Contractor's factory for four (4) personnel from the Surprise Fire Department to inspect the vehicle and construction details prior to shipment of the completed vehicle. This inspection shall take place after any specified striping and lettering is installed.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the final inspection conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

### **DELIVERY AND DEMONSTRATION**

The Contractor shall be responsible for the delivery of the completed unit to the Surprise Fire Department's location. On initial delivery of the apparatus, the Contractor shall supply a qualified representative to demonstrate the apparatus and provide initial instruction to representatives of the Surprise Fire Department regarding the operation, care and maintenance of the apparatus and equipment supplied at Surprise Fire Department location.

The Delivery Engineer shall set delivery and instruction schedule with the person appointed by Surprise Fire Department.

After delivery of the apparatus, the Surprise Fire Department shall be responsible for ongoing training of its personnel to proficiency regarding the proper and safe use of the apparatus and associated equipment.

Fees: AZ Tax, 5.6%

### **MODEL**

The chassis shall be a Metro Star model. The cab and chassis shall include design considerations for multiple emergency vehicle applications, rapid transit and maneuverability. The chassis shall be manufactured for heavy duty service with the strength and capacity to support a fully laden apparatus, one hundred (100) percent of the time.

### **MODEL YEAR**

The chassis shall have a vehicle identification number that reflects a 2015 model year.

### **COUNTRY OF SERVICE**

The chassis shall be put in service in the country of United States of America (USA).

The chassis will meet applicable U.S.A. federal motor vehicle safety standards per CFR Title 49 Chapter V Part 571 as clarified in the incomplete vehicle book per CFR Title 49 Chapter V Part 568 Section 4 which accompanies each chassis. Spartan Chassis is not responsible for compliance to state, regional, or local regulations. Dealers should identify those regulations and order any necessary optional equipment from Spartan Chassis or their OEM needed to be in compliance with those regulations.

### **APPARATUS TYPE**

The apparatus shall be a rescue vehicle designed for emergency service use which shall include the functions of a multipurpose vehicle which primarily provides support services at emergency scenes.

# Surprise Fire Dept

## Surprise, AZ

### **VEHICLE TYPE**

The chassis shall be manufactured for use as a straight truck type vehicle and designed for the installation of a permanently mounted apparatus behind the cab. The apparatus of the vehicle shall be supplied and installed by the apparatus manufacturer.

### **AXLE CONFIGURATION**

The chassis shall feature a 4 x 2 axle configuration consisting of a single rear drive axle with a single front steer axle.

### **GROSS AXLE WEIGHT RATINGS FRONT**

The front gross axle weight rating (GAWR) of the chassis shall be 20,000 pounds.

This front gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

### **GROSS AXLE WEIGHT RATINGS REAR**

The rear gross axle weight rating (GAWR) of the chassis shall be 24,000 pounds.

This rear gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

### **PUMP PROVISION**

The chassis shall include clearance provisions in the cross members to mount a pump in the middle of the chassis, driven by transmission mounted PTO.

### **CAB STYLE**

The cab shall be a custom, fully enclosed, LFD model with a 10.00 inch raised roof over the driver, officer, and crew area, designed and built specifically for use as an emergency response vehicle by a company specializing in cab and chassis design for all emergency response applications. The cab shall be designed for heavy-duty service utilizing superior strength and capacity for the application of protecting the occupants of the vehicle. This style of cab shall offer up to ten (10) seating positions.

The cab shall incorporate a fully enclosed design with side wall roof supports, allowing for a spacious cab area with no partition between the front and rear sections of the cab. To provide a superior finish by reducing welds that fatigue cab metal; the roof, the rear wall and side wall panels shall be assembled using a combination of welds and proven industrial adhesives designed specifically for aluminum fabrication for construction.

The cab shall be constructed using multiple aluminum extrusions in conjunction with aluminum plate, which shall provide proven strength and the truest, flattest body surfaces ensuring less expensive paint repairs if needed. All aluminum welding shall be completed to the American Welding Society and ANSI D1.2-96 requirements for structural welding of aluminum.

All interior and exterior seams shall be sealed for optimum noise reduction and to provide the most favorable efficiency for heating and cooling retention.

# Surprise Fire Dept

## Surprise, AZ

The cab shall be constructed of 5052-H32 corrosion resistant aluminum plate. The cab shall incorporate tongue and groove fitted 6061-T6 0.13 & 0.19 inch thick aluminum extrusions for extreme duty situations. A single formed, one (1) piece extrusion shall be used for the "A" pillar, adding strength and rigidity to the cab as well as additional roll-over protection. The cab side walls and lower roof skin shall be 0.13 inch thick; the rear wall and raised roof skins shall be 0.09 inch thick; the front cab structure shall be 0.19 inch thick.

The exterior width of the cab shall be 94.00 inches wide with a minimum interior width of 88.00 inches. The overall cab length shall be 144.60 inches with 67.50 inches from the centerline of the front of the axle to the back of the cab.

The cab interior shall be designed to afford the maximum usable interior space and attention to ergonomics with hip and legroom while seated which exceeds industry standards. The crew cab floor shall be flat across the entire walking area for ease of movement inside the cab.

The cab shall offer an interior height of 57.50 inches from the front floor to the headliner and a rear floor to headliner height of 65.00 inches in the raised roof area, at a minimum. The cab shall offer an interior measurement at the floor level from the rear of the engine tunnel to the rear wall of the cab of 63.38 inches. All interior measurements shall include the area within the interior trimmed surfaces and not to any unfinished surface.

The cab shall include a driver and officer area with two (2) cab doors large enough for personnel in full firefighting gear. The front doors shall offer a clear opening of 40.25 inches wide X 53.50 inches high, from the cab floor to the top of the door opening. The cab shall also include a crew area with up to two (2) cab doors, also large enough for personnel in full firefighting gear. The rear doors shall offer a clear opening of 32.25 inches wide X 61.00 inches high, from the cab floor to the top of the door opening.

The cab shall incorporate a progressive two (2) step configuration from the ground to the cab floor at each door opening. The progressive steps are vertically staggered and extend the full width of each step well allowing personnel in full firefighting gear to enter and exit the cab easily and safely.

The first step for the driver and officer area shall measure approximately 10.25 inches deep X 31.13 inches wide. The intermediate step shall measure approximately 8.38 inches deep X 32.13 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 11.00 inches.

The first step for the crew area shall measure approximately 10.38 inches deep X 20.44 inches wide. The intermediate step shall measure approximately 10.20 inches deep X 21.00 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 12.80 inches.

### **CAB FRONT FASCIA**

The front cab fascia shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate which shall be an integral part of the cab.

The cab fascia will encompass the entire front of the aluminum cab structure from the bottom of the windshield to the bottom of the cab and shall be the "Classic" design.

The front cab fascia shall include two (2) molded plastic modules on each side accommodating a total of up to four (4) Hi/Low beam headlights and two (2) turn signal lights or up to four (4) warning lights. A chrome plated molded plastic bezel shall be provided on each side around each set of four lamps.

# Surprise Fire Dept

## Surprise, AZ

### **FRONT GRILLE**

The front fascia shall include a box style, 304 stainless steel front grille 44.45 inches wide X 33.50 inches high X 1.50 inches deep. The grille shall include a minimum free air intake of 732.00 square inches. The upper portion of the grille shall be hinged to provide service access behind the grille.

### **CAB UNDERCOAT**

There shall be a rubberized undercoating applied to the underside of the cab that provides abrasion protection, sound deadening and corrosion protection.

### **CAB SIDE DRIP RAIL**

There shall be a drip rail along the top radius of each cab side. The drip rails shall help prevent water from the cab roof running down the cab side.

### **CAB PAINT EXTERIOR**

The cab shall be painted prior to the installation of glass accessories and all other cab trim to ensure complete paint coverage and the maximum in corrosion protection of all metal surfaces.

All metal surfaces on the entire cab shall be ground by disc to remove any surface oxidation or surface debris which may hinder the paint adhesion. Once the surface is machine ground a high quality acid etching of base primer shall be applied. Upon the application of body fillers and their preparation, the cab shall be primed with a coating designed for corrosion resistance and surface paint adhesion. The maximum thickness of the primer coat shall be 2.00 mils.


The entire cab shall then be coated with an intermediate solid or epoxy surfacing agent that is designed to fill any minor surface defects, provide an adhesive bond between the primer and the paint and improve the color and gloss retention of the color. The finish to this procedure shall be a sanding of the cab with 360 grit paper followed by sealing the seams with SEM brand seam sealer.

The cab shall then be painted the specific color designated by the customer with an acrylic urethane type system designed to retain color and resist acid rain and most atmospheric chemicals found on the fire ground or emergency scene. The paint shall have a minimum thickness of 2.00 mils, followed by a clear top coat not to exceed 2.00 mils. The entire cab shall then be baked at 180 degrees for one (1) hour to speed the curing process of the coatings.

### **CAB PAINT MANUFACTURER**

The cab shall be painted with PPG Industries paint.

### **CAB PAINT PRIMARY/LOWER COLOR**

The lower paint color shall be **PPG FBCH 71663 Red**. 

### **CAB PAINT SECONDARY/UPPER COLOR**

The secondary/upper paint color shall be PPG FBCH 911645 white.



# Surprise Fire Dept

## Surprise, AZ

### **CAB PAINT EXTERIOR BREAKLINE**

The upper and lower paint shall meet at a breakline on the cab which shall be located approximately 1.00 inch below the door windows on each side of the cab. The breakline shall curve down at the front cab corners to approximately 5.00 inches below the windshields on the front of the cab.

### **CAB PAINT PINSTRIPE**

A 0.50 inch wide gold reflective tape with black borders shall be applied on the break line between the two different colored surfaces.

### **CAB PAINT WARRANTY**

The cab and chassis shall be covered by a limited manufacturer paint warranty which shall be in effect for ten (10) years from the first owner's date of purchase or in service or the first 100,000 actual miles, whichever occurs first.

### **CAB PAINT INTERIOR**

The visible interior cab structure surfaces shall be painted with a Zolatone **onyx-black texture finish**.

### **CAB ENTRY DOORS**

The cab shall include four (4) entry doors, two (2) front doors and two (2) crew doors designed for ease of entering and egress when outfitted with an SCBA. The doors shall be constructed of extruded aluminum with a nominal thickness of 0.13 inch. The exterior skins shall be constructed of 0.13 inch aluminum plate.

The doors shall include a double rolled style automotive rubber seal around the perimeter of each door frame and door edge which ensures a weather tight fit.

All door hinges shall be hidden within flush mounted cab doors for a pleasing smooth appearance and perfect fit along each side of the cab. Each door hinge shall be piano style with a 0.38 inch pin and shall be constructed of stainless steel.

### **CAB ENTRY DOOR TYPE**

All cab entry doors shall be barrier clear design resulting in exposed lower cab steps. The doors shall provide approximately 32.00 inches of clearance from the ground to the bottom of the door so cab doors may be opened un-hindered by most obstacles encountered, such as guard rails along interstate highways.

### **CAB INSULATION**

The cab ceiling and walls shall include 1.00 inch thick foam insulation. The insulation shall act as a barrier absorbing noise as well as assisting in sustaining the desired climate within the cab interior.

### **LH EXTERIOR REAR COMPARTMENT**

The cab shall offer an exterior compartment on the left side of the cab behind the rear door. The compartment opening shall be 10.00 inches wide X 21.19 inches high. The compartment size shall be 11.34 inches wide X 21.19 inches high X 21.19 inches deep. The compartment shall have a 10.63 inch wide, 32.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a bright aluminum tread plate inner panel and a bent D-ring slam latch. There shall be a switch to activate a light inside the compartment and the open compartment warning light in the cab in the event the door is left ajar.

# Surprise Fire Dept

## Surprise, AZ

### **LEFT HAND EXTERIOR REAR COMPARTMENT LIGHTING**

There shall be one (1) SoundOff Signal brand LED strip light installed to illuminate the exterior rear compartment on the left side of the cab. The strip light shall be 10.00 inches long and shall include three (3) bright white Gen3 LEDs.

### **LH EXTERIOR COMPARTMENT INTERIOR FINISH**

The interior of the left hand exterior compartment shall have a DA sanded finish.

### **RH EXTERIOR REAR COMPARTMENT**

The cab shall offer an exterior compartment on the right side of the cab behind the rear door. The compartment opening shall be 10.00 inches wide X 21.19 inches high. The compartment size shall be 11.34 inches wide X 21.19 inches high X 21.19 inches deep. The compartment shall have a 10.63 inch wide, 32.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a bright aluminum tread plate inner panel and a bent D-ring slam latch. There shall be a switch to activate a light inside the compartment and the open compartment warning light in the cab in the event the door is left ajar.

### **RIGHT HAND EXTERIOR REAR COMPARTMENT LIGHTING**

There shall be one (1) SoundOff Signal brand LED strip light installed to illuminate the exterior rear compartment on the right side of the cab. The strip light shall be 10.00 inches long and shall include three (3) bright white Gen3 LEDs.

### **RH EXTERIOR COMPARTMENT INTERIOR FINISH**

The interior of the right hand exterior compartment shall have a DA sanded finish.

### **CAB STRUCTURAL WARRANTY**

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN CHASSIS, INC. LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The cab structure shall be warranted for a period of ten (10) years or one hundred thousand (100,000) miles which ever may occur first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

### **CAB TEST INFORMATION**

The cab shall have successfully completed the preload side impact, static roof load application and frontal impact without encroachment to the occupant survival space when tested in accordance with Section 4 of SAE J2420 COE Frontal Strength Evaluation Dynamic Loading Heavy Trucks, Section 5 of SAE J2422 Cab Roof Strength Evaluation Quasi -Static Loading Heavy Trucks and ECE R29 Uniform Provisions Concerning the Approval of Vehicles with regard to the Protection of the Occupants of the Cab of a Commercial Vehicles Annex 3 Paragraph 5.

# Surprise Fire Dept

## Surprise, AZ

The above tests have been witnessed by and attested to by an independent third party. The test results were recorded using cameras, high speed imagers, accelerometers and strain gauges. Documentation of the testing shall be provided upon request.

### **ELECTRICAL SYSTEM**

The chassis shall include a single starting electrical system which shall include a 12 volt direct current Weldon brand of multiplexing system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be color coded and shall include the circuit number and function where possible. The wiring shall be protected by 275 degree Fahrenheit minimum high temperature flame retardant loom. All nodes and sealed Deutsch connectors shall be waterproof.

### **APPARATUS WIRING PROVISION**

An apparatus wiring panel shall be installed in the center dash area behind the rocker switch panel which shall include eight (8) open circuits consisting of three (3) 20 amp, one (1) 30 amp, three (3) 10 amp, and one (1) 15 amp circuit, with relays and breakers with trigger wires which shall be routed to the rocker switch panel.

### **MULTIPLEX DISPLAY**

The multiplex electrical system shall include two (2) Weldon Vista IV Touchscreen displays which shall be located one (1) on the left side dash in the switch panel and one (1) on the right side of the dash in the switch panel. The Touchscreen displays shall feature full color LCD display screens. The display shall include a message bar displaying the time of day, and important messages requiring acknowledgement by the user. There shall be virtual controls for the on-board diagnostics. The display screens shall be video ready for back- up cameras, thermal cameras, and DVD. A DIN type input connector ready for GPS interfacing shall be incorporated into the back of the display.

The Touchscreen displays shall measure approximately 6.25 inches wide x 3.38 inches in height. The displays shall offer varying fonts and background colors. The display shall be fully programmable to the needs of the customer and shall offer virtually infinite flexibility for screen configuration options.

### **DATA RECORDING SYSTEM**

The chassis shall have a Weldon Vehicle Data Recorder (VDR) system installed. The system shall be designed to meet NFPA 1901 and shall be integrated with the Weldon Multiplex electrical system. The following information shall be recorded:

- Vehicle Speed
- Acceleration
- Deceleration
- Engine Speed
- Engine Throttle Position
- ABS Event
- Seat Occupied Status
- Seat Belt Status
- Master Optical Warning Device Switch Position
- Time
- Date

# Surprise Fire Dept

## Surprise, AZ

Each portion of the data shall be recorded at the specified intervals and stored for the specified length of time to meet NFPA 1901 guidelines and shall be retrievable by connecting a laptop computer to the VDR system.

### **ACCESSORY POWER**

The electrical distribution panel shall include two (2) power studs. The studs shall be size #10 and each of the power studs shall be circuit protected with a fuse of the specified amperage. One (1) power stud shall be capable of carrying up to a 40 amp battery direct load. One (1) power stud shall be capable of carrying up to a 15 amp ignition switched load. The two (2) power studs shall share one (1) #10 ground stud. A 225 amp battery direct power and ground stud shall be provided and installed on the chassis near the left hand battery box for OEM body connections.

### **EXTERIOR ELECTRICAL TERMINAL COATING**

All terminals exposed to the elements will be sprayed with a high visibility protective rubberized coating to prevent corrosion.

### **ENGINE**

The chassis engine shall be a Cummins ISL9 engine. The ISL9 engine shall be an in-line six (6) cylinder, four cycle diesel powered engine. The engine shall offer a rating of 450 horse power at 2100 RPM and shall be governed at 2200 RPM. The torque rating shall feature 1250 foot pounds of torque at 1400 RPM with 543 cubic inches (8.9 liters) of displacement.

The ISL9 engine shall feature a VGT™ Turbocharger, a high pressure common rail fuel system, fully integrated electronic controls with an electronic governor, and shall be EPA certified to meet the 2013 emissions standards using cooled exhaust gas recirculation and selective catalytic reduction technology.

The engine shall include an engine mounted combination full flow/by-pass oil filter with replaceable spin on cartridge for use with the engine lubrication system. The engine shall include Citgo brand Citgard 500, or equivalent SAE 15W40 CJ4 low ash engine oil which shall be utilized for proper engine lubrication.

A wiring harness shall be supplied ending at the back of the cab. The harness shall include a connector which shall allow an optional harness for the pump panel. The included circuits shall be provided for a tachometer, oil pressure, engine temperature, hand throttle, high idle and a PSG system. A circuit for J1939 data link shall also be provided at the back of the cab.

### **CAB ENGINE TUNNEL**

The cab interior shall include an integrated engine tunnel constructed of 5052-H32 Marine Grade, 0.19 of an inch thick aluminum. The tunnel shall be a maximum of 41.50 inches wide X 25.50 inches high.

### **DIESEL PARTICULATE FILTER CONTROLS**

There shall be two (2) controls for the diesel particulate filter. One (1) control shall be for regeneration and one (1) control shall be for regeneration inhibit.

### **ENGINE PROGRAMMING HIGH IDLE SPEED**

The engine high idle control shall maintain the engine idle at approximately 1250 RPM when engaged.

# Surprise Fire Dept

## Surprise, AZ

### **ENGINE HIGH IDLE CONTROL**

The vehicle shall be equipped with an automatic high-idle speed control. It shall be pre-set so when activated, it will operate the engine at the appropriate RPM to increase alternator output. This device shall operate only when the master switch is activated and the transmission is in neutral with the parking brake set. The device shall disengage when the operator depresses the brake pedal, or the transmission is placed in gear, and shall be available to manually or automatically re-engage when the brake is released, or when the transmission is placed in neutral. There shall be an indicator on the Vista display and control screen for the high idle speed control.

### **ENGINE PROGRAMMING ROAD SPEED GOVERNOR**

The engine shall include programming which will govern the top speed of the vehicle.

### **AUXILIARY ENGINE BRAKE**

A compression brake, for the six (6) cylinder engine shall be provided. A cutout relay shall be installed to disable the compression brake when in pump mode or when an ABS event occurs. The engine compression brake shall activate upon 0% accelerator when in operation mode and actuate the vehicle's brake lights.

The engine shall utilize a variable geometry turbo (VGT) as an integrated auxiliary engine brake to offer a variable rate of exhaust flow, which when activated in conjunction with the compression brake shall enhance the engine's compression braking capabilities.

### **AUXILIARY ENGINE BRAKE CONTROL**

An engine compression brake control device shall be included. The electronic control device shall monitor various conditions and shall activate the engine brake only if all of the following conditions are simultaneously detected:

- A valid gear ratio is detected.
- The driver has requested or enabled engine compression brake operation.
- The throttle is at a minimum engine speed position.
- The electronic controller is not presently attempting to execute an electronically controlled final drive gear shift.

The compression brake shall be controlled via an on/off/ button. The multiplex system shall remember and default to the ON position when the vehicle is shut off and re-started.

### **ELECTRONIC ENGINE OIL LEVEL INDICATOR**

The engine oil shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal. The warning shall activate in a low oil situation upon turning on the master battery and ignition switches without the engine running.

### **FLUID FILLS**

The front of the chassis shall accommodate fluid fill for the engine oil through the grille. This area shall also accommodate a check for the engine oil. The transmission, power steering, and coolant fluid fills and checks shall be under the cab. The windshield washer fill shall be accessible through the front left side mid step.

# Surprise Fire Dept

## Surprise, AZ

### **ENGINE DRAIN PLUG**

The engine shall include an original equipment manufacturer installed oil drain plug.

### **ENGINE WARRANTY**

The Cummins engine shall be warranted for a period of five (5) years or 100,000 miles, whichever occurs first.

### **ENGINE PROGRAMMING REMOTE THROTTLE**

The engine ECM (Electronic Control Module) discreet wire remote throttle circuit shall be turned off for use with a J1939 based pump controller or when the discreet wire remote throttle controls are not required.

### **ENGINE PROGRAMMING IDLE SPEED**

The engine low idle speed will be programmed at 700 rpm.

### **ENGINE FAN DRIVE**

The engine cooling system fan shall incorporate a thermostatically controlled, Horton clutched type fan drive.

When the clutched fan is disengaged it shall facilitate improved vehicle performance, cab heating in cold climates, and fuel economy. The fan clutch design shall be fail safe so that if the clutch drive fails the fan shall engage to prevent engine overheating due to the fan clutch failure.

### **ENGINE COOLING SYSTEM**

There shall be a heavy-duty aluminum cooling system designed to meet the demands of the emergency response industry. The cooling system shall have the capacity to keep the engine properly cooled under all conditions of road and pumping operations. The cooling system shall be designed and tested to meet or exceed the requirements specified by the engine and transmission manufacturer and all EPA requirements. The complete cooling system shall be mounted to isolate the entire system from vibration or stress. The individual cores of the cooling system shall be mounted in a manner to allow expansion and contraction at various rates without inducing stress into the adjoining cores.

The cooling system shall utilize a charge air cooler to radiator serial flow package that provides the maximum cooling capacity for the specified engine as well as serviceability. The main components shall include a surge tank, an air to air charge air cooler bolted to the front of the radiator, recirculation shields, a shroud, a fan, and required tubing.

The radiator shall be a down-flow design constructed with aluminum cores, plastic end tanks, and a steel frame. The radiator shall be equipped with a drain cock to drain the coolant for serviceability.

The cooling system shall include a one piece injection molded polymer eleven (11) blade fan with a fiberglass fan shroud.

The cooling system shall be equipped with a surge tank that is capable of removing entrained air from the system. The surge tank shall be equipped with a low coolant probe and sight glass to monitor the level of the coolant. The surge tank shall have a dual seal cap that meets the engine manufacturer's pressure requirements, and allows for expansion and recovery of coolant into a separate integral expansion chamber.

# Surprise Fire Dept

## Surprise, AZ

All radiator tubes shall be formed from aluminized steel tubing. Recirculation shields shall be installed where required to prevent heated air from reentering the cooling package and affecting performance.

The charge air cooler shall be a cross-flow design constructed completely of aluminum with cast tanks. All charge air cooler tubes shall be formed from aluminized steel tubing and installed with silicone hump hoses and stainless steel "constant torque" style clamps meeting the engine manufacturer's requirements.

### **ENGINE COOLING SYSTEM PROTECTION**

The engine cooling system shall include a recirculation shield designed to act as a light duty skid plate below the radiator to provide additional protection for the engine cooling system from light impacts, stones, and road debris. The skid plate shall be painted to match the frame color.

### **ENGINE COOLANT**

The cooling package shall include Extended Life Coolant (ELC). The use of ELC provides longer intervals between coolant changes over standard coolants providing improved performance. The coolant shall contain a 50/50 mix of ethylene glycol and de-ionized water to keep the coolant from freezing to a temperature of -34 degrees Fahrenheit.

Proposals offering supplemental coolant additives (SCA) shall not be considered, as this is part of the extended life coolant makeup.

### **ENGINE COOLANT FILTER**

An engine coolant filter with a shut-off valve for the inlet and outlet shall be installed on the chassis. The location of the filter shall allow for easy maintenance.

Proposals offering engines equipped with coolant filters shall be supplied with standard non-chemical type particulate filters.

### **ELECTRONIC COOLANT LEVEL INDICATOR**

The instrument panel shall feature a low engine coolant indicator light which shall be located in the center of the instrument panel. An audible tone alarm shall also be provided to warn of a low coolant incident.

### **ENGINE PUMP HEAT EXCHANGER**

A single bundle type coolant to water heat exchanger shall be installed between the engine and the radiator. The heat exchanger shall be designed to prohibit water from the pump from coming in contact with the engine coolant. This shall allow the use of water from the discharge side of the pump to assist in cooling the engine.

### **COOLANT HOSES**

The cooling systems coolant hoses shall be silicone heater hose and shall include silicone hoses for all radiator coolant plumbing including the surge tank hoses. The radiator coolant hoses shall be formed silicone with formed aluminized steel tubing. All radiator silicone coolant hose and tubing, heater hose, and surge tank plumbing shall be secured with stainless steel constant torque band clamps.

# Surprise Fire Dept

## Surprise, AZ

### **ENGINE COOLANT OVERFLOW BOTTLE**

A remote engine coolant overflow bottle shall be provided in the case of over filling the coolant system. The overflow bottle shall capture the expansion fluid or overfill rather than allow the fluid to drain on the ground. The overflow bottle provided on the cooling system shall only be a catch bottle and shall not return excess coolant back into the surge tank.

### **ENGINE AIR INTAKE**

The engine air intake system shall include an ember separator air intake filter which shall be located in the front of the cab behind the right hand side fascia. This filter shall protect the downstream air filter from embers using a combination of unique flat and crimped metal screens constructed into a corrosion resistant steel frame. This multilayered screen shall be designed to trap embers or allow them to burn out before passing through the pack, while creating only minimal air flow restriction through the system. Periodic cleaning or replacement of the screen shall be all that is required after installation.

The engine shall also include an air intake filter which shall be bolted to the frame and located under the front of the cab on the right hand side. The system shall utilize a replaceable dry type filter which ensures dust and debris remains safely contained inside the housing during operation via leak-tight seals. The service cover shall be located on the bottom of the housing, eliminating the chance of contaminating the air intake system during air filter service.

The air flow distribution and dust loading shall be uniform throughout the high-performance filter element, which shall result in pressure differential for improved horsepower and fuel economy. The air intake ember separator shall be mounted within easy access via a hinged panel behind the right hand side headlight module. The air intake system shall include a restriction indicator light in the warning light cluster on the instrument panel, which shall activate when the air cleaner element requires replacement.

### **AIR INTAKE PROTECTION**

A light duty skid plate shall be supplied for the engine air intake system below the right front side of the cab. The skid plate shall provide protection for the air intake system from light impacts, stones, and road debris.

### **ENGINE EXHAUST SYSTEM**

The exhaust system shall include a diesel particulate filter (DPF), a diesel oxidation catalyst, and a selective catalytic reduction (SCR) catalyst to meet current EPA standards. The selective catalytic reduction catalyst utilizes a diesel exhaust fluid solution consisting of urea and purified water to convert NOx into nitrogen, water, and trace amounts of carbon dioxide. The solution shall be injected into the system through the decomposition tube between the DPF and SCR.

The system shall utilize 0.07 inch thick stainless steel exhaust tubing between the engine turbo and the DPF. Zero leak clamps seal all system joints between the turbo and DPF.

The DPF, the decomposition tube, and the SCR canister through the end of the tailpipe shall be connected with zero leak clamps. The discharge shall terminate horizontally on the right side of the vehicle ahead of the rear tires.

The exhaust system shall be mounted below the frame in the outboard position with the SCR canister in line rearward of the DPF.



# Surprise Fire Dept

## Surprise, AZ

### **DIESEL EXHAUST FLUID TANK**

The exhaust system shall include a molded cross linked polyethylene tank for Diesel Exhaust Fluid (DEF). The tank shall have a capacity of **ten (10) usable gallons** and shall be mounted on the left hand side of the chassis frame behind the batteries below the frame.

The DEF tank shall be designed with capacity for expansion in case of fluid freezing. Engine coolant, which shall be thermostatically controlled, shall be run through lines in the tank to help prevent the DEF from freezing and to provide a means of thawing the fluid if it should become frozen.

The tank fill tube shall be routed under the rear of the cab with the fill neck and splash guard accessible in the top rear step.

### **ENGINE EXHAUST ACCESSORIES**

Two (2) exhaust temperature mitigation devices shall be shipped loose for installation by the body manufacturer on the vehicle. The temperature mitigation devices shall lower the temperature of the exhaust by combining ambient air with the exhaust gasses at the exhaust outlet.

### **ENGINE EXHAUST WRAP**

The exhaust tubing between the engine turbo and the diesel particulate filter (DPF) shall be wrapped with a thermal cover in order to retain the necessary heat for DPF regeneration. The exhaust wrap shall also help protect surrounding components from radiant heat which can be transferred from the exhaust.

### **TRANSMISSION**

The drive train shall include an Allison model EVS 3000 torque converting, automatic transmission which shall include electronic controls. The transmission shall feature two (2) 10-bolt PTO pads located on the converter housing.

The transmission shall include two (2) internal oil filters and Castrol TranSynd™ synthetic TES 295 transmission fluid which shall be utilized in the lubrication of the EVS transmission. An electronic oil level sensor shall be included with the readout located in the shift selector.

The transmission gear ratios shall be:

1st	3.49:1
2nd	1.86:1
3rd	1.41:1
4th	1.00:1
5th	0.75:1
6th	0.65:1 (if applicable)
Rev	5.03:1

### **TRANSMISSION MODE PROGRAMMING**

The transmission, upon start-up, will automatically select a five (5) speed operation. The sixth speed over drive shall be available with the activation of the mode button on the shifting pad.

# Surprise Fire Dept

## Surprise, AZ

### **TRANSMISSION FEATURE PROGRAMMING**

The Allison Gen V-E transmission EVS group package number 127 shall contain the 227 vocational package in consideration of the duty of this apparatus for rescue. This package shall incorporate an automatic neutral with selector override. This feature commands the transmission to neutral when the park brake is applied, regardless of drive range requested on the shift selector. This requires re-selecting drive range to shift out of neutral for the override.

A transmission interface connector shall be provided in the cab. This package shall contain the following input/output circuits to the transmission control module. The Gen V-E transmission shall include prognostic diagnostic capabilities. These capabilities shall include the monitoring of the fluid life, filter change indication, and transmission clutch maintenance.

<u>Function ID</u>	<u>Description</u>	<u>Wire assignment</u>
Inputs		
C	PTO Request	143
F	Aux. Function Range Inhibit (Special)	101/142
Outputs		
G	PTO Enable Output (See Input Function C)	130
S	Neutral Indicator for PTO	145
	Signal Return	103

### **TRANSMISSION SHIFT SELECTOR**

An Allison pressure sensitive range selector touch pad shall be provided and located to the right of the driver within clear view and easy reach. The shift selector shall have a graphical Vacuum Florescent Display (VFD) capable of displaying two lines of text. The shift selector shall provide mode indication and a prognostic indicator (wrench symbol) on the digital display. The prognostics monitor various operating parameters and shall alert you when a specific maintenance function is required.

### **ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR**

The transmission fluid shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal.

### **TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE**

When the auxiliary brake is engaged, the transmission shall automatically shift to second gear to decrease the rate of speed assisting the secondary braking system and slowing the vehicle.

### **TRANSMISSION COOLING SYSTEM**

The transmission shall include a water to oil cooler system located in the cooling loop between the radiator and the engine. The transmission cooling system shall meet all transmission manufacturer requirements. The transmission cooling system shall feature continuous flow of engine bypass water to maintain uninterrupted transmission cooling.

### **TRANSMISSION DRAIN PLUG**

The transmission shall include an original equipment manufacturer installed oil drain plug.

# Surprise Fire Dept

## Surprise, AZ

### **TRANSMISSION WARRANTY**

The Allison EVS series transmission shall be warranted for a period of five (5) years with unlimited mileage. Parts and labor shall be included in the warranty.

### **LH PTO**

A PTO shall be installed on the transmission by the OEM.

### **LH PTO MODEL**

A ten (10) bolt Chelsea model 859-XGFJP-B5XV heavy duty transmission driven PTO shall be installed. The clutched shifted PTO is designed specifically for the Allison world transmission and provides torque ranges from 250 to 335 lb. ft.

### **RH PTO**

A PTO shall be installed on the transmission by the OEM.

### **RH PTO MODEL**

A ten (10) bolt Chelsea **model 280-SGFJP-B5XV** heavy duty transmission driven PTO shall be installed. The clutched shifted PTO is designed specifically for the Allison world transmission and provides torque ranges from 250 to 335 lb. ft.

### **PTO LOCATION**

The transmission shall have two (2) power take off (PTO) mounting locations, one (1) in the 8:00 o'clock position and one (1) in the 1:00 o'clock position.

### **DRIVELINE**

All drivelines shall be heavy duty metal tube and equipped with Spicer 1710 series universal joints. The shafts shall be dynamically balanced prior to installation to alleviate future vibration. In areas of the driveline where a slip shaft is required, the splined slip joint shall be coated with Glide Coat®.

### **DRIVELINE RETARDER**

A Telma electromagnetic driveline retarder shall be focal mounted on the rear axle to act as an auxiliary braking system.

### **MIDSHIP RETARDER CONTROL**

There shall be four (4) stages of activation for the driveline retarder. The first stage shall be 25% activation, the second stage shall be 50% activation, the third stage shall be 75% activation and the fourth stage shall be 100% activation. All four stages shall work off pressure applied to the service brake. The first stage shall activate with 3 PSI of pressure, the second stage shall activate with 5 PSI of pressure, the third stage shall activate with 7 PSI of pressure, and the fourth stage shall activate with 10 PSI of pressure. The driveline retarder shall be controlled by a virtual On/Off switch located on the Vista display. There shall be an indicator light mounted in the instrument panel. The indicator light shall indicate each of the four (4) stages of activation.

# Surprise Fire Dept

## Surprise, AZ

The driveline retarder shall disengage in pump mode or during an ABS event. A positive activation of the driveline retarder shall activate the brake lights.

### **MIDSHIP PUMP / GEARBOX**

A mid-ship split shaft pump shall be installed by the apparatus manufacturer. The chassis manufacturer shall not provide any driveline provisions for the pump installation.

### **FUEL FILTER/WATER SEPARATOR**

The fuel system shall have a Racor S3201T fuel filter/water separator as a primary filter. The fuel filter shall have a drain valve and a see through cover to allow visual inspection of fuel and filter condition.

A secondary fuel filter shall be included as approved by the engine manufacturer.

An instrument panel lamp and audible alarm which indicates when water is present in the fuel-water separator shall also be included.

### **FUEL LINES**

The fuel system supply and return lines installed from the fuel tank to the engine shall be black textile braided lines which are reinforced with braided high tensile steel wire. The fuel lines shall be connected with reusable steel fittings.

### **FUEL SHUTOFF VALVE**

A fuel shutoff valve shall be installed in the fuel draw line, near the fuel tank to allow maintenance to be performed with minimal loss of fuel.

### **ELECTRIC FUEL PRIMER**

Integral to the engine assembly is an electric lift pump that serves the purpose of pre-filter fuel priming.

### **FUEL COOLER**

An aluminum cross flow air to fuel cooler shall be provided to lower fuel temperature allowing the vehicle to operate at higher ambient temperatures. The fuel cooler shall be located above the fuel tank.

### **FUEL TANK**

The fuel tank shall have a capacity of sixty-eight (68) gallons and shall measure 35.00 inches in width X 20.00 inches in height X 24.00 inches in length. The increased height and reduced length allows for the use of a shorter rear frame overhang on the chassis. The baffled tank shall be made of 14 gauge aluminized steel. The exterior of the tank shall be painted with a PRP Corsol™ black anti-corrosive exterior metal treatment finish. This results in a tank which offers the internal and external corrosion resistance.

The tank shall have a vent port to facilitate venting to the top of the fill neck for rapid filling without "blow-back" and a roll over ball check vent for temperature related fuel expansion and draw.

# Surprise Fire Dept

## Surprise, AZ

The tank is designed with dual draw tubes and sender flanges. The tank shall have 2.00 inch NPT fill ports for right or left hand fill. A 0.50 inch NPT drain plug shall be centered in the bottom of the tank.

The fuel tank shall be mounted below the frame, behind the rear axle. Two (2) three-piece strap hanger assemblies with "U" straps bolted midway on the fuel tank front and rear shall be utilized to allow the tank to be easily lowered and removed for service purposes. Rubber isolating pads shall be provided between the tank and the upper tank mounting brackets. Strap mounting studs through the rail, hidden behind the body shall not be acceptable.

### **FUEL TANK FILL PORT**

The fuel tank fill ports shall be offset with the left fill port located in the rearward position and the right fill port located in the middle position on the fuel tank.

### **FUEL TANK SERVICEABILITY PROVISIONS**

The chassis fuel lines shall have additional length provided so the tank can be easily lowered and removed for service purposes. The additional 8.00 feet of length shall be located above the fuel tank and shall be coiled and secured. The fuel line fittings shall be pointed towards the right side (curbside) of the chassis.

### **FRONT AXLE**

The front axle shall be a Meritor Easy Steer Non drive front axle, model number MFS-20. The axle shall include a 3.74 inch drop and a 71.00 inch king pin intersection (KPI). The axle shall include a conventional style hub with a standard knuckle.

### **FRONT AXLE WARRANTY**

The front axle shall be warranted by Meritor for two (2) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

### **FRONT WHEEL BEARING LUBRICATION**

The front axle wheel bearings shall be lubricated with oil. The oil level can be visually checked via clear inspection windows in the front axle hubs.

### **FRONT SHOCK ABSORBERS**

Two (2) Bilstein inert, nitrogen gas filled shock absorbers shall be provided and installed as part of the front suspension system. The shocks shall be a monotubular design and fabricated using a special extrusion method, utilizing a single blank of steel without a welded seam, achieving an extremely tight peak-to-valley tolerance and maintains consistent wall thickness. The monotubular design shall provide superior strength while maximizing heat dissipation and shock life.

The ride afforded through the use of a gas shock is more consistent and shall not deteriorate with heat, the same way a conventional oil filled hydraulic shock would.

The Bilstein front shocks shall include a digressive working piston assembly allowing independent tuning of the compression and rebound damping forces to provide optimum ride and comfort without compromise. The working piston design shall feature fewer parts than most conventional twin tube and "road sensing" shock designs and shall contribute to the durability and long life of the Bilstein shock absorbers.

# Surprise Fire Dept

## Surprise, AZ

Proposals offering the use of conventional twin tube or "road sensing" designed shocks shall not be considered.

### **FRONT SUSPENSION**

The front suspension shall include a nine (9) leaf spring pack in which the longest leaf measures 54.00 inch long and 4.00 inches wide and shall include a military double wrapped front eye. Both spring eyes shall have a case hardened threaded bushing installed with lubrication counter bore and lubrication land off cross bore with grease fitting. The spring capacity shall be rated at 21,500 pounds.

### **STEERING COLUMN/ WHEEL**

The cab shall include a Douglas Autotech steering column which shall include a seven (7) position tilt, a 2.25 inch telescopic adjustment, and an 18.00 inch, four (4) spoke steering wheel located at the driver's position. The steering wheel shall be covered with black polyurethane foam padding.

The steering column shall contain a horn button, self-canceling turn signal switch, four-way hazard switch and headlamp dimmer switch.

### **ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR**

The power steering fluid shall be monitored electronically and shall send a signal to activate an audible alarm and visual warning in the instrument panel when fluid level falls below normal.

### **POWER STEERING PUMP**

The hydraulic power steering pump shall be a TRW PS and shall be gear driven from the engine. The pump shall be a balanced, positive displacement, sliding vane type.

### **FRONT AXLE CRAMP ANGLE**

The chassis shall have a front axle cramp angle of 48-degrees to the left and 44-degrees to the right.

### **POWER STEERING GEAR**

The power steering gear shall be a TRW model TAS 65 with an assist cylinder.

### **CHASSIS ALIGNMENT**

The chassis frame rails shall be measured to insure the length is correct and cross checked to make sure they run parallel and are square to each other. The front and rear axles shall be laser aligned. The front tires and wheels shall be aligned and toe-in set on the front tires by the chassis manufacturer.

### **REAR AXLE**

The rear axle shall be a Meritor model RS-23-186 single drive axle. The axle shall include precision forged, single reduction differential gearing, and shall have a fire service rated capacity of 24,000 pounds.

# Surprise Fire Dept

## Surprise, AZ

The axle shall be built of superior construction and quality components to provide the rugged dependability needed to stand up to the fire industry's demands. The axle shall include rectangular shaped, hot-formed housing with a standard wall thickness of 0.50 of an inch for extra strength and rigidity and a rigid differential case for high axle strength and reduced maintenance.

The axle shall have heavy-duty Hypoid gearing for longer life, greater strength and quieter operation. Industry-standard wheel ends for compatibility with both disc and drum brakes, and unitized oil seal technology to keep lubricant in and help prevent contaminant damage will be used.

### **REAR AXLE DIFFERENTIAL LUBRICATION**

The rear axle differential shall be lubricated with oil.

### **REAR AXLE WARRANTY**

The rear axle shall be warranted by Meritor for two (2) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

### **REAR WHEEL BEARING LUBRICATION**

The rear axle wheel bearings shall be lubricated with oil.

### **VEHICLE TOP SPEED**

The top speed of the vehicle shall be approximately 68 MPH +/-2 MPH at governed engine RPM.

### **REAR SUSPENSION**

The single rear axle shall feature a Reyco 102AR air suspension with a single air bag on each side attached to a tapered forged drop leaf spring with one adjustable and one fixed torque rod.

The suspension shall feature dual air height control valves which shall be installed to ensure equal frame height on both sides of the vehicle regardless of the load. The suspension shall also include two premium shock absorbers, one each side.

The rear suspension capacity shall be rated at 21,000 to 27,000 pounds to meet the rear axle rating selected.

### **REAR SHOCK ABSORBERS**

Shock absorbers shall be supplied by the suspension manufacturer and installed on the rear axle suspension.

### **FRONT TIRE**

The front tires shall be Michelin 365/70R-22.5 20PR "L" tubeless radial XZA highway tread.

The front tire stamped load capacity shall be 21,000 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 125 pounds per square inch.

The Michelin Tire Intermittent Service Rating load capacity shall be 22,500 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 130 pounds per square inch. The Michelin Intermittent Service Rating

# Surprise Fire Dept

## Surprise, AZ

limits the operation of the emergency vehicle to one (1) hour of loaded travel with a one (1) hour cool down prior to another loaded run.

### **REAR TIRE**

The rear tires shall be Michelin 11R-22.5 16PR "H" tubeless radial XDN2 all-weather tread designed for exceptional traction and mileage.

The rear tire stamped load capacity shall be 24,020 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Tire Intermittent Service Rating load capacity shall be 24,820 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch. The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to one (1) hour of loaded travel with a one (1) hour cool down prior to another loaded run.

### **REAR AXLE RATIO**

The rear axle ratio shall be 5.13:1.

### **TIRE PRESSURE INDICATOR**

There shall be a PressurePro™ electronic tire pressure indication transmitter at each valve stem on the vehicle that shall transmit a signal to a display mounted on the left side sun visor with a Velcro® hook and loop mount. The display shall monitor if there is sufficient pressure in each specific tire. The monitor shall have two low pressure alert levels, the first at 12.5% and the second at 25% drop in pressure. The monitor shall also have a variable high pressure alert that can be adjusted by the end user, the high pressure alert shall come set to alert at a 24 pounds per square inch increase. The monitor shall have self-tests for signal strength and sensor packet counts.

### **FRONT WHEEL**

The front wheels shall be Alcoa hub piloted, 22.50 inch X 10.50 inch polished aluminum wheels. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts. The wheels shall feature one-piece forged strength and shall include Alcoa's Dura-Bright® finish with XBR technology as an integral part of the wheel surface. Alcoa Dura-Bright® wheels keep their shine without polishing. Brake dust, grime and road debris are easily removed by simply cleaning the wheels with soap and water.

### **REAR WHEEL**

The outer rear wheels shall be Alcoa hub piloted, 22.50 inch X 8.25 inch LvL One™ aluminum wheels with a polished outer surface and Alcoa Dura-Bright® wheel treatment with XBR® technology as an integral part of the wheel. The inner rear wheels shall be Alcoa hub piloted, 22.50 inch X 8.25 inch aluminum wheels with a LvL One™ bright machine finish. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

### **BALANCE WHEELS AND TIRES**

All of the wheels and tires, including any spare wheels and tire assemblies, shall be dynamically balanced.



# Surprise Fire Dept

## Surprise, AZ

### **BRAKE SYSTEM**

A rapid build-up air brake system shall be provided. The air brakes shall include a two (2) air tank, three (3) reservoir system with a total of 4152 cubic inch of air capacity. A floor mounted treadle valve shall be mounted inside the cab for graduated control of applying and releasing the brakes. An inversion valve shall be installed to provide a service brake application in the unlikely event of primary air supply loss. All air reservoirs provided on the chassis shall be labeled for identification.

The rear axle spring brakes shall automatically apply in any situation when the air pressure falls below 25 PSI and shall include a mechanical means for releasing the spring brakes when necessary. An audible alarm shall designate when the system air pressure is below 60 PSI.

A four (4) sensor, four (4) modulator Anti-lock Braking System (ABS) shall be installed on the front and rear axles in order to prevent the brakes from locking or skidding while braking during hard stops or on icy or wet surfaces. This in turn shall allow the driver to maintain steering control under heavy braking and in most instances, shorten the braking distance. The electronic monitoring system shall incorporate diagonal circuitry which shall monitor wheel speed during braking through a sensor and tone ring on each wheel. A dash mounted ABS lamp shall be provided to notify the driver of a system malfunction. The ABS system shall automatically disengage the auxiliary braking system device when required. The speedometer screen shall be capable of reporting all active defaults using PID/SID and FMI standards.

Additional safety shall be accommodated through Automatic Traction Control (ATC) which shall be installed on the single rear axle. The ATC system shall apply the ABS when the drive wheels loose traction. The system shall scale the electronic engine throttle back to prevent wheel spin while accelerating on ice or wet surfaces.

A virtual style switch shall be provided and properly labeled "mud/snow". When the switch is pressed once, the system shall allow a momentary wheel slip to obtain traction under extreme mud and snow conditions. During this condition the ATC light shall blink continuously notifying the driver of activation. Pressing the switch again shall deactivate the mud/snow feature.

The Electronic Stability Control (ESC) unit is a functional extension of the electronic braking system. It is able to detect any skidding of the vehicle about its vertical axis as well as any rollover tendency. The control unit comprises an angular-speed sensor that measures the vehicle's motion about the vertical axis, caused, for instance, by cornering or by skidding on a slippery road surface. An acceleration sensor measures the vehicle's lateral acceleration. The Controller Area Network (CAN) bus provides information on the steering angle. On the basis of lateral acceleration and steering angle, an integrated microcontroller calculates a theoretical angular speed for the stable vehicle condition.

### **FRONT BRAKES**

The front brakes shall be Meritor EX225 Disc Plus disc brakes with 17.00 inch vented rotors.

### **REAR BRAKES**

The rear brakes shall be Meritor 16.50 inch X 7.00 inch S-cam drum type.

### **PARK BRAKE**

Upon application of the push-pull valve in the cab, the rear brakes will engage via mechanical spring force. This is accomplished by dual chamber rear brakes, satisfying the FMVSS parking brake requirements.

# Surprise Fire Dept

## Surprise, AZ

### **PARK BRAKE CONTROL**

A Meritor-Wabco manual hand control push-pull style valve shall operate the parking brake system. The control shall be yellow in color.

The parking brake actuation valve shall be mounted 6.00 inches to the left of center of the dash within easy access of the driver.

### **REAR BRAKE SLACK ADJUSTERS**

The rear brakes shall include Meritor automatic slack adjusters installed on the axle which features a simple, durable design offering reduced weight. The automatic slack adjusters shall feature a manual adjusting nut which cannot inadvertently be backed off and threaded grease fittings for easy serviceability.

### **AIR DRYER**

The brake system shall include a Wabco System Saver 1200 air dryer with an integral heater with a Metri-Pack sealed connector. The air dryer incorporates an internal turbo cutoff valve that closes the path between the air compressor and air dryer purge valve during the compressor "unload" cycle. The turbo cutoff valve allows purging of moisture and contaminants without the loss of turbo boost pressure. The air dryer shall be mounted behind the battery box on the left hand side.

### **FRONT BRAKE CHAMBERS**

The front brakes shall be provided with MGM type 24 long stroke brake chambers.

### **REAR BRAKE CHAMBERS**

The rear axle shall include TSE 30/30 H.O.T. (High Output Technology) brake chambers shall convert the energy of compressed air into mechanical force and motion. This shall actuate the brake camshaft, which in turn shall operate the foundational brake mechanism forcing the brake shoes against the brake drum. The TSE 30/30 H.O.T. chambers are designed to provide the same performance as 30/36 chambers in a smaller package.

### **AIR COMPRESSOR**

The air compressor provided for the engine shall be a Wabco® SS318 single cylinder pass-through drive type compressor which shall be capable of producing 18.7 CFM at 1200 engine RPMs. The air compressor shall feature a higher delivery efficiency translating to more air delivery per horsepower absorbed. The compressor shall include an aluminum cylinder head which shall improve cooling, reduce weight and decrease carbon formation. Superior piston and bore finishing technology shall reduce oil consumption and significantly increasing the system component life.

### **AIR GOVERNOR**

An air governor shall be provided to control the cut-in and cut-out pressures of the engine mounted air compressor. The governor shall be calibrated to meet FMVSS requirements. The air governor shall be located on the air dryer bracket on the left frame rail behind the battery box.

# Surprise Fire Dept

## Surprise, AZ

### **MOISTURE EJECTORS**

Automatic moisture ejectors with a manual pet-cock type drain provision shall be installed on all reservoirs of the air supply system.

### **AIR SUPPLY LINES**

The air system on the chassis shall be plumbed with color coded reinforced nylon tubing air lines. The primary (rear) brake line shall be green, the secondary (front) brake line red, the parking brake line orange and the auxiliary (outlet) will be blue.

Brass compression type fittings shall be used on the nylon tubing. All drop hoses shall include fiber reinforced neoprene covered hoses.

### **AIR INLET CONNECTION**

An air connection for the shoreline air inlet shall be supplied.

### **AIR INLET LOCATION**

The air inlet shall be installed in the left hand side lower front step in the forward position.

### **PLUMBING AIR INLET CONNECTION**

The air inlet connector shall be plumbed to the air system with a check valve to prevent air from escaping through the inlet connector.

### **AIR INLET/ OUTLET FITTING TYPE**

The air connector supplied shall be a 0.25 inch size Tru-Flate Interchange style manual connection which is compatible with Milton 'T' style, Myers 0.25 inch Automotive style and Parker 0.25 inch 10 Series connectors.

### **AIR TANK SPACERS**

There shall be spacers included with the air tank mounting. The spacers shall move the air tanks 1.50 inches inward towards the center of the chassis. This shall provide clearance between the air tanks and the frame for body U-bolt clearance.

### **WHEELBASE**

The chassis wheelbase shall be 200.50 inches.

### **REAR OVERHANG**

The chassis rear overhang shall be 78.00 inches.

### **FRAME**

The frame shall consist of double rails running parallel to each other with cross members forming a ladder style frame. The frame rails shall be formed in the shape of a "C" channel, with the outer rail measuring 10.25 inches

# Surprise Fire Dept

## Surprise, AZ

high X 3.50 inches deep upper and lower flanges X 0.38 inches thick with an inner channel of 9.44 inches high X 3.13 inches deep and 0.38 inches thick. Each rail shall be constructed of 110,000 psi minimum yield high strength low alloy steel. Each double rail section shall be rated by a Resistance Bending Moment (RBM) minimum of 3,213,100 inch pounds and have a minimum section modulus of 29.21 cubic inches. The frame shall measure 35.00 inches in width.

Proposals calculating the frame strength using the "box method" shall not be considered.

Proposals including heat treated rails shall not be considered. Heat treating frame rails produces rails that are not uniform in their mechanical properties throughout the length of the rail. Rails made of high strength, low alloy steel are already at the required yield strength prior to forming the rail.

A minimum of seven (7) fully gusseted 0.25 inch thick cross members shall be installed. The inclusion of the body mounting, or bumper mounting shall not be considered as a cross member. The cross members shall be attached using zinc coated grade 8 fasteners. The bolt heads shall be flanged type, held in place by distorted thread flanged lock nuts. Each cross member shall be mounted to the frame rails utilizing a minimum of 0.25 inch thick gusset reinforcement plates at all corners balancing the area of force throughout the entire frame.

Any proposals not including additional reinforcement for each cross member shall not be considered.

All relief areas shall be cut in with a minimum 2.00 inch radius at intersection points with the edges ground to a smooth finish to prevent a stress concentration point.

The frame and cross members shall carry a lifetime warranty to the original purchaser. A copy of the frame warranty shall be made available upon request.

Proposals offering warranties for frames not including cross members shall not be considered.

### **FRAME WARRANTY**

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN CHASSIS, INC. LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The frame and cross members shall carry a limited lifetime warranty to the original purchaser. The warranty period shall commence on the date the vehicle is delivered to the first end user.

### **FRAME CLEAR AREA**

The chassis frame shall be left clear of chassis mounted components inside or outside the frame rails within the first 30.00 inches behind the cab to allow space for OEM installed components. Cross members may be installed in the clear area if required for proper frame or driveline configuration.

### **FRAME PAINT**

The frame shall be powder coated black prior to any attachment of components.

# Surprise Fire Dept

## Surprise, AZ

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 shall not have a fail of more than ten (10) squares. The pencil hardness test per ASTM D3363 shall have a final post-curved pencil hardness of H-2H. The direct impact resistance test per ASTM D2794 shall have an impact resistance of 120.00 inches per pound at 2 mils.

Any proposals offering painted frame with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

### **FRONT BUMPER**

A one piece, two (2) rib wrap-around style, polished stainless steel front bumper shall be provided. The material shall be 10 gauge 304 stainless steel, 12.00 inches high and 99.00 inches wide.

### **FRONT BUMPER EXTENSION LENGTH**

The front bumper shall be extended approximately 28.00 inches ahead of the cab.

### **FRONT BUMPER EXTENSION FRAME WIDTH**

The front bumper extension frame shall feature an overall width of 48.25 inches.

### **FRONT BUMPER APRON**

The 28.00 inch extended front bumper shall include an apron constructed of 0.19 inch thick embossed aluminum tread plate.

The apron shall be installed between the bumper and the front face of the cab affixed using stainless steel bolts attaching the apron to the top bumper flange.

**NOTE: the bumper gravel shield shall be installed by SVI.**

### **MECHANICAL SIREN**

**A Federal Q2B™ siren shall be provided and installed by SVI.**

### **AIR HORN**

The front bumper shall include two (2) Hadley brand E-Tone air horns which shall measure 21.00 inches long with a 6.00 inch round flare. The air horns shall be trumpet style with a chrome finish on the exterior and a painted finish deep inside the trumpet.

### **AIR HORN LOCATION**

The air horns shall be recess mounted in the front bumper face, one (1) on the right side of the bumper in the inboard position relative to the right hand frame rail and one (1) on the left side of the bumper in the inboard position relative to the left hand frame rail.

**NOTE: Air horns shall be shipped loose by Spartan, and installed by SVI.**

### **AIR HORN RESERVOIR**

One (1) air reservoir, with a 2084 cubic inch capacity, shall be installed on the chassis to act as a supply tank for operating air horns. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

# Surprise Fire Dept

## Surprise, AZ

### **ELECTRONIC SIREN SPEAKER**

There shall be two (2) Cast Products Inc. model SA4301, 100 watt speakers provided. Each speaker shall measure 6.20 inches tall X 7.36 inches wide X 3.06 inches deep. Each speaker shall include a flat mounting flange which shall be polished aluminum.

### **ELECTRONIC SIREN SPEAKER LOCATION**

The two (2) electronic siren speakers shall be located on the front bumper face outboard of the frame rails with one (1) on the right side and one (1) on the left side in the outboard positions.

### **FRONT BUMPER TOW HOOKS**

Two (2) heavy duty tow hooks, painted to match the chassis frame, shall be installed in a rearward position out of the approach angle area, bolted directly to the side of the chassis frame with grade 8 bolts.

### **CAB HEIGHT ADJUSTMENT**

The cab shall include 0.75 inch thick shims raising the cab to provide additional clearance under the cab.

### **CAB TILT SYSTEM**

The entire cab shall be capable of tilting approximately 45-degrees to allow for easy maintenance of the engine and transmission. The cab tilt pump assembly shall be located on the right side of the chassis above the battery box.

The electric-over-hydraulic lift system shall include an ignition interlock and red cab lock down indicator lamp on the tilt control which shall illuminate when holding the "Down" button to indicate safe road operation.

It shall be necessary to activate the master battery switch and set the parking brake in order to tilt the cab. As a third precaution the ignition switch must be turned off to complete the cab tilt interlock safety circuit.

Two (2) spring-loaded hydraulic hold down hooks located outboard of the frame shall be installed to hold the cab securely to the frame. Once the hold-down hooks are set in place, it shall take the application of pressure from the hydraulic cab tilt lift pump to release the hooks.

Two (2) cab tilt cylinders shall be provided with velocity fuses in each cylinder port. The cab tilt pivots shall be 1.90 inch ball and be anchored to frame brackets with 1.25 inch diameter studs.

A steel safety channel assembly, painted safety yellow shall be installed on the right side cab lift cylinder to prevent accidental cab lowering. The safety channel assembly shall fall over the lift cylinder when the cab is in the fully tilted position. A cable release system shall also be provided to retract the safety channel assembly from the lift cylinder to allow the lowering of the cab.

### **CAB TILT CONTROL RECEPTACLE**

The cab tilt control cable shall include a receptacle which shall be temporarily located on the right hand chassis rail rear of the cab to provide a place to plug in the cab tilt remote control pendant. The tilt pump shall include 8.00 feet of cable with a six (6) pin Deutsch receptacle with a cap.

# Surprise Fire Dept

## Surprise, AZ

The remote control pendant shall include 20.00 feet of cable with a mating Deutsch connector. The remote control pendant shall be shipped loose with the chassis.

### **CAB WINDSHIELD**

The cab windshield shall have a surface area of 2825.00 square inches and be of a two (2) piece wraparound design for maximum visibility.

The glass utilized for the windshield shall include standard automotive tint. The left and right windshield shall be fully interchangeable thereby minimizing stocking and replacement costs.

Each windshield shall be installed using black self locking window rubber.

### **GLASS FRONT DOOR**

The front cab doors shall include a window which is 27.00 inches in width X 26.00 inches in height. These windows shall have the capability to roll down completely into the door housing. This shall be accomplished manually utilizing a crank style handle on the inside of the door. A reinforced window regulator assembly shall be provided for severe duty use.

There shall be an irregular shaped fixed window which shall measure 2.50 inches wide at the top, 8.00 inches wide at the bottom X 26.00 inches in height, more commonly known as "cozy glass" ahead of the front door roll down windows.

The windows shall be mounted within the frame of the front doors trimmed with a black anodized ring on the exterior.

### **GLASS TINT FRONT DOOR**

The windows located in the left and right front doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

### **GLASS REAR DOOR RH**

The rear right hand side door shall include a window which is 27.00 inches in width X 26.00 inches in height. This window shall roll up and down manually utilizing a crank style handle on the inside of the door. A reinforced window regulator assembly shall be provided for severe duty use.

### **GLASS TINT REAR DOOR RIGHT HAND**

The window located in the right hand side rear window shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

# Surprise Fire Dept

## Surprise, AZ

### **GLASS REAR DOOR LH**

The rear left hand side door shall include a window which is 27.00 inches in width X 26.00 inches in height. This window shall roll up and down manually utilizing a crank style handle on the inside of the door. A reinforced window regulator assembly shall be provided for severe duty use.

### **GLASS TINT REAR DOOR LEFT HAND**

The window located in the left hand side rear door shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

**NOTE: THERE SHALL BE NO TINTING INSTALLED IN FRONT OF THE BATTERY DISPLAY GAUGE.**

### **GLASS SIDE MID RH**

The cab shall include a window on the right side behind the front and ahead of the crew door which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

### **GLASS TINT SIDE MID RIGHT HAND**

The window located on the right hand side of the cab between the front and rear doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

### **GLASS SIDE MID LH**

The cab shall include a window on the left side behind the front door and ahead of the crew door and above the wheel well which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

### **GLASS TINT SIDE MID LEFT HAND**

The window located on the left hand side of the cab between the front and rear doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

### **CLIMATE CONTROL**

A ceiling mounted SGM combination defroster and cabin heating and air conditioning system shall be located above the engine tunnel area. The system covers and plenums shall be of severe duty design made of aluminum which shall be coated with a customer specified interior paint. The design of the system's covers shall provide quick access to washable air intake filters as well as easy access to other serviceable items.

The air delivery plenums provide targeted airflow directly to the vehicle occupants. Six (6) adjustable louvers will provide comfort for the front seat occupants and ten (10) adjustable louvers will provide comfort for the rear crew occupants.



# Surprise Fire Dept

## Surprise, AZ

The system shall be capable of producing up to 12 FPM of air velocity at all occupant seating positions. Separate front and rear blower motors shall be of brushless design and shall be controlled independently. It shall be capable of reducing the interior cabin air temperature from 122° F (+/- 3° F) to 80° F in thirty minutes with 50% relative humidity and full solar load as described in SAE J2646.

The system shall also provide heater pull up performance which meets or exceeds the performance requirements of SAE J1612 as well as defrost performance that meets or exceeds the performance requirements of SAE J381.

A gravity drain system shall be provided that is capable of evacuating condensate from the vehicle while on a slope of up to a 13% grade in any direction.

The air conditioning system plumbing shall be a mixture of custom bent zinc coated steel fittings and Aeroquip GH134 flexible hose with Aeroquip EZ-Clip fittings.

The overhead heater/defroster plumbing shall include an electronic flow control valve that re-directs hot coolant away from the evaporator, via a bypass loop, as the temperature control is moved toward the cold position.

Any component which needs to be accessed to perform system troubleshooting shall be accessible by one person using basic hand tools. Regularly serviced items shall be replaceable by one person using basic hand tools.

*\*\*Performance data is based on testing performed by an independent third party test facility using a medium four-door 10" Raised roof Gladiator chassis equipped with an ISL engine.*

### **CLIMATE CONTROL DRAIN**

The climate control system shall include a venturi pump for water management. The venturi pump drain shall remove condensation from the air conditioning system.

### **CLIMATE CONTROL ACTIVATION**

The heating, defrosting and air conditioning controls shall be on the dash next to driver panel, in a position which is easily accessible to the driver. The climate control shall be activated by a rotary switch.

### **HVAC OVERHEAD COVER PAINT**

The overhead HVAC cover shall be painted with a Zolatone onyx-black texture finish.

### **A/C CONDENSER LOCATION**

A roof mounted A/C condenser shall be installed centered on the cab forward of the raised roof against the slope rise.

### **A/C COMPRESSOR**

The air-conditioning compressor shall be a belt driven, engine mounted, open type compressor that shall be capable of producing a minimum of 32,000 BTU at 1500 engine RPMs. The compressor shall utilize R-134A refrigerant and PAG oil.

# Surprise Fire Dept

## Surprise, AZ

### **UNDER CAB INSULATION**

The underside of the cab tunnel surrounding the engine and the underside of the entire cab floor shall be lined with multi-layer insulation, engineered for application inside diesel engine compartments. In addition the insulation shall have an expanded aluminum overlay installed to assist in retaining the insulation tight against the engine tunnel surfaces and the underside of the cab floor.

The insulation shall act as a noise barrier, absorbing noise thus keeping the decibel level in the cab well within NFPA recommendations. As an additional benefit, the insulation shall assist in sustaining the desired temperature within the cab interior.

The engine tunnel insulation shall measure approximately 0.75 inch thick including a vertically lapped polyester fiber layer, a 1.0 lb/ft<sup>2</sup> PVC barrier layer, an open cell foam layer, and a moisture and heat reflective foil facing reinforced with a woven fiberglass layer. The foil surface acts as protection against moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.

The cab floor insulation shall measure 0.56 inch thick including a 1.0#/sf PVC barrier and a moisture and heat reflective foil facing, reinforced with fiberglass strands. The foil surface acts as protection against moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.

The insulation shall be cut precisely to fit each section and sealed for additional heat and sound deflection. The insulation shall be held in place by 3 mils of acrylic pressure sensitive adhesive and aluminum pins with hard hat, hold in place fastening heads.

### **INTERIOR TRIM FLOOR**

The floor of the cab shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive and aluminum trim molding. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.

### **INTERIOR TRIM**

The cab interior shall include trim on the front ceiling, rear crew ceiling, and the cab walls. It shall be easily removable to assist in maintenance. The trim shall be constructed of insulated vinyl over a hard board backing.

### **REAR WALL INTERIOR TRIM**

The rear wall of the cab shall be trimmed with vinyl.

### **HEADER TRIM**

The cab interior shall feature header trim over the driver and officer dash constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum.

### **TRIM CENTER DASH**

The main center dash area shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate. There shall be four (4) holes located on the top of the dash near each outer edge of the electrical access cover for ventilation.

# Surprise Fire Dept

## Surprise, AZ

### **TRIM LH DASH**

The left hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate for a perfect fit around the instrument panel. For increased occupant protection the extreme duty left hand dash utilizes patent pending break away technology to reduce rigidity in the event of a frontal crash. The left hand dash shall offer lower vertical surface area to the left and right of the steering column to accommodate control panels.

### **TRIM RH DASH**

The right hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate and shall include a glove compartment with a hinged door and a Mobile Data Terminal (MDT) provision. The glove compartment size will measure 14.00 inches wide X 6.38 inches high X 5.88 inches deep. The MDT provision shall be provided above the glove compartment.

### **ENGINE TUNNEL TRIM**

The cab engine tunnel shall be covered with a multi-layer mat consisting of 0.25 inch closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The mat shall be held in place by pressure sensitive adhesive. The engine tunnel mat shall be trimmed with anodized aluminum stair nosing trim for an aesthetically pleasing appearance.

### **POWER POINT DASH MOUNT**

The cab shall include two (2) 12 volt cigarette lighter type receptacles in the dash to provide a power source for 12 volt electrical equipment. The receptacles shall be wired battery direct.

### **AUXILIARY POWER POINT ENGINE TUNNEL**

The cab interior shall include two (2) 12 volt cigarette lighter type receptacles to provide power sources for 12 volt electrical equipment. The receptacles shall be connected directly to the batteries. The receptacles shall be located on the rear of the engine tunnel near the top, one (1) near the left corner and one (1) near the right corner.

### **STEP TRIM**

Each cab entry door shall include a three step entry. The first step closest to the ground shall be constructed of polished 5052 H32 aluminum Grip Strut® grating with angled outer corners. The grating shall allow water and other debris to flow through rather than becoming trapped within the stepping surface. The lower step shall be mounted to a frame which is integral with the construction of the cab for rigidity and strength. The middle step shall be integral with the cab construction and shall be trimmed in 0.08 inch thick 3003-H22 embossed aluminum tread plate.

### **STEP TRIM KICKPLATE**

The cab steps shall include a kick plate in the rise of each step. The risers shall be trimmed in brushed stainless steel. **TO BE SVI FURNISHED.**

### **UNDER CAB ACCESS DOOR**

The cab shall include an access door in the left crew step riser constructed of smooth aluminum painted with a push and turn latch. The under cab access door shall provide access to the diesel exhaust fluid fill.

# Surprise Fire Dept

## Surprise, AZ

### **INTERIOR DOOR TRIM**

The interior trim on the doors of the cab shall consist of an aluminum panel constructed of Marine Grade 5052-H32 0.13 of an inch thick aluminum plate. The door panels shall include a painted finish.

### **DOOR TRIM KICKPLATE**

The inner door panels shall include an aluminum embossed tread kick plate which shall be fastened to the lower portion of the door panels.

### **DOOR TRIM CUSTOMER NAMEPLATE**

The interior door trim on the front doors shall include a customer nameplate which states the vehicle was custom built for their Department.

### **CAB DOOR TRIM REFLECTIVE**

The interior of each door shall include high visibility reflective tape. A white reflective tape shall be provided vertically along the rear outer edge of the door. The lowest portion of each door skin shall include a reflective tape chevron with red and white stripes and a Spartan logo. The chevron tape shall measure 6.00 inches in height.

### **INTERIOR GRAB HANDLE "A" PILLAR**

A grab handle on the inside of the cab on the hinge post at the driver and officer doors shall be omitted.

### **INTERIOR GRAB HANDLE FRONT DOOR**

Each front door shall include one (1) ergonomically contoured 9.00 inch cast aluminum handle mounted horizontally on the interior door panels. The handles shall feature a textured black powder coat finish to assist personnel entering and exiting the cab.

### **INTERIOR GRAB HANDLE REAR DOOR**

A black powder coated cast aluminum assist handle shall be provided on the inside of each rear crew door. A 30.00 inch long handle shall extend horizontally the width of the window just above the window sill. The handle shall assist personnel in exiting and entering the cab.

### **INTERIOR SOFT TRIM COLOR**

The cab interior soft trim surfaces shall be black in color.

### **INTERIOR TRIM SUNVISOR**

The header shall include two (2) sun visors, one each side forward of the driver and officer seating positions above the windshield. Each sun visor shall be constructed of Masonite and covered with padded vinyl trim.

### **INTERIOR FLOOR MAT COLOR**

The cab interior floor mat shall be black in color.

# Surprise Fire Dept

## Surprise, AZ

### **CAB PAINT INTERIOR DOOR TRIM**

The inner door panel surfaces shall be painted with Zolatone onyx/black texture finish.

### **HEADER TRIM INTERIOR PAINT**

The metal surfaces in the header area shall be coated with Zolatone onyx/black texture finish.

### **TRIM CENTER DASH INTERIOR PAINT**

The entire center dash shall be coated with Zolatone onyx/black texture finish. Any accessory pods attached to the dash shall also be painted this color.

### **TRIM LEFT HAND DASH INTERIOR PAINT**

The left hand dash shall be painted with Zolatone onyx/black texture finish.

### **TRIM RIGHT HAND DASH INTERIOR PAINT**

The right hand dash shall be painted with Zolatone onyx/black texture finish.

### **DASH PANEL GROUP**

The main center dash area shall include three (3) removable panels located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer.

### **SWITCHES CENTER PANEL**

The center dash panel shall include no rocker switches or legends.

### **SWITCHES LEFT PANEL**

The left dash panel shall include one (1) windshield wiper/washer control switch located in the left hand side of the panel. The switch shall have backlighting provided.

### **SWITCHES RIGHT PANEL**

The right dash panel shall include no rocker switches or legends.

### **SEAT BELT WARNING**

A Weldon seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the cab. The system shall provide a visual warning indicator in the Vista display and control screen(s), an indicator light in the instrument panel, and an audible alarm.

The warning system shall activate when any seat is occupied with a minimum of 60 pounds, the corresponding seat belt remains unfastened, and the park brake is released. The warning system shall also activate when any seat is occupied, the corresponding seat belt was fastened in an incorrect sequence, and the park brake is released. Once activated, the visual indicators and audible alarm shall remain active until all occupied seats have the seat belts fastened.

# Surprise Fire Dept

## Surprise, AZ

### **SEAT MATERIAL**

The seats shall include a covering of high strength, wear resistant fabric made of durable ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Common trade names for this material are Imperial 1200 and Durawear.

### **SEAT COLOR**

All seats supplied with the chassis shall be black in color. All seats shall include red seat belts.

### **SEAT BACK LOGO**

The seat backs shall include the logo for the Surprise Fire Department of Surprise, Arizona. The logo shall be centered on the standard headrest of the seat back and on the left side of a split headrest.

### **SEAT DRIVER**

The driver's seat shall be an H.O. Bostrom Sierra model seat with air suspension. The four-way seat shall feature 3.00 inch vertical travel air suspension and manual fore and aft adjustment with 5.00 inches of travel. The suspension control shall be located on the seat below the left front corner of the bottom cushion. The seat shall also feature integral springs to isolate shock.

The seat position shall include a three-point shoulder harness with lap belt and an automatic retractor attached to the cab. The buckle portion of the seat belt shall be mounted on a semi-rigid stalk extending from the seat base within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 37.00 inches measured with the seat suspension height adjusted to the upper limit of its travel.

This model of seat shall have successfully completed the static load tests set forth by FMVSS 207, 209, and 210 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity.

The materials used in construction of the seat shall also have successfully completed testing with regard to the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which dictates the allowable burning rate of materials in the occupant compartments of motor vehicles.

### **SEAT BACK DRIVER**

The driver's seat shall feature a two (2) way adjustable lumbar support and offer an infinite fully reclining adjustable titling seat back. The seat back shall also feature a contoured head rest.

### **SEAT MOUNTING DRIVER**

The driver's seat shall be installed in an ergonomic position in relation to the cab dash.

### **SEAT OFFICER**

The officer's seat shall be an H.O. Bostrom Sierra model seat with air suspension. The four-way seat shall feature 3.00 inch vertical travel air suspension and manual fore and aft adjustment with 5.00 inches of travel. The

# Surprise Fire Dept

## Surprise, AZ

suspension control shall be located on the seat below the left front corner of the bottom cushion. The seat shall also feature integral springs to isolate shock.

The seat position shall include a three-point shoulder harness with lap belt and an automatic retractor attached to the cab. The buckle portion of the seat belt shall be mounted on a semi-rigid stalk extending from the seat base within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 37.00 inches measured with the seat suspension height adjusted to the upper limit of its travel.

This model of seat shall have successfully completed the static load tests set forth by FMVSS 207, 209, and 210 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity.

The materials used in construction of the seat shall also have successfully completed testing with regard to the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which dictates the allowable burning rate of materials in the occupant compartments of motor vehicles.

### **SEAT BACK OFFICER**

The officer's seat shall feature a SecureAll™ SCBA locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto- locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

### **SEAT MOUNTING OFFICER**

The officer's seat shall be installed in an ergonomic position in relation to the cab dash.

### **SEAT BELT ORIENTATION CREW**

The crew position seat belts shall follow the standard orientation which extends from the outboard shoulder extending to the inboard hip.

### **SEAT REAR FACING OUTER LOCATION**

The crew area shall include two (2) rear facing crew seats, which include one (1) located directly behind the left side front seat and one (1) located directly behind the right side front seat.

# Surprise Fire Dept

## Surprise, AZ

### **SEAT CREW REAR FACING OUTER**

The crew area shall include a seat in the rear facing outboard position which shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion. The seat and cushion shall be spring load hinged and compact in design for additional room and shall remain in the stored position until occupied.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

### **SEAT BACK REAR FACING OUTER**

The rear facing outboard seat shall feature a Bostrom SecureAll™ self contained breathing apparatus (SCBA) locking system which shall store most U.S. and International SCBA brands and bottle sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the center of the bottom seat cushion for easy access and to eliminate hooking the release handle with clothing or other equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

### **SEAT MOUNTING REAR FACING OUTER**

The rear facing outer seats shall offer special mounting positions which shall be 2.00 inches towards the rear wall offering additional space between the front seats and the outer rear facing seats.



# Surprise Fire Dept

## Surprise, AZ

### **SEAT FORWARD FACING CENTER LOCATION**

The crew area shall include two (2) forward facing center crew seats with both located at the center of the rear wall.

### **SEAT CREW FORWARD FACING CENTER**

The crew area shall include a seat in the forward facing center position which shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion. **The seat shall have a forward/aft adjustment.**

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

### **SEAT BACK FORWARD FACING CENTER**

The seat back in the rear facing center position shall be comprised of a standard seat back. The seat back shall feature an all belts to seat (ABTS) style safety restraint. The ABTS feature shall include a red, three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The seat back shall feature a contoured, adjustable head rest.

### **ARMREST FOWARD FACING CENTER**

All forward facing center crew seat positions shall include armrests on the inboard and outboard side of each seat. Each armrest shall be covered with black urethane material and shall be an integral part of the seat.

### **SEAT FRAME FORWARD FACING**

The forward facing center seating positions shall include an enclosed seat frame located and installed on the rear wall. The seat frame shall measure 48.00 inches wide X 12.38 inches high X 22.00 inches deep. The seat frame shall be constructed of Marine Grade 5052-H32 0.19 inch thick aluminum plate. The seat box shall be painted the same color as the remaining interior.

# Surprise Fire Dept

## Surprise, AZ

### **SEAT FRAME FORWARD FACING STORAGE ACCESS**

There shall be two (2) access points to the storage area one (1) each side of the seat frame. Each access point shall be covered by a hinged door which measures 18.00 inches wide X 8.63 inches high to allow access for storage in the seat box. The access door hinges shall be at the rear edge of the doors.

### **SEAT MOUNTING FORWARD FACING CENTER**

The forward facing center seats shall offer a special mounting. The seats shall be installed a **minimum of 9.00** inches apart offering additional room for each occupant.

### **CAB FRONT UNDERSEAT STORAGE ACCESS**

The left and right under seat storage areas shall have a solid aluminum hinged door with non-locking latch.

### **SEAT COMPARTMENT DOOR FINISH**

All underseat storage compartment access doors shall have a Zolatone onxy/black texture finish.

### **WINDSHIELD WIPER SYSTEM**

The cab shall include a dual arm wiper system which shall clear the windshield of water, ice and debris. There shall be two (2) windshield wipers which shall be affixed to a radial wet arm. The system shall include a single motor which shall initiate the arm in which both the left hand and right hand windshield wipers are attached, initiating a back and forth motion for each wiper. The wiper motor shall be activated by an intermittent wiper control located within easy reach of the driver's position.

### **ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR**

The windshield washer fluid level shall be monitored electronically. When the washer fluid level becomes low the yellow "Check Message Center" indicator light on the instrument panel shall illuminate and the message center in the dual air pressure gauge shall display a "Check Washer Fluid Level" message.

### **CAB DOOR HARDWARE**

The cab entry doors shall be equipped with exterior pull handles, suitable for use while wearing firefighter gloves. The handles shall be made of aluminum with a chrome plated finish.

The interior exit door handles shall be flush paddle type with a black finish, which are incorporated into the upper door panel.

All cab entry doors shall include locks which are keyed alike. The door locks shall be designed to prevent accidental lockout.

The exterior pull handles shall include a scuff plate behind the handle constructed of polished stainless steel to help protect the cab finish.

### **DOOR LOCKS**

The cab entry doors shall include a Controller Area Network (CAN) based electronic door lock system which shall include two (2) external keypads, one (1) located on the left side next to the front grab handle and one (1) on the right side next to the front grab handle. There shall be one (1) red rocker switch provided on the inside of each

# Surprise Fire Dept

## Surprise, AZ

front cab entry door to actuate the cab door locks. Each door lock may also be manually actuated from the inside of the cab by means of a red knob located on the paddle handle of the respective door. The electronic door lock system shall include four (4) key fobs for actuation with buttons for cab entry door locks and for compartment door locks.

When the doors are unlocked using the external keypad or the key fobs the interior dome lights shall illuminate and remain on for a period of twenty (20) seconds.

Wiring shall also be provided for up to four (4) exterior cab compartments and up to four (4) body compartments.

### **DOOR LOCK LH REAR CAB COMPARTMENT**

The left hand side rear compartment shall feature a power door lock actuator.

### **DOOR LOCK RH REAR CAB COMPARTMENT**

The right hand side rear compartment shall feature a power door lock actuator.

### **GRAB HANDLES**

The cab shall include one (1) 24.00 inch knurled, anti-slip, one-piece exterior assist handle behind each cab door. The grab handle shall be made of 14 gauge 304- stainless steel and be 1.25 inch diameter to enable non-slip assistance with a gloved hand.

### **POWER DOOR LOCK COMPARTMENT ACTIVATION**

The power door lock feature shall include activation for exterior compartment door locks through the key fob, keypads and through a virtual switch on the multiplex display.

### **REARVIEW MIRRORS**

**Ramco model 6015-PCHR bus style mirrors shall be provided.** The mirror heads shall be polished cast aluminum and shall measure 9.75 inches wide X 13.00 inches high. The mirrors shall be mounted one (1) on each front cab corner radius below the windshield with 15.00 inch long polished cast aluminum arms.

The mirrors shall feature an upper remote controlled heated flat glass and a lower remote controlled heated convex glass. The mirror control switches shall be located within easy reach of the driver. The mirrors shall be manufactured using the finest quality non-glare glass and shall feature a rigid mounting thereby reducing vibration. The mirrors shall be corrosion free under all weather conditions.

### **EXTERIOR TRIM REAR CORNER**

There shall be mirror finish stainless steel scuff plates on the outside corners at the back of the cab. The stainless steel plate shall be affixed to the cab using two sided adhesive tape.

### **CAB FENDER**

Full width wheel well liners shall be installed on the extruded cab to limit road splash and enable easier cleaning. Each two-piece liner shall consist of an inner liner 16.00 inches wide made of vacuum formed ABS composite and an outer fenderette 3.50 inches wide made of 14 gauge 304 polished stainless steel.

# Surprise Fire Dept

## Surprise, AZ

### **MUD FLAPS FRONT**

The front wheel wells shall have mud flaps installed on them.

### **CAB EXTERIOR FRONT & SIDE EMBLEMS**

The cab shall include three (3) Spartan Chassis emblems. There shall be one (1) installed on the front air intake grille and one (1) emblem with an integrated model nameplate installed on the exterior of the cab on the lower forward portion of the front driver and officer side doors. **Shipped loose from Spartan.**

### **CAB EXTERIOR MODEL NAMEPLATE**

The cab shall include custom "Metro Star" nameplates integrated into the side emblem. **Shipped loose from Spartan.**

### **IGNITION**

A master battery system with a keyless start ignition system shall be provided. Each system shall be controlled by a one-quarter turn Cole Hersee switch, both of which shall be mounted to the left of the steering wheel on the dash. A chrome push type starter button shall be provided adjacent to the master battery and ignition switches.

Each switch shall illuminate a green LED indicator light on the dash when the respective switch is placed in the "ON" position.

The starter button shall only operate when both the master battery and ignition switches are in the "ON" position.

### **BATTERY**

**The single start electrical system shall include six (6) Deka 9A31 925 CCA absorbed glass mat batteries with a 190 minute reserve capacity and 4/0 welding type dual path starter cables per SAE J541.**

### **BATTERY TRAY**

The batteries shall be installed within two (2) steel battery trays located on the left side and right side of the chassis, securely bolted to the frame rails. The battery trays shall be coated with the same material as the frame.

The battery trays shall include drain holes in the bottom for sufficient drainage of water. A durable, non-conducting, interlocking mat made by Dri-Dek shall be installed in the bottom of the trays to allow for air flow and help prevent moisture build up. The batteries shall be held in place by non-conducting phenolic resin hold down boards.

### **BATTERY BOX COVER**

Each battery box shall include a steel cover which protects the top of the batteries. Each cover shall include flush latches which shall keep the cover secure as well as a black powder coated handle for convenience when opening.

### **BATTERY CABLE**

The starting system shall include cables which shall be protected by 275 degree F. minimum high temperature flame retardant loom, sealed at the ends with heat shrink and sealant.

# Surprise Fire Dept

## Surprise, AZ

### **BATTERY JUMPER STUD**

The starting system shall include battery jumper studs. These studs shall be located on the rear face of the left hand battery tray. The studs shall allow the vehicle to be jump started, charged, or the cab to be raised in an emergency in the event of battery failure.

### **ALTERNATOR**

The charging system shall include a 320 amp Leece-Neville 12 volt alternator. The alternator shall include a self-exciting integral regulator.

### **BATTERY CONDITIONER**

A Kussmaul 1200 Pump Plus battery conditioner shall be supplied. The battery conditioner shall be mounted in the cab in the LH rear facing outer seating position.

### **BATTERY CONDITIONER DISPLAY**

A Kussmaul battery conditioner display shall be supplied. The battery conditioner display shall be mounted in the cab, viewable through the cab mid side window behind the left front door.

### **AUXILIARY AIR COMPRESSOR**

A Kussmaul Pump 12V air compressor shall be supplied. The air compressor shall be installed behind the driver's seat. The air compressor shall be plumbed to the air brake system to maintain air pressure.

### **ELECTRICAL INLET**

A Kussmaul 20 amp super auto-eject electrical receptacle shall be supplied. It shall automatically eject the plug when the starter button is depressed.

A single item or an addition of multiple items must not exceed the rating of the electric inlet that it's connected to.

#### **Amp Draw Reference List:**

*Kussmaul 1000 Charger - 3.5 Amps*

*Kussmaul 1200 Charger - 10 Amps*

*Kussmaul 35/10 Charger - 10 Amps*

*1000W Engine Heater - 8.33 Amps*

*1500W Engine Heater - 12.5 Amps*

*120V Air Compressor - 4.2 Amps*

### **ELECTRICAL INLET LOCATION**

An electrical inlet shall be installed on the left hand side of cab over the wheel well.

### **ELECTRICAL INLET CONNECTION**

The electrical inlet shall be connected to the battery conditioner.

### **ELECTRICAL INLET COLOR**

The electrical inlet connection shall include a red cover.

# Surprise Fire Dept

## Surprise, AZ

### **HEADLIGHTS**

The cab front shall include four (4) rectangular halogen headlamps with separate high and low beams mounted in bright chrome bezels.

### **FRONT TURN SIGNALS**

The front fascia shall include two (2) Whelen model 600 4.00 inch X 6.00 inch programmable LED amber turn signals which shall be installed in a chrome bezel outboard of the front warning and headlamps.

### **HEADLIGHT LOCATION**

The headlights shall be located on the front fascia of the cab directly below the front warning lights.

### **SIDE TURN/MARKER LIGHTS**

The sides of the cab shall include two (2) LED round side marker lights which shall be provided just behind the front cab radius corners.

### **MARKER AND ICC LIGHTS**

In accordance with FMVSS, there shall be five (5) LED cab marker lamps designating identification, center and clearance provided. These lights shall be installed on the face of the cab within full view of other vehicles from ground level.

### **HEADLIGHT AND MARKER LIGHT ACTIVATION**

The headlights and marker lights shall be controlled via a virtual button on the Vista display. There shall be a virtual dimmer control on the Vista display to adjust the brightness of the dash lights. The headlamps and markers lamps shall illuminate to 100% brilliance when the ignition switch is in the "On" position.

**NOTE: Headlights shall be programmed to turn OFF when the parking brake is set thru the VMUX display.**

### **GROUND LIGHTS**

Each door shall include one (1) On-Scene brand Night Axe LED strip model ground light mounted to the underside of the cab step below each door. The ground light shall be mounted in a polished aluminum bezel. The ground lighting shall be activated by the opening of the respective side door, respective side turn signal, when the parking brake is set, as well as being activated through a virtual button on the Vista display and control screen.

### **STEP LIGHTS**

The middle step located at each door shall include a recess mounted 4.00 inch round LED light which shall activate with the opening of the respective door.

### **ENGINE COMPARTMENT LIGHT**

There shall be an incandescent NFPA compliant light mounted under the engine tunnel for area work lighting on the engine. The light shall include a polycarbonate lens, a housing which is vibration welded and a bulb which shall be shock mounted for extended life. The light shall activate automatically when the cab is tilted.

# Surprise Fire Dept

## Surprise, AZ

### **FRONT SCENE LIGHTS**

The front of the cab shall include two (2) Fire Research Focus model FCA800-S50 contour roof mount scene lights installed on the brow of the cab.

Each lamp head shall have one (1) quartz halogen 120 volt 500 watt bulb. The bulb shall draw 4.2 amps and generate 10,500 lumens. The lamp head shall direct 50 percent of the light onto the action area while providing 50 percent to illuminate the working area. Each lamp head shall be no more than 4.75 inches in height X 11.50 inches in width. The lamp heads and brackets shall be powder coated white.

### **FRONT SCENE LIGHTS ACTIVATION**

The 120 volt or 240 volt front scene lighting shall be pre-wired for final connection by the OEM and shall be programmed for activation by a virtual button on the Vista display and control screen.

### **FRONT SCENE LIGHT LOCATION**

There shall be two (2) scene lights mounted to the front brow of the cab inboard of the outer front marker lights.

### **SIDE SCENE LIGHTS**

The side of the cab shall include two (2) Whelen 900 series 9SC0ENZR model scene lights, one (1) each side which shall be surface mounted with a chrome bezel. The Whelen lights shall offer LED lighting at a gradient 32-degree angle.

### **SIDE SCENE LIGHT LOCATION**

The scene lighting located on the left and right sides of the cab shall be mounted rearward of the cab "B" pillar in the 10.00 inch raised roof portion of the cab between the front and rear crew doors.

### **SIDE SCENE ACTIVATION**

The scene lights shall be activated by two (2) virtual buttons on the Vista display and control screen(s), one (1) for each light, and by opening the respective side cab doors.

### **INTERIOR OVERHEAD LIGHTS**

The cab shall include a two-section, red and clear Weldon LED dome lamp located over each door. The dome lamps shall be rectangular in shape and shall measure approximately 7.00 inches in length X 3.00 inches in width with a black colored bezel. The clear portion of each lamp shall be activated by opening the respective door. Both the red and clear portion can be activated by individual push lenses on each lamp.

An additional two-section, red and clear Weldon LED dome lamp shall be provided over the engine tunnel which can be activated by individual switches on the lamp.

### **MAP LIGHTS**

A Sunnex swivel map light shall be provided. The light shall have a clear lens and a control switch on the base. The light shall be mounted on the overhead HVAC cover on the right hand side.

# Surprise Fire Dept

## Surprise, AZ

### **DO NOT MOVE APPARATUS LIGHT**

The front headliner of the cab shall include a flashing red Whelen 500 Series 5mm LED light clearly labeled "Do Not Move Apparatus". In addition to the flashing red light, an audible alarm shall be included which shall sound while the light is activated.

The flashing red light shall be 5.40 inches long X 1.70 inches wide X 0.90 inches high and shall be located centered left to right for greatest visibility.

The light and alarm shall be interlocked for activation when either a cab door is not firmly closed or an apparatus compartment door is not closed, and the parking brake is released.

### **MASTER WARNING SWITCH**

A master switch shall be included, as a virtual button on the Vista display and control screen which shall be labeled "E Master" for identification. The button shall feature control over all devices wired through it. Any warning device switches left in the "ON" position when the master switch is activated shall automatically power up.

### **HEADLIGHT FLASHER**

An alternating high beam headlight flashing system shall be installed into the high beam headlight circuit which shall allow the high beams to flash alternately from left to right.

Deliberate operator selection of high beams will override the flashing function until low beams are again selected. Per NFPA, these clear flashing lights will also be disabled "On Scene" when the park brake is applied.

### **HEADLIGHT FLASHER SWITCH**

The flashing headlights shall be activated through a virtual button on the Vista display and control screen.

### **INBOARD FRONT WARNING LIGHTS**

The cab front fascia shall include two (2) Whelen 600 series Super LED front warning lights in the left and right inboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel.

### **INBOARD FRONT WARNING LIGHTS COLOR**

The warning lights mounted on the cab front fascia in the inboard positions shall be blue on the left and red on the right side.

### **FRONT WARNING SWITCH**

The front warning lights shall be controlled through a virtual control on the Vista display and control screen. This switch shall be clearly labeled for identification.

### **INTERSECTION WARNING LIGHTS**

The chassis shall include two (2) Whelen 600 series Super LED intersection warning lights, one (1) each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.



# Surprise Fire Dept

## Surprise, AZ

### **INTERSECTION WARNING LIGHTS COLOR**

The intersection lights shall be red/blue vertical split with a clear lens. The intersection lights located on the left side shall be red forward and the intersection lights on the right side shall be blue forward.

### **INTERSECTION WARNING LIGHTS LOCATION**

The intersection lights shall be mounted on the side of the bumper in the rearward position.

### **SIDE WARNING LIGHTS**

The cab sides shall include two (2) Whelen 900 series Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the sides of the cab within a chrome bezel.

### **SIDE WARNING LIGHTS COLOR**

The warning lights located on the side of the cab shall be blue/blue on the left side and red/red on the right side.

### **SIDE WARNING LIGHTS LOCATION**

The warning lights on the side of the cab shall be mounted above the "B" pillar in the highest available position.

### **AUXILIARY SIDE WARNING LIGHTS**

The cab side shall include an auxiliary set of Whelen 600 series 4.00 inch tall X 6.00 inch wide Super LED warning lights, one (1) each side, which shall feature fourteen (14) flash patterns plus a steady burn for solid colors and twenty (20) flash patterns plus a steady burn for split colors. The lights shall be surface mounted within a chrome bezel.

### **AUXILIARY SIDE WARNING LIGHTS COLOR**

The auxiliary warning lights located on the left hand side of the cab shall be red and the auxiliary warning lights located on the right hand side of the cab shall be blue.

### **AUXILIARY SIDE WARNING LIGHTS LOCATION**

The auxiliary warning lights on the side of the cab shall be mounted over the front wheel well, above the electrical inlet, and directly over the center of the front axle

### **SIDE AND INTERSECTION WARNING SWITCH**

The side warning lights shall be controlled through a virtual button on the Vista display and control screen. This button shall be clearly labeled for identification.

# Surprise Fire Dept

## Surprise, AZ

### **HORN BUTTON SELECTOR SWITCH**

A virtual button on the Vista display and control screen shall be provided to allow control of either the electric horn or the air horn from the steering wheel horn button. The electric horn shall sound by default when the selector switch is in either position to meet FMCSA requirements.

### **AIR HORN ACTIVATION**

The air horn activation shall be accomplished by the steering wheel horn button and a left hand side Linemaster model SP491-S81 foot switch for the driver and a black momentary push button on the switch panel. An air horn activation circuit shall be provided to the chassis harness pump panel harness connector.

**NOTE: Air horn shall default to the last position it was set at when the engine stops and is restarted.**

### **MECHANICAL SIREN ACTIVATION**

The mechanical siren shall be actuated by a black push button in the switch panel on the dash. A black push button siren brake control shall be provided in the switch panel on the dash.

The siren shall only be active when master warning switch is on to prevent accidental engagement.

### **ELECTRONIC SIREN AUXILIARY ACTIVATION**

The electronic siren shall include pre-wiring for activation by a left hand side foot switch outboard of the air horn foot controller.

### **BACK-UP ALARM**

A Preco-Matic model 270 backup alarm shall be installed at the rear of the chassis with an output level of 107 dB. The alarm shall automatically activate when the transmission is placed in reverse.

### **INSTRUMENTATION**

An ergonomically designed instrument panel shall be provided. Each gauge shall be backlit with LED lamps. Stepper motor movements shall drive all gauges. The instrumentation system shall be multiplexed and shall receive ABS, engine, and transmission information over the J1939 data bus to reduce redundant sensors and wiring.

The instrument panel shall contain the following gauges:

One (1) electronic speedometer shall be included. The primary scale on the speedometer shall read from 0 to 100 MPH, and the secondary scale on the speedometer shall read from 0 to 160 KM/H.

One (1) electronic tachometer shall be included. The scale on the tachometer shall read from 0 to 3000 RPM.

One (1) two-movement gauge displaying primary system, and secondary system air volumes and integral LCD odometer/trip odometer shall be included on the lower portion of the LCD. The scale on the air pressure gauges shall read from 0 to 150 pounds per square inch (PSI). The air pressure scales shall be linear to operate with an accuracy of 1 degree of the measured data with a red indication zone on the gauge showing critical levels of air pressure. A red indicator light in the gauge shall indicate a low air pressure, as well as a message on the LCD screen. The odometer shall display up to 9,999,999.9 miles. The trip odometer shall display 9,999.9 miles. The LCD shall display Transmission Temperature in degrees Fahrenheit on the upper portion of the LCD. The LCD screen shall also be capable of displaying certain diagnostic functions.

# Surprise Fire Dept

## Surprise, AZ

One (1) four-movement gauge displaying engine oil pressure, coolant temperature, fuel level, voltmeter, and an \*indicator bar displaying Diesel Exhaust Fluid (DEF) LED bar shall be included. The scale on the engine oil pressure gauge shall read from 0 to 120 pounds per square inch (PSI). The engine oil pressure scale shall be linear to operate with an accuracy of 1 degree of the measured. A red indicator light in the gauge shall indicate a low engine oil pressure, as well as a message on the LCD screen. The scale on the coolant temperature gauge shall read from 100 to 250 degrees Fahrenheit (F). The coolant temperature scale shall be linear to operate with an accuracy of 1 degree of the measured data with a red indication zone on the gauge showing critical levels of air pressure. A red indicator light in the gauge shall indicate high coolant temperature, as well as a message on the LCD screen. The scale on the fuel level gauge shall read from empty to full as a percentage of fuel remaining. An amber indicator light shall indicate low fuel at 25% tank level. The scale on the voltmeter shall read from 10 to 16 volts with a red indication zone on the gauge showing critical levels of battery voltage. A red indicator light shall indicate high or low system voltage, as well as a message on the LCD screen. The scale on the DEF LED bar will consist of four (4) LEDs displaying levels in increments of 25% of useable DEF in green. Upon decreasing levels, the indicator bar will change colors to notify the driver of decreasing levels of DEF and action will be required. An amber indicator light shall indicate low levels of DEF, as well as a message on the LCD screen and an audible alarm.

The instrument panel shall include a light bar that contains the following LED indicator lights and produce the following audible alarms in applicable configurations:

### **RED LAMPS**

Stop Engine-indicates critical engine fault  
Air Filter Restricted-indicates excessive engine air intake restriction  
Park Brake-indicates parking brake is set  
Seat Belt Indicator-indicates when a seat is occupied and corresponding seat belt remains unfastened  
Low Coolant-indicates engine coolant is required

### **AMBER LAMPS**

MIL-indicates an engine emission control system fault  
Check Engine-indicates engine fault  
Check Trans-indicates transmission fault  
High Transmission Temperature-indicates excessive transmission oil temperature  
ABS-indicates anti-lock brake system fault  
HEST-indicates a high exhaust system temperature  
Water in Fuel-indicates presence of water in fuel filter  
\*DPF-indicates a restriction of the diesel particulate filter  
\*Regen Inhibit-indicates regeneration has been postponed due to user interaction  
Range Inhibit-indicates a transmission operation is prevented and requested shift request may not occur.  
\*SRS-indicates a problem in the supplemental restraint system  
Check Message-Turn Signal On  
Check Message-Door Ajar  
Check Message-Cab Ajar  
\*Check Message-ESC Active  
\*Check Message-DPF Regen Active  
Check Message-No Engine Data  
Check Message-No Transmission Data  
Check Message-No ABS Data  
Check Message-No Data All Communication With The Vehicle Systems Has Been Lost  
Check Message-Check Engine Oil Level

# Surprise Fire Dept

## Surprise, AZ

Check Message-Check Washer Fluid Level  
Check Message-Check Power Steering Fluid Level  
Check Message-Low Transmission Fluid Level  
Check Message-Check Coolant Level

### **GREEN LAMPS**

Left and Right turn signal indicators

\*ATC-indicates low wheel traction for automatic traction control equipped vehicles, also indicates mud/snow mode is active for ATC system

High Idle-indicates engine high idle is active.

Cruise Control-indicates cruise control is active

OK to Pump-indicates the pump engage conditions have been met

Pump Engaged-indicates the pump is currently in use

Auxiliary Brake-indicates secondary braking device is active

### **BLUE LAMP**

High Beam Indicator

### **WHITE LAMP**

Wait to Start-indicates active engine air preheat cycle

### **AUDIBLE ALARMS FROM GAUGE PACKAGE**

High Trans Temp

High or Low Voltage

Check Engine

Check Transmission

Stop Engine

Low Air Pressure

Fuel Low

Water in Fuel

\*ESC

High Coolant Temperature

Low Engine Oil Pressure

Low Coolant Level

\*Low DEF Level

Air Filter Restricted

Extended Left and Right Turn Remaining On

Cab Ajar

Door Ajar

ABS System Fault

Seatbelt Indicator

### **EXTERNAL AUDIBLE ALARM**

Air Filter

Cab Ajar

Door Ajar

Check Engine

Stop Engine

Low Air Pressure

Low Engine Oil Pressure

Water in Fuel

\*Low DEF

# Surprise Fire Dept

## Surprise, AZ

ABS System Fault

Seatbelt Indicator

\*Items marked with an asterisk are provided only in applicable configurations.

### **LCD MESSAGES**

Transmission Temperature

Battery Voltage

Engine Hours

Vehicle Speed

Engine RPMs

Fuel Level

DEF Level

Engine Oil Pressure

Ammeter (If quipped)

Auxiliary Ammeter (If quipped)

Engine Coolant Temp

Primary System Air Pressure

Secondary System Air Pressure

Turbo Boost Pressure

Exhaust Temperature

Engine Load

Engine Torque

Instant Fuel Economy

Average Fuel Economy

### **BACKLIGHTING COLOR**

The instrumentation gauges and the switch panel legends shall be backlit using red LED backlighting.

### **RADIO**

A Panasonic radio with weather band, AM/FM stereo receiver, compact disc player, with and (4) speakers shall be installed in the cab wired battery direct. The radio shall be installed above the officer position. The speakers shall be installed inside the cab with two (2) speakers recessed within the headliner of the front of the cab just behind the windshield and two (2) speakers on the upper rear wall of the cab.

**NOTE: be sure the AM/FM radio is wired to Battery Direct.**

### **AM/FM ANTENNA**

A small antenna shall be located on the right hand side of the cab roof for AM/FM and weather band reception.

### **CAMERA**

An Audiovox Voyager heavy duty rearview camera system shall be supplied. One (1) box shaped camera shall be shipped loose for OEM installation in the body to afford a clear view of the rear of the vehicle and two (2) cameras with a teardrop shaped chrome plated housings shall be mounted on the left and right side of the cab below the windshield ahead of the front door at approximately the same level as the cab door handle. The side cameras shall afford a clear view of the area each side of the vehicle.

The cameras shall be wired to dual Weldon Vista displays which shall be located on the left and right sides of the dash. The rear camera shall activate when the transmission is placed in reverse and the side cameras shall

# Surprise Fire Dept

## Surprise, AZ

activate with the respective side turn signal. Each camera shall also be activated by a button on the Vista displays.

### **CAB EXTERIOR PROTECTION**

The cab face shall have a removable plastic film installed over the painted surfaces to protect the paint finish during transport to the body manufacturer. The rear wall shall also include a removable plastic film installed on the exterior surface of the cab to protect the finish during transport.

### **FIRE EXTINGUISHER**

A 2.50 pound D.O.T approved fire extinguisher with BC rating shall be shipped loose with the cab.

### **ROAD SAFETY KIT**

The cab and chassis shall include one (1) emergency road safety triangle kit.

### **DOOR KEYS**

The cab and chassis shall include a total of four (4) door keys for the manual door locks.

### **WARRANTY**

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN CHASSIS, INC. LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The chassis manufacturer shall provide a limited parts and labor warranty to the original purchaser of the custom built cab and chassis for a period of twenty-four (24) months, or the first 36,000 miles, whichever occurs first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

### **CAB AND CHASSIS LABELING LANGUAGE**

The cab and chassis shall include the applicable caution, warning, and safety notice labels with text to be written in English.

### **CHASSIS OPERATION MANUAL**

There shall be two (2) digital copies of the chassis operation manual provided with the chassis. The digital data shall include a parts list specific to the chassis model.

### **ENGINE AND TRANSMISSION OPERATION MANUALS**

The following manuals specific to the engine and transmission models ordered will be included with the chassis in the ship loose items:

(1) Digital copy of the Engine Owner's manual

# Surprise Fire Dept

## Surprise, AZ

(1) Digital copy of the Transmission Operator's manual

(1) Hard copy of the Engine Operation and Maintenance manual with CD

### **CAB/CHASSIS AS BUILT WIRING DIAGRAMS**

The cab and chassis shall include two (2) digital copies of wiring schematics and option wiring diagrams.

F. Axle Weight: 15,186

R. Axle Weight: 5,788

### **CAB TO AXLE DIMENSION**

Cab to axle will be **133"**.

### **CAB/CHASSIS PREPAYMENT**

The specified cab/chassis shall be prepaid by Surprise Fire Department within 30 days of invoice. Surprise Fire Department understands that if payment is made after 30 days, additional interest charges may apply.

### **CHASSIS MODIFICATIONS**

### **LUBRICATION AND TIRE DATA PLATE**

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid . . (if applicable)
- Pump priming system fluid, if applicable . . (if applicable)
- Drive axle(s) lubrication fluid
- Air conditioning refrigerant . . (if applicable)
- Air conditioning lubrication oil . . (if applicable)
- Power steering fluid
- Cab tilt mechanism fluid . . (if applicable)
- Transfer case fluid . . (if applicable)
- Equipment rack fluid (if applicable)
- CAFS air compressor system lubricant . . (if applicable)
- Generator system lubricant . . (if applicable)
- Front tire cold pressure
- Rear tire cold pressure
- Maximum tire speed ratings

### **VEHICLE DATA PLATE**

A permanent label in the driving compartment which indicates the following:

# Surprise Fire Dept

## Surprise, AZ

- Filter part numbers for the;
  - Engine
  - Transmission
  - Air
  - Fuel
- Serial numbers for the;
  - Engine
  - Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

### **OVERALL HEIGHT, LENGTH DATA PLATE (US)**

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in feet and inches, the length of the completed fire apparatus in feet and inches, and the GVWR in pounds.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

### **ACCIDENT PREVENTION**

There shall be a placard in the cab seating area which reads, "**ALL OCCUPANTS MUST BE SEATED AND BELTED WHEN THE APPARATUS IS IN MOTION**".

### **PERSONNEL CAPACITY**

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

### **ACCIDENT PREVENTION**

If the rear bumper is 8" deep or more, there shall be a placard on the rear face of the body, in clear sight from the ground, which reads, "**WARNING - DO NOT RIDE ON STEPS OR DECK AREAS WHILE THE APPARATUS IS IN MOTION. DEATH OR SERIOUS INJURY MAY RESULT**".

### **WEARING HELMET WARNING**

A label stating "**DO NOT WEAR HELMET WHILE SEATED**" shall be visible from each seating location.

### **FINAL STAGE MANUFACTURER VEHICLE CERTIFICATION**

A final stage manufacturer vehicle certification label shall be provided and installed in the driver cab door jamb area.



# Surprise Fire Dept

## Surprise, AZ

### **FRONT BUMPER**

The front bumper shall be as provided by the cab/chassis manufacturer. No other alteration or modifications are required.

### **BUMPER GRAVEL SHIELD**

The front bumper extension shall have a 3/16" NFPA compliant aluminum tread plate gravel shield. The gravel shield shall cover the full width of the front bumper to the front of the cab and the full height of the bumper on each end. **SVI Installed.**

### **AIR HORN(S)**

The air horn(s) shall be supplied by the cab/chassis manufacturer. SVI to install. Customer would like them to be installed to the inboard of the frame rails if possible.

### **MOTOR DRIVEN SIREN**

There shall be a Federal model Q2BP motor driven streamlined rotary siren with chrome plated grill and housing, pedestal mounted on extended front bumper. The siren shall be wired through the master warning light switch, and properly wired with heavy copper cable for minimum voltage drop.

The siren shall be located on the streetside of the front bumper.

There shall be a siren brake installed in the rocker switch control panel to activate the siren brake.

### **SIREN ACTIVATION**

The siren shall be operated by the steering wheel horn button located at the driver position and a push button switch on the cab dash at the officer position.

### **AIR HORN / ELECTRIC HORN SWITCH**

There shall be a switch which allows the driver to select the steering column horn ring operation. This switch shall allow the driver to select either the air horn or electric horn activation.

**NOTE: air horn shall default to the last position it was set at when engine stops and is restarted.**

### **FRONT TOW PROVISIONS**

The front tow provisions shall be supplied and installed by the cab/chassis manufacturer.

### **AIR INTAKE SYSTEM**

An air filter shall be provided in the engine's air intake system.

Air inlet restrictions shall not exceed the engine manufacturer's recommendations.

The air inlet shall be equipped with a means of separating water and burning embers from the air intake system.

This requirement shall be permitted to be achieved by either of the following methods:

# Surprise Fire Dept

## Surprise, AZ

1. Provision of a device such that burning particulate matter larger than 0.039 in. (1.0 mm) in diameter cannot reach the air filter element.
2. Provision of a multi screen ember separator capable of meeting the test requirements defined in the Parker Hannafin, Racor Division, publication LF 1093-90, *Ember Separation Test Procedure*, or an equivalent test.

### **EXHAUST DIVERTER**

An exhaust diverter valve shall be located in-line of exhaust tubing and controlled from driver's position to re-route exhaust discharge. Exhaust diverter valve shall be constructed from 14 gauge stainless steel material with air actuated control.

As a default, the exhaust shall always discharge to streetside just ahead of rear wheels, and when selected the exhaust shall discharge to curbside just ahead of rear wheels.

**When engine is turned off and re-started, the diverter shall default to the streetside at all times.**

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the apparatus or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

### **DOCKING STATION INSTALLATION**

There shall be one (1) Surprise Fire Department supplied Havis #LPS-101 docking stations mounted on backside of the engine tunnel.

Docking stations shall be installed per manufacturer's requirements and wired battery direct for proper 12 volt power and ground. Antennas shall be labeled and wired to cab roof per antenna layout.

Two (2) power supplies and cellular antennas shall be provided and installed for above docking stations.

**Docking stations shall match the previous pumper job #898.**

### **12 VDC FUSE BLOCK**

There shall be two (2) 100 amp Blue Sea Systems ST Series blade type fuse block with screw type terminals for both positive and negative buss with cover provided for distribution of up to six (6) 30 amp, 12 VDC circuits. Fuse block shall be located per required circuits and be protected from damage.

The terminal blocks will be located on the rear edge of the engine tunnel under the mounting platform and under the rear forward facing seat box located in such a manner that is it easy to access.

### **FIVE (5) POSITION ANTENNA RAIL**

Two (2) radio antenna rail(s) shall be provided and installed on roof of vehicle. Each rail be constructed of aluminum, forming a two piece box design. The top section shall be removable for easy access to the individual antenna wiring. Five (5) antenna bases shall be provided and installed in each rail. Each antenna base shall

# Surprise Fire Dept

## Surprise, AZ

include enough cable to reach radio location plus a service loop of at least 10' of LMR195 flexible communications cable.

The antenna wiring shall enter the vehicle roof at a single point under the end of the rail. The end of each radio antenna shall be **labeled** and routed to radio mounting locations, as specified below or as determined by the Surprise Fire Department.D

Due to the various configurations of antenna whips, the contractor shall provide the antenna to the rear docking station only, and the SFD shall provide the antenna whip.

Locations as follows:

### Drivers side Rail #1

- #1. EPCR antenna (to be routed down streetside "B" pillar and connected to the D/S rear EPCR docking station)
- #2. Mobile 150 antenna (to be connected to the dual band mobile radio behind the officers seat).
- #3. Mobile 800 (to be terminated at the center cab dash)
- #4. SPARE #4 (to be routed down the streetside "B" pillar and terminate in the center of cab dash/console).
- #5. SPARE #5, (to be routed down the streetside "B" pillar and terminate in the center of cab dash/console).

### Rail #2

- #6. AVL-Antenna (to be routed down curb-side "B" pillar to behind officer's seat)
- #7. AVL Puck (to be routed down curb-side "B" pillar to behind officer's seat) \*F.D. to provide the two (2) AVL Puck Antennas.
- #8. Mobile 150 (to be terminated at the center cab dash) .
- #9. To be determined.
- #10. To be determined.

Match previous job #928.

### **PAINT ANTENNA RAIL**

Antenna rail shall be provided with a powder coat paint finish, white color.

### **DOOR LOCK PROGRAMMING**

The Spartan supplied cab door locks shall be programmed with "07621" prior to delivery.  
The authorization code is: "14250".

### **ENGINE TUNNEL ACCESSORY PLATFORM**

There will be a 3/16" smooth aluminum deck painted gray with a hammer tone finish located on top of the engine tunnel. The platform will extend from the bottom edge of the center switch panel to the map box of the engine tunnel. The platform will be mounted to that it provides a level surface for FD supplied items.

The platform will feature two (2) cup holders, one each side within easy reach of the of the front seats and match the last fire engine.

### **MAP BOX**

A map box shall be provided in the cab with an open top and as deep as possible. The map box shall be securely fastened to the cab interior per NFPA 1901 standards. It shall be fabricated of 1/8" smooth aluminum and painted with a gray textured powder coat paint finish for durability and finished appearance.

# Surprise Fire Dept

## Surprise, AZ

The map box shall be designed to match previous job #898.

The mapbox will feature two (2) cup holders forward of the map box, one each side and a small storage bin between the cup holders, and a glove box with a hinged cover each side.

### **CUP HOLDERS**

There will be two (2) cup holder located at the rear cab corners about 18" from floor for the forward facing crew seats, one (1) each side within easy reach while seated.

Match the previous pumper job #898.

### **CREW STORAGE BINS**

There will be two (2) storage bins located on the back wall of the cab, one (1) each side of the rear forward facing seats. The bottom of the bin will be even with the bottom of the rear wall vinyl cover.

The bins will be approximately 4" x 8" x 4". Each bin will be equally divided in two sections.

The bins will be fabricated from smooth aluminum and will be powder coated gray with a hammer tone finish.

### **TRASH CAN HOLDER**

A trash can holder shall be provided and located behind driver seat full width of area. The trash can holder shall be fabricated from smooth aluminum and will be powder coated gray with a hammer tone finish.

**DO NOT install. Customer will install at final inspection.**

### **EMS MASK HOLDER**

An EMS mask holder shall be provided and located between the crew forward face seats. The EMS mask holder shall be fabricated from smooth aluminum and will be powder coated gray with a hammer tone finish.

### **VEST HOLDERS/GEAR HOOKS**

Vest holders shall be provided on front cab doors and total of ten (10) gear hooks shall be provided inside cab (same as #898).

Back wall of cab shall be reinforced to hold the gear hooks securely.

Protective material shall be wrapped around the knuckle guard of the steering shaft under the steering wheel to protect any item of clothing from getting caught in it.

(SVI to install if Spartan fails to do so).

A protective kickplate shall be installed in front of the windshield washer reservoir in cab step area to prevent any damage from kicking it.

### **CAB WINDOW TINT**

The cab side windows shall be provided with an after market "limo" tint.

**NOTE: There shall be no tint installed directly in front of the battery charge meter.**

# Surprise Fire Dept

## Surprise, AZ

SVI to be sure to check all the air hose intake clamps to be certain that they are all tightened securely.

### **TOE KICK TRIM PROTECTION**

Brushed stainless steel toe kick protection shall be provided in the following locations;

Six (6) total, one (1) at each Zolatone painted foot well at each cab door  
One (1) on the face of the rear cab forward facing seat box  
One (1) on all the surface area below and to the right of the officer's glove box  
Four (4) panels and a 1" x 1" angle on the top of the glove box  
One (1) under each rear facing fold down crew cab seat bottom.

### **HUB AND NUT COVERS**

Front and rear wheels shall be provided with stainless steel hub caps and wheel nut covers.

### **STEP CAB KICKPLATES**

There shall be brushed stainless steel kickplates installed on the cab step risers to protect the painted finish. (SVI to install if Spartan does not install). Will need to confirm after delivery of chassis.

### **MUDFLAPS**

There shall be 1/4" rubber mudflaps provided and installed behind each set of tires to prevent throwing road debris and lower road spray.

### **ELECTRIC DOOR LOCK INTERFACE**

Electric door locks shall be provided and interfaced as follows;

The electric cab door locks shall be provided by the cab/chassis manufacturer.

The body electric door locks shall be interfaced with the chassis electric door lock system.

### **ROAD EMERGENCY SAFETY KIT**

One (1) set of three (3) dual faced triangular warning flares with fold away base complete with storage case per DOT requirements shall be provided with the completed apparatus.

One (1) 2.5 lb. ABC type vehicle fire extinguisher with bracket per DOT requirements shall be provided and mounted inside cab area.

### **FUEL FILL**

There shall be one (1) fuel fill door located in the streetside exterior wheel well panel, behind the rear axle. The fill door shall be fabricated from brushed stainless steel. There shall be a permanent label with the text "DIESEL FUEL ONLY" located adjacent to the fuel fill access.

# Surprise Fire Dept

## Surprise, AZ

### **FUEL FILL**

There shall be two (2) fuel fill doors located in both sides of the exterior wheel well panel, behind the rear axle. The fill doors shall be fabricated from brushed stainless steel. There shall be a permanent label with the text "DIESEL FUEL ONLY" located adjacent to the fuel fill access.

### **BODY DESIGN**

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the Surprise Fire Department to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the Surprise Fire Department from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

SHOP NOTES  
SP

### **EXTERIOR ALUMINUM BODY**

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 3/16" (.187) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas, No Exceptions.

# Surprise Fire Dept

## Surprise, AZ

The front and rear corners of body shall be formed as part of the front or rear body panels. This provides a stronger body corner and finished appearance. The use of extruded corners, or caps will not be acceptable, No Exceptions.

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded and caulked to prevent moisture from entering the compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

### **DRIP RAILS**

The body shall have drip rails over the side full height compartments. The drip rails shall be formed into the upper body panels providing a ridged lower panel and a flat upper body panel surface. The use of mechanically fastened, taped or glued on drip rails will not be acceptable, No Exceptions.

### **ROOF CONSTRUCTION**

The roof shall be integral with the body and shall be all welded construction. The roof shall be constructed from 3/16" (.188) aluminum 3003H-14 alloy treadplate and supported with 2" x 2" x 1/4" tubing running the full width of the body. The supports shall be welded in place on approximate 16" centers.

All seams in the roof area shall be welded to the radius and supports prior to paint to prevent entry of moisture. All roof seams shall be continuously welded.

A 2" formed radius shall be provided along the body sides. The use of extrusions will not be acceptable, No Exceptions.

### **BODY SUBFRAME**

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

# Surprise Fire Dept

## Surprise, AZ

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 4" x 1/4" aluminum tubes minimum, the same width as the chassis frame rails. Welded to this tubing shall be cross members of 2" x 4" x 1/4" aluminum. Smaller dimension, lighter gauge tubing or angle material subframe shall not be accepted.

These cross members shall extend the full width of the body to support the compartments. Cross members shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum cross members shall be located on 16" centers, or as necessary to support walkway or heavy equipment.

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.

### **BODY MOUNTING**

The body subframe shall be fastened to the chassis frame with a minimum of six (6) spring loaded body mounts. Each mount shall be configured using a two-piece encapsulated slide bracket. The two (2) brackets shall be fabricated of heavy duty 1/4" thick steel and shall have a powder coat finish to prevent any corrosion. Each mounting assembly shall utilize two (2) 3/4" diameter x 6" long grade 8 bolts and two (2) heavy duty springs. The assembly design shall allow the body and subframe to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall eliminate any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement will not be acceptable.

### **14" REAR STEP BUMPER**

The full width rear bumper shall be constructed from 2" x 2" x 1/4" aluminum tubing frame and covered with 3/16" NFPA compliant aluminum tread plate. The bumper shall extend from the rear vertical body panel **14"** and provide a rear step with a minimum of 1/2" space at body for water drainage.

### **REAR TOW EYES**

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below the apparatus body. The tow eyes shall be fabricated from 3/4" thick steel plate and shall have a black powder coat finish.

### **GROUND LIGHTS**

There shall be two (2) OnScene Solutions Rough-Service 9" LED light provided installed below the bumper, capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle.

The light shall be activated when the parking brake is set.

Light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.



# Surprise Fire Dept

## Surprise, AZ

### **WHEEL WELL EXTERIOR PANEL**

The exterior panel of the body wheel well enclosure shall be constructed from 3/16" smooth aluminum panels.

### **STAINLESS STEEL BODY FENDERS**

The body wheel well openings shall be provided with round radius, polished stainless steel fenderettes. The fenderettes shall be bolted and easily replaceable if damaged. The fenderettes shall be installed using a rubber gasket to reduce buildup of moisture and/or debris.

### **WHEEL WELL LINERS**

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will not accumulate dirt or water.

### **SCBA CYLINDER COMPARTMENTS**

There shall be two (2) SCBA cylinder storage compartments located, one (1) on the curbside, and one (1) on the streetside of rear wheel well area. Each compartment shall be capable of storing two (3) SCBA cylinders (6.5" dia cylinders). Each compartment shall have a vertically hinged door with a positive catch latch installed and painted primary lower body color. Each compartment shall allow the storage of an SCBA cylinder 24" deep. The door shall activate the "Hazard Warning Light" in the cab when not in the closed position.

There shall be no PVC tubes installed in the compartments to allow storage of the (3) bottles.

### **PAINT FINISH - SINGLE COLOR**

The body shall be painted with a single color of PPG Delfleet® Evolution per Surprise Fire Department approved paint spray out provided.

A small touch-up bottle of paint shall be provided with completed vehicle.

### **FASTENERS**

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, a mylar isolation tape, or gasket shall be used to prevent damage to the finish painted surface. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nutserts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

### **ELECTROLYSIS CORROSION CONTROL**

The vehicle shall be assembled using ECK brand or similar corrosion control compound on all high corrosion potential areas.

ECK protects aluminum and stainless steel against electrolytic reaction, isolates dissimilar metals and gives bedding protection for hardware and fasteners. ECK contains anti-seizing lubricant for threads. ECK is dielectric and perfect for use with electrical connectors.

# Surprise Fire Dept

## Surprise, AZ



- Paint Color: Match cab/chassis supplied paint **color.**

### **BODY UNDERCOATING**

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

### **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

### **PAINT WARRANTY**

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle. **Pro-rated warranties will not be acceptable.**

### **COMPARTMENT INTERIOR FINISH**

The interior of all exterior body compartments shall be a "Maintenance Free" smooth unpainted finish. All body seams shall be finished with a caulk sealant for both appearance and moisture protection.

### **REFLECTIVE STRIPE REQUIREMENTS**

#### **Material**

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retroreflection of 10 with observation angle of 0.2 degrees and entrance angle of -4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

#### **Minimum Requirements**

A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 4 in. (100 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

# Surprise Fire Dept

## Surprise, AZ

### **GRAPHICS PROOF**

A color graphics proof of the reflective striping layout shall be provided for approval by Surprise Fire Department prior to installation. The graphics proof shall be submitted to Surprise Fire Department on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

### **REFLECTIVE STRIPE - CAB SIDE**

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

### **REFLECTIVE STRIPE - CAB FRONT**

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

### **REFLECTIVE STRIPE - CAB DOOR INTERIOR**

Any door of the apparatus designed to allow persons to enter or exit the apparatus shall have at least 96 in.2 (62,000 mm2) of retroreflective material affixed to the inside of the door.

The inside of each cab and crew doors shall have 4" Chevron style diamond grade reflective striping. The colors shall be red and fluorescent yellow-green.

### **REFLECTIVE STRIPE - BODY SIDES**

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

The stripe shall extend straight from front of cab, then ahead of the rear wheels, it shall form an "S" shape and extend straight back to the rear of the body. The "S" portion of the stripe shall remain a solid color.

### **CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS**

At least 50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width.

The rear side panels of the body on each side of a rear stairway or compartment shall have a chevron style reflective stripe, extending from bumper height up to side compartment drip rail height. Each chevron panel shall be a full sheet and shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panel shall have a minimum 10 year warranty for material failure, and colorfastness.

The stripe material shall be 3M Diamond Grade.

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

# Surprise Fire Dept Surprise, AZ

## **LETTERING**

### **GRAPHICS PROOF**

A color graphics proof of the lettering layout shall be provided for approval by Surprise Fire Department prior to installation. The graphics proof shall be submitted to Surprise Fire Department on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

The following lettering shall be provided and installed on the completed unit as follows;

### **SIDE CAB DOOR LETTERING**

There shall be eight (8) 9" high reflective letters furnished and installed on the vehicle.

- This reflective lettering shall be gold in color.

### **UPPER BODY SIDE LETTERING**

There shall be thirty four (34) 11" high reflective letters furnished and installed on the vehicle.

#### **"SURPRISE MEDICAL FIRE DEPT."**

- This reflective lettering shall be gold in color.

There shall be forty two (42) 6" high reflective letters furnished and installed on the vehicle.

"Always There  
Always Ready"

- This reflective lettering shall be gold in color.

### **REAR BODY LETTERING**

There shall be four (4) 6" high reflective letters furnished and installed on the vehicle.

#### **"LT 305"**

- This reflective lettering shall be gold in color.

### **FRONT OF CAB LETTERING**

There shall be four (4) 6" high reflective letters furnished and installed on the vehicle.

#### **"SURPRISE MEDICAL FIRE DEPT"**

- This reflective lettering shall be gold in color.

There shall be sixteen (16) 3" high reflective letters furnished and installed on the vehicle.

#### **"SURPRISE MEDICAL FIRE DEPT." - Above grille.**

# Surprise Fire Dept

## Surprise, AZ

- This reflective lettering shall be gold in color.

### **DECAL LOGO - 12"**

Two (2) custom decals shall be provided and installed on the front cab doors. The decals will match the Surprise Fire Department design.

### **PARAMEDIC STAR OF LIFE DECAL**

Two (2) reflective star of life decals shall be provided and install on S2/C2 roll-up doors. The decal will have the lettering of "PARAMEDIC" within the center of the decal. The layout will match the current Fire Department units.

### **EXTERIOR COMPARTMENT DOORS**

#### **ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM)**

The apparatus shall be equipped with Robinson ROM Series III roll-up exterior compartment doors. Robinson roll-up doors shall be complete with the following features;

- Doors shall be front roll with drum positioned at upper front portion of compartment to afford maximum clearances and head room for mounting equipment to ceiling of compartment
- There shall be a non-abrasive side brush seals
- Every slat must have interlocking end shoes to prevent slat from moving side-to-side and binding the door
- Between each slat must be a co-extruded PVC inner seal to prevent metal-to-metal contact and to repel moisture. This inner seal is not visible to detract from appearance of door
- Slat are to have interlocking joints with a folding locking flange to provide security and prevent penetration by sharp objects
- Slat to be double-wall extrusion 1.366" high by .315" thick. Exterior surface to be flat and interior surface to be concave to prevent loose equipment from interfering with door operation
- Latch system to be a full width one piece lift bar operable by one hand
- A 2" wide finger pull integrated into bottom rail extrusion for easy one hand opening and closing
- Clip system that connects the curtain slats to the operator drum which allows for easy tension adjustment without tools
- Each roll-up door shall have a 4" diameter counterbalance operator drum to assist in lifting the door.
- Track shall be one-piece aluminum that has an attaching flange and finishing flange incorporated into its design
- Drip rail will have specially designed seal that prevents the seal from scratching the door
- Bottom rail extrusion must have smooth back to prevent loose equipment from jamming the door
- Bottom rail to have "V" shaped double seal to prevent water and debris from entering the compartment
- Standard replacement parts to be shipped from the United States and available in as little as 48 hours
- Will be free from manufacturing defects for a period of up to 7 years from date of purchase provided that the Product is used under conditions of normal use, that regular periodic maintenance and service is performed and that the product was installed in accordance with R•O•M's instructions.

Each roll-up door framework shall decrease the compartment door opening by approximately 2.25" and 4.5" in height for standard bottom rail and 6.0" in height for tall bottom rail option.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.

# Surprise Fire Dept

## Surprise, AZ

### **BODY HEIGHT MEASUREMENTS**

The vertical body dimensions shall be as follows:

#### **AHEAD OF REAR AXLE**

	<u>Description</u>	<u>Dimension</u>
A	Bottom of Subframe to Top of Body	74.0"
B	Bottom of Subframe to Bottom of Body	22.5"
C	Vertical Door Opening	
	-with roll-up door	67.5"
	-with hinged door	71.5"

#### **ABOVE REAR AXLE**

	<u>Description</u>	<u>Dimension</u>
D	Vertical Door Opening - Above Rear Wheel	
	-with roll-up door	34.0"
	-with hinged door	37.0"

#### **BEHIND REAR AXLE**

	<u>Description</u>	<u>Dimension</u>
E	Bottom of Subframe to Bottom of Body	20.0"
F	Vertical Door Opening	
	-with roll-up door	62.0"
	-with hinged door	66.0"

#### **GENERAL**

	<u>Description</u>	<u>Dimension</u>
G	Bottom of Drip Rail to Top of Body	23.5"

(Dimensions are approximate and subject to change during the actual design process.)

### **FIVE (5) UPPER BODY COMPARTMENTS (OPEN)**

The forward transverse compartment shall be 90.0" long x 27.0" wide x 18.5" deep. There shall be four (4) compartments parallel to the sides of the body, two (2) on each side. The (2) forward compartments shall be 46.0" long x 28.0" wide x 18.5" deep. **The two (2) rearward compartments shall be 72" long x 28.0" wide x 18.5" deep.** The side compartments shall be open under each door sill to allow for long equipment. Each compartment shall be integral with the body construction, and will not be bolted or add-on modules. The outside walls of each compartment will be double walled to prevent equipment from denting the outside painted surface.

Each compartment shall have a lift-up type compartment door hinged on the outboard side. Each door shall be fabricated from 3/16" aluminum tread plate. Each door shall have two (2) pneumatic type cylinders, one (1) at each end, attached to cast aluminum brackets mounted to the interior surface of the door to hold the door in both the opened and closed positions. Each door shall be mounted using multiple 16" long, equally spaced, 14 gauge stainless steel hinges, with 1/4" stainless steel pin. A polyester barrier film gasket shall be placed between stainless steel hinge and the body mounting surface as necessary to prevent corrosion caused by dissimilar metals.

Each compartment door shall overlap a 2" vertical lip on the body roof to prevent entry of moisture and sealed with automotive type rubber molding to provide a weather resistant seal.

# Surprise Fire Dept

## Surprise, AZ

Each roof compartment door shall have a chrome 7" handle bolted to center of each door.

Each compartment shall have a 13/16" drain hole located in floor of compartment with a 1" flexible drain tube that terminates below body.

Each compartment shall have a horizontally mounted OnScene Solutions LED light on the underside of the door. The light and NFPA door ajar system shall be automatically activated by an individual switch per compartment.

The hinged door(s) shall have a chrome grab handle. . A gasket shall be placed between the handle and the compartment exterior wall. Door latches shall be a single point, D-ring style, mounted on the compartment cover. **Match style used on previous job #898.**

### **UPPER BODY WALKWAY**

A 34" wide, upper body walkway shall be provided at the center of body and recessed into the roof structure. The walkway shall be fabricated from NFPA compliant 3/16" aluminum tread plate with continuously welded cross seams to prevent moisture penetration into apparatus body, No Exceptions. The walkway shall be supported with 2" x 2" tubing on 14" - 22" centers.

13/16" drains shall be installed at front of walkway connected to 1" flexible drain tubes that will terminate below the body.

### **WALKWAY/STEP LIGHTS**

There shall be two (2) OnScene Solutions Rough-Service 9" LED lights provided to illuminate the walkway or step area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

Lighting shall provide illumination at a minimum level of 2 fc (20 lx) on all work surfaces, steps, and walkways. Lighting shall be switchable but activated automatically when the vehicle park brake is set.

### **ROOF ACCESS LADDER**

The ladder shall be weld constructed of vertical aluminum extrusion tubing and aluminum grip surface ladder rungs with slip resistant tread grip pattern. It shall be set off from body 8 inches and mounted to body with chrome plated end stanchions bolted to the body with stainless steel bolts. The ladder shall NOT extend above the body roof.

The location shall be on the rear streetside of the apparatus body. Leave enough room under the ladder for a hose clamp.

#### **SHOP NOTES**

Need to have room for Humat Valve mounted under ladder

# Surprise Fire Dept

## Surprise, AZ

### **WALKWAY/STEP LIGHTS**

There shall be two (2) OnScene Solutions Rough-Service 9" LED lights provided to illuminate the walkway or step area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

Lighting shall provide illumination at a minimum level of 2 fc (20 lx) on all work surfaces, steps, and walkways. Lighting shall be switchable but activated automatically when the vehicle park brake is set.

There shall be two (2) adjustable compartment dividers installed into the upper body compartments.

The 12 volt electrical distribution panel shall be located up in the upper body compartment on the streetside of the transverse compartment.

### **BODY WIDTH DIMENSIONS**

The body shall be 100.0" wide, not including drip rail or non-permanent fixtures. Interior compartment depth dimensions shall be approximately:

<u>Area Description</u>	<u>Dimension</u>
Transverse Area above Subframe	95.0"

Compartment Depth below Subframe	24.5"
----------------------------------	-------

### **STREETSIDE COMPARTMENT - FRONT (S1)**

SHOP NOTES

SP

The interior useable compartment width shall be approximately 53.0" wide.

The compartment door opening shall be approximately 46.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.



# Surprise Fire Dept

## Surprise, AZ

### COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) OnScene Solutions 81 series aluminum tray base with 100% extension, and rating of 1,000 lbs. Slide-out tray(s) base shall be approximately **50" deep** and as wide as the compartment layout or door opening permits mounted above the body subframe. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. The tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".

**NOTE:** equipment to be mounted onto this tray will be (2) chain saws, (2) K-12 saws, spare equipment box, (2) 1-gallon gas cans, and a 2-slot box for storing spare saw blades.

- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) air bag storage module. The module shall be fabricated from 1/8" (.125) 3003H-14 aluminum alloy sheet. Circular notches shall be provided along the front edge to ease the access to the air bags. Each bay shall be sized to hold the air bag and a matching piece of 1/2" plywood (plywood not provided). The module will hold a total of five (5) high pressure air bags, and (2) low pressure air bag. The make, model, qty and exact dimensions of the air bags shall be provided by the department during the construction process.
- Retaining straps shall be installed over the opening.

#### SHOP NOTES

Designed to hold six (6) bag. FD to supply info

- There shall be four (4) OnScene Solutions cargo straps provided to secure the stored equipment.
- There shall be two (2) removable plastic tool box(s) **with external handles** for carrying cribbing. Each tool box shall be fabricated from 1/2" (.50) textured finish polypropylene sheet.

The tool box(s) shall be used to store a Surprise Fire Department supplied 40 Lincoln Log cribbing package.

**There shall be (2) extra compartment vents installed in the lower area of this compartment due to the spare gas appliances and gas cans stored in it.**

The following equipment shall be stored on the floor of this compartment:

- (2) black poly boxes with external handles
- (1) Genesis brand MACH III gas driven hyd pump
- (2) 50' sections of spare hydraulic hose.

- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.

# Surprise Fire Dept

## Surprise, AZ

- Two (2) specified speedlay storage trays shall be located up high in transverse to opposite side located above chassis frame rails.

Trays shall be mounted side-by-side.

- One (1) Surprise Fire Department supplied gas powered hydraulic power unit(s).
- One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.
- The lights shall have the protective aluminum housing.

### **STREETSIDE COMPARTMENT - AHEAD OF REAR WHEELS (S2)**

SHOP NOTES

SP

The interior useable compartment width shall be approximately 41.0" wide.

The compartment door opening shall be approximately 34.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) 400 lbs. stationary slide-out tray(s) approximately 48" deep and as wide as the compartment layout or door opening permits. . Tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray shall have NO pneumatic cylinder mounted on underside, in order to keep the height down as low as possible in compartment floor, and will only have an IN/OUT locking device.

# Surprise Fire Dept

## Surprise, AZ

- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) OnScene Solutions 81 series aluminum tray base with 100% extension, and rating of 1,000 lbs. Slide-out tray(s) base shall be approximately 50" deep and as wide as the compartment layout or door opening permits located above the body subframe and shall be stationary. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".

The front edge will be notched to allow for the water spout of the cooler to be accessed.

- There shall be one (1) vertical partition(s) installed on tray dividing the tray into left and right sides. The vertical partition shall be horizontally adjustable; mounted on aluminum shelf trac on tray floor.

The following equipment shall be mounted onto the vertical divider and tray:

Two (2) equipment hooks located on the rear side of the vertical divider.

Two (2) Zico brackets for holding air packs mounted one each side of the board towards the rearward section.

One water cooler mounted to the outboard section on the forward side.

- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be two (2) Zico 1000 series KD-UH walkaway type SCBA air pack bracket(s) with high cycle coated spring clips and angled foot plate ( w ith CRS strap inc.). These brackets will be installed on to the vertical divider of the pull-out tray.
- One (1) SVI supplied and installed water cooler will be located in the On Scene pull-out tray closest to the front edge in one corner. There will be a cup holder adjacent to the water cooler.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- The generator gauge panel shall be installed directly above the Command Light Control box.
- The controls for the specified light tower(s).
- The pump operator's panel shall be located in this compartment.

There shall be one (1) OnScene Solutions Rough-Service 9" LED light provided below the body. The light shall be activated when the parking brake is set.

Light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

# Surprise Fire Dept

## Surprise, AZ

### STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S3)

#### SHOP NOTES

SP

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 20" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.

#### SHOP NOTES

**NOTE: CUSTOMER MAY DELETE THIS TRAY.**

- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) OnScene Solutions 84 series aluminum tray base with 90% extension, and rating of 150 lbs. Slide-out tray(s) base shall be approximately 20" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will hold the tray in the closed position. Each tray

# Surprise Fire Dept

## Surprise, AZ

shall be fabricated from 3/16" 3003 aluminum sheet and have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".

### SHOP NOTES

20"D will OnScene make one that shallow?

- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- Two (2) OnScene 36" Access LED compartment lights, vertically mounted.

### **STREETSIDE COMPARTMENT - REAR (S4)**

#### SHOP NOTES

SP

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
  - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the shelf. The striping shall be red/white in color.

# Surprise Fire Dept

## Surprise, AZ

- There shall be three (3) slide-out smooth aluminum vertical tool board(s) approximately 24" deep. Each tool board(s) vertical exterior edge shall have a double 90 degree formed edge to provide an easy grip handle. The top and bottom of tool board(s) shall be provided with Accuride 9300 series slide tracks. Each board shall be rated for a maximum 200 lbs. evenly distributed load. Each tool board shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.
- The vertical tool board material shall be 3/16" (.188) 3003H-14 aluminum alloy sheet. Sheet shall be perforated with 1/4" (.25) holes on 1" centers.
- Each tool board shall be horizontally adjustable; mounted on aluminum shelf trac on compartment floor.
- 3M™ Diamond Grade™ Conspicuity striping shall be provided on both sides of the toolboard. The striping shall be 2" wide and red/white in color.
- There shall be one (1) bolt-in vertical compartment partition dividing the compartment into left and right sides. The divider will come from the top of the ceiling to the top of the tool box.

### SHOP NOTES

Do not run to floor. To come from ceiling and back wall to the top of the tool-box

- One (1) Lista drawer cabinet, shall be provided in compartment. The Lista cabinet(s) shall be 17" wide x 27.5" high x 22-1/2" deep. Cabinet shall have eight (8) individual locking drawers as follows as follows; one (1) 2", one (1) 3", one (1) 4", one (1) 5", one (1) 7", and one (1) 9". The cabinet shall be red in color with light gray drawers.

There shall be a horizontal pipe installed above the Lista toolbox in this compartment to hold five (5) orange traffic safety cones.

- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.

There shall be one (1) OnScene Solutions Rough-Service 9" LED light provided below the body. The light shall be activated when the parking brake is set.

Light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

### **CURBSIDE COMPARTMENT - FRONT (C1)**

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.

# Surprise Fire Dept

## Surprise, AZ

- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf approximately 50" deep. Shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
- Shelf will be used to store (2) sheets of plywood.
- There shall be one (1) OnScene Solutions 86 series aluminum tray base with 100% extension, and rating of 600 lbs. The tray base shall be 30" wide maximum x 26" deep. Each slide base shall have a cable operated, spring loaded latch complimented by a red "T" handle (Pull to Release) which shall lock the tray in the closed and full extension positions. Each tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3 1/2" vertical lip and welded corners to form a box type tray surface and as wide as the compartment layout or door opening permits located below the level of the chassis frame rails.

This tray shall be made to hold salvage bags.

- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) OnScene Solutions 86 series aluminum tray base with 100% extension, and rating of 600 lbs. The tray base shall be 30" wide maximum x 45" deep. Each slide base shall have a cable operated, spring loaded latch complimented by a red "T" handle (Pull to Release) which shall lock the tray in the closed and full extension positions. Each tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3 1/2" vertical lip and welded corners to form a box type tray surface and as wide as the compartment layout or door opening permits located below the level of the chassis frame rail
- Tray shall be located on the forward side of the vertical partition.
- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) OnScene Solutions 84 series aluminum tilt-tray base with 90% extension, and rating of 250 lbs. Slide-out/tilt tray(s) base shall be approximately 50" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height. Each slide shall have a cable operated, spring loaded latch complimented by a large


# Surprise Fire Dept

## Surprise, AZ

hand opening and red pull handle (Pull to Release) which will hold the tray in the closed position. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".

Tray will be designed to hold 48" long pieces of 4 x 4 wood cribbing.

- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) bolt-in vertical compartment partition(s) provided dividing the compartment into left and right sides. The vertical partition(s) shall be 3/16" (.188) 3003H-14 alloy smooth aluminum sheet.  
**Vertical partition shall be approx 46" Deep and located above the transverse floor only.**
- Three (3) FD extinguishers shall be mounted in the lower section of the compartment to the forward side of the vent fans, one above the other. There shall be one (1) 2.5gal H2O, one (1) 15lb. CO2, and one (1) 20lb ABC.

Extinguishers to be mounted in slanted PVC tubes. 

Two ventilation fans shall be mounted on the floor of this compartment. Be sure the wheels are blocked to prevent the fans from shifting in transit.

- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.

There shall be one (1) OnScene Solutions Rough-Service 9" LED light provided below the body. The light shall be activated when the parking brake is set.

Light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

### **CURBSIDE COMPARTMENT - AHEAD OF REAR WHEEL (C2)**

#### **SHOP NOTES**

SP

The interior useable compartment width shall be approximately 41.0" wide.

The compartment door opening shall be approximately 34.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked



# Surprise Fire Dept

## Surprise, AZ

with activation from a single switch located in the cab.

- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be two (2) adjustable shelf/shelves approximately 26" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
- **NOTE: the lower shelf shall have the lip in the down position, and be mounted as close to the Medi-Redi cooler as possible.**
- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the shelf. The striping shall be red/white in color.
- There shall be one (1) OnScene Solutions 84 series aluminum tilt-down tray base with 90% extension, and rating of 250 lbs. Slide-out tray(s) base shall be approximately 46" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will hold the tray in the closed position. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".

There shall be (1) 5 gallon plastic bucket supplied by the SFD and stored in this compartment.

- One (1) 14" x 14" mount plate shall be provided for SFD supplied TIC charger located in upper compartment on back wall.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).

### **12 VDC ACCESSORY PLUG**

There shall be two (2) 12 volt accessory plug(s) furnished and installed above the adjustable shelf.

- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- There shall be one (1) 100 amp Blue Sea Systems ST Series blade type fuse block with screw type terminals for both positive and negative buss with cover provided for distribution of up to six (6) 30 amp, 12 VDC circuits. Fuse block shall be located per required circuits and be protected from damage.
- There shall be one MediRedi model 2000-C 6399 drug cooler with WiFi-300 series with 3000 user capability provided and installed in the lower area of the compartment. The cooler shall include a 5 year sales warranty.

# Surprise Fire Dept

## Surprise, AZ

### SHOP NOTES

- There shall be one (1) 120 VAC outlet(s) located in compartment on the forward wall.
  - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
  - Outlet(s) shall be powered by both the on-board generator and shore power system through a relay system.
- There shall be one (1) Furman PLUGLOCK-PFP circuit breaker protected locking outlet strip provided and installed in the compartment, adjacent to the specified 120VAC outlet.

The PLUGLOCK-PFP secure clamping design "locks" transformers and conventional plugs in place, ensuring they cannot accidentally get disconnected from the power source. Adjustable clamps accommodate transformers and plugs from 0.4" to 2.1" above outlet.

The PLUGLOCK-PFP outlet strip shall be of sturdy, all steel construction and heavy-duty 5 foot (14 AWG) three conductor cord.

Along with the drug cooler, there shall be a Permatron 6" x 6" air filter installed in the compartment wall for additional cooling.

To match a previous job #898.

There shall be one (1) OnScene Solutions Rough-Service 9" LED light provided below the body. The light shall be activated when the parking brake is set.

Light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

### **CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C3)**

#### SHOP NOTES

SP

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.

# Surprise Fire Dept

## Surprise, AZ

- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf approximately 26" deep. Shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
  - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the shelf. The striping shall be red/white in color.
- There shall be one (1) OnScene Solutions 84 series aluminum tilt-tray base with 90% extension, and rating of 150 lbs. Slide-out tray(s) base shall be approximately 26" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails. Each slide shall have a cable operated, spring loaded latch complemented by a large hand opening and red pull handle (Pull to Release) which will hold the tray in the closed position. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".

### SHOP NOTES

Verify Depth



- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- Two (2) OnScene 36" Access LED compartment lights, vertically mounted.

### **CURBSIDE COMPARTMENT - REAR (C4)**

#### SHOP NOTES

SP

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.

# Surprise Fire Dept

## Surprise, AZ

- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be three (3) adjustable shelves approximately 26" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.

There shall be one (1) OnScene Solutions Rough-Service 9" LED light provided below the body. The light shall be activated when the parking brake is set.

Light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

•

### **REAR COMPARTMENT - CENTER (RC1)**

SHOP NOTES

SP

The rear center compartment shall be closed to both side rear compartments.

The rear center compartment shall begin just above the bumper height, between the chassis frame rails and be as high as the side compartments, unless specified otherwise. The body sub-frame shall extend to the back of the body, stopping just inside the door opening.

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

This compartment shall have a ROM roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.

# Surprise Fire Dept

## Surprise, AZ

- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) OnScene Solutions 81 series aluminum tray base with 100% extension, and rating of 1,000 lbs. Slide-out tray(s) base shall be approximately 46" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".
- 

**NOTE:** See location of tray on the slides, it is larger on the right hand side.

### **SHOP NOTES**

approximately 49" deep x 21" wide and located above the level of the chassis frame rails.

- Vertical partition(s) shall be provided on slide-out tray base dividing the tray into left and right sides. Each vertical partition shall be horizontally adjustable; mounted on aluminum Shelf Trac on tray floor. The vertical partition(s) shall be 3/16" (.188) 3003H-14 alloy smooth aluminum sheet.

**This vertical partition shall hold several fire department rescue struts and jacks.**

**(2) JYD-ZRS-W struts.**

**(2) CTC-501, 45.5" LG struts**

**(2) CTC-502 struts**

**(1) CTC-503 strut**

**(2) 51.5" LG struts**

**SFD to supply SVI the struts to mount.**

- There shall be one (1) slide-out smooth aluminum vertical tool board(s) approximately 50" deep. Each tool board(s) vertical exterior edge shall have a double 90 degree formed edge to provide an easy grip handle. The top and bottom of tool board(s) shall be provided with Accuride 9300 series slide tracks. Each board shall be rated for a maximum 200 lbs. evenly distributed load. Each tool board shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.

**Toolboard to be located above the ladder storage area and shall hold (1) 51" long strut, model #JYD-ZRS-N**

# Surprise Fire Dept

## Surprise, AZ

- The vertical tool board material shall be 3/16" (.188) 3003H-14 aluminum alloy sheet.
- Each tool board will be bolted to compartment floor.
- There shall be one (1) ladder/pike pole storage module with removable side access panels (located in compartments C1, C2 and C3). The module shall extend from the curbside edge of the compartment to the approximate compartment center without gaps along the outside edge of the module and compartment wall. A vertical partition shall be provided to separate the ladder storage side of the compartment from the open storage side. The module shall be designed with adequate space considerations given to allow tools and other equipment to be quickly and easily deployed and stowed from compartment.

The module shall hold the following and equipment:

-(4) Leatherhead pike poles, 6', 8' 10' and 12'

-(3) Leatherhead trash hooks

-(1) Leatherhead drywall saw

### SHOP NOTES

ladder / pike pole storage module with removable side access panels (located in compartments C1, C2 and C3). The module will extend from the curbside edge of the compartment to the approximate compartment center without gaps along the outside edge of the module and compartment wall. A vertical partition will be provided to separate the ladder storage side of the compartment from the open storage side. The module will be designed with adequate space considerations given to allow tools and other equipment to be quickly and easily deployed and stowed from compartment.

- Two (2) Surprise Fire Department supplied backboards shall be installed alongside the ladders.
- Backboards shall be Ferno model Redi-Hold model NB-1100

NOTE: SFD will furnish the backboards.

### SHOP NOTES

above the pike pole tubes.

- Surprise Fire Department supplied trash hooks. Manufacturer, model number and dimensions of the trash hooks shall be provided during the pre-construction meeting.

**All trash hooks shall be specially ordered with the handles rotated 90 degrees from standard.**

- Four (4) Manufacturer supplied ladders. Ladders to include:
  - One (1) Duo-Safety 1225A series 35' 3-section extension ladder stored on edge in the outboard position of the storage module
  - One (1) Duo-Safety 900A series 24' 2-section extension ladder stored on edge in the middle position of the storage module
  - One (1) Duo-Safety 775A series 14' aluminum roof ladder stored on edge in the inboard position of the storage module
  - One (1) Duo-Safety 585A series 10' folding attic ladder stored on edge above the 14' ladder position

### SHOP NOTES

See spec for details

# Surprise Fire Dept

## Surprise, AZ


- Four (4) SVI supplied pike poles. The pike poles will be as followed and stored as follows from inboard to outboard.
  - ~~(1) Leatherhead 6' Pike Pole #DBO-6AH-B~~
  - ~~(1) Leatherhead 8' Pike Pole #DBO-8AH-B~~
  - (1) Leatherhead 10' Pike Pole #DBO-10AH-B
  - (1) Leatherhead 12' Pike Pole #DBO-12AH-B

The pike pole will be in individual tubes with a notch to lock the pike head into a stowed position. The tubes will be located above the ladder storage. Each tube will be **CLEARLY LABELED** to indicate the pike pole size.

### SHOP NOTES

- (1) Nupla YPD 6' Pike Poles
- (1) Nupla YPD 8' Pike Poles
- (1) Nupla YPD 10' Pike Pole
- (1) Nupla YPD 12' Pike Pole

The pike pole will be in individual tubes with a notch to lock the pike head into a stowed position. The tubes will be located above the ladder storage. Each tube will be labeled to indicate the pike pole size.

- There shall be two (2) removable plastic tool box(s) with hand holes for carrying. Each tool box shall be fabricated from ½" (.50) textured finish polypropylene sheet.
- One (1) Hannay ECR1618-17-18 electric cable reel(s) capable of storing 200' of 10/3 electric cable. Reel(s) shall be designed to hold 110% of the capacity of cord length, with fully enclosed 45 amp, three (3) conductor collector rings. Reel(s) shall be mounted to channel structure that allows for side-to-side adjustment of reel position.
  - Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and not be more than 72 in. (1830 mm) above the operator's standing position, and shall be marked with a label indicating its function.
  - A label shall be provided in a visible location adjacent to reel with following information: Current rating, Current type, Phase, Voltage, and Total cord length.
- The cable reel shall be equipped with 200' of 10/3 SEOW yellow cable, a molded plastic ball clamp, and a single heavy duty L5-30 twist-lock female plug at the end.
- One (1) Circle-D PF-51G-YEL series, cast aluminum power distribution box with yellow powder coat painted finish shall be provided. The power distribution box shall meet all requirements described in NFPA 1901. The power distribution box shall include:
  - A 12" pigtail that terminates in an L5-30 configuration to match the cable on the cord reel. The outlet configuration shall include:
    - One (1) 120 VAC, L5-15R single twist lock receptacle 
    - One (1) 120 VAC, L5-15R single twist lock receptacle.
    - One (1) 120 VAC, L5-15R single twist lock receptacle.

# Surprise Fire Dept

## Surprise, AZ

- One (1) 120 VAC, L5-15R single twist lock receptacle.
- The fairlead roller shall be mounted directly to the reel.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.

### **PLASTIC FLOOR AND SHELF TILE**

All compartment floors, shelves, and trays shall be covered with Turtle Tile plastic interlocking grating.

- The plastic floor tile shall be black.
- The plastic edge trim shall be black.

### **SIDE BODY PROTECTION - RUB RAIL**

OnScene Solutions rub rails shall be provided below the compartment door openings on both the streetside and curbside.

The rub rail shall be fabricated from 6063 extruded aluminum, measuring approximately 2-3/4" high x 1-3/8" thick with tapered aluminum end caps. The rub rail shall be bolted to the body using stainless steel bolts and 1-1/2" diameter x 5/8" thick rubber mount isolators to prevent damage to the body.

The rails shall incorporate LED clearance marker lighting recessed into the rail fascia to avoid damage to the light in case of impact. The rub rail shall have an accessory mounting track integrated into the backside of the rail to allow mounting of accessories such as ground lighting.

3M™ Diamond Grade™ Conspicuity striping shall be provided in the rub rail. The striping shall be red/white in color.

### **FRONT GRAVEL GUARDS**

Gravel guards shall be provided on front lower body corners. Guards shall be 12" high, extend from behind cab or step and wrap around to the front compartment door opening fabricated from 20 gauge brushed stainless steel.

### **FOLDING STEP**



There shall be one (1) Cast Products model SP2014-1B 11" x 14" polished cast aluminum folding step(s) provided and installed on completed vehicle. Each step shall be heavy duty with stainless steel spring and textured step surface meeting NFPA standards. Each step will include integrated upper and lower LED lights. One (1) step shall be installed on the passengers side rear of body, There shall be a clear opening left under the step to accommodate the hose clamp.

### **LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC**

#### **General**

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.



# Surprise Fire Dept

## Surprise, AZ

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

### Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125 % of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10 %. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

### Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage overcurrent protective devices. Such devices shall be readily accessible and protected against heat in excess of the overcurrent device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

# Surprise Fire Dept

## Surprise, AZ

- SAE J156, *Fusible Links*
- SAE J553, *Circuit Breakers*
- 1) SAE J554, *Electric Fuses (Cartridge Type)*
- 2) SAE J1888, *High Current Time Lag Electric Fuses*
- 3) SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125 % of maximum current for which the circuit is protected.

### Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

### Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- 4) The propulsion engine and transmission
- 5) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- 1) The radio(s) at a duty cycle of 10 percent transmit and 90 % receive (for calculation and testing purposes, a default value of 5 A continuous)
- 2) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- 3) The minimum optical warning system, where the apparatus is blocking the right-of way
- 4) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- 5) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

### Electromagnetic Interference

# Surprise Fire Dept

## Surprise, AZ

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

### Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

### Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

### **12 VOLT MULTIPLEX CONTROL CENTER**

The apparatus shall be equipped with a Weldon V-MUX multiplexed 12 volt electrical system that will provide complete diagnostic capability, No Exception. The system shall have the capability of delivering multiple signals via a CAN bus, utilizing specifications set forth by SAE J1939. The system shall be node based to maximize stability so that failure of one node does not affect the operation of the other nodes. The system shall use shielded twisted-pair wire for transmission of system function signals. The shielded wire shall provide protection against EMI and RFI noise interruptions.

The multiplex system shall be responsible for providing power management functions as well as load shedding. The warning light system shall be controlled by the multiplex system. The system shall be capable of displaying text and/or graphic messages on a display module. The system shall be based on solid-state technology and shall include self-contained diagnostic indicators.

### **WELDON CERTIFICATION**

A letter shall be provided with bid submittal that the Contractor has successfully completed the Weldon training requirements for Level 1 of the V-MUX Certified Supplier Program and is authorized to design, build, and service V-MUX electrical systems.

The apparatus shall be equipped with a Weldon V-MUX multiplexed 12 volt electrical system that will provide complete diagnostic capability, No Exception. The system shall have the capability of delivering multiple signals via a CAN bus, utilizing specifications set forth by SAE J1939. The system shall be node based to maximize stability so that failure of one node does not affect the operation of the other nodes. The system shall use shielded twisted-pair wire for transmission of system function signals. The shielded wire shall provide protection against EMI and RFI noise interruptions.

The multiplex system shall be responsible for providing power management functions as well as load shedding. The warning light system shall be controlled by the multiplex system. The system shall be capable of displaying text and/or graphic messages on a display module. The system shall be based on solid-state technology and shall include self-contained diagnostic indicators.

### **CUSTOM PROGRAMMING**

The programming will match the template of the previous Surprise Fire Department unit #856 with SFD logo on main screen.

# Surprise Fire Dept

## Surprise, AZ

Light controls from both Vista screens as follows:

Position #1 All amber lights only

Position #2 All colored lights including position #1 lights

Position #3 All warning lights (Unitrol 480K electronic siren, Q2B siren, and clear lights wired to parking brake switch.)

Items controlled by the officers side Vista Display shall be:

The MPH of chassis

The Command Light control.

### **BATTERY SYSTEM**

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

A master load disconnect switch shall be provided between the starter solenoid(s) and the remainder of the electrical loads on the apparatus. The starter solenoids shall be connected directly to the batteries.

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

A green "battery on" pilot light that is visible from the driver's position shall be provided.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within five (5) seconds.

### **BATTERY SWITCH**

One (1) battery "On/Off" switch in cab located within easy reach of Driver with green "BATTERY ON" pilot light

# Surprise Fire Dept

## Surprise, AZ

that is visible from the driver's position shall be provided. The switch and pilot light shall be supplied and installed by the cab/chassis manufacturer.

### **BATTERY SOLENOID**

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

### **BATTERY CONDITIONER**

The battery conditioner shall be supplied and installed by the cab chassis manufacturer.

### **ENGINE COMPARTMENT LIGHT**

Engine compartment light(s) shall be supplied and installed by the cab chassis manufacturer.

### **REAR SCENE LIGHTS (BACK-UP LIGHTS)**

There shall be a switch on the streetside rear body panel to turn on scene lights during night operations. The switch shall be of momentary style and shall be connected to a bi-stable relay, allowing the light to also be switched from the cab V-Mux screen. The scene/reverse lights shall automatically shut off when the parking brake is disengaged.

### **CAB SPOTLIGHT**

There shall be **one (1) GoLight LED 20204** motorized, white, 12 VDC, 3 Amp, spotlight(s) that operates via a **wired dash mount controller with joystick and on/off button, one each side of the dash for both the officer and the driver to control it.** The joystick controls the motorized 135 degree tilt of the spotlight and the motorized rotation of the light a full 370 degrees. The light continues to move while the joystick is pressed. Once any button is released, the spotlight remains locked in that position until the joystick is moved again. The dash controller also turns the light on and off, so no additional switches are required. The dash mounted remote control allows for fingertip operation and is hard wired to the searchlight.

The Golight is mounted to the surface of vehicle using (4) stainless steel screws and a rubber gasket for a quick, safe and secure attachment. Light shall have a 3 year limited warranty.

#### **SHOP NOTES**

Model 20204 is white.

### **CAB HAZARD WARNING LIGHT**

A red flashing or rotating light, located in the driving compartment. The light shall be furnished by the cab/chassis manufacturer. The light shall be illuminated automatically whenever the vehicles parking brake is not fully engaged and any of the following conditions exist:

- 6) Any passenger or equipment compartment door is not closed.
- 7) Any ladder or equipment rack is not in the stowed position.
- 8) Stabilizer system is not in its stowed position.
  - Powered light tower is not stowed.
  - Any other device permanently attached to the apparatus is open, extended, or deployed in a manner that is likely to cause damage to the apparatus if the apparatus is moved.

# Surprise Fire Dept

## Surprise, AZ

Compartments and equipment meeting all of the following conditions shall be permitted to be exempt from being wired to the hazard light:

- The volume is less than or equal to 4 ft<sup>3</sup> (0.1 m<sup>3</sup>).
- The compartment has an opening less than or equal to 144 in.<sup>2</sup> (92,900 mm<sup>2</sup>).
- The open door does not extend sideways beyond the mirrors or up above the top of the fire apparatus.
- All equipment in the compartment is restrained so that nothing can fall out if the door is open while the apparatus is moving.
- Manually raised pole lights with an extension of less than 5 ft (1.5 m).

The hazard light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

### **BACK-UP ALARM**

An electronic back-up alarm shall be supplied and installed by the cab/chassis manufacturer. The back-up alarm shall actuate automatically when the transmission gear selector is placed in reverse.

### **REAR VIEW CAMERA**

The cab chassis provided rear view camera shall be installed on the rear of the body.

### **TAIL LIGHTS**

Rear body tail lights shall be vertically mounted and located per Federal Motor Vehicle Safety Standards, FMVSS and Canadian Motor Vehicle Safety Standards CMVSS. The following lights shall be furnished;

- Two (2) Whelen amber LED 600 Series 60A00TAR turn signal lights
- Two (2) Whelen red LED 600 Series 60BTT stop/tail lights
- Two (2) Whelen LED 600 Series 60C00WCR maximum intensity back-up lights with clear lens

Each of the lights above shall be mounted in a 6EFLANGE, chrome finish bezel.

### **MIDSHIP MARKER/TURN SIGNAL**

Two (2) Whelen model T0A00MAR 2" round amber LED midship body clearance marker/turn signal lights shall be provided and installed, one (1) light on each side of the body, in forward wheel well of rear axle. Midship marker/turn lights shall be wired to the headlight circuit of the chassis.

### **MARKER LIGHTS**

The body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) and Canadian Motor Vehicle Safety Standards (CMVSS) regulations. All body clearance lights shall be Truck-Lite Model 18 LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

### **CAB STEP LIGHTS / GROUND LIGHTS**

The step lights and/or ground lights shall be supplied and installed by the cab/chassis manufacturer. Light(s) shall be capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of

# Surprise Fire Dept

## Surprise, AZ

the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting designed to provide illumination on areas under the driver and crew riding area exits shall be switchable but activated automatically when the exit doors are opened.

### **LICENSE PLATE LIGHT**



One (1) Arrow #437 chrome plated LED license plate light shall be installed on the rear of the body. License plate light shall be wired to the headlight circuit of chassis. A fastener system shall be provided for license plate installation.

### **ELECTRONIC SIREN**

One (1) Federal/Unitrol U480K-15 electronic siren with sliding light control switch (60 amps maximum) shall be provided in the cab. Power shall be provided through the VMUX system "Master" warning lights. The VMUX menu provides selection of Position 1, 2, or 3 programming. Siren shall be wired as follows:

- Position 0 - Blocked
- Position 1 - Blocked
- Position 2 - Blocked
- Position 3 - All Lights and siren.

The siren shall be wired to the radio auxiliary speaker for the outside radio speaker in the "radio" mode.

### **VIBRATING TONES SOUND DEVICE SYSTEM**

**One (1) Federal Rumbler** vibrating tones sound device shall be provided. Rumbler shall be connected to specified primary electronic siren amplifier. Siren power shall be wired through the master warning light switch. The speakers for system shall be mounted under front of vehicle and protected from weather or road damage.

**Rumbler shall be controlled by a foot switch on the officers side floor.**

A Unitrol model UMNCT-B, noise canceling type microphone shall be provided for the PA system.

### **SIREN SPEAKER**

The siren speaker(s) shall be supplied and installed by the cab/chassis manufacturer.

### **SIDE SCENE LIGHTS**

There shall be four (4) Whelen Super LED 900 series (9" x 7") recess mounted scene lights (9SC0ENZR) provided on the upper body. Light quantity shall be divided equally per side. Each light will have twenty-four LED diodes that draw a total of 4.0 amps, with 3,000 lumens. The light shall be an 8-32 degree gradient lens and chrome flange.

Two (2) switches shall be provided, one (1) for the streetside scene lights, and one (1) for the curbside scene lights.

# Surprise Fire Dept

## Surprise, AZ

The lights shall be switched at the Vista display in the cab.

### **REAR SCENE LIGHTS**

Two (2) Whelen Super LED 600 series (6" x 4") **surface mounted scene lights** (60C0ELZR) shall be provided on the upper rear body to light the work area immediately behind the vehicle to a level of at least 3 fc (30 lx) within a 10 ft x 10 ft (3 m x 3 m) square. Each light will have twelve LED diodes. The light shall have an 8-32 degree gradient lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

### **DAVID CLARK INTERCOM SYSTEM**

The following David Clark intercom system shall be provided and installed to improve the safety of firefighters and rescue professionals through enhanced communication and hearing protection. System shall have the following major components as minimum;

One (1) U3800 - Mater station  
Two (2) U3815 - Radio interface/headset station  
One (1) U3806 - Dual headset intercom station  
One (1) U3805 - Radio cord junction module  
Three (3) C3812 - Jumper cord 12'  
Two (2) C3821 - Radio interface cord 21'  
One (1) C3820 - Power cord 20'  
Six (6) H3442 - Headsets Behind-the-Head style  
Two (2) 18352G-07 - MS Connector - 5 pin for remote PTT  
Two (2) 18352G-17 – MS connector 6 socket for radio cords

**NOTE: the system shall be wired thru both the 800mhz and the 150mhz radios with a PTT button on engine tunnel on the officers side.**

### **INTERCOM SYSTEM INSTALLATION**

The above listed intercom system shall be installed in the cab locations as follows;

#### **Front of Cab**

- Driver's – Mounted above the right shoulder position on ceiling.
- Officer's – Mounted above the left shoulder position on ceiling.

#### **Rear Crew Area**

- Driver's side rear facing – Above the right shoulder on the wall or ceiling.
- Driver's side rear facing center – Above the left shoulder on the ceiling.
- Officer's side rear facing – Above the left shoulder on the wall or ceiling.
- Officer's side rear facing center – Above the right shoulder on the ceiling.
- Driver's side forward facing – Above the right shoulder on the rear wall or ceiling.
- Driver's side forward facing center – Above the left shoulder on the rear wall or ceiling.



# Surprise Fire Dept

## Surprise, AZ

- Officer's side forward facing – Above the left shoulder on the rear wall or ceiling.
- Officer's side forward facing center – Above the right shoulder on the rear wall or ceiling.

### **WARNING LIGHT PACKAGE**

#### **SHOP NOTES**

#### **SP**

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four (4) warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four (4) zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two (2) separate signaling modes during emergency operations. One (1) mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One (1) mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two (2) signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

### **UPPER LEVEL OPTICAL WARNING DEVICES**

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

### **ZONE A - FRONT WARNING LIGHTS**

# Surprise Fire Dept

## Surprise, AZ

There shall be one (1) Whelen Edge FN72QLEDCUSTOM LED 72" lightbar permanently mounted to the cab roof.

The lightbar configuration (streetside to curbside) shall be:

<u>SECTION</u>	<u>INTERNAL COMPONENTS</u>	<u>LENS COLOR</u>
1	Red Linear LED - Side Facing	Clear
2	Red Corner LED	Clear
3	Blue Linear LED	Clear
4	Red Linear LED	Clear
5	Blue Liner LED	Clear
6	Red Linear LED	Clear
7	TOMAR IR Emitter	Clear
8	TOMAR IR emitter	Clear
9	Blue Linear LED	Clear
10	Red Linear LED	Clear
11	Blue Linear LED	Clear
12	Red Linear LED	Clear
13	Blue Corner LED	Clear
14	Blue Linear LED - Side Facing	Clear

All clear lights shall shut down when the parking brake is set to comply with "Blocking" mode requirements as outlined in NFPA 1901.

### SHOP NOTES

Copy Surprise #898

The lightbar shall be separately switched at the vista display in the cab.

### TOMARE TRAFFIC EMITTER

A Tomar IT traffic pre-emption emitter light shall be provided inside specified light bar. The emitter option may replace specified light(s) in specified light bar. The emitter shall be activated with light bar and de-activated when the park brake is set and the vehicle is in blocking mode.

**Match unit that was installed in job #898.**

### ZONES B AND D - SIDE WARNING LIGHTS

### UPPER REAR CORNER WARNING LIGHTS

# Surprise Fire Dept

## Surprise, AZ

There shall be two (2) Whelen 900 series (9" x 7") Linear Super-LED lights provided, one (1) each side. Each light shall have a red lens and chrome flange.

The streetside light will be red with a red lens and the curbside light will be blue with a blue lens.

The lights shall be switched at the Vista display in the cab.

### UPPER FORWARD CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Linear Super-LED lights provided, one (1) each side. Each light shall have a blue lens and chrome flange.

The streetside light will be blue with a blue lens and the curbside light will be red with a red lens.

#### SHOP NOTES

Street side light will be blue with a blue lens curb side light will be red with a red lens.

The lights shall be switched at the Vista display in the cab.

There shall be two (2) Whelen 500 series (5" x 2") amber Linear Super-LED lights (50A02ZCR) provided, one (1) each side of upper rear corners of cab. Each light shall be mounted in a white painted 45 degree bezel facing rear of vehicle. Each light shall have a clear lens and chrome flange.

Lights shall be mounted vertically to match previous job.

### ZONE C - REAR WARNING LIGHTS

There shall be four (4) Whelen 600 series (6" x 4") Linear Super-LED lights provided, two (2) each side. Each light shall have a chrome flange.

There will be one located above each upper scene light with an amber lens.

There will be one located below each scene light. The streetside light shall have a blue lens, the curbside light shall have a red lens.

#### SHOP NOTES

amber above scene lights blue street side and red curb side below scene light.

The lights shall be switched at the Vista display in the cab.

### LOWER LEVEL OPTICAL WARNING DEVICES

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1220 mm) above level ground for small apparatus.

# Surprise Fire Dept

## Surprise, AZ

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

### ZONE A - FRONT WARNING LIGHTS

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the Vista display in the cab.

### ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the Vista display in the cab.

### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY WHEELWELL AREA)

There shall be two (2) Whelen 500 series (5" x 2") Linear Super-LED lights provided, one (1) each side. Each light shall have a red lens and chrome flange.

The streetside shall have a blue lens, curbside light shall have a red lens.

#### SHOP NOTES

Street side blue curb side red.

The lights shall be switched at the Vista display in the cab.

### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Whelen 500 series (5" x 2") Linear Super-LED lights provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The streetside light shall have a blue lens, curbside light shall have a red lens.

#### SHOP NOTES

Street side blue curb side red

The lights shall be switched at the Vista display in the cab.

### ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") Linear Super-LED lights provided, one (1) each side. Each light shall have a red lens and chrome flange.

The streetside light shall have a red lens, curbside light shall have a blue lens.

# Surprise Fire Dept

## Surprise, AZ

### SHOP NOTES

Street side red with red lens curb side blue with blue lens

The lights shall be switched at the Vista display in the cab.

### **LINE VOLTAGE ELECTRICAL SYSTEM**

#### SHOP NOTES

SP

### **HYDRAULIC GENERATOR SYSTEM**

A Harrison HydraGen model 20.0MPC-16D, hydraulic driven generator set shall be installed on the vehicle. The generator shall be rated at 20,000 watts at 120/240 VAC, 166/83 amps, single phase. Current frequency shall be stable at 60 hertz.

A means shall be provided to activate the hydraulic generator system.

If the hydraulic generator system is not capable of output as stated on the power source specification label at all engine speeds, an automatic engine speed control system shall be provided.

If the vehicle is equipped with a fire pump driven by the chassis engine, the generator shall be capable of output as stated on the power source specification label with the engine at idle.

### **GENERATOR BONDING**

A minimum of four (4) 16" x 2 gauge copper ground straps shall be bolted to body sub-frame and chassis sub-frame for proper bonding of high voltage system. The conductor shall have a minimum amperage rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated amperage on the power source specification label.

### **GENERATOR MOUNTING**

The hydraulic generator module shall contain all system components necessary to comprise a complete hydraulic generating system. The components shall be grouped and assembled into a compact modular unit.

The generator unit shall be modular, packaged with a heavy steel protective frame. All connections to the module (both hydraulic and electrical) shall be easily removable for easy removal of unit from compartment.

Hydraulic oil reservoir and filter shall be easily accessible with adequate clearance to facilitate oil filling and filter changing.

### **WARRANTY PERIOD**

Provided such goods are operated and maintained in accordance with Harrison's written instructions, Harrison warrants that the MPC series hydraulic generators shall be free from defects in material and workmanship for a period of two (2) years or two thousand (2,000) hours, whichever comes first, from the date of delivery to the first purchaser.

# Surprise Fire Dept

## Surprise, AZ

### **HYDRAULIC COMPONENTS**

A hydraulic system filter and strainer shall be provided and shall be located in a readily accessible area.

Hydraulic hose shall meet the hydraulic pump manufacturer's recommendations for pressure, size, vacuum, and abrasion resistance. Hydraulic fittings shall meet the hydraulic pump manufacturer's recommendations for pressure, size, and the type of hose used.

Where the hydraulic hose comes into contact with other surfaces, the hose shall be protected from chafing.

The generator shall be engaged at the driver's Vista display in the cab.

### **GENERATOR MOUNTING**

The generator shall be mounted in an upper dunnage area or roof compartment on rubber vibration isolators. The compartment shall be reinforced and ventilated where necessary to hold weight and provide cooling air for the generator. A valve shall be provided on the generator oil drain outlet and piped to underside of generator compartment with flexible hose and plug. The drain shall be located where easily accessible for generator service.

### **MANUALS AND SCHEMATICS**

Two (2) complete manuals on parts list, maintenance, wiring schematics, hydraulic schematics, circuit boards, voltage regulator board and other components shall be provided on delivery.

There shall be a drain tube installed in the dunnage area near the generator with the tube draining down th the chassis frama and have alabel clearly inteifying it.The remaining seam around floor of dunnage area shall be completely caulked.

### **POWER-TAKE-OFF GENERATOR DRIVE**

There shall be a "Hot Shift" power-take-off (PTO) installed on the transmission PTO opening of the chassis. The "Hot Shift" PTO is provided to allow the engagement of the PTO at higher engine RPM speeds. The PTO output shall be connected to the generator through hollow tube type driveline with heavy duty universals.

The engagement of the PTO shall be in the chassis cab with a rocker switch and red pilot light to note engagement of the PTO or via the V-Mux screen if so equipped.

The power supply to the PTO engagement control shall be wired to the parking brake and a neutral position transmission switch to prevent engagement unless the vehicle is stopped and transmission has been placed in neutral.

The installation of the engine, transmission, driven accessories (power takeoffs (PTO), etc.) shall meet the engine and transmission manufacturers' installation recommendations for the service intended.

Model part number shall be Chelsea 859XSFJP-B5XV, 128% Ratio.

### **LOADCENTER**

The loadcenter shall be a Cutler Hammer, BR Series, specifically designed for protection and distribution of 120/240 volt AC, such as lighting and small motor branch circuits. The loadcenter enclosure shall be made of 16

# Surprise Fire Dept

## Surprise, AZ

gauge galvanized sheet steel. The galvanized coating provides corrosion protection and as such does not require paint. All trims used on the BR Loadcenter shall be chromate sealed and finished with electro disposition epoxy paint (ASA61) which exceeds requirements for outdoor and indoor applications. A combination surface/flush cover with integral door shall be supplied.

The loadcenter shall be UL/CSA listed, **NO EXCEPTIONS** will be allowed.

**Loadcenter to be located up in the coffin box on the curbside.**

### **GENERATOR MONITORING PANEL**

To properly monitor the generator performance and load demand during operation, the generator installation shall be equipped with a full instrument monitor panel.

- Generator frequency in hertz
- Line 1 current in amperes
- Line 2 current in amperes
- Generator voltage in volts

The program shall support the accumulation of elapsed generator hours. Generator hours shall be displayed.

The 120v load center shall be located up in the transverse upper body compartment offset to the curbside.

### **SHORE POWER INLET - BATTERY CHARGER**

The above mentioned shore power inlet, and battery conditioner shall be specified in the 12 volt section.

### **OUTLETS AND CIRCUITS**

The generator and or shore power shall supply the 120/240 volt electrical equipment and outlets outlined below. Proper circuit protection shall be installed as noted:

One (1) 120 volt exterior outlets, located in center of front bumper compartment center section, high on rear wall as close to the hinged lid as possible to allow usage without removing any tools to access it.


#### **SHOP NOTES**

One outlet located in center tool compartment on back wall high

- The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).

**Two (2) 120 volt exterior outlets, both located on the rear of the body on the curbside above the folding step.**

#### **SHOP NOTES**

- The outlet receptacle(s) shall be 20 , twist-lock (NEMA L5-20R).

The 120v outlets shall be wired thru the **generator only**.

# Surprise Fire Dept

## Surprise, AZ

### LINE VOLTAGE ELECTRICAL SYSTEM

#### GENERAL REQUIREMENTS

##### Stability

Any fixed line voltage power source producing alternating current (ac) shall produce electric power at 60 Hz,  $\pm 3$  Hz when producing power at all levels between no load and full rated power. Any fixed line voltage power source shall produce electric power at the rated voltage  $\pm 10$  percent when producing power at all levels between no load and full rated power.

The maximum voltage supplied to portable equipment shall not exceed 275 volts to ground. Higher voltage shall be permitted only when used to operate fixed wired, permanently mounted equipment on the apparatus.

##### Conformance with National Electrical Code

All components, equipment, and installation procedures shall conform to *NFPA 70, National Electrical Code*, except where superseded by the requirements of this chapter. Where the requirements of this chapter differ from those in *NFPA 70*, the requirements in this chapter shall apply.

Where available, line voltage electrical system equipment and materials included on the apparatus shall be listed and used only in the manner for which they have been listed. All equipment and materials shall be installed in accordance with the manufacturer's instructions.

##### Location Ratings

Any equipment used in a dry location shall be listed for dry locations. Any equipment used in a wet location shall be listed for wet locations.

Any equipment, except a PTO-driven generator, used in an underbody or under chassis location that is subject to road spray shall be either listed as Type 4 or mounted in an enclosure that is listed as Type 4.

If a PTO-driven generator is located in an underbody or under chassis location, the installation shall include a shield to prevent road spray from splashing directly on the generator.

##### Grounding

Grounding shall be in accordance with 250.34(A) and 250.34(B) of *NFPA 70*. Ungrounded systems shall not be used.

Only stranded or braided copper conductors shall be used for grounding and bonding.

The grounded current-carrying conductor (neutral) shall be insulated from the equipment-grounding conductors and from the equipment enclosures and other grounded parts.

The neutral conductor shall be colored white or gray in accordance with 200.6, "Means of Identifying Grounded Conductors," of *NFPA 70*.



# Surprise Fire Dept

## Surprise, AZ

Any bonding screws, straps, or buses in the distribution panel board or in other system components between the neutral and equipment-grounding conductor shall be removed and discarded.

### Bonding

The neutral conductor of the power source shall be bonded to the vehicle frame. The neutral bonding connection shall occur only at the power source. In addition to the bonding required for the low voltage return current, each body and each driving or crew compartment enclosure shall be bonded to the vehicle frame by a copper conductor.

The conductor shall have a minimum ampere rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated ampere on the power source specification label.

A single conductor that is sized to meet the low voltage and line voltage requirements shall be permitted to be used.

### Ground Fault Circuit Interrupters

In special service vehicles incorporating a lavatory, sink, toilet, shower, or tub, 120 V, 15 or 20 A receptacles within 6 ft (1.8 m) of these fixtures shall have ground fault circuit interrupter (GFCI) protection. GFCIs integrated into outlets or circuit breakers or as stand-alone devices shall be permitted to be used in situations.

### Power Source General Requirements

All power source system mechanical and electrical components shall be sized to support the continuous duty nameplate rating of the power source.

The power source shall be shielded from contamination that would prevent the power source from operating within its design specifications.

### Power Source Rating

For power sources of 8 kW or larger, the power source manufacturer shall declare the continuous duty rating that the power source can provide when installed on fire apparatus according to the manufacturer's instructions and run at 120°F (49°C) air intake temperature at 2000 ft (600 m) above sea level.

The rating on the power source specification label shall not exceed the declared rating from the power source manufacturer.

Access shall be provided to permit both routine maintenance and removal of the power source for major servicing. The power source shall be located such that neither it nor its mounting brackets interfere with the routine maintenance of the fire apparatus.

### Instrumentation

If the power source is rated at less than 3 kW, a "Power On" indicator shall be provided. If the power source is rated at 3 kW or more but less than 8 kW, a voltmeter shall be provided.

If the power source is rated at 8 kW or more, the following instrumentation shall be provided at an operator's panel:

- Voltmeter
- Current meters for each ungrounded leg

# Surprise Fire Dept

## Surprise, AZ

- Frequency (Hz) meter
- Power source hour meter

The instrumentation shall be permanently mounted at an operator's panel. The instruments shall be located in a plane facing the operator. Gauges, switches, or other instruments on this panel shall each have a label to indicate their function.

The instruments and other line voltage equipment and controls shall be protected from mechanical damage and not obstructed by tool mounting or equipment storage.

An instruction plate(s) that provides the operator with the essential power source operating instructions, including the power-up and power-down sequence, shall be permanently attached to the apparatus at any point where such operations can take place.

### Operation

Provisions shall be made for placing the generator drive system in operation using controls and switches that are identified and within convenient reach of the operator.

Where the generator is driven by the chassis engine and engine compression brakes or engine exhaust brakes are furnished, they shall be automatically disengaged for generator operations.

Any control device used in the generator system power train between the engine and the generator shall be equipped with a means to prevent unintentional movement of the control device from its set position in the power generation mode.

If there is permanent wiring on the apparatus that is designed to be connected to the power source, a power source specification label that is permanently attached to the apparatus at the operator's control station shall provide the operator with the information required.

The power source, at any load, shall not produce a noise level that exceeds 90 dBA in any driving compartment, crew compartment, or onboard command area with windows and doors closed or at any operator's station on the apparatus.

### Power Supply Assembly

The conductors used in the power supply assembly between the output terminals of the power source and the main over current protection device shall not exceed 12 ft (4 m) in length.

All power supply assembly conductors, including neutral and grounding conductors, shall have an equivalent amperage rating and shall be sized to carry not less than 115 percent of the amperage of the nameplate current rating of the power source.

If the power supply assembly connects to the vibrating part of a generator (not a connection on the base), the conductors shall be flexible cord or other fine-stranded conductors enclosed in metallic or nonmetallic liquid tight flexible conduit rated for wet locations and temperatures not less than 194°F (90°C).

### Overcurrent Protection

Manually resettable over current devices shall be installed to protect the line voltage electrical system components.

# Surprise Fire Dept

## Surprise, AZ

### Power Source Protection

A main over current protection device shall be provided that is either incorporated in the power source or connected to the power source by a power supply assembly.

The size of the main over current protection device shall not exceed 100 percent of the rated amperage stated on the power source specification label or the rating of the next larger available size over current protection device, where so recommended by the power source manufacturer.

If the main over current protection device is subject to road spray, the unit shall be housed in a Type 4-rated enclosure.

### Branch Circuit Overcurrent Protection

Over current protection devices shall be provided for each individual circuit and shall be sized at not less than 15 amps in accordance with 240.4, "Protection of Conductors," of *NFPA 70*.

Any panel board shall have a main breaker where the panel has six or more individual branch circuits or the power source is rated 8 kW or larger.

Each over current protection device shall be marked with a label to identify the function of the circuit it protects.

Dedicated circuits shall be provided for any large appliance or device (air conditioning units, large motors, etc.) that requires 60 percent or more of the rated capacity of the circuit to which it is connected, and that circuit shall serve no other purpose.

### Panelboards

All fixed power sources shall be hardwired to a permanently mounted panel board unless one of the following conditions exists:

- All line voltage power connections are made through receptacles on the power source and the receptacles are protected by integrated over current devices.
- 1) Only one circuit is hardwired to the power source, which is protected by an integrated over current device.

The panel shall be visible and located so that there is unimpeded access to the panel board controls. All panel boards shall be designed for use in their intended location. The panel(s) shall be protected from mechanical damage, tool mounting, and equipment storage.

Where the power source is 120/240 V and 120 V loads are connected, the apparatus manufacturer or line voltage system installer shall consider load balancing to the extent that it is possible.

### Wiring Methods

Fixed wiring systems shall be limited to the following:

- 2) Metallic or nonmetallic liquid tight flexible conduit rated at temperatures not less than 194°F (90°C) with stranded copper wire rated for wet locations and temperatures not less than 194°F (90°C)
- 3) Type SOW, SOOW, SEOW, or SEOOW flexible cord rated at 600 V and at temperatures not less than 194°F (90°C)

# Surprise Fire Dept

## Surprise, AZ

Electrical cord or conduit shall not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring and shall be arranged as follows:

- 4) Separated by a minimum distance of 12 in. (300 mm) from exhaust piping or shielded from such piping
- 1) Separated from fuel lines by a minimum distance of 6 in. (150 mm)

A means shall be provided to allow “flexing” between the driving and crew compartment, the body, and other areas or equipment whose movement would stress the wiring.

Electrical cord or conduit shall be supported within 6 in. (150 mm) of any junction box and at a minimum of every 24 in. (600 mm) of run.

Supports shall be made of nonmetallic materials or of corrosion-resistant or corrosion-protected metal. All supports shall be of a design that does not cut or abrade the conduit or cord and shall be mechanically fastened to the apparatus.

Only fittings and components listed for the type of cord or conduit being installed shall be used.

Splices shall be made only in a listed junction box.

### Additional Requirements for Flexible Cord Installations

Where flexible cord is used in any location where it could be damaged, it shall be protected by installation in conduit, enclosures, or guards.

Where flexible cord penetrates a metal surface, rubber or plastic grommets or bushings shall be installed.

### Wiring Identification

Each line voltage circuit originating from the main panel board shall be identified.

The wire or circuit identification either shall reference a wiring diagram or wire list or shall indicate the final termination point of the circuit.

Where pre-wiring for future power sources or devices exists, the un-terminated ends shall be marked with a label showing their wire size and intended function.

### Wiring System Components

Only stranded copper conductors with an insulation rated for temperatures of at least 194°F (90°C) and wet locations shall be used. Conductors in flexible cord shall be sized in accordance with Table 400.5(A) of *NFPA 70*. Conductors used in conduit shall be sized in accordance with 310.15, “Ampacities for Conductors Rated 0–2000 Volts,” of *NFPA 70*. Aluminum or copper-clad aluminum conductors shall not be used.

All boxes shall conform to and be mounted in accordance with Article 314, “Outlet, Device, Pull, and Junction Boxes; Conduit Bodies; Fittings; and Manholes,” of *NFPA 70*. All boxes shall be accessible using ordinary hand tools. Boxes shall not be permitted behind welded or pop-riveted panels.

The maximum number of conductors permitted in any box shall be in accordance with 314.16, “Number of Conductors in Outlet, Device, and Junction Boxes, and Conduit Bodies,” of *NFPA 70*.

# Surprise Fire Dept

## Surprise, AZ

All wiring connections and terminations shall provide a positive mechanical and electrical connection. Connectors shall be installed in accordance with the manufacturer's instructions. Wire nuts or insulation displacement and insulation piercing connectors shall not be used.

Each switch shall indicate the position of its contact points (i.e., open or closed) and shall be rated for the continuous operation of the load being controlled. All switches shall be marked with a label indicating the function of the switch. Circuit breakers used as switches shall be "switch rated" (SWD) or better. Switches shall simultaneously open all associated line voltage conductors. Switching of the neutral conductor alone shall not be permitted.

Line voltage circuits controlled by low voltage circuits shall be wired through properly rated relays in listed enclosures that control all non-grounded current-carrying conductors.

### Receptacles and Inlet Devices

#### Wet and Dry Locations

All wet location receptacle outlets and inlet devices, including those on hardwired, remote power distribution boxes, shall be of the grounding type, provided with a wet location cover, and installed in accordance with Section 406.8, "Receptacles in Damp or Wet Locations," of *NFPA 70*.

All receptacles located in a wet location shall be not less than 24 in. (600 mm) from the ground. Receptacles on off road fire apparatus shall be a minimum of 30 in. (750 mm) from the ground. All receptacles located in a dry location shall be of the grounding type and shall be at least 12 in. (300 mm) above the interior floor height. No receptacle shall be installed in a face-up position.

The face of any wet location receptacle shall be installed in a plane from vertical to not more than 45 degrees off vertical.

#### Receptacle Label

Each receptacle shall be marked with a label indicating the nominal line voltage (120 volts or 240 volts) and the current rating in amps of the circuit. If the receptacle is DC or other than single phase, that information shall also be marked on the label.

All receptacles and electrical inlet devices shall be listed to UL 498, *Standard for Safety Attachment Plugs and Receptacles*, or other recognized performance standards.

Receptacles used for DC voltages shall be rated for DC service.

### Wiring Schematics

An "As-Built" Wiring diagrams for line voltage systems shall be provided to include the following information;

- 2) Pictorial representations of circuit logic for all electrical components and wiring
  - 1) Circuit identification
  - 2) Connector pin identification
  - 1) Zone location of electrical components
  - 2) Safety interlocks
  - (a) Alternator–battery power distribution circuits
  - (b) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems

# Surprise Fire Dept

## Surprise, AZ

### **120/240 VAC SCENE LIGHTING**

#### **FRONT CAB-MOUNTED SCENE LIGHT(S)**

Floodlight(s) shall be provided on the front of the cab by the cab/chassis manufacturer. Each light shall be mounted in a brow-style mounting flange with a lens or a means for preventing damage from water spray and listed for wet location usage.

Each light shall be wired directly to the electrical generator system with Carflex conduit and stranded copper wire. The floodlights shall be protected with circuit breakers rated at the proper amperage and wire size.

The lights shall be switched at the Vista display in the cab.

#### **LIGHT TOWER**

One (1) Command Light, CL Series light tower(s) shall be provided and installed on the completed unit. A flashing warning light shall be provided in cab, indicating when a light tower is not in nested position as required by NFPA 1901.

The Command Light shall be covered by a five (5) year limited warranty from defects in materials and workmanship. An operation, maintenance, and parts manual shall be provided with the completed unit.

The light tower shall extend 131" above the mounting surface and shall extend to full upright position in less than 15 seconds. The overall size of nested light tower shall be approximately 42" wide x 74" long x 12" high and weigh approximately 300 pounds.

#### **Light Tower Construction and Design**

The Command Light assembly shall be of aluminum construction, with stainless steel shafts and bronze bushings for long life and low maintenance.

The electrically controlled unit shall not require usage of the vehicle's air supply for operation, thereby eliminating the chance for air leaks in the vehicle braking system. Hydraulic or pneumatic type floodlights are not acceptable alternatives to the specified all electric light tower.

The light tower shall be tested to in wind conditions of 90 mph (150 kph) minimum. Light towers that have not been tested to these conditions are not acceptable.

The light tower shall be capable of overhanging the side or back of the vehicle to provide maximum illumination to the vicinity adjacent to the vehicle for the safety of emergency personnel in high traffic conditions. Light towers that are only capable of rotation at the top of a pole are not acceptable to the specified light tower.

#### **Light Tower Electrical System**

The light tower shall be a two-stage articulating device with a lighting bank on top of the second stage capable of continuous 360 degree rotation. The light shall be elevated by electric linear actuators, one (1) actuator shall elevate the light bank and one (1) actuator shall adjust the light bank angle from 0 to 110 degrees. Power for the light bank shall be supplied through power collecting rings thus allowing continuous 360 degree rotation in either direction.

The tower base shall have a light that illuminates the envelope of motion during any movement of the light tower mast as required by NFPA 1901.

# Surprise Fire Dept

## Surprise, AZ

### Light Tower Floodlights

The Command Light model CL615-MH2 shall be equipped with the following bank of floodlights:

Floodlight manufacturer:	Hubbell Quartz/ Akron Brass MH
Number of lamp heads:	Four (4) 1,500 watt Quartz Halogen Two (2) 1,000 watt Extenda-Lite Metal Halide
Voltage:	240 volts
Total watts of light tower:	8,000 watts
Total lumens of light tower:	350,000 lumens
Configuration:	The light heads shall be mounted with three (3) on each side of the light tower, giving two (2) vertical lines of three (3) when the lights are in the upright position.

### Light Tower Backlight Option

A backlight option shall be provided on the light tower. The lower pair of light heads shall be capable of being rotated about a horizontal axis 180 degree, providing light down on the vehicle or to the opposite side of the vehicle while allowing the fixed lights to remain pointed at the scene.

The hand-held remote control shall have an additional switch supplied for the backlight rotation option.

### Light Tower Paint

The light tower shall be electrostatically powder coated with a hammer tone gray color.

### Light Tower Controls: Wired Hand-held and Multiplex

The light tower(s) shall be controlled by both the specified Weldon multiplex Vista display in cab and with a hand-held 15-foot umbilical line remote control. The Vista display shall have a button programmed to take control from the wired controller. The program shall have four (4) different programmed quadrants to raise and face light tower too. System shall require a Weldon Node to control light tower system. The wired hand-held storage station shall have a switch to take control from the Vista display in cab.

The storage station for the remote control unit shall be equipped with a button to activate the "Auto-Park" automatic nesting feature. The remote control shall be located per the itemized compartment list and include;

Three (3) switches; one (1) for each pair of lights.

One (1) switch for light bank rotation.

One (1) switch for elevating lower stage.

One (1) switch for elevating upper stage.

One (1) switch for optional light bank rotation.

One (1) switch for the optional strobe.

One (1) indicator light to indicate when light bank is out of the roof nesting position.

One (1) indicator light to indicate when light bank is rotated to proper nesting position.

### Light Tower Mounting

The specified light tower(s) shall be recessed into the roof of body to allow light tower(s) to be stowed below roof level. The floor and side walls of recessed area shall be fabricated as a separate module from 3/16" aluminum

# Surprise Fire Dept

## Surprise, AZ

treadplate with an overlapping 3" flange around perimeter roof line. The recessed area shall be completely water tight. All electrical connections made to light tower shall be located on sidewalls for a water tight connection.

The recessed area shall have two (2) water drain holes (in opposite corners) with flexible 1" diameter hose routed to the area below the body.

### **WATEROUS CL 500 GPM SINGLE STAGE FIRE PUMP**

A Waterous Model CLVK fire pump shall be midship mounted, single stage construction and shall comply with all applicable requirements of the latest standards for automotive fire apparatus of the National Fire Protection Association, NFPA 1901, and shall have a rated capacity of 500 GPM.

The CLVK is capable of supplying volumes of 500 GPM (2000 L/min) @ 150 psi (10.3 bar) or pressures of 400 psi (28 bar) @ 60 GPM (227 L/min). When installed in vehicle, complete with proper intake piping, CL meets NFPA 1901 for a 500 GPM rating.

#### Casing

One-piece, high-tensile, ductile iron.

#### Impeller

Bronze, fully enclosed, double-hubbed to balance hydraulic thrust, mechanically balanced to eliminate vibration.

#### Wear Rings

Replaceable wear rings to increase pump life and maintenance costs down.

#### Impeller Shaft

Stainless steel, heat treated, ground to precise size, and polished under shaft seal. Fully supported by anti-friction bearings.

#### Intake

4.0" (10.1 cm) NPT

#### Discharge

5.0" (12.7 cm) NPT

#### Discharge Positions

Available in either rotation with four discharge positions; gear case can be mounted horizontally, vertically, or inverted.

#### Bearings

All bearings are oil or grease lubricated, ball type, located outside the pump casting to accurately align and support the impeller shaft assembly. Ball bearings are deep-grooved type designed to carry both radial and axial thrust.

#### Transmission

K Series, close-grained, gray iron with the proper gear ratio to provide required impeller speeds at available input speeds, whether pumping from tank, draft, or in relay operation.

#### Transmission Gears

Helical, precision cut, crown shaved for proper load distribution and quiet operation.

### **PAINT FINISH**



# Surprise Fire Dept

## Surprise, AZ

The paint finish will be red primer from pump manufacturer.

### **PUMP DRIVE SYSTEM**

The water system pump shall be driven by a Chelsea "Hot-Shift" transmission PTO and shall be mounted directly to the transmission of the chassis. The drive line shall be hollow tube type, with heavy duty universals and splined shaft, to allow movement of the chassis components and pump.

The engagement of the PTO shall be in the chassis cab with a rocker switch and red pilot light to note engagement of the PTO.

The power supply to the PTO engagement control shall be wired to a neutral position transmission switch to prevent engagement unless the vehicle is in neutral with the parking brake set.

Two (2) green indicator lights shall be supplied in the chassis cab. One (1) light shall be energized when the chassis transmission is in neutral and shall be labeled "OK TO PUMP", the second light shall engage when the pump drive (PTO) has been engaged and shall be labeled "PUMP ENGAGED".

One (1) green indicator light shall be supplied at the Pump Operator's panel adjacent to the engine hand throttle. The green light shall be energized when both the chassis transmission is in neutral and the pump drive (PTO) has been engaged. Green light shall be labeled "OK TO PUMP".

Model part number shall be Chelsea 280GKFJP-B5XV, 164% Ratio.

### **PUMP PACKINGS**

The stuffing boxes shall be equipped with two-piece adjustable Grafoil packing glands.

### **1/2" PUMP COOLER LINE**

There shall be a 1/2" line installed from the discharge side of the pump to the water tank. The line shall be used to cool the pump during long periods of pumping when water is not being discharged. The pump cooler shall be controlled with a quarter-turn ball valve on operators panel, and shall be clearly labeled "Pump Cooler".

### **PUMP COOLER CHECK VALVE**

There shall be a check valve installed in the pump cooler line to prevent tank water from back flowing into the pump when it is not in use.

### **WATEROUS FIVE YEAR PUMP WARRANTY**

The fire pump shall be warranted by Waterous for a period of five (5) years from the date of delivery to the Surprise Fire Department.

### **MANUFACTURER FIRE PUMP TEST**

The pump shall undergo a manufacturer's test per applicable sections of NFPA 1901 standards, prior to delivery of the completed apparatus.

# Surprise Fire Dept

## Surprise, AZ

The test shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming device tests, and the vacuum test.

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 500 psi (3400 kPa) for a minimum for 10 min. The pump shall be fully tested at the pump manufacturer's factory to the performance specifications as outlined by applicable NFPA 1901 standards.

The results of this test shall be furnished with the vehicle on delivery.

### **FIRE PUMP TEST LABEL**

A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve

The pump shall comply with the applicable requirements of "Standard for Fire Apparatus 1901, latest edition.

The pump shall be capable of producing fire streams that are free from objectionable pulsation under all normal operating conditions.

### **ALTITUDE REQUIREMENT**

The apparatus shall be designed to meet the specified rating at 2,000 feet (610 meters) altitude.

### **PUMP DRAIN VALVE**

A manifold drain valve assembly shall be supplied. This drain shall provide the capability to drain the entire pump by pulling a single control. The valve assembly shall consist of a stainless steel plunger in a bronze body with multiple ports.

Drain shall be controlled by a T-handle .

### **PUMP DRAIN CONTROL**

The pump drain shall be controlled at the pump operator's panel and identified as "Pump Drain". The control shall be provided in the form of a "T" handle control that is easily actuated with a gloved hand.

### **DISCHARGE RELIEF VALVE**

The discharge pressure relief shall be controlled by the electronic engine controlled device as specified.

### **HEAT EXCHANGER**

A heat exchanger shall be provided on the pump driving engine cooling system that uses water from the discharge side of the pump to cool the engine coolant through the use of a closed heat exchanger. The water from the pump and the engine coolant shall not be intermixed. This cooling system shall be controlled by a T-handle valve on the pump operator's panel.

# Surprise Fire Dept

## Surprise, AZ

### **INTAKE RELIEF VALVE**

There shall be an Akron model 59 intake relief valve factory set to 125 PSI installed on the suction side of the pump. The system shall be controlled by an adjustable valve and designed to prevent vibration from altering the setting of the valve. Provisions for adjusting or servicing the valve {will/shall} be provided. The relief outlet shall be directed below the pump with the discharge terminating in a 2-1/2" NSTM connection. The discharge shall be away from the pump operator and labeled "DO NOT CAP".

### **PLUMBING SPECIFICATIONS**

The fire pump plumbing system shall be of rigid or flexible piping with stainless steel fittings. Victaulic couplings shall be installed to permit flexing of the plumbing system and allow for quick removal of piping or valves for service. Flexible hose couplings shall be threaded stainless steel or Victaulic connections.

The fire pump and plumbing shall be hydrostatically tested in compliance to applicable sections of NFPA standards, with test results submit with the delivery documentation.

### **STAINLESS STEEL INTAKE MANIFOLD**

The suction manifold assembly shall be fabricated with Schedule #10 type 304 stainless steel. All threaded fittings shall be a minimum of Schedule 10 stainless steel. The suction manifold assembly shall have radiused sweep elbows to minimize water turbulence into the suction volute.

The suction manifold shall be welded and pressure tested prior to installation. The stainless steel manifold assembly shall be attached to the pump intake volute with a heavy-duty, flexible Victaulic coupling.

### **STAINLESS STEEL DISCHARGE MANIFOLD**

The discharge manifold assembly shall be fabricated with Schedule #10 type 304 stainless steel. All threaded fittings shall be a minimum of Schedule 10 stainless steel. The discharge manifold assembly shall have radiused sweep elbows to minimize water turbulence into the discharge header.

The manifold shall be welded and pressure tested prior to installation. The stainless steel manifold assembly shall be attached to the pump intake volute with a heavy-duty, flexible Victaulic coupling.

### **STAINLESS STEEL PLUMBING WARRANTY**

The stainless steel plumbing shall be free of defects in material and workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

The contractor shall supply details of their warranty information with their bid submission.

### **INTAKES**

The pump shall have a sufficient number and size of intakes to perform the apparatus pump system certification test. The intakes shall have male National Hose Threads (NST) if the apparatus is to be used in the United States.

If the couplings on the suction hose carried on the apparatus are of a different size from that of the pump intake(s)

# Surprise Fire Dept

## Surprise, AZ

or have means of hose attachment other than that provided on the intake(s), an adapter(s) shall be provided to allow connection of the suction hose to the pump intake(s).

A sign shall be provided on the pump operator's panel that states the following:

**WARNING:** Death or serious injury might occur if proper operating procedures are not followed. The pump operator as well as individuals connecting supply or discharge hoses to the apparatus must be familiar with water hydraulics hazards and component limitations.

Each intake shall have a removable or accessible strainer inside the connection. The strainer(s) shall restrict spherical debris that is too large to pass through the pump.

At least one valved intake shall be provided that can be controlled from the pump operator's position. The valve and piping shall be a minimum 2-1/2 in. (65 mm) nominal size.

If the intake is 2-1/2 in. (65 mm) nominal size, the intake shall be equipped with a female swivel coupling with NH threads. Any 3 in. (75 mm) or larger intake valve except the tank-to-pump intake valve shall be a slow-operating valve.

Each valved intake shall be equipped with a bleeder valve having a minimum 3/4 in. (19 mm) pipe thread connection to bleed off air or water. The bleeder valve shall be operational without the operator having to get under the apparatus. If a valved appliance is attached to an intake, it shall be equipped with a 3/4 in. (19 mm) bleeder valve on each intake. Bleeder valves for valved intakes 4 in. (100 mm) and larger not located at the pump operator's panel shall be located where the bleeder valve controls are visible and operationally functional while the operator remains stationary at the valved intake position.

Each valved intake having a connection size larger than 3 in. (75 mm) shall be equipped with an adjustable automatic pressure relief device installed on the supply side of the valve to bleed off pressure from a hose connected to the valved intake.

All intakes shall be provided with caps or closures capable of withstanding a hydrostatic gauge pressure of 500 psi (3400 kPa). Intakes having male threads shall be equipped with caps; intakes having female threads shall be equipped with plugs. Where adapters for special threads or other means for hose attachment are provided on the intakes, closures shall be provided for the adapters in lieu of caps or plugs. Caps or closures for intake connections smaller than 4 in. (100 mm) shall remain secured to the apparatus when removed from the connection.

If the suction inlets are to be equipped with a valve, siamese, or adapter that will remain in place while the apparatus is in motion, that valve, siamese, or adapter shall not project beyond the apparatus running board. The purchaser shall specify if any valve, siamese, or adapter is to be permanently installed on an intake and identify the brand and model of such item.

The completed apparatus shall have the following intake(s);

### **STREETSIDE INTAKE - 3-1/2"**

There shall be one (1) 3-1/2" (89 mm) gated intake(s) located on pump panel. Each intake shall include:

- (c) One (1) Akron Brass 8800 series slow-operating, manual type 3-1/2" (89 mm) valve(s). Each valve shall be equipped with a brass type valve adapter on inlet side, and discharge side with drain port.

# Surprise Fire Dept

## Surprise, AZ

- (d) Valve(s) shall be controlled with a handle for direct valve operation through panel.
- (e) Each intake shall have a 3-1/2" (89 mm) NSTF polished aluminum swivel adapter with strainer provided.
- (f) The specified adapter shall be provided with a 3-1/2" (89 mm) NSTM polished aluminum plug with chain.
- (g) One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.

### **TANK TO PUMP CHECK VALVE**

There shall be a check valve between the pump suction and the booster tank valve. The check valve shall eliminate back flow into the water tank when the pump is connected to a pressurized source.

### **TANK TO PUMP VALVE**

A 3" (75 mm) full flow ball valve shall be installed between the fire pump and the water tank. The connection between the tank and the pump shall be capable of the flow recommendations as set forth in the latest edition of NFPA 1901. The valve shall be flanged to bolt directly to the pump and shall incorporate a chromium plated bronze ball. The remaining internal moving parts shall be stainless steel for years of dependable service. A non collapsible flexible hose shall be incorporated into the tank to pump plumbing to allow movement in the line as the chassis flexes to avoid damage during normal road operation.

The tank to pump valve shall be controlled from the pump operator's panel.

- Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
- An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.

### **DISCHARGES**

A minimum of two 2-1/2 in. (65 mm) outlets shall be provided on any pump rated at 750 gpm (3000 L/min) or greater, and a minimum of one 2-1/2 in. (65 mm) outlet shall be provided on any pump rated at less than 750 gpm (3000 L/min).

All 1-1/2" (65 mm) or larger discharge outlet connections shall be equipped with male National Hose Threads (NST). Adapters with special threads or other means for hose attachment shall be permitted to be attached to any outlets.

The piping and valves supplying any preconnected 1-1/2 in. (38 mm), 1-3/4 in. (45 mm), or 2 in. (52 mm) hose line, including the piping to the preconnected hose storage areas shall be at least 2 in. (52 mm) in size.

All discharge outlet connections, except connections to which a hose will be preconnected, shall be equipped with caps or closures capable of withstanding a hydrostatic gauge pressure of 100 psi (700 kPa) over the maximum pump close-off pressure or 500 psi (3400 kPa), whichever is greater.

Where adapters are provided on the discharge outlet connections, the closures shall fit on the adapters.

Caps or closures for outlet connections smaller than 4 in. (100 mm) shall remain secured to the apparatus when removed from the connection.

# Surprise Fire Dept

## Surprise, AZ

Each discharge outlet shall be equipped with a valve that can be opened and closed smoothly at pump discharge gauge pressures of 250 psi (1700 kPa).

The flow-regulating element of each valve shall not change its position under any condition of operation that involves discharge pressures to the maximum pressure of the pump; the means to prevent a change in position shall be incorporated in the operating mechanism and shall be permitted to be manually or automatically controlled.

Any 3 in. (75 mm) or larger discharge valve shall be a slow-operating valve.

All 1-1/2 in. (38 mm) or larger discharge outlets shall be equipped with a drain or bleeder valve having a minimum 3/4 in. (19 mm) pipe thread connection for draining or bleeding off pressure from a hose connected to the outlet.

Any 2 in. (52 mm) or larger discharge outlet that is located more than 42 in. (1070 mm) off the ground to which hose is to be connected and that is not in a hose storage area shall be supplied with a sweep elbow of at least 30 degrees downward.

The completed apparatus shall have the following discharge(s);

### **STREETSIDE DISCHARGE**

There shall be one (1) 2-1/2" (65 mm) gated discharge(s) located on pump panel. Each discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8000 series, manual type 2-1/2" (65 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a handle for direct valve operation through panel.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM polished aluminum 30 degree downsweep elbow provided.
  - The specified elbow shall be provided with a 2-1/2" (65 mm) NSTF polished aluminum cap with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s)
  - This gauge(s) shall have the IC Nite Glo Gauge. Match style to previous unit job #898.
- The above gauge shall have a range from 0 to 400 PSI.

# Surprise Fire Dept

## Surprise, AZ

### MISCELLANEOUS DISCHARGE

#### 2" SPEED LAY(S)

There shall be one (1) 2" speed lay(s) located in pump module, or per the itemized compartment list. The speedlay(s) shall be transverse of the pump module or body with access from either side.

Each speed lay shall have a minimum storage capacity of 200' of 1-3/4" double jacket hose and nozzle.

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8600 series, actuated type 2" (52 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
- An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.
- There shall be a 2" (52 mm) VFC x 1-1/2" (38 mm) NSTM 90 degree brass chicksan swivel elbow provided for each discharge.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s)
  - This gauge(s) shall be an IC brand with Nite Glo style.
  - Match style used on previous job #898.
- The above gauge shall have a range from 0 to 400 PSI.

#### 2-1/2" SPEED LAY(S)

There shall be one (1) 2-1/2" speed lay(s) located in pump module, or per the itemized compartment list. The speedlay(s) shall be transverse of the pump module or body with access from either side.

Each speed lay shall have a minimum storage capacity of 200' of 2-1/2" double jacket hose and nozzle.

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8600 series, actuated type 2-1/2" (65 mm) valve(s). Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.

# Surprise Fire Dept

## Surprise, AZ

- An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.
- There shall be a 2" (52 mm) VFC x 1-1/2" (38 mm) NSTM 90 degree brass chicksan swivel elbow provided for each discharge.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valves shall be located on bottom of pump panel and plumbed to drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s)
  - This gauge(s) shall be an IC brand with Nite Glo style.
  - Match style used on previous job #898.
- The above gauge shall have a range from 0 to 400 PSI.

### **TANK FILL VALVE**

There shall be one (1) 2" (52 mm) tank fill valve plumbed with 2" plumbing from the pump to the tank. Installation shall be completed with 2" rubber hose and stainless steel hose couplings. The tank fill valve shall be controlled from the operator's control panel.

- One (1) Akron Brass 8600 series, actuated type 2" (52 mm) valve(s). Each valve shall be equipped with a brass type valve adapter on inlet side, and discharge side with drain port.
  - Akron valve(s) shall be controlled with a remote handwheel connected to the gear actuated valve.
- An Akron portrait layout handwheel actuator with NFPA compliant valve position indicator shall be located on the pump operator's panel.

### **PUMP PANEL**

The rescue vehicle side mount pump controls shall be mounted on an aluminum control panel which shall have a GREY powdercoat painted finish. The panel shall be hinged, or bolted in place allowing it to be easily removed to gain access to plumbing components.

### **PUMP PANEL LOCATION**

The pump control panel shall be located as per the itemized compartment list.

The pump panel shall include the following items;

### **PUMP PANEL ACCESS**

The pump panel shall be covered by the compartment roll-up door which shall protect the pump control panel from the environment.

### **ENGINE GAUGES**

The cab/chassis engine gauges shall be provided with the specified pump pressure governor system.



# Surprise Fire Dept

## Surprise, AZ

### **PRESSURE GOVERNOR**

The apparatus shall be equipped with the Class 1 Total Pressure Governor (TPG) connected to the Engine Control Module (ECM) mounted on the engine. The "TPG" will operate as a pressure sensor (regulating) governor (PSG) utilizing the engine's J1939 data for optimal resolution and response when supported by the engine manufacturer. If J-1939 engine control is not supported, then analog remote throttle control shall be provided by the "TPG" with the following features;

- Audible alarm output
- Easy set-up and configuration
- Large, easy to read alpha-numeric display
- Improved ergonomic tactile feedback buttons
- Totally integrated instruments including battery voltage, temperature, oil pressure, and RPM
- Controls engine speed directly over the J1939 CAN bus for improved resolution and response
- Integrated engine information reduces required pump panel space
- Programmable presets

### **MASTER DISCHARGE GAUGE**

There shall be one (1) Innovative Controls/NoShok 4" liquid filled gauge to display the Master Discharge Pressure. Gauge shall be labeled "MASTER DISCHARGE".

### **MASTER INTAKE GAUGE**

There shall be one (1) Innovative Controls/NoShok 4" liquid filled gauge to display the Master Intake Pressure. Gauge shall be labeled "MASTER INTAKE".

- This gauge(s) shall have a IC Nite-Glo style gauge.
- The above gauge(s) shall have a range from -30" to 600 PSI.

### **PUMP SAFETY AND TEST LABELS**

Safety, information, data, and instruction labels for apparatus shall be provided and installed at the operator's instrument panel.

The labels shall include rated capacities, pressure ratings, and engine speeds as determined by the certification tests. The no-load governed speed of the engine, as stated by the engine manufacturer, shall also be included.

The labels shall be provided with all information and be attached to the apparatus prior to delivery.

### **COLOR CODED LABELS**

The pump panel shall have Innovative Controls Inc. color coded die cast zinc, chrome plated bezels with plastic labels inserts for each intake, discharge, master gauges, and drain. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

ALL labels and tags shall match colors as close as possible to previous pumper #898 (where applicable).

# Surprise Fire Dept

## Surprise, AZ

### **PUMP PANEL LIGHTING**

All gauges and controls on the pump operator's panel shall be adequately illuminated by a full panel width shielded light assembly with full width OnScene Solutions LED light (each panel, if equipped). The light shall be activated by a weather-proof type switch on the pump operator's panel as well as automatically when pump is engaged. This switch shall also activate any area step lighting.

### **PUMP PANEL AIR HORN SWITCH**

A switch to activate the cab/chassis air horn(s) shall be provided on pump panel. Switch shall be constantly illuminated and labeled.

### **TEST TAPS**

Test taps for pump intake and pump pressure shall be provided on the pump instrument panel and be properly labeled.

### **POLY WATER TANK**

The water tank capacity shall be approximately 320 US gallon or 291 Imperial gallons. Certification of the tank capacity shall be recorded on the manufacturer's record of construction and shall be provided to the purchaser upon delivery of the apparatus.

### **CONSTRUCTION**

The tank must be designed and fabricated by a tank manufacturer that is ISO 9001:2008 certified. The ISO certification must be to the current standard in effect at the time of the design and fabrication of the tank.

The water tank shall be of a specific configuration and designed to be completely independent of the body and compartments. Joints and seams shall be fused using nitrogen gas as required and tested for maximum strength and integrity. The tank construction shall include PolyProSeal™ technology wherein a sealant shall be installed between the plastic components prior to being fusion welded. This sealing method will provide a liquid barrier offering leak protection in the event of a weld compromise. The top of the booster tank is fitted with removable lifting assembly designed to facilitate tank removal. The transverse and longitudinal swash partitions shall be manufactured of a minimum of 3/8" PT3™ polypropylene. All partitions shall be equipped with vent and air holes to permit movement of air and water between compartments. The partitions shall be designed to provide maximum water flow. All swash partitions interlock with one another and are completely fused to each other as well as to the walls of the tank. All partitions and spacing shall comply with NFPA 1901. The walls shall be welded to the floor of the tank providing maximum strength as part of the tank's unique Full Floor Design™. Tolerances in design allow for a maximum variation of 1/8" on all dimensions.

### **WATER FILL TOWER AND COVER**

The tank shall have a combination vent and manual fill tower. The fill tower shall be constructed of 1/2" PT3™ polypropylene and shall be a minimum dimension of 8" x 8" outer perimeter. The fill tower shall be blue in color indicating that it is a water-only fill tower. The tower shall be located in the left front corner of the tank unless otherwise specified by the tank manufacturer to the purchaser. The tower shall have a 1/4" thick removable polypropylene screen and a PT3™ polypropylene hinged cover. The capacity of the tank shall be engraved on the top of the fill tower lid. Inside the fill tower there shall be a combination vent/overflow pipe. The vent overflow shall be a minimum of schedule 40 polypropylene pipe with a minimum I.D. of 4" that is designed to run through the tank, and shall be piped to discharge water behind the rear wheels as required in NFPA 1901 so as to not interfere with rear tire traction.

# Surprise Fire Dept

## Surprise, AZ

The tank cover shall be constructed of 1/2" thick PT3™ polypropylene and UV stabilized, to incorporate a multi-piece locking design, which allows for individual removal and inspection if necessary. The tank cover(s) shall be flush or recessed 3/8" from the top of the tank and shall be fused to the tank walls and longitudinal partitions for maximum integrity. Each one of the covers shall have hold downs consisting of 2" minimum polypropylene dowels spaced a maximum of 40" apart. These dowels shall extend through the covers and will assist in keeping the covers rigid under fast filling conditions. A minimum of two lifting dowels shall accommodate the necessary lifting hardware.

### **SUMP**

There shall be one (1) sump standard per tank. The sump shall be constructed of a minimum of 1/2" PT3™ polypropylene and be located in the left front quarter of the tank, unless specified otherwise. On all tanks that require a front suction, a 3" schedule 40 polypropylene pipe shall be installed that will incorporate a dip tube from the front of the tank to the sump location. The sump shall have a minimum 3" N.P.T. threaded outlet on the bottom for a drain plug per NFPA. This shall be used as a combination clean-out and drain. All tanks shall have an anti-swirl plate located approximately 3" above the inside floor.

### **OUTLETS**

There will be two (2) standard tank outlets: one for the tank-to-pump suction line, which shall be sized to provide adequate water flow to the pump; and, one for tank fill line, which shall be sized according to the NFPA minimum size chart for booster tanks. All tank fill couplings shall be backed with flow deflectors to break up the stream of water entering the tank, and be capable of withstanding sustained fill rates of up to 1000 G.P.M. The addition of rear suction fittings, nurse valve fittings, dump valve fittings, and through-the-tank sleeves to accommodate rear discharge piping must be specified. All auxiliary outlets and inlets must meet all NFPA guidelines in effect at the time of manufacture.

### **MOUNTING**

The tank shall rest on the body cross members in conjunction with such additional cross members, spaced at a distance that would not allow for more than 530 square inches of unsupported area under the tank floor. In cases where overall height of the tank exceeds 40 inches, cross member spacing must be decreased to allow for not more than 400 square inches of unsupported area.

The tank must be isolated from the cross members through the use of hard rubber strips with a minimum thickness and width dimension of 1/4" x 1" and a Shore A Hardness of approximately 60 durometer. The rubber must be installed so it will not become dislodged during normal operation of the vehicle. Additionally, the tank must be supported around the entire bottom outside perimeter and captured both in the front and rear as well as side to side to prevent tank from shifting during vehicle operation.

A picture frame type cradle mount with a minimum of 2" x 2" x 1/4" mild steel, stainless steel, or aluminum angle shall be provided or the use of corner angles having a minimum dimension of 4" x 4" x 1/4" by 6" high are permitted for the purpose of capturing the tank.

Although the tank is designed on a free floating suspension principle, it is required that the tank have adequate vertical hold down restraints to minimize movement during vehicle operation. If proper retention has not been incorporated into the apparatus hose floor structure, an optional mounting restraint system shall be located on top of the tank, half way between the front and the rear on each side of the tank. These stops can be constructed of steel, stainless steel or aluminum angle having minimum dimensions of 3" x 3" x 1/4" and shall be approximately 6" to 12" long. These brackets must incorporate rubber isolating pads with a minimum thickness of 1/4" inch and a hardness of 60 durometer affixed on the underside of the angle. The angle should then be bolted to the body side

# Surprise Fire Dept

## Surprise, AZ

walls of the vehicle while extending down to rest on the top outside edge of the upper side wall of the tank. Hose beds floors must be so designed that the floor slat supports extend full width from side wall to side wall and are not permitted to drop off the edge of the tank or in any way come in contact with the individual covers where a puncture could occur. Tank top must be capable of supporting loads up to 200 lbs per sq. foot when evenly distributed. Other equipment such as generators, portable pumps, etc. must not be mounted directly to the tank top unless provisions have been designed into the Poly-Tank® III for that purpose. The tank shall be completely removable without disturbing or dismantling the apparatus structure.

### **CENTER OF GRAVITY**

A center of gravity calculation shall be determined for each tank and provided as requested in order to provide the apparatus manufacturer with the necessary data to design and certify the apparatus with respect to the NFPA requirements regarding rollover stability.

### **WATER TANK LEVEL GAUGE**

There shall be one (1) Class 1 model ITL-40B tank level gauge(s) for indicating water level. The tank level gauge shall indicate the liquid level or volume on an easy to read blue LED display and show increments of 1/8 of a tank.

Each tank level gauge system shall include;

- A pressure transducer that is mounted on the outside of the tank in an easily accessible area. Sealed foam tanks will require zero pressure vacuum vents.
- A super bright LED display viewable from 180 degrees with a visual indication at nine accurate levels.
- A set of weather resistant connectors to connect to the digital display, to the pressure transducer and to the apparatus power.
- The system shall include the ability to display “text messages”
- The system shall include built-in diagnostic capabilities.

**NOTE:** The tank level gauge shall be located directly above the tank fill valve. Be sure gauge is wired to the DIM setting.

### **UPF POLY WATER TANK WARRANTY**

The UPF poly water tank shall be provided with a lifetime material and workmanship limited warranty. The manufacturer shall supply details of their warranty information with their bid submission.

### **HOSE BED STORAGE AREA**

Hose bed storage area shall be located over water tank and body, and shall exit at the rear of the apparatus. The interior of storage area shall be free from all projections such as nuts, sharp angles, or brackets that may damage equipment.

### **ALUMINUM HOSE BED DECKING**

The hose bed deck shall be constructed from 3" x 3/4" hollow aluminum extrusions welded into a one-piece grid to allow ventilation and water drainage. The extrusions shall have a radiused ribbed top surface. The deck will be completely removable for easy access to the booster tank. The booster tank fill tower shall be protected as necessary to prevent damage from equipment located in the storage area.

# Surprise Fire Dept

## Surprise, AZ

**The left hand side of the hosebed area shall be an aluminum treadplate floor. There shall be no hose stored in this area.**

### **FILL TOWER PROTECTION**

The fill tower(s) shall be boxed in with an aluminum panel for protection from damage. **There shall be an aluminum non-latching cover over the top of the dome. It shall have an expanded metal insert installed in it.**

The hosebed shall hold the following amount of hose:

500' of 4" DJ hose

There shall be an aluminum treadplate step at the rear of the hosebed area. It shall be the full width of the hosebed walkway. Step shall be supplied with a notch for hose, similar to the rear step on a previous job #898.

### **HOSE BED DIVIDER(S)**

One (1) adjustable aluminum hose bed partition(s) shall be provided in the hose storage area. The partition(s) shall be 3/16" smooth aluminum with split aluminum tubing welded to the top and rear edges.

### **ALUMINUM HOSE BED COVER**

**A hose bed cover shall be provided on the curbside portion of upper walkway area only. NO cover over the streetside area.** Door shall be fabricated from 1/8" NFPA aluminum treadplate with formed hat sections for bracing. Door shall be hinged along side of the hose body using stainless steel piano hinge. The top surface of section shall slant down with the highest point in the center of the hose bed area and shall be supported from underneath by at least one (1) adjustable hose bed divider.

The section shall be constructed to support the weight of a person (300 lbs).

The section shall utilize pneumatic cylinders to assist with opening and closing. There shall be one (1) 24" vertical handrail on the door to assist in raising and lowering hose bed door. Handrail shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

The door shall have a horizontally mounted On Scene LED light on the underside of it that will be automatically activated when the door is opened and wired to the compartment door ajar warning light provided in cab.

The opening at the end of the hosebed will be covered with a black nylon style webbing. All pull tabs on webbing shall have white reflective material sewn into them. It will be secured in place with bungee style cord on shoulder bolts. Match style used on a previous job #898.

There shall be (1) vertical 24" long handrail installed onto the rear of the body on the curbside.

There shall be (1) chrome 7" grab handle installed onto the top cover on the drivers side rear of the body for access to the hosebed area.

# Surprise Fire Dept

## Surprise, AZ

### **EQUIPMENT PAYLOAD WEIGHT ALLOWANCE**

In compliance with NFPA 1901 standards, the special service vehicle shall be designed for an equipment loading allowance of 4,000 lbs. of Surprise Fire Department provided equipment based on a 30,001 - 40,000 pound gross vehicle weight rating.

### **EQUIPMENT**

The following equipment shall be furnished with the completed special service vehicle;

### **EQUIPMENT MOUNTING**

There is a \$10,000.00 allowance in funds for the mounting of equipment.

The Surprise Fire Department supplied equipment shall be mounted at direction of Surprise Fire Department including all necessary PAC or equivalent mounting brackets.

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.

Install (1) Igloo water cooler into the slideout tray in compartment S2.


#### **SHOP NOTES**

To match the same as the engine

- There shall be two (2) Zico SAC-44-E NFPA approved folding aluminum wheel chocks provided for 44" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20 % grade, with the transmission in neutral, and the parking brake released.
  - The wheel chock(s) shall be mounted behind rear wheels, below body on streetside.
- One (1) Duo-Safety 900-A series 24' 2-section extension ladder(s) shall be provided with the completed unit.
  - The ladder(s) shall be located in specified ladder compartment.
- One (1) Duo-Safety 1225-A series 35' 3-section extension ladder(s) shall be provided with the completed unit.
  - The ladder(s) shall be located in specified ladder compartment.
- One (1) Duo-Safety 775A series 14' aluminum roof ladder(s) shall be provided with the completed unit.
  - The ladder(s) shall be located in specified ladder compartment.
- One (1) Duo-Safety 585-A 10' aluminum folding ladder(s) shall be provided with the completed unit.
  - The ladder(s) shall be located in specified ladder compartment.
- One (1) Duo-Safety 10' fiberglass pike pole(s) shall be provided with the completed unit.

# Surprise Fire Dept

## Surprise, AZ

- One (1) Duo-Safety 8' fiberglass pike pole(s) shall be provided with the completed unit.
  - The above specified pike pole will not have a D handle attached
- The pike pole(s) shall be mounted on vehicle, per itemized compartment list.
- The above specified pike pole will not have a D handle attached
- The pike pole(s) shall be mounted on vehicle, per itemized compartment list.
- One (1) Duo-Safety 12' fiberglass pike pole(s) shall be provided with the completed unit.
  - The above specified pike pole will not have a D handle attached
  - The pike pole(s) shall be mounted on vehicle, per itemized compartment list.
- Four (4) **Leatherhead 6' fiberglass arson trash hook(s)** shall be provided with the completed unit.
  - The above specified pike pole will have a D handle attached
  - The pike pole(s) shall be mounted on vehicle, per itemized compartment list.
- One (1) **Customer supplied/SVI installed 718VR3, 18" electric variable speed ventilation fan(s)** shall be with the completed unit 
  - The above specified ventilation fan(s) shall be installed on completed unit using mounting brackets and/or straps, located in compartment C1.
- Two (2) Streamlight FireBox halogen flashlight(s) with shoulder strap shall be provided. Each flashlight shall be orange in color and have a 12 volt DC charger and vehicle mount kit. Each flashlight shall have a 8 watt, 150 lumen halogen spotlight style bulb and reflector with 2 ultra-bright LED taillights. The flashlight(s) shall be wired to battery direct unless otherwise specified by Surprise Fire Department.
  - One flashlight(s) shall be mounted on the completed unit in the upper area on the rear wall of compartment S2.
  - One flashlight shall be mounted up high on wall of compartment C2.

### **REMAINING NFPA MINOR EQUIPMENT BY PURCHASER**

All other minor equipment not specified above, but required by NFPA 1901 for special service vehicles, section 10.5.1 shall be supplied and mounted by Surprise Fire Department before the unit is placed in emergency service.