

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

[Table of Contents](#)

<b>LIABILITY INSURANCE</b> .....	5
<b>INTERNET IN-PROCESS SITE</b> .....	5
The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C). ....	
<b>HIGHWAY PERFORMANCE</b> .....	6
<b>SERVICEABILITY</b> .....	6
<b>FIRE APPARATUS DOCUMENTATION</b> .....	6
<b>OPERATIONS AND SERVICE DOCUMENTATION</b> .....	8
<b>NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE</b> .....	9
<b>STATEMENT OF EXCEPTIONS</b> .....	9
<b>STATEMENT OF EXCEPTIONS</b> .....	9
<b>CARRYING CAPACITY</b> .....	10
<b>TESTING</b> .....	12
<b>ROAD TEST</b> .....	12
<b>LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST</b> .....	12
<b>TEST SEQUENCE</b> .....	12
<b>1. RESERVE CAPACITY TEST</b> .....	13
<b>2. ALTERNATOR PERFORMANCE TEST</b> .....	13
<b>TEST AT IDLE</b> .....	13
<b>TEST AT FULL LOAD</b> .....	13
<b>3. LOW VOLTAGE ALARM TEST</b> .....	13
<b>LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST</b> .....	13
<b>DOCUMENTATION</b> .....	13
<b>WARRANTY</b> .....	14
<b>GENERAL LIMITED WARRANTY - TWO (2) YEARS</b> .....	14
<b>LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS</b> .....	14
<b>STRUCTURAL WARRANTY - TEN (10) YEARS</b> .....	14
<b>UNDERCOAT WARRANTY</b> .....	14
<b>PAINT LIMITED WARRANTY - TEN (10) YEARS</b> .....	15

**EAST POINT FIRE DEPT**  
**Utility Unit**  
Production Specifications  
SVI #1015

<b>GRAPHICS LIMITED WARRANTY .....</b>	<b>15</b>
<b>CONSTRUCTION PERIOD .....</b>	<b>15</b>
<b>OVERALL HEIGHT REQUIREMENT .....</b>	<b>15</b>
<b>OVERALL LENGTH REQUIREMENT .....</b>	<b>15</b>
<b>OVERALL WIDTH .....</b>	<b>15</b>
<b>DELIVERY AND DEMONSTRATION .....</b>	<b>15</b>
<b>CHASSIS MODIFICATIONS .....</b>	<b>24</b>
<b>LUBRICATION AND TIRE DATA PLATE .....</b>	<b>24</b>
<b>VEHICLE DATA PLATE .....</b>	<b>24</b>
<b>OVERALL HEIGHT, LENGTH DATA PLATE (US) .....</b>	<b>25</b>
<b>FRONT BUMPER .....</b>	<b>26</b>
<b>FRONT TOW PROVISIONS .....</b>	<b>26</b>
<b>EXHAUST .....</b>	<b>27</b>
<b>SEAT BELT COLOR AND MOUNTING .....</b>	<b>27</b>
<b>SEAT BELT WEB LENGTH - COMMERCIAL CAB .....</b>	<b>27</b>
<b>SEAT BELT MONITORING SYSTEM - COMMERCIAL CAB .....</b>	<b>28</b>
<b>IGNITION KEY .....</b>	<b>28</b>
<b>SIX (6) – LED TIRE PRESSURE VISUAL INDICATORS .....</b>	<b>28</b>
<b>HELMET STORAGE .....</b>	<b>28</b>
<b>CAB MIRRORS, DRIVER ADJUSTABLE .....</b>	<b>28</b>
<b>MUDFLAPS .....</b>	<b>28</b>
<b>ROAD EMERGENCY SAFETY KIT .....</b>	<b>28</b>
<b>FUEL FILL .....</b>	<b>29</b>
<b>DEF FLUID FILL .....</b>	<b>29</b>
<b>BODY DESIGN .....</b>	<b>29</b>
<b>EXTERIOR ALUMINUM BODY .....</b>	<b>29</b>
<b>ALUMINUM TREADPLATE ROOF .....</b>	<b>30</b>
<b>BODY SUBFRAME .....</b>	<b>30</b>
<b>BODY MOUNTING .....</b>	<b>31</b>
<b>10" REAR STEP BUMPER .....</b>	<b>31</b>

**EAST POINT FIRE DEPT**  
**Utility Unit**  
Production Specifications  
SVI #1015

<b>GROUND LIGHTS .....</b>	<b>31</b>
<b>WHEEL WELL EXTERIOR PANEL.....</b>	<b>31</b>
<b>DIEFORMED BEADED EDGE BODY FENDERS .....</b>	<b>32</b>
<b>WHEEL WELL LINERS.....</b>	<b>32</b>
<b>BODY PAINT SPECIFICATIONS .....</b>	<b>32</b>
<b>BODY PAINT PREPARATION.....</b>	<b>32</b>
<b>PAINT PROCESS.....</b>	<b>32</b>
<b>BODY UNDERCOATING .....</b>	<b>33</b>
<b>UNDERCOAT WARRANTY.....</b>	<b>34</b>
<b>PAINT WARRANTY .....</b>	<b>34</b>
<b>COMPARTMENT INTERIOR FINISH.....</b>	<b>34</b>
<b>REFLECTIVE STRIPE REQUIREMENTS.....</b>	<b>34</b>
<b>REFLECTIVE STRIPE - CAB SIDE.....</b>	<b>35</b>
<b>REFLECTIVE STRIPE - CAB FRONT .....</b>	<b>35</b>
<b>REFLECTIVE STRIPE - CAB DOOR INTERIOR.....</b>	<b>35</b>
<b>REFLECTIVE STRIPE - BODY SIDES .....</b>	<b>35</b>
<b>CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS.....</b>	<b>35</b>
<b>LETTERING.....</b>	<b>36</b>
<b>SIDE CAB DOOR LETTERING.....</b>	<b>36</b>
<b>UPPER BODY SIDE LETTERING.....</b>	<b>36</b>
<b>REAR BODY LETTERING.....</b>	<b>36</b>
<b>FRONT OF CAB LETTERING.....</b>	<b>36</b>
<b>ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM) .....</b>	<b>36</b>
<b>BODY HEIGHT MEASUREMENTS.....</b>	<b>37</b>
<b>BODY WIDTH DIMENSIONS .....</b>	<b>38</b>
<b>STREETSIDE COMPARTMENT - FRONT (S1).....</b>	<b>38</b>
<b>COMPARTMENT LAYOUT .....</b>	<b>38</b>
<b>STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2).....</b>	<b>39</b>
<b>COMPARTMENT LAYOUT .....</b>	<b>39</b>
<b>STREETSIDE COMPARTMENT - REAR (S3) .....</b>	<b>39</b>

**EAST POINT FIRE DEPT**  
**Utility Unit**  
Production Specifications  
SVI #1015

COMPARTMENT LAYOUT .....	39
CURBSIDE COMPARTMENT - FRONT (C1).....	40
COMPARTMENT LAYOUT .....	40
CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C2).....	40
COMPARTMENT LAYOUT .....	41
CURBSIDE COMPARTMENT - REAR (C3) .....	41
COMPARTMENT LAYOUT .....	41
COMPARTMENT LAYOUT .....	42
REAR BODY HANDRAILS.....	42
LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC.....	42
12 VOLT DIAGNOSTIC RELAY CONTROL CENTER .....	45
ROCKER SWITCH PANEL.....	45
BATTERY SYSTEM.....	46
BATTERY SWITCH.....	47
BATTERY SOLENOID.....	47
BATTERY CONDITIONER.....	47
SHORE POWER INLET .....	48
ENGINE COMPARTMENT LIGHT.....	48
BACK-UP ALARM.....	48
TAIL LIGHTS.....	49
MARKER LIGHTS .....	49
CAB STEP LIGHTS / GROUND LIGHTS.....	49
LICENSE PLATE LIGHT .....	49
ELECTRONIC SIREN .....	49
SIREN SPEAKERS .....	49
SIDE SCENE LIGHTS.....	49
REAR SCENE LIGHTS.....	50
WARNING LIGHT PACKAGE.....	50
UPPER LEVEL OPTICAL WARNING DEVICES.....	51
LOWER LEVEL OPTICAL WARNING DEVICES.....	52

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

<b>EQUIPMENT PAYLOAD WEIGHT ALLOWANCE .....</b>	<b>53</b>
<b>EQUIPMENT .....</b>	<b>53</b>
<b>REMAINING NFPA MINOR EQUIPMENT BY PURCHASER .....</b>	<b>53</b>

**LIABILITY INSURANCE**

The manufacturer shall furnish with the bid a certificate of insurance for;

Workman's Compensation and Employer's Liability Insurance covering for all employees.

General Liability (each occurrence) of \$1,000,000.00. General Aggregate coverage of \$2,000,000.00. Products Completed / Operations Aggregate coverage of \$2,000,000.00. Medical Expense coverage of \$5,000 (any one person). Personal Injury of \$1,000,000.00.

Automobile liability of \$1,000,000.00 combined single limit (each accident), including any auto, all owned autos, scheduled autos, hired autos, non-owned autos, and garage liability.

Excess Umbrella Liability coverage of \$4,000,000.00 each occurrence, Aggregate of \$4,000,000.00. Garage Keepers Liability coverage of \$4,000,000.00 combined limit.

All insurance policies must be;

- Maintained for the life of the contract,
- Must provide ten (10) days notice before cancellation,
- Must cover all operations of the contractor, or anyone employed by them.

**INTERNET IN-PROCESS SITE**

The manufacturer shall post and maintain a website where the East Point Fire Department will be able to view digital images of their apparatus as its being built. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of unit.

**VEHICLE STABILITY SUPPLIED WITH CAB/CHASSIS**

The cab/chassis shall be equipped with a stability control system. The system shall have, at a minimum, a steering wheel position sensor, a vehicle yaw sensor, a lateral accelerometer and individual wheel brake controls.

**FIRE APPARATUS PERFORMANCE**

The fire apparatus shall meet the requirements of this standard at elevations of 2000 ft (600 m) above sea level.

# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

The fire apparatus shall meet all the requirements of this standard while stationary on a grade of 6 percent in any direction.

The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C).

#### **HIGHWAY PERFORMANCE**

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- 1) Accelerating from 0 to 35 mph (55 km/hr) within 25 seconds on a 0 percent grade
- 2) Attaining a speed of 50 mph (80 km/hr) on a 0 percent grade
- 3) Maintaining a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent

The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (109 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal (4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (95 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

#### **SERVICEABILITY**

The fire apparatus shall be designed to allow the manufacturer's recommended routine maintenance checks of lubricant and fluid levels to be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

#### **FIRE APPARATUS DOCUMENTATION**

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

- 1) The manufacturers record of apparatus construction details, including the following documents:
  - b) Owner's name and address
  - c) Apparatus manufacturer, model, and serial number
  - d) Chassis make, model, and serial number
  - e) GAWR of front and rear axles and GVWR
  - f) Front tire size and total rated capacity in pounds (kilograms)
  - g) Rear tire size and total rated capacity in pounds (kilograms)
  - h) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

- i) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
  - j) Type of fuel and fuel tank capacity
  - k) Electrical system voltage and alternator output in amps
  - l) Battery make, model, and capacity in cold cranking amps (CCA)
  - m) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
  - n) Ratios of all driving axles
  - o) Maximum governed road speed
  - p) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), maximum discharge pressure capability rating, and serial number
  - q) Pump transmission make, model, serial number, and gear ratio
  - r) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
  - s) Water tank certified capacity in gallons or liters
  - t) Foam tank (if provided) certified capacity in gallons (liters)
  - u) Aerial device type, rated vertical height in feet (meters), rated horizontal reach in feet (meters), and rated capacity in pounds (kilograms)
  - v) Paint manufacturer and paint number(s)
  - w) Company name and signature of responsible company representative
  - x) Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall fire apparatus (with the water tank full but without personnel, equipment, and hose)
- 2) Certification of compliance of the optical warning system (*see 13.8.16*)
  - 3) Siren manufacturer's certification of the siren (*see 13.9.1.1*)
  - 4) Written load analysis and results of the electrical system performance tests (*see 13.14.1 and Section 13.15*)
  - 5) Certification of slip resistance of all stepping, standing, and walking surfaces (*see 15.7.4.5*)
  - 6) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability (*see 16.2.4.1*)
  - 7) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions (*see 16.2.4.2*)
  - 8) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications (*see 16.3.1*)
  - 9) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed (*see 16.3.2.2*)
  - 10) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test (*see 16.5.2.2*)
  - 11) If the apparatus has a fire pump with a maximum discharge pressure capability rating that exceeds the hydrostatic test pressure of 16.5.2.1, the pump manufacturer's certification of the hydrodynamic test
  - 12) If the apparatus has a fire pump, the certification of inspection and test for the fire pump (*see 16.13.1.1.5 or 16.13.1.2.4 as applicable*)
  - 13) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test (*see Section 17.13*)
  - 14) When the apparatus is equipped with a water tank, the certification of water tank capacity (*see Section 18.6*)
  - 15) If the apparatus has an aerial device, the certification of inspection and test for the aerial device (*see Section 19.24*)
  - 16) If the apparatus has an aerial device, all the technical information required for inspections to comply with NFPA 1911

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

- 17) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy (*see 20.10.4.2*) and the final installer's certification the foam proportioning system meets this standard (*see 20.11.2*)
- 18) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests (*see Section 21.9*)
- 19) If the apparatus has a line voltage power source, the certification of the test for the power source (*see 22.15.7.2*)
- 20) If the apparatus is equipped with an air system, air tank certificates (*see 24.5.1.2*), the SCBA fill station certification (*see 24.9.6*), and the results of the testing of the air system installation (*see 24.14.5 and 24.15.4*)
- 21) Any other required manufacturer test data or reports

**OPERATIONS AND SERVICE DOCUMENTATION**

The contractor shall deliver with the fire apparatus complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof.

The contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- 1) Manufacturer's name and address
- 2) Country of manufacture
- 3) Source for service and technical information
- 4) Parts replacement information
- 5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- 6) Wiring diagrams for low voltage and line voltage systems to include the following information:
  - a) Pictorial representations of circuit logic for all electrical components and wiring
  - b) Circuit identification
  - c) Connector pin identification
  - d) Zone location of electrical components
  - e) Safety interlocks
  - f) Alternator–battery power distribution circuits
  - g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- 7) Lubrication charts
- 8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- 9) Precautions related to multiple configurations of aerial devices, if applicable
- 10) Instructions regarding the frequency and procedure for recommended maintenance
- 11) Overall apparatus operating instructions
- 12) Safety considerations
- 13) Limitations of use
- 14) Inspection procedures
- 15) Recommended service procedures
- 16) Troubleshooting guide
- 17) Apparatus body, chassis and other component manufacturer's warranties
- 18) Special data required by this standard
- 19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus



# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

20) One copy of the latest edition of FAMA's *Fire Apparatus Safety Guide*

The contractor shall deliver with the apparatus all manufacturer's operations and service documents supplied with components and equipment that are installed or supplied by the contractor.

#### **NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE**

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a USB Flash Drive. These manuals shall be divided into sections for ease of reference. There shall be two (2) USB flash drives provided with the completed vehicle.

#### **FIRE APPARATUS SAFETY GUIDE**

A Fire Apparatus Safety Guide published by Fire Apparatus manufacturer's Association shall be provided with delivered vehicle. This manual includes essential safety information for fire fighters, fire chiefs, apparatus mechanics, and fire department safety officers. The guide is applicable to municipal, wildland, and airport fire fighting apparatus manufactured on either custom or commercial chassis.

#### **STATEMENT OF EXCEPTIONS**

The final-stage manufacturer shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- 1) A separate specification of the section of the applicable standard for which compliance is lacking
- 2) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
- 3) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance
- 4) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to or at the time of delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

#### **STATEMENT OF EXCEPTIONS**

The East Point Fire Department specified emergency vehicle is NOT fully compliant with the latest NFPA 1901 edition. Listed below are the noncompliant or missing required items that need to be changed to be become fully compliant with latest NFPA 1901 edition;

#### **Change**

<b><u>Item</u></b>	<b><u>Page</u></b>	<b><u>Current Description</u></b>
--------------------	--------------------	-----------------------------------

	<b><u>Responsibility</u></b>	
--	------------------------------	--

<b><u>Changed Description</u></b>
-----------------------------------

**EAST POINT FIRE DEPT**  
**Utility Unit**  
Production Specifications  
SVI #1015

1 Section 14.1.3.9 of the NFPA 1901 Standards, requires that a seat belt warning system be provided. The seat belt warning device is intended to assist the driver or officer in determining whether all occupants are seated and belted before the vehicle is driven.

Per East Point Fire Department specification for a commercial chassis, this emergency vehicle may not have a seat belt monitoring system. Without this device, the driver must manually determine that all occupants are seated and belted before the apparatus is placed in motion. This specification for an emergency fire apparatus for the seat belt monitoring system shall be non-compliant to NFPA 1901 standards, effective at the time of order.

2  
3  
4  
5

Prior to, or at the time of, delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

SVI Trucks  
3842 Redman Drive  
Fort Collins, CO 80524

\_\_\_\_\_  
Regional Sales Manager

Date: \_\_\_\_\_

An apparatus that is delivered subject to a Statement of Exceptions other than a certification of full compliance shall not be placed in emergency service until the apparatus has been modified as necessary to accomplish full compliance with this standard.

On Behalf of East Point Fire Department

## CARRYING CAPACITY

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The manufacturer shall establish the estimated in service weight during the design of the vehicle.

The estimated in-service weight shall include the following:

# EAST POINT FIRE DEPT

## Utility Unit

### Production Specifications

SVI #1015

1. The chassis, body and tank(s)
2. Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
3. Full water and other agent tanks
4. \*250 lb (114 kg) in each seating position
5. Fixed equipment such as pumps, aerial devices, generators, reels and air systems as installed
6. Ground ladders, suction hose, designed hose load in their hose beds and on their reels
7. An allowance for miscellaneous equipment that is the greatest of the following:
  - h) The values shown for items 1 - 7
  - i) A purchaser-provided list of equipment to be carried with weights
  - j) A purchaser-specified miscellaneous equipment allowance

The manufacturer shall engineer and design the fire apparatus such that the completed apparatus, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

A final manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed unequipped fire apparatus in feet and inches (meters), the length of the completed fire apparatus in feet and inches (meters), and the GVWR in tons (metric tons).

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

Apparatus Type	Equip. Storage Area	Apparatus Size	Equipment Allowance	
			lb.	kg.
Special Service Fire Apparatus	Minimum of 120 cu ft (3.4 cu mt) of enclosed compartmentation.	10,000 lb to 15,000 lb (4,500 kg to 7,000 kg) GVWR	2,000	910
		15,001 lb to 20,000 lb (7,001 kg to 9,000 kg) GVWR	2,500	1,135
		20,001 lb to 30,000 lb (9,001 kg to 14,000 kg) GVWR	3,000	1,350
		30,001 lb to 40,000 lb (14,001 kg to 18,000 kg) GVWR	4,000	1,800
		40,001 lb to 50,000 lb (18,001 kg to 23,000 kg) GVWR	6,000	2,700
		50,001 lb to 60,000 lb (23,001 kg to 27,000 kg)	8,000	3,600

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

		GVWR		
		60,001 lb and up (27,001 kg) GVWR	10,000	4,500

**TESTING**

**ROAD TEST**

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the Body Manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

**LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (−18°C and 43°C).

**TEST SEQUENCE**

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for ten (10) minutes. Failure of any of these tests shall require a repeat of the sequence.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**1. RESERVE CAPACITY TEST**

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

**2. ALTERNATOR PERFORMANCE TEST**

**TEST AT IDLE**

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

**TEST AT FULL LOAD**

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

**3. LOW VOLTAGE ALARM TEST**

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

**LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

**DOCUMENTATION**

The manufacturer shall deliver the following with the fire apparatus:

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

- 1) Documentation of the electrical system performance tests
- 2) A written electrical load analysis, including the following:
  - a) The nameplate rating of the alternator
  - b) The alternator rating
  - c) Each of the component loads specified that make up the minimum continuous electrical load
  - d) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
  - e) Each individual intermittent electrical load

**WARRANTY**

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source and will deal directly with the East Point Fire Department on all warranty work.

**GENERAL LIMITED WARRANTY - TWO (2) YEARS**

The vehicle shall be free of defects in material and workmanship for a period of two (2) years or 36,000 miles (or 57,936 kilometers), whichever occurs first starting thirty (30) days after the original invoice date.

The Contractor must be the "single source" coordinator of all warranties on the vehicle.

**LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS**

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles (or 96,561 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

**STRUCTURAL WARRANTY - TEN (10) YEARS**

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

**UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**PAINT LIMITED WARRANTY - TEN (10) YEARS**

The body shall be free of bubbling or peeling as a result of a defect in the method of manufacture for a period of ten (10) years or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date. **Pro-rated warranties will not be acceptable.**

**GRAPHICS LIMITED WARRANTY**

The 3M graphics installation shall be warranted for a period of two (2) years. The 3M materials installed on completed vehicle shall be warranted for seven (7) years. The 3M Diamond grade film (if specified) shall be warranted for ten (10) years.

**CONSTRUCTION PERIOD**

The completed vehicle shall be delivered within one hundred eighty (180) days after receipt of a purchase order or contract. **NO LATER THAN MAY 30, 2017**

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to East Point Fire Department as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

**OVERALL HEIGHT REQUIREMENT**

There is no overall height (OAH) restriction for this vehicle.

**OVERALL LENGTH REQUIREMENT**

There is no overall length (OAL) restriction for this vehicle.

**OVERALL WIDTH**

The overall width (OAW) of the body at drip rails shall be 98" (8' - 2"), and body shall be 96" (8' - 0").

**ANGLE OF APPROACH**

The angle of approach for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

**ANGLE OF DEPARTURE**

The angle of departure for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

**DELIVERY AND DEMONSTRATION**

The Contractor shall be responsible for the delivery of the completed unit to the East Point Fire Department's location. On initial delivery of the apparatus, the Contractor shall supply a qualified representative to demonstrate the apparatus and provide initial instruction to representatives of the East Point Fire Department regarding the operation, care and maintenance of the apparatus and equipment

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

supplied at East Point Fire Department location.

The Delivery Engineer shall set delivery and instruction schedule with the person appointed by East Point Fire Department.

After delivery of the apparatus, the East Point Fire Department shall be responsible for ongoing training of its personnel to proficiency regarding the proper and safe use of the apparatus and associated equipment.

**Cab and Chassis Specifications**

**2017 F-550 Chassis, SD Super Cab**

4x2 SD Super Cab

*Includes:*

- Tires: 225/70Rx19.5G BSW AS
- Wheels: 19.5" Argent Painted Steel
- HD Vinyl 40/20/40 Split Bench Seat

*Includes center armrest, cupholder, storage and driver's side manual lumbar.*

- Radio: AM/FM Stereo

*Includes 6 speakers.*

**Powertrain**

99T Engine: 6.7L 4V OHV Power Stroke

V8 Turbo Diesel B20

*Includes split-shaft calibration compatibility.*

*Includes:*

- Dual 78-AH 750 CCA Batteries

44W Transmission: TorqShift 6-Speed

Automatic

N/C

*(6R140). Includes SelectShift, tow/haul mode and B20 capability.*

X8L Limited Slip w/4.88 Axle Ratio

68M GVWR: 19,500 lb Payload Plus

Upgrade Package

*Includes upgraded frame, rear-axle and low deflection/high capacity springs. Increases max RGAWR to 14, 706. NOTE: See Order Guide Supplemental Reference for further details on GVWR.*

**Wheels & Tires**

TFB Tires: 225/70Rx19.5G BSW AS Included

64Z Wheels: 19.5" Argent Painted Steel Included

**Seats & Seat Trim**

A HD Vinyl 40/20/40 Split Bench Seat Included

*Includes center armrest, cupholder, storage and driver's side manual lumbar.*

**Other Options**

PAINT Monotone Paint Application STD

~~192WB 192"~~ Wheelbase STD (WB is not correct).

90L Power Equipment Group

Selected Options

*Deletes passenger side lock cylinder. Includes upgraded door-trim panel.*



**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

*Includes:*

- Accessory Delay

- Trailer Tow Mirrors w/Power Heated Glass

*Includes manual telescoping, heated convex spotter mirror and integrated clearance lamps/turn signals.*

- MyKey

*Includes owner controls feature.*

- Perimeter Anti-Theft Alarm

- Power Front & Rear Side Windows

*Includes 1-touch up/down driver/passenger window.*

- Power Locks

- Remote Keyless Entry

- SecuriLock Passive Anti-Theft System (PATS)

98R Operator Commanded Regeneration  
(OCR)

Included

*Includes active regeneration inhibit.*

67B Dual Extra Heavy-Duty Alternators  
(Total 377-Amps)

Included

STDRD Radio: AM/FM Stereo Included

*Includes 6 speakers.*

**Fleet Options**

47J Fire/Rescue Prep Pkg w/EPA Special  
Emissions (LPO)

REQUIRES valid FIN code.

*Includes 7,000 lbs. max front springs/GAWR rating for configuration selected. Incomplete vehicle package - requires further manufacture and certification by a final stage manufacturer. Ford urges Fire/Rescue Vehicle manufacturers to follow the recommendations of the Ford Incomplete Vehicle Manual and the Ford Truck Body Builders Layout Book (and pertinent supplements). NOTE 1: Stationary Elevated Idle Control (SEIC) has been integrated into the engine control module. NOTE 2: Engine calibration significantly reduces the possibility of depower mode when in stationary PTO operation. NOTE 3: Operator commanded regen allowed down to 30% of DPF filter full, instead of 100%. NOTE 4: Must meet the definition of an Emergency Vehicle, an Ambulance or Fire Truck per 40 CFR 86.1803.01 in the Federal Register. NOTE 5: California Code of Regulations allows for the sale of Federally certified emergency vehicles in California.*

*Includes:*

- Dual Extra Heavy-Duty Alternators (Total 377-Amps)

- Operator Commanded Regeneration (OCR)

*Includes active regeneration inhibit.*

**Emissions**

425 50-State Emissions System STD

**Interior Colors**

AS\_04 Medium Earth Gray N/C

**Primary Colors**

PQ\_01 Race Red N/C

**Upfit Options**

4 al wheels Add [4] Factory Aluminum Wheels

**Dimensions**

# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

- \* Front legroom: 43.9"
- \* Rear legroom: 33.5" \* Front headroom: 40.8"
- \* Rear headroom: 40.3" \* Front hiproom: 62.5"
- \* Rear hiproom: 64.7" \* Front shoulder room: 66.7"
- \* Rear shoulder room: 65.8" \* Passenger volume: 116.0cu.ft.
- \* Cargo volume: 31.6cu.ft. \* Maximum cargo volume: 31.6cu.ft.

#### **Powertrain**

- \* Powerstroke 330hp 6.7L OHV 32 valve intercooled turbo V-8 engine with diesel direct injection
- \* Recommended fuel : diesel
- \* federal \* TorqShift 6 speed automatic transmission with overdrive
- \* Rear-wheel drive \* Limited slip differential
- \* Fuel Economy Cty: N/A \* Fuel Economy Highway: N/A

#### **Suspension/Handling**

- \* Front Mono-beam non-independent suspension with anti-roll bar, HD shocks
- \* Rear DANA 130 rigid axle leaf spring suspension with anti-roll bar, HD shocks
- \* Firm ride Suspension \* Hydraulic power-assist re-circulating ball Steering
- \* Front and rear 19.5 x 6 argnt steel wheels \* LT225/70SR19.5 GBSW AS front and rear tires
- \* Dual rear wheels

#### **Body Exterior**

- \* 4 doors \* Reverse opening left rear passenger
- \* Reverse opening right rear passenger \* Driver and passenger power remote heated folding door mirrors with turn signal indicator
- \* Turn signal indicator in mirrors \* Black door mirrors
- \* Black bumpers \* Trailer harness
- \* Clearcoat paint \* Front and rear 19.5 x 6 wheels

#### **Convenience**

- \* Manual air conditioning with air filter \* Power windows
- \* Driver and passenger 1-touch up \* Driver and passenger 1-touch down
- \* Remote power door locks with 2 stage unlock and illuminated entry
- \* Manual tilt steering wheel
- \* Manual telescopic steering wheel \* Day-night rearview mirror
- \* 1 1st row LCD monitor \* Front cupholders
- \* Passenger visor mirror \* Full overhead console
- \* Driver and passenger door bins \* Rear door bins

#### **Seats and Trim**

- \* Seating capacity of 6 \* Front 40-20-40 split-bench seat
- \* 4-way driver seat adjustment \* Manual driver lumbar support
- \* 4-way passenger seat adjustment \* Centre front armrest with storage
- \* 60-40 folding rear split-bench seat

#### **Entertainment Features**

- \* AM/FM stereo radio \* 6 speakers
- \* Fixed antenna

#### **Lighting, Visibility and Instrumentation**

- \* Halogen aero-composite headlights \* Delay-off headlights
- \* Fully automatic headlights \* Variable intermittent front windshield wipers

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

- \* Light tinted windows \* Front reading lights
- \* Tachometer \* Outside temperature display
- \* Trip computer \* Trip odometer

**Safety and Security**

- \* 4-wheel ABS brakes \* 4-wheel disc brakes
- \* Driveline traction control \* Dual front impact airbag supplemental restraint system with passenger cancel
- \* Dual seat mounted side impact airbag supplemental restraint system
- \* Safety Canopy System curtain 1st and 2nd row overhead airbag supplemental restraint system
- \* Remote activated perimeter/approach lighting \* Power remote door locks with 2 stage unlock and panic alarm
- \* Security system with SecuriLock immobilizer \* MyKey restricted driving mode
- \* Manually adjustable front head restraints \* 3 manually adjustable rear head restraints

**Dimensions**

*General Weights*

Curb 7961 lbs. GVWR 19500 lbs.  
Front GAWR 7000 lbs. Rear GAWR 14706 lbs.  
Payload 11580 lbs. Front curb weight 4611 lbs.  
Rear curb weight 3350 lbs. Front axle capacity 7000 lbs.  
Rear axle capacity 14706 lbs. Front spring rating 7000 lbs.  
Rear spring rating 15000 lbs. Front tire/wheel capacity 7500 lbs.  
Rear tire/wheel capacity 15000 lbs.

*Trailing Type*

Harness Yes Trailer sway control Yes

*General Trailing*

5th-wheel towing capacity 16900 lbs. Towing capacity 16000 lbs.  
GCWR 26000 lbs.

*Fuel Tank type*

Capacity 40 gal.

*Interior cargo*

Cargo volume 31.6 cu.ft. Maximum cargo volume 31.6 cu.ft.

**Powertrain**

*Engine Type*

Brand Powerstroke Block material Iron  
Cylinders V-8 Head material Aluminum  
Ignition Compression Injection Diesel direct injection  
Liters 6.7L Orientation Longitudinal  
Recommended fuel Diesel Valves per cylinder 4  
Valvetrain OHV Forced induction Intercooled turbo

*Engine Spec*

Bore 3.90" Compression ratio 16.2:1

Displacement 406 cu.in. Stroke 4.25"

*Engine Power*

Output 330 HP @ 2,600 RPM Torque 750 ft.-lb @ 2,000 RPM

*Alternator*

Type Dual Amps 220

*Battery*

Amp hours 78 Cold cranking amps 750  
Run down protection Yes Type Dual

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

*Transmission*

Electronic control Yes Lock-up Yes

Overdrive Yes Speed 6

Type Automatic

*Transmission Gear Ratios*

1st 3.974 2nd 2.318

3rd 1.516 4th 1.149

5th 0.858 6th 0.674

Reverse Gear ratios 3.128

*Transmission Torque Converter*

Stall ratio 1.90

*Transmission Extras*

Driver selectable mode Yes Sequential shift control SelectShift

*Drive Type*

Type Rear-wheel

*Drive Feature*

Limited slip differential Mechanical Traction control Driveline

*Drive Axle*

Ratio 4.88

*Exhaust*

Material Stainless steel System type Single

*Emissions*

CARB Federal EPA Tier 2 Bin 8

*Fuel Economy*

Fuel type Diesel

*Engine Retarder*

Type Yes

**Driveability**

*Brakes*

ABS 4-wheel ABS channels 3

Type 4-wheel disc Vented discs Front and rear

*Suspension Control*

Ride Firm

*Front Suspension*

Independence Mono-beam non-independent Anti-roll bar Regular

*Front Spring*

Type Coil Grade HD

*Front Shocks*

Type HD

*Rear Suspension*

Independence DANA 130 rigid axle Type Leaf

Anti-roll bar Regular

*Rear Spring*

Type Leaf Grade HD

*Rear Shocks*

Type HD

*Steering*

Activation Hydraulic power-assist Type Re-circulating ball

*Steering Specs*

# of wheels 2

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**Exterior**

*Front Wheels*

Diameter 19.5" Width 6.00"

*Rear Wheels*

Diameter 19.5" Width 6.00"

Dual Yes

*Front and Rear Wheels*

Appearance Argent Material Steel

*Front Tires*

Aspect 70 Diameter 19.5"

Sidewalls BSW Speed S

Tread AS Type LT

Width 225mm LT load rating G

RPM 647

*Rear Tires*

Aspect 70 Diameter 19.5"

Sidewalls BSW Speed S

Tread AS Type LT

Width 225mm LT load rating G

RPM 647

*Wheels*

*Body Features*

Front license plate bracket Yes Front splash guards Yes

Body material Aluminum Side impact beams Yes

*Body Doors*

Door count 4 Left rear passenger Reverse opening

Right rear passenger Reverse opening

*Exterior Dimensions*

Cab to axle 84.0" Frame section modulus 17.2cu.in.

**Safety**

*Airbags*

Driver front-impact Yes Driver side-impact Seat mounted

Overhead Safety Canopy System curtain 1st  
and 2nd row

Passenger front-impact Cancellable

Passenger side-impact Seat mounted

*Seatbelt*

Height adjustable Front

*Security*

Immobilizer SecuriLock Panic alarm Yes

Restricted driving mode MyKey

**Seating**

*Passenger Capacity*

Capacity 6

*Front Seats*

Split 40-20-40 Type Split-bench

*Driver Seat*

Fore/aft Manual Reclining Manual

Way direction control 4 Lumbar support Manual

*Passenger seat*

Fore/aft Manual Reclining Manual

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

Way direction control 4  
*Front Head Restraint*  
Control Manual Type Adjustable  
*Front Armrest*  
Centre Yes Storage Yes  
*Rear Seats*  
Descriptor Split-bench Facing Front  
Folding 60-40 Folding position Fold-up cushion  
Type Fixed  
*Rear Head Restraints*  
Control Manual Type Adjustable  
Number 3  
*Front Seat Trim*  
Material Vinyl Back material Vinyl  
  
*Rear Seat Trim Group*  
Material Vinyl Back material Carpet  
**Convenience**  
*AC And Heat Type*  
Air conditioning Manual Air filter Yes  
Underseat ducts Yes  
*Audio System*  
Radio AM/FM stereo Radio grade Regular  
Seek-scan Yes  
*Audio Speakers*  
Speaker type Regular Speakers 6  
*Audio Antenna*  
Type Fixed  
*LCD Monitors*  
1st row 1 Primary monitor size (inches) 2.3  
*Convenience Features*  
Retained accessory power Yes 12V DC power outlet 2  
*Door Lock Activation*  
Type Power with 2 stage unlock Remote Keyfob (front doors)  
Integrated key/remote Yes  
*Instrumentation Type*  
Display Analog  
*Instrumentation Gauges*  
Tachometer Yes Engine temperature Yes  
Turbo/supercharger boost Yes Transmission fluid temp Yes  
Engine hour meter Yes  
*Instrumentation Warnings*  
Oil pressure Yes Engine temperature Yes  
Battery Yes Lights on Yes  
Key Yes Low fuel Yes  
Door ajar Yes Service interval Yes  
Brake fluid Yes  
*Instrumentation Displays*  
Clock In-radio display Exterior temp Yes  
Systems monitor Yes  
*Instrumentation Feature*

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

Trip computer Yes Trip odometer Yes

*Steering Wheel Type*

Material Urethane Tilting Manual

Telescoping Manual

*Front Side Windows*

Window 1st row activation Power

*Windows Rear Side*

2nd row activation Power

*Window Features*

1-touch down Driver and passenger 1-touch up Driver and passenger

Tinted Light

*Front Windshield*

Wiper Variable intermittent

*Rear Windshield*

Window Fixed

**Interior**

*Passenger Visor*

Mirror Yes

*Rear View Mirror*

Day-night Yes

*Headliner*

Coverage Full Material Cloth

*Floor Trim*

Coverage Full Covering Vinyl/rubber

*Trim Feature*

Gear shift knob Urethane Interior accents Chrome

*Lighting*

Dome light type Fade Front reading Yes

Illuminated entry Yes Variable IP lighting Yes

*Overhead Console Storage*

Storage Yes Type Full

*Storage*

Driver door bin Yes Front Beverage holder(s) Yes

Glove box Locking Passenger door bin Yes

Illuminated Yes Instrument panel Bin

Dashboard Covered Rear door bins Yes

*Legroom*

Front 43.9" Rear 33.5"

*Headroom*

Front 40.8" Rear 40.3"

*Hip Room*

Front 62.5" Rear 64.7"

*Shoulder Room*

Front 66.7" Rear 65.8"

*Interior Volume*

Passenger volume 116.0 cu.ft.

**Warranty**

*Basic*

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

Distance 36000 miles Months 36 months  
*Powertrain*  
Distance 60000 miles Months 60 months  
*Corrosion Perforation*  
Distance Unlimited miles Months 60 months  
*Roadside Assistance*  
Distance 60000 miles Months 60 months  
*Diesel Engine*  
Distance 100000 miles Months 60 months

**CAB TO AXLE DIMESION**

Cab to axle will be 60".

**CHASSIS MODIFICATIONS**

**LUBRICATION AND TIRE DATA PLATE**

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid . . (if applicable)
- Pump priming system fluid, if applicable . . (if applicable)
- Drive axle(s) lubrication fluid
- Air conditioning refrigerant . . (if applicable)
- Air conditioning lubrication oil . . (if applicable)
- Power steering fluid
- Cab tilt mechanism fluid . . (if applicable)
- Transfer case fluid . . (if applicable)
- Equipment rack fluid (if applicable)
- CAFS air compressor system lubricant . . (if applicable)
- Generator system lubricant . . (if applicable)
- Front tire cold pressure
- Rear tire cold pressure
- Maximum tire speed ratings

**VEHICLE DATA PLATE**

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the;
  - Engine
  - Transmission
  - Air
  - Fuel
- Serial numbers for the;



**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

- Engine
- Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

**OVERALL HEIGHT, LENGTH DATA PLATE (US)**

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in feet and inches, the length of the completed fire apparatus in feet and inches, and the GVWR in pounds.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**PERSONNEL CAPACITY**

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

**SEAT BELT WARNING - FAMA06/07**

A safety sign FAMA06 shall be visible from each seat that is not equipped with occupant restraint and therefore not intended to be occupied while the vehicle is in motion.

A safety sign FAMA07, which warns of the importance of seat belt use, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

**EQUIPMENT MOUNTING FAMA10**

A safety sign FAMA10, which warns of the need to secure items in the cab, shall be visible inside the cab.

**FIRE SERVICE TIRES - FAMA12**

A safety sign FAMA12, which warns of the special requirements for fire service-rated tires, shall be visible to the driver entering the cab of any apparatus so equipped.

**HELMET WARNING - FAMA15**

A safety sign FAMA15, which warns not to wear helmets while the vehicle is in motion, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

**CLIMBING METHOD - FAMA23**

A safety sign FAMA23, which warns of the proper climbing method, shall be visible to personnel entering the cab and at each designated climbing location on the body.

**REAR STEP CROSSWALK WARNING - FAMA24**

A safety sign FAMA24, which warns personnel not to ride on the vehicle, shall be located at the rear step areas and at any cross walkways.

**FINAL STAGE MANUFACTURER VEHICLE CERTIFICATION**

A final stage manufacturer vehicle certification label shall be provided and installed in the driver cab door jamb area.

**FRONT BUMPER**

The front bumper shall be as provided by the cab/chassis manufacturer. No other alteration or modifications are required to extension length.

**FRONT TOW PROVISIONS**

The front tow provisions shall be supplied and installed by the cab/chassis manufacturer.

# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

#### **AIR INTAKE SYSTEM**

An air filter shall be provided in the engine's air intake system by the body builder. Air inlet restrictions shall not exceed the engine manufacturer's recommendations.

The air inlet shall be equipped with a means of separating water and burning embers from the air intake system.

This requirement shall be permitted to be achieved by either of the following methods:

1. Provision of a device such that burning particulate matter larger than 0.039 in. (1.0 mm) in diameter cannot reach the air filter element.
2. Provision of a multi screen ember separator capable of meeting the test requirements defined in the Parker Hannafin, Racor Division, publication LF 1093-90, *Ember Separation Test Procedure*, or an equivalent test.

#### **EXHAUST**

The exhaust system shall be as provided by cab/chassis manufacturer. The tailpipe may require some modifications for proper ground clearances and fit with body.

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the vehicle or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position or entry doors on body.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

#### **SEAT BELT COLOR AND MOUNTING**

Section 14.1.3.3 of the NFPA 1901 Standards, requires all seat belt webbing in cab to be bright red or bright orange in color, and the buckle portion of the seat belt shall be mounted on a rigid or semi rigid stalk such that the buckle remains positioned in an accessible location.

The seat belt webbing color requirement of 14.1.3.3 shall not apply to vehicles with a GVWR of 19,500 lb (8,845 kg) or less.

#### **SEAT BELT WEB LENGTH - COMMERCIAL CAB**

Sections 14.1.3.2 and 14.1.3.3 of the NFPA 1901 standards, require the effective seat belt web length for a Type 1 lap belt for pelvic restraint to be a minimum of 60", and a Type 2 pelvic and upper torso restraint-style seat belt assembly to be a minimum of 110".

The chassis seat belt web length as supplied by the commercial chassis manufacturer will not be compliant to NFPA Standards 14.1.3.2 and 14.1.3.3.

Per East Point Fire Department specification for a commercial chassis, this emergency vehicle may not have seat belts of this required length. These belts may not provide sufficient length for large firefighters in bunker gear. This specification for an emergency fire apparatus for these seat belts shall be non-compliant to NFPA 1901 standards, effective at the time of order.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**SEAT BELT MONITORING SYSTEM - COMMERCIAL CAB**

Section 14.1.3.9 of the NFPA 1901 Standards, requires that a seat belt warning system be provided. The seat belt warning device is intended to assist the driver or officer in determining whether all occupants are seated and belted before the vehicle is driven.

Per East Point Fire Department specification for a commercial chassis, this emergency vehicle may not have a seat belt monitoring system. Without this device, the driver must manually determine that all occupants are seated and belted before the apparatus is placed in motion. This specification for an emergency fire apparatus for the seat belt monitoring system shall be non-compliant to NFPA 1901 standards, effective at the time of order.

**IGNITION KEY**

If the vehicle is specified to have an ignition key it will be attached to steering column or dash with vinyl covered steel cable.

**SIX (6) – LED TIRE PRESSURE VISUAL INDICATORS**

Each tire shall be equipped with a VECSAFE heavy duty valve cap (or equal) LED indicator that indicates proper tire pressure. The VECSAFE valve cap is self-calibrating. When the cap is mounted on the valve stem the first time, it will memorize that tire pressure, and can be set to recognize a drop in pressure as little as 4 psi. It can be checked for functionality and battery condition by simply unscrewing the cap. If it is in working condition, it will immediately start blinking.

**HELMET STORAGE**

No helmet storage is required in the cab driving area.

**CAB MIRRORS, DRIVER ADJUSTABLE**

Section 14.3.5 of the NFPA 1901 Standards, 2009 edition, requires all primary rear view mirrors used by the driver to be adjustable from the driver's position.

**MUDFLAPS**

There shall be 1/4" rubber mudflaps provided and installed behind each set of tires to prevent throwing road debris and lower road spray.

**ROAD EMERGENCY SAFETY KIT**

The completed unit shall be supplied with one (1) set of three (3) dual faced reflective triangles, and three (3) warning flares complete with storage case per DOT requirements.

One (1) 2.5 lb. ABC type vehicle fire extinguisher with bracket per DOT requirements shall be provided and mounted inside cab area.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**FUEL FILL**

There shall be one (1) chassis supplied fuel fill mounted in the streetside exterior wheel well panel, behind the rear axle. The fill shall have a permanent label with the text "DIESEL FUEL ONLY".

**DEF FLUID FILL**

The DEF fluid fill shall be as supplied by commercial cab/chassis manufacturer and mounted in the streetside fender panel.

**BODY DESIGN**

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the East Point Fire Department to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the East Point Fire Department from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

**EXTERIOR ALUMINUM BODY**

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas.

The front and rear corners of body shall be formed as part of the front or rear body panels. This provides a stronger body corner and finished appearance. The use of extruded corners, or caps will not be acceptable, No Exceptions.

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded and caulked to prevent moisture from entering the compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

#### **DRIP RAILS**

The body shall have drip rails over the side full height compartments. The drip rails shall be formed into the upper body panels providing a ridged lower panel and a flat upper body panel surface. The use of mechanically fastened, taped or glued on drip rails will not be acceptable, No Exceptions.

#### **ALUMINUM TREADPLATE ROOF**

The roof shall be constructed with .125" aluminum 3003H-14 alloy tread plate. Roof panel shall be welded or bolted in place. If bolted in place the bolt heads will be properly caulked and sealed to prevent moisture penetration into body.

#### **BODY SUBFRAME**

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 4" x 1/8" aluminum tubes minimum, the same width as the chassis frame rails. Welded to this

# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

tubing shall be cross members of 2" x 4" x 1/8" aluminum. Smaller dimension, lighter gauge tubing or angle material subframe shall not be accepted.

These cross members shall extend the full width of the body to support the compartments. Cross members shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum cross members shall be located as necessary to support walkway or heavy equipment.

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.

#### **BODY MOUNTING**

The body subframe shall be fastened to the chassis frame with a minimum of four (4) spring loaded body mounts. Each mount shall be configured using a two-piece encapsulated slide bracket. The two (2) brackets shall be fabricated of heavy duty 1/4" thick steel and shall have a powder coat finish to prevent any corrosion. Each mounting assembly shall utilize one (1) 3/4" diameter x 6" long grade 8 bolts and one (1) heavy duty spring. The assembly design shall allow the body and subframe to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall eliminate any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement will not be acceptable.

#### **10" REAR STEP BUMPER**

The full width rear bumper shall be constructed from 2" x 2" x 1/8" steel tubing frame and covered with 3/16" aluminum tread plate. Any stepping surface shall have a grip surface insert to meet NFPA requirements. The bumper shall extend from the rear vertical body panel 10" and provide a rear step with a minimum of 1/2" space at body for water drainage.

#### **REAR TOW EYES**

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below body. The tow eyes shall be fabricated from 3/4" thick steel plate with a 3" diameter opening. Tow eyes shall have a black powder coat finish.

#### **GROUND LIGHTS**

There shall be two (2) OnScene 8" Access LED lights installed below bumper capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting shall be switchable but activated automatically when the vehicle park brake is set.

#### **WHEEL WELL EXTERIOR PANEL**

The exterior panel of the body wheel well enclosure shall be constructed from 1/8" aluminum smooth plate and will be bolted on for easy removal and replacement.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**DIEFORMED BEADED EDGE BODY FENDERS**

A die formed beaded edge shall be provided along the radius of the wheel well opening for a finished appearance.

**WHEEL WELL LINERS**

The wheel wells shall be constructed by the compartment walls that surround the wheel well area. The interior wheel well area shall be designed so that it does not accumulate dirt or water.

**BODY PAINT SPECIFICATIONS**

**BODY PAINT PREPARATION**

After the body and components have been fabricated they shall be disassembled so when vehicle is complete there shall be finish paint beneath the removable components. The body shall be removed from chassis during the paint process to insure proper paint coverage. The body and components shall be metal finished as follows to provide a superior substrate for painting.

The exterior (and interior, if painted) body shall undergo a thorough cleaning process starting with a biodegradable phosphoric acid solution to begin the etching process followed by a complete clear water rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the metal surface for greater film adhesion.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

**PAINT PROCESS**

The paint process shall follow the strict standards set forth by PPG Industries guidelines. Painters applying PPG products will be PPG Certified Commercial Technicians, and re-certified every two (2) years. The body shall go through the following paint process;

- 1) Clean bare metal with a wax and grease remover using low lint rags.
- 2) Inspect, straighten, and hammer high points, grind all seams, sharp edges, and welds. DA sand entire paintable surfaces using 24-180 grit dry paper. Plastic fill all low spots and DA sand fill areas using 36-180 grit dry paper. Apply pinhole filler and DA sand areas using 80-180 grit dry paper.
- 3) Re-clean bare metal using a wax and grease remover and low lint rags.
- 4) Within 24 hours, a PPG Delfleet® epoxy color primer with proper hardener for corrosion resistance using a pressure pot spray gun and applying 2-5 full wet coats or 1.5-8.0 dry mils max. achieving full hiding and allow to air dry 60 minutes @ 70°F or bake for 45 minutes @ 140°F degree.
- 5) Inspect, putty fill, and dry guild coat entire body surface and DA sand using 180-400 grit dry paper.
- 6) Re-clean bare metal using a wax and grease remover using low lint rags.
- 7) A PPG Delfleet® primer sealer with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 1 full wet coat or 1.0-2.0 dry mils achieving full hiding and allow to flash off in spray booth for minimum of 60 minutes @ 70°F.
- 8) A PPG Delfleet® FBCH basecoat (color) with proper hardener and dry additive shall then be sprayed using a pressure pot set @ 45-60 PSI and achieving full hiding or 1.5-2.0 wet mils and allow to flash off in spray booth 45-60 minutes before applying clearcoat.



# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

- 9) A PPG Delfleet® clearcoat with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 2-3 full wet coats or 5.0 wet mils for a uniform gloss and allow to flash off in spray booth 10 minutes and bake for 120-140 minutes @ 125°F (surface temp.).
- 10) After cooling, DA sand heavy orange peel or runs using 1000 grit dry sand paper and final DA sand using 1500-2000 grit dry sand paper. Wipe off all surfaces to remove dust and debris. Buff unit as needed using 3M rubbing compound and a white wool pad and inspect until all sand scratches are removed.
- 11) Polish as needed using 3M Perfect-It-Polish and a black foam pad, repeat as necessary and inspect until all sand scratches are removed.

#### **PAINT - ENVIRONMENTAL IMPACT**

The contractor shall meet or exceed all current State (his) regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. PPG Delfleet® Evolution paint shall be free of all heavy metal (lead & chromate) components. Paint emissions from sanding and painting shall be filtered and collected. All paint wastes shall be disposed of in an environmentally safe manner. Solvents used in cleanup operations shall be collected, sent off-site for distillation and returned for reuse.

#### **FASTENERS**

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, an isolation tape, or gasket shall be used to prevent damage to the finish painted surfaces. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nuts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

#### **ELECTROLYSIS CORROSION CONTROL**

The apparatus shall be assembled using ECK or similar corrosion control on all high corrosion potential areas.

ECK protects aluminum and stainless steel against electrolytic reaction, isolates dissimilar metals and gives bedding protection for hardware and fasteners. ECK contains anti-seizing lubricant for threads. ECK is dielectric and perfect for use with electrical connectors.

#### **PAINT FINISH - SINGLE COLOR**

The body shall be painted with a single color of PPG Delfleet® Evolution paint per approved customer spray-out.

Touch-up paint shall be provided with completed vehicle.

- Paint Color: Match cab/chassis supplied paint color.

#### **BODY UNDERCOATING**

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

**PAINT WARRANTY**

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle. **Pro-rated warranties will not be acceptable.**

**COMPARTMENT INTERIOR FINISH**

The interior of all exterior body compartments shall be a "Maintenance Free" smooth unpainted finish. All body seams shall be finished with a caulk sealant for both appearance and moisture protection.

**REFLECTIVE STRIPE REQUIREMENTS**

**Material**

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retro-reflection of 10 with observation angle of 0.2 degrees and entrance angle of - 4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

**Minimum Requirements**

A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 4 in. (100 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

**GRAPHICS PROOF**

A color graphics proof of the reflective striping layout shall be provided for approval by East Point Fire Department prior to installation. The graphics proof shall be submitted to East Point Fire Department on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**REFLECTIVE STRIPE - CAB SIDE**

The reflective stripe material shall be 4" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

There shall be a 1" Scotchcal reflective stripe located 1" above and a second 1" Scotchcal reflective stripe located 1" below the main stripe.

- This reflective stripe shall be white in color.

**REFLECTIVE STRIPE - CAB FRONT**

The reflective stripe material shall be 4" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

**REFLECTIVE STRIPE - CAB DOOR INTERIOR**

Any door of the apparatus designed to allow persons to enter or exit the apparatus shall have at least 96 in.2 (62,000 mm2) of retroreflective material affixed to the inside of the door.

The stripe material shall be 3M Scotchlite 680.

- This reflective stripe shall be white in color.

**REFLECTIVE STRIPE - BODY SIDES**

The reflective stripe material shall be 4" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

There shall be a 1" Scotchcal reflective stripe located 1" above and a second 1" Scotchcal reflective stripe located 1" below the main stripe.

- This reflective stripe shall be white in color.

The stripe shall remain in a straight line from the front of the front of cab to the rear body.

**CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS**

At least 50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width.

The rear side panels of the body on each side of a rear stairway or compartment shall have a chevron style reflective stripe, extending from bumper height up to side compartment drip rail height. Each chevron panel shall be a full sheet and shall have a 3M UV over laminate to protect from UV rays, scene

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

damage, and everyday use. Chevron panel shall have a minimum 10 year warranty for material failure, and colorfastness.

The stripe material shall be 3M Scotchcal 680 series.

This reflective chevron stripe shall alternate red and yellow in color.

**LETTERING**

**GRAPHICS PROOF**

A color graphics proof of the lettering layout shall be provided for approval by East Point Fire Department prior to installation. The graphics proof shall be submitted to East Point Fire Department on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

The following lettering shall be provided and installed on the completed unit as follows;

**SIDE CAB DOOR LETTERING**

There shall be thirty (30) 3" high reflective letters furnished and installed on the vehicle.

- This reflective lettering shall be gold in color.

**UPPER BODY SIDE LETTERING**

There shall be thirty (30) 6" high reflective letters furnished and installed on the vehicle.

- This reflective lettering shall be gold in color.

**REAR BODY LETTERING**

**FRONT OF CAB LETTERING**

**ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM)**

The vehicle shall be equipped with R•O•M Series IV roll-up exterior compartment doors. The R•O•M roll-up doors shall be complete with the following features;

Each shutter slat, track, bottom rail, and drip rail shall be constructed from anodized 6063 T6 aluminum. Shutter slats shall feature a double wall extrusion 0.315" thick with a concave interior surface to minimize loose equipment jamming the shutter door closed. Shutter slats shall feature an interlocking end shoe to prevent side to side binding of the shutter door during operation. Slat must have interlocking joints with an inverted locking flange. Slat inner seal shall be a one piece PVC extrusion; seal design will be such to prevent metal to metal contact while minimizing dirt and water from entering the compartment.

Shutter door track shall be one piece design with integral overlapping flange to provide a clean finished look without the need of caulk. Door track shall feature an extruded Santoprene rubber double lip low profile side seal with a silicone co-extruded back to reduce friction during shutter operation.

# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

Shutter bottom rail shall be a one piece double wall extrusion with integrated finger pull. Finger pull shall be curved upward with a linear striated surface to improve operator grip while operating the shutter door. Bottom rail shall have a smooth contoured interior surface to prevent loose equipment from jamming the shutter door. Bottom rail seal shall be made from Santoprene; it will be a double "V" seal to prevent water and debris from entering compartment. Bottom rail lift bar shall be a one piece "D" shaped aluminum extrusion with linear striations to improve operator grip during operation. Lift bar shall have a wall thickness of 0.125". Lift bar shall be supported by no less than two pivot blocks; pivot blocks shall be constructed from Type 66 Glass filled reinforced nylon for superior strength. Bottom rail end blocks shall have incorporated drain holes which will allow any moisture that collects inside the extrusion to drain out.

Shutter door shall have an enclosed counter balance system. Counter balance system shall be 4" in diameter and held in place by two (2) heavy duty 18 gauge zinc plated plates. Counter balance system shall have two (2) over-molded rubber guide wheels to provide a smooth transition from vertical track to counter balance system; no foam material of any kind shall be permitted or used in this area.

#### **ROM DOOR BOTTOM RAIL**

All exterior compartment doors shall have the standard 3.0" tall bottom rail extrusion for easy one (1) hand opening and closing.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.

#### **BODY HEIGHT MEASUREMENTS**

The body height shall be approximately the same height as cab roof with vertical body dimensions as follows:

##### **AHEAD OF REAR AXLE**

	<u>Description</u>	<u>Dimension</u>
A	Bottom of Subframe to Top of Body	47.0"
B	Bottom of Subframe to Bottom of Body	12.0"
C	Vertical Door Opening	
	-with roll-up door	43.0"
	-with hinged door	52.0"

##### **ABOVE REAR AXLE**

	<u>Description</u>	<u>Dimension</u>
D	Vertical Door Opening - Above Rear Wheel	
	-with roll-up door	23.5"
	-with hinged door	32.5"

##### **BEHIND REAR AXLE**

	<u>Description</u>	<u>Dimension</u>
E	Bottom of Subframe to Bottom of Body	9.0"
F	Vertical Door Opening	
	-with roll-up door	40.0"
	-with hinged door	49.0"

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**GENERAL**

	<u>Description</u>	<u>Dimension</u>
G	Bottom or Drip Rail to Top of Body -with roll-up door	8.0"
	Bottom or Drip Rail to Top of Body -with hinged door	2.5"

(Dimensions are approximate and subject to change during construction or design process.)

**BODY WIDTH DIMENSIONS**

The body shall be 96.0" wide, and 98.0" wide at drip rails. Interior compartment depth dimensions shall be approximately:

<u>Area Description</u>	<u>Dimension</u>
Transverse above subframe	91.0"
Compartment depth below subframe	21.0"

**STREETSIDE COMPARTMENT - FRONT (S1)**

The interior useable compartment width shall be approximately 32.0" wide.

The compartment door opening shall be approximately 28.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

**COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-Trac for specified component installation.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- One (1) OnScene 64" Access LED compartment light, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2)**

The interior useable compartment width shall be approximately 46.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

**COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-Trac for specified component installation.
- One (1) OnScene 28" Access LED compartment light, vertically mounted.

**STREETSIDE COMPARTMENT - REAR (S3)**

The interior useable compartment width shall be approximately 22.0" wide.

The compartment door opening shall be approximately 18.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

**COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-Trac for specified component installation.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- One (1) OnScene 64" Access LED compartment light, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

**CURBSIDE COMPARTMENT - FRONT (C1)**

The interior useable compartment width shall be approximately 32.0" wide.

The compartment door opening shall be approximately 28.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

**COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-Trac for specified component installation.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- One (1) OnScene 64" Access LED compartment light, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

**CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C2)**

The interior useable compartment width shall be approximately 46.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.



**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

**COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-Trac for specified component installation.
- One (1) OnScene 28" Access LED compartment light, vertically mounted.

**CURBSIDE COMPARTMENT - REAR (C3)**

The interior useable compartment width shall be approximately 22.0" wide.

The compartment door opening shall be approximately 18.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

**COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-Trac for specified component installation.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- One (1) OnScene 64" Access LED compartment light, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

**REAR COMPARTMENT - CENTER (RC1)**

The open rear storage area will be closed in to provide a rear center compartment.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 41.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

**COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum shelf-Trac for specified component installation.

**FRONT GRAVEL GUARDS**

Gravel guards shall be provided on front lower body corners. Guards shall be 12" high, extend from behind cab or step and wrap around to the front compartment door opening fabricated from 20 gauge brushed stainless steel.

**REAR BODY HANDRAILS**

There shall be two (2) 24" vertical handrails on the rear of the body. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

**LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC**

General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

# EAST POINT FIRE DEPT

## Utility Unit

### Production Specifications

SVI #1015

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125 % of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10 %. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

#### Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage over-current protective devices. Such devices shall be readily accessible and protected against heat in excess of the over-current device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- SAE J156, *Fusible Links*
- 1) SAE J553, *Circuit Breakers*
- 2) SAE J554, *Electric Fuses (Cartridge Type)*
- 3) SAE J1888, *High Current Time Lag Electric Fuses*
- 4) SAE J2077, *Miniature Blade Type Electrical Fuses*

# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125 % of maximum current for which the circuit is protected.

#### Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

#### Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- 5) The propulsion engine and transmission
- 1) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- 2) The radio(s) at a duty cycle of 10 percent transmit and 90 % receive (for calculation and testing purposes, a default value of 5 A continuous)
- 3) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- 4) The minimum optical warning system, where the apparatus is blocking the right-of way
- 5) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- 6) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

#### Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

#### Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

#### Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

#### **12 VOLT DIAGNOSTIC RELAY CONTROL CENTER**

The 12 volt power distribution shall be conveniently located with easy access for service. All relays and circuit breakers shall be plug-in type allowing for removal for repairs without necessitating soldering or tools. The sockets mounts for both the relays and circuit breakers shall be of a design that permits the use of standard automotive type components.

The 12 volt distribution panel shall utilize printed circuit boards mounted in high strength enclosure. Each printed circuit board shall be provided with twelve (12) heavy duty independent switching relays. Each relay shall have the ability to be configured either normally open or normally closed and be protected by a 20 amp automatic reset breaker. Each circuit will be provided with a LED for visual diagnostic.

Power distribution panel shall be located in apparatus body within a protected enclosure with removable or hinged cover.

#### **CAB CONSOLE**

A center cab console shall be provided and located in the center of the cab, on the floor just ahead of the seat. Console shall be as large as possible and fabricated of 1/8" smooth aluminum. A textured powder coat paint finish shall be provided for durability and finished appearance.

The console shall contain the 12 volt switches to operate the emergency warning equipment on the vehicle. There shall be room available for a siren control head or customer supplied radio.

The final design of console shall be determined by the East Point Fire Department at the pre-construction meeting.

#### **ROCKER SWITCH PANEL**

The control of the 12 volt equipment installed on chassis and body shall be centrally located in the cab. The individual rocker style switches shall be located on a separate electrical panel, complete with backlit name tags describing function of each individual switch. The back lighting shall have two (2) levels of intensity, low level lights activated when the vehicle lights or ignition switch is turned "On", and high level lights activated when individual switch is turned "On". An internally lighted rocker switch shall be furnished to the left of specified emergency lighting switches, and identified as "MASTER EMERGENCY SWITCH".

Switch circuitry shall be on a printed circuit board. The lights shall be solid state type and have a 100,000 hour life span.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**ELECTRICAL SYSTEM MANAGER**

**LOAD MANAGEMENT**

If the total continuous electrical load exceeds the minimum continuous electrical output rating of the installed alternator(s), an Innovative Controls automatic electrical load management system shall be required. The minimum continuous electrical loads shall not be subject to automatic load management.

The apparatus 12 volt electrical system shall be provided with a system manager for:

- 7) Monitoring chassis battery voltage
  - Shedding pre-determined electrical circuits
  - Sequencing pre-determined electrical circuits
  - Automatically controlling chassis engine fast-idle
  - Monitor master switch and parking brake applications
  - Automatically control warning light modes ("Calling-For" and "Blocking Right of Way")
  - Provide low voltage alarm
  - Programmable control circuits
  - Remote system status indicator panel

System manager shall perform all electrical functions required by current NFPA 1901 Standards.

**BATTERY MONITORING**

The system manager shall monitor the vehicle battery voltage. When electrical loads exceed the alternator output and the voltage drops, the load manager shall start shutting down electrical outputs. The system shall shut down only as many outputs required to maintain the system voltage. A special indicator to show different states of the electrical system by flashing at rate proportional to the battery discharge.

**LOAD SEQUENCING AND SHEDDING**

The system shall be capable of sequentially switching and shedding 12 volt loads. The Master light switch starts the sequential switch when it is turned "On". Likewise turning the Master Switch "Off" will sequentially de-energize the loads.

**BATTERY SYSTEM**

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

An onboard battery conditioner or charger or a polarized inlet shall be provided for charging all batteries. Where an onboard conditioner or charger is supplied, the associated line voltage electrical power system shall be installed in accordance with Chapter 22.

One of the following master disconnect switches shall be provided:

- A master body disconnect switch that disconnects all electrical loads not provided by the chassis manufacturer
- 1) A master load disconnect switch that disconnects all electrical loads on the apparatus except the starter

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

A green "battery disconnect on" indicator light that is visible from the driver's position shall be provided.

Rechargeable hand lights, radios, and other similar devices shall be permitted to be connected to the electrical system ahead of the master disconnect switch.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within 5 seconds.

#### **BATTERY SWITCH**

The chassis ignition key shall activate a heavy duty relay to provide 12 volt battery power to the vehicle. There shall be a green "BATTERY ON" pilot light that is visible from the driver's position.

#### **BATTERY SOLENOID**

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

#### **BATTERY CONDITIONER**

One (1) Kussmaul model Auto Charge 1000 single battery conditioner, with 120 VAC input and 15 amp, 12 volt output shall be provided. This system shall monitor the condition of batteries and provide an electrical current at variable rates to overcome battery failure. A display shall be provided with charge indicator, remote mounted.

# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

#### **SHORE POWER INLET**

One (1) Kussmaul 120 VAC, 20 amp Super Auto-Eject shore power inlet(s) shall be provided. The shore power connection shall automatically disengage from vehicle when chassis ignition is engaged.

The protective ground from the shoreline inlet shall be bonded to the vehicle frame.

2) The outlet cover shall be red.

- The shore power inlet shall be located on the streetside front of body, outboard of the cab.

#### **ENGINE COMPARTMENT LIGHT**

There shall be one (1) OnScene Severe Service LED light(s) mounted in the engine compartment with integral switch with a light output of at least 20 candlepower (250 lumens). The engine compartment light(s) shall operate only when the master battery switch is turned "On".

#### **CAB HAZARD WARNING LIGHT**

A Truck-Lite red LED flashing light shall be provided and located in the driving compartment and be illuminated automatically whenever the vehicles parking brake is not fully engaged and any of the following conditions exist:

- Any passenger or equipment compartment door is not closed.
- Any ladder or equipment rack is not in the stowed position.
- Stabilizer system is not in its stowed position.
- Powered light tower is not stowed.
- Any other device permanently attached to the apparatus is open, extended, or deployed in a manner that is likely to cause damage to the apparatus if the apparatus is moved.

Compartments and equipment meeting all of the following conditions shall be permitted to be exempt from being wired to the hazard light:

- The volume is less than or equal to 4 ft<sup>3</sup> (0.1 m<sup>3</sup>).
- The compartment has an opening less than or equal to 144 in.<sup>2</sup> (92,900 mm<sup>2</sup>).
- The open door does not extend sideways beyond the mirrors or up above the top of the fire apparatus.
- All equipment in the compartment is restrained so that nothing can fall out if the door is open while the apparatus is moving.
- Manually raised pole lights with an extension of less than 5 ft (1.5 m).

The hazard light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

An audible alarm shall be provided for the door ajar light.

#### **BACK-UP ALARM**

The body manufacturer shall furnish and install one (1) 107 dB(A) electronic back-up alarm. Back-up alarm to actuate automatically when the transmission gear selector is placed in reverse.



# **EAST POINT FIRE DEPT**

## **Utility Unit**

### **Production Specifications**

SVI #1015

#### **TAIL LIGHTS**

Rear body tail lights shall be mounted and located per Federal Motor Vehicle Safety Standards, FMVSS and Canadian Motor Vehicle Safety Standards CMVSS. The following lights shall be furnished

- Two (2) Truck Light LED stop/tail/turn lights with red lens
- Two (2) Truck Light LED back-up lights with clear lens

Each light will be separately mounted in a black rubber grommet.

#### **MARKER LIGHTS**

The body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) and Canadian Motor Vehicle Safety Standards (CMVSS) regulations. All body clearance lights shall be Truck-Lite Mini LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

#### **CAB STEP LIGHTS / GROUND LIGHTS**

There shall be two (2) OnScene 8" Access LED light(s) installed on the vehicle capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting designed to provide illumination on areas under the driver and crew riding area exits shall be switchable but activated automatically when the exit doors are opened.

#### **LICENSE PLATE LIGHT**

One (1) Arrow #437 chrome plated LED license plate light shall be installed on the rear of the body. License plate light shall be wired to the headlight circuit of chassis. A fastener system shall be provided for license plate installation.

#### **ELECTRONIC SIREN**

One (1) Whelen model 295SLSA1 electronic siren control with selectable 100 or 200 watt output, hands-free operation, user selectable siren tones, park kill, and standard hard wired microphone shall be provided and installed in cab within easy reach of Driver. Siren power shall be wired through the master warning light switch.

#### **SIREN SPEAKERS**

Two (2) Cast Products Inc. model SAD/P3815-17FSD-1 watt siren speaker shall be provided, one (1) streetside and one (1) curbside.

#### **SIDE SCENE LIGHTS**

There shall be four (4) Whelen Super LED 600 series (6" x 4") recess mounted scene lights (60C0ELZR) provided on the upper body. Light quantity shall be divided equally per side. Each light will have twelve LED diodes. The light shall be an 8-32 degree gradient lens and chrome flange.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

Two (2) switches shall be provided, one (1) for the streetside scene lights, and one (1) for the curbside scene lights.

The lights shall be controlled at the switch panel in cab.

**REAR SCENE LIGHTS**

Two (2) Whelen Super LED 600 series (6" x 4") recess mounted scene lights (60C0ELZR) shall be provided on the upper rear body to light the work area immediately behind the vehicle. Each light will have twelve LED diodes. The light shall have an 8-32 degree gradient lens and chrome flange.

The above scene lights shall light to a level of at least 3 fc (30 lx), measured at 25 equally spaced points on a 2.5 ft (750 mm) grid with in a 10 ft x 10 ft (3 m x 3m) square to the rear of vehicle.

The lights shall be controlled at the switch panel in cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

**WARNING LIGHT PACKAGE**

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four (4) warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four (4) zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two (2) separate signaling modes during emergency operations. One (1) mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One (1) mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two (2) signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

Steadily burning, non flashing optical sources shall be permitted to be used.

**UPPER LEVEL OPTICAL WARNING DEVICES**

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

**ZONE A - FRONT WARNING LIGHTS**

There shall be one (1) Whelen Justice JE2NFPA LED 56" lightbar permanently mounted to the cab roof.

The lightbar configuration (streetside to curbside) shall be:

<u>SECTION</u>	<u>INTERNAL COMPONENTS</u>	<u>LENS COLOR</u>
1	Red Rear Corner Linear LED	Clear
2	Red Front Corner Linear LED	Clear
3	Red Linear LED	Clear
4	Clear Linear LED	Clear
5	Red Linear LED	Clear
6	Blank (Opticom if specified)	Clear
7	Blank (Opticom if specified)	Clear
8	Red Linear LED	Clear
9	Clear Linear LED	Clear
10	Red Linear LED	Clear
11	Red Front Corner Linear LED	Clear
12	Red Rear Corner Linear LED	Clear

All clear lights shall shut down when the parking brake is set to comply with "Blocking" mode requirements as outlined in NFPA 1901.

The lightbar(s) shall be separately controlled at switch panel in the cab.

**ZONE C - REAR WARNING LIGHTS**

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

**LOWER LEVEL OPTICAL WARNING DEVICES**

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1600 mm) above level ground.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

**ZONE A - FRONT WARNING LIGHTS**

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

**ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)**

There shall be two (2) Whelen 500 series (5" x 2") red Linear Super-LED lights (50R02ZRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

**ZONES B AND D - BODY LIGHT (BODY WHEELWELL AREA)**

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

**ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)**

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

**EAST POINT FIRE DEPT**  
**Utility Unit**  
**Production Specifications**  
SVI #1015

**ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)**

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

**EQUIPMENT PAYLOAD WEIGHT ALLOWANCE**

In compliance with NFPA 1901 standards, the special service vehicle shall be designed for an equipment loading allowance of 2,500 lbs. of East Point Fire Department provided equipment based on a 15,001 - 20,000 pound gross vehicle weight rating.

**EQUIPMENT**

The following equipment shall be furnished with the completed special service vehicle;

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- There shall be two (2) Zico AC-32, NFPA approved aluminum wheel chocks provided for 32" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20% grade, with the transmission in neutral, and the parking brake released.
  - The wheel chock(s) shall be mounted behind rear wheels, below body on streetside.
- Two (2) Streamlight FireBox halogen flashlight(s) with shoulder strap shall be provided. Each flashlight shall be orange in color and have a 12 volt DC charger and vehicle mount kit. Each flashlight shall have an 8 watt, 150 lumen halogen spotlight style bulb and reflector with 2 ultra-bright LED taillights. The flashlight(s) shall be wired to battery direct unless otherwise specified by East Point Fire Department.
  - The flashlight(s) shall be mounted on the completed unit in the lower area of compartment S1.

**REMAINING NFPA MINOR EQUIPMENT BY PURCHASER**

All other minor equipment not specified above, but required by NFPA 1901 for special service vehicles, section 10.9.3 shall be supplied and mounted by East Point Fire Department before the unit is placed in emergency service.