

PROPOSAL FOR:

**Las Vegas Fire & Rescue**

**Las Vegas, NV 89101**

**FOR**

**ONE (1) AIR TRUCK**



***"ROCK SOLID QUALITY"***

**DATE: September, 2016**

**SVI TRUCKS** - A Division of Super Vacuum Mfg. Co., Inc.  
3842 Redman Drive - Fort Collins, CO 80524  
Phone: 970.297.7100, Fax: 970.297-7099  
Website: [www.svitrucks.com](http://www.svitrucks.com), Email: [sales@svitrucks.com](mailto:sales@svitrucks.com)

# Las Vegas Fire & Rescue

## Production Specification

### Table of Contents

<b>LIABILITY INSURANCE</b> .....	7
<b>INTERNET IN-PROCESS SITE</b> .....	7
<b>HIGHWAY PERFORMANCE</b> .....	8
<b>SERVICEABILITY</b> .....	8
<b>FIRE APPARATUS DOCUMENTATION</b> .....	8
<b>OPERATIONS AND SERVICE DOCUMENTATION</b> .....	10
<b>NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE</b> .....	10
<b>STATEMENT OF EXCEPTIONS</b> .....	11
<b>CARRYING CAPACITY</b> .....	11
<b>TESTING</b> .....	12
<b>ROAD TEST</b> .....	12
<b>LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST</b> .....	12
<b>TEST SEQUENCE</b> .....	12
<b>TEST AT IDLE</b> .....	13
<b>TEST AT FULL LOAD</b> .....	13
<b>3. LOW VOLTAGE ALARM TEST</b> .....	13
<b>LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST</b> .....	14
<b>DOCUMENTATION</b> .....	14
<b>UL 120/240 VAC CERTIFICATION</b> .....	14
<b>DIELECTRIC VOLTAGE WITHSTAND TEST</b> .....	15
<b>WARRANTY</b> .....	16
<b>CONSTRUCTION PERIOD</b> .....	17
<b>OVERALL HEIGHT REQUIREMENT</b> .....	17
<b>OVERALL LENGTH REQUIREMENT</b> .....	17
<b>OVERALL WIDTH</b> .....	17
<b>PRE-CONSTRUCTION CONFERENCE</b> .....	17
<b>PRE-PAINT CONFERENCE</b> .....	17
<b>FINAL INSPECTION CONFERENCE</b> .....	18
<b>DELIVERY AND DEMONSTRATION</b> .....	18
<b>CAB CHASSIS SPECIFICATIONS</b> .....	18

# Las Vegas Fire & Rescue

## Production Specification

<b>CHASSIS MODIFICATIONS</b> .....	23
<b>LUBRICATION AND TIRE DATA PLATE</b> .....	23
<b>VEHICLE DATA PLATE</b> .....	23
<b>OVERALL HEIGHT, LENGTH DATA PLATE (US)</b> .....	24
<b>FRONT BUMPER</b> .....	25
<b>BUMPER GRAVELSHIELD</b> .....	25
<b>AIR HORN(S)</b> .....	25
<b>FRONT TOW PROVISIONS</b> .....	25
<b>EXHAUST DIVERTER</b> .....	25
<b>BATTERIES</b> .....	26
<b>RADIO ANTENNA INSTALLATION</b> .....	26
<b>12 VDC USB, DUAL PORT PLUG</b> .....	26
<b>12 VDC FUSE BLOCK</b> .....	27
<b>CAB DOOR INTERIOR HAZARD LIGHT - TWO DOOR CAB</b> .....	27
<b>SEAT BELT COLOR</b> .....	27
<b>SEAT BELT WEB LENGTH - COMMERCIAL CAB</b> .....	27
<b>SEAT BELT MONITORING AND VEHICLE DATA RECORDER (VDR) SYSTEMS</b> .....	28
<b>SEAT BELT MONITORING</b> .....	28
<b>VEHICLE DATA RECORDER (VDR)</b> .....	28
<b>OCCUPANT RESTRAINT INDICATOR</b> .....	28
<b>IGNITION KEY</b> .....	28
<b>SIX (6) – LED TIRE PRESSURE VISUAL INDICATORS</b> .....	28
<b>HELMET STORAGE</b> .....	28
<b>CAB CRASH TEST CERTIFICATION</b> .....	29
<b>CAB MIRRORS, DRIVER ADJUSTABLE</b> .....	29
<b>CAB STEP COVER AND BATTERY COMPARTMENT</b> .....	29
<b>BATTERY CHARGING RECEPTACLE LOCATION</b> .....	29
<b>HUB AND NUT COVERS</b> .....	29
<b>MUDFLAPS</b> .....	29
<b>AIR BRAKE SYSTEM QUICK BUILD-UP</b> .....	30
<b>ELECTRIC DOOR LOCK INTERFACE</b> .....	30

# Las Vegas Fire & Rescue

## Production Specification

<b>ROAD EMERGENCY SAFETY KIT</b> .....	30
<b>BODY DESIGN</b> .....	30
<b>EXTERIOR ALUMINUM BODY</b> .....	31
<b>ROOF CONSTRUCTION</b> .....	32
<b>BODY SUBFRAME</b> .....	32
<b>BODY MOUNTING</b> .....	33
<b>10" REAR STEP BUMPER</b> .....	33
<b>REAR TOW EYES</b> .....	33
<b>GROUND LIGHTS</b> .....	33
<b>WHEEL WELL EXTERIOR PANEL</b> .....	33
<b>STAINLESS STEEL BODY FENDERS</b> .....	33
<b>WHEEL WELL LINERS</b> .....	34
<b>SCBA CYLINDER COMPARTMENTS</b> .....	34
<b>BODY PAINT SPECIFICATIONS</b> .....	34
<b>BODY PAINT PREPARATION</b> .....	34
<b>PAINT PROCESS</b> .....	34
<b>BODY UNDERCOATING</b> .....	35
<b>UNDERCOAT WARRANTY</b> .....	36
<b>PAINT WARRANTY</b> .....	36
<b>COMPARTMENT INTERIOR FINISH</b> .....	36
<b>NFPA REQUIRED REFLECTIVE STRIPE</b> .....	36
<b>EXTERIOR COMPARTMENT DOORS</b> .....	37
<b>ROLL-UP DOOR CONSTRUCTION - AMDOR</b> .....	37
<b>STREETSIDE COMPARTMENT - FRONT (S1)</b> .....	37
<b>COMPARTMENT LAYOUT</b> .....	38
<b>STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2)</b> .....	38
<b>COMPARTMENT LAYOUT</b> .....	39
<b>STREETSIDE COMPARTMENT - REAR (S3)</b> .....	40
<b>COMPARTMENT LAYOUT</b> .....	40
<b>CURBSIDE COMPARTMENT - FRONT (C1)</b> .....	41
<b>COMPARTMENT LAYOUT</b> .....	41

# Las Vegas Fire & Rescue

## Production Specification

<b>CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C2)</b> .....	42
<b>COMPARTMENT LAYOUT</b> .....	43
<b>CURBSIDE COMPARTMENT - REAR (C3)</b> .....	43
<b>COMPARTMENT LAYOUT</b> .....	44
<b>REAR COMPARTMENT - CENTER (RC1)</b> .....	44
<b>COMPARTMENT LAYOUT</b> .....	45
<b>ROOF ACCESS HANDRAIL</b> .....	47
<b>LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC</b> .....	47
<b>12 VOLT MULTIPLEX CONTROL CENTER</b> .....	50
<b>BATTERY SYSTEM</b> .....	52
<b>BATTERY SWITCH</b> .....	53
<b>BATTERY SOLENOID</b> .....	53
<b>BATTERY CONDITIONER</b> .....	53
<b>CHASSIS AIR SHORE PUMP</b> .....	53
<b>SHORE POWER INLET</b> .....	53
<b>ENGINE COMPARTMENT LIGHT</b> .....	53
<b>REAR SCENE LIGHTS (BACK-UP LIGHTS)</b> .....	54
<b>INTERIOR CAB LIGHT, LED</b> .....	54
<b>CAB SPOTLIGHT</b> .....	54
<b>BACK-UP ALARM</b> .....	55
<b>REAR VIEW CAMERA</b> .....	55
<b>TAIL LIGHTS</b> .....	55
<b>MIDSHIP MARKER/TURN SIGNAL</b> .....	55
<b>MARKER LIGHTS</b> .....	55
<b>CAB STEP LIGHTS / GROUND LIGHTS</b> .....	56
<b>LICENSE PLATE LIGHT</b> .....	56
<b>ELECTRONIC SIREN</b> .....	56
<b>SIREN ACTIVATION</b> .....	56
<b>SIREN SPEAKER</b> .....	56
<b>BROW MOUNT FLOODLIGHT(S) - LED</b> .....	57
<b>SIDE SCENE LIGHTS - LED</b> .....	57

# Las Vegas Fire & Rescue

## Production Specification

<b>REAR SCENE LIGHTS - LED</b> .....	57
<b>SETCOM INTERCOM SYSTEM</b> .....	57
<b>INTERCOM SYSTEM INSTALLATION</b> .....	58
<b>WARNING LIGHT PACKAGE</b> .....	58
<b>UPPER LEVEL OPTICAL WARNING DEVICES</b> .....	59
<b>LOWER LEVEL OPTICAL WARNING DEVICES</b> .....	60
<b>ONAN PTO GENERATOR</b> .....	61
<b>GENERATOR ENGAGEMENT</b> .....	62
<b>WARRANTY PERIOD</b> .....	62
<b>GENERATOR SPLASH GUARD</b> .....	62
<b>GENERATOR MOUNTING</b> .....	62
<b>MANUALS AND SCHEMATICS</b> .....	62
<b>POWER-TAKE-OFF GENERATOR DRIVE</b> .....	63
<b>ENGINE SPEED CONTROL</b> .....	63
<b>LOADCENTER</b> .....	63
<b>GENERATOR MONITORING PANEL</b> .....	64
<b>SHORE POWER INLET - BATTERY CHARGER</b> .....	64
<b>OUTLETS AND CIRCUITS</b> .....	64
<b>LINE VOLTAGE ELECTRICAL SYSTEM</b> .....	64
<b>GENERAL REQUIREMENTS</b> .....	64
<b>EQUIPMENT PAYLOAD WEIGHT ALLOWANCE</b> .....	71
<b>EQUIPMENT</b> .....	71
<b>REMAINING NFPA MINOR EQUIPMENT BY PURCHASER</b> .....	71

# Las Vegas Fire & Rescue

## Production Specification

### **LIABILITY INSURANCE**

The manufacturer shall furnish with the bid a certificate of insurance for;

Workman's Compensation and Employer's Liability Insurance covering for all employees.

General Liability (each occurrence) of \$1,000,000.00. General Aggregate coverage of \$2,000,000.00. Products Completed / Operations Aggregate coverage of \$2,000,000.00. Medical Expense coverage of \$5,000 (any one person). Personal Injury of \$1,000,000.00.

Automobile liability of \$1,000,000.00 combined single limit (each accident), including any auto, all owned autos, scheduled autos, hired autos, non-owned autos, and garage liability.

Excess Umbrella Liability coverage of \$4,000,000.00 each occurrence, Aggregate of \$4,000,000.00. Garage Keepers Liability coverage of \$4,000,000.00 combined limit.

All insurance policies must be;

- Maintained for the life of the contract,
- Must provide ten (10) days' notice before cancellation,
- Must cover all operations of the contractor, or anyone employed by them.

### **INTERNET IN-PROCESS SITE**

The manufacturer shall post and maintain a website where the Las Vegas Fire & Rescue will be able to view digital images of their apparatus as its being built. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of unit.

### **VEHICLE STABILITY SUPPLIED WITH CAB/CHASSIS**

The cab/chassis shall be equipped with a stability control system. The system shall have, at a minimum, a steering wheel position sensor, a vehicle yaw sensor, a lateral accelerometer and individual wheel brake controls.

### **FIRE APPARATUS PERFORMANCE**

The fire apparatus shall meet the requirements of this standard at elevations of 2000 ft (600 m) above sea level.

The fire apparatus shall meet all the requirements of this standard while stationary on a grade of 6 percent in any direction.

The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C).

# Las Vegas Fire & Rescue

## Production Specification

### **HIGHWAY PERFORMANCE**

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- 1) Accelerating from 0 to 35 mph (55 km/hr) within 25 seconds on a 0 percent grade
- 2) Attaining a speed of 50 mph (80 km/hr) on a 0 percent grade
- 3) Maintaining a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent

The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (109 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal (4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (95 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

### **SERVICEABILITY**

The fire apparatus shall be designed to allow the manufacturer's recommended routine maintenance checks of lubricant and fluid levels to be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

### **FIRE APPARATUS DOCUMENTATION**

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

- 1) The manufacturer's record of apparatus construction details, including the following documents:
  - b) Owner's name and address
  - c) Apparatus manufacturer, model, and serial number
  - d) Chassis make, model, and serial number
  - e) GAWR of front and rear axles and GVWR
  - f) Front tire size and total rated capacity in pounds (kilograms)
  - g) Rear tire size and total rated capacity in pounds (kilograms)
  - h) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
  - i) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
  - j) Type of fuel and fuel tank capacity
  - k) Electrical system voltage and alternator output in amps
  - l) Battery make, model, and capacity in cold cranking amps (CCA)
  - m) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio



# Las Vegas Fire & Rescue

## Production Specification

- n) Ratios of all driving axles
  - o) Maximum governed road speed
  - p) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), maximum discharge pressure capability rating, and serial number
  - q) Pump transmission make, model, serial number, and gear ratio
  - r) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
  - s) Water tank certified capacity in gallons or liters
  - t) Foam tank (if provided) certified capacity in gallons (liters)
  - u) Aerial device type, rated vertical height in feet (meters), rated horizontal reach in feet (meters), and rated capacity in pounds (kilograms)
  - v) Paint manufacturer and paint number(s)
  - w) Company name and signature of responsible company representative
  - x) Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall fire apparatus (with the water tank full but without personnel, equipment, and hose)
- 2) Certification of compliance of the optical warning system (*see 13.8.16*)
  - 3) Siren manufacturer's certification of the siren (*see 13.9.1.1*)
  - 4) Written load analysis and results of the electrical system performance tests (*see 13.14.1 and Section 13.15*)
  - 5) Certification of slip resistance of all stepping, standing, and walking surfaces (*see 15.7.4.5*)
  - 6) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability (*see 16.2.4.1*)
  - 7) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions (*see 16.2.4.2*)
  - 8) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications (*see 16.3.1*)
  - 9) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed (*see 16.3.2.2*)
  - 10) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test (*see 16.5.2.2*)
  - 11) If the apparatus has a fire pump with a maximum discharge pressure capability rating that exceeds the hydrostatic test pressure of 16.5.2.1, the pump manufacturer's certification of the hydrodynamic test
  - 12) If the apparatus has a fire pump, the certification of inspection and test for the fire pump (*see 16.13.1.1.5 or 16.13.1.2.4 as applicable*)
  - 13) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test (*see Section 17.13*)
  - 14) When the apparatus is equipped with a water tank, the certification of water tank capacity (*see Section 18.6*)
  - 15) If the apparatus has an aerial device, the certification of inspection and test for the aerial device (*see Section 19.24*)
  - 16) If the apparatus has an aerial device, all the technical information required for inspections to comply with NFPA 1911
  - 17) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy (*see 20.10.4.2*) and the final installer's certification the foam proportioning system meets this standard (*see 20.11.2*)
  - 18) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests (*see Section 21.9*)
  - 19) If the apparatus has a line voltage power source, the certification of the test for the power source (*see 22.15.7.2*)
  - 20) If the apparatus is equipped with an air system, air tank certificates (*see 24.5.1.2*), the SCBA fill station certification (*see 24.9.6*), and the results of the testing of the air system installation (*see 24.14.5 and 24.15.4*)
  - 21) Any other required manufacturer test data or reports

# Las Vegas Fire & Rescue

## Production Specification

### **OPERATIONS AND SERVICE DOCUMENTATION**

The contractor shall deliver with the fire apparatus complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof.

The contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- 1) Manufacturer's name and address
- 2) Country of manufacture
- 3) Source for service and technical information
- 4) Parts replacement information
- 5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- 6) Wiring diagrams for low voltage and line voltage systems to include the following information:
  - a) Pictorial representations of circuit logic for all electrical components and wiring
  - b) Circuit identification
  - c) Connector pin identification
  - d) Zone location of electrical components
  - e) Safety interlocks
  - f) Alternator–battery power distribution circuits
  - g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- 7) Lubrication charts
- 8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- 9) Precautions related to multiple configurations of aerial devices, if applicable
- 10) Instructions regarding the frequency and procedure for recommended maintenance
- 11) Overall apparatus operating instructions
- 12) Safety considerations
- 13) Limitations of use
- 14) Inspection procedures
- 15) Recommended service procedures
- 16) Troubleshooting guide
- 17) Apparatus body, chassis and other component manufacturer's warranties
- 18) Special data required by this standard
- 19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus
- 20) One copy of the latest edition of FAMA's *Fire Apparatus Safety Guide*

The contractor shall deliver with the apparatus all manufacturer's operations and service documents supplied with components and equipment that are installed or supplied by the contractor.

### **NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE**

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a USB Flash Drive. These manuals shall be divided into sections for ease of reference. There shall be two (2) USB flash drives provided with the completed vehicle.

# Las Vegas Fire & Rescue

## Production Specification

### **STATEMENT OF EXCEPTIONS**

The final-stage manufacturer shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- 21) A separate specification of the section of the applicable standard for which compliance is lacking
  - 1) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
  - 2) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance
  - 3) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to or at the time of delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

### **CARRYING CAPACITY**

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The Body Manufacturer shall establish the estimated in-service weight during the design of the vehicle

The estimated in-service weight shall include the following:

- 4) The chassis, body and tank(s)
  1. Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
  2. Full water and other agent tanks
  3. \*250 lb (114 kg) in each seating position
  4. Fixed equipment such as pumps, aerial devices, generators, reels and air systems as installed
  5. Ground ladders, suction hose, designed hose load in their hose beds and on their reels
  6. An allowance for miscellaneous equipment that is the greatest of the following:
    7. The values shown in Table 12.1.2
    - h) A purchaser-provided list of equipment to be carried with weights
    - i) A purchaser-specified miscellaneous equipment allowance

The manufacturer shall engineer and design the fire apparatus such that the completed apparatus, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

A final manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

# Las Vegas Fire & Rescue

## Production Specification

The label shall show the height of the completed unequipped fire apparatus in feet and inches (meters), the length of the completed fire apparatus in feet and inches (meters), and the GVWR in tons (metric tons).

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

### **TESTING**

#### **ROAD TEST**

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the Body Manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

#### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (-18°C and 43°C).

#### **TEST SEQUENCE**

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for ten (10) minutes. Failure of any of these tests shall require a repeat of the sequence.

# Las Vegas Fire & Rescue

## Production Specification

### **1. RESERVE CAPACITY TEST**

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

### **2. ALTERNATOR PERFORMANCE TEST**

#### **TEST AT IDLE**

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

#### **TEST AT FULL LOAD**

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

### **3. LOW VOLTAGE ALARM TEST**

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

# Las Vegas Fire & Rescue

## Production Specification

### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

#### **DOCUMENTATION**

The manufacturer shall deliver the following with the fire apparatus:

- j) Documentation of the electrical system performance tests
  - 1) A written electrical load analysis, including the following:
    - 2) The nameplate rating of the alternator
      - a) The alternator rating
      - b) Each of the component loads specified that make up the minimum continuous electrical load
      - c) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
      - d) Each individual intermittent electrical load

#### **UL 120/240 VAC CERTIFICATION**

The 120/240 volt electrical system shall be third-party, independent, audit-certified through Underwriters Laboratory (UL) to the current edition of NFPA 1901 to perform as listed below;

The prime mover shall be started from a cold start condition, and the unloaded voltage and frequency shall be recorded.

The line voltage electrical system shall be loaded to at least 100% of the continuous rated wattage stated on the power source specification label. Testing with a resistive load bank shall be permitted.

The power source shall be operated in the manner specified by the apparatus manufacturer as documented on instruction plates or in operation manuals. The power source shall be operated at a minimum of 100% of the continuous rated wattage as stated on the power source specification label for a minimum of two (2) hours.

The load shall be adjusted to maintain the output wattage at or above the continuous rated wattage during the entire 2-hour test.

The following conditions shall be recorded at least every 1/2 hour during the test:

- e) The power source output voltage, frequency and amperes
  - 1) The prime mover's oil pressure, water temperature and transmission temperature, if applicable
  - 2) The power source hydraulic fluid temperature, if applicable
  - 3) The ambient temperature and power source air inlet temperature

The following conditions shall be recorded once during the test for power sources driven by dedicated auxiliary internal combustion engines:

- 4) Altitude
  - 1) Barometric pressure
  - 2) Relative humidity

If the generator is driven by the chassis engine and the generator allows for operation at variable speeds, the chassis engine speed shall be reduced to the lowest rpm allowed for generator operation and the voltage and frequency shall be recorded.

The load shall be removed and the unloaded voltage and frequency shall be recorded.

# Las Vegas Fire & Rescue

## Production Specification

Voltage shall be maintained within  $\pm 10\%$  of the voltage stated on the power source specification label during the entire test. Frequency shall be maintained within  $\pm 3$  Hz of the frequency stated on the power source specification label during the entire test.

The total continuous electrical loads, excluding those loads associated with the equipment defined in NFPA 22.15.7.3.11.2, shall be applied during the testing unless an auxiliary engine drives the power source.

If the apparatus is equipped with a fire pump, the 2-hour certification test of the power source shall be completed with the fire pump pumping at 100% capacity at 150 psi (1000 kPa) net pump pressure. The test shall be permitted to be run concurrently with the pump certification test.

### **DOCUMENTATION**

The Body Manufacturer shall deliver the following with the fire apparatus:

The results of each test shall be recorded on an appropriate form and provided with the delivery of the fire apparatus.

### **DIELECTRIC VOLTAGE WITHSTAND TEST**

The line voltage wiring and permanently connected devices and equipment shall be subjected to a dielectric voltage withstand test of 900 volts for one (1) minute. The testing shall be performed after all body work has been completed.

The test shall be conducted as follows:

- 3) Isolate the power source from the panel board and disconnect any solid state low voltage components
- 1) Connect one lead of the dielectric tester to all the hot and neutral buses tied together
- 2) Connect the other lead to the fire apparatus frame or body
- 3) Close any switches and circuit breakers in the circuit(s)
- 4) Apply the dielectric voltage for one (1) minute in accordance with the testing equipment manufacturer's instructions

The electrical polarity of all permanently wired equipment, cord reels and receptacles shall be tested to verify that wiring connections have been properly made.

Electrical continuity shall be verified from the chassis or body to all line voltage electrical enclosures, light housings, motor housings, light poles, switch boxes and receptacle ground connections that are accessible to fire fighters in normal operations.

If the apparatus is equipped with a transfer switch, it shall be tested to verify operation and that all non grounded conductors are switched.

Electrical light towers, floodlights, motors, fixed appliances and portable generators shall be operated at their full rating or capacity for 30 minutes to ensure proper operation.

# Las Vegas Fire & Rescue

## Production Specification

### **WARRANTY**

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source and will deal directly with the Las Vegas Fire & Rescue on all warranty work.

### **GENERAL LIMITED WARRANTY - TWO (2) YEARS**

The vehicle shall be free of defects in material and workmanship for a period of two (2) years or 36,000 miles (or 57,936 kilometers), whichever occurs first starting thirty (30) days after the original invoice date.

The Contractor must be the "single source" coordinator of all warranties on the vehicle.

### **LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS**

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles (or 96,561 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

### **STRUCTURAL WARRANTY - TEN (10) YEARS**

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

### **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

### **PAINT LIMITED WARRANTY - TEN (10) YEARS**

The body shall be free of bubbling or peeling as a result of a defect in the method of manufacture for a period of ten (10) years or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date. **Pro-rated warranties will not be acceptable.**



# Las Vegas Fire & Rescue

## Production Specification

### **CONSTRUCTION PERIOD**

The completed vehicle shall be delivered within three hundred sixty (360) days after receipt of a purchase order or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to Las Vegas Fire & Rescue as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

### **OVERALL HEIGHT REQUIREMENT**

There is no overall height (OAH) restriction for this vehicle.

### **OVERALL LENGTH REQUIREMENT**

There is no overall length (OAL) restriction for this vehicle.

### **OVERALL WIDTH**

The overall width (OAW) of the body at drip rails shall be 102" (8' - 6"), and body shall be 100" (8' - 4").

### **ANGLE OF APPROACH**

The angle of approach for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

### **ANGLE OF DEPARTURE**

The angle of departure for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

### **PRE-CONSTRUCTION CONFERENCE**

A pre-construction conference shall be required at the Contractor's factory for three (3) personnel from the Las Vegas Fire & Rescue to finalize all construction details prior to manufacturing.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the pre-construction conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

### **PRE-PAINT CONFERENCE**

A pre-paint conference shall be required at the Contractor's factory for three (3) personnel from the Las Vegas Fire & Rescue to inspect the vehicle and construction details prior to the painting process.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the pre-paint conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

# Las Vegas Fire & Rescue

## Production Specification

### **FINAL INSPECTION CONFERENCE**

A final inspection conference shall be required at the Contractor's factory for three (3) personnel from the Las Vegas Fire & Rescue to inspect the vehicle and construction details prior to shipment of the completed vehicle. This inspection shall take place after any specified striping and lettering is installed.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the final inspection conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

### **DELIVERY AND DEMONSTRATION**

The Contractor shall be responsible for the delivery of the completed unit to the Las Vegas Fire & Rescue's location. On initial delivery of the apparatus, the Contractor shall supply a qualified representative to demonstrate the apparatus and provide initial instruction to representatives of the Las Vegas Fire & Rescue regarding the operation, care and maintenance of the apparatus and equipment supplied at Las Vegas Fire & Rescue location.

The Delivery Engineer shall set delivery and instruction schedule with the person appointed by Las Vegas Fire & Rescue.

After delivery of the apparatus, the Las Vegas Fire & Rescue shall be responsible for ongoing training of its personnel to proficiency regarding the proper and safe use of the apparatus and associated equipment.

### **CAB CHASSIS SPECIFICATIONS**

#### **Vehicle Configuration**

M2 106 CONVENTIONAL CHASSIS  
2017 MODEL YEAR SPECIFIED  
SET BACK AXLE - TRUCK

#### **General Service**

RESCUE AND EMERGENCY SERVICE  
MEDIUM TRUCK WARRANTY  
EXPECTED FRONT AXLE LOAD: 12000 lbs  
EXPECTED REAR DRIVE AXLE LOAD: 21000 lbs  
EXPECTED GROSS VEHICLE CAPACITY: 33000 lbs

#### **Engine**

CUM ISB 6.7-360 360 HP @ 2400 RPM, 2600 GOV, 800 LB/FT @ 1800 RPM,  
RESCUE/FIRE/EMERGENCY

#### **Engine Equipment**

2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG17  
NFPA COMPLIANT EMBER SCREEN AND FIRE RETARDANT DONALDSON AIR CLEANER  
LN 12V 320 AMP 4962PA PAD MOUNT ALTERNATOR  
(2) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 2250 CCA THREADED  
STUD BATTERIES WITH POSITIVE JUMP START POST  
BATTERY BOX FRAME MOUNTED  
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN  
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD  
DRIVER

# Las Vegas Fire & Rescue

## Production Specification

CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE  
CUMMINS EXHAUST BRAKE INTEGRAL WITH VARIABLE GEOMETRY TURBO WITH ON/OFF DASH SWITCH  
RH MTD HORIZONTAL AFTERTREATMENT WITH RH TAILPIPE EXITING FORWARD OF REAR TIRES  
HORTON HT650 FRONTAL AIR ON/OFF ENGINE FAN CLUTCH  
AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED  
CUMMINS SPIN ON FUEL FILTER  
FULL FLOW OIL FILTER  
950 SQUARE INCH ALUMINUM RADIATOR  
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT  
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT  
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES  
ELECTRIC GRID AIR INTAKE WARMER  
DELCO 12V 29MT STARTER WITH INTEGRATED MAGNETIC SWITCH

### Transmission

ALLISON 3000 EVS AUTOMATIC TRANSMISSION WITH PTO PROVISION

### Transmission Equipment

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN  
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED  
TRANSMISSION PROGNOSTICS - ENABLED 2013  
WATER TO OIL TRANSMISSION COOLER  
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK  
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

### Front Axle and Equipment

DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE  
BENDIX ADB22X-V AIR DISC FRONT BRAKES  
FRONT DISC BRAKE ROTORS  
FRONT AIR DISC BRAKE INTERNAL ADJUSTERS  
TRW THP-60 POWER STEERING  
2 QUART SEE THROUGH POWER STEERING RESERVOIR

### Front Suspension

12,000# DUAL TAPERLEAF FRONT SUSPENSION  
MAINTENANCE FREE RUBBER BUSHINGS  
FRONT SHOCK ABSORBERS

### Rear Axle and Equipment

DETROIT DA-RS-21.0-4 21,000# R-SERIES SINGLE REAR AXLE  
5.88 REAR AXLE RATIO  
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING  
MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES  
BENDIX ADB22X-V AIR DISC REAR BRAKES  
FIRE AND EMERGENCY SEVERE SERVICE NON-ASBESTOS REAR BRAKE LINING  
AIR DISC LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS

# Las Vegas Fire & Rescue

## Production Specification

REAR AIR DISC BRAKE INTERNAL ADJUSTERS

### Rear Suspension

21,000# 52 INCH VARIABLE RATE MULTI-LEAF SPRING REAR SUSPENSION WITH LEAF SPRING HELPER  
SPRING SUSPENSION - 1.50" AXLE SPACER  
STANDARD AXLE SEATS IN AXLE CLAMP GROUP

### Brake System

AIR BRAKE PACKAGE  
WABCO 4S/4M ABS WITH TRACTION CONTROL & ESC  
STANDARD AIR SYSTEM PRESSURE PROTECTION  
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER  
CUSTOM STEEL AIR BRAKE RESERVOIRS  
BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER - WET TANK

### Electrical Connections

UPGRADED CHASSIS MULTIPLEXING UNIT  
UPGRADED BULKHEAD MULTIPLEXING UNIT

### Wheelbase & Frame

(168 INCH) WHEELBASE / (102 INCH) CA  
11/32X3-1/2X10-15/16 INCH STEEL FRAME 120KSI  
1/4" C-CHANNEL INNER FRAME REINFORCEMENT  
(75 INCH) REAR FRAME OVERHANG

### Chassis Equipment

THREE-PIECE 14 INCH PAINTED STEEL BUMPER WITH COLLAPSIBLE ENDS PAINTED JOB COLOR  
FRONT TOW HOOKS - FRAME MOUNTED  
FENDER & FRONT OF HOOD MTD FRONT MUDFLAPS  
GRADE 8 THREADED HEX HEADED FRAME FASTENERS

### Fuel Tanks

50 GALLON RECTANGULAR ALUMINUM FUEL TANK  
6 GALLON DIESEL EXHAUST FLUID TANK  
ALLIANCE FUEL FILTER/WATER SEPARATOR WITH PRIMER PUMP  
EQUIFLO INBOARD FUEL SYSTEM

### Tires

MICHELIN XZE2 11R22.5 14 PLY RADIAL FRONT TIRES  
MICHELIN XDN2 11R22.5 14 PLY RADIAL REAR TIRES

### Hubs

CONMET PRESET PLUS IRON FRONT HUBS  
CONMET PRESET PLUS IRON REAR HUBS

### Wheels

ALCOA 22.5X8.25 10-HUB PILOT POLISHED ALUMINUM DISC FRONT WHEELS  
ALCOA 22.5X8.25 10-HUB PILOT POLISHED ALUMINUM DISC REAR OUTER WHEELS

# Las Vegas Fire & Rescue

## Production Specification

### Cab Exterior

106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL AIR RIDE CAB  
NFPA COMPLIANT EXTERIOR GRAB HANDLES  
HOOD MOUNTED CHROMED PLASTIC GRILLES  
FIBERGLASS HOOD WITH FIREWALL INSULATION  
DUAL 25 INCH ROUND STUTTER TONE HOOD MOUNTED AIR HORNS WITH SHIELDS  
(1) RH FOOT SWITCH WITH DASH SWITCH FOR HORN BUTTON TO CONTROL AIR HORN,  
DEFAULT TO ELECTRIC <85 PSI  
DUAL ELECTRIC HORNS  
INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZELS AND DAYTIME RUNNING  
LIGHTS  
LED AERODYNAMIC MARKER LIGHTS  
DUAL 102" WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE  
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS  
DUAL LEVEL CAB ENTRY STEPS ON BOTH SIDES  
ELECTRIC HORN WARNING SYSTEM FOR PARK BRAKE NOT SET W/ DOOR OPEN & ALL KEY  
POSITIONS  
63X14 INCH TINTED REAR WINDOW  
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS  
RH/LH ELECTRIC PWRED WINDOWS & DOOR LOCKS  
TINTED WINDSHIELD  
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME  
MOUNTED

### Cab Interior

OPAL GRAY VINYL INTERIOR  
MOLDED PLASTIC DOOR PANELS WITH ALUMINUM KICKPLATES LOWER DOORS  
BLACK MATS WITH PREMIUM INSULATION  
GRAY INSTRUMENT PANELS  
FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS WITHOUT  
NETTING  
IN DASH STORAGE BIN  
(2) CUP HOLDERS LH AND RH DASH  
HEATER, DEFROSTER AND AIR CONDITIONER  
MAIN HVAC CONTROLS W/ RECIRCULATION SWITCH  
STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES AT SUPPLY LINES ONLY  
SOLID-STATE CIRCUIT PROTECTION AND FUSES  
12V NEGATIVE GROUND ELECTRICAL SYSTEM  
DOME LIGHT WITH 3-WAY SWITCH ACTIVATED BY LH AND RH DOORS  
(2) 12 VOLT POWER RECEPTACLES MOUNTED IN DASH  
SEATS INC 911 UNIVERSAL SERIES HIGH BACK AIR SUSPENSION DRIVER SEAT NFPA  
COMPLIANT  
SEATS INC 911 UNIVERSAL SERIES HIGH BACK AIR SUSPENSION PASSENGER SEAT NFPA  
COMPLIANT  
LH AND RH INTEGRAL DOOR PANEL ARMRESTS  
GRAY CORDURA PLUS CLOTH SEAT COVERS  
3 POINT HIGH VISIBILITY ORANGE RETRACTOR DRIVER AND RH FRONT PASSENGER SEAT  
BELTS NFPA COMPLIANT

# Las Vegas Fire & Rescue

## Production Specification

ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN  
4-SPOKE 18 INCH STEERING WHEEL  
DRIVER AND PASSENGER INTERIOR SUN VISORS

### Instruments & Controls

BLACK GAUGE BEZELS  
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM  
2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES  
ENGINE COMPARTMENT MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS  
PRECO 1040 87 DB TO 112 DB AUTOMATIC SELF-ADJUSTING BACKUP ALARM  
ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL  
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED  
FIRE AND EMERGENCY SERVICE VEHICLES ENGINE WARNING  
2 INCH ELECTRIC FUEL GAUGE  
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE  
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE  
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY  
ELECTRIC ENGINE OIL PRESSURE GAUGE  
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE  
ELECTRONIC 3000 RPM TACHOMETER  
IGNITION SWITCH CONTROLLED ENGINE STOP  
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY  
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY  
MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH  
ONE VALVE PARKING BRAKE SYSTEM WITH DASH VALVE  
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE  
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS

### Paint Design

ONE SOLID CUSTOM BASE/CLEAR COAT COLOR  
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

### CAB TO AXLE DIMENSION

Cab to axle will be 87.5".

# Las Vegas Fire & Rescue

## Production Specification

### **CHASSIS MODIFICATIONS**

#### **LUBRICATION AND TIRE DATA PLATE**

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- 5) Engine oil
  - Engine coolant
  - Chassis transmission fluid
  - Pump transmission lubrication fluid . . (if applicable)
  - Pump priming system fluid, if applicable . . (if applicable)
  - Drive axle(s) lubrication fluid
  - Air conditioning refrigerant . . (if applicable)
  - Air conditioning lubrication oil . . (if applicable)
  - Power steering fluid
  - Cab tilt mechanism fluid . . (if applicable)
  - Transfer case fluid . . (if applicable)
  - Equipment rack fluid (if applicable)
  - CAFS air compressor system lubricant . . (if applicable)
  - Generator system lubricant . . (if applicable)
  - Front tire cold pressure
  - Rear tire cold pressure
  - Maximum tire speed ratings

#### **VEHICLE DATA PLATE**

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the;
  - Engine
  - Transmission
  - Air
  - Fuel
- Serial numbers for the;
  - Engine
  - Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

# Las Vegas Fire & Rescue

## Production Specification

### **OVERALL HEIGHT, LENGTH DATA PLATE (US)**

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in feet and inches, the length of the completed fire apparatus in feet and inches, and the GVWR in pounds.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

### **PERSONNEL CAPACITY**

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

### **SEAT BELT WARNING - FAMA06/07**

A safety sign FAMA06 shall be visible from each seat that is not equipped with occupant restraint and therefore not intended to be occupied while the vehicle is in motion.

A safety sign FAMA07, which warns of the importance of seat belt use, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

### **EQUIPMENT MOUNTING FAMA10**

A safety sign FAMA10, which warns of the need to secure items in the cab, shall be visible inside the cab.

### **FIRE SERVICE TIRES - FAMA12**

A safety sign FAMA12, which warns of the special requirements for fire service-rated tires, shall be visible to the driver entering the cab of any apparatus so equipped.

### **HELMET WARNING - FAMA15**

A safety sign FAMA15, which warns not to wear helmets while the vehicle is in motion, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

### **CLIMBING METHOD - FAMA23**

A safety sign FAMA23, which warns of the proper climbing method, shall be visible to personnel entering the cab and at each designated climbing location on the body.

### **REAR STEP CROSSWALK WARNING - FAMA24**

A safety sign FAMA24, which warns personnel not to ride on the vehicle, shall be located at the rear step areas and at any cross walkways.



# Las Vegas Fire & Rescue

## Production Specification

### **FINAL STAGE MANUFACTURER VEHICLE CERTIFICATION**

A final stage manufacturer vehicle certification label shall be provided and installed in the driver cab door jamb area.

### **FRONT BUMPER**

The front bumper shall be as provided by the cab/chassis manufacturer. No other alteration or modifications are required to extension length.

### **BUMPER GRAVELSHIELD**

The bumper extension gravel shield shall be provided by the cab/chassis manufacturer.

### **AIR HORN(S)**

The air horn(s) shall be supplied and installed by the cab/chassis manufacturer.

### **FRONT TOW PROVISIONS**

The front tow provisions shall be supplied and installed by the cab/chassis manufacturer.

### **AIR INTAKE SYSTEM**

An air filter shall be provided in the engine's air intake system by the commercial cab/chassis manufacturer. Air inlet restrictions shall not exceed the engine manufacturer's recommendations.

The air inlet shall be equipped with a means of separating water and burning embers from the air intake system.

This requirement shall be permitted to be achieved by either of the following methods:

- Provision of a device such that burning particulate matter larger than 0.039 in. (1.0 mm) in diameter cannot reach the air filter element.
- 1. Provision of a multi screen ember separator capable of meeting the test requirements defined in the Parker Hannafin, Racor Division, publication LF 1093-90, *Ember Separation Test Procedure*, or an equivalent test.

### **EXHAUST DIVERTER**

An exhaust diverter valve shall be located in-line of exhaust tubing and controlled from driver's position to re-route exhaust discharge. Exhaust diverter valve shall be constructed from 14 gauge stainless steel material with air actuated control.

As a default, the exhaust shall always discharge to curbside just ahead of rear wheels, and when generator is selected the exhaust shall discharge to a vertical exhaust pipe, extending above the body height 12".

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the apparatus or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position.

# Las Vegas Fire & Rescue

## Production Specification

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

### **PLYMOVENT ADAPTER**

There will be a 5" diameter Plymovent adapter and backing plate installed on the apparatus. It will also include the Plymovent wireless trigger to activate upon start-up. (Part # KTX24SS-IG2B-PL, Transmitter, Dual Ignition/Brake 2.4GHZ, Wired female spade lugs, Codes 3515 A01-A09, AOA-AOK E 542B02)

### **BATTERIES**

One (1) of the chassis supplied batteries shall be relocated to a lower body compartment.

Need to relocate one battery to body. Chassis is shipping with three (3) batteries.

### **RADIO ANTENNA INSTALLATION**

There shall be one (1) Laird style 800 MHZ antenna mount provided and installed on the roof of the cab/chassis. The end of radio antenna shall be routed to a location determined by the Las Vegas Fire & Rescue.

### **RADIO/ANTENNA INSTALLATION**

There shall be one (1) Las Vegas Fire & Rescue supplied radio(s) with antenna installed in the cab within easy reach of driver. The location of radio shall be determined by the Las Vegas Fire & Rescue at the pre-construction meeting. All required radio programming shall be responsibility of Las Vegas Fire & Rescue. Radio(s) may not be fully tested if no radio program is provided with radio and will be responsibility of Las Vegas Fire & Rescue after delivery.

Radio shall be installed per Manufacturer's requirements and wired for proper 12 volt power and ground.

### **12 VDC USB, DUAL PORT PLUG**

There shall be one (1) 12 volt dual port USB plug(s) provided and installed in the cab area, wired battery direct. The location of the USB plugs shall be determined by the Las Vegas Fire & Rescue at the pre-construction meeting.

### **KNOX BOX**

There will be one Knox Box KeySecure 4 with WiFi with blue strobe provided and installed on the apparatus.

EVG supply and install

### **12 VOLT POWER POINT**

Three (3) 12 VDC outlets provided in the front face of the console.

Cigarette style

# Las Vegas Fire & Rescue

## Production Specification

### **RADIO CHARGER INSTALLATION**

There will be two FD supplied radio chargers installed in the cab. The location will be determined at the pre-construction meeting.

EVG to install

### **MCT DOCK**

One (1) Havis MCT docking station provided and installed on the apparatus. The model will be a Havis DS-DELL-406-3

EVG supply and install

### **12 VDC FUSE BLOCK**

There shall be one (1) 100 amp Blue Sea Systems ST Series blade type fuse block with screw type terminals for both positive and negative buss with cover provided for distribution of up to six (6) 30 amp, 12 VDC circuits. Fuse block shall be located per required circuits and be protected from damage.

### **CAB DOOR INTERIOR HAZARD LIGHT - TWO DOOR CAB**

There shall be one (1) Whelen OS Series (OSA00FCR) amber surface mounted flashing LED light mounted to the inside of each cab entry door to provide a visual indication to oncoming traffic that the door is open. Each light shall be activated when the door is open.

### **SCBA SEAT AIR PACK BRACKETS**

No SCBA air pack bracket(s) shall be provided in specified commercial cab SCBA seats. Las Vegas Fire & Rescue will provide and install necessary bracket(s) after delivery.

### **SEAT BELT COLOR**

Section 14.1.3.4 of the NFPA 1901 Standards, requires all seat belt webbing in cab to be bright red or bright orange in color, and the buckle portion of the seat belt shall be mounted on a rigid or semi rigid stalk such that the buckle remains positioned in an accessible location.

### **SEAT BELT WEB LENGTH - COMMERCIAL CAB**

Sections 14.1.3.2 and 14.1.3.3 of the NFPA 1901 standards, require the effective seat belt web length for a Type 1 lap belt for pelvic restraint to be a minimum of 60", and a Type 2 pelvic and upper torso restraint-style seat belt assembly to be a minimum of 110".

The chassis seat belt web length as supplied by the commercial chassis manufacturer shall be compliant to NFPA Standards 14.1.3.2 and 14.1.3.3.

# Las Vegas Fire & Rescue

## Production Specification

### **SEAT BELT MONITORING AND VEHICLE DATA RECORDER (VDR) SYSTEMS**

#### **SEAT BELT MONITORING**

A Weldon 6204 series system with Vista IV display shall be provided and installed to allow the driver to know if all persons seated in the vehicle are secured with seat belts before moving the vehicle. Built-in smart seating logic shall detect if the correct sit and buckle sequence is not followed for all seats. System shall also provide an output for an external alarm. Weldon diagnostic port will be located under dash on driver side. System shall include the following features;

#### **VEHICLE DATA RECORDER (VDR)**

The vehicle data recorder shall have the following features;

2. Recorded Data Includes: Vehicle Speed, Acceleration, Deceleration, Engine Speed, Engine Throttle Position, ABS Event, Seat Occupied Status, Seat Belt Status, Master Optical Warning Switch, Park Brake, Service Brake, Time, Date and Engine Hours.
  - Password Protected by the customer
  - Six (6) seat position inputs for occupied and belts buckled. Additional six (6) seat expansion module available.
  - Easily interfaces with V-MUX™ or other multiplexing systems
  - Data is extracted by a standard, mini USB cable

#### **OCCUPANT RESTRAINT INDICATOR**

The occupant restraint indicator shall have the following features;

- Will be displayed on Vista IV panel.
- Supports commercial and custom cab seating layouts; up to 12 seats
- Built-in audible alarm
- Use in conjunction with Vehicle Data Recorder (VDR)

#### **IGNITION KEY**

If the vehicle is specified to have an ignition key it will be attached to steering column or dash with vinyl covered steel cable.

#### **SIX (6) – LED TIRE PRESSURE VISUAL INDICATORS**

Each tire shall be equipped with a VECSAFE heavy duty valve cap (or equal) LED indicator that indicates proper tire pressure. The VECSAFE valve cap is self-calibrating. When the cap is mounted on the valve stem the first time, it will memorize that tire pressure, and can be set to recognize a drop in pressure as little as 4 psi. It can be checked for functionality and battery condition by simply unscrewing the cap. If it is in working condition, it will immediately start blinking.

#### **HELMET STORAGE**

No helmet storage is required in the cab driving area.

# Las Vegas Fire & Rescue

## Production Specification

### **CAB CRASH TEST CERTIFICATION**

A cab crash test certification from the fire apparatus manufacturer shall be provided with the equipment. A copy of this certification shall be included with the bid.

NOTE: There shall be no exception to any portion of the cab integrity certification requirements. Nonconformance shall lead to immediate rejection of bid.

The certification shall state that the cab does meet or exceed the requirements below:

- European Occupant Protection Standard ECE Regulation No. 29.
- 1) SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks.

### **CAB MIRRORS, DRIVER ADJUSTABLE**

Section 14.3.5 of the NFPA 1901 Standards, 2009 edition, requires all primary rear view mirrors used by the driver to be adjustable from the driver's position.

### **CAB STEP COVER AND BATTERY COMPARTMENT**

The stock cab upper and lower entry steps shall be overlaid with 1/8" NFPA compliant aluminum treadplate. There will be a removable panel to access and replace the chassis batteries and a hinged fuel fill access door.

The maximum stepping height shall not exceed 18", with the exception of the ground to first step, which shall not exceed 24" when the vehicle is loaded to its estimated in-service weight. All steps shall have a minimum area of 35 sq in and shall be of such a shape that a 5" diameter disk does not overlap any side when placed on the step, and shall be arranged to provide a t least 8" of clearance between the leading edge of the step and any obstruction. All platforms shall have a minimum depth of 8" from the leading edge of the platform to any obstruction.

The following options will be cut into the step cover:

### **BATTERY CHARGING RECEPTACLE LOCATION**

The specified battery charging receptacle and/or display panel shall be located on front face of specified cab step cover.

### **HUB AND NUT COVERS**

Front and rear wheels shall be provided with stainless steel hub caps and wheel nut covers.

### **MUDFLAPS**

There shall be 1/4" rubber mudflaps provided and installed behind each set of tires to prevent throwing road debris and lower road spray.

# Las Vegas Fire & Rescue

## Production Specification

### **AIR BRAKE SYSTEM QUICK BUILD-UP**

There shall be one (1) Milton male quick connector type air shoreline inlet to provide air to the chassis air tanks from an external source compressed air shoreline hookup in order to maintain full operating air pressure while the vehicle is not running. Air inlet shall be located near driver's door. The female end of the connector shall be supplied by the Las Vegas Fire & Rescue.

The quick buildup system shall provide sufficient air pressure so that the apparatus has no brake drag and is able to stop under the intended operating conditions following the 60-second buildup time.

### **ELECTRIC DOOR LOCK INTERFACE**

Electric door locks shall be provided and interfaced as follows;

- The electric cab door locks shall be provided by the cab/chassis manufacturer.
- The body electric door locks shall be interfaced with the chassis electric door lock system.
- One (1) hidden unlock switch will be located at pre-construction.
- Hidden unlock switch on exterior

### **ROAD EMERGENCY SAFETY KIT**

One (1) set of three (3) dual faced triangular warning flares with fold away base complete with storage case per DOT requirements shall be provided with the completed apparatus.

One (1) 2.5 lb. ABC type vehicle fire extinguisher with bracket per DOT requirements shall be provided and mounted inside cab area.

### **BODY DESIGN**

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the Las Vegas Fire & Rescue to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the Las Vegas Fire & Rescue from such repair and shall NOT be used.

# Las Vegas Fire & Rescue

## Production Specification

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

### **EXTERIOR ALUMINUM BODY**

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 3/16" (.187) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas, No Exceptions.

The front and rear corners of body shall be formed as part of the front or rear body panels. This provides a stronger body corner and finished appearance. The use of extruded corners, or caps will not be acceptable, No Exceptions.

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded and caulked to prevent moisture from entering the compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

# Las Vegas Fire & Rescue

## Production Specification

### **DRIP RAILS**

The body shall have drip rails over the side full height compartments. The drip rails shall be formed into the upper body panels providing a ridged lower panel and a flat upper body panel surface. The use of mechanically fastened, taped or glued on drip rails will not be acceptable, No Exceptions.

### **ROOF CONSTRUCTION**

The roof structure shall be integral with the body sheet metal construction and shall be an all welded assembly. The body roof structure shall be overlaid with not less than 3/16" aluminum 3003H-14 alloy tread plate and welded to roof structure and body sheet metal. All seams in roof material shall be fully and continuously welded to prevent entry of moisture.

There shall be a total of four (4) 2" x 2" x 1/4" 6061-T6 alloy aluminum "C" channels running the length of body, two (2) on each outboard side. These "C" channels shall be used for roof support and in addition shall be used for mounting of any specified reels. This open "C" channel design along with special reel mounting clips allows for a universal location of any specified reels within each compartment.

In between the two (2) center "C" channels running the length of body shall be 2" x 2" x 1/4" 6061-T6 alloy aluminum tubing running in between and welded in place on approximate 16" centers to support roof and/or walkway structure if specified.

A 2" formed radius shall be provided along the body sides and utilized as a wiring trough. The use of aluminum extrusions in this area shall not be acceptable, .

### **BODY SUBFRAME**

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 4" x 1/4" aluminum tubes minimum, the same width as the chassis frame rails. Welded to this tubing shall be cross members of 2" x 4" x 1/4" aluminum. Smaller dimension, lighter gauge tubing or angle material subframe shall not be accepted.

These cross members shall extend the full width of the body to support the compartments. Cross members shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum cross members shall be located on 16" centers, or as necessary to support walkway or heavy equipment.

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.



# Las Vegas Fire & Rescue

## Production Specification

### **BODY MOUNTING**

The body subframe shall be fastened to the chassis frame with a minimum of six (6) spring loaded body mounts. Each mount shall be configured using a two-piece encapsulated slide bracket. The two (2) brackets shall be fabricated of heavy duty 1/4" thick steel and shall have a powder coat finish to prevent any corrosion. Each mounting assembly shall utilize two (2) 3/4" diameter x 6" long grade 8 bolts and two (2) heavy duty springs. The assembly design shall allow the body and subframe to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall eliminate any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement will not be acceptable.

### **10" REAR STEP BUMPER**

The full width rear bumper shall be constructed from 2" x 2" x 1/4" aluminum tubing frame and covered with 3/16" NFPA compliant aluminum tread plate. The bumper shall extend from the rear vertical body panel 10" and provide a rear step with a minimum of 1/2" space at body for water drainage.

The area under the RC1 compartment will have a depth of approximately 3" to allow the operator to be closer to the fill station.

### **REAR TOW EYES**

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below the apparatus body. The tow eyes shall be fabricated from 3/4" thick steel plate and shall have a black powder coat finish.

### **GROUND LIGHTS**

There shall be two (2) OnScene 9" Night Axe LED lights installed below bumper capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting shall be switchable but activated automatically when the vehicle park brake is set.

### **WHEEL WELL EXTERIOR PANEL**

The exterior panel of the body wheel well enclosure shall be constructed from 3/16" smooth aluminum panels.

### **STAINLESS STEEL BODY FENDERS**

The body wheel well openings shall be provided with round radius, polished stainless steel fenderettes. The fenderettes shall be bolted and easily replaceable if damaged. The fenderettes shall be installed using a rubber gasket to reduce buildup of moisture and/or debris.

# Las Vegas Fire & Rescue

## Production Specification

### **WHEEL WELL LINERS**

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will not accumulate dirt or water.

### **SCBA CYLINDER COMPARTMENTS**

There shall be four (4) SCBA cylinder storage compartments located, two (2) on each side of body in the rear wheel well area. Each compartment shall be capable of storing two (2) SCBA cylinders (60 min cylinders). Each compartment shall have a vertically hinged door with a positive catch latch installed and painted primary lower body color. Each compartment shall allow the storage of an SCBA cylinder or a fire extinguisher up to 7-3/4" in diameter and 24" deep. The door shall activate the "Hazard Warning Light" in the cab when not in the closed position.

### **BODY PAINT SPECIFICATIONS**

#### **BODY PAINT PREPARATION**

After the body and components have been fabricated they shall be disassembled so when vehicle is complete there shall be finish paint beneath the removable components. The body shall be removed from chassis during the paint process to insure proper paint coverage. The body and components shall be metal finished as follows to provide a superior substrate for painting.

The exterior (and interior, if painted) body shall undergo a thorough cleaning process starting with a biodegradable phosphoric acid solution to begin the etching process followed by a complete clear water rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the metal surface for greater film adhesion.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

#### **PAINT PROCESS**

The paint process shall follow the strict standards set forth by PPG Industries guidelines. Painters applying PPG products will be PPG Certified Commercial Technicians, and re-certified every two (2) years. The body shall go through the following paint process;

- Clean bare metal with a wax and grease remover using low lint rags.
- 1) Inspect, straighten, and hammer high points, grind all seams, sharp edges, and welds. DA sand entire paintable surfaces using 24-180 grit dry paper. Plastic fill all low spots and DA sand fill areas using 36-180 grit dry paper. Apply pinhole filler and DA sand areas using 80-180 grit dry paper.
- 2) Re-clean bare metal using a wax and grease remover and low lint rags.
- 3) Within 24 hours, a PPG Delfleet® epoxy color primer with proper hardener for corrosion resistance using a pressure pot spray gun and applying 2-5 full wet coats or 1.5-8.0 dry mils max. achieving full hiding and allow to air dry 60 minutes @ 70°F or bake for 45 minutes @ 140°F degree.
- 4) Inspect, putty fill, and dry guild coat entire body surface and DA sand using 180-400 grit dry paper.
- 5) Re-clean bare metal using a wax and grease remover using low lint rags.
- 6) A PPG Delfleet® primer sealer with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 1 full wet coat or 1.0-2.0 dry mils achieving full hiding and allow to flash off in spray booth for minimum of 60 minutes @ 70°F.

# Las Vegas Fire & Rescue

## Production Specification

- 7) A PPG Delfleet® FBCH basecoat (color) with proper hardener and dry additive shall then be sprayed using a pressure pot set @ 45-60 PSI and achieving full hiding or 1.5-2.0 wet mils and allow to flash off in spray booth 45-60 minutes before applying clearcoat.
- 8) A PPG Delfleet® clearcoat with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 2-3 full wet coats or 5.0 wet mils for a uniform gloss and allow to flash off in spray booth 10 minutes and bake for 120-140 minutes @ 125°F (surface temp.).
- 9) After cooling, DA sand heavy orange peel or runs using 1000 grit dry sand paper and final DA sand using 1500-2000 grit dry sand paper. Wipe off all surfaces to remove dust and debris. Buff unit as needed using 3M rubbing compound and a white wool pad and inspect until all sand scratches are removed.
- 10) Polish as needed using 3M Perfect-It-Polish and a black foam pad, repeat as necessary and inspect until all sand scratches are removed.

### **PAINT - ENVIRONMENTAL IMPACT**

The contractor shall meet or exceed all current State (his) regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. PPG Delfleet® Evolution paint shall be free of all heavy metal (lead & chromate) components. Paint emissions from sanding and painting shall be filtered and collected. All paint wastes shall be disposed of in an environmentally safe manner. Solvents used in cleanup operations shall be collected, sent off-site for distillation and returned for reuse.

### **FASTENERS**

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, a Mylar isolation tape, or gasket shall be used to prevent damage to the finish painted surface. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nut-surts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

### **ELECTROLYSIS CORROSION CONTROL**

The vehicle shall be assembled using ECK brand or similar corrosion control compound on all high corrosion potential areas.

ECK protects aluminum and stainless steel against electrolytic reaction, isolates dissimilar metals and gives bedding protection for hardware and fasteners. ECK contains anti-seizing lubricant for threads. ECK is dielectric and perfect for use with electrical connectors.

### **PAINT FINISH - SINGLE COLOR**

The body shall be painted with a single color of PPG Delfleet® Evolution per Las Vegas Fire & Rescue approved paint spray out provided.

A small touch-up bottle of paint shall be provided with completed vehicle.

- 11) Paint Color: Match cab/chassis supplied paint color.

### **BODY UNDERCOATING**

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

# Las Vegas Fire & Rescue

## Production Specification

### **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

### **PAINT WARRANTY**

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle. **Pro-rated warranties will not be acceptable.**

### **COMPARTMENT INTERIOR FINISH**

The compartment interior paintable surfaces shall be prepared and DA sanded using 80 grit dry paper and cleaned with a wax and grease remover.

A Scorpion rubberized spray-on XO2 rubberized coating formulation consisting of ZBG (Zero Biological Growth), Fire Retardant, High Pressure Polyurea Systems shall be applied to the horizontal floors and vertical wall surfaces. Scorpion material shall be gray (match cab color used).

All specified shelves shall also have the same Scorpion finish.

Include shelves and trays added \$2,000.00

### **NFPA REQUIRED REFLECTIVE STRIPE**

The NFPA required reflective striping on all four sides including the rear chevrons shall be furnished and installed by the Dealer or the Las Vegas Fire & Rescue prior to the unit being entered into emergency service. The Manufacturer will NOT be required to furnish or install any material.

Statement of Exception required with this option.

# Las Vegas Fire & Rescue

## Production Specification

### **EXTERIOR COMPARTMENT DOORS**

#### **ROLL-UP DOOR CONSTRUCTION - AMDOR**

The apparatus shall be equipped with Amdor brand exterior roll-up compartment doors. Amdor roll-up doors shall be complete with the following features;

- 1" aluminum double wall slats with continuous ball & socket hinge joint and recessed dual durometer slat seal
- Double wall reinforced bottom panel with stainless steel lift bar latching system
- Bottom panel flange with cut-outs for ease of access with gloved hands
- Reusable slat shoes with positive snap-in securement
- Smooth interior door curtain to prevent equipment hang-ups
- One-piece aluminum door track / side frame, top gutter with non-marring seal
- Non-marring recessed side seals with UV stabilizers to prevent warping
- Dual leg bottom seal, with all wear component material to be Type 6 Nylon
- The door shall be warranted for a period of 36 months from the date of delivery. AMDOR Inc. liability covers the replacement or repair of any component that fails due to defects in material and / or workmanship during the coverage period.

Each shutter door shall decrease the compartment door frame opening approximately 2.00" in width and approximately 5.50" in height for the bottom section of door assembly.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.

#### **- STREETSIDE COMPARTMENT - FRONT (S1)**

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door finish guard shall be provided with the roll-up door.

# Las Vegas Fire & Rescue

## Production Specification

- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
- There shall be three (3) 1,000 lbs. slide-out tray(s) with a SlideMaster structural steel base approximately 94" deep and as wide as the compartment layout or door opening permits, capable of extending out either side of the body located above the level of the chassis frame rails. It shall be vertically adjustable in height. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) Amdor LED Lumabar AY-9250-62, 62" compartment lights, vertically mounted.
- One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.
- The 12 volt electrical distribution panel shall be located in the front compartment above the subframe.

### **STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2)**

The interior useable compartment width shall be approximately 64.0" wide.

The compartment door opening shall be approximately 57.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door finish guard shall be provided with the roll-up door.

# Las Vegas Fire & Rescue

## Production Specification

- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- Two (2) Amdor LED Lumabar AY-9250-22, 22" compartment lights, vertically mounted.
- A Bauer model BP-13H-E3 air compressor with a recharging rate of 13.0 SCFM @ 6,000 PSI shall be provided, Compressor skid shall include 13 HP, 3-phase soft start electric motor, P5 Securus purification system, electronic CO monitor with calibration kit, and fill station inter-connecting harness. Compressor module shall be approximately 53.5" L x 33.5" W x 37.5" H and weigh 700 pounds.
  - A shore power receptacle and electrical circuit shall not be provided for operating compressor system from in-house electrical building system.
- Air storage consisting of two (2) UN/ISO DOT, 510 SCF @ 6,000 PSI, (requires hydraulic pressure or ultrasonic examination test every 10 years) shall be provided on completed vehicle complete with gauges and valves. Each cylinder shall measure 9.4" diameter x 52" long, and weigh 202 lbs.

A label shall be placed on or near the operator's panel that provides the following:

- The original cylinder test date stamped on the cylinders.
- The recommended testing interval.
- Five additional open spaces, appropriately labeled, for the user to enter actual retesting dates.

The manufacturer's test date (month and year) on each air tank shall be current within 12 months of the apparatus delivery date.

Air tanks shall be marked with a label that reads;

"High Pressure 6,000 PSI Breathing Air" or "High Pressure 41,368 kPa Breathing Air."

- There will be a welded reinforcement in the floor area to carry specified DOT cylinders. The mounting of the cylinders will be with adjustable track and powder coated steel band straps to securely hold all cylinders in place.
- The Bauer compressor shall be free from defects in material and workmanship for a period of two (2) years. The foregoing warranty period shall be extended to five (5) years from the date of shipment from Bauer for Customers that are Municipal Fire Departments with respect to the compressor block (breathing air application), provided that such extended warranty period shall only apply to product parts with proof of proper maintenance being completed in accordance with published Bauer factory recommendations. To be eligible for this limited warranty to cover Customer's product, Customer must return a properly completed start-up/warranty registration form to Bauer within ninety (90) days from the date of start-up.
- Training and instruction shall be provided by compressor manufacturer at Las Vegas Fire & Rescue location on proper use of complete air compressor system.

# Las Vegas Fire & Rescue

## Production Specification

- The NFPA required air quality test shall be completed by manufacturer prior to delivery. Complete results of test shall be provided to Las Vegas Fire & Rescue upon delivery.

### **STREETSIDE COMPARTMENT - REAR (S3)**

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) nylon strap shall be provided to assist in closing the door.
- One (1) aluminum drip pan/door finish guard shall be provided with the roll-up door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) bolt-in vertical compartment partition(s) provided dividing the compartment into left and right sides. The vertical partition(s) shall be 3/16" (.188) 3003H-14 alloy smooth aluminum sheet.
- There shall be one (1) SCBA cylinder storage module for 8" OD (maximum) SCBA bottles. The maximum length of the SCBA cylinder shall be 24.75". The module shall have an exterior shell fabricated from 1/8" (.125) 3003H-14 aluminum alloy sheet. The module shall have a 2" slope, front to back to prevent cylinders from sliding out. The SCBA cylinder storage tubing shall be fabricated from PVC pipe to prevent damage or abrasion to cylinders. In addition there shall be rubber matting provided in the base of each storage tube for bottle protection and to prevent slipping.

Brand: \_\_\_\_\_ Diameter: \_\_\_\_\_" (Must be less than 7.625") Length: \_\_\_\_\_" (with valve)

- The SCBA cylinder module shall be capable of storing sixteen (16) SCBA cylinders up to 7.5" diameter.



# Las Vegas Fire & Rescue

## Production Specification

- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- There will be four (4) Fire Department supplied Streamlight Portable Scene Lights mounted to one side of the above tool board. Each light will be wired for 12V charging.
- Two (2) Amdor LED Lumabar AY-9250-62, 62" compartment lights, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

### **CURBSIDE COMPARTMENT - FRONT (C1)**

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door finish guard shall be provided with the roll-up door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize locking in/out slides with the front drawer release to hold the tray in both the extended and closed positions. Tray will be designed to hold the Engel electric cooler.

# Las Vegas Fire & Rescue

## Production Specification

- There shall be three (3) 1,000 lbs. slide-out tray(s) with a SlideMaster structural steel base approximately 94" deep, capable of extending out either side of the body located above the level of the chassis frame rails. It shall be vertically adjustable in height. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- One (1) Engel, model MT80F-U1, 12 VDC/120VAC, refrigerator/freezer. The unit will be a top load chest style unit and mounted on a roll-out tray listed above in the lower compartment area. The refrigerator shall operate from both 12 VDC and 120 VAC power. The dimensions are approximately 32"L x 15"W x 17"D.
- Two (2) Amdor LED Lumabar AY-9250-62, 62" compartment lights, vertically mounted.
- One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.

### **CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C2)**

The interior useable compartment width shall be approximately 64.0" wide.

The compartment door opening shall be approximately 57.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door finish guard shall be provided with the roll-up door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

# Las Vegas Fire & Rescue

## Production Specification

### **COMPARTMENT LAYOUT**

- There shall be one (1) tent and chair storage module for the following equipment;
  - One (1) Las Vegas Fire & Rescue supplied folding tents. Manufacturer, model number and dimensions of the folding table(s) shall be provided during the pre-construction meeting.
    - 1- EZ-Up tent 64" x 9" x 9"
    - 1- Privacy Tent 38" x 8" x 8"
    - 1-Portable Toilette Tent 29" x 20" x 10"
  - Twelve (12) Las Vegas Fire & Rescue supplied folding rehab chairs.
    - Rehab chairs 42" x 8" x 9"
- There shall be four (4) OnScene Solutions Velcro cargo straps provided to secure the stored equipment.
- Two (2) Amdor LED Lumabar AY-9250-22, 22" compartment lights, vertically mounted.
- One (1) 120/240 VAC load center.

### **CURBSIDE COMPARTMENT - REAR (C3)**

The interior useable compartment width shall be approximately 45.0" wide.

The compartment door opening shall be approximately 38.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door finish guard shall be provided with the roll-up door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

# Las Vegas Fire & Rescue

## Production Specification

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be three (3) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- Two (2) Fire Department supplied misting fans (20" x 20" x 20" ea.) will be located in the lower compartment on the floor mounted tray.
- Two (2) Amdor LED Lumabar AY-9250-62, 62" compartment lights, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

### **REAR COMPARTMENT - CENTER (RC1)**

The rear center compartment shall be closed to both side rear compartments.

The rear center compartment shall begin just above the bumper height and be as high as the side compartments, unless specified otherwise. The body sub-frame shall extend at least 20" into the compartment to allow for the spring loaded body mounts.

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

- This compartment shall have vertically hinged box pan style doors fabricated of 1/8" thick smooth aluminum. The inner liner of the door shall be 1/8" thick smooth aluminum with an unpainted finish. The door exterior shall be painted job color.
  - Horizontal hinged lift up
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The hinged door(s) shall have a stainless steel 6" offset bent D-ring handle. A manual key lock and electric lock shall be provided. A gasket shall be placed between handle and door. Door latches shall be a two-point rotary slam, double-catch latch, recessed inside the double panel door with striker plate.
- The hinged door(s) shall have a pneumatic cylinder to hold door in the open and closed positions. Each door shall be capable of being closed without unlatching. Door checks shall be bolted to the compartment door header and the box pan of the door.
- A positive style latch lock will be provided to prevent accidental closer of the door.

Add positive lock to prevent it from accidentally closing

# Las Vegas Fire & Rescue

## Production Specification

- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### **COMPARTMENT LAYOUT**

- There shall be one (1) SCBA cylinder storage module for 8" OD (maximum) SCBA bottles. The maximum length of the SCBA cylinder shall be 24.75". The module shall have an exterior shell fabricated from 1/8" (.125) 3003H-14 aluminum alloy sheet. The module shall have a 2" slope, front to back to prevent cylinders from sliding out. The SCBA cylinder storage tubing shall be fabricated from PVC pipe to prevent damage or abrasion to cylinders. In addition there shall be rubber matting provided in the base of each storage tube for bottle protection and to prevent slipping.  
  
Brand: \_\_\_\_\_ Diameter: \_\_\_\_\_" (Must be less than 7.625") Length: \_\_\_\_\_" (with valve)
- The SCBA cylinder module shall be capable of storing eight (8) SCBA cylinders up to 7.5" diameter.
- One (1) Hannay EFH1514-17-18 high pressure air hose reel(s) shall be provided in this compartment. Reel shall be designed to hold 110% of the capacity needed.
  - Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and shall be marked with a label indicating its function and shall be guarded to prevent accidental operation.
  - A label shall be provided in a visible location adjacent to reel with following information: (1) Utility air or breathing air, (2) Operating pressure, (3) Total hose length, (4) Hose size (ID).
  - The hose reel shall be equipped with 200' of 3/16" Parker 6,000 PSI, high pressure air hose. A molded plastic ball clamp shall be provided on the hose to stop it at the 4-way roller. The hose shall be Gray in color with a red color coded end.
  - The fitting on the end of the high pressure air hose reel shall be a CGA-347 high pressure fitting.
  - The air supply shall be from the mobile breathing air system. A reel shut-off valve, pressure regulator, and 0-6,000 psi gauge shall be provided at the air control panel.
- The air supply shall be from the mobile breathing air system.
- The fairlead roller shall be mounted directly to the reel.
- Two (2) Amdor LED Lumabar AY-9250-62, 62" compartment lights, vertically mounted.
- One (1) Scott RevolveAir filling station shall be provided and installed. Fill station shall be capable of simultaneously filling (2) SCBA's while two (2) SCBA's are being exchanged on the outside of station. The unit comes complete with safety interlocks, safety gauges, charge and bleed valves and pressure regulator for automatic SCBA filling.

# Las Vegas Fire & Rescue

## Production Specification

- A Bauer remote control panel shall be provided near the specified fill station equipped with lower 2-bank cascade control with gauge and fill control valves, upper Bauer compressor control panel with electronic controller, emergency start/stop button, and fault alarm. Panel will be approximately 30" wide x 20" high x 6" deep.

Two (2) bank cascade

- One (1) low pressure air hose gauge, 0-300 psi adjustable regulator, and control shall be provided on front panel with outlet port located on the rear of the fill station.
- The fill station fill whip(s) shall terminate in a high pressure CGA-347 threaded connectors for 4,500 - 5,500 PSI air pack cylinders.

### **PLASTIC FLOOR AND SHELF TILE**

The floor in RC1 around the fill station will be covered with Turtle Tile plastic interlocking grating.

Just RC1 around fill station

- The plastic floor tile shall be black.
- The plastic edge trim shall be black.

### **LOWER SIDE BODY PROTECTION - RUB RAIL**

OnScene Solutions rub rails shall be provided below the compartment door openings on both the streetside and curbside.

The rub rail shall be fabricated from 6063 extruded aluminum, measuring approximately 2-3/4" high x 1-3/8" thick with tapered aluminum end caps. The rub rail shall be bolted to the body using stainless steel bolts and 1-1/2" diameter x 5/8" thick rubber mount isolators to prevent damage to the body.

The rails shall incorporate LED clearance marker lighting recessed into the rail fascia to avoid damage to the light in case of impact. The rub rail shall have an accessory mounting track integrated into the backside of the rail to allow mounting of accessories such as ground lighting.

### **FRONT GRAVEL GUARDS**

Gravel guards shall be provided on front lower body corners. Guards shall be 12" high, extend from behind cab or step and wrap around to the front compartment door opening fabricated from 20 gauge brushed stainless steel.

### **ROOF ACCESS LADDER**

The ladder shall be weld constructed of vertical aluminum extrusion tubing and aluminum grip surface ladder rungs with slip resistant tread grip pattern. It shall be set off from body 8 inches and mounted to body with chrome plated end stanchions bolted to the body with stainless steel bolts. The ladder shall NOT extend above the body roof.

The location shall be on the rear curbside of the apparatus body.

# Las Vegas Fire & Rescue

## Production Specification

### **ROOF ACCESS HANDRAIL**

There shall be one (1) 24" horizontal handrail mounted on top of body to assist in roof access. Handrail shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

### **ROOF ACCESS HATCH COVER**

One (1) roof access hatch cover shall be provided in the roof structure to allow for installation or removal of large equipment into the compartment area. The roof around the hatch opening shall be reinforced as necessary to prevent deflection in the roof area. The hatch cover shall overlap a 2" vertical lip on the body roof to prevent entry of moisture. It shall be sealed with automotive type rubber molding to provide a weather resistant seal.

The hatch cover shall have a lift-up type door hinged on the front side. The door shall be fabricated from 3/16" aluminum treadplate with a pair of pneumatic type cylinders mounted to hold the door in the open position. The door shall be mounted using a full length 14 gauge stainless steel hinge, with 1/4" stainless steel pin. A polyester barrier film gasket shall be placed between the stainless steel hinge and any dissimilar metals as necessary to prevent corrosion.

There will be an additional compressor ventilation hatch within the main service hatch. This hatch will be tied to the compressor controls and will raise the hatch automatically with the start-up of the compressor. This will allow for proper ventilation of the unit when in operation. Additionally the streetside compartment door will be interlocked with the compressor start-up.

Addition ventilation hatch with automatic actuators for ventilation.

### **LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC**

#### General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

#### Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125% of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10%. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

# Las Vegas Fire & Rescue

## Production Specification

### Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage over current protective devices. Such devices shall be readily accessible and protected against heat in excess of the over current device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- SAE J156, *Fusible Links*
- SAE J553, *Circuit Breakers*
- SAE J554, *Electric Fuses (Cartridge Type)*
- 1) SAE J1888, *High Current Time Lag Electric Fuses*
- 2) SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125% of maximum current for which the circuit is protected.

### Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.



# Las Vegas Fire & Rescue

## Production Specification

### Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- 1) The propulsion engine and transmission
- 2) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- 3) The radio(s) at a duty cycle of 10 percent transmit and 90% receive (for calculation and testing purposes, a default value of 5 A continuous)
- 1) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- 2) The minimum optical warning system, where the apparatus is blocking the right-of way
- 3) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- 4) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

### Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

### Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

### Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

# Las Vegas Fire & Rescue

## Production Specification

### **12 VOLT MULTIPLEX CONTROL CENTER**

The apparatus shall be equipped with a Weldon V-MUX multiplexed 12 volt electrical system that will provide complete diagnostic capability, No Exception. The system shall have the capability of delivering multiple signals via a CAN bus, utilizing specifications set forth by SAE J1939. The system shall be node based to maximize stability so that failure of one node does not affect the operation of the other nodes. The system shall use shielded twisted-pair wire for transmission of system function signals. The shielded wire shall provide protection against EMI and RFI noise interruptions.

The multiplex system shall be responsible for providing power management functions as well as load shedding. The warning light system shall be controlled by the multiplex system. The system shall be capable of displaying text and/or graphic messages on a display module. The system shall be based on solid-state technology and shall include self-contained diagnostic indicators.

#### **Outputs:**

The outputs shall perform all the following items without added modules to perform any of the tasks;

1. **Load Shedding:** The system shall have the capability to load shed with 8 levels any output. This means you can specify which outputs (barring NFPA restrictions) you would like load shed. Level 1 12.9v, Level 2 12.5V, Level 3 - 12.1V, Level 4 - 11.7V, Level 5 11.3V, Level 6 10.9V, Level 7 10.5, Level 8 10.1. Unlike conventional load shedding devices you can assign a level to any or all outputs.
2. **Load Sequencing:** The system shall be able to sequence from 0 8 levels any output. With 0 being no delay and 1 being a 1 second delay, 2 being a 2 second delay and so on. Sequencing reduces the amount of voltage spikes and drops on your vehicle, and can help limit damage to your charging system.
3. **Output Device:** The system shall have solid-state output devices. Each solid-state output shall be a MOS-FET (Metal Oxide Semiconductor - Field Effect Transistors); MOS-FETs are solid-state devices with no moving parts to wear out. A typical relay when loaded to spec has a life of 100,000 cycles. The life of a FET is more than *100 times* that of a relay.
4. **Flashing Outputs:** The system shall be able to flash any output in either A or B phase, and logic is used to shut down needed outputs in park, or any one of several combined interlocks. The flash rate can be selected at either 80, 160 or 200 FPM. This means any light can be specified with a multiplex truck with no need to add flashers. Flashing outputs can also be used to warn of problems or other unique idea you may come up with.
5. **PWM:** The modules shall have the ability to PWM at some outputs so that a headlight PWM module is not needed.
6. **Diagnostics:** An output should be able to detect either a short or open circuit. The system should be able report in "real time" a text based message that points the maintenance person to a specific output.

#### **Inputs:**

1. The inputs shall have the ability to switch by a ground or vbatt signal.
2. The inputs shall be filtered for noise suppression via hardware and software so that RF or dirty power will not trick an input into changing its status.

# Las Vegas Fire & Rescue

## Production Specification

### **Auto-Throttle:**

The multiplex system shall be able to perform automatic high idle via a network gateway or by using an existing output on a module to provide the proper signals to an OEM Engine ECU. This task should be handled with existing inputs and outputs.

### **Displays:**

Displays shall be able to provide real time information regarding load shedding and system status, such as network traffic/errors or shorts and open circuits.

### **System Network:**

The multiplex system shall contain a Peer-to-Peer network. A Master Slave Type network is not suitable for this type of unit. A Peer-to-Peer network means that all the modules are equal on the network; a Master is not needed to tell other nodes when to talk, **No Exceptions**.

### **System Reliability:**

The multiplex system shall be able to perform in extreme temperature conditions, from 40° to +85° C (-40° to +185° F.) The system shall be sealed against the environment, moisture, humidity, salt or fluids such as diesel fuel, motor oil or brake fluid. The enclosures shall be rugged to withstand being mounted in various locations or compartments around the vehicle. The modules shall be protected from over voltage and reverse polarity.

### **WELDON CERTIFICATION**

A letter shall be provided with bid submittal that the Contractor has successfully completed the Weldon training requirements for Level 1 of the V-MUX Certified Supplier Program and is authorized to design, build, and service V-MUX electrical systems.

### **MULTIPLEX SYSTEM INTERFACE DISPLAY**

One (1) Weldon V-MUX Vista IV multiplex system interface display(s) with push-button control shall be provided in cab easily accessible to driver and/or passenger. The full-color Vista interface display allows the user to control warning and scene lighting, HVAC controls (when specified), and view on-board diagnostics including service information. This display has a wide operating temperature range, automatic screen switching in response to current conditions, and a sleep mode option to eliminate night glare. The following features shall be included;

- 5) 800 x 480 resolution
- 6) Four video ports
- 7) Flash updates with USB memory stick
  - Display inside and outside temperature (when specified)
  - Automatic climate control (when specified)
  - 100% Configurable (OEM Level)
  - Field re-programmable
  - Peer to peer network
  - On-board diagnostics / service information
  - Colors change to indicate button status
  - Video Ready for: Backup camera, Thermal camera, DVD, GPS...

The V-Mux display shall be located in the cab center console for control of all master and emergency lights.

# Las Vegas Fire & Rescue

## Production Specification

### **CAB CONSOLE**

A center cab console shall be provided between the Driver's and Officer's seats. Console shall be as large as possible and fabricated of 1/8" smooth aluminum. A textured powder coat paint finish shall be provided for durability and finished appearance.

The rear portion of the console shall be provided with open top storage for notebooks or maps. Two (2) adjustable dividers shall be provided in the storage area. The forward portion of console shall be slanted for easy viewing of the V-Mux display screen, and any siren or radio equipment. The area shall be within easy access to both Driver and Officer.

The final design of console shall be determined by the Las Vegas Fire & Rescue at the pre-construction meeting.

### **BATTERY SYSTEM**

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

An onboard battery conditioner or charger or a polarized inlet shall be provided for charging all batteries. Where an onboard conditioner or charger is supplied, the associated line voltage electrical power system shall be installed in accordance with Chapter 22.

One of the following master disconnect switches shall be provided:

- A master body disconnect switch that disconnects all electrical loads not provided by the chassis manufacturer
- A master load disconnect switch that disconnects all electrical loads on the apparatus except the starter

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

# Las Vegas Fire & Rescue

## Production Specification

A green "battery disconnect on" indicator light that is visible from the driver's position shall be provided.

Rechargeable hand lights, radios, and other similar devices shall be permitted to be connected to the electrical system ahead of the master disconnect switch.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within 5 seconds.

### **BATTERY SWITCH**

One (1) battery "On/Off" switch in cab located within easy reach of Driver with green "BATTERY ON" pilot light that is visible from the driver's position shall be provided.

### **BATTERY SOLENOID**

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

### **BATTERY CONDITIONER**

One (1) Blue Sea Battery model 7522 battery conditioner, with 120 VAC input and 12 volt output shall be provided. This system shall monitor the condition of batteries and provide an electrical current at variable rates to overcome battery failure. A display model 7517 will be provided with charge indicator, remote mounted.

### **CHASSIS AIR SHORE PUMP**

One (1) Kussmaul Auto-Pump 091-9-12, 12 VDC, 80 psi air compressor shall be provided and installed to maintain air pressure in chassis air brake system.

### **SHORE POWER INLET**

One (1) Kussmaul 120 VAC, 20 amp Super Auto-Eject shore power inlet(s) shall be provided. The shore power connection shall automatically disengage from vehicle when chassis ignition is engaged.

The protective ground from the shoreline inlet shall be bonded to the vehicle frame.

- The outlet cover shall be yellow.
- 1) The shore power plug shall be located near the Driver door area.

### **ENGINE COMPARTMENT LIGHT**

There shall be one (1) light(s) mounted in the engine compartment with integral switch with a light output of at least 20 candlepower (250 lumens). The engine compartment light(s) shall operate only when the master battery switch is turned "On".

# Las Vegas Fire & Rescue

## Production Specification

### **REAR SCENE LIGHTS (BACK-UP LIGHTS)**

There shall be a switch on the left side rear to convert backup lights and rear step lights to scene lights during night operations. The switch shall be of momentary style and shall be connected to a bi-stable relay, allowing multiple switching locations. The scene/reverse lights shall automatically shut off when the parking brake is disengaged.

### **INTERIOR CAB LIGHT, LED**

Two (2) OnScene Solution model #70152, 10" x 6" x 7/8", 10-30 VDC, surface mount dual red and white LED light(s) with clear lens shall be provided on cab ceiling. Each light shall be individually switched with a high/low intensity setting. In addition light(s) will be capable of a 5 second delay after switching off.

### **CAB SPOTLIGHT**

There shall be one (1) Marinco SPL-12COEM motorized spotlight that operates via a wired dash mount controller and on/off button (SPLR-3).

The is mounted to a pedestal above the lightbar.

Marinco Model SPL-12C.OEM with SPLR-3 hardwire control. Mounted above light bar

### **CHASSIS HEADLIGHT WIG/WAG**

A Whelen PFLASH wig/wag flashing unit shall be provided and wired to the brow lights. The flasher shall shut down when the parking brake is engage for "Blocking Mode".

Whelen PFLASH wired to the brow lights

The lights shall be switched at the Vista display in the cab.

### **CAB HAZARD WARNING LIGHT**

A Whelen 5SR00FR red flashing light, located in the driving compartment, shall be illuminated automatically whenever the vehicles parking brake is not fully engaged and any of the following conditions exist:

- Any passenger or equipment compartment door is not closed.
- Any ladder or equipment rack is not in the stowed position.
- Stabilizer system is not in its stowed position.
- Powered light tower is not stowed.
- Any other device permanently attached to the apparatus is open, extended, or deployed in a manner that is likely to cause damage to the apparatus if the apparatus is moved.

Compartments and equipment meeting all of the following conditions shall be permitted to be exempt from being wired to the hazard light:

- The volume is less than or equal to 4 ft3 (0.1 m3).
- The compartment has an opening less than or equal to 144 in.2 (92,900 mm2).
- The open door does not extend sideways beyond the mirrors or up above the top of the fire apparatus.
- All equipment in the compartment is restrained so that nothing can fall out if the door is open while the apparatus is moving.

# Las Vegas Fire & Rescue

## Production Specification

- Manually raised pole lights with an extension of less than 5 ft (1.5 m).

The hazard light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

Whelen 5SR00FR

An audible alarm shall be provided for the door ajar light.

### **BACK-UP ALARM**

The body manufacturer shall furnish and install one (1) 107 dB(A) electronic back-up alarm. Back-up alarm to actuate automatically when the transmission gear selector is placed in reverse.

### **REAR VIEW CAMERA**

There shall be one (1) ASA Voyager rear observation camera system provided and installed on completed unit. The system shall include one (1) model VCC150 high resolution CCD color camera installed on the rear body.

The camera image shall be displayed on the Weldon Vista screen located within the driver's range of view.

### **TAIL LIGHTS**

Rear body tail lights shall be vertically mounted and located per Federal Motor Vehicle Safety Standards, FMVSS and Canadian Motor Vehicle Safety Standards CMVSS. The following lights shall be furnished;

- Two (2) Federal amber LED QL64Z-ARROW turn signal lights
- Two (2) Federal red LED QL64Z-BTT stop/tail lights
- Two (2) Federal white LED QL64Z-BACKUP back-up lights

Each of the lights above shall be mounted in a QL64MC, chrome finish bezel.

### **MIDSHIP MARKER/TURN SIGNAL**

Two (2) Whelen model T0A00MAR 2" round amber LED midship body clearance marker/turn signal lights shall be provided and installed, one (1) light on each side of the body, in forward wheel well of rear axle. Midship marker/turn lights shall be wired to the headlight circuit of the chassis.

### **MARKER LIGHTS**

The body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) and Canadian Motor Vehicle Safety Standards (CMVSS) regulations. All body clearance lights shall be Truck-Lite Model 18 LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

# Las Vegas Fire & Rescue

## Production Specification

### **CAB STEP LIGHTS / GROUND LIGHTS**

There shall be two (2) OnScene 9" Night Axe LED light(s) installed on the vehicle capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting designed to provide illumination on areas under the driver and crew riding area exits shall be switchable but activated automatically when the exit doors are opened.

### **LICENSE PLATE LIGHT**

One (1) Arrow #437 chrome plated LED license plate light shall be installed on the rear of the body. License plate light shall be wired to the headlight circuit of chassis. A fastener system shall be provided for license plate installation.

### **ELECTRONIC SIREN**

One (1) Federal PA4000, 200 watt electronic siren with standard microphone shall be provided and installed in cab in cab console. Siren power shall be wired through the master warning light switch.

PA4000

### **VIBRATING TONES SOUND DEVICE SYSTEM**

One (1) Federal Rumbler vibrating tones sound device shall be provided. Rumbler shall be connected to specified primary electronic siren amplifier. Siren power shall be wired through the master warning light switch. The speakers for system shall be mounted under front of vehicle and protected from weather or road damage.

### **SIREN ACTIVATION**

There shall be two (2) foot switches provided to activate the siren; one (1) for the driver, and one (1) for the officer. The switches shall be mounted on the floor in a location to prevent accidental activation.

### **SIREN SPEAKER**

Two (2) Cast Products Inc. model SA4311, 100 watt siren speaker shall be provided recessed in the front bumper, one (1) on the streetside and one (1) on the curbside.



# Las Vegas Fire & Rescue

## Production Specification

### **BROW MOUNT FLOODLIGHT(S) - LED**

There shall be two (2) Whelen Pioneer Plus model PFP2 with dual panel Super LED light(s) on front of cab. Light quantity shall be divided equally per side. Lights shall be 12 VDC, 12 amp, 150 watt, with 14,000 useable lumens.

Each light shall be mounted in a PBA0130, 3" adjustment radius with either a straight out, 0 degree or a 15 degree downward angle.

The lights will have the Whelen PFLASH wig wag option.

PFLASH Wig Wag option

The lights shall be switched at the Vista display in the cab.

### **SIDE SCENE LIGHTS - LED**

There shall be four (4) Whelen Pioneer Plus model PFP2 with dual Panel Super LED lights on the upper body sides. Light quantity shall be divided equally per side. Lights shall be 12 VDC, 12 amp, 168 watt, with 16,000 useable lumens.

Each light shall be mounted in PBA203 mounting bracket, semi recessed into the apparatus body with chrome trim ring housing. The light mounts will provide either a straight out, 0 degree or a 15 degree downward angle.

The lights shall be switched at the Vista display in the cab.

### **REAR SCENE LIGHTS - LED**

Two (2) Whelen Pioneer Plus model PFP1 with single panel Super LED lights on the upper rear body, one (1) each side. Lights shall be 12 VDC, 12 amp, 75 watt, with 7,000 useable lumens.

Each light shall be mounted in PBA103 mounting bracket, semi recessed into the apparatus body with chrome trim ring housing. The light mounts will provide either a straight out, 0 degree or a 15 degree downward angle.

The above scene lights shall light to a level of at least 3 fc (30 lx), measured at 25 equally spaced points on a 2.5 ft (750 mm) grid with in a 10 ft x 10 ft (3 m x 3m) square to the rear of vehicle.

The lights shall be switched at the Vista display in the cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

### **SETCOM INTERCOM SYSTEM**

There will be a SetCom 900 Series intercom system provided with the apparatus. The system will include the following:

- 900 Series base system
- Two (2) Liberator wireless headsets with charging wires
- Two (2) NFPA Headset hooks
- One (1) radio interface (Motorola APX6500)

EVG to supply and install

# Las Vegas Fire & Rescue

## Production Specification

### **INTERCOM SYSTEM INSTALLATION**

The above listed intercom system shall be installed in the cab locations as follows;

#### **Front of Cab**

- Driver's      - Mounted above the right shoulder position on ceiling.
- Officer's    - Mounted above the left shoulder position on ceiling.

EVG to install

### **WARNING LIGHT PACKAGE**

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four (4) warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four (4) zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two (2) separate signaling modes during emergency operations. One (1) mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One (1) mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two (2) signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

Steadily burning, non flashing optical sources shall be permitted to be used.

# Las Vegas Fire & Rescue

## Production Specification

### UPPER LEVEL OPTICAL WARNING DEVICES

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

#### ZONE A - FRONT WARNING LIGHTS

There shall be one (1) Federal Signal 60" Navigator reference #1454008323.

The lightbar will have the all clear lens and the following light configuration:

Section 1: Mirror, LED Red/White rotator

Section 2: LED Red, LED Blue

Section 3: Opticom, LED Blue

Section 4: LED Red, LED Blue

Section 5: Mirror, LED Blue/White rotator

All clear lights shall shut down when the parking brake is set to comply with "Blocking" mode requirements as outlined in NFPA 1901.

The lightbar shall be separately switched at the vista display in the cab.

#### ZONE B & D - SIDE WARNING LIGHTS

There shall be four (4) Federal Signal QuadraFlare model QL97SFRB, 9" x 7" split LED red/blue lights provided, two (2) on each side of the apparatus in the upper corners. Each light shall have a clear lens and chrome flange.

The lights shall be switched at the Vista display in the cab.

#### ZONE C - REAR WARNING LIGHTS

There shall be two (2) Federal Signal QuadraFlare model QL97S, 9" x 7" split LED lights provided, one (1) on each side of the apparatus in the upper corners. Each light shall have a clear lens and chrome flange.

One (1) light will be red/amber, and one (1) light will be blue/amber.

1-red/amber & 1-blue/amber

The lights shall be switched at the Vista display in the cab.

# Las Vegas Fire & Rescue

## Production Specification

### LOWER LEVEL OPTICAL WARNING DEVICES

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1600 mm) above level ground.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

### ZONE A - FRONT WARNING LIGHTS

There shall be four (4) Federal MicroPulse Wide Angle LED horizontally mounted lights provided, two (2) on each side. The upper lights shall have a red lens and chrome flange and the lower lights will have blue lens and chrome flanges.

The lights shall be switched at the Vista display in the cab.

### ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

There shall be two (2) Federal MicroPulse 6 MPS600U- red/blue LED lights provided, one (1) on each side. Each light shall have a clear lens and chrome flange.

Lights will be mounted to the side of the hood.

#### PRICE

Federal MicroPulse Wide Red/Blue LED with Chrome Flange Clear Lens

The lights shall be switched at the Vista display in the cab.

### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY WHEELWELL AREA)

There shall be two (2) Federal MicroPulse 6 MPS600U- red/blue LED lights provided, one (1) on each side. Each light shall have a clear lens and chrome flange.

#### PRICE

Federal MicroPulse Wide Red LED with Chrome Flange

The lights shall be switched at the Vista display in the cab.

# Las Vegas Fire & Rescue

## Production Specification

### ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Federal MicroPulse 6 MPS600U- red/blue LED lights provided, one (1) on each side. Each light shall have a clear lens and chrome flange.

MicroPule Red/Blue clear lens

The lights shall be switched at the 12 volt control panel in the cab.

### ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Federal Signal QuadraFlare model QL64XF, 6" x 4" red LED lights provided, one (1) on each side. Each light shall have a chrome flange.

One (1) light will be red, and one (1) light will be blue.

1-red & 1-blue

The lights shall be switched at the Vista display in the cab.

### LINE VOLTAGE ELECTRICAL SYSTEM

#### ONAN PTO GENERATOR

The vehicle shall be equipped with an Onan Protec PTO generator system with a capacity of 20,000 watts at 120/240 VAC, three phase. Current frequency shall be stable at 60 hertz.

The transmission's PTO port and PTO, or the split shaft PTO, and all associated drive shaft components shall be rated to support the continuous duty torque requirements of the generator's continuous duty rating as stated on the power source nameplate.

Where the generator is driven by the chassis engine and transmission through a split shaft PTO, the driving compartment speedometer shall register when the generator drive system is engaged.

Where the generator is driven by the chassis engine and transmission through a split shaft PTO and a chassis transmission retarder is furnished, it shall be automatically disengaged for generator operations.

The direct drive generator shall be mounted so that it does not change the ramp break-over angle, angle of departure, or angle of approach as defined by other components, and it shall not extend into the ground clearance area.

The direct drive generator shall be mounted away from exhaust and muffler areas or provided with a heat shield to reduce operating temperatures in the generator area.

# Las Vegas Fire & Rescue

## Production Specification

### **GENERATOR BONDING**

A minimum of four (4) 16" x 2 gauge copper ground straps shall be bolted to body sub-frame and chassis sub-frame for proper bonding of high voltage system. The conductor shall have a minimum amperage rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated amperage on the power source specification label.

### **GENERATOR ENGAGEMENT**

A "Generator Engaged" indicator shall be provided in the driving compartment to indicate that the generator shift has been successfully completed.

An "OK to Operate Generator" indicator shall be provided in the driving compartment to indicate that the generator is engaged (if not always engaged), the transmission is in the proper gear (if required, automatic transmissions only), and the parking brake is engaged (if applicable).

An interlock system shall be provided to prevent advancement of the engine speed in the driving compartment or at any operator's panel unless the parking brake is engaged, and the transmission is in neutral or the output of the transmission is correctly connected to a pump or generator instead of the drive wheels.

### **WARRANTY PERIOD**

Provided such goods are operated and maintained in accordance with Onan's written instructions, Onan warrants that the Protec YDCR series PTO generators shall be free from defects in material and workmanship for a period of five (5) years or one thousand (1,000) hours, whichever comes first, from the date of delivery to the first purchaser.

### **GENERATOR SPLASH GUARD**

A powder coat painted splash cover shall be installed to reduce the amount of road spray on the frame mounted PTO generator. A V-ring seal shall also be installed in the cover to provide additional protection against contaminants reaching the generator front seals.

The generator shall be engaged at the driver's Vista display in the cab.

### **GENERATOR MOUNTING**

The generator shall be mounted between the chassis frame rails. The generator mounting brackets shall be fabricated using heavy duty steel tubing, or structural channel. The generator mounting shall be bolted and removable so that the generator can be lowered from under apparatus for service, if necessary. The generator case shall not extend below the bottom edge of the apparatus body.

### **MANUALS AND SCHEMATICS**

Two (2) complete manuals on parts list, maintenance, wiring schematics, hydraulic schematics, circuit boards, voltage regulator board and other components shall be provided on delivery.

# Las Vegas Fire & Rescue

## Production Specification

### **POWER-TAKE-OFF GENERATOR DRIVE**

There shall be a "Hot Shift" power-take-off (PTO) installed on the transmission PTO opening of the chassis. The "Hot Shift" PTO is provided to allow the engagement of the PTO at higher engine RPM speeds. The PTO output shall be connected to the generator through hollow tube type driveline with heavy duty universals.

The engagement of the PTO shall be in the chassis cab with a rocker switch and red pilot light to note engagement of the PTO or via the V-Mux screen if so equipped.

The power supply to the PTO engagement control shall be wired to the parking brake and a neutral position transmission switch to prevent engagement unless the vehicle is stopped and transmission has been placed in neutral.

The installation of the engine, transmission, driven accessories (power takeoffs (PTO), etc.) shall meet the engine and transmission manufacturers' installation recommendations for the service intended.

Model part number shall be Chelsea 280GKFJP-B5XV, 164% Ratio.

Double check the model number and ratio with engineering before ordering the PTO on the chassis.

### **ENGINE SPEED CONTROL**

The apparatus shall be equipped with an InPower ETM, Electronic Throttle Module to maintain a stable cycle output from generator.

An interlock shall prevent the operation of the engine speed auxiliary control device unless the parking brake is engaged and the transmission is in neutral or park, or the parking brake is engaged and the engine is disengaged from the drive wheels.

The engine shall be prevented from regulating its own engine speed during times when engine rpm control is critical for consistent apparatus functions such as generator, water pump, or aerial operation.

### **LOADCENTER**

The load center shall be a Cutler Hammer, BR Series, specifically designed for protection and distribution of 120/240 volt AC, such as lighting and small motor branch circuits. The load center enclosure shall be made of 16 gauge galvanized sheet steel. The galvanized coating provides corrosion protection and as such does not require paint. All trims used on the BR Load center shall be chromate sealed and finished with electro disposition epoxy paint (ASA61) which exceeds requirements for outdoor and indoor applications. A combination surface/flush cover with integral door shall be supplied.

The load center shall be UL / CSA listed, **NO EXCEPTIONS** will be allowed.

# Las Vegas Fire & Rescue

## Production Specification

### **GENERATOR MONITORING PANEL**

To properly monitor the generator performance and load demand during operation, the generator installation shall be equipped with a full instrument monitor panel.

- Generator frequency in hertz
- Line voltage, phase to neutral or phase to phase, in volts
- Line current in amperes

Individual line current and voltage shall be displayed at the push of a button.

The program shall support the accumulation of elapsed generator hours. Generator hours shall be displayed.

### **SHORE POWER INLET - BATTERY CHARGER**

The above mentioned shore power inlet, and battery conditioner shall be specified in the 12 volt section.

### **OUTLETS AND CIRCUITS**

The generator and or shore power shall supply the 120/240 volt electrical equipment and outlets outlined below. Proper circuit protection shall be installed as noted:

- Two (2) 120 volt exterior outlets, one (1) each side near rear wheel well area.
  - The outlet receptacle(s) shall be 20 amp, twist-lock (NEMA L5-20R).

### **LINE VOLTAGE ELECTRICAL SYSTEM**

#### **GENERAL REQUIREMENTS**

##### Stability

Any fixed line voltage power source producing alternating current (ac) shall produce electric power at 60 Hz,  $\pm 3$  Hz when producing power at all levels between no load and full rated power. Any fixed line voltage power source shall produce electric power at the rated voltage  $\pm 10$  percent when producing power at all levels between no load and full rated power.

The maximum voltage supplied to portable equipment shall not exceed 275 volts to ground. Higher voltage shall be permitted only when used to operate fixed wired, permanently mounted equipment on the apparatus.

##### Conformance with National Electrical Code

All components, equipment, and installation procedures shall conform to *NFPA 70, National Electrical Code*, except where superseded by the requirements of this chapter. Where the requirements of this chapter differ from those in *NFPA 70*, the requirements in this chapter shall apply.

Where available, line voltage electrical system equipment and materials included on the apparatus shall be listed and used only in the manner for which they have been listed. All equipment and materials shall be installed in accordance with the manufacturer's instructions.



# Las Vegas Fire & Rescue

## Production Specification

### Location Ratings

Any equipment used in a dry location shall be listed for dry locations. Any equipment used in a wet location shall be listed for wet locations.

Any equipment, except a PTO-driven generator, used in an underbody or under chassis location that is subject to road spray shall be either listed as Type 4 or mounted in an enclosure that is listed as Type 4.

If a PTO-driven generator is located in an underbody or under chassis location, the installation shall include a shield to prevent road spray from splashing directly on the generator.

### Grounding

Grounding shall be in accordance with 250.34(A) and 250.34(B) of *NFPA 70*. Ungrounded systems shall not be used.

Only stranded or braided copper conductors shall be used for grounding and bonding.

The grounded current-carrying conductor (neutral) shall be insulated from the equipment-grounding conductors and from the equipment enclosures and other grounded parts.

The neutral conductor shall be colored white or gray in accordance with 200.6, "Means of Identifying Grounded Conductors," of *NFPA 70*.

Any bonding screws, straps, or buses in the distribution panel board or in other system components between the neutral and equipment-grounding conductor shall be removed and discarded.

### Bonding

The neutral conductor of the power source shall be bonded to the vehicle frame. The neutral bonding connection shall occur only at the power source. In addition to the bonding required for the low voltage return current, each body and each driving or crew compartment enclosure shall be bonded to the vehicle frame by a copper conductor.

The conductor shall have a minimum ampere rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated ampere on the power source specification label.

A single conductor that is sized to meet the low voltage and line voltage requirements shall be permitted to be used.

### Ground Fault Circuit Interrupters

In special service vehicles incorporating a lavatory, sink, toilet, shower, or tub, 120 V, 15 or 20 A receptacles within 6 ft (1.8 m) of these fixtures shall have ground fault circuit interrupter (GFCI) protection. GFCIs integrated into outlets or circuit breakers or as stand-alone devices shall be permitted to be used in situations.

# Las Vegas Fire & Rescue

## Production Specification

### Power Source General Requirements

All power source system mechanical and electrical components shall be sized to support the continuous duty nameplate rating of the power source.

The power source shall be shielded from contamination that would prevent the power source from operating within its design specifications.

### Power Source Rating

For power sources of 8 kW or larger, the power source manufacturer shall declare the continuous duty rating that the power source can provide when installed on fire apparatus according to the manufacturer's instructions and run at 120°F (49°C) air intake temperature at 2000 ft (600 m) above sea level.

The rating on the power source specification label shall not exceed the declared rating from the power source manufacturer.

Access shall be provided to permit both routine maintenance and removal of the power source for major servicing. The power source shall be located such that neither it nor its mounting brackets interfere with the routine maintenance of the fire apparatus.

### Instrumentation

If the power source is rated at less than 3 kW, a "Power On" indicator shall be provided. If the power source is rated at 3 kW or more but less than 8 kW, a voltmeter shall be provided.

If the power source is rated at 8 kW or more, the following instrumentation shall be provided at an operator's panel:

- Voltmeter
- Current meters for each ungrounded leg
- Frequency (Hz) meter
- Power source hour meter

The instrumentation shall be permanently mounted at an operator's panel. The instruments shall be located in a plane facing the operator. Gauges, switches, or other instruments on this panel shall each have a label to indicate their function.

The instruments and other line voltage equipment and controls shall be protected from mechanical damage and not obstructed by tool mounting or equipment storage.

An instruction plate(s) that provides the operator with the essential power source operating instructions, including the power-up and power-down sequence, shall be permanently attached to the apparatus at any point where such operations can take place.

### Operation

Provisions shall be made for placing the generator drive system in operation using controls and switches that are identified and within convenient reach of the operator.

Where the generator is driven by the chassis engine and engine compression brakes or engine exhaust brakes are furnished, they shall be automatically disengaged for generator operations.

# Las Vegas Fire & Rescue

## Production Specification

Any control device used in the generator system power train between the engine and the generator shall be equipped with a means to prevent unintentional movement of the control device from its set position in the power generation mode.

If there is permanent wiring on the apparatus that is designed to be connected to the power source, a power source specification label that is permanently attached to the apparatus at the operator's control station shall provide the operator with the information required.

The power source, at any load, shall not produce a noise level that exceeds 90 dBA in any driving compartment, crew compartment, or onboard command area with windows and doors closed or at any operator's station on the apparatus.

### Power Supply Assembly

The conductors used in the power supply assembly between the output terminals of the power source and the main over current protection device shall not exceed 12 ft (4 m) in length.

All power supply assembly conductors, including neutral and grounding conductors, shall have an equivalent ampere rating and shall be sized to carry not less than 115 percent of the ampere rating of the nameplate current rating of the power source.

If the power supply assembly connects to the vibrating part of a generator (not a connection on the base), the conductors shall be flexible cord or other fine-stranded conductors enclosed in metallic or nonmetallic liquid tight flexible conduit rated for wet locations and temperatures not less than 194°F (90°C).

### Over-current Protection

Manually re-settable over current devices shall be installed to protect the line voltage electrical system components.

### Power Source Protection

A main over current protection device shall be provided that is either incorporated in the power source or connected to the power source by a power supply assembly.

The size of the main over current protection device shall not exceed 100 percent of the rated ampereage stated on the power source specification label or the rating of the next larger available size over current protection device, where so recommended by the power source manufacturer.

If the main over current protection device is subject to road spray, the unit shall be housed in a Type 4-rated enclosure.

### Branch Circuit Over-current Protection

Over current protection devices shall be provided for each individual circuit and shall be sized at not less than 15 amps in accordance with 240.4, "Protection of Conductors," of *NFPA 70*.

Any panel board shall have a main breaker where the panel has six or more individual branch circuits or the power source is rated 8 kW or larger.

Each over current protection device shall be marked with a label to identify the function of the circuit it protects.

# Las Vegas Fire & Rescue

## Production Specification

Dedicated circuits shall be provided for any large appliance or device (air conditioning units, large motors, etc.) that requires 60 percent or more of the rated capacity of the circuit to which it is connected, and that circuit shall serve no other purpose.

### Panelboards

All fixed power sources shall be hardwired to a permanently mounted panel board unless one of the following conditions exists:

- All line voltage power connections are made through receptacles on the power source and the receptacles are protected by integrated over current devices.
- Only one circuit is hardwired to the power source, which is protected by an integrated over current device.

The panel shall be visible and located so that there is unimpeded access to the panel board controls. All panel boards shall be designed for use in their intended location. The panel(s) shall be protected from mechanical damage, tool mounting, and equipment storage.

Where the power source is 120/240 V and 120 V loads are connected, the apparatus manufacturer or line voltage system installer shall consider load balancing to the extent that it is possible.

### Wiring Methods

Fixed wiring systems shall be limited to the following:

- 1) Metallic or nonmetallic liquid tight flexible conduit rated at temperatures not less than 194°F (90°C) with stranded copper wire rated for wet locations and temperatures not less than 194°F (90°C)
- 1) Type SOW, SOOW, SEOW, or SEOOW flexible cord rated at 600 V and at temperatures not less than 194°F (90°C)

Electrical cord or conduit shall not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring and shall be arranged as follows:

- 2) Separated by a minimum distance of 12 in. (300 mm) from exhaust piping or shielded from such piping
- 1) Separated from fuel lines by a minimum distance of 6 in. (150 mm)

A means shall be provided to allow "flexing" between the driving and crew compartment, the body, and other areas or equipment whose movement would stress the wiring.

Electrical cord or conduit shall be supported within 6 in. (150 mm) of any junction box and at a minimum of every 24 in. (600 mm) of run.

Supports shall be made of nonmetallic materials or of corrosion-resistant or corrosion-protected metal. All supports shall be of a design that does not cut or abrade the conduit or cord and shall be mechanically fastened to the apparatus.

Only fittings and components listed for the type of cord or conduit being installed shall be used.

Splices shall be made only in a listed junction box.

# Las Vegas Fire & Rescue

## Production Specification

### Additional Requirements for Flexible Cord Installations

Where flexible cord is used in any location where it could be damaged, it shall be protected by installation in conduit, enclosures, or guards.

Where flexible cord penetrates a metal surface, rubber or plastic grommets or bushings shall be installed.

### Wiring Identification

Each line voltage circuit originating from the main panel board shall be identified.

The wire or circuit identification either shall reference a wiring diagram or wire list or shall indicate the final termination point of the circuit.

Where pre-wiring for future power sources or devices exists, the un-terminated ends shall be marked with a label showing their wire size and intended function.

### Wiring System Components

Only stranded copper conductors with an insulation rated for temperatures of at least 194°F (90°C) and wet locations shall be used. Conductors in flexible cord shall be sized in accordance with Table 400.5(A) of *NFPA 70*. Conductors used in conduit shall be sized in accordance with 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*. Aluminum or copper-clad aluminum conductors shall not be used.

All boxes shall conform to and be mounted in accordance with Article 314, "Outlet, Device, Pull, and Junction Boxes; Conduit Bodies; Fittings; and Manholes," of *NFPA 70*. All boxes shall be accessible using ordinary hand tools. Boxes shall not be permitted behind welded or pop-riveted panels.

The maximum number of conductors permitted in any box shall be in accordance with 314.16, "Number of Conductors in Outlet, Device, and Junction Boxes, and Conduit Bodies," of *NFPA 70*.

All wiring connections and terminations shall provide a positive mechanical and electrical connection. Connectors shall be installed in accordance with the manufacturer's instructions. Wire nuts or insulation displacement and insulation piercing connectors shall not be used.

Each switch shall indicate the position of its contact points (i.e., open or closed) and shall be rated for the continuous operation of the load being controlled. All switches shall be marked with a label indicating the function of the switch. Circuit breakers used as switches shall be "switch rated" (SWD) or better. Switches shall simultaneously open all associated line voltage conductors. Switching of the neutral conductor alone shall not be permitted.

Line voltage circuits controlled by low voltage circuits shall be wired through properly rated relays in listed enclosures that control all non-grounded current-carrying conductors.

# Las Vegas Fire & Rescue

## Production Specification

### Receptacles and Inlet Devices

#### Wet and Dry Locations

All wet location receptacle outlets and inlet devices, including those on hardwired, remote power distribution boxes, shall be of the grounding type, provided with a wet location cover, and installed in accordance with Section 406.8, "Receptacles in Damp or Wet Locations," of *NFPA 70*.

All receptacles located in a wet location shall be not less than 24 in. (600 mm) from the ground. Receptacles on off road fire apparatus shall be a minimum of 30 in. (750 mm) from the ground. All receptacles located in a dry location shall be of the grounding type and shall be at least 12 in. (300 mm) above the interior floor height. No receptacle shall be installed in a face-up position.

The face of any wet location receptacle shall be installed in a plane from vertical to not more than 45 degrees off vertical.

#### Receptacle Label

Each receptacle shall be marked with a label indicating the nominal line voltage (120 volts or 240 volts) and the current rating in amps of the circuit. If the receptacle is DC or other than single phase, that information shall also be marked on the label.

All receptacles and electrical inlet devices shall be listed to UL 498, *Standard for Safety Attachment Plugs and Receptacles*, or other recognized performance standards.

Receptacles used for DC voltages shall be rated for DC service.

#### Wiring Schematics

An "As-Built" Wiring diagrams for line voltage systems shall be provided to include the following information;

- 2) Pictorial representations of circuit logic for all electrical components and wiring
- 1) Circuit identification
- 2) Connector pin identification
- (a) Zone location of electrical components
- (b) Safety interlocks
- (c) Alternator–battery power distribution circuits
- (d) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems

# Las Vegas Fire & Rescue

## Production Specification

### **EQUIPMENT PAYLOAD WEIGHT ALLOWANCE**

In compliance with NFPA 1901 standards, the special service vehicle shall be designed for an equipment loading allowance of 4,000 lbs. of Las Vegas Fire & Rescue provided equipment based on a 30,001 - 40,000 pound gross vehicle weight rating.

### **EQUIPMENT**

The following equipment shall be furnished with the completed special service vehicle;

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- There shall be two (2) Zico SAC-44-E NFPA approved folding aluminum wheel chocks provided for 44" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20 % grade, with the transmission in neutral, and the parking brake released.
  - The wheel chock(s) shall be mounted behind rear wheels, below body on streetside.
- Two (2) Streamlight Survivor, C4 LED flashlight(s) shall be provided with 140 lumens, and 3.5/14 hour run time. Each flashlight shall be orange in color and have a 12 volt DC charger and vehicle mount kit. Each flashlight shall have an LED spotlight style bulbs and reflectors. The flashlight(s) shall be wired to battery direct unless otherwise specified by Las Vegas Fire & Rescue.
  - The flashlight(s) shall be mounted on the completed unit in the lower area of compartment S1.
- Four (4) Streamlight 4670 Portable Scene Lights and located as listed in the body section.

EVG Supply

### **REMAINING NFPA MINOR EQUIPMENT BY PURCHASER**

All other minor equipment not specified above, but required by NFPA 1901 for special service vehicles, section 10.9.3 shall be supplied and mounted by Las Vegas Fire & Rescue before the unit is placed in emergency service.