

# LAKE DILLON FIRE-RESCUE

Lake Dillon, Colorado

Type III Pumper, SVI #1043

## PRODUCTION SPECIFICATION

Contract Administrator; Bill Wood

Sales Administrator; Bob Sorensen



**ROCK SOLID QUALITY**

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **LIABILITY INSURANCE**

The manufacturer shall furnish with the bid a certificate of insurance for;

Workman's Compensation and Employer's Liability Insurance covering for all employees.

General Liability (each occurrence) of \$1,000,000.00. General Aggregate coverage of \$2,000,000.00. Products Completed / Operations Aggregate coverage of \$2,000,000.00. Medical Expense coverage of \$5,000 (any one person). Personal Injury of \$1,000,000.00.

Automobile liability of \$1,000,000.00 combined single limit (each accident), including any auto, all owned autos, scheduled autos, hired autos, non-owned autos, and garage liability.

Excess Umbrella Liability coverage of \$4,000,000.00 each occurrence, Aggregate of \$4,000,000.00.  
Garage Keepers Liability coverage of \$4,000,000.00 combined limit.

All insurance policies must be;

- Maintained for the life of the contract,
- Must provide ten (10) days notice before cancellation,
- Must cover all operations of the contractor, or anyone employed by them.

## **INTERNET IN-PROCESS SITE**

The manufacturer shall post and maintain a website where the Lake Dillon Fire-Rescue will be able to view digital images of their apparatus as its being built. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of unit.

## **VEHICLE STABILITY SUPPLIED WITH CAB/CHASSIS**

The cab/chassis shall be equipped with a stability control system. The system shall have, at a minimum, a steering wheel position sensor, a vehicle yaw sensor, a lateral accelerometer and individual wheel brake controls.

## **FIRE APPARATUS PERFORMANCE**

The fire apparatus shall meet the requirements of this standard at elevations of 2000 ft (600 m) above sea level.

The fire apparatus shall meet all the requirements of this standard while stationary on a grade of 10 percent in any direction.

The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C).

## **ROADABILITY**

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- 1) From a standing start, the apparatus shall be able to attain a speed of 35 mph (55 km/hr) within 25 seconds on a level road.
- 2) The apparatus shall be able to attain a minimum top speed of 50 mph (80 km/hr) on a level road.
- 3) The apparatus shall be able to maintain a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

The maximum top speed of fire apparatus with a GVWR over 33,000 lb (11,800 kg) shall not exceed 68 mph (105 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal ( 4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (85 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

The vehicle shall be capable of maneuvering across a 20 percent grade and up and down a 25 percent grade.

### **SERVICEABILITY**

The fire apparatus shall be designed to allow the manufacturer's recommended routine maintenance checks of lubricant and fluid levels to be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

### **WILDLAND DOCUMENTATION**

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

1. The manufacturer's record of apparatus construction details, including the following information:
  - (a) Owner's name and address
  - (b) Apparatus manufacturer, model, and serial number
  - (c) Chassis make, model, and serial number
  - (d) GAWR of front and rear axles and GVWR
  - (e) Front tire size and total rated capacity in pounds (kilograms)
  - (f) Rear tire size and total rated capacity in pounds (kilograms)
  - (g) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
  - (h) For each engine: make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
  - (i) Type of fuel and fuel tank capacity
  - (j) Electrical system voltage and alternator output in amps
  - (k) Battery make, model, and capacity in cold cranking amps (CCA)
  - (l) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
  - (m) Ratios of all driving axles
  - (n) Maximum governed road speed
  - (o) For each pump: make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
  - (p) For each pump transmission: make, model, serial number, and gear ratio
  - (q) Reserved
  - (r) Water tank certified capacity in gallons or liters
  - (s) Reserved
  - (t) Paint manufacturer and paint number(s)
  - (u) Company name and signature of responsible company representative

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

- (v) Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall fire apparatus (with water tank full but without personnel, equipment, and hose)
- 2. Certification of compliance of the optical warning system
- 3. Siren manufacturer's certification of siren
- 4. Written load analysis and results of the electrical system performance tests
- 5. Certification of slip resistance of all stepping, standing, and walking surfaces
- 6. The wildland fire pump manufacturer's certification of suction capability
- 7. If special conditions are specified by the purchaser of the wildland fire pump, the pump manufacturer's certification of suction capacity under the special conditions
- 8. A copy of the apparatus manufacturer's approval for stationary pumping applications of the wildland fire pump
- 9. For each pump, the pump manufacturer's certification of the hydrostatic test
- 10. For each pump, the certification of inspection and test for the pump
- 11. The certification of water tank capacity
- 12. If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy and the final installer's certification that the foam proportioning system meets this standard
- 13. If the system has a CAFS, the documentation of the manufacturer's pre delivery tests
- 14. If the apparatus has a line voltage power source, the certification of the test for the power source (*see NFPA 1901, Standard for Automotive Fire Apparatus, 22.15.7.2*)
- 15. If the apparatus is equipped with an air system, air tank certificates (*see NFPA 1901, 24.5.1.2*), the SCBAfill station certification (*see NFPA 1901, 24.9.7*), and the results of the testing of the air system installation (*see NFPA 1901, 24.14.5 and NFPA 1901, 24.15.4*)
- 16. Certification of vehicle side slope stability, including the weight distribution assumed for the calculations or as loaded on the vehicle for the tilt table test
- 17. Any other required manufacturer test data or reports

### **OPERATIONS AND SERVICE DOCUMENTATION**

The contractor shall deliver with the fire apparatus complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof.

The contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- 1) Manufacturer's name and address
- 2) Country of manufacture
- 3) Source for service and technical information
- 4) Parts replacement information
- 5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- 6) Wiring diagrams for low voltage and line voltage systems to include the following information:
  - a) Pictorial representations of circuit logic for all electrical components and wiring
  - b) Circuit identification
  - c) Connector pin identification
  - d) Zone location of electrical components
  - e) Safety interlocks
  - f) Alternator–battery power distribution circuits
  - g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- 7) Lubrication charts
- 8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- 9) Precautions related to multiple configurations of aerial devices, if applicable

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

- 10) Instructions regarding the frequency and procedure for recommended maintenance
- 11) Overall apparatus operating instructions
- 12) Safety considerations
- 13) Limitations of use
- 14) Inspection procedures
- 15) Recommended service procedures
- 16) Troubleshooting guide
- 17) Apparatus body, chassis and other component manufacturer's warranties
- 18) Special data required by this standard
- 19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus
- 20) One copy of the latest edition of FAMA's *Fire Apparatus Safety Guide*

The contractor shall deliver with the apparatus all manufacturer's operations and service documents supplied with components and equipment that are installed or supplied by the contractor.

### **NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE**

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a USB Flash Drive. These manuals shall be divided into sections for ease of reference. There shall be two (2) USB flash drives provided with the completed vehicle.

### **FIRE APPARATUS SAFETY GUIDE**

A Fire Apparatus Safety Guide published by Fire Apparatus manufacturer's Association shall be provided with delivered vehicle. This manual includes essential safety information for fire fighters, fire chiefs, apparatus mechanics, and fire department safety officers. The guide is applicable to municipal, wildland, and airport fire fighting apparatus manufactured on either custom or commercial chassis.

### **STATEMENT OF EXCEPTIONS**

The final-stage manufacturer shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- 1) A separate specification of the section of the applicable standard for which compliance is lacking
- 2) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
- 3) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance
- 4) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to or at the time of delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

GVWR Chassis			Storage Area		Equipment Weight		Ground Clearance	
Apparatus Type	lb.	kg.	ft.3	m3	lb.	kg.	in.	mm.
Wildland Fire Apparatus	15,000	7,000	20	0.56	200	90	12	300
	15,001 - 20,000	7,001 - 9,000	50	1.42	500	225	13	330
	20,001 - 26,000	9,001 - 12,000	50	1.42	500	225	15	380
	>26,000	>12,000	75	2.12	750	340		
Wildland Mobile Water Supply Fire Apparatus	All	All			200	90		

## **TESTING**

### **ROAD TEST**

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the Body Manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

### **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (-18°C and 43°C).

### **TEST SEQUENCE**

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for ten (10) minutes. Failure of any of these tests shall require a repeat of the sequence.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **1. RESERVE CAPACITY TEST**

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

## **2. ALTERNATOR PERFORMANCE TEST**

### **TEST AT IDLE**

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

### **TEST AT FULL LOAD**

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

## **3. LOW VOLTAGE ALARM TEST**

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST**

### **DOCUMENTATION**

The manufacturer shall deliver the following with the fire apparatus:

- 1) Documentation of the electrical system performance tests
- 2) A written electrical load analysis, including the following:
  - a) The nameplate rating of the alternator
  - b) The alternator rating
  - c) Each of the component loads specified that make up the minimum continuous electrical load
  - d) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
  - e) Each individual intermittent electrical load

### **MANUFACTURER PUMP CERTIFICATION**

The apparatus upon completion shall be tested and certified by the manufacturer. The certification tests shall follow the guide lines outlined in NFPA 1901 "Standard for Fire Apparatus".

If the fire pump has a rated capacity of less than 750 gpm (3000 L/min), the pump shall be tested after the pump and all its associated piping and equipment have been installed on the apparatus.

The fire pump shall be tested and results certified to perform as listed below;

- 100% of rated capacity at 150 psi (1,000 kPa) net pressure
- 70% of rated capacity at 200 psi (1,400 kPa) net pressure
- 50% of rated capacity at 250 psi (1,700 kPa) net pressure

The test shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming device tests, and the vacuum test.

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 500 psi (3,400 kPa).

The pump shall comply with the applicable requirements of "Standard for Fire Apparatus 1901, latest edition.

The pump shall be capable of producing fire streams that are free from objectionable pulsation under all normal operating conditions.

If the apparatus is equipped with a pump driven by the chassis engine designed for both stationary pumping and pump-and-roll, the test shall verify that the engine speed control at the pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the parking brake is off, and the pump shift status in the driving compartment is disengaged.
- (2) The chassis transmission is in any gear other than neutral, the parking brake is on, and the pump shift in the driving compartment is in the "Pump Engaged" or the "OK to Pump-and-Roll" position.

A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve.



# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **WARRANTY**

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source and will deal directly with the Lake Dillon Fire-Rescue on all warranty work.

## **GENERAL LIMITED WARRANTY - TWO (2) YEARS**

The vehicle shall be free of defects in material and workmanship for a period of two (2) years or 36,000 miles (or 57,936 kilometers), whichever occurs first starting thirty (30) days after the original invoice date.

The Contractor must be the "single source" coordinator of all warranties on the vehicle.

## **LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS**

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles (or 96,561 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

## **STRUCTURAL WARRANTY - TEN (10) YEARS**

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

## **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

## **PAINT LIMITED WARRANTY - TEN (10) YEARS**

The body shall be free of bubbling or peeling as a result of a defect in the method of manufacture for a period of ten (10) years or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date. **Pro-rated warranties will not be acceptable.**

## **GRAPHICS LIMITED WARRANTY**

The 3M graphics installation shall be warranted for a period of two (2) years. The 3M materials installed on completed vehicle shall be warranted for seven (7) years. The 3M Diamond grade film (if specified) shall be warranted for ten (10) years.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **HALE FIVE YEAR PUMP WARRANTY**

The fire pump shall be warranted by Hale for a period of five (5) years from the date of delivery to the Lake Dillon Fire-Rescue. Within this warranty period Hale shall cover parts and labor for the first two (2) years and parts only for years three (3) through five (5).

## **STAINLESS STEEL PLUMBING WARRANTY**

The stainless steel plumbing shall be free of defects in material and workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

The contractor shall supply details of their warranty information with their bid submission.

## **AKRON BRASS FIVE YEAR VALVE WARRANTY**

The Akron Brass valves shall be warranted by Akron Brass for a period of ten (10) years from the date of delivery to the Lake Dillon Fire-Rescue. The warranty for electronics shall be warranted by Akron Brass for a period of five (5) years from date of delivery to the Lake Dillon Fire-Rescue.

## **UPF POLY WATER TANK WARRANTY**

The UPF poly water tank shall be provided with a lifetime material and workmanship limited warranty. The manufacturer shall supply details of their warranty information with their bid submission.

## **CONSTRUCTION PERIOD**

The completed vehicle shall be delivered within three hundred ninety (390) days after receipt of a purchase order or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to Lake Dillon Fire-Rescue as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

## **OVERALL HEIGHT REQUIREMENT**

There is no overall height (OAH) restriction for this vehicle.

## **OVERALL LENGTH REQUIREMENT**

There is no overall length (OAL) restriction for this vehicle.

## **OVERALL WIDTH**

The overall width (OAW) of the body at drip rails shall be 100" (8' - 4"), and body shall be 98" (8' - 2").

## **ANGLE OF APPROACH**

The angle of approach for this vehicle shall not be less than twenty (20) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1906.

## **ANGLE OF DEPARTURE**

The angle of departure for this vehicle shall not be less than twenty (20) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1906.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **INSPECTION TRIPS**

All required inspection trips shall be the financial responsibility of the Lake Dillon Fire-Rescue, including but not limited to transportation, food and lodging.

## **DELIVERY AND DEMONSTRATION**

The Contractor shall be responsible for the delivery of the completed unit to the Lake Dillon Fire-Rescue's location. On initial delivery of the apparatus, the Contractor shall supply a qualified representative to demonstrate the apparatus and provide initial instruction to representatives of the Lake Dillon Fire-Rescue regarding the operation, care and maintenance of the apparatus and equipment supplied at Lake Dillon Fire-Rescue location.

The Delivery Engineer shall set delivery and instruction schedule with the person appointed by Lake Dillon Fire-Rescue.

After delivery of the apparatus, the Lake Dillon Fire-Rescue shall be responsible for ongoing training of its personnel to proficiency regarding the proper and safe use of the apparatus and associated equipment.

## **CAB/CHASSIS SPECIFICATIONS**

### **Vehicle Configuration**

108SD CONVENTIONAL CHASSIS  
2018 MODEL YEAR SPECIFIED  
SET BACK AXLE - TRUCK

### **General Service**

RESCUE AND EMERGENCY SERVICE  
MEDIUM TRUCK WARRANTY  
EXPECTED FRONT AXLE LOAD: 14000 lbs  
EXPECTED REAR DRIVE AXLE LOAD: 23000 lbs  
EXPECTED GROSS VEHICLE CAPACITY: 37000 lbs

### **Engine**

CUM L9 380EV HP @ 2000 RPM, 2200 GOV RPM, 1150 LB/FT @ 1400 RPM

### **Engine Equipment**

2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG17  
NFPA COMPLIANT EMBER SCREEN AND FIRE RETARDANT  
DONALDSON AIR CLEANER  
DR 12V 275 AMP 40-SI BRUSHLESS PAD ALTERNATOR WITH REMOTE BATTERY VOLTAGE SENSE  
(3) ALLIANCE MODEL 1031, GROUP 31, 12 VOLT MAINTENANCE FREE 2280 CCA THREADED STUD BATTERIES WITH POSITIVE JUMP START POST  
BATTERY BOX FRAME MOUNTED  
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN  
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH  
INTERNAL SAFETY VALVE  
C-BRAKE BY JACOBS WITH LOW/OFF/HIGH BRAKING DASH SWITCH  
RH MTD HORIZONTAL AFTERTREATMENT WITH RH HORIZONTAL  
TAILPIPE  
HORTON DRIVEMASTER ADVANTAGE ON/OFF FAN DRIVE  
AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR  
LIGHT  
CUMMINS SPIN ON FUEL FILTER  
COMBINATION FULL FLOW/BYPASS OIL FILTER  
1200 SQUARE INCH ALUMINUM RADIATOR WITH SENDURE HEAT  
EXCHANGER  
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED  
LIFE COOLANT  
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT  
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES  
ELECTRIC GRID AIR INTAKE WARMER  
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH

### Transmission

ALLISON 3000 EVS 6 SPD AUTOMATIC TRANSMISSION WITH PTO  
PROVISION

### Transmission Equipment

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S)  
FILL AND DRAIN  
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED  
TRANSMISSION PROGNOSTICS - ENABLED 2013  
WATER TO OIL TRANSMISSION COOLER  
MERITOR MTC-4210 TRANSFER CASE W/ OIL COOLER  
SKID PLATE UNDER OIL PAN AND TRANSFER CASE  
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL  
CHECK  
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

### Front Axle and Equipment

MX-14-120-EVO 14,000# 1790MM KPI SINGLE FRONT DRIVE AXLE  
MXL 16T MERITOR EXTENDED LUBE FRONT STEERING AXLE  
DRIVELINE WITH HALF ROUND YOKES  
MERITOR 16.5X5 Q+ MX DRIVE AXLE CAST SPIDER HEAVY DUTY CAM  
FRONT BRAKES  
FIRE AND EMERGENCY SEVERE SERVICE, NON-ASBESTOS FRONT  
LINING  
FRONT BRAKE DUST SHIELDS  
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS  
TRW TAS-85 POWER STEERING  
SYNTHETIC 75W-90 FRONT AXLE LUBE

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## Front Suspension

14,600# TAPERLEAF FRONT SUSPENSION  
MAINTENANCE FREE RUBBER BUSHINGS  
FRONT SHOCK ABSORBERS

## Rear Axle and Equipment

24,000 LB FIRE/EMERGENCY SERVICE SINGLE REAR AXLE  
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING  
MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF  
ROUND YOKES  
DRIVER CONTROLLED TRACTION DIFFERENTIAL  
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE  
ANCHOR HEAVY DUTY BRAKE AND SHOES  
FIRE AND EMERGENCY SEVERE SERVICE NON-ASBESTOS REAR  
BRAKE LINING  
REAR BRAKE DUST SHIELDS  
REAR OIL SEALS  
HALDEX GOLDSEAL LONGSTROKE 1-DRIVE AXLE SPRING PARKING  
CHAMBERS  
MERITOR AUTOMATIC REAR SLACK ADJUSTERS  
SYNTHETIC 75W-90 REAR AXLE LUBE

## Rear Suspension

24,000# FLAT LEAF SPRING REAR SUSPENSION WITH HELPER, WITH  
RADIUS ROD, FOR FIRE/EMERGENCY  
STANDARD AXLE SEATS IN AXLE CLAMP GROUP  
FORE/AFT CONTROL RODS

## Brake System

AIR BRAKE PACKAGE  
WABCO 4S/4M ABS WITH TRACTION CONTROL & ESC  
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM  
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER  
CUSTOM STEEL AIR BRAKE RESERVOIRS  
BW DV-2 AUTO DRAIN VALVE - WET TANK

## Electrical Connections

UPGRADED CHASSIS MULTIPLEXING UNIT  
UPGRADED BULKHEAD MULTIPLEXING UNIT

## Wheelbase & Frame

(176 INCH) WHEELBASE / (63 INCH) CA  
11/32X3-1/2X10-15/16 INCH STEEL FRAME 120KSI  
(74 INCH) REAR FRAME OVERHANG

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## Chassis Equipment

OMIT FRONT BUMPER  
24 INCH INTEGRAL FRONT FRAME EXTENSION  
FRONT TOW HOOKS - FRAME MOUNTED  
12 TON JACK WITH HANDLE AND WHEEL WRENCH  
FENDER & FRONT OF HOOD MTD FRONT MUDFLAPS  
GRADE 8 THREADED HEX HEADED FRAME FASTENERS

## Fuel Tanks

70 GAL 23" DIAMETER ROUND ALUMINUM FUEL TANK  
6 GALLON DIESEL EXHAUST FLUID TANK  
FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR, HAND  
PRIMER AND 12 VOLT PREHEATER  
EQUIFLO INBOARD FUEL SYSTEM

## Tires

MICHELIN XDS 12R22.5 16 PLY RADIAL FRONT TIRES  
MICHELIN XDS 12R22.5 16 PLY RADIAL REAR TIRES  
MICHELIN XDS 12R22.5 16 PLY RADIAL SPARE TIRE

## Hubs

MERITOR IRON FRONT HUBS  
CONMET PRESET PLUS IRON REAR HUBS

## Wheels

22.5X8.25 10-HUB PILOT 2-HAND STEEL DISC FRONT WHEELS  
PAINTED JOB COLOR  
22.5X8.25 10-HUB PILOT 2-HAND STEEL DISC REAR WHEELS PAINTED  
JOB COLOR  
22.5X8.25 10-HUB PILOT 2-HAND STEEL DISC SPARE WHEEL PAINTED  
JOB COLOR

## Cab Exterior

156 INCH BBC HIGH-ROOF ALUMINUM CONVENTIONAL AIR RIDE  
CREW CAB  
BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS  
NFPA COMPLIANT EXTERIOR GRAB HANDLES  
STATIONARY BLACK GRILLE WITH BRIGHT ACCENTS  
FIBERGLASS HOOD & FIREWALL INSULATION  
BRIGHT FINISH RADIATOR SHELL/HOOD BEZEL  
NONREMOVABLE BUGSCREEN MTD BEHIND GRILLE  
AIR HORN PREP KIT FOR CUSTOMER SUPPLIED HORN  
DUAL ELECTRIC HORNS  
INTEGRAL HEADLIGHTS WITH CHROME BEZELS & DAYTIME RUNNING  
LIGHTS  
WIG-WAG FEATURE LOW BEAM HEADLAMPS WITH DASH SWITCH,  
WITH PARK BRAKE RELEASED  
LED AERODYNAMIC MARKER LIGHTS  
FOG LIGHT WIRING PREP FOR CUSTOMER INSTALLED FOG LIGHTS  
DUAL 102" WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH  
AND RH REMOTE

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED  
UNDER PRIMARY MIRRORS  
REAR WINDOW OMIT  
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING  
WING WINDOWS  
RH AND LH ELECTRIC POWERED WINDOWS  
TINTED WINDSHIELD  
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL  
INDICATOR, FRAME MOUNTED

### Cab Interior

OPAL GRAY VINYL INTERIOR  
MOLDED PLASTIC DOOR PANELS WITH ALUMINUM KICKPLATES  
LOWER DOORS  
BLACK MATS WITH PREMIUM INSULATION  
WOODGRAIN INSTRUMENT PANELS  
FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE  
COMPARTMENTS WITHOUT NETTING  
IN DASH STORAGE BIN  
AM/FM/WB DASH MTD RADIO WITH BLUETOOTH AND USB AND  
AUXILIARY INPUTS, J1939  
(2) CUP HOLDERS LH AND RH DASH  
HEATER, DEFROSTER AND AIR CONDITIONER  
MAIN HVAC CONTROLS W/ RECIRCULATION SWITCH  
SOLID-STATE CIRCUIT PROTECTION AND FUSES  
12V NEGATIVE GROUND ELECTRICAL SYSTEM  
OVERHEAD INSTRUMENT PANEL  
DOOR ACTIVATED DOME/RED MAP LIGHTS, FORWARD LH AND RH  
AND REAR LH, RH AND CENTER  
CAB DOOR LATCHES WITH MANUAL DOOR LOCKS  
(1) 12V POWER SUPPLY & USB CHARGER IN DASH  
SEATS INC 911 UNIVERSAL SERIES HIGH BACK AIR SUSPENSION  
DRIVER SEAT NFPA COMPLIANT  
SEATS INC 911 UNIVERSAL SERIES HIGH BACK NON SUSPENSION  
PASSENGER SEAT WITH UNDERSEAT STORAGE NFPA COMPLIANT  
SEATS INC 911 UNIVERSAL SERIES HIGH BACK NON SUSPENSION LH  
AND RH REAR PASSENGER SEATS WITH RECLINING BACK, UNDER  
SEAT STORAGE NFPA COMPLIANT  
LH AND RH INTEGRAL DOOR PANEL ARMRESTS  
BLACK CORDURA PLUS CLOTH SEAT COVERS  
NFPA 1901-2009 HIGH VISIBILITY ORANGE SEAT BELTS  
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN  
4-SPOKE 18 INCH STEERING WHEEL  
DRIVER AND PASSENGER INTERIOR SUN VISORS

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## Instruments & Controls

BLACK GAUGE BEZELS  
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM  
2" PRIMARY & SECONDARY AIR PRESSURE GAUGES  
ENGINE COMPARTMENT MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS  
CUSTOM 97 DB BACKUP ALARM  
ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL  
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED  
FIRE AND EMERGENCY SERVICE VEHICLES ENGINE WARNING  
2 INCH ELECTRIC FUEL GAUGE  
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE  
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE  
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY  
ELECTRIC ENGINE OIL PRESSURE GAUGE  
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE  
ELECTRONIC 3000 RPM TACHOMETER  
IGNITION SWITCH CONTROLLED ENGINE STOP  
PRE-TRIP LAMP INSPECTION, ALL OUTPUTS FLASH, WITH SMART SWITCH  
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY  
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY  
MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH  
ONE VALVE PARKING BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR  
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE  
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS

## Paint Design

TWO COLOR CUSTOM BASE/CLEAR COAT PAINT METALLIC BLACK OVER RED  
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

## TOTAL VEHICLE SUMMARY

### Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight <sup>+</sup>	9247 lbs	5058 lbs	14305 lbs
(+ ) Weights shown are estimates only.			



# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **CAB TO AXLE DIMENSION**

Cab to axle will be 63".

## **CAB/CHASSIS PREPAYMENT**

The specified cab/chassis shall be prepaid by Lake Dillon Fire-Rescue within 30 days of invoice. Lake Dillon Fire-Rescue understands that if payment is made after 30 days, additional interest charges may apply.

## **CHASSIS MODIFICATIONS**

## **LUBRICATION AND TIRE DATA PLATE**

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid . . (if applicable)
- Pump priming system fluid, if applicable . . (if applicable)
- Drive axle(s) lubrication fluid
- Air conditioning refrigerant . . (if applicable)
- Air conditioning lubrication oil . . (if applicable)
- Power steering fluid
- Cab tilt mechanism fluid . . (if applicable)
- Transfer case fluid . . (if applicable)
- Equipment rack fluid (if applicable)
- CAFS air compressor system lubricant . . (if applicable)
- Generator system lubricant . . (if applicable)
- Front tire cold pressure
- Rear tire cold pressure
- Maximum tire speed ratings

## **VEHICLE DATA PLATE**

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the;
  - Engine
  - Transmission
  - Air
  - Fuel
- Serial numbers for the;
  - Engine
  - Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **OVERALL HEIGHT, LENGTH DATA PLATE (US)**

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in feet and inches, the length of the completed fire apparatus in feet and inches, and the GVWR in pounds.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

## **PERSONNEL CAPACITY**

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

## **SEAT BELT WARNING - FAMA06/07**

A safety sign FAMA06 shall be visible from each seat that is not equipped with occupant restraint and therefore not intended to be occupied while the vehicle is in motion.

A safety sign FAMA07, which warns of the importance of seat belt use, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

## **EQUIPMENT MOUNTING FAMA10**

A safety sign FAMA10, which warns of the need to secure items in the cab, shall be visible inside the cab.

## **FIRE SERVICE TIRES - FAMA12**

A safety sign FAMA12, which warns of the special requirements for fire service-rated tires, shall be visible to the driver entering the cab of any apparatus so equipped.

## **HELMET WARNING - FAMA15**

A safety sign FAMA15, which warns not to wear helmets while the vehicle is in motion, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

## **CLIMBING METHOD - FAMA23**

A safety sign FAMA23, which warns of the proper climbing method, shall be visible to personnel entering the cab and at each designated climbing location on the body.

## **REAR STEP CROSSWALK WARNING - FAMA24**

A safety sign FAMA24, which warns personnel not to ride on the vehicle, shall be located at the rear step areas and at any cross walkways.

## **FINAL STAGE MANUFACTURER VEHICLE CERTIFICATION**

A final stage manufacturer vehicle certification label shall be provided and installed in the driver cab door jamb area.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **BUMPER**

The cab/chassis supplied bumper will be replaced with a swept-back style bumper. The bumper shall come with openings for front bumper discharge(s), if specified and painted cab color choice.

## **FRONT BUMPER**

The front bumper shall be as provided by the cab/chassis manufacturer. No other alteration or modifications are required to extension length.

## **BUMPER GRAVEL SHIELD**

The front bumper extension shall have a 3/16" NFPA compliant aluminum tread plate gravel shield. The gravel shield shall cover the full width of the front bumper to the front of the cab and the full height of the bumper on each end.

## **BUMPER HOSEWELL COMPARTMENTS**

There shall be three (3) hosewells in the front extended bumper. Each hosewell shall be constructed of .125" smooth aluminum and contain drain holes.

The curbside hosewell shall be approximately 28.25" wide x 11.5" deep x 7" front to back with a tapered side to the right side of the hosewell (1.38 cubic foot). The hosewell shall include a diamond plate hinged cover. The cover shall be manufactured with bevel style ends. A stainless steel D-Ring handle shall be used to open the lid with a gas shock to hold the lid in the open position.

The center hosewell (mounted between the frame rails) shall be 26" wide x 11.5" deep x 9.5" front to back (1.65 cubic foot). The center hosewell shall include a diamond plate hinged cover. The cover shall be manufactured with bevel style ends. A stainless steel D-Ring handle shall be used to open the lid with a gas shock to hold the lid in the open position. The left and right forward corners of the lid shall have a cutout to allow a Pre-connected hose to be stored with the hosewell cover closed.

The streetside hosewell shall be approximately 28.25" wide x 11.5" deep x 7" front to back with a tapered side to the right side of the hosewell (1.38 cubic foot). The hosewell shall include a diamond plate hinged cover. The cover shall be manufactured with bevel style ends. A stainless steel D-Ring handle shall be used to open the lid with a gas shock to hold the lid in the open position.

A safety sign FAMA22, which warns of the need to secure hose, shall be visible to personnel at each hose storage area.

## **AIR HORN**

One (1) Grover painted air horn shall be provided underhood or behind grille and connected to the cab/chassis supplied air horn prep kit.

## **AIR HORN ACTIVATION**

The air horn(s) shall be operated by a foot switch on the cab floor located at both the driver and officer positions.

## **FRONT TOW PLATE**

A horizontal full frame width, 1/2" thick steel plate, center pull, front tow eye shall be furnished and installed through or below the front bumper. The tow eye plate shall be triangle shaped extended 6" beyond the front bumper with a 3" x 4" rectangle tow eye. The tow eye must be braced and gusseted to prevent frame rail or bumper damage and bolted to the front frame rail web with eight (8) 5/8" SAE Grade 8 frame bolts and lock nuts.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **FRONT TOW EYES**

There shall be two (2) heavy duty cast tow eyes securely mounted to the chassis frame below the front bumper.

## **AIR INTAKE SYSTEM**

An air filter shall be provided in the engine's air intake system by the commercial cab/chassis manufacturer. Air inlet restrictions shall not exceed the engine manufacturer's recommendations. The air inlet shall be equipped with a means of separating water and burning embers from the air intake system.

In addition to the engine's air intake, the cab fresh air intake and/or outside cab vent shall be equipped with a means of separating water and burning embers from the air intake system

This requirement shall be permitted to be achieved by either of the following methods:

1. Provision of a device such that burning particulate matter larger than 0.039 in. (1.0 mm) in diameter cannot reach the air filter element.
2. Provision of a multi screen ember separator capable of meeting the test requirements defined in the Parker Hannafin, Racor Division, publication LF 1093-90, *Ember Separation Test Procedure*, or an equivalent test.

## **EXHAUST**

The exhaust system shall be modified to exit to rear of vehicle. The tailpipe may require some modifications for proper ground clearances and fit with body.

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the vehicle or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position or entry doors on body.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

## **RADIO/ANTENNA INSTALLATION**

There shall be two (2) Lake Dillon Fire-Rescue supplied radio(s) with antenna installed in center console. One VHF B/K GMH and one Tait TM 9300, 800 MHz DTR. All required radio programming shall be responsibility of Lake Dillon Fire-Rescue. Radio(s) may not be fully tested if no radio program is provided with radio and will be responsibility of Lake Dillon Fire-Rescue after delivery.

Radio shall be installed per Manufacturer's requirements and wired for proper 12 volt power and ground.

A Lake Dillon Fire-Rescue supplied cell signal booster shall also be installed in base of center console.

## **12 VDC FUSE BLOCK**

There shall be one (1) Blue Sea Systems 100 amp ST Series blade type fuse block with screw type terminals for both positive and negative buss with cover provided for distribution of up to six (6) 30 amp, 12 VDC circuits. Fuse block shall be located per required circuits and be protected from damage.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **SCBA SEAT AIR PACK BRACKETS**

No SCBA air pack bracket(s) shall be provided in specified commercial cab SCBA seats. Lake Dillon Fire-Rescue will provide and install necessary bracket(s) after delivery.

## **SEAT BELT COLOR**

Section 14.1.3.4 of the NFPA 1901 Standards, requires all seat belt webbing in cab to be bright red or bright orange in color, and the buckle portion of the seat belt shall be mounted on a rigid or semi rigid stalk such that the buckle remains positioned in an accessible location.

## **SEAT BELT WEB LENGTH - COMMERCIAL CAB**

Sections 14.1.3.2 and 14.1.3.3 of the NFPA 1901 standards, require the effective seat belt web length for a Type 1 lap belt for pelvic restraint to be a minimum of 60", and a Type 2 pelvic and upper torso restraint-style seat belt assembly to be a minimum of 110".

The chassis seat belt web length as supplied by the commercial chassis manufacturer shall be compliant to NFPA Standards 14.1.3.2 and 14.1.3.3.

## **SEAT BELT MONITORING AND VEHICLE DATA RECORDER (VDR) SYSTEMS**

### **SEAT BELT MONITORING**

A Weldon 6204 series system with Occupant Restraint Indicator (ORI) display shall be provided and installed to allow the driver to know if all persons seated in the vehicle are secured with seat belts before moving the vehicle. Built-in smart seating logic shall detect if the correct sit and buckle sequence is not followed for all seats. System shall also provide an output for an external alarm. Weldon diagnostic port will be located under dash on driver side. System shall include the following features;

### **VEHICLE DATA RECORDER (VDR)**

The vehicle data recorder shall have the following features;

- Recorded Data Includes: Vehicle Speed, Acceleration, Deceleration, Engine Speed, Engine Throttle Position, ABS Event, Seat Occupied Status, Seat Belt Status, Master Optical Warning Switch, Park Brake, Service Brake, Time, Date and Engine Hours.
- Password Protected by the customer
- Six (6) seat position inputs for occupied and belts buckled. Additional six (6) seat expansion module available.
- Easily interfaces with traditional wiring, or optional V-MUX™ or other multiplexing systems
- Data is extracted by a standard, mini USB cable
- Use in conjunction with the Occupant Restraint Indicator or optional V-MUX™ multiplex system

### **OCCUPANT RESTRAINT INDICATOR**

The occupant restraint indicator shall have the following features;

- Supports commercial and custom cab seating layouts; up to 12 seats
- Built-in audible alarm
- Use in conjunction with Vehicle Data Recorder (VDR)

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **IGNITION KEY**

If the vehicle is specified to have an ignition key it will be attached to steering column or dash with vinyl covered steel cable.

## **WIRELESS TIRE PRESSURE MONITOR**

The AirBAT RF® tire pressure monitoring system is a state of the art tire pressure monitoring system making use of cutting edge RF technology. Improved fuel economy, reduced road calls, increased vehicle up time and increased tread life are all within reach for your fleet using the AirBAT tire pressure monitoring system.

The tire pressure sensors are simple to install and provide immediate feedback on tire pressure with readily visible LED low pressure indicators. When you do find a low tire, the conveniently located fill ports make fishing in the dark for that inner dual valve stem a thing of the past.

With the new CSA 2010 requirements, maintaining tire pressures is more important than ever with an increased driver responsibility for tire pressure. Improved fuel efficiency, reduced operating costs, increased tire life and increased safety are just a few of the key benefits you will see using the AirBAT tire pressure monitoring system.

Features:

Continually monitors tire pressures

Adjustable visual alerts for under-inflation

Easy access fill ports save time

Wireless transmission of pressures Driver Alert System

Wide operating temperature and pressure ranges

## **HELMET STORAGE**

No helmet storage is required in the cab driving area.

## **HELMET STORAGE**

No helmet storage is required in the cab crew area.

## **CAB CRASH TEST CERTIFICATION**

A cab crash test certification from the fire apparatus manufacturer shall be provided with the equipment. A copy of this certification shall be included with the bid.

NOTE: There shall be no exception to any portion of the cab integrity certification requirements. Nonconformance shall lead to immediate rejection of bid.

The certification shall state that the cab does meet or exceed the requirements below:

- 1) European Occupant Protection Standard ECE Regulation No. 29.
- 2) SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks.

## **CAB WINDOW TINT**

The cab door windows shall be provided with profesional grade 30% window tint.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **CAB MIRRORS, DRIVER ADJUSTABLE**

Section 14.3.5 of the NFPA 1901 Standards, 2009 edition, requires all primary rear view mirrors used by the driver to be adjustable from the driver's position.

## **CAB STEP OVERLAY**

Four (4) of the cab/chassis supplied entry steps will be overlaid with 1/8" NFPA compliant aluminum treadplate non-skid stepping surface.

The maximum stepping height shall not exceed 18", with the exception of the ground to first step, which shall not exceed 24" when the vehicle is loaded to its estimated in-service weight. All steps shall have a minimum area of 35 sq in and shall be of such a shape that a 5" diameter disk does not overlap any side when placed on the step, and shall be arranged to provide a t least 8" of clearance between the leading edge of the step and any obstruction. All platforms shall have a minimum depth of 8" from the leading edge of the platform to any obstruction.

One (1) storage compartment shall be provided below the cab on curbside below crew door.

## **MUDFLAPS**

There shall be 1/4" rubber mudflaps provided and installed behind each set of tires to prevent throwing road debris and lower road spray.

## **AIR BRAKE SYSTEM QUICK BUILD-UP**

The air brake quick build-up system shall be supplied from the specified automatic electric compressor in order to maintain full operating air pressure while the vehicle is not running.

The quick buildup system shall provide sufficient air pressure so that the apparatus has no brake drag and is able to stop under the intended operating conditions following the 60-second buildup time.

## **ELECTRIC DOOR LOCK INTERFACE**

Electric door locks shall be provided and interfaced as follows;

The 4 door cab manual door locks shall be retrofitted with a POP Locks electric actuated door locking system. All cab doors shall be locked and un-locked from a numeric key pad located adjacent to the drivers door. All doors shall have a manual key operated override capability in the event of a failure of the electric lock system. All cab doors shall be keyed alike. Four (4) hand held remote control units shall be provided for remote switching.

A switch shall be provided in the center of the cab dash to activate the body electric door locks.

## **ROAD EMERGENCY SAFETY KIT**

The completed unit shall be supplied with one (1) set of three (3) dual faced reflective triangles, and three (3) warning flares complete with storage case per DOT requirements.

One (1) 2.5 lb. ABC type vehicle fire extinguisher with bracket per DOT requirements shall be provided and mounted inside cab area.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

### **BODY DESIGN**

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the Lake Dillon Fire-Rescue to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the Lake Dillon Fire-Rescue from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

### **EXTERIOR ALUMINUM BODY**

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 3/16" (.187) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas, No Exceptions.

The front and rear corners of body shall be formed as part of the front or rear body panels. This provides a stronger body corner and finished appearance. The use of extruded corners, or caps will not be acceptable, No Exceptions.

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.



# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded and caulked to prevent moisture from entering the compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

### **DRIP RAILS**

The body shall have drip rails over the side full height compartments. The drip rails shall be formed into the upper body panels providing a ridged lower panel and a flat upper body panel surface. The use of mechanically fastened, taped or glued on drip rails will not be acceptable, No Exceptions.

### **ROOF CONSTRUCTION**

The roof structure shall be integral with the body sheet metal construction and shall be an all welded assembly. The body roof structure shall be overlaid with not less than 3/16" aluminum 3003H-14 alloy tread plate and welded to roof structure and body sheet metal. All seams in roof material shall be fully and continuously welded to prevent entry of moisture.

There shall be a total of four (4) 2" x 2" x 1/4" 6061-T6 alloy aluminum "C" channels running the length of body, two (2) on each outboard side. These "C" channels shall be used for roof support and in addition shall be used for mounting of any specified reels. This open "C" channel design along with special reel mounting clips allows for a universal location of any specified reels within each compartment.

In between the two (2) center "C" channels running the length of body shall be 2" x 2" x 1/4" 6061-T6 alloy aluminum tubing running in between and welded in place on approximate 16" centers to support roof and/or walkway structure if specified.

A 2" formed radius shall be provided along the body sides and utilized as a wiring trough. The use of aluminum extrusions in this area shall not be acceptable, .

### **BODY SUBFRAME**

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 4" x 1/4" aluminum tubes minimum, the same width as the chassis frame rails. Welded to this tubing shall be cross members of 2" x 4" x 1/4" aluminum. Smaller dimension, lighter gauge tubing or angle material subframe shall not be accepted.

These cross members shall extend the full width of the body to support the compartments. Cross members shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum cross members shall be located on 16" centers, or as necessary to support walkway or heavy equipment.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.

### **BODY MOUNTING**

The body subframe shall be fastened to the chassis frame with a minimum of four (4) spring loaded body mounts. Each mount shall be configured using a two-piece encapsulated slide bracket. The two (2) brackets shall be fabricated of heavy duty 1/4" thick steel and shall have a powder coat finish to prevent any corrosion. Each mounting assembly shall utilize two (2) 3/4" diameter x 6" long grade 8 bolts and two (2) heavy duty springs. The assembly design shall allow the body and subframe to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall eliminate any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement will not be acceptable.

### **12" REAR STEP BUMPER**

The full width rear bumper shall be constructed from 2" x 2" x 1/4" aluminum tubing frame and covered with 3/16" NFPA compliant aluminum tread plate. The bumper shall extend from the rear vertical body panel 12" and provide a rear step with a minimum of 1/2" space at body for water drainage.

### **REAR TOW EYES**

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below body. The tow eyes shall be fabricated from 3/4" thick steel plate with a 3" diameter opening. Tow eyes shall have a black powder coat finish.

### **GROUND LIGHTS**

There shall be two (2) OnScene 8" Access LED lights installed below bumper capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting shall be switchable but activated automatically when the vehicle park brake is set.

### **SPARE TIRE CARRIER**

A ratchet type cable lift spare tire carrier shall be provided and installed under the chassis frame aft of the rear axle. The use of the vehicle's lug wrench shall be the mechanism to raise and lower the spare tire. The spare tire shall be secured to the body assembly in the raised position with four (4) "right hand thread" wheel studs and supplied lug nuts of the same OEM type and style that match the vehicle. Access to the ratchet assembly shall be at the rear of the vehicle. An access door cover shall be provided to cover and protect the ratchet assembly.

### **WHEEL WELL EXTERIOR PANEL**

The exterior panel of the body wheel well enclosure shall be constructed from 3/16" smooth aluminum panels.

### **RUBBER BODY FENDERS**

The body wheel well openings shall be provided with round radius, rubber fenderettes. The fenderettes shall be bolted and easily replaceable if damaged. The fenderettes shall be installed using stainless steel fasteners with plastic isolators to help prevent corrosion.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **WHEEL WELL LINERS**

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will not accumulate dirt or water.

## **SCBA CYLINDER COMPARTMENTS**

There shall be four (4) SCBA cylinder storage compartments, two (2) on each side of body in the rear wheel well area. Each compartment shall have a stainless steel hinge with brushed stainless steel door assembly with a positive catch latch. Each compartment shall have a 8" diameter tube behind the wheel well panel attached to the door assembly. Each compartment shall allow the storage of an SCBA cylinder or a fire extinguisher up to 7-3/4" in diameter and 22" deep. The door shall activate the "Hazard Warning Light" in the cab when not in the closed position.

## **EXTINGUISHER COMPARTMENTS**

There shall be two (2) Lake Dillon Fire-Rescue supplied fire extinguisher storage compartments located, one (1) on the curbside, and one (1) on the streetside of rear wheel well area. Each compartment shall be capable of storing one (1) fire extinguisher. Each compartment shall have a vertical stainless steel hinged aluminum door with a positive catch latch and painted primary lower body color. The door shall activate the "Hazard Warning Light" in the cab when not in the closed position.

## **BODY PAINT SPECIFICATIONS**

### **BODY PAINT PREPARATION**

After the body and components have been fabricated they shall be disassembled so when vehicle is complete there shall be finish paint beneath the removable components. The body shall be removed from chassis during the paint process to insure proper paint coverage. The body and components shall be metal finished as follows to provide a superior substrate for painting.

The exterior (and interior, if painted) body shall undergo a thorough cleaning process starting with a biodegradable phosphoric acid solution to begin the etching process followed by a complete clear water rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the metal surface for greater film adhesion.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

### **PAINT PROCESS**

The paint process shall follow the strict standards set forth by PPG Industries guidelines. Painters applying PPG products will be PPG Certified Commercial Technicians, and re-certified every two (2) years. The body shall go through the following paint process;

- 1) Clean bare metal with a wax and grease remover using low lint rags.
- 2) Inspect, straighten, and hammer high points, grind all seams, sharp edges, and welds. DA sand entire paintable surfaces using 24-180 grit dry paper. Plastic fill all low spots and DA sand fill areas using 36-180 grit dry paper. Apply pinhole filler and DA sand areas using 80-180 grit dry paper.
- 3) Re-clean bare metal using a wax and grease remover and low lint rags.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

- 4) Within 24 hours, a PPG Delfleet® epoxy color primer with proper hardener for corrosion resistance using a pressure pot spray gun and applying 2-5 full wet coats or 1.5-8.0 dry mils max. achieving full hiding and allow to air dry 60 minutes @ 70°F or bake for 45 minutes @ 140°F degree.
- 5) Inspect, putty fill, and dry guild coat entire body surface and DA sand using 180-400 grit dry paper.
- 6) Re-clean bare metal using a wax and grease remover using low lint rags.
- 7) A PPG Delfleet® primer sealer with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 1 full wet coat or 1.0-2.0 dry mils achieving full hiding and allow to flash off in spray booth for minimum of 60 minutes @ 70°F.
- 8) A PPG Delfleet® FBCH basecoat (color) with proper hardener and dry additive shall then be sprayed using a pressure pot set @ 45-60 PSI and achieving full hiding or 1.5-2.0 wet mils and allow to flash off in spray booth 45-60 minutes before applying clearcoat.
- 9) A PPG Delfleet® clearcoat with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 2-3 full wet coats or 5.0 wet mils for a uniform gloss and allow to flash off in spray booth 10 minutes and bake for 120-140 minutes @ 125°F (surface temp.).
- 10) After cooling, DA sand heavy orange peel or runs using 1000 grit dry sand paper and final DA sand using 1500-2000 grit dry sand paper. Wipe off all surfaces to remove dust and debris. Buff unit as needed using 3M rubbing compound and a white wool pad and inspect until all sand scratches are removed.
- 11) Polish as needed using 3M Perfect-It-Polish and a black foam pad, repeat as necessary and inspect until all sand scratches are removed.

### **PAINT - ENVIRONMENTAL IMPACT**

The contractor shall meet or exceed all current State (his) regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. PPG Delfleet® Evolution paint shall be free of all heavy metal (lead & chromate) components. Paint emissions from sanding and painting shall be filtered and collected. All paint wastes shall be disposed of in an environmentally safe manner. Solvents used in cleanup operations shall be collected, sent off-site for distillation and returned for reuse.

### **FASTENERS**

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, a Mylar isolation tape, or gasket shall be used to prevent damage to the finish painted surface. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nut-surts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

### **ELECTROLYSIS CORROSION CONTROL**

The vehicle shall be assembled using ECK brand or similar corrosion control compound on all high corrosion potential areas.

ECK protects aluminum and stainless steel against electrolytic reaction, isolates dissimilar metals and gives bedding protection for hardware and fasteners. ECK contains anti-seizing lubricant for threads. ECK is dielectric and perfect for use with electrical connectors.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **PAINT FINISH - TWO COLOR**

The body shall be painted with a two-tone single color of PPG Delfleet® Evolution per Lake Dillon Fire-Rescue approved paint spray out provided.

A small touch-up bottle of paint shall be provided with completed vehicle.

Candy Apple Red FBCH 914040.  
Met.Mica Black FBCH 911130.

Standard body paint break with red drip rail.

- Paint Color: Match cab/chassis supplied paint color.

## **BODY UNDERCOATING**

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

## **UNDERCOAT WARRANTY**

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

## **PAINT WARRANTY**

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle. **Pro-rated warranties will not be acceptable.**

## **COMPARTMENT INTERIOR FINISH**

The interior of all exterior body compartments shall be a "Maintenance Free" smooth unpainted finish. All body seams shall be finished with a caulk sealant for both appearance and moisture protection.

## **REFLECTIVE STRIPE REQUIREMENTS**

### **Material**

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retro-reflection of 10 with observation angle of 0.2 degrees and entrance angle of -4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

### Minimum Requirements

A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 4 in. (100 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

### **GRAPHICS PROOF**

A color graphics proof of the reflective striping layout shall be provided for approval by Lake Dillon Fire-Rescue prior to installation. The graphics proof shall be submitted to Lake Dillon Fire-Rescue on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

### **REFLECTIVE STRIPE - CAB SIDE**

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be black in color.

There shall be a 2" Scotchcal reflective stripe located approx. 1" above the main stripe.

- This reflective stripe shall be black in color.

### **REFLECTIVE STRIPE - CAB FRONT**

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be black in color.

There shall be a 2" Scotchcal reflective stripe located approx. 1" above the main stripe.

- This reflective stripe shall be black in color.

### **CHEVRON STRIPE - CAB BUMPER**

A reflective stripe shall be affixed to the front of cab. The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The approximate 10" wide Chevron retroreflective stripe shall be affixed to at least 25 percent of the width of the front of the apparatus with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width. Chevron panels shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panels shall have a minimum 10 year warranty for material failure, and colorfastness.

- The stripe material shall be 3M Scotchlite Diamond Grade.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

All retroreflective materials required shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

### **REFLECTIVE STRIPE - CAB DOOR INTERIOR**

Any door of the apparatus designed to allow persons to enter or exit the apparatus shall have at least 96 in.<sup>2</sup> (62,000 mm<sup>2</sup>) of retroreflective material affixed to the inside of the door.

The stripe material shall be 3M Scotchlite 680.

- This reflective stripe shall be white in color.

### **REFLECTIVE STRIPE - BODY SIDES**

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be black in color.

There shall be a 2" Scotchcal reflective stripe located approx. 1" above the main stripe.

- This reflective stripe shall be black in color.

The stripe shall remain in a straight line from the front of the front of cab to the rear body.

### **CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS**

At least 50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width.

The rear side panels of the body on each side of a rear stairway or compartment shall have a chevron style reflective stripe, extending from bumper height up to side compartment drip rail height. Each chevron panel shall be a full sheet and shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panel shall have a minimum 10 year warranty for material failure, and colorfastness.

The stripe material shall be 3M Diamond Grade.

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

### **LETTERING**

### **GRAPHICS PROOF**

A color graphics proof of the lettering layout shall be provided for approval by Lake Dillon Fire-Rescue prior to installation. The graphics proof shall be submitted to Lake Dillon Fire-Rescue on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

The following lettering shall be provided and installed on the completed unit as follows;

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **SIDE CAB DOOR LETTERING**

There shall be twelve (12) 4" high 22K gold letters provided and installed on the vehicle. Lettering shall have a clear 3M UV protective overlamine applied before installation

Final design and layout shall be determined prior to construction.

## **UPPER BODY SIDE LETTERING**

There shall be one hundred (100) 4" high reflective letters furnished and installed on the vehicle.

- This reflective lettering shall be black in color.

## **REAR BODY LETTERING**

There shall be NO lettering applied in this area.

## **FRONT OF CAB LETTERING**

There shall be NO lettering applied in this area.

## **CUSTOM DECAL LOGO - 12" -18"**

One (1) custom designed 12" - 18" Scotchcal type retroreflective logo shall be provided and located on the completed vehicle. The exact design and/or artwork shall be provided by the Lake Dillon Fire-Rescue prior to construction.

One (1) copy of the above custom logo shall be provided and located on the completed vehicle as directed by Lake Dillon Fire-Rescue.



# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **EXTERIOR COMPARTMENT DOORS**

### **ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM)**

The vehicle shall be equipped with R•O•M Series IV roll-up exterior compartment doors. The R•O•M roll-up doors shall be complete with the following features;

Each shutter slat, track, bottom rail, and drip rail shall be constructed from anodized 6063 T6 aluminum. Shutter slats shall feature a double wall extrusion 0.315" thick with a concave interior surface to minimize loose equipment jamming the shutter door closed. Shutter slats shall feature an interlocking end shoe to prevent side to side binding of the shutter door during operation. Slat must have interlocking joints with an inverted locking flange. Slat inner seal shall be a one piece PVC extrusion; seal design will be such to prevent metal to metal contact while minimizing dirt and water from entering the compartment.

Shutter door track shall be one piece design with integral overlapping flange to provide a clean finished look without the need of caulk. Door track shall feature an extruded Santoprene rubber double lip low profile side seal with a silicone co-extruded back to reduce friction during shutter operation.

Shutter bottom rail shall be a one piece double wall extrusion with integrated finger pull. Finger pull shall be curved upward with a linear striated surface to improve operator grip while operating the shutter door. Bottom rail shall have a smooth contoured interior surface to prevent loose equipment from jamming the shutter door. Bottom rail seal shall be made from Santoprene; it will be a double "V" seal to prevent water and debris from entering compartment. Bottom rail lift bar shall be a one piece "D" shaped aluminum extrusion with linear striations to improve operator grip during operation. Lift bar shall have a wall thickness of 0.125". Lift bar shall be supported by no less than two pivot blocks; pivot blocks shall be constructed from Type 66 Glass filled reinforced nylon for superior strength. Bottom rail end blocks shall have incorporated drain holes which will allow any moisture that collects inside the extrusion to drain out.

Shutter door shall have an enclosed counter balance system. Counter balance system shall be 4" in diameter and held in place by two (2) heavy duty 18 gauge zinc plated plates. Counter balance system shall have two (2) over-molded rubber guide wheels to provide a smooth transition from vertical track to counter balance system; no foam material of any kind shall be permitted or used in this area.

### **ROM DOOR BOTTOM RAIL**

All exterior compartment doors shall have the standard 3.0" tall bottom rail extrusion for easy one (1) hand opening and closing.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

### STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S1)

The interior useable compartment width shall be approximately 54.0" wide.

The compartment door opening shall be approximately 49.5" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

### COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- One (1) smooth aluminum unfinished module shall be provided in forward section of compartment. Module shall be full depth of compartment and divided into two individual storage areas approximately 14" wide x 20" high.
- There shall be two (2) slide-out smooth aluminum vertical tool board(s) approximately 22" deep. Each tool board(s) vertical exterior edge shall have a double 90 degree formed edge to provide an easy grip handle. The top and bottom of tool board(s) shall be provided with Accuride 9300 series slide tracks. Each board shall be rated for a maximum 200 lbs. evenly distributed load. Each tool board shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.
  - The vertical tool board material shall be 3/16" (.188) 3003H-14 aluminum alloy sheet.
  - The above component(s) shall have a smooth un-painted finish.
  - Each tool board will be bolted to compartment floor.
- There shall be four (4) Zico 1000 series KD-UH walkaway type SCBA air pack bracket(s) with high cycle coated spring clips and angled foot plate (no CRS strap inc.). Air pack brackets to be mounted on specified tool boards.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **STREETSIDE COMPARTMENT - REAR (S2)**


The interior useable compartment width shall be approximately 47.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

## **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be <sup>Two (2)</sup>  (1) 400 lbs. slide-out tray(s) approximately 22" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
  - The above component(s) shall have a smooth un-painted finish.

NOTE: two (2) 400 pound trays to be provided, one on floor and one adjustable below frame level. Requires full height shelf track. BTW 1/3/2018

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

- There shall be two (2) OnScene Solutions 84 series slide-out, drop-down style aluminum tray base with 90% extension, and rating of 250 lbs. Slide-out tray(s) base shall be approximately 22" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will hold the tray in the closed position. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".
  - The above component(s) shall have a smooth un-painted finish.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.
- One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.
  - The ground lights shall be activated with barking brake, turn signal and when the apparatus is in reverse.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **CURBSIDE COMPARTMENT - ABOVE REAR WHEELS (C1)**

The interior useable compartment width shall be approximately 54.0" wide.

The compartment door opening shall be approximately 49.5" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

## **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be two (2) adjustable shelf/shelves approximately 12" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.
  - The above component(s) shall have a smooth un-painted finish.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 22" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
  - The above component(s) shall have a smooth un-painted finish.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **CURBSIDE COMPARTMENT - REAR (C2)**

The interior useable compartment width shall be approximately 47.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

## **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 22" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
  - The above component(s) shall have a smooth un-painted finish.
  - The back wall of compartment (12" deep area above frame level) shall be provided with bolted 3/16" (.188) 3003H-14 aluminum alloy sheet, approximately 45" wide x 28" high. Sheet shall be perforated with 1/4" (.25) holes on 1" centers. To assist in equipment mounting sheet shall be spaced from compartment wall approximately 1".
  - The above component(s) shall have a smooth un-painted finish.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.
- One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

- The ground lights shall also be activated with barking brake, turn signal and when the apparatus is in reverse.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

### **REAR COMPARTMENT - CENTER (RC1)**

The rear center compartment shall start at the top of the body sub-frame and be as high as the side compartments, unless specified otherwise.

The interior useable compartment width shall be approximately 50.0" wide.

The compartment door opening shall be approximately 31.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The roll-up doors shall be equipped with an electric power lock system. All doors shall be locked or unlocked with activation from a single switch located in the cab.
- One (1) 1" wide nylon strap shall be provided to assist in closing the compartment door. The strap shall be fastened to the lower left inside door sill with a nickel plated Footman loop secured to back of door. The strap shall extend from door to a nickel plated Footman loop secured to wall or vertical slot of Shelf-Trac on left side of the door opening.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.

### **COMPARTMENT LAYOUT**

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf/shelves approximately 24" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edge.
  - The above component(s) shall have a smooth un-painted finish.
- There shall be two (2) aluminum handrail sections with brackets assembled under the hose bed extension step. Brackets shall be designed to hold the handrails in position with a quick pin to hold in place for operation. Inside the right rear ladder compartment door shall be a storage bracket to hold the handrails when not in use. The I-Zone brackets are provided to lace the hose between when moving from house to house during structure fire protection operations.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## ROPE ANCHOR OR PORTABLE WINCH RECEIVERS

The completed unit shall have an integrated receiver or anchor system for use with removable rope anchor point and/or a portable electric winch, when specified.

Receivers or anchors installed at any location on the apparatus for use as removable winch anchors shall be designed and affixed to provide at least a 2.0 to 1 straight line pull no-yield safety factor over the load rating of the removable winch.

Receivers or anchors installed at any location on the apparatus for use with rope operations shall be designed and affixed to the apparatus to provide at least a 9,000 lbf (40,000 N) no-yield condition with a straight line pull.

A safety sign FAMA28 shall be located on or near each receiver or anchor stating the maximum straight line pull rating.

Side receiver(s) (if specified) shall have the following load rating:

	<u>STRAIGHT PULL</u>	<u>SAFETY FACTOR</u>
Rope Tie Off:	600 Lbs.	15:1
Winch:	5,000 Lbs.	2:1

Front and/or rear receiver(s) (if specified) shall have the following load rating:

	<u>STRAIGHT PULL</u>	<u>SAFETY FACTOR</u>
Rope Tie Off:	600 Lbs.	15:1
Winch:	Winch Load Rating (9,000 Lbs. Max)	2:1

The following items shall be provided to accomplish rope rescue and/or portable winch operation;

- There shall be one (1) 2" x 2" x 1/4" wall steel receiver tube(s) with black hammertone powder coat paint finish located at the front bumper for use with removable rope anchor point and/or a portable electric winch (when specified) and/or a removable hose roller.
  - There shall be one (1) 12 VDC plug(s) with quick connect provided to power a Warn portable winch. All 12 VDC cables to be sized according to Warn and installation for intended use.
  - The receiver(s) shall have one (1) rubber cover(s) provided.
- There shall be one (1) 2" x 2" x 1/4" wall steel receiver tube(s) with black hammertone powder coat paint finish located at the rear bumper for use with removable rope anchor point and/or a portable electric winch (when specified).
  - There shall be one (1) 12 VDC plug(s) with quick connect provided to power a Warn portable winch. All 12 VDC cables to be sized according to Warn and installation for intended use.
  - The receiver(s) shall have one (1) rubber cover(s) provided.



# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **LADDER / EQUIPMENT STORAGE, REAR CURBSIDE**

There shall be a ladder and/or equipment storage compartment located on the rear curbside of vehicle. The bottom of compartment shall be located at approximate top of fender height extending thru body behind the streetside compartments and the booster tank.

Access to the compartment shall be from a rear facing vertically hinged compartment door. The door shall be fabricated from 3/16" smooth aluminum with full length 14 gauge stainless steel hinge, with 1/4" stainless steel pin, a 6" stainless steel locking "D" ring handle. A polyester barrier film gasket shall be placed between stainless steel hinge and any dissimilar metals as necessary to prevent corrosion. Door shall overlap body surface to prevent entry of moisture and sealed with automotive type rubber molding to provide a weather resistant seal.

Compartment shall have a flush mounted OnScene LED light near door opening that shall be automatically activated when door is opened, and wired to compartment door ajar warning light provided in cab.

Devices to secure equipment, compartment dividers, or UHMW plastic angles, or sheeting shall be used for storage of specified equipment as required to prevent damage to equipment.

Storage shall be provided for the following ladders and equipment with proper labeling;

- One (1) 20' 3-section ladder(s). Manufacturer, model number of the ladder shall be provided in equipment section of specification, or at pre-construction meeting when provided by Lake Dillon Fire-Rescue.

## **FRONT PROTECTION PANELS**

To protect areas subject to intensive wear, scuffing or abuse, protection panels shall be installed on the front vertical body panels and wrapped around to the front compartment door opening. The protection panels shall be fabricated from 20 gauge brushed stainless steel.

## **REAR BODY HANDRAILS**

There shall be two (2) 24" vertical handrails on the rear of the body. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

## **REAR BODY HANDRAILS**

There shall be two (2) 24" horizontal handrails on the rear of the body. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

## **PUMP MODULE HANDRAILS**

There shall be two (2) 24" handrails, one (1) each side of pump module for access to upper dunnage area. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

## **FOLDING STEP(S)**

There shall be four (4) Innovative Controls polished cast aluminum folding step(s) provided and installed on completed vehicle. Each step shall be heavy duty with stainless steel spring and textured step surface meeting NFPA standards. Each step shall include an LED light.

Location(s): \_\_\_\_\_

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## REAR STEP

Two (2) Zico PS-8 manual pull-out and down step(s) shall be installed below the rear bumper. The step surface, when pulled out from its nested position, shall be approximately 8" below the rear bumper step.

## LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC

### General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

### Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125% of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10%. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

### Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage over-current protective devices. Such devices shall be readily accessible and protected against heat in excess of the over-current device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- 1) SAE J156, *Fusible Links*
- 2) SAE J553, *Circuit Breakers*
- 3) SAE J554, *Electric Fuses (Cartridge Type)*
- 4) SAE J1888, *High Current Time Lag Electric Fuses*
- 5) SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125% of maximum current for which the circuit is protected.

### Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

### Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- 1) The propulsion engine and transmission
- 2) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- 3) The radio(s) at a duty cycle of 10 percent transmit and 90% receive (for calculation and testing purposes, a default value of 5 A continuous)
- 4) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- 5) The minimum optical warning system, where the apparatus is blocking the right-of way
- 6) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- 7) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

### Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

### Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

### Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

### **12 VOLT DIAGNOSTIC RELAY CONTROL CENTER**

The 12 volt power distribution shall be conveniently located with easy access for service. All relays and circuit breakers shall be plug-in type allowing for removal for repairs without necessitating soldering or tools. The sockets mounts for both the relays and circuit breakers shall be of a design that permits the use of standard automotive type components.

The 12 volt distribution panel shall utilize printed circuit boards mounted in high strength enclosure. Each printed circuit board shall be provided with twelve (12) heavy duty independent switching relays. Each relay shall have the ability to be configured either normally open or normally closed and be protected by a 20 amp automatic reset breaker. Each circuit will be provided with a LED for visual diagnostic.

Power distribution panel shall be located in apparatus body within a protected enclosure with removable or hinged cover.

### **CAB CONSOLE 4-DOOR**

A center cab console shall be provided between the Driver's and Officer's seats. Console shall be as large as possible and fabricated of 1/8" smooth aluminum. A textured powder coat paint finish shall be provided for durability and finished appearance.

The rear portion of the console shall be provided with open top storage for notebooks or maps. Two (2) adjustable dividers shall be provided in the storage area, as required per pre-construction meeting. The forward portion of console shall be slanted for mounting of siren head, radio or 12 volt control panel, and etc, with easy access to both Driver and Officer.

The center cab console shall be extend to rear wall of 4-door cab between the forward facing outboard seats. Console shall be as large as possible and fabricated of 1/8" smooth aluminum. A textured powder coat paint finish shall be provided for durability and finished appearance.

The final design of console shall be submitted to the Lake Dillon Fire-Rescue by engineering for review.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **ROCKER SWITCH PANEL**

The control of the 12 volt equipment installed on chassis and body shall be centrally located in the cab. The individual rocker style switches shall be located on a separate electrical panel, complete with backlit name tags describing function of each individual switch. The back lighting shall have two (2) levels of intensity, low level lights activated when the vehicle lights or ignition switch is turned "On", and high level lights activated when individual switch is turned "On". An internally lighted rocker switch shall be furnished to the left of specified emergency lighting switches, and identified as "MASTER EMERGENCY SWITCH".

Switch circuitry shall be on a printed circuit board. The lights shall be solid state type and have a 100,000 hour life span.

Switch Layout (left-right): E-Master, Light Bar, Warning Lts, Front Scene, Left Scene, Rear Scene, Right Scene.

The following options shall be provided in specified console. Final layout to be determined by Lake Dillon Fire-Rescue at pre-construction meeting.

There shall be two (2) 12 VDC power plug(s) provided, one (1) in front console, and one (1) in rear console.

There shall be two (2) Blue Sea 12 VDC USB port(s) provided, one (1) in front console, and one (1) in rear console.

## **ELECTRICAL SYSTEM MANAGER**

### **LOAD MANAGEMENT**

If the total continuous electrical load exceeds the minimum continuous electrical output rating of the installed alternator(s), an Innovative Controls automatic electrical load management system shall be required. The minimum continuous electrical loads shall not be subject to automatic load management.

The apparatus 12 volt electrical system shall be provided with a system manager for:

- Monitoring chassis battery voltage
- Shedding pre-determined electrical circuits
- Sequencing pre-determined electrical circuits
- Automatically controlling chassis engine fast-idle
- Monitor master switch and parking brake applications
- Automatically control warning light modes ("Calling-For" and "Blocking Right of Way")
- Provide low voltage alarm
- Programmable control circuits
- Remote system status indicator panel

System manager shall perform all electrical functions required by current NFPA 1901 Standards.

### **BATTERY MONITORING**

The system manager shall monitor the vehicle battery voltage. When electrical loads exceed the alternator output and the voltage drops, the load manager shall start shutting down electrical outputs. The system shall shut down only as many outputs required to maintain the system voltage. A special indicator to show different states of the electrical system by flashing at rate proportional to the battery discharge.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **LOAD SEQUENCING AND SHEDDING**

The system shall be capable of sequentially switching and shedding 12 volt loads. The Master light switch starts the sequential switch when it is turned "On". Likewise turning the Master Switch "Off" will sequentially de-energize the loads.

## **BATTERY SYSTEM**

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

An onboard battery conditioner or charger or a polarized inlet shall be provided for charging all batteries. Where an onboard conditioner or charger is supplied, the associated line voltage electrical power system shall be installed in accordance with Chapter 22.

One of the following master disconnect switches shall be provided:

- 1) A master body disconnect switch that disconnects all electrical loads not provided by the chassis manufacturer
- 2) A master load disconnect switch that disconnects all electrical loads on the apparatus except the starter

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

A green "battery disconnect on" indicator light that is visible from the driver's position shall be provided.

Rechargeable hand lights, radios, and other similar devices shall be permitted to be connected to the electrical system ahead of the master disconnect switch.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within 5 seconds.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **BATTERY SWITCH**

One (1) battery "On/Off" switch in cab located within easy reach of Driver with green "BATTERY ON" pilot light that is visible from the driver's position shall be provided.

## **BATTERY SOLENOID**

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

## **BATTERY CONDITIONER**

One (1) Kussmaul model 091-9-1000 Pump-Plus 1000, single battery charger/air compressor, with 120 VAC input, and 15 amp 12 VDC amp output battery conditioner with a 12 volt, 80 psi air compressor shall be provided and installed. This system shall monitor the condition of battery(s) and provide an electrical current at variable rates to overcome battery failure. The air compressor shall maintain air pressure in the chassis air brake system. A Kussmaul bar graph type indicator panel shall be provided for showing status of battery conditioner.

## **SHORE POWER INLET**

One (1) Kussmaul 120 VAC, 20 amp Super Auto-Eject shore power inlet(s) shall be provided. The shore power connection shall automatically disengage from vehicle when chassis ignition is engaged.

The protective ground from the shoreline inlet shall be bonded to the vehicle frame.

- The outlet cover shall be red.
- The shore power plug shall be located near the Driver door area.

## **INVERTER**

A Tripp-Lite model PV700, 700 watt inverter with three (3) 120 VAC outlets shall be provided on back of center console with outlets facing upward (provide outlet protection if necessary).

## **ENGINE COMPARTMENT LIGHT**

There shall be one (1) OnScene Severe Service LED light(s) mounted in the engine compartment with integral switch with a light output of at least 20 candlepower (250 lumens). The engine compartment light(s) shall operate only when the master battery switch is turned "On".

## **MAP LIGHT**

There shall be one (1) 18-24" LED goose neck 12 volt LED map light(s) provided and installed on the officer side console area.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **CAB SPOTLIGHT**

There shall be one (1) GoLight LED 20214 motorized, black, 12 VDC, 3 Amp, spotlight(s) that operates via a wired dash mount controller with joystick and on/off button. The joystick controls the motorized 135 degree tilt of the spotlight and the motorized rotation of the light a full 370 degrees. The light continues to move while the joystick is pressed. Once any button is released, the spotlight remains locked in that position until the joystick is moved again. The dash controller also turns the light on and off, so no additional switches are required. The dash mounted remote control allows for fingertip operation and is hard wired to the searchlight.

The Golight is mounted to the surface of vehicle using (4) stainless steel screws and a rubber gasket for a quick, safe and secure attachment. Light shall have a 3 year limited warranty.

## **CHASSIS HEADLIGHT WIG/WAG**

A chassis headlight wig/wag flashing unit shall be provided. The headlight flasher shall shut down when the parking brake is engage for "Blocking Mode".

The lights shall be controlled at the switch panel in cab.

## **CAB HAZARD WARNING LIGHT**

A Truck-Lite red LED flashing ligh shall be provided and located in the driving compartment and be illuminated automatically whenever the vehicles parking brake is not fully engaged and any of the following conditions exist:

- Any passenger or equipment compartment door is not closed.
- Any ladder or equipment rack is not in the stowed position.
- Stabilizer system is not in its stowed position.
- Powered light tower is not stowed.
- Any other device permanently attached to the apparatus is open, extended, or deployed in a manner that is likely to cause damage to the apparatus if the apparatus is moved.

Compartments and equipment meeting all of the following conditions shall be permitted to be exempt from being wired to the hazard light:

- The volume is less than or equal to 4 ft<sup>3</sup> (0.1 m<sup>3</sup>).
- The compartment has an opening less than or equal to 144 in.<sup>2</sup> (92,900 mm<sup>2</sup>).
- The open door does not extend sideways beyond the mirrors or up above the top of the fire apparatus.
- All equipment in the compartment is restrained so that nothing can fall out if the door is open while the apparatus is moving.
- Manually raised pole lights with an extension of less than 5 ft (1.5 m).

The hazard light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

An audible alarm shall be provided for the door ajar light.

## **BACK-UP ALARM**

An electronic back-up alarm shall be supplied and installed by the cab/chassis manufacturer. The back-up alarm shall actuate automatically when the transmission gear selector is placed in reverse.



# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **REAR VIEW CAMERA**

There shall be one (1) ASA Voyager rear observation camera system provided and installed on completed unit. The system shall include one (1) model VCC150 high resolution CCD color camera installed on the rear body.

The camera image shall be displayed on a model AOM713, 7" color flat panel display (up to 3 camera inputs) located within the driver's range of view.

## **TAIL LIGHTS**

Rear body tail lights shall be vertically mounted and located per Federal Motor Vehicle Safety Standards, FMVSS and Canadian Motor Vehicle Safety Standards CMVSS. The following lights shall be furnished;

- Two (2) Whelen M6 Series M6T amber LED turn lights
- Two (2) Whelen M6 Series M6BTT red LED stop/tail lights
- Two (2) Whelen M6 Series M6BUW clear LED back-up lights with clear lens

Each light above shall be mounted in an M6FC chrome finish bezel.

## **MIDSHIP MARKER/TURN SIGNAL**

Two (2) Whelen model T0A00MAR 2" round amber LED midship body clearance marker/turn signal lights shall be provided and installed, one (1) light on each side of the body, in forward wheel well of rear axle. Midship marker/turn lights shall be wired to the headlight circuit of the chassis.

## **MARKER LIGHTS**

The body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) and Canadian Motor Vehicle Safety Standards (CMVSS) regulations. All body clearance lights shall be Truck-Lite Model 18 LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

## **CAB STEP LIGHTS / GROUND LIGHTS**

There shall be two (2) OnScene 8" Access LED light(s) installed on the vehicle capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting designed to provide illumination on areas under the driver and crew riding area exits shall be switchable but activated automatically when the exit doors are opened.

Ground light activate with barking brake and turn signal.

## **LICENSE PLATE LIGHT**

One (1) Arrow #437 chrome plated LED license plate light shall be installed on the rear of the body. License plate light shall be wired to the headlight circuit of chassis. A fastener system shall be provided for license plate installation.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **ELECTRONIC SIREN**

One (1) Whelen model 295SLSA1 electronic siren control with selectable 100 or 200 watt output, hands-free operation, user selectable siren tones, park kill, and standard hard wired microphone shall be provided and installed in cab within easy reach of Driver. Siren power shall be wired through the master warning light switch.

## **SIREN SPEAKER**

One (1) Whelen model SA314A 100 watt aluminum, 6.4" x 6.1" x 3.1" deep siren speaker shall be provided behind the front bumper. The solid state siren speaker shall be vibration resistant. The SA314A shall comply with California Title XIII, Class A, and SAE J1849 requirements and with OSHA 1910.95 Guidelines regarding "Permissible Noise Exposure". All mounting hardware shall be stainless steel and covered by a two year factory warranty.

The siren speaker shall be located on the streetside of front bumper.

## **FRONT LED FLOODLIGHT**

One (1) Rigid Industries E-Series model 120312, 20" combination spot/flood LED light(s) with white housing color and cradle mount brackets shall be provided on front of vehicle. The E-Series 20" LED light(s) shall have 9,200 lumen output each.

Each light shall be wired directly to the 12 VDC electrical system with stranded copper wire. The floodlights shall be protected with circuit breakers rated at the proper amperage and wire size.

Front scene light located on grill.

The lights shall be controlled at the cab supplied "fog light" switch in cab.

## **SIDE LED SCENE LIGHTS**

There shall be four (4) Whelen M9 Series Model M9LZC , 9" x 7" surface mounted scene light(s) provided on the upper body. Light quantity shall be divided equally per side. The M9LZC configuration shall consist of 24 clear Super-LEDs and a clear gradien optic polycarbonate lens with chrome flange. The M9LZC series light shall have 6,500 useable lumens each. The scene light is covered by a five year factory warranty.

Two (2) switches shall be provided, one (1) for the streetside scene lights, and one (1) for the curbside scene lights.

The lights shall be controlled at the switch panel in cab, and pump panel.

## **REAR LED SCENE LIGHTS**

Two (2) Whelen M9 Series Model M9LZC , 9" x 7" surface mounted scene light(s) shall be provided on the upper rear body to light the work area. The M9LZC configuration shall consist of 24 clear Super-LEDs and a clear gradien optic polycarbonate lens with chrome flange. The M9LZC series light shall have 6,500 useable lumens each. The scene light is covered by a five year factory warranty

The above scene lights shall light to a level of at least 3 fc (30 lx), measured at 25 equally spaced points on a 2.5 ft (750 mm) grid with in a 10 ft x 10 ft (3 m x 3m) square to the rear of vehicle.

The lights shall be controlled at the switch panel in cab and at pump panel.

The rear scene lights shall also be activated when the apparatus is in reverse.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **TRAFFIC ADVISOR LIGHTS**

Traffic Advisor lights shall be comprised of six (6) Whelen ION series amber Wide Angle Super-LED lights with clear lens. Lights shall be individually mounted with chrome bezels to the rear face of the vehicle and evenly distributed, if split by a hose bed, or walkway.

The lights shall be controlled by a Whelen TACTL5 control located in cab dash or center console area and provide; Left Arrow, Right Arrow, Center Out, and Wig-Wag patterns. The LED display on the control head shall replicate the Traffic Advisor's directional sequence. The TACTL5 shall have a rear panel dip switch for the ability to set eight additional Scan-Lock™ flash patterns. The wig-wag light pattern shall be activated with the E-Master and can be switched to the other patterns at any time through the control panel.

## **DAVID CLARK INTERCOM SYSTEM**

The following David Clark intercom system shall be provided and installed to improve the safety of firefighters and rescue professionals through enhanced communication and hearing protection. System shall have the following major components as minimum;

Provide total of four (4) position David Clark intercom system with capabilities of dual radio transmit at driver and officer positions.

One (1) - U3800, Master Station  
Two (2) - U3805, Radio Junction Module  
Two (2) - U3816, Dual Radio Interface Module  
Four (4) - C3821-05, Jumper Cords  
Two (2) - C3812, 12' Jumper Cords  
One (1) - C3820, Power Cord  
Two (2) - C3821-RD1, Radio Cord  
Four (4) - H3442, Headsets

## **INTERCOM SYSTEM INSTALLATION**

The above listed intercom system shall be installed in the cab locations as follows;

### **Front of Cab**

- Driver's – Mounted above the right shoulder position on ceiling.
- Officer's – Mounted above the left shoulder position on ceiling.

### **Rear Crew Area**

- Driver's side forward facing – Above the right shoulder on the rear wall or ceiling.
- Officer's side forward facing – Above the left shoulder on the rear wall or ceiling.

Intercom worksheet on file.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **WARNING LIGHT PACKAGE**

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four (4) warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four (4) zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two (2) separate signaling modes during emergency operations. One (1) mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One (1) mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two (2) signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

Steadily burning, non flashing optical sources shall be permitted to be used.

## **UPPER LEVEL OPTICAL WARNING DEVICES**

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## ZONE A - FRONT WARNING LIGHTS

There shall be one (1) Whelen Freedom F4N0VLED LED 60" lightbar permanently mounted to the cab roof.

The lightbar configuration (streetside to curbside) shall be:

<u>SECTION</u>	<u>INTERNAL COMPONENTS</u>	<u>LENS COLOR</u>
1	Red Rear Corner LED	Clear
2	Red Front Corner LED	Clear
3	BlueLong Super-LED	Clear
4	White Long Super-LED	Clear
5	Red Long Super-LED	Clear
6	BlueLong Super-LED	Clear
7	Opticom	Clear
8	Opticom	Clear
9	Blue Long Super-LED	Clear
10	Red Long Super-LED	Clear
11	White Long Super-LED	Clear
12	Blue Long Super-LED	Clear
13	Red Front Corner LED	Clear
14	Red Rear Corner LED	Clear

All clear lights shall shut down when the parking brake is set to comply with "Blocking" mode requirements as outlined in NFPA 1901.

WeCad on file.

The lightbar(s) shall be separately controlled at switch panel in the cab.

## GTT OPTICOM

A GTT Opticom model 795H Infrared LED emitter light with built-in power supply shall be provided inside the specified light bar. Adding the Opticom LED may re-configure the standard light(s) in specified light bar. The LED technology uses less power, has a longer life, and non-visible to the human eye.

The Opticom emitter light shall be activated with light bar and de-activated when the park brake is set and the vehicle is in blocking mode.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## ZONES B AND D - SIDE WARNING LIGHTS

### UPPER REAR CORNER WARNING LIGHTS

There shall be two (2) Whelen M9 series Red Linear Super-LED lights (M9RC) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

### UPPER FORWARD CORNER WARNING LIGHTS

There shall be two (2) Whelen M9 series Blue Linear Super-LED lights (M9BC) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

## ZONE C - REAR WARNING LIGHTS

There shall be two (2) Whelen M6 series linear Super-LED lights provided, one (1) blue streetside and one (1) red curbside. Each light shall have a clear lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

## LOWER LEVEL OPTICAL WARNING DEVICES

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1600 mm) above level ground.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

## ZONE A - FRONT WARNING LIGHTS

There shall be two (2) Whelen M4 series Linear Super-LED lights provided, one (1) blue on streetside, and one (1) red on curbside. Each light shall have a clear lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

## ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

There shall be two (2) Whelen M6 series Red Linear Super-LED lights (M6RC) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## ZONES B AND D - BODY LIGHT (BODY WHEELWELL AREA)

There shall be two (2) Whelen ION Blue V-Series Super-LED surface mount lights (IONSV3BC) with combination 180° warning and puddle lights provided, one (1) each side. Puddle lights will be turned on with specified scene lighting. Each light shall have a clear lens and chrome die cast flange.

The lights shall be controlled at the switch panel in cab.

## ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Whelen M6 series Red Linear Super-LED lights (M6RC) provided, one (1) each side. Each light shall have a clear lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

## ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Whelen M6 series Linear Super-LED lights provided, one (1) blue on curbside, and one (1) red on streetside. Each light shall have a clear lens and chrome flange.

The lights shall be controlled at the switch panel in cab.

## WILDLAND SIDE MOUNT PUMP MODULE

The 74" (measured laterally across vehicle width) x 29" wide side mount pump enclosure shall be removable and supported from the chassis frame rails with spring type body mounts. This enclosure shall allow independent flexing of the pump enclosure from the body and allow for quick removal. The support structure shall be constructed of extruded aluminum tubing and angle.

All pump suction and discharge controls are to be mounted on the driver side pump operator's panel so as to permit operation of the pump from a central location. The fire pump, valves and controls shall be accessible for service and maintenance as required by applicable sections of NFPA standards.

The "master" gauges shall be suitably enclosed and mounted on a full pump compartment width "hinged" gauge panel constructed of the same material as the pump operators control panel, allowing access to the backside of all gauges and gauge lines. The individual gauges shall be mounted inline with the control handle or adjacent to the control handle. Panel is to include a stainless steel piano hinge, flush mounted chrome plated trigger latch, and stainless steel cable end stops. Electrical wiring and all gauge lines shall be properly tie wrapped to prevent kinking or cutting of the lines when the panel is opened.

The following controls and equipment shall be provided on the pump panel or within the pump enclosure:

- 1) Electric primer.
- 2) Pump and plumbing area service lights.
- 3) Pressure control device and throttle control.
- 4) Fire pump and engine instruments.
- 5) Pump intakes and discharge controls.
- 6) Master intake and discharge gauges.
- 7) Tank fill control.
- 8) Tank suction control.
- 9) Water tank level gauge.
- 10) Pump panel lights.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **PUMP COMPARTMENT SERVICE ACCESS**

The front portion of the pump compartment structure (directly behind the chassis cab) shall not be overlaid to provide an opening for access to the midship fire pump.

## **PUMP PANEL - SIDE MOUNT**

The pump operator's panel, along with the lower streetside and curbside pump panels shall be constructed of smooth plate aluminum with powder coated paint finish, fastened to the pump enclosure with 1/4" stainless steel bolts.

The instrument area shall have a stainless steel continuous hinge that shall swing towards the front of the module for easy access to gauges.

## **STREETSIDE PUMP PANEL - BOLTED**

The streetside pump panel shall be fastened to the pump enclosure with 1/4" stainless steel bolts and nutserts.

## **LOWER CURBSIDE PUMP PANEL - BOLTED**

The curbside pump panel shall be fastened to the pump enclosure with 1/4" stainless steel bolts and nutserts.

## **PUMP MODULE EQUIPMENT STORAGE COMPARTMENT**

There shall be one (1) equipment compartment located on the upper curbside of the pump module. It shall have dimensions of approximately 22" wide x 42" high. The clear door compartment dimensions shall be 20.5" wide x 40" high x 12" deep with the door closed. An OnScene LED light shall illuminate the interior of the compartment when the door is open.

The equipment compartment shall be provided with a flush style hinged door. The doors shall be provided with a high quality, continuous double seal type weather stripping to prevent moisture and dust from entering the exterior compartment. The door shall be double pan design with the outer door material being 1/8" aluminum door with a 1/8" aluminum removable inner liner that shall have a natural finish to provide reflective qualities during night operations. The vertically hinged door shall have a gas shock and polished stainless steel 1/4" piano hinge.

The door latch shall be an Eberhard locking slam latch, with a chrome "D" ring with a 5-degree bend for easier grasping of each door handle with gloved hands. The door shall be provided with a keyed lock.

The exterior of the door shall be painted to match the lower job color. The interior shall be painted to match the compartment interior paint specified.

There shall be two (2) adjustable shelf(s) approximately 12" deep, fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.

There shall be two (2) large removable panels provided on the inside of the compartment. These panels shall provide an opening for service access to the right side of the interior of the pump module and to the bottom side of the diesel pump.

## **WHEEL CHOCK COMPARTMENT**

Below (or incorporated into) the equipment storage compartment shall be a wheel chock compartment. This compartment shall be equipped with a plate lap style 1/8" aluminum door mounted on a piano hinge with a push latch. The compartment shall have clear door dimensions of 8.3" wide x 13.5" high x 13-.5" deep with the door closed.



# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **PUMP COMPARTMENT TOP OVERLAY**

The top of the pump compartment shall be overlaid with materials of a non slip 1/8" NFPA compliant aluminum treadplate.

## **DUNNAGE AREA**

A single wall 3/16" aluminum diamond plate dunnage area shall be provided above the pump house compartment for equipment mounting and storage space. The dunnage area shall be as wide as possible from side to side, and as deep as allowed with the available space.

## **STREETSIDE RUNNING BOARD - SIDE MOUNT PANEL**

The streetside pump panel shall be equipped with a side running board. The running board shall extend along the width of the pump module.

The running board stepping surface shall be constructed of aluminum NFPA compliant tread plate, bolted in place with stainless steel fasteners.

- One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.

## **CURBSIDE RUNNING BOARD - SIDE MOUNT PANEL**

The curbside pump panel shall be equipped with a side running board. The running board shall extend along the width of the pump module.

The running board stepping surface shall be constructed of aluminum NFPA compliant tread plate, bolted in place with stainless steel fasteners.

- One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.

## **PUMP MODULE FINISH**

The upper exterior sides above pump panels shall be constructed of 1/8" smooth plate aluminum and painted body color. The upper exterior front and rear of pump module shall be constructed of 1/8" treadplate aluminum.

## **PUMP HEAT PAN ENCLOSURE**

No pump heat pan enclosures are required to protect pump from freezing.

## **PUMP MODULE HEATER**

The pump module shall be provided with one (1) Red Dot 35,000 BTU hot water type heater(s). The heater(s) shall be connected to the chassis engine cooling system and have three-speed, 12 volt blower. The cooling system lines shall be insulated and be provided with 1/4 turn shut-off valves to isolate system, if required.

The pump operator's panel shall have an Innovative Controls switch panel for heat control switch with indicator light. Switch shall be constantly illuminated and labeled.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## CROSS LAY

The specified pump module shall have one (1) cross lay(s). The cross lay hose bed(s) shall be located in the upper portion of the pump module.

The cross lay area shall be located at the front of side pump module and at the rear of top control module. The cross lay area shall span the entire width of the pump module.

## CROSS LAY TRIM

Brushed stainless steel trim shall be installed at the openings on each side of the cross lay hose bed area. The trim shall reduce the chaffing of the hose jacket on the edges of the bay area.

The divider(s) between the hose bed areas shall be fabricated from 3/16" smooth aluminum and mounted in a channel on each end for adjustability.

Removable slotted aluminum flooring shall be provided for the hose bed area.

The pump module cross lay(s) shall have two (2) OnScene Rough Service 9" LED lights provided, one (1) each end to light the interior cross lay hose bed area.

Each end of hose bed shall have a black nylon style webbing cover. The covers will be mechanically fastened at the top of the hose bed and the bottom edges will be secured using elastic cord and shoulder bolts.

A safety sign FAMA22, which warns of the need to secure hose, shall be visible to personnel at each hose storage area.

## CROSS LAY BED COVER

A 1/8" aluminum tread plate hinged cover shall be provided over the crosslay beds with netting style end flaps and full length stainless steel piano hinge. Stops shall be provided to protect cab or other adjacent body components. The hinge shall be located on the forward section of the cover, closest to the chassis cab.

## HALE MBP SINGLE STAGE FIRE PUMP

### PUMP ASSEMBLY

1. The pump shall be of a size and design to mount on the chassis rails of commercial and or a custom truck chassis, and have the capacity of up to 1,000 GPM (4,000 LPM), NFPA 1901 rated performance. **Pump to be rated at 750 GPM.**
2. The entire pump shall be assembled and tested at the pump manufacturer's factory.
3. The pump shall be driven by a the truck transmission mounted PTO. The engine shall provide sufficient horsepower and RPM to enable pump to meet and exceed its rated performance within the torque rating of the PTO, truck transmission and drive line components.
4. The entire pump shall be hydrostatically tested to a pressure of 600 PSI. The pump shall be fully tested at the pump manufacturer's factory to the performance spots as outlined by the latest NFPA Pamphlet No. 1901. Pump shall be free from objectionable pulsation and vibration.
5. The pump body and related parts shall be of fine grain alloy cast iron, with a minimum tensile strength of 30,000 PSI (2069 bar). All metal moving parts in contact with water shall be of high quality bronze or stainless steel. Pump utilizing castings made of lower tensile strength cast iron not acceptable.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

6. Pump body shall be vertically split, on a single plane for easy removal of entire impeller assembly including clearance rings.
7. Pump shaft to be rigidly supported by two bearings for minimum deflection. The bearings shall be heavy-duty, deep groove ball bearings in the gearbox and they shall be splash lubricated.
8. The pump impeller shall be hard, fine grain bronze of the mixed flow design; accurately machines, hand-ground and individually balanced. The vanes of the impeller intake eye shall be hand ground and polished to a sharp edge, and be of sufficient size and design to provide ample reserve capacity utilizing minimum horsepower.
9. Impeller clearance rings shall be bronze, easily renewable without replacing impeller or pump volute body.
10. The pump shaft shall be heat-treated, electric furnace, corrosion resistant stainless steel. Pump shaft must be sealed with double-lip oil seal to keep road dirt and water out of gearbox.

### **ANODES**

To reduce the effect of galvanic action, the fire pump shall be equipped with two (2) easily replaceable sacrificial catalytic action 3/4" magnesium anodes. One anode shall be installed on the inlet (suction) side of the system, and one anode shall be installed on the pressure (outlet) side of the main fire pump.

### **CERTIFICATION**

The pump will perform and meet the following tests:

100% of rated capacity @150 PSI net pump pressure.  
100% of rated capacity @ 165 PSI net pumps pressure.  
70% of rated capacity @ 200 PSI net pump pressure.  
50% of rated capacity @ 250 PSI net pump pressure

Pump shall be tested at manufacturer under full NFPA suction conditions.

### **GEARBOX**

1. Pump gearbox shall be of sufficient size to withstand up to 16,000 lbs. ft. of torque of the engine. The drive unit shall be designed of ample capacity for lubrication reserve and to maintain the proper operating temperature..
2. The gearbox drive shafts shall be of heat-treated chrome nickel steel and at least 2-3/4 inches in diameter, on both the input and output drive shafts. They shall withstand the full torque of the engine.
3. All gears, both drive and pump, shall be of highest quality electric furnace chrome nickel steel. Bores shall be ground to size and teeth integrated and hardened, to give an extremely accurate gear for long life, smooth, quiet running, and higher load carrying capability. An accurately cut spur design shall be provided to eliminate all possible end thrust. (No exceptions.)
4. The pump ratio shall be selected by the apparatus manufacturer to give maximum performance with the engine and transmission selected.
5. If the gearbox is equipped with a power shift, the shifting mechanism shall be a heat treated, hard anodized aluminum power cylinder, with stainless steel shaft. An in-cab control for rapid shift shall be provided that locks in road or pump.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

6. For automatic transmissions, three green warning lights shall be provided to indicate to the operator(s) when the pump has completed the shift from Road to Pump position. Two green lights to be located in the truck driving compartment and one green light on pump operators panel adjacent to the throttle control. For manual transmissions, one green warning light will be provided for the driving compartment. All lights to have appropriate identification/instruction plates.

### **PAINT FINISH**

The paint finish will be black finish paint.

### **PUMP DRIVE SYSTEM**

The water system pump shall be driven by a Chelsea "Hot-Shift" transmission PTO and mounted directly to the transmission of the chassis. The drive line shall be hollow tube type, with heavy duty universals and splined shaft to allow movement of the chassis components and pump.

The engagement of the PTO shall be in the chassis cab with a rocker switch and red pilot light to note engagement of the PTO.

The power supply to the PTO engagement control shall be wired to a neutral position transmission switch to prevent engagement unless the vehicle is in neutral with the parking brake set.

Two (2) green indicator lights shall be supplied in the chassis cab. One (1) light shall be energized when the chassis transmission is in neutral and shall be labeled "OK TO PUMP", the second light shall engage when the pump drive (PTO) has been engaged and shall be labeled "PUMP ENGAGED".

One (1) green indicator light shall be supplied at the Pump Operator's panel adjacent to the engine hand throttle. The green light shall be energized when both the chassis transmission is in neutral and the pump drive (PTO) has been engaged. Green light shall be labeled "OK TO PUMP".

Model part number shall be Chelsea 859 series.

Double check the model number and ratio with engineering before ordering the PTO on the chassis.

### **MECHANICAL SEALS**

The Hale pump shall be equipped with a mechanical seal in place of pump packing on the suction (inboard) side of the pump. The mechanical seal must be two (2) inches in diameter and shall be spring loaded, maintenance free and self-adjusting. Mechanical seal construction shall be a carbon sealing ring, stainless steel coil spring, Viton rubber cup, and a tungsten carbide seat with Teflon backup seal.

### **1/2" PUMP COOLER LINE**

There shall be a 1/2" line installed from the discharge side of the pump to the water tank. The line shall be used to cool the pump during long periods of pumping when water is not being discharged. The pump cooler shall be controlled with a quarter-turn ball valve on main pump panel, and shall be clearly labeled "Pump Cooler".

### **PUMP COOLER CHECK VALVE**

There shall be a check valve installed in the pump cooler line to prevent tank water from back flowing into the pump when it is not in use.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **HALE FIVE YEAR PUMP WARRANTY**

The fire pump shall be warranted by Hale for a period of five (5) years from the date of delivery to the Lake Dillon Fire-Rescue. Within this warranty period Hale shall cover parts and labor for the first two (2) years and parts only for years three (3) through five (5).

## **MANUFACTURER FIRE PUMP TEST**

The pump shall undergo a manufacturer's test per applicable sections of NFPA 1901 standards, prior to delivery of the completed apparatus.

The test shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming device tests, and the vacuum test.

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 500 psi (3400 kPa) for a minimum for 10 min. The pump shall be fully tested at the pump manufacturer's factory to the performance specifications as outlined by applicable NFPA 1901 standards.

The results of this test shall be furnished with the vehicle on delivery.

## **FIRE PUMP TEST LABEL**

A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve

The pump shall comply with the applicable requirements of "Standard for Fire Apparatus 1901, latest edition.

The pump shall be capable of producing fire streams that are free from objectionable pulsation under all normal operating conditions.

## **SAFETY SIGN**

A safety sign FAMA25, which warns of the need for training prior to operating the apparatus, shall be located on the pump operators panel.

## **ALTITUDE REQUIREMENT**

The apparatus shall be designed to meet the specified rating at 9,100 feet (2,773 meters) altitude.

## **PUMP DRAIN VALVE**

A manifold drain valve assembly shall be supplied to drain the entire pump and manifold. The drain valve assembly shall consist of a stainless steel plunger in a bronze body with multiple ports.

## **PUMP DRAIN CONTROL**

The pump drain shall be controlled at the pump operator's panel and identified as "Pump Drain". The control shall be a Class1 round 1/4 turn handle control that is easily actuated with a gloved hand.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **AIR PRIMING PUMP CONTROL AT PUMP PANEL**

The priming pump shall be a Trident Emergency Products compressed air powered, high efficiency, multi-stage venturi based AirPrime System.

The priming pump shall be rigidly attached to the pump transmission and utilizes air supplied from the chassis air system to operate the pump primer. The AirPrime is more efficient and reliable than the conventional electric motor driven primers, and virtually eliminates the impact load on the vehicles electrical system improving the reliability of the vehicle. AirPrime also improves performance in the elapsed time for establishing water supply resulting in improved fire ground operations and safety.

A manual rocker switch with Auto-Prime / Off / Manual-Prime shall be provided on main pump operator's panel.

The primer shall be capable of priming the pump through a 20' section of suction hose with a 10' lift within 30 seconds for pumps less than 1,500 gpm, and 45 seconds for pumps 1,500 gpm and larger.

## **DISCHARGE RELIEF VALVE**

The discharge pressure relief shall be controlled by the electronic engine controlled device as specified.

## **6" SUCTION INLET - STREETSIDE**

One (1) 6" (150 mm) un-gated suction intake shall be installed on the streetside pump panel to supply the fire pump from an external water supply. The threads shall be 6" NH male threads.

The intake shall be provided with a removable screen.

## **SHORT SUCTION TUBE**

The specified pump intake shall be provided with a short suction tube. Suction tube shall have built-in zinc anode protection and multiple suction flanges per pump configuration.

- One (1) rigid 6" NHF x 5" NHM rigid adapter with k-chrome finish shall be provided on 6" steamer intake.

## **SUCTION CAP**

The suction inlet shall be equipped with a 5" NH chrome plated, long handled, cap capable of withstanding 500 psi.

## **HEAT EXCHANGER**

A heat exchanger shall be provided on the pump driving engine cooling system that uses water from the discharge side of the pump to cool the engine coolant through the use of a closed heat exchanger. The water from the pump and the engine coolant shall not be intermixed. This cooling system shall be controlled by a 1/4 turn valve on the pump operator's panel.

## **INTAKE RELIEF VALVE**

There shall be an Akron model 59 intake relief valve factory set to 125 PSI installed on the suction side of the pump. The system shall be controlled by an adjustable valve and designed to prevent vibration from altering the setting of the valve. Provisions for adjusting or servicing the valve {will/shall} be provided. The relief outlet shall be directed below the pump with the discharge terminating in a 2-1/2" NSTM connection. The discharge shall be away from the pump operator and labeled "DO NOT CAP".

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **AUXILIARY DIESEL PUMP**

There shall be a Darley 1-1/2 AGE diesel engine auxiliary pump provided in upper pump module. The auxiliary pump shall only provide pressure to all 2" discharge valves including the hose reel and be capable of re-circulating tank water through the 2" tank filler valve.

The pump shall be plumbed in common with that of the main pump for pump and roll applications. The pump shall have a minimum rated capacity of 160 GPM @ 245 PSI.

The pump shall be mounted above the main fire pump and its engine fuel and electrical system shall be common with the truck chassis. The oil drain will be extended below the chassis frame rail.

## **ENGINE**

Kubota V1505 Diesel, 39 HP naturally aspirated, 4 cylinders, liquid-cooled, 12-volt, electric start, 40 amp alternator, pressure lubed, oil and fuel pump filters. The pump power unit shall be furnished as follows:

Dry element, direct mounted air filter with stainless steel air intake ember screen.

Exhaust system equipped with USDA approved spark arrestor and appropriate heat shields to protect various components and personnel from heat related damage/injuries from high exhaust pipe temperatures. The exhaust system shall be routed vertically above the fire apparatus discharged away from any working surfaces and be manufactured from heavy duty aluminized steel exhaust pipe to meet the manufacturer's specifications.

Spin on automotive type fuel and oil filters that meet the engine manufacturer specifications.

Fuel system shall be designed to draw fuel from the apparatus fuel tank thru the use of an inline 12 volt automotive electric fuel pump, Stewart Warner #235A-D, or equal. The fuel tank pick-up tube shall be designed so as to assure the auxiliary engine will not exhaust the fuel supply of the vehicle. (minimum 10 gallon reserve). A marine grade one way check valve shall be installed in the fuel line to eliminate the possibility of air locks in the fuel line.

A 1/2" crankcase oil drain extension line routed below the frame to facilitate oil changes, with Aeroquip style hose, threaded fittings and drain plug.

12 volt electric start.

Removal of the auxiliary engine alternator is acceptable if an OEM fan belt idler is available and installed.

## **1-1/2 AGE PUMP FEATURES**

Aluminum alloy casing and discharge valve. Sulfuric anodized aluminum alloy gear case. Bronze impeller and wear rings. Stainless steel impeller shaft. Heat treated alloy steel helical gears. Ball bearing construction. Adjustable throttle. 2" NPT suction. 2-1/2" or 1-2/2" NPT discharge.

## **DIMENSIONS**

41" L x 24" W x 42 1/2" H, 523 lbs. (237 kg)

## **PUMP PERFORMANCE**

160 GPM (605 L/M) @ 245 PSI (16.9 bar)

80 GPM (303 L/M) @ 310 PSI (21.4 bar)

25 GPM (94 L/M) @ 300 PSI (20.7 bar)

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **REMOTE START IN CAB**

There shall be a remote start assembly provided in cab area for the portable pump. This panel shall contain the following:

- Auxiliary pump water pressure gauge (Class 1 dry type, 0-400 psi, white face with black numerals, LED back lighted (red in color).
- Vernier throttle cable
- Pump ignition on/off/start switch
- Low Oil Pressure indicator light
- Engine Overheat indicator light
- Glow Plug operational light
- Primer

## **AUXILIARY PUMP PRESSURE GAUGES**

All auxiliary pump pressure gauges shall be 0/400 lbs. liquid less style, stainless steel case, chrome bezel with a white face and black numerals. Two (2) gauges shall be supplied; one (1) 2" mounted on the pump operator's panel, and one (1) 2-1/2" mounted inside the cab within clear view of the vehicle operator's position and labeled as to their function. The in-cab gauge shall be an LED back lighted style gauge, red in color. The light shall be controlled by the auxiliary pump ignition switch and both gauges shall be properly labeled as to their function.

## **AUXILIARY PUMP CONTROLS**

An auxiliary pump control panel and a back lighted pressure gauge shall be provided inside the apparatus cab located in an area readily accessible to the vehicle operator. A second set of controls and pressure gauges shall be located on the left exterior main pump operator's panel.

The auxiliary pump engine control switches shall be marine grade weather proof toggle type switches. Key type ignition switches will not be provided. The apparatus electrical system (Master Switch) shall provide the power for the operation of the auxiliary pump assembly.

The wiring for the auxiliary pump assembly shall be run in a separate loom isolated from the main apparatus wiring loom. The pump engine ignition circuit shall be wired so that the pump may be started from either control panel without regard to the position of the same switch at the other location. The mounting locations for the pump controls and pressure gauges shall be in cab and left pump panel controls shall each consist of the following:

- Vernier cable type adjustable throttle controls on both pump panels (lockable type). Electronic throttle controls shall not be provided.
- Ignition and Kill switch.
- Ignition "on" green panel light.
- Starter button.
- Low oil pressure indicator lamp.
- Coolant overheat indicator lamp.
- Pump pressure gauges, shall be located in the cab and on the left pump panel.

The in-cab pressure gauge shall be back-lighted Red and the light shall be controlled by the auxiliary pump ignition switch. Note: Glow plugs (if necessary) shall be automatically controlled by the ignition switch.

An electric hour meter shall be provided for the auxiliary pump for the recording of pump operating hours. The hour meter shall be remote mounted on either pump panel and must be labeled "Auxiliary Pump Hours" and in a location where it can be easily read.



# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **AUXILIARY PUMP PLUMBING**

The auxiliary pump shall be plumbed in common with the main pump and shall only provide discharge pressure and foam concentrate to all 1" and 2" discharge valves. Plumbing between the tank sump or main manifold and the auxiliary pump suction eye shall be 2" schedule 10 stainless steel with Victaulic couplings, Gates 4684CF 2" flexible wire reinforced suction hose with threaded fittings or combination of both.

A 2" one way full flow check valve shall be installed in the auxiliary pump suction hose as close to the tank sump as possible to ensure that the auxiliary pump remains primed at all times.

## **PORTABLE PUMP PIPING**

The inlet to the diesel pump shall be connected to the 4" intake manifold for the PTO pump with 2" stainless steel pipe and wire reinforced high pressure hose coupled with stainless steel fittings. There shall be a 2" check valve at the connection to the 4" intake manifold to prevent back flow from the 2" line with the 4" line under vacuum.

The discharge of the diesel pump shall be piped with 2" stainless steel pipe and wire reinforced high pressure hose coupled with stainless steel fittings to a double check valve. The other inlet to the double check valve shall be connected to the PTO pump pressure side. The double check valve shall prevent water from the PTO pump and the diesel pump from back feeding under pressure. The check valve outlet shall feed the foam manifold upstream of the foam system check valve.

## **PUMP PANEL CONTROL**

The auxiliary pump shall have a control panel located on the midship pump module operator's position. This panel shall contain the following:

- Auxiliary pump water pressure gauge (Class 1 dry type, 0-400 psi, white face with black numerals).
- Vernier throttle cable
- Pump ignition on / off / start switch
- Low Oil Pressure indicator light
- Engine Overheat indicator light
- Glow Plug operational light
- Primer

## **AUXILIARY PUMP MOUNTING**

The pump and water cooled diesel power unit assembly shall be mounted on a sub frame on the upper right side of the apparatus above the main pump module and in such a manner so as to eliminate vibration while operating and will provide suitable access for performing routine maintenance. The pump and power unit assembly shall be designed so the entire assembly may be easily removed as a unit to gain access to plumbing or components below.

A slotted hinged cover with suitable latches shall be provided over the pump and power unit assembly. The area around the assembly shall remain open for maintenance and air circulation and the radiator shall be located behind a removable or swing-away expanded metal screen. All parts (e.g. auxiliary pump, power unit and bracketing) shall be commercially available.

Unit shall run off the chassis fuel tank (provisions will need to be made on tank) with a 1-way check valve for fuel feed to pump must be accessible.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **FOAM SYSTEM**

The apparatus shall be equipped with a FoamPro 2001 electronic, fully automatic, variable speed, direct injection, discharge side foam proportioning system. The system shall be capable of handling Class A foam concentrates and most Class B foam concentrates. The foam proportioning operation shall be based on direct measurement of water flows, and remain consistent within the specified flows and pressures. System must be capable of delivering accuracy to within 5% of calibrated settings over the advertised operation range when installed according to factory standards. The system shall be equipped with a digital electronic control display suitable for installation on the pump panel. Incorporated within the control display shall be a microprocessor that receives input from the system flowmeter(s), while also monitoring foam concentrate pump output, comparing values to ensure that the operator preset proportional amount of foam concentrate is injected into the discharge side of the fire pump.

Paddlewheel-type flowmeter(s) shall be installed in the discharges specified to be "foam capable." When the use of more than one flowmeter is required, an interface electronics module will be provided to totalize these flows and send the flow total to the microprocessor in the computer control display.

The digital computer control display shall enable the pump operator to perform the following control and operation functions for the foam proportioning system:

- Provide push-button control of foam proportioning rates from 0.1% to 9.9%, in 0.1% increments
- Show current flow-per-minute of water
- Show total volume of water discharged during and after foam operations are completed
- Show total amount of foam concentrate consumed
- Simulate flow rates for manual operation
- Perform setup and diagnostic functions for the computer control microprocessor
- Flash a "low concentrate" warning when the foam concentrate tank(s) runs low
- Flash a "no concentrate" warning and shut the foam concentrate pump off, preventing damage to the pump, should the foam tank(s) empty

A 12-volt electric motor drive positive displacement foam concentrate pump, rated up to 2.5 gpm (9.5 L/min) @ 150 psi with operating pressures up to 400 psi (27.6 BAR), shall be installed in a suitable, accessible location. The system will draw a maximum of 40 amps @ 12 VDC. A pump motor electronic driver (mounted to the base of the pump) shall receive signals from the computer control display and power the 1/2 hp (0.40 kW) electric motor directly coupled to the concentrate pump in a variable speed duty cycle to ensure that the correct proportion of concentrate preset by the pump operator is injected into the water stream.

Full flow check valve shall be provided to prevent foam contamination of fire pump and water tank or water contamination of foam tank.

Components of the complete proportioning system shall include:

- Operator control and display
- Paddlewheel flowmeter(s)
- Pump and electric motor/motor driver
- Wiring harnesses
- Low level tank switch
- Foam injection check valve
- Main waterway check valve

An installation and operation manual shall be provided for the unit, along with a one-year limited warranty by the manufacturer. The system must be installed and calibrated by a Certified FoamPro Dealer.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

The system design shall have passed environmental testing which simulates heavy use on off-road mobile apparatus. Testing shall have been conducted in accordance to SAE standards.

A means shall be provided to prevent water back flow into the foam proportioning system and the foam concentrate storage tank.

A remote start/stop feature shall be available to be incorporated into the 2000/3012 series proportioners. This option shall allow the operator to start and/or stop the operation of the proportioner from more than one location on the apparatus. Included in this option are a special control module, a local start/stop switch with LED lamp for mounting near the control module, a remote start/stop switch with LED lamp for remote mounting, and the 20 foot interface cable.

### **FOAM TANK REFILL SYSTEM**

The apparatus shall be equipped with an electronic, automatic, concentrate refill system. System shall operate independently of the foam proportioner allowing simultaneous use. Refill operation shall not require apparatus or fire pump to be running. The system shall be capable of handling Class A or Class B foam concentrates, emulsifiers, gels and decontamination concentrates. The apparatus shall be plumbed from the externally accessed intake/flush ports to the concentrate cell following manufacturer's recommendations. External fill and flush connections to be quick-connect, cam-lock type. Internal piping to incorporate check valves to prevent back flow. Concentrate tank inlet shall be positioned to minimize agitation per manufacturer's recommendations. The refill operation shall be based on direct measurement of concentrate level in tank. System must be capable of automatically stopping when cell is full and include a manual override feature. The system shall be equipped with an electronic control suitable for installation on the pump panel. Incorporated within the control shall be a microprocessor that receives input from the system while controlling foam concentrate pump output. An all bronze three-way valve shall be included to allow the operator to flush system after use. Valve control, intake and flush ports shall be located within corresponding panel plate.

The system shall enable the operator to perform the following control/operation functions and status indicators for the refill operation:

- Provide push-button start/stop control of foam refill
- Solid green light advises operator concentrate cell is full
- Flashing green indicates system is running
- Green light off, system off
- Allow override of "full tank" condition
- Provide a means to flush the pump and intake piping

System shall include a 12 volt electric motor driven, positive displacement concentrate pump. Pump shall deliver minimum flow of 10 gpm (37.8 L/min) @ 20 psi with all concentrates currently utilized in fire apparatus. Pump body to be of all bronze construction and other wetted components and piping to be constructed of non-corrosive materials. The system will draw a maximum of 38 amps @ 12 VDC. A pump/motor solenoid (mounted to the base of the pump) shall receive signals from the computer control display and power the 1/2 hp (0.4 kW) electric motor directly coupled to the concentrate pump. The system shall receive readings when the concentrate tank is full and stop operation to prevent overflow.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

Components of the complete refill system shall include:

- Operator control and display with Weather-Pac connectors
- Refill/flush quick-connect cam-lock fittings and cap
- Check valves
- Pump/motor assembly and solenoid
- Strainer
- Tank level switch
- Three-way fill/flush valve
- Stainless steel pick-up wand and 6' of reinforced suction hose, 1" diameter to allow maximum flow
- Panel placards

An installation and operation manual shall be provided, along with a one-year limited warranty by the manufacturer. The system must be installed and plumbed by a Certified FoamPro Dealer. When two types of concentrates are to be used, a separate refill system must be specified for each.

### **PLUMBING SPECIFICATIONS**

The fire pump plumbing system shall be fabricated with rigid stainless steel and or flexible piping with stainless steel fittings. Victaulic couplings shall be installed to permit flexing of the plumbing system and allow for quick removal of piping or valves for service. Flexible hose couplings shall be threaded stainless steel or Victaulic connections.

The fire pump and plumbing shall be hydrostatically tested in compliance to applicable sections of NFPA standards, with test results submit with the delivery documentation.

### **STAINLESS STEEL INTAKE MANIFOLD**

The suction manifold assembly shall be fabricated with Schedule #10 type 304 stainless steel. All threaded fittings shall be a minimum of Schedule 10 stainless steel. The suction manifold assembly shall have radiused sweep elbows to minimize water turbulence into the suction volute.

The suction manifold shall be welded and pressure tested prior to installation. The stainless steel manifold assembly shall be attached to the pump intake volute with a heavy-duty, flexible Victaulic coupling.

The entire intake piping system, valves, bleeder valves, and intake closures, excluding the tank-to-pump line on the tank side of the valve, shall be capable of withstanding a hydrostatic pressure of 250 psi (1700 kPa).

### **STAINLESS STEEL DISCHARGE MANIFOLD**

The discharge manifold assembly shall be fabricated with Schedule #10 type 304 stainless steel. All threaded fittings shall be a minimum of Schedule 10 stainless steel. The discharge manifold assembly shall have radiused sweep elbows to minimize water turbulence into the discharge header.

The manifold shall be welded and pressure tested prior to installation. The stainless steel manifold assembly shall be attached to the pump intake volute with a heavy-duty, flexible Victaulic coupling.

The entire discharge piping system; valves; drain cocks; and outlet closures, excluding the tank fill line on the tank side of the valve and CAF system piping and components that include valves that permit isolation from discharge pressure, shall be capable of withstanding a hydrodynamic discharge pressure of 500 psi (3400 kPa) or 100 psi (700 kPa) over the maximum discharge pressure capability rating of the pump, whichever is greater.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **STAINLESS STEEL PLUMBING WARRANTY**

The stainless steel plumbing shall be free of defects in material and workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

The contractor shall supply details of their warranty information with their bid submission.

## **STREETSIDE INTAKE - 2-1/2"**

There shall be one (1) 2-1/2" (65 mm) gated intake(s) located on pump panel. Each intake shall include:

- One (1) Akron Brass 8900 series Gen II, manual type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a brass type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a handle for direct valve operation through panel.
- Each intake shall have a 2-1/2" (65 mm) NSTF chrome swivel adapter with strainer provided.
  - The specified adapter shall be provided with a 2-1/2" (65 mm) NSTM chrome plated plug with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

## **CURBSIDE INTAKE - 2-1/2"**

There shall be one (1) 2-1/2" (65 mm) gated intake(s) located on pump panel. Each intake shall include:

- One (1) Akron Brass 8900 series Gen II, manual type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a brass type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a handle for direct valve operation through panel.
- Each intake shall have a 2-1/2" (65 mm) NSTF chrome swivel adapter with strainer provided.
  - The specified adapter shall be provided with a 2-1/2" (65 mm) NSTM chrome plated plug with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

## **DIRECT TANK FILL**

One (1) 2-1/2" (65 mm) direct tank fill(s) shall be located on rear body panel with check valve.

- One (1) Akron Brass 8900 series Gen II, manual type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a brass type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a handle for direct valve operation through panel.
- Each intake shall have a 2-1/2" (65 mm) NSTF chrome swivel adapter with strainer provided.
  - The specified adapter shall be provided with a 2-1/2" (65 mm) NSTM chrome plated plug with chain.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **TANK TO PUMP CHECK VALVE**

There shall be a check valve between the pump suction and the booster tank valve. The check valve shall eliminate back flow into the water tank when the pump is connected to a pressurized source.

## **TANK TO PUMP VALVE**

A 3" (75 mm) full flow ball valve shall be installed between the fire pump and the water tank. The connection between the tank and the pump shall be capable of the flow recommendations as set forth in the latest edition of NFPA 1901. The valve shall be flanged to bolt directly to the pump and shall incorporate a chromium plated bronze ball. The remaining internal moving parts shall be stainless steel for years of dependable service. A non collapsible flexible hose shall be incorporated into the tank to pump plumbing to allow movement in the line as the chassis flexes to avoid damage during normal road operation.

The tank to pump valve shall be controlled from the pump operator's panel.

- Akron valve(s) shall be controlled with a Class 1 air toggle switch located on the pump operator's panel and connected to Class 1 air cylinder to actuate valve(s).
- A dual position electric over air control switch shall be located on the pump operator's panel and in cab console.

## **FRONT DISCHARGE**

There shall be two (2) 2" (52 mm) gated discharge(s) with control located on valve. Each discharge shall include:

- Two (2) of the discharge(s) shall flow water and foam.
- Two (2) Akron Brass 8900 series Gen II, manual type 2" (52 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a handle for direct valve operation through panel.
- There shall be a 2" (52 mm) VFC x 1-1/2" (38 mm) NSTM brass or chrome plated 90 degree swivel elbow provided for each discharge on top of front bumper extension.
- Two (2) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

## **REMOTE CONTROL MONITOR**

A Task Force Tips Tornado model # Y2-E84A electric remote controlled monitor shall be provided on completed vehicle. The monitor shall be controlled by a monitor mounted membrane switch panel with functions that control rotation, elevation and nozzle patterns, oscillate, park, auxiliary 1 and auxiliary 2.

The monitor shall have the following travel capabilities: full horizontal rotation with travel 185 degrees left and right of center, full 135 degrees of vertical travel with field changeable vertical stops at 45 degrees above and 20 degrees below horizontal, field changeable rotation stops shall be provided 90 degrees left and right of center, flow capability of 500 GPM with no more than 25 PSI loss, maximum operating pressure of 200 PSI.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

The electrical components for the monitor shall be waterproof and utilize current limiting and position encoders to protect the drive train at the ends of travel. Monitor shall have waterproof plug for power and control cable connection for easy removal. An electrical connection for a TFT remote control nozzle shall be provided. The monitor shall be compatible with optional wired and wireless control panels and monitor position display. The monitor shall be equipped with manual override knobs for use in the event of power failure.

For resistance to corrosion the monitor shall be constructed from hardcoat anodized aluminum with a red powder coat interior and exterior finish.

The monitor shall be configured with a 2" NPT inlet x 1.5" NH male outlet. The unit shall be covered by a five-year warranty.

A model B-TOS-ERP selectable electric remote tip 1.5" NH (38mm) nozzle shall be provided with infinite adjustment between 15 and 120 gpm @ 100 psi (50-450 l/min at 7 bar). Indexed flow settings are provided at 15 gpm and 50 l/min increments. Flow setting may be adjusted without shutting down or locked to a specific setting as desired. Includes flush without shutting down and molded rubber teeth for full-fill "power fog" pattern. Lightweight hardcoat anodized aluminum for maximum resistance to corrosion and wear.

A model Y4E-JS joystick monitor operator station shall be provided to allow any TFT RC electric monitor to be controlled using a joystick. Moving the joystick controls monitor vertical and horizontal movement. Thumb switches control nozzle pattern. A trigger built into the joystick handle can be used to open and close some water valves. The joystick control is also equipped with push buttons on top for PARK and OSCILLATE functions as well as a toggle switch to select water valve open, close, and joystick control. The joystick control is factory wired so that the AUX2 button on TFT monitor operator stations will also open and close the water valve. Mounting bracket meets NFPA 1901 9G force requirements which ensures the security of equipment and safety of personnel.

A Y4E-DISP monitor position display will show the stream position of the electric monitor. Position is indicated by two sets of LEDs, one set for the vertical position and one set for the horizontal position. Buttons for the PARK & Oscillate features and HIGH/LOW speed selection are also supplied.

A Class 1 high pressure flexible hose with stainless steel Victaulic couplers shall connect the discharge valve and monitor. Hose shall be secured to body and chassis frame with bolted "P" style clamps and protected from abrasion, sharp edges, or high heat.

- One (1) of the discharge(s) shall flow water and foam.
- One (1) TFT model YE-VK-PH electric actuated type 2" (52 mm) stainless steel valve with Polypropylene ball and valve interface control shall be provided and connected to specified remote controlled monitor. Valve shall be equipped with a Class1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

### **CAB MOUNTED WATER TANK INDICATOR**

There shall be one (1) Class 1 Mini 4-light, remote tank level gauge for indicating water level installed in cab. The tank level gauge shall indicate the liquid level or volume on an easy to read red LED display and show increments of 1/4 of a tank.

The Mini remote gauge will receive data from the same source as the Master Display. No additional transducers shall be required.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

### **STREETSIDE DISCHARGE**

There shall be one (1) 2-1/2" (65 mm) gated discharge(s) with control located on pump panel. Each discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8900 series Gen II, manual type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a push/pull type chromed "T" handle with adjustable linkage connected to the valve. The control handle shall be located adjacent to the plumbing connection.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated 30 degree downsweep elbow provided.
- There shall be a 2-1/2" (65 mm) NSTF x 1-1/2" (38 mm) NSTM chrome plated rigid adapter provided for discharge(s).
  - The specified elbow shall be provided with a 1-1/2" (38 mm) NSTF chrome plated cap with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with blue (water) LED backlighting activated with pump engagement.
  - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
  - Gauge(s) shall have a range from 0 to 400 PSI.

### **CURBSIDE DISCHARGE**

There shall be one (1) 2-1/2" (65 mm) gated discharge(s) with control located on pump panel. Each discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8900 series Gen II, manual type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a push/pull type chromed "T" handle with adjustable linkage connected to the valve. The control handle shall be located adjacent to the plumbing connection.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated 30 degree downsweep elbow provided.



# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

- There shall be a 2-1/2" (65 mm) NSTF x 1-1/2" (38 mm) NSTM chrome plated rigid adapter provided for discharge(s).
  - The specified elbow shall be provided with a 1-1/2" (38 mm) NSTF chrome plated cap with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with blue (water) LED backlighting activated with pump engagement.
  - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
  - Gauge(s) shall have a range from 0 to 400 PSI.
  - The gauge shall have a die cast zinc, chrome plated bezel with color-coded labels insert and a color-coded gauge trim ring. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

### **REAR STREETSIDE DISCHARGE**

There shall be one (1) 2-1/2" (65 mm) gated discharge(s) with control located on valve. Each discharge shall include:

- One (1) of the discharge(s) shall flow water and foam.
- One (1) Akron Brass 8900 series Gen II, manual type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a chrome handle directly connected to valve.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated 30 degree downsweep elbow provided.
  - The specified elbow shall be provided with a 2-1/2" (65 mm) NSTF chrome plated cap with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **REAR CURBSIDE DISCHARGE**

There shall be one (1) 2-1/2" (65 mm) gated discharge(s) with control located on valve. Each discharge shall include:

- One (1) of the discharge(s) shall flow water and foam.
- One (1) Akron Brass 8900 series Gen II, manual type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a chrome handle directly connected to valve.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated 30 degree downsweep elbow provided.
- There shall be a 2-1/2" (65 mm) NSTF x 1-1/2" (38 mm) NSTM chrome plated rigid adapter provided for discharge(s).
  - The specified elbow shall be provided with a 1-1/2" (38 mm) NSTF chrome plated cap with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

## **MISCELLANEOUS DISCHARGE**

### **2" CROSS LAY(S)**

There shall be one (1) 2" cross lay(s) located in pump module, or per the itemized compartment list. The crosslay(s) shall be transverse of the pump module or body with access from either side.

Each cross lay shall have a minimum storage capacity of 200' of 1-3/4" double jacket hose and nozzle.

- One (1) of the discharge(s) shall flow water and foam.
- One (1) Akron Brass 8900 series Gen II, manual type 2" (52 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a push/pull type chromed "T" handle with adjustable linkage connected to the valve. The control handle shall be located adjacent to the plumbing connection.
- There shall be a 2" (52 mm) VFC x 1-1/2" (38 mm) NSTM brass or chrome plated 90 degree swivel elbow provided for each discharge.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with red (foam) LED backlighting activated with pump engagement.
  - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
  - Gauge(s) shall have a range from 0 to 400 PSI.
  - The gauge shall have a die cast zinc, chrome plated bezel with color-coded labels insert and a color-coded gauge trim ring. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

### **FRONT/REAR BUMPER GROUND SWEEP SNOZZLES**

The front and rear bumper shall be provided with 1/2" ground sweep nozzles with 145 degree spray angle (approx. 16 GPM @ 100 PSI) with spray overlap. Sweep nozzles shall be individually controlled in cab.

- Two (2) of the discharge(s) shall flow water and foam.
- Four (4) KZ #KZ84DM 1/2" (12 mm) 12 VDC electric stainless steel on/off valves shall be provided to control the front and rear ground sweep nozzles. Four (4) MSC 1/2" NPT brass fog nozzles shall be provided and mounted, one (1) each corner of bumper and plumbed to valve using high pressure flexible 1/2" hose. Each valve shall be individually controlled with 12 VDC on/off switches located in cab near driver, and labeled "Front Spray Bar", and "Rear Spray Bar".
- Two (2) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

### **BOOSTER REEL**

There shall be one (1) Hannay SBEF24-23-24-12 (26" wide x 23.5" high x 20.5" deep ) polished aluminum booster hose reel discharge(s) with electric rewind motor located in upper streetside pump module. Reel shall be capable of holding 100' of 1" or 150' of 3/4" booster hose.

- Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and not be more than 72 in. (1830 mm) above the operator's standing position, and shall be marked with a label indicating its function.
- Each booster hose reel shall be equipped with a Hannay FH-3 hose guide rollers.
- Each booster reel shall be supplied with 100' x 1" of lightweight 100% polyester booster hose with 1" NST Pyrolite couplings. Hose color shall be red.
- No nozzle is required with specified booster hose reel(s).
- One (1) of the discharge(s) shall flow water and foam.
- One (1) Akron Brass 8900 series Gen II, manual type 1-1/2" (38 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
  - Valve(s) shall be controlled with a push/pull type chromed "T" handle with adjustable linkage connected to the valve. The control handle shall be located adjacent to the plumbing connection.

# Lake Dillon Fire-Rescue

## TYPE III Pumper, SVI #1042

- One (1) Innovative Controls model 3003000, ¾" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with red (foam) LED backlighting activated with pump engagement.
  - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
  - Gauge(s) shall have a range from 0 to 400 PSI.
  - The gauge shall have a die cast zinc, chrome plated bezel with color-coded labels insert and a color-coded gauge trim ring. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

### **TANK FILL VALVE**

There shall be one (1) 2" (52 mm) tank fill valve plumbed with 2" plumbing from the pump to the tank. Installation shall be completed with 2" rubber hose and stainless steel hose couplings. The tank fill valve shall be controlled from the operator's control panel.

- One (1) Akron Brass 8900 series Gen II, actuated type 2" (52 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a brass type valve adapter on inlet side, and discharge side with drain port.
  - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
- Two (2) Akron 9323 Navigator Pro electric valve controllers with full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, and VMUX capable integration shall be located; one (1) on the pump operator's panel, and one (1) on the cab console.

### **PUMP PANEL**

The side mount pump control panel shall be hinged, or bolted in place allowing it to be easily removed to gain access to plumbing components.

The pump controls shall be mounted on an aluminum control panel with a black powdercoat painted finish.

### **PUMP PANEL LOCATION**

The pump control panel shall be side mounted.

The pump panel shall include the following items;

### **PUMP PANEL ACCESS**

The pump panel shall be open to the side of the truck. The Pump Operator shall NOT be required to open a compartment door to access the pump control panel.

### **ENGINE GAUGES**

The cab/chassis engine gauges shall be provided with the specified pump pressure governor system.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **PRESSURE GOVERNOR and ENGINE MONITORING DISPLAY**

A Fire Research PumpBoss series PBA401-D00 pressure governor and monitoring display kit shall be installed. The kit shall include a control module, intake pressure sensor, discharge pressure sensor, and cables. The control module case shall be waterproof and have dimensions not to exceed 6 3/4" high by 4 5/8". The control knob shall be 2" in diameter with no mechanical stops, have a serrated grip, and a red idle push button in the center. It shall not extend more than 1 3/4" from the front of the control module. Inputs for monitored engine information shall be from a J1939 data bus or independent sensors. Outputs for engine control shall be on the J1939 databus or engine specific wiring. Inputs from the pump discharge and intake pressure sensors shall be electrical.

The following continuous displays shall be provided:

- Engine RPM; shown with four daylight bright LED digits more than 1/2" high
- Check engine and stop engine warning LEDs
- Engine oil pressure; shown on a dual color (green/red) LED bar graph display
- Engine coolant temperature; shown on a dual color (green/red) LED bar graph display
- Transmission Temperature; shown on a dual color (green/red) LED bar graph display
- Battery voltage; shown on a dual color (green/red) LED bar graph display
- Pressure and RPM operating mode LEDs
- Pressure / RPM setting; shown on a dot matrix message display
- Throttle ready LED.

A dot-matrix message display shall show diagnostic and warning messages as they occur. It shall show monitored apparatus information, stored data, and program options when selected by the operator. All LED intensity shall be automatically adjusted for day and night time operation.

The program shall store the accumulated operating hours for the pump and engine to be displayed with the push of a button. It shall monitor inputs and support audible and visual warning alarms for the following conditions:

• High Battery Voltage	• Low Engine Oil Pressure
• Low Battery Voltage (Engine Off)	• High Engine Coolant Temperature
• Low Battery Voltage (Engine Running)	• Out of Water (visual alarm only)
• High Transmission Temperature	• No Engine Response (visual alarm only).

The program features shall be accessed via push buttons located on the front of the control module. There shall be a USB port located at the rear of the control module to upload future firmware enhancements.

The governor shall operate in two control modes, pressure and RPM. No discharge pressure or engine RPM variation shall occur when switching between modes. A throttle ready LED shall light when the interlock signal is recognized. The governor shall start in pressure mode and set the engine RPM to idle. In pressure mode the governor shall automatically regulate the discharge pressure at the level set by the operator. In RPM mode the governor shall maintain the engine RPM at the level set by the operator except in the event of a discharge pressure increase. The governor shall limit a discharge pressure increase in RPM mode to a maximum of 30 psi. Other safety features shall include recognition of no water conditions with an automatic programmed response and a push button to return the engine to idle.

The pressure governor and monitoring pressure display shall be programmed at installation for a specific engine.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **MASTER INTAKE/PRESSURE GAUGES**

There shall be one (1) Innovative Controls/NoShok 4" liquid filled gauge to display the Master Intake Pressure, and labeled "PUMP INTAKE".

There shall be one (1) Innovative Controls/NoShok 4" liquid filled gauge to display the Master Discharge Pressure. Gauge shall be labeled "PUMP DISCHARGE".

Both gauges shall have a die cast zinc, chrome plated bezel and color-coded. The left side (Pump Intake) bezel shall be color coded red, and the right side (Pump Discharge) bezel shall be colored black.

A test gauge port manifold shall be integrated into lower center bezel.

- Gauge(s) shall have a white background with black text.
- Gauge(s) shall have a range from -30" to 600 PSI.

## **PUMP SAFETY AND TEST LABELS**

Safety, information, data, and instruction labels for apparatus shall be provided and installed at the operator's instrument panel.

The labels shall include rated capacities, pressure ratings, and engine speeds as determined by the certification tests. The no-load governed speed of the engine, as stated by the engine manufacturer, shall also be included.

The labels shall be provided with all information and be attached to the apparatus prior to delivery.

## **PUMP PANEL LIGHTING**

All gauges and controls on the pump operator's panel shall be adequately illuminated by a full panel width shielded light assembly with full width OnScene Solutions LED light (each panel, if equipped). The light shall be activated by a weather-proof type switch on the pump operator's panel as well as automatically when pump is engaged. This switch shall also activate any area step lighting.

## **LOW PRESSURE AIR OUTLET**

There shall be one (1) air outlet connection to supply low pressure air for general maintenance. The outlet shall terminate in a 1/4" NPT threaded port. Air outlet shall be located on lower pump operator's panel. The connector shall be supplied by the Lake Dillon Fire-Rescue.

The outlet will be located in the lower rearward corner of the pump operators panel.

## **BACK PACK FILLER VALVE**

A brass, Innovative Controls 3/4", quarter turn ball valve with chrome T-handle shall be supplied and labeled "Back Pack Filler". The valve shall be installed on the streetside lower forward side of the pump panel with the discharge hose terminating at the outside of the apparatus body. The valve plumbing shall be 3/4" I.D. properly routed and clamped from the tank sump to the filler valve.

The outlet will be located in the lower rearward corner of the pump operators panel.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **POLY WATER TANK**

The water tank capacity shall be approximately 500 US gallon or 416 Imperial gallons. Certification of the tank capacity shall be recorded on the manufacturer's record of construction and shall be provided to the purchaser upon delivery of the apparatus.

## **CONSTRUCTION**

The tank must be designed and fabricated by a tank manufacturer that is ISO 9001:2008 certified. The ISO certification must be to the current standard in effect at the time of the design and fabrication of the tank.

The water tank shall be of a specific configuration and designed to be completely independent of the body and compartments. Joints and seams shall be fused using nitrogen gas as required and tested for maximum strength and integrity. The tank construction shall include PolyProSeal™ technology wherein a sealant shall be installed between the plastic components prior to being fusion welded. This sealing method will provide a liquid barrier offering leak protection in the event of a weld compromise. The top of the booster tank is fitted with removable lifting assembly designed to facilitate tank removal. The transverse and longitudinal swash partitions shall be manufactured of a minimum of 3/8" PT3™ polypropylene. All partitions shall be equipped with vent and air holes to permit movement of air and water between compartments. The partitions shall be designed to provide maximum water flow. All swash partitions interlock with one another and are completely fused to each other as well as to the walls of the tank. All partitions and spacing shall comply with NFPA 1901. The walls shall be welded to the floor of the tank providing maximum strength as part of the tank's unique Full Floor Design™. Tolerances in design allow for a maximum variation of 1/8" on all dimensions.

## **WATER FILL TOWER AND COVER**

The tank shall have a combination vent and manual fill tower. The fill tower shall be constructed of 1/2" PT3™ polypropylene and shall be a minimum dimension of 8" x 8" outer perimeter. The fill tower shall be blue in color indicating that it is a water-only fill tower. The tower shall be located in the left front corner of the tank unless otherwise specified by the tank manufacturer to the purchaser. The tower shall have a 1/4" thick removable polypropylene screen and a PT3™ polypropylene hinged cover. The capacity of the tank shall be engraved on the top of the fill tower lid. Inside the fill tower there shall be a combination vent/overflow pipe. The vent overflow shall be a minimum of schedule 40 polypropylene pipe with a minimum I.D. of 4" that is designed to run through the tank, and shall be piped to discharge water behind the rear wheels as required in NFPA 1901 so as to not interfere with rear tire traction.

The tank cover shall be constructed of 1/2" thick PT3™ polypropylene and UV stabilized, to incorporate a multi-piece locking design, which allows for individual removal and inspection if necessary. The tank cover(s) shall be flush or recessed 3/8" from the top of the tank and shall be fused to the tank walls and longitudinal partitions for maximum integrity. Each one of the covers shall have hold downs consisting of 2" minimum polypropylene dowels spaced a maximum of 40" apart. These dowels shall extend through the covers and will assist in keeping the covers rigid under fast filling conditions. A minimum of two lifting dowels shall accommodate the necessary lifting hardware.

## **SUMP**

There shall be one (1) sump standard per tank. The sump shall be constructed of a minimum of 1/2" PT3™ polypropylene and be located in the left front quarter of the tank, unless specified otherwise. On all tanks that require a front suction, a 3" schedule 40 polypropylene pipe shall be installed that will incorporate a dip tube from the front of the tank to the sump location. The sump shall have a minimum 3" N.P.T. threaded outlet on the bottom for a drain plug per NFPA. This shall be used as a combination clean-out and drain. All tanks shall have an anti-swirl plate located approximately 3" above the inside floor.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **OUTLETS**

There will be two (2) standard tank outlets: one for the tank-to-pump suction line, which shall be sized to provide adequate water flow to the pump; and, one for tank fill line, which shall be sized according to the NFPA minimum size chart for booster tanks. All tank fill couplings shall be backed with flow deflectors to break up the stream of water entering the tank, and be capable of withstanding sustained fill rates of up to 1000 G.P.M. The addition of rear suction fittings, nurse valve fittings, dump valve fittings, and through-the-tank sleeves to accommodate rear discharge piping must be specified. All auxiliary outlets and inlets must meet all NFPA guidelines in effect at the time of manufacture.

## **MOUNTING**

The tank shall rest on the body cross members in conjunction with such additional cross members, spaced at a distance that would not allow for more than 530 square inches of unsupported area under the tank floor. In cases where overall height of the tank exceeds 40 inches, cross member spacing must be decreased to allow for not more than 400 square inches of unsupported area.

The tank must be isolated from the cross members through the use of hard rubber strips with a minimum thickness and width dimension of 1/4" x 1" and a Shore A Hardness of approximately 60 durometer. The rubber must be installed so it will not become dislodged during normal operation of the vehicle. Additionally, the tank must be supported around the entire bottom outside perimeter and captured both in the front and rear as well as side to side to prevent tank from shifting during vehicle operation.

A picture frame type cradle mount with a minimum of 2" x 2" x 1/4" mild steel, stainless steel, or aluminum angle shall be provided or the use of corner angles having a minimum dimension of 4" x 4" x 1/4" by 6" high are permitted for the purpose of capturing the tank.

Although the tank is designed on a free floating suspension principle, it is required that the tank have adequate vertical hold down restraints to minimize movement during vehicle operation. If proper retention has not been incorporated into the apparatus hose floor structure, an optional mounting restraint system shall be located on top of the tank, half way between the front and the rear on each side of the tank. These stops can be constructed of steel, stainless steel or aluminum angle having minimum dimensions of 3" x 3" x 1/4" and shall be approximately 6" to 12" long. These brackets must incorporate rubber isolating pads with a minimum thickness of 1/4" inch and a hardness of 60 durometer affixed on the underside of the angle. The angle should then be bolted to the body side walls of the vehicle while extending down to rest on the top outside edge of the upper side wall of the tank. Hose beds floors must be so designed that the floor slat supports extend full width from side wall to side wall and are not permitted to drop off the edge of the tank or in any way come in contact with the individual covers where a puncture could occur. Tank top must be capable of supporting loads up to 200 lbs per sq. foot when evenly distributed. Other equipment such as generators, portable pumps, etc. must not be mounted directly to the tank top unless provisions have been designed into the Poly-Tank® III for that purpose. The tank shall be completely removable without disturbing or dismantling the apparatus structure.

## **CENTER OF GRAVITY**

A center of gravity calculation shall be determined for each tank and provided as requested in order to provide the apparatus manufacturer with the necessary data to design and certify the apparatus with respect to the NFPA requirements regarding rollover stability.



# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **WATER TANK LEVEL GAUGE**

There shall be one (1) Class 1 model ITL-40B tank level gauge(s) for indicating water level. The tank level gauge shall indicate the liquid level or volume on an easy to read blue LED display and show increments of 1/8 of a tank.

Each tank level gauge system shall include;

- A pressure transducer that is mounted on the outside of the tank in an easily accessible area. Sealed foam tanks will require zero pressure vacuum vents.
- A super bright LED display viewable from 180 degrees with a visual indication at nine accurate levels.
- A set of weather resistant connectors to connect to the digital display, to the pressure transducer and to the apparatus power.
- The system shall include the ability to display "text messages"
- The system shall include built-in diagnostic capabilities.

Additional (slave) displays (if requested) are to be easily integrated and will receive data from the same source as the Master Display. No additional transducers shall be required.

## **WATER TANK LEVEL INDICATOR**

There shall be three (3) Whelen Strip-Lite model PSTANK LED lights provided to indicate the water tank level and connected to tank level sensor in water tank.

The four tank levels to be indicated as follows;

Green =	"Full"
Blue =	"3/4"
Amber =	"1/2"
Red =	"1/4"

The red "1/4" level light shall flash when the tank level drops below "1/4" of the tank capacity. Each light will be installed in a vertical orientation and be de-activated whenever the parking brake is released.

One light each side upper body panel and one light mounted on rear body panel.

Body mounted tank level indicator lights shall be provided with a parking brake interlock, so that lights turn off when parking brake disengaged.

## **UPF POLY WATER TANK WARRANTY**

The UPF poly water tank shall be provided with a lifetime material and workmanship limited warranty. The manufacturer shall supply details of their warranty information with their bid submission.

## **FILL TOWER PROTECTION**

The fill tower(s) shall be boxed in with an aluminum panel for protection from damage.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **CLASS A POLYPROPYLENE FOAM CELL**

There shall be one (1) 20 US gallon or 16.6 Imperial gallons polypropylene foam cell incorporated into the polypropylene water tank. This foam tank capacity shall be deducted from water tank size specified.

There shall be one (1) pressure/vacuum vent installed on the foam tank.

A minimum 1 in. (25 mm) inside diameter full flow drain valve and piping shall be provided at the lowest point of any foam concentrate tank. The drain shall be piped to drain directly to the surface beneath the apparatus without contacting other body or chassis components.

A label shall be affixed to the foam tank fill indicating: "WARNING" Class A foam tank fill, do not mix brands or types of foam.

## **FOAM TANK LEVEL GAUGE**

There shall be one (1) Class 1 model ITLF-40R tank level gauge(s) for indicating foam level. The tank level gauge shall indicate the liquid level or volume on an easy to read red LED display and show increments of 1/8 of a tank.

Each tank level gauge system shall include;

- A pressure transducer that is mounted on the outside of the tank in an easily accessible area. Sealed foam tanks will require zero pressure vacuum vents.
- A super bright LED display viewable from 180 degrees with a visual indication at nine accurate levels.
- A set of weather resistant connectors to connect to the digital display, to the pressure transducer and to the apparatus power.
- The system shall include the ability to display "text messages"
- The system shall include built-in diagnostic capabilities.

Additional (slave) displays (if requested) are to be easily integrated and will receive data from the same source as the Master Display. No additional transducers shall be required.

## **HOSE BED STORAGE AREA**

Hose bed storage area shall be located over water tank, full width of body, and shall exit at the rear of the apparatus. The interior of storage area shall be free from all projections such as nuts, sharp angles, or brackets that may damage equipment.

## **ALUMINUM HOSE BED DECKING**

The hose bed deck shall be constructed from 3" x 3/4" hollow aluminum extrusions welded into a one-piece grid to allow ventilation and water drainage. The extrusions shall have a radiused ribbed top surface. The deck will be completely removable for easy access to the booster tank. The booster tank fill tower shall be protected as necessary to prevent damage from equipment located in the storage area.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **WALKWAY/STEP LIGHTS**

There shall be four (4) OnScene Solutions Rough-Service 9" LED lights provided to illuminate the walkway or step area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

Lighting shall provide illumination at a minimum level of 2 fc (20 lx) on all work surfaces, steps, and walkways. Lighting shall be switchable but activated automatically when the vehicle park brake is set.

## **FILL TOWER PROTECTION**

The fill tower(s) shall be boxed in with an aluminum panel for protection from damage.

## **HOSE BED DIVIDER(S)**

Two (2) adjustable aluminum hose bed divider(s) shall be provided in the hose bed storage area. The dividers(s) shall be fabricated from 3/16" smooth aluminum with 1" round split aluminum tubing welded to the top and rear edges. A radiused hand-hold opening shall be provided on rear of divider to assist in access to hose bed area. Hose pay-out shall be unobstructed by the divider.

Two (2) dividers on each side of center compartment.

Hosebed layout (L-R);

- 1" forestry hose (2) widths approximately 350 feet.
- 1.5" forestry hose (4) widths approximately 500 feet.
- 3" DJ hose (3 ) widths approximately 300 feet.
- 2.5" DJ hose (2) widths 200 feet.

## **ALUMINUM HOSE BED COVER**

A two-section hose bed cover shall be provided. Each door shall be fabricated from 1/8" NFPA aluminum treadplate with formed hat sections for bracing. Doors shall be hinged along each side of the hose body using stainless steel piano hinge. The top surface of each section shall slant down with the highest point in the center of the hose bed area and shall be supported from underneath by at least one (1) adjustable hose bed divider. Each section shall be constructed to support the weight of a person (300 lbs).

A flashing warning light signal shall be provided indicating when a hose bed door is not in a closed position as required by NFPA 1901.

There shall be one (1) 24" vertical handrail on each door to assist in raising and lowering hose bed door. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

Each door shall have a horizontally mounted On Scene LED light on the underside of the door that will be automatically activated when the door is opened and wired to the compartment door ajar warning light provided in cab.

A netting style hose bed flap shall be provided attached to each door and extend downward to bottom of hose bed to protect hose and equipment from weather and dust. The center where both doors come together shall have a Velcro seam to join two-pieces of netting together. Bottom of each flap shall be weighted for quick deployment of hose.

## **MANUAL ASSIST**

Each hose bed door section shall utilize a manul type pneumatic cylinder to assist with opening and closing.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **AIR VENT SCOOPS**

Each hose bed door shall have a rectangular opening on top rear door with a bolt-on air deflector on surface to capture air and force air down through opening onto rear hose bed to provide aid in ventilation for drying hose.

## **HOSE BED FULL WIDTH EXTENSION**

A full width, bolt-on type hose bed extension step shall be provided. Step shall be fabricated from 3/16" NFPA compliant treadplate aluminum with side gusset supports to body. The specified center rear marker lights shall be located on rear facing edge. The underside of step shall have a 36" OnScene LED light to light the bumper or compartment area below.

## **HOSEBED TOP LOADING EQUIPMENT COMPARTMENT**

In the center of the hosebed area a top loading equipment compartment shall run the length of the hosebed. The compartment shall be constructed of 1/8" smooth aluminum with a total volume of 13.8 cubic feet. Inside dimensions shall be 78" long x 17" deep and 18" wide. The top of the compartment shall be open and covered by the hose bed doors.

A rear access door shall be provided and constructed of aluminum with smooth finished inside panels and painted to match job color on the exterior.

The compartment floor shall be formed with a recess ribbed design for strength and to create a depressed area that will allow any accumulated debris or moisture to collect without the equipment resting in the contaminant. The depressed area is to be covered with open grating material. There shall be large diameter drain holes with removable plugs placed in the depresses area of the compartment floor for cleaning out the compartment.

The compartment door shall be wired into the door open warning circuit. Inside the compartment there shall be lights activated when the door is open for low ambient light operating conditions. The compartment shall be bolted in place and removable for water tank service.

An OnScene LED light shall be provided that runs from front to back of the compartment.

## **HOSEBED COMPARTMENT - CURBSIDE**

Hosebed curbside shall be provided with a compartment approximately 10" wide for storage of long equipment.

Access to the compartment shall be from a rear facing compartment door. Door shall be fabricated from 3/16" smooth aluminum with full length 14 gauge stainless steel hinge, with 1/4" stainless steel pin, push latch.

Devices to secure equipment, compartment dividers, or UHMW plastic angles, or sheeting will be used for storage of specified equipment as required to prevent damage to equipment.

Compartment shall have three (3) adjustable vertical dividers.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **HOSEBED COMPARTMENT - STREETSIDE**

Hosebed streetside shall be provided with a compartment for storage of long equipment.

Access to the compartment shall be from a rear facing compartment door. Door shall be fabricated from 3/16" smooth aluminum with full length 14 gauge stainless steel hinge, with 1/4" stainless steel pin, push latch.

Devices to secure equipment, compartment dividers, or UHMW plastic angles, or sheeting will be used for storage of specified equipment as required to prevent damage to equipment.

The compartment will be designed to store the following equipment:

Three (3) specified 5" hard suction tubes with folding lug handles.

Three (3) Lake Dillon Fire-Rescue supplied straight handled pike poles, mounted to hose bed cover.

One (1) Lake Dillon Fire-Rescue back board mounted vertically.

# Lake Dillon Fire-Rescue

TYPE III Pumper, SVI #1042

## **EQUIPMENT PAYLOAD WEIGHT ALLOWANCE**

In compliance with NFPA 1906 standards, the vehicle shall be designed for an equipment loading allowance of 500 lbs. of Lake Dillon Fire-Rescue provided equipment based on the wildland body having at least 50 cu. ft. of storage space under 26,000 GVWR, and an equipment loading allowance of 750 lbs with 75 cu. ft. of storage space over 26,000 GVWR.

## **EQUIPMENT**

The following equipment shall be furnished with the completed wildland vehicle;

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- There shall be two (2) Worden HW C7Y-WH yellow handled aluminum wheel chocks provided for 44" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20% grade, with the transmission in neutral, and the parking brake released. The wheel chocks shall have a bright yellow powder coat finish for high visibility, safety and corrosion resistance.

– The wheel chock(s) shall be mounted on the apparatus, location as per the Lake Dillon Fire-Rescue.

Location to be determined during engineering review.

- One (1) Duo-Safety 912 series 20' 3-section extension ladder(s) shall be provided with the completed unit.
  - The ladder(s) shall be located in rear curbside ladder compartment.
- Three (3) Kochek 5.0" x 8' Flexlite PVC flexible suction hose(s) shall be provided with completed unit. The hose shall have light weight NH couplings with folding long handles.

Add to change order #1

- One (1) 5" barrel strainer(s) with foot valve shall be provided with completed unit. Barrell strainer hard suction end shall match provided hard suction(s).

## **REMAINING NFPA MINOR EQUIPMENT BY PURCHASER**

All other minor equipment not specified above, but required by NFPA 1906 for wildland vehicles, section 5.7 shall be supplied and mounted by Lake Dillon Fire-Rescue before the unit is placed in emergency service.