

ASPEN FIRE PROTECTION DISTRICT

ASPEN, COLORADO

TYPE III APPARATUS, SVI #1080

Production Specification

Contract Administrator: Jackie Sipes

Sales Administrator: Justin Kline



ROCK SOLID QUALITY

Aspen Fire Protection District

Type III Engine, SVI #1080

LIABILITY INSURANCE

The manufacturer shall furnish with the bid a certificate of insurance for;

Workman's Compensation and Employer's Liability Insurance covering for all employees.

General Liability (each occurrence) of \$1,000,000.00. General Aggregate coverage of \$2,000,000.00. Products Completed / Operations Aggregate coverage of \$2,000,000.00. Medical Expense coverage of \$5,000 (any one person). Personal Injury of \$1,000,000.00.

Automobile liability of \$1,000,000.00 combined single limit (each accident), including any auto, all owned autos, scheduled autos, hired autos, non-owned autos, and garage liability.

Excess Umbrella Liability coverage of \$4,000,000.00 each occurrence, Aggregate of \$4,000,000.00. Garage Keepers Liability coverage of \$4,000,000.00 combined limit.

All insurance policies must be;

- Maintained for the life of the contract,
- Must provide ten (10) days notice before cancellation,
- Must cover all operations of the contractor, or anyone employed by them.

INTERNET IN-PROCESS SITE

The manufacturer shall post and maintain a website where the Aspen Fire Protection District will be able to view digital images of their apparatus as its being built. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of unit.

FIRE APPARATUS PERFORMANCE

The fire apparatus shall meet the requirements of this standard at elevations of 2000 ft (600 m) above sea level.

The fire apparatus shall meet all the requirements of this standard while stationary on a grade of 6 percent in any direction.

The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C).

HIGHWAY PERFORMANCE

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- 1) Accelerating from 0 to 35 mph (55 km/hr) within 25 seconds on a 0 percent grade
- 2) Attaining a speed of 50 mph (80 km/hr) on a 0 percent grade
- 3) Maintaining a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent

The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (109 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

Aspen Fire Protection District

Type III Engine, SVI #1080

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal (4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (95 km/ hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

SERVICEABILITY

The fire apparatus shall be designed to allow the manufacturer's recommended routine maintenance checks of lubricant and fluid levels to be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

FIRE APPARATUS DOCUMENTATION

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

- 1) The manufacturers record of apparatus construction details, including the following documents:
 - a) Owner's name and address
 - b) Apparatus manufacturer, model, and serial number
 - c) Chassis make, model, and serial number
 - d) GAWR of front and rear axles and GVWR
 - e) Front tire size and total rated capacity in pounds (kilograms)
 - f) Rear tire size and total rated capacity in pounds (kilograms)
 - g) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
 - h) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
 - i) Type of fuel and fuel tank capacity
 - j) Electrical system voltage and alternator output in amps
 - k) Battery make, model, and capacity in cold cranking amps (CCA)
 - l) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
 - m) Ratios of all driving axles
 - n) Maximum governed road speed
 - o) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), maximum discharge pressure capability rating, and serial number
 - p) Pump transmission make, model, serial number, and gear ratio
 - q) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
 - r) Water tank certified capacity in gallons or liters
 - s) Foam tank (if provided) certified capacity in gallons (liters)
 - t) Aerial device type, rated vertical height in feet (meters), rated horizontal reach in feet (meters), and rated capacity in pounds (kilograms)
 - u) Paint manufacturer and paint number(s)
 - v) Company name and signature of responsible company representative

Aspen Fire Protection District

Type III Engine, SVI #1080

- w) Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall fire apparatus (with the water tank full but without personnel, equipment, and hose)
- 2) Certification of compliance of the optical warning system (see 13.8.16)
- 3) Siren manufacturer's certification of the siren (see 13.9.1.1)
- 4) Written load analysis and results of the electrical system performance tests (see 13.14.1 and Section 13.15)
- 5) Certification of slip resistance of all stepping, standing, and walking surfaces (see 15.7.4.5)
- 6) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability (see 16.2.4.1)
- 7) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions (see 16.2.4.2)
- 8) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications (see 16.3.1)
- 9) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed (see 16.3.2.2)
- 10) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test (see 16.5.2.2)
- 11) If the apparatus has a fire pump with a maximum discharge pressure capability rating that exceeds the hydrostatic test pressure of 16.5.2.1, the pump manufacturer's certification of the hydrodynamic test
- 12) If the apparatus has a fire pump, the certification of inspection and test for the fire pump (see 16.13.1.1.5 or 16.13.1.2.4 as applicable)
- 13) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test (see Section 17.13)
- 14) When the apparatus is equipped with a water tank, the certification of water tank capacity (see Section 18.6)
- 15) If the apparatus has an aerial device, the certification of inspection and test for the aerial device (see Section 19.24)
- 16) If the apparatus has an aerial device, all the technical information required for inspections to comply with NFPA 1911
- 17) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy (see 20.10.4.2) and the final installer's certification the foam proportioning system meets this standard (see 20.11.2)
- 18) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests (see Section 21.9)
- 19) If the apparatus has a line voltage power source, the certification of the test for the power source (see 22.15.7.2)
- 20) If the apparatus is equipped with an air system, air tank certificates (see 24.5.1.2), the SCBA fill station certification (see 24.9.6), and the results of the testing of the air system installation (see 24.14.5 and 24.15.4)
- 21) Any other required manufacturer test data or reports

OPERATIONS AND SERVICE DOCUMENTATION

The contractor shall deliver with the fire apparatus complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof.

The contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- 1) Manufacturer's name and address
- 2) Country of manufacture
- 3) Source for service and technical information
- 4) Parts replacement information
- 5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- 6) Wiring diagrams for low voltage and line voltage systems to include the following information:
 - a) Pictorial representations of circuit logic for all electrical components and wiring
 - b) Circuit identification

Aspen Fire Protection District

Type III Engine, SVI #1080

- c) Connector pin identification
- d) Zone location of electrical components
- e) Safety interlocks
- f) Alternator–battery power distribution circuits
- g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- 7) Lubrication charts
- 8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- 9) Precautions related to multiple configurations of aerial devices, if applicable
- 10) Instructions regarding the frequency and procedure for recommended maintenance
- 11) Overall apparatus operating instructions
- 12) Safety considerations
- 13) Limitations of use
- 14) Inspection procedures
- 15) Recommended service procedures
- 16) Troubleshooting guide
- 17) Apparatus body, chassis and other component manufacturer's warranties
- 18) Special data required by this standard
- 19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus
- 20) One copy of the latest edition of FAMA's *Fire Apparatus Safety Guide*

The contractor shall deliver with the apparatus all manufacturer's operations and service documents supplied with components and equipment that are installed or supplied by the contractor.

NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a USB Flash Drive. These manuals shall be divided into sections for ease of reference. There shall be two (2) USB flash drives provided with the completed vehicle.

FIRE APPARATUS SAFETY GUIDE

A Fire Apparatus Safety Guide published by Fire Apparatus manufacturer's Association shall be provided with delivered vehicle. This manual includes essential safety information for fire fighters, fire chiefs, apparatus mechanics, and fire department safety officers. The guide is applicable to municipal, wildland, and airport fire fighting apparatus manufactured on either custom or commercial chassis.

STATEMENT OF EXCEPTIONS

The final-stage manufacturer shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- 1) A separate specification of the section of the applicable standard for which compliance is lacking
- 2) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
- 3) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance

Aspen Fire Protection District

Type III Engine, SVI #1080

- 4) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to or at the time of delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

CARRYING CAPACITY

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The manufacturer shall establish the estimated in service weight during the design of the vehicle.

The estimated in-service weight shall include the following:

1. The chassis, body and tank(s)
2. Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
3. Full water and other agent tanks
4. *250 lb (114 kg) in each seating position
5. Fixed equipment such as pumps, aerial devices, generators, reels and air systems as installed
6. Ground ladders, suction hose, designed hose load in their hose beds and on their reels
7. An allowance for miscellaneous equipment that is the greatest of the following:
 - a) The values shown for items 1 - 7
 - b) A purchaser-provided list of equipment to be carried with weights
 - c) A purchaser-specified miscellaneous equipment allowance

The manufacturer shall engineer and design the fire apparatus such that the completed apparatus, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

A final manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed unequipped fire apparatus in feet and inches (meters), the length of the completed fire apparatus in feet and inches (meters), and the GVWR in tons (metric tons).

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the

Aspen Fire Protection District

Type III Engine, SVI #1080

TESTING

ROAD TEST

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the Body Manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (-18°C and 43°C).

TEST SEQUENCE

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for ten (10) minutes. Failure of any of these tests shall require a repeat of the sequence.

1. RESERVE CAPACITY TEST

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

Aspen Fire Protection District

Type III Engine, SVI #1080

2. ALTERNATOR PERFORMANCE TEST

TEST AT IDLE

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

TEST AT FULL LOAD

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

3. LOW VOLTAGE ALARM TEST

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST

DOCUMENTATION

The manufacturer shall deliver the following with the fire apparatus:

- 1) Documentation of the electrical system performance tests
- 2) A written electrical load analysis, including the following:
 - a) The nameplate rating of the alternator
 - b) The alternator rating
 - c) Each of the component loads specified that make up the minimum continuous electrical load
 - d) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
 - e) Each individual intermittent electrical load

Aspen Fire Protection District

Type III Engine, SVI #1080

UL PUMP CERTIFICATION

The apparatus upon completion shall be tested and certified by Underwriters Laboratories, Inc. (UL). The certification tests shall follow the guide lines outlined in NFPA 1901 "Standard for Fire Apparatus".

If the fire pump has a rated capacity of 750 gpm (3000 L/min) or greater, the pump shall be tested after the pump and all its associated piping and equipment have been installed on the apparatus.

The fire pump shall be tested and certified to perform as listed below;

- 100% of rated capacity at 100 psi (700 kPa) net pressure
- 70% of rated capacity at 150 psi (1,000 kPa) net pressure
- 50% of rated capacity at 200 psi (1,400 kPa) net pressure

The test shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming device tests, and the vacuum test.

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 500 psi (3,400 kPa).

The pump shall comply with the applicable requirements of "Standard for Fire Apparatus 1901, latest edition.

The pump shall be capable of producing fire streams that are free from objectionable pulsation under all normal operating conditions.

If the apparatus is equipped with a pump driven by the chassis engine designed for both stationary pumping and pump-and-roll, the test shall verify that the engine speed control at the pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the parking brake is off, and the pump shift status in the driving compartment is disengaged.
- (2) The chassis transmission is in any gear other than neutral, the parking brake is on, and the pump shift in the driving compartment is in the "Pump Engaged" or the "OK to Pump-and-Roll" position.

A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve.

WARRANTY

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source and will deal directly with the Aspen Fire Protection District on all warranty work.

Aspen Fire Protection District

Type III Engine, SVI #1080

GENERAL LIMITED WARRANTY - TWO (2) YEARS

The vehicle shall be free of defects in material and workmanship for a period of two (2) years or 36,000 miles (or 57,936 kilometers), whichever occurs first starting thirty (30) days after the original invoice date.

The Contractor must be the "single source" coordinator of all warranties on the vehicle.

LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles (or 96,561 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

STRUCTURAL WARRANTY - TEN (10) YEARS

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

UNDERCOAT WARRANTY

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

PAINT LIMITED WARRANTY - TEN (10) YEARS

The body shall be free of bubbling or peeling as a result of a defect in the method of manufacture for a period of ten (10) years or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date. **Pro-rated warranties will not be acceptable.**

GRAPHICS LIMITED WARRANTY

The 3M graphics installation shall be warranted for a period of two (2) years. The 3M materials installed on completed vehicle shall be warranted for seven (7) years. The 3M Diamond grade film (if specified) shall be warranted for ten (10) years.

HALE FIVE YEAR PUMP WARRANTY

The fire pump shall be warranted by Hale for a period of five (5) years from the date of delivery to the Aspen Fire Protection District. Within this warranty period Hale shall cover parts and labor for the first two (2) years and parts only for years three (3) through five (5).

STAINLESS STEEL PLUMBING WARRANTY

The stainless steel plumbing shall be free of defects in material and workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

The contractor shall supply details of their warranty information with their bid submission.

Aspen Fire Protection District

Type III Engine, SVI #1080

AKRON BRASS FIVE YEAR VALVE WARRANTY

The Akron Brass valves shall be warranted by Akron Brass for a period of ten (10) years from the date of delivery to the Aspen Fire Protection District. The warranty for electronics shall be warranted by Akron Brass for a period of five (5) years from date of delivery to the Aspen Fire Protection District.

UPF POLY WATER TANK WARRANTY

The UPF poly water tank shall be provided with a lifetime material and workmanship limited warranty. The manufacturer shall supply details of their warranty information with their bid submission.

CONSTRUCTION PERIOD

The completed vehicle shall be delivered within four hundred (400) days after receipt of a purchase order or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to Aspen Fire Protection District as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

OVERALL HEIGHT REQUIREMENT

The overall height (OAH) of the vehicle shall be approximately 132" from the ground. This measurement shall be taken on flat ground with the tires properly inflated, in the unloaded condition, at that highest point of the vehicle.

OVERALL LENGTH REQUIREMENT

There is no overall length (OAL) restriction for this vehicle.

ANGLE OF APPROACH

The angle of approach for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

ANGLE OF DEPARTURE

The angle of departure for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

PRE-CONSTRUCTION CONFERENCE

A pre-construction conference shall be required at the Aspen Fire Protection District location to finalize all construction details prior to manufacturing.

PRE-PAINT CONFERENCE

A pre-paint conference shall be required at the Contractor's factory for two (2) personnel from the Aspen Fire Protection District to inspect the vehicle and construction details prior to the painting process.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the pre-paint conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

Aspen Fire Protection District

Type III Engine, SVI #1080

FINAL INSPECTION CONFERENCE

A final inspection conference shall be required at the Contractor's factory for two (2) personnel from the Aspen Fire Protection District to inspect the vehicle and construction details prior to shipment of the completed vehicle. This inspection shall take place after any specified striping and lettering is installed.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the final inspection conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

DELIVERY AND DEMONSTRATION

The Contractor shall be responsible for the delivery of the completed unit to the Aspen Fire Protection District's location. On initial delivery of the apparatus, the Contractor shall supply a qualified representative to demonstrate the apparatus and provide initial instruction to representatives of the Aspen Fire Protection District regarding the operation, care and maintenance of the apparatus and equipment supplied at Aspen Fire Protection District location.

The Delivery Engineer shall set delivery and instruction schedule with the person appointed by Aspen Fire Protection District.

After delivery of the apparatus, the Aspen Fire Protection District shall be responsible for ongoing training of its personnel to proficiency regarding the proper and safe use of the apparatus and associated equipment.

CAB/CHASSIS SPECIFICATIONS

MAKE/MODEL: 2019 7500 SFA 4X4 (SR537)

MISSION: Requested GVWR: 37000. Calc. GVWR: 37000
Calc. Start / Grade Ability: 35.44% / 3.48% @ 55 MPH
Calc. Geared Speed: 72.6 MPH

ENGINE, DIESEL: {Cummins L9 380} EPA 2017, 380HP @ 2000 RPM, 1150 lb-ft Torque @ 1400 RPM,
2200 RPM Governed Speed, 380 Peak HP (Max)

TRANSMISSION, AUTOMATIC: {Allison 3000 EVS} 5th Generation Controls, Close Ratio, 6-Speed with Double
Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-
lb GVW and GCW Max

AXLE, FRONT DRIVING: {Meritor MX-14-120 EVO} Single Reduction, 14,000-lb Capacity, with Hub Piloted
Mounting Wheel

AXLE, REAR, SINGLE: {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, Driver Controlled Locking
Differential, 200 Wheel Ends Gear Ratio: 5.63

CAB: Conventional 6-Man Crew Cab

TIRE, FRONT: (2) 12R22.5 Load Range H G282 MSD (GOODYEAR), 481 rev/mile, 75 MPH, Drive
TIRE, REAR: (4) 11R22.5 Load Range G G622 RSD (GOODYEAR), 497 rev/mile, 75 MPH, Drive

Aspen Fire Protection District

Type III Engine, SVI #1080

**SUSPENSION, RR,
SPRING, SINGLE:**

Vari-Rate; 23,500-lb Capacity, with 4500 lb Auxiliary Rubber Spring

PAINT:

Cab schematic 100GM
Location 1: 2781, Red (Prem)

Base Chassis, Model 7500 SFA 4X4 with 205.00 Wheelbase, 84 CA, and 47.00 Axle to Frame.

TOW HOOK, FRONT (2) Frame Mounted

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm);
456.0" (11582mm) Maximum OAL

BUMPER, FRONT Stainless Steel Clad Aluminum, Swept Back

CROSSMEMBER, REAR, AF

FRAME EXTENSION, FRONT Integral; 20" In Front of Grille

AXLE, FRONT DRIVING {Meritor MX-14-120 EVO} Single Reduction, 14,000-lb Capacity, with Hub Piloted Wheel
Mounting

SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 14,000-lb Capacity; with Shock Absorbers

Includes

: SPRING PINS Rubber Bushings, Maintenance-Free

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE LINES Color and Size Coded Nylon

: DRAIN VALVE Twist-Type

: DUST SHIELDS, FRONT BRAKE

: DUST SHIELDS, REAR BRAKE

: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster

: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel

: PARKING BRAKE VALVE For Truck

: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4

: SLACK ADJUSTERS, FRONT Automatic (with Air Cam Brakes)

: SLACK ADJUSTERS, REAR Automatic (with Air Cam Brakes)

: SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6

DRAIN VALVE {Berg} with Pull Chain, for Air Tank

Includes

: Drain Valve Mounted in Wet Tank

AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel) with
Automatic Traction Control

AIR DRYER {Bendix AD-IP} with Heater

Includes

: AIR DRYER LOCATION Outside Left Rail, Back of Cab

BRAKE CHAMBERS, FRONT AXLE {MGM} 20 SqIn

Aspen Fire Protection District

Type III Engine, SVI #1080

BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake

BRAKES, FRONT, AIR CAM S-Cam; 16.5" x 5.0"; Includes 20 Sq. In. Long Stroke Brake Chambers

BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake

AIR COMPRESSOR {Cummins} 18.7 CFM Capacity

AIR TANK LOCATION (2) Mounted Left Side BOC Under Battery Box

AIR DRYER LOCATION Mounted Inside Left Rail, Behind Transfer Case Mounting

STEERING COLUMN Tilting

STEERING WHEEL 2-Spoke, 18" Dia., Black

STEERING GEAR {Sheppard M110} Power

AFTERTREATMENT COVER Steel, Black

EXHAUST SYSTEM Single, Horizontal Aftertreatment Device, Frame Mounted Right Side, Under Cab, for Single Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab, for All-Wheel Drive

ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger

SWITCH, FOR EXHAUST 3 Position, Momentary, Lighted Momentary, ON/CANCEL, Center Stable, INHIBIT REGEN, Mounted in IP Inhibits Diesel Particulate Filter Regeneration When Switch is Moved to ON While Engine is Running, Resets When Ignition is Turned OFF

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab

: HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: HEADLIGHTS (2) Halogen, Round, with Chrome Plated Bezels

: JUMP START STUD Located on Positive Terminal of Outermost Battery

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector

: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature

WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted

: WIRING, CHASSIS Color Coded and Continuously Numbered

IGNITION SWITCH Keyless

POWER SOURCE Cigar Type Receptacle without Plug and Cord

Aspen Fire Protection District

Type III Engine, SVI #1080

RADIO Accommodation package; Less Radio, with Wiring and Antenna, Includes Multiple Speakers

Includes

: SPEAKERS IN CAB (2) Dual Cone with Deluxe Interior

: SPEAKERS IN CAB (4) Coaxial with Premium Interior

ALTERNATOR {Leece-Neville BLP4006HN} Brushless, 12 Volt 325 Amp. Capacity, Pad Mount, with Remote Sense

BODY BUILDER WIRING Back of Standard or Sleeper Cab at Left Frame or Under Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn

ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket

BATTERY SYSTEM {International} Maintenance-Free, (3) 12-Volt 1950CCA Total

HORN, ELECTRIC Disc Style

BATTERY BOX Steel, with Plastic Cover, 30" Wide, 2, 3 or 4 Battery Capacity, Mounted Left Side Back of Fuel Tank

WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time

HEADLIGHTS Long Life Halogen; for Two Light System

CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade

TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights

HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on

INDICATOR, LOW COOLANT LEVEL with Audible Alarm

ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, with Ignition "OFF" and any Door Opened

STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start

INDICATOR, BATTERY WARNING Green BATTERY ON Indicator, Mounted on Left Side of Instrument Panel, To be Used with Factory Installed or Customer Mounted Battery Disconnect Switch

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

SWITCH, AUXILIARY Switch 40 amp Circuit for Customer Use; Includes Wiring Connection at PDC and Control in Cab

TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender

BATTERY DISCONNECT SWITCH for Cab Power Disconnect Switch; Cab Mounted, Disconnects Power to Power Distribution Center (PDC) and Body Builder Through Solenoid, Does Not Disconnect Charging Circuits; Locks with Padlock

Aspen Fire Protection District

Type III Engine, SVI #1080

FENDER EXTENSIONS Rubber

GRILLE Stationary, Chrome

FRONT END Tilting, Fiberglass, with Three Piece Construction; for WorkStar/HV

GRILLE EMBER SCREEN Mounted to Grille and Cowl Tray to Keep Hot Embers out of Engine and HVAC Air Intake System

PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

: PAINT SCHEMATIC ID LETTERS "GM"

: COLOR NAV2464 "Coco-Cola Red"

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

PAINT CLASS Premium Color

KEYS - ALL ALIKE, ID Z-001

PROMOTIONAL PACKAGE Government and Municipal Silver Package; Two Year Limited Subscription of On-Command Service Information (Formerly Fleet ISIS), and On-Command Parts Information (Formerly Fleet Parts Catalog), Requires Specific Feature Combinations

CLUTCH Omit Item (Clutch & Control)

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

ENGINE, DIESEL {Cummins L9 380} EPA 2017, 380HP @ 2000 RPM, 1150 lb-ft Torque @ 1400 RPM, 2200 RPM Governed Speed, 380 Peak HP (Max)

FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed with Residual Torque Device for Disengaged Fan Speed

Includes

: FAN Nylon

RADIATOR Cross Flow, Series System; 1228 SqIn Aluminum Radiator Core with Internal Water to Oil Transmission Cooler and 1167 In Charge Air Cooler

Includes

: DEAERATION SYSTEM with Surge Tank

: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps

: RADIATOR HOSES Premium, Rubber

AIR CLEANER Dual Element

Includes

: GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted

FEDERAL EMISSIONS {Cummins L9} EPA, OBD and GHG Certified for Calendar Year 2018

THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel

EMISSION COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations

Aspen Fire Protection District

Type III Engine, SVI #1080

ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; with Ignition Switch Control for Cummins ISB/B6.7 or ISL/L9 Engines

TRANSMISSION, AUTOMATIC {Allison 3000 EVS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max

TRANSFER CASE {Meritor T-4210 2} Two-Speed, 10,000 lb-ft Capacity with PTO Provision, with Electric Over Air Control Includes

: LIGHT, INDIC, ALL-WHEEL DRIVE Illuminates With All Wheel Drive Engaged, Located on Instrument Panel

TRANSMISSION SHIFT CONTROL {Allison} Push-Button Type; for Allison 3000 & 4000 Series Transmission

TRANSFER CASE LUBE {EmGard 50W} Synthetic; 1 thru 14.99 Pints

OIL COOLER, TRANSFER CASE Remote Mounted Back of Cab

TRANSMISSION OIL Synthetic; 29 thru 42 Pints

ALLISON SPARE INPUT/OUTPUT for Emergency Vehicle Series (EVS); Fire/Pumper, Tank, Aerial/Ladder

SHIFT CONTROL PARAMETERS Allison 3000 or 4000 Series Transmissions, 5th Generation Controls, Performance Programming

PTO LOCATION Left Side of Transmission

AXLE, REAR, SINGLE {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, Driver Controlled Locking Differential, 200 Wheel Ends . Gear Ratio: 5.63

Includes

: REAR AXLE DRAIN PLUG (1) Magnetic, For Single Rear Axle

SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 23,500-lb Capacity, with 4500 lb Auxiliary Rubber Spring 0/62 62

SHOCK ABSORBERS, REAR (2)

LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail, 41" Back of Cab

FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor

FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 50 US Gal (189L), with Quick Connect Outlet, Mounted Left Side, Under Cab

FUEL COOLER Less Thermostat; Mounted in Front of Cooling Module

DEF TANK 7 U.S. Gal. 26.5L Capacity, Frame Mounted Outside Left Rail, Under Cab

Aspen Fire Protection District

Type III Engine, SVI #1080

CAB Conventional 6-Man Crew Cab

Includes

- : ARM REST (2) Molded Plastic; One Each Door
- : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window
- : CUP HOLDERS Two Cup Holders, Located in Lower Center of Instrument Panel
- : DOME LIGHT, CAB Rectangular, Door Activated and Push On-Off at Light Lens, Timed Theater Dimming,
Integral to Console, Center Mounted
- : GLASS, ALL WINDOWS Tinted
- : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side
- : GRAB HANDLE, CAB INTERIOR (2) Front of "B" Pillar Mounted, One Each Side
- : GRAB HANDLE, CAB INTERIOR (4) Two Each Side, Rear Door Mounted at Hinge Side and "C" Pillar Mounted
- : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color
- : STEP (8) Two Steps Per Door

GAUGE CLUSTER English with English Electronic Speedometer

Includes

- : GAUGE CLUSTER (6) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic),
Tachometer (Electronic), Voltmeter, Washer Fluid Level
- : ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout
- : WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage
(Visual and Audible)

SEATBELT WARNING PREWIRE Includes Seat Belt Switches and Seat Sensors for all Belted Positions in the Cab and a Harness Routed to the Center of the Dash for the Aftermarket Installation of the Data Recorder and Seatbelt Indicator Systems, for 4 to 6 Seat Belts

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

GAUGE, DEF FLUID LEVEL

SEAT, DRIVER {National 2000} NFPA Compliant, Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, -3 to +14 Degree Back Angle Adjust

Includes

- : SEAT BELT 3-Point, Lap and Shoulder Belt Type

SEAT, REAR {National 2000} Two Individual Outboard Seats, NFPA Compliant, Air Suspension, High Back, Vinyl, Isolator, with 2 Position Front Cushion Adjustment, -3 to +14 Degree Seat back Adjustment, Lumbar, with 18" Wide Cushion and 20" Seat Back

Includes

- : SEAT BELT Two 3-Point Shoulder Belts

SEAT, PASSENGER {National 2000} NFPA Compliant, Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjustment, -3 to +14 Degree Back Angle Adjust

Includes

- : SEAT BELT 3-Point, Lap and Shoulder Belt Type

GRAB HANDLE (2) Chrome Towel Bar Type with Anti-Slip Rubber Inserts; for Cab Entry, Mounted Left and Right, Each Side at "B" Pillar

GRAB HANDLE, ADDITIONAL EXT (2) Chrome; Towel Bar Type with Anti-Slip Rubber Inserts; Mounted Left and Right Side on Exterior, Rear of Rear Doors, with Crew Cab

Aspen Fire Protection District

Type III Engine, SVI #1080

MIRRORS (2) {Lang Mekra} Styled; Rectangular, Power Both Sides, Thermostatically Controlled Heated Heads, Clearance Lights LED, Bright Finish Heads & Brackets, Breakaway Type, 7.09" x 15.75" & Integral Convex Both Sides, 102" Inside Spacing

SEAT BELT All Red; 4 to 6

AIR CONDITIONER {Blend-Air} with Integral Heater & Defroster

Includes

: HEATER HOSES Premium

: HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps

: REFRIGERANT Hydrofluorocarbon HFC-134A

INSTRUMENT PANEL Center Section, Flat Panel

WINDOW, POWER (4) And Power Door Locks, Front and Rear Doors, Left and Right, Includes Express Down Feature

HVAC FRESH AIR FILTER

STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door

CAB INTERIOR TRIM Deluxe; for Crew Cab

Includes

: CAB INTERIOR TRIM PANELS Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering

: CONSOLE, OVERHEAD Molded Plastic; With Dual Storage Pockets with Retainer Nets and CB Radio Pocket

: DOOR TRIM PANELS Molded Plastic; Driver and Passenger Doors

: FLOOR COVERING Rubber, Black

: HEADLINER Soft Padded Cloth

: INSTRUMENT PANEL TRIM Molded Plastic with Black Center Section

: STORAGE POCKET, DOOR (1) Molded Plastic, Full-Length; Driver Door

: SUN VISOR (2) Padded Vinyl with Driver Side Toll Ticket Strap, Integral to Console

CAB REAR SUSPENSION Air Bag Type

WHEELS, FRONT DISC; 22.5x8.25 Rims, Polished Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

Notes

: Aluminum Wheels not Painted or Coated

WHEELS, REAR DUAL DISC; 22.5x8.25 Rims, Polished Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

Notes

: Aluminum Wheels not Painted or Coated

: Polished Surface Outside Dual Only

(4) TIRE, REAR 11R22.5 Load Range G G622 RSD (GOODYEAR), 497 rev/mile, 75 MPH, Drive

(2) TIRE, FRONT 12R22.5 Load Range H G282 MSD (GOODYEAR), 481 rev/mile, 75 MPH, Drive

Services Section:

WARRANTY Standard for PayStar 7500/7600 Effective with Vehicles Built January 2, 2015 or Later, CTS-2003Z

Aspen Fire Protection District

Type III Engine, SVI #1080

CAB TO AXLE DIMESION

Cab to axle will be 83".

CHASSIS MODIFICATIONS

LUBRICATION AND TIRE DATA PLATE

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid . . (if applicable)
- Pump priming system fluid, if applicable . . (if applicable)
- Drive axle(s) lubrication fluid
- Air conditioning refrigerant . . (if applicable)
- Air conditioning lubrication oil . . (if applicable)
- Power steering fluid
- Cab tilt mechanism fluid . . (if applicable)
- Transfer case fluid . . (if applicable)
- Equipment rack fluid (if applicable)
- CAFS air compressor system lubricant . . (if applicable)
- Generator system lubricant . . (if applicable)
- Front tire cold pressure
- Rear tire cold pressure
- Maximum tire speed ratings

VEHICLE DATA PLATE

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the;
 - Engine
 - Transmission
 - Air
 - Fuel
- Serial numbers for the;
 - Engine
 - Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

Aspen Fire Protection District

Type III Engine, SVI #1080

OVERALL HEIGHT, LENGTH DATA PLATE (US)

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in feet and inches, the length of the completed fire apparatus in feet and inches, and the GVWR in pounds.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

PERSONNEL CAPACITY

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

SEAT BELT WARNING - FAMA06/07

A safety sign FAMA06 shall be visible from each seat that is not equipped with occupant restraint and therefore not intended to be occupied while the vehicle is in motion.

A safety sign FAMA07, which warns of the importance of seat belt use, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

EQUIPMENT MOUNTING FAMA10

A safety sign FAMA10, which warns of the need to secure items in the cab, shall be visible inside the cab.

FIRE SERVICE TIRES - FAMA12

A safety sign FAMA12, which warns of the special requirements for fire service-rated tires, shall be visible to the driver entering the cab of any apparatus so equipped.

HELMET WARNING - FAMA15

A safety sign FAMA15, which warns not to wear helmets while the vehicle is in motion, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

CLIMBING METHOD - FAMA23

A safety sign FAMA23, which warns of the proper climbing method, shall be visible to personnel entering the cab and at each designated climbing location on the body.

REAR STEP CROSSWALK WARNING - FAMA24

A safety sign FAMA24, which warns personnel not to ride on the vehicle, shall be located at the rear step areas and at any cross walkways.

FINAL STAGE MANUFACTURER VEHICLE CERTIFICATION

A final stage manufacturer vehicle certification label shall be provided and installed in the driver cab door jamb area.

Aspen Fire Protection District

Type III Engine, SVI #1080

BUMPER

The International cab/chassis supplied swept-back style bumper shall be provided. The bumper shall come with openings for front bumper discharge(s), if specified and painted cab color choice.

FRONT BUMPER EXTENSION

The front bumper of the chassis shall be extended approximately 20" ahead of the cab using Junior I-beams.

The bumper mounting plate shall be welded to the Junior I-beam for mounting of the chassis bumper. After fabrication of the bumper extension, the panels shall be removed and the unit shall be primed and painted black.

BUMPER GRAVEL SHIELD

The front bumper extension shall have a 3/16" NFPA compliant aluminum tread plate gravel shield. The gravel shield shall cover the full width of the front bumper to the front of the cab and the full height of the bumper on each end.

BUMPER PRE-CONNECT COMPARTMENT

The bumper extension shall have one (1) fire hose pre-connect compartment capable of storing 200' of 1 3/4" hose and nozzle. The compartment shall be as large as room allows. Compartment door shall be 1/8" NFPA compliant aluminum tread plate with stainless steel hinge wrapped with vinyl and chrome push release type latches. Door shall be notched to allow fire hose to be pre-connected to swivel located on streetside of front bumper. The compartment door shall have a gas shock type hold open device. This compartment shall not be watertight but shall include a compartment drain.

A safety sign FAMA22, which warns of the need to secure hose, shall be visible to personnel at each hose storage area.

If the bumper compartment is greater than 4 cu.ft. in volume and has an opening greater than 144 sq.in. it shall have sufficient compartment lighting to provide a minimum of 2 fc (20 lx) at any location on the floor of the compartment without any equipment in the compartment. There shall be one (1) 9" OnScene LED type ground light mounted below the bumper.

A flashing warning light signal shall be provided indicating when a compartment door is not in a closed position as required by NFPA 1901.

AIR HORNS

Two (2) Grover 24" Stuttertone chrome plated air horns shall be mounted, one (1) each side of the cab hood. An emergency air shut off valve shall be provided in cab.

AIR HORN ACTIVATION

The air horn(s) shall be operated by a foot switch on the cab floor located at both the driver and officer positions.

AIR INTAKE SYSTEM

An air filter shall be provided in the engine's air intake system by the commercial cab/chassis manufacturer. Air inlet restrictions shall not exceed the engine manufacturer's recommendations. The air inlet shall be equipped with a means of separating water and burning embers from the air intake system.

In addition to the engine's air intake, the cab fresh air intake and/or outside cab vent shall be equipped with a means of separating water and burning embers from the air intake system

Aspen Fire Protection District

Type III Engine, SVI #1080

This requirement shall be permitted to be achieved by either of the following methods:

1. Provision of a device such that burning particulate matter larger than 0.039 in. (1.0 mm) in diameter cannot reach the air filter element.
2. Provision of a multi screen ember separator capable of meeting the test requirements defined in the Parker Hannafin, Racor Division, publication LF 1093-90, *Ember Separation Test Procedure*, or an equivalent test.

EXHAUST

The exhaust system shall be as provided by cab/chassis manufacturer. The tailpipe may require some modifications for proper ground clearances and fit with body.

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the vehicle or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position or entry doors on body.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

Exhaust to be 90 degrees to side of body for exhaust removal system.

RADIO/ANTENNA INSTALLATION

There shall be two (2) Aspen Fire Protection District supplied radio(s) with antenna installed in the cab within easy reach of driver. The location of radio shall be determined by the Aspen Fire Protection District at the pre-construction meeting. All required radio programming shall be responsibility of Aspen Fire Protection District. Radio(s) may not be fully tested if no radio program is provided with radio and will be responsibility of Aspen Fire Protection District after delivery.

Radio shall be installed per Manufacturer's requirements and wired for proper 12 volt power and ground.

MULTIMEDIA INTERFACE DISPLAY

A Pioneer Electronics model number: AVH-X491BHS or equivalent Multimedia Interface Display shall be incorporated into the dash of cab. Custom mounting required shall provide a pleasing appearance as well as an ergonomical use by driver. Component shall have the following minimum functions:

- HD Radio Tuner.
- Bluetooth interface.
- iPod/iPhone Smartphone integration.
- 7" Touch Screen Display with Backlight.
- SAT Radio Connectivity (requires optional service).
- Navigation System (Requires AVIC-U280 module).
- CD/DVD Player.
- Rearview Display (Requires optional camera).

Aspen Fire Protection District

Type III Engine, SVI #1080

SEAT BELT COLOR

Section 14.1.3.4 of the NFPA 1901 Standards, requires all seat belt webbing in cab to be bright red or bright orange in color, and the buckle portion of the seat belt shall be mounted on a rigid or semi rigid stalk such that the buckle remains positioned in an accessible location.

SEAT BELT WEB LENGTH - COMMERCIAL CAB

Sections 14.1.3.2 and 14.1.3.3 of the NFPA 1901 standards, require the effective seat belt web length for a Type 1 lap belt for pelvic restraint to be a minimum of 60", and a Type 2 pelvic and upper torso restraint-style seat belt assembly to be a minimum of 110".

The chassis seat belt web length as supplied by the commercial chassis manufacturer shall be compliant to NFPA Standards 14.1.3.2 and 14.1.3.3.

SEAT BELT MONITORING AND VEHICLE DATA RECORDER (VDR) SYSTEMS

SEAT BELT MONITORING

A Weldon 6204 series system with Occupant Restraint Indicator (ORI) display shall be provided and installed to allow the driver to know if all persons seated in the vehicle are secured with seat belts before moving the vehicle. Built-in smart seating logic shall detect if the correct sit and buckle sequence is not followed for all seats. System shall also provide an output for an external alarm. Weldon diagnostic port will be located under dash on driver side. System shall include the following features;

VEHICLE DATA RECORDER (VDR)

The vehicle data recorder shall have the following features;

- Recorded Data Includes: Vehicle Speed, Acceleration, Deceleration, Engine Speed, Engine Throttle Position, ABS Event, Seat Occupied Status, Seat Belt Status, Master Optical Warning Switch, Park Brake, Service Brake, Time, Date and Engine Hours.
- Password Protected by the customer
- Six (6) seat position inputs for occupied and belts buckled. Additional six (6) seat expansion module available.
- Easily interfaces with traditional wiring, or optional V-MUX™ or other multiplexing systems
- Data is extracted by a standard, mini USB cable
- Use in conjunction with the Occupant Restraint Indicator or optional V-MUX™ multiplex system

OCCUPANT RESTRAINT INDICATOR

The occupant restraint indicator shall have the following features;

- Supports commercial and custom cab seating layouts; up to 12 seats
- Built-in audible alarm
- Use in conjunction with Vehicle Data Recorder (VDR)

IGNITION KEY

If the vehicle is specified to have an ignition key it will be attached to steering column or dash with vinyl covered steel cable.

Aspen Fire Protection District

Type III Engine, SVI #1080

SIX (6) – LED TIRE PRESSURE VISUAL INDICATORS

Each tire valve stem shall be equipped with an LED Tire Alert (or equal), heavy duty valve cap LED indicator that indicates proper tire pressure. The LED Tire Alert valve cap is self-calibrating. When the cap is mounted on the valve stem the first time, it will memorize that tire pressure, and can be set to recognize a drop in pressure as little as 6 psi. It can be checked for functionality and battery condition by simply unscrewing the cap. If it is in working condition, it will immediately start blinking.

HELMET STORAGE

No helmet storage is required in the cab driving area.

HELMET STORAGE

No helmet storage is required in the cab crew area.

CAB CRASH TEST CERTIFICATION

A cab crash test certification from the fire apparatus manufacturer shall be provided with the equipment. A copy of this certification shall be included with the bid.

NOTE: There shall be no exception to any portion of the cab integrity certification requirements. Nonconformance shall lead to immediate rejection of bid.

The certification shall state that the cab does meet or exceed the requirements below:

- 1) European Occupant Protection Standard ECE Regulation No. 29.
- 2) SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks.

CAB MIRRORS, DRIVER ADJUSTABLE

Section 14.3.5 of the NFPA 1901 Standards, 2009 edition, requires all primary rear view mirrors used by the driver to be adjustable from the driver's position.

CAB STEP AND FUEL TANK COVER

The stock cab upper and lower entry steps shall be overlaid with 1/8" NFPA compliant aluminum treadplate. There will be a removable panel to access and replace the chassis batteries and a hinged fuel fill access door.

The maximum stepping height shall not exceed 18", with the exception of the ground to first step, which shall not exceed 24" when the vehicle is loaded to its estimated in-service weight. All steps shall have a minimum area of 35 sq in and shall be of such a shape that a 5" diameter disk does not overlap any side when placed on the step, and shall be arranged to provide a t least 8" of clearance between the leading edge of the step and any obstruction. All platforms shall have a minimum depth of 8" from the leading edge of the platform to any obstruction.

The following options will be cut into the step cover:

BATTERY CHARGING RECEPTACLE LOCATION

The specified battery charging receptacle and/or display panel shall be located on front face of specified cab step cover.

Aspen Fire Protection District

Type III Engine, SVI #1080

MUDFLAPS

There shall be 1/4" rubber mudflaps provided and installed behind each set of tires to prevent throwing road debris and lower road spray.

AIR BRAKE SYSTEM QUICK BUILD-UP

There shall be one (1) Kussmaul Air Auto Eject type air shoreline inlet to provide air to the chassis air tanks from an external source compressed air shoreline hookup in order to maintain full operating air pressure while the vehicle is not running. Shore air connection shall automatically disengage from vehicle when the chassis ignition is engaged. Air inlet shall be located near driver's door. The female end of the connector shall be supplied by the Aspen Fire Protection District.

The quick buildup system shall provide sufficient air pressure so that the apparatus has no brake drag and is able to stop under the intended operating conditions following the 60-second buildup time.

ROAD EMERGENCY SAFETY KIT

The completed unit shall be supplied with one (1) set of three (3) dual faced reflective triangles, and three (3) warning flares complete with storage case per DOT requirements.

One (1) 2.5 lb. ABC type vehicle fire extinguisher with bracket per DOT requirements shall be provided and mounted inside cab area.

CAB STORAGE CABINET

There shall be one (1) full height cabinet located in rear center cab area between rear crew seats fabricated from 1/8" smooth aluminum. The cabinet shall be finished with a dark gray hammer tone powder coat paint for a hard and durable finish.

Lower section shall extend forward of full height cabinet approximately 26" high and have a hinged lift-up lid and will hold four (4) SCBA bottles stored vertically.

Upper section approximately 23" wide x 18" deep shall have a ROM series IV un-painted roll-up door.

There shall be one (1) OnScene Solutions 54" Night Axe LED light(s) mounted inside the cabinet.

- Cabinet shall be provided with vertically mounted shallow aluminum Shelf-Trac for specified component installation.
- There shall be two (2) adjustable shelf/shelves in the above cabinet(s). Each shelf shall have a 1.25" vertical lip at front to contain items while vehicle is in motion.
- A keyed cylinder lock shall be provided on bottom rail of the roll-up door.
- There shall be one (1) Blue Sea Systems 100 amp ST Series blade type fuse block with screw type terminals for both positive and negative buss with cover provided for distribution of up to six (6) 30 amp, 12 VDC circuits. Fuse block shall be located per required circuits and be protected from damage.
 - Locate the 12VDC Fuse block to be in this rear cab cabinet.

Aspen Fire Protection District

Type III Engine, SVI #1080

- There shall be two (2) 120 VAC outlet(s) located inside cabinet against the back wall, and run off the inverter with a transfer switch.
 - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
 - Outlet(s) shall be powered by both the on-board generator and shore power system through a relay system.

BODY DESIGN

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the Aspen Fire Protection District to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the Aspen Fire Protection District from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

EXTERIOR ALUMINUM BODY

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas, No Exceptions.

The front and rear corners of body shall be formed as part of the front or rear body panels. This provides a stronger body corner and finished appearance. The use of extruded corners, or caps will not be acceptable, No Exceptions.

Aspen Fire Protection District

Type III Engine, SVI #1080

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded and caulked to prevent moisture from entering the compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

DRIP RAILS

The body shall have drip rails over the side full height compartments. The drip rails shall be formed into the upper body panels providing a ridged lower panel and a flat upper body panel surface. The use of mechanically fastened, taped or glued on drip rails will not be acceptable, No Exceptions.

BODY SUBFRAME

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 4" x 1/4" aluminum tubes minimum, the same width as the chassis frame rails. Welded to this tubing shall be cross members of 2" x 4" x 1/4" aluminum. Smaller dimension, lighter gauge tubing or angle material subframe shall not be accepted.

These cross members shall extend the full width of the body to support the compartments. Cross members shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum cross members shall be located on 16" centers, or as necessary to support walkway or heavy equipment.

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.

Aspen Fire Protection District

Type III Engine, SVI #1080

BODY MOUNTING

The body subframe shall be fastened to the chassis frame with a minimum of four (4) spring loaded body mounts. Each mount shall be configured using a two-piece encapsulated slide bracket. The two (2) brackets shall be fabricated of heavy duty 1/4" thick steel and shall have a powder coat finish to prevent any corrosion. Each mounting assembly shall utilize two (2) 3/4" diameter x 6" long grade 8 bolts and two (2) heavy duty springs. The assembly design shall allow the body and subframe to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall eliminate any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement will not be acceptable.

REAR BUMPER (FLAT)

The full width rear bumper shall be constructed from minimum 2" x 2" x 1/4" aluminum tubing and painted with black Scorpion finish. The bumper shall extend from the rear vertical body panel 2" with a minimum of 1/2" space between the body and bumper for water drainage.

REAR TOW EYES

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below body. The tow eyes shall be fabricated from 3/4" thick steel plate with a 3" diameter opening. Tow eyes shall have a black powder coat finish.

GROUND LIGHTS

There shall be two (2) OnScene 8" Access LED lights installed below bumper capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting shall be switchable but activated automatically when the vehicle park brake is set.

WHEEL WELL EXTERIOR PANEL

The exterior panel of the body wheel well enclosure shall be constructed from 3/16" smooth aluminum panels.

RUBBER BODY FENDERS

The body wheel well openings shall be provided with round radius, rubber fenderettes. The fenderettes shall be bolted and easily replaceable if damaged. The fenderettes shall be installed using stainless steel fasteners with plastic isolators to help prevent corrosion.

WHEEL WELL LINERS

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will not accumulate dirt or water.

Aspen Fire Protection District

Type III Engine, SVI #1080

ANGLED BODY PANEL BELOW SIDE REAR COMPARTMENTS

No angled body panel shall be provided below the side rear compartments.

SCBA CYLINDER COMPARTMENTS

There shall be four (4) SCBA cylinder storage compartments, two (2) on each side of body in the rear wheel well area. Each compartment shall have a stainless steel hinge with brushed stainless steel door assembly with a positive catch latch. Each compartment shall have a 8" diameter tube behind the wheel well panel attached to the door assembly. Each compartment shall allow the storage of an SCBA cylinder or a fire extinguisher up to 7-3/4" in diameter and 22" deep. The door shall activate the "Hazard Warning Light" in the cab when not in the closed position.

BODY PAINT SPECIFICATIONS

BODY PAINT PREPARATION

After the body and components have been fabricated they shall be disassembled so when vehicle is complete there shall be finish paint beneath the removable components. The body shall be removed from chassis during the paint process to insure proper paint coverage. The body and components shall be metal finished as follows to provide a superior substrate for painting.

The exterior (and interior, if painted) body shall undergo a thorough cleaning process starting with a biodegradable phosphoric acid solution to begin the etching process followed by a complete clear water rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the metal surface for greater film adhesion.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

PAINT PROCESS

The paint process shall follow the strict standards set forth by PPG Industries guidelines. Painters applying PPG products will be PPG Certified Commercial Technicians, and re-certified every two (2) years. The body shall go through the following paint process;

- 1) Clean bare metal with a wax and grease remover using low lint rags.
- 2) Inspect, straighten, and hammer high points, grind all seams, sharp edges, and welds. DA sand entire paintable surfaces using 24-180 grit dry paper. Plastic fill all low spots and DA sand fill areas using 36-180 grit dry paper. Apply pinhole filler and DA sand areas using 80-180 grit dry paper.
- 3) Re-clean bare metal using a wax and grease remover and low lint rags.
- 4) Within 24 hours, a PPG Delfleet® epoxy color primer with proper hardener for corrosion resistance using a pressure pot spray gun and applying 2-5 full wet coats or 1.5-8.0 dry mils max. achieving full hiding and allow to air dry 60 minutes @ 70°F or bake for 45 minutes @ 140°F degree.
- 5) Inspect, putty fill, and dry guild coat entire body surface and DA sand using 180-400 grit dry paper.
- 6) Re-clean bare metal using a wax and grease remover using low lint rags.
- 7) A PPG Delfleet® primer sealer with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 1 full wet coat or 1.0-2.0 dry mils achieving full hiding and allow to flash off in spray booth for minimum of 60 minutes @ 70°F.
- 8) A PPG Delfleet® FBCH basecoat (color) with proper hardener and dry additive shall then be sprayed using a pressure pot set @ 45-60 PSI and achieving full hiding or 1.5-2.0 wet mils and allow to flash off in spray booth 45-60 minutes before applying clearcoat.

Aspen Fire Protection District

Type III Engine, SVI #1080

- 9) A PPG Delfleet® clearcoat with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 2-3 full wet coats or 5.0 wet mils for a uniform gloss and allow to flash off in spray booth 10 minutes and bake for 120-140 minutes @ 125°F (surface temp.).
- 10) After cooling, DA sand heavy orange peel or runs using 1000 grit dry sand paper and final DA sand using 1500-2000 grit dry sand paper. Wipe off all surfaces to remove dust and debris. Buff unit as needed using 3M rubbing compound and a white wool pad and inspect until all sand scratches are removed.
- 11) Polish as needed using 3M Perfect-It-Polish and a black foam pad, repeat as necessary and inspect until all sand scratches are removed.

PAINT - ENVIRONMENTAL IMPACT

The contractor shall meet or exceed all current State (his) regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. PPG Delfleet® Evolution paint shall be free of all heavy metal (lead & chromate) components. Paint emissions from sanding and painting shall be filtered and collected. All paint wastes shall be disposed of in an environmentally safe manner. Solvents used in cleanup operations shall be collected, sent off-site for distillation and returned for reuse.

FASTENERS

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, a Mylar isolation tape, or gasket shall be used to prevent damage to the finish painted surface. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nut-surts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

ELECTROLYSIS CORROSION CONTROL

The vehicle shall be assembled using ECK brand or similar corrosion control compound on all high corrosion potential areas.

ECK protects aluminum and stainless steel against electrolytic reaction, isolates dissimilar metals and gives bedding protection for hardware and fasteners. ECK contains anti-seizing lubricant for threads. ECK is dielectric and perfect for use with electrical connectors.

PAINT FINISH - SINGLE COLOR

The body shall be painted with a single color of PPG Delfleet® Evolution per Aspen Fire Protection District approved paint spray out provided.

A small touch-up bottle of paint shall be provided with completed vehicle.

- Paint Color: Match cab/chassis supplied paint color.

BODY UNDERCOATING

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

Aspen Fire Protection District

Type III Engine, SVI #1080

UNDERCOAT WARRANTY

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

PAINT WARRANTY

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle. **Pro-rated warranties will not be acceptable.**

COMPARTMENT INTERIOR FINISH

The compartment interior paintable surfaces shall be prepared and DA sanded using 80-120 grit dry paper and cleaned with a wax and grease remover. A PPG Delfleet® primer topcoat of either a solids epoxy primer or an etch primer shall be applied.

A PPG Delfleet® color primer with proper hardener and thinner mix shall then be sprayed using a pressure pot spray gun and applying 2 wet coats achieving full hiding on entire compartment surface and allow to air dry for 30 minutes @ 70°F before applying texture coat.

A PPG Delfleet® F3985 White/F3986 Gray top coat/texture coat with proper hardener and dry additive shall then be sprayed using a pressure pot and reducing the atomizing air pressure and turn fan pattern all the way in on the gun. Apply the first color texture coat as needed and allow to air dry @ 70°F over night before assembly and 7 days before putting into full service.

REFLECTIVE STRIPE REQUIREMENTS

Material

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retro-reflection of 10 with observation angle of 0.2 degrees and entrance angle of -4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

Minimum Requirements

A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 4 in. (100 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

Aspen Fire Protection District

Type III Engine, SVI #1080

GRAPHICS PROOF

A color graphics proof of the reflective striping layout shall be provided for approval by Aspen Fire Protection District prior to installation. The graphics proof shall be submitted to Aspen Fire Protection District on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

REFLECTIVE STRIPE - CAB SIDE

The reflective stripe material shall be 10" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

REFLECTIVE STRIPE - CAB FRONT

The reflective stripe material shall be 10" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

CHEVRON STRIPE - CAB BUMPER

A reflective stripe shall be affixed to the front of cab. The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The approximate 10" wide Chevron retroreflective stripe shall be affixed to at least 25 percent of the width of the front of the apparatus with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width. Chevron panels shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panels shall have a minimum 10 year warranty for material failure, and colorfastness.

- The stripe material shall be 3M Scotchlite Diamond Grade.

All retroreflective materials required shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

REFLECTIVE STRIPE - CAB DOOR INTERIOR

Any door of the apparatus designed to allow persons to enter or exit the apparatus shall have at least 96 in.2 (62,000 mm2) of retroreflective material affixed to the inside of the door.

The stripe material shall be 3M Scotchcal 680.

- This reflective stripe shall be white in color.

Aspen Fire Protection District

Type III Engine, SVI #1080

REFLECTIVE STRIPE - BODY SIDES

The reflective stripe material shall be 10" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color.

The stripe shall remain in a straight line from the front of the front of cab to the rear body.

CHEVRON REFLECTIVE STRIPE - REAR CENTER/SIDE PANELS

At least 50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width.

The rear side panels and center of the body shall have a chevron style reflective stripe, extending from bumper height up to side compartment drip rail height. Chevron panels shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panels shall have a minimum 10 year warranty for material failure, and colorfastness.

The stripe material shall be 3M Diamond Grade.

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

LETTERING

GRAPHICS PROOF

A color graphics proof of the lettering layout shall be provided for approval by Aspen Fire Protection District prior to installation. The graphics proof shall be submitted to Aspen Fire Protection District on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

The following lettering shall be provided and installed on the completed unit as follows;

SIDE CAB DOOR LETTERING

There shall be ten (10) 4" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

Final design and layout shall be determined prior to construction.

"ASPEN" Forward cab doors upper.

There shall be forty four (44) 3" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

Final design and layout shall be determined prior to construction.

"FIRE PROTECTION DISTRICT" forward cab doors lower.

Aspen Fire Protection District

Type III Engine, SVI #1080

There shall be six (6) 8" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

Final design and layout shall be determined prior to construction.

"E-63" crew cab doors.

There shall be three (3) 11" high reflective letters furnished and installed on the vehicle.

"E-63" on RC1 compartment door.

- This reflective lettering shall be white in color.

CAB ROOF LETTERING

There shall be three (3) 22" high reflective letters furnished and installed on the vehicle.

E-63

- This reflective lettering shall be white in color.

Aspen Fire Protection District

Type III Engine, SVI #1080

EXTERIOR COMPARTMENT DOORS

ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM)

The vehicle shall be equipped with R•O•M Series IV roll-up exterior compartment doors. The R•O•M roll-up doors shall be complete with the following features;

Each shutter slat, track, bottom rail, and drip rail shall be constructed from anodized 6063 T6 aluminum. Shutter slats shall feature a double wall extrusion 0.315" thick with a concave interior surface to minimize loose equipment jamming the shutter door closed. Shutter slats shall feature an interlocking end shoe to prevent side to side binding of the shutter door during operation. Slat must have interlocking joints with an inverted locking flange. Slat inner seal shall be a one piece PVC extrusion; seal design will be such to prevent metal to metal contact while minimizing dirt and water from entering the compartment.

Shutter door track shall be one piece design with integral overlapping flange to provide a clean finished look without the need of caulk. Door track shall feature an extruded Santoprene rubber double lip low profile side seal with a silicone co-extruded back to reduce friction during shutter operation.

Shutter bottom rail shall be a one piece double wall extrusion with integrated finger pull. Finger pull shall be curved upward with a linear striated surface to improve operator grip while operating the shutter door. Bottom rail shall have a smooth contoured interior surface to prevent loose equipment from jamming the shutter door. Bottom rail seal shall be made from Santoprene; it will be a double "V" seal to prevent water and debris from entering compartment. Bottom rail lift bar shall be a one piece "D" shaped aluminum extrusion with linear striations to improve operator grip during operation. Lift bar shall have a wall thickness of 0.125". Lift bar shall be supported by no less than two pivot blocks; pivot blocks shall be constructed from Type 66 Glass filled reinforced nylon for superior strength. Bottom rail end blocks shall have incorporated drain holes which will allow any moisture that collects inside the extrusion to drain out.

Shutter door shall have an enclosed counter balance system. Counter balance system shall be 4" in diameter and held in place by two (2) heavy duty 18 gauge zinc plated plates. Counter balance system shall have two (2) over-molded rubber guide wheels to provide a smooth transition from vertical track to counter balance system; no foam material of any kind shall be permitted or used in this area.

ROM DOOR BOTTOM RAIL

All exterior compartment doors shall have the standard 3.0" tall bottom rail extrusion for easy one (1) hand opening and closing.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.

Aspen Fire Protection District

Type III Engine, SVI #1080

STREETSIDE COMPARTMENT - FRONT (S1)

The interior useable compartment width shall be approximately 15.2" wide x 14" deep

The compartment door opening shall be approximately 12.5" wide.

- This compartment shall have vertically hinged lap style compartment door with push release style latches. The door exterior shall be painted job color.
- The interior door panel shall have a smooth un-painted aluminum panel.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The hinged door(s) shall have a pneumatic cylinder to hold door in the open and closed positions. Each door shall be capable of being closed without unlatching. Door checks shall be bolted to the compartment door header and the box pan of the door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- The floor shall have a 2" vertical retention lip located on outer edge of compartment floor.
- One (1) OnScene Access LED, full height compartment light, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

Aspen Fire Protection District

Type III Engine, SVI #1080

STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S2)

The interior useable compartment width shall be approximately 54.0" wide.

The compartment door opening shall be approximately 49.5" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- A keyed cylinder lock shall be provided on bottom rail of the roll-up door.
- One (1) nylon strap shall be provided to assist in closing the door.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- The floor shall have a 2" vertical retention lip located on outer edge of compartment floor.
- There shall be vertically mounted aluminum Shelf-Trac welded to compartment walls for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf/shelves approximately 12" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.
 - The above component(s) shall have a smooth un-painted finish.
- The floor shall have a 2" vertical retention lip located on outer edge of compartment floor.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.

Aspen Fire Protection District

Type III Engine, SVI #1080

STREETSIDE COMPARTMENT - REAR (S3)

The interior useable compartment width shall be approximately 47.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- A keyed cylinder lock shall be provided on bottom rail of the roll-up door.
- One (1) nylon strap shall be provided to assist in closing the door.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- The floor shall have a 2" vertical retention lip located on outer edge of compartment floor.
- There shall be vertically mounted aluminum Shelf-Trac welded to compartment walls for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be two (2) adjustable shelf/shelves approximately 12" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.
 - The above component(s) shall have a smooth un-painted finish.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

Aspen Fire Protection District

Type III Engine, SVI #1080

CURBSIDE COMPARTMENT - FRONT (C1)

The interior useable compartment width shall be approximately 15.2" wide x 14" deep.

The compartment door opening shall be approximately 12.5" wide.

- This compartment shall have vertically hinged lap style compartment door with push release style latches. The door exterior shall be painted job color.
- The interior door panel shall have a smooth un-painted aluminum panel.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- The hinged door(s) shall have a pneumatic cylinder to hold door in the open and closed positions. Each door shall be capable of being closed without unlatching. Door checks shall be bolted to the compartment door header and the box pan of the door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be one (1) slide-out smooth aluminum vertical tool board(s) approximately 14" deep. Each tool board(s) vertical exterior edge shall have a double 90 degree formed edge to provide an easy grip handle. The top and bottom of tool board(s) shall be provided with Accuride 9300 series slide tracks. Each board shall be rated for a maximum 200 lbs. evenly distributed load. Each tool board shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions.
 - The vertical tool board material shall be 3/16" (.188) 3003H-14 aluminum alloy sheet.
 - The above component(s) shall have a smooth un-painted finish.
 - Each tool board will be bolted to compartment floor.
- There shall be four (4) Zico ULLH walkaway type SCBA air pack bracket(s) with "V" type clip and strap assembly to hold SCBA in place.
- One (1) OnScene Access LED, full height compartment light, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

Aspen Fire Protection District

Type III Engine, SVI #1080

CURBSIDE COMPARTMENT - ABOVE REAR WHEELS (C2)

The interior useable compartment width shall be approximately 54.0" wide.

The compartment door opening shall be approximately 49.5" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- A keyed cylinder lock shall be provided on bottom rail of the roll-up door.
- One (1) nylon strap shall be provided to assist in closing the door.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- The floor shall have a 2" vertical retention lip located on outer edge of compartment floor.
- There shall be vertically mounted aluminum Shelf-Trac welded to compartment walls for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf/shelves approximately 12" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.
 - The above component(s) shall have a smooth un-painted finish.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.

Aspen Fire Protection District

Type III Engine, SVI #1080

CURBSIDE COMPARTMENT - REAR (C3)

The interior useable compartment width shall be approximately 47.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- A keyed cylinder lock shall be provided on bottom rail of the roll-up door.
- One (1) nylon strap shall be provided to assist in closing the door.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- The floor shall have a 2" vertical retention lip located on outer edge of compartment floor.
- There shall be vertically mounted aluminum Shelf-Trac welded to compartment walls for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be two (2) adjustable shelf/shelves approximately 12" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.
 - The above component(s) shall have a smooth un-painted finish.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

Aspen Fire Protection District

Type III Engine, SVI #1080

REAR COMPARTMENT - CENTER (RC1)

The rear center compartment shall start at the top of rear bumper and be as high as hose bed, unless specified otherwise.

The interior useable compartment width shall be approximately 50.0" wide.

The compartment door opening shall be approximately 31.0" wide.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- A keyed cylinder lock shall be provided on bottom rail of the roll-up door.
- One (1) nylon strap shall be provided to assist in closing the door.
- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.

COMPARTMENT LAYOUT

- The floor shall have a 2" vertical retention lip located on outer edge of compartment floor.
- There shall be vertically mounted aluminum Shelf-Trac welded to compartment walls for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be two (2) aluminum handrail sections with brackets assembled under the hose bed extension step. Brackets shall be designed to hold the handrails in position with a quick pin to hold in place for operation. Inside the right rear ladder compartment door shall be a storage bracket to hold the handrails when not in use. The I-Zone brackets are provided to lace the hose between when moving from house to house during structure fire protection operations.
- One (1) booster hose reel(s) shall be located in this compartment area.

Booster reel in upper section of compartment.

- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.

PLASTIC FLOOR AND SHELF TILE

All compartment floors, shelves, and trays shall be covered with Dri-Dek plastic interlocking grating.

- The plastic floor tile shall be red.

Aspen Fire Protection District

Type III Engine, SVI #1080

ROPE ANCHOR OR PORTABLE WINCH RECEIVERS

The completed unit shall have an integrated receiver or anchor system for use with removable rope anchor point and/or a portable electric winch, when specified.

Receivers or anchors installed at any location on the apparatus for use as removable winch anchors shall be designed and affixed to provide at least a 2.0 to 1 straight line pull no-yield safety factor over the load rating of the removable winch.

Receivers or anchors installed at any location on the apparatus for use with rope operations shall be designed and affixed to the apparatus to provide at least a 9,000 lbf (40,000 N) no-yield condition with a straight line pull.

A safety sign FAMA28 shall be located on or near each receiver or anchor stating the maximum straight line pull rating.

Side receiver(s) (if specified) shall have the following load rating:

| | <u>STRAIGHT PULL</u> | <u>SAFETY FACTOR</u> |
|---------------|----------------------|----------------------|
| Rope Tie Off: | 600 Lbs. | 15:1 |
| Winch: | 5,000 Lbs. | 2:1 |

Front and/or rear receiver(s) (if specified) shall have the following load rating:

| | <u>STRAIGHT PULL</u> | <u>SAFETY FACTOR</u> |
|---------------|------------------------------------|----------------------|
| Rope Tie Off: | 600 Lbs. | 15:1 |
| Winch: | Winch Load Rating (9,000 Lbs. Max) | 2:1 |

The following items shall be provided to accomplish rope rescue and/or portable winch operation;

- Two (2) removable rope anchor(s) shall be provided with completed vehicle. Each rope anchor shall be fabricated from 3/4" steel, 2" high x 11.5" long with a 3" OD/2" ID eyelet. Eyelet end shall have radiused edge to prevent damage to rope or carabineer. Each rope anchor shall have a black hammertone powder coat paint finish and a steel 5/8" hitch pin to lock it in place. An aluminum mounting bracket shall be provided to store rope anchor(s) inside a body compartment as close to receiver location as possible.
- There shall be one (1) 2" x 2" x 1/4" wall steel receiver tube(s) with a black hammertone powder coat paint finish located at the front bumper for use with removable rope anchor point and/or a portable electric winch (if specified).
 - There shall be one (1) 12 VDC plug(s) with quick connect provided to power a Ramsey portable winch. All 12 VDC cables to be sized according to Ramsey and installation for intended use.
 - The receiver(s) shall have one (1) rubber cover(s) provided.
- There shall be one (1) 2" x 2" x 1/4" wall steel receiver tube(s) with black hammertone powder coat paint finish located at the rear bumper for use with removable rope anchor point and/or a portable electric winch (when specified).
 - There shall be one (1) 12 VDC plug(s) with quick connect provided to power a Ramsey portable winch. All 12 VDC cables to be sized according to Ramsey and installation for intended use.
 - The receiver(s) shall have one (1) rubber cover(s) provided.

Aspen Fire Protection District

Type III Engine, SVI #1080

LADDER LIFT SYSTEM, CURBSIDE

A Ziamatic 12 VDC, 60 amp, HLAS (Horizontal Ladder Access System), model HLAS-975 shall be provided above the exterior side body compartments, on the curbside.

The lift system shall be electro-hydraulic with built-in electric safety latches and warning alarm when in operation. Access shall still be provided to compartments with system in lowered position. Flashing lights on ends shall produce a visual signal when the system is out of the stored position. A flashing warning light signal shall be provided indicating when a ladder rack is not in a stowed position as required by NFPA 1901. The outward ends of the equipment rack that protrude beyond the body of the apparatus shall have retroreflective material to indicate a hazard or an obstruction.

The ladder control panel shall be located on curbside pump panel. The ladder lift system shall be designed to store the specified ladders and equipment. The side of ladder storage area shall be enclosed with an aluminum panel and painted the same color as body.

LADDER LIFT INTERLOCK

An interlock circuit shall be included on the ladder lift system to prevent the lift from raising if a specified hose bed or compartment doors are in the open position.

Storage shall be provided for the following;

- One (1) 24' 2-section ladder(s). Manufacturer, model number of the ladder shall be provided in equipment section of specification, or at pre-construction meeting when provided by Aspen Fire Protection District.
- One (1) 14' roof ladder(s). Manufacturer, model number of the ladder shall be provided in equipment section of specification, or at pre-construction meeting when provided by Aspen Fire Protection District.
- One (1) 10' folding ladder(s). Manufacturer, model number of the ladder shall be provided in equipment section of specification, or at pre-construction meeting when provided by Aspen Fire Protection District.
- Two (2) pike pole(s). Manufacturer, model number of the pike pole shall be provided in equipment section of specification, or at pre-construction meeting when provided by Aspen Fire Protection District.
- One (1) 10' length of hard suction hose. Hard suction hose(s) shall be supplied by contractor with completed unit. See equipment section.

NO EQUIPMENT STORAGE, REAR STREETSIDE

No equipment storage compartment shall be provided on rear facing streetside of body. The specified streetside compartments shall now be 24" deep.

NO EQUIPMENT STORAGE, REAR STREETSIDE

No equipment storage compartment shall be provided on rear facing curbside of body. The specified curbside compartments shall now be 24" deep.

Aspen Fire Protection District

Type III Engine, SVI #1080

LOWER SIDE BODY PROTECTION - RUB RAIL

OnScene Solutions rub rails shall be provided below the compartment door openings on both the streetside and curbside.

The rub rail shall be fabricated from 6063 extruded aluminum, measuring approximately 2-3/4" high x 1-3/8" thick with tapered aluminum end caps. The rub rail shall be bolted to the body using stainless steel bolts and 1-1/2" diameter x 5/8" thick rubber mount isolators to prevent damage to the body.

The rails shall incorporate LED clearance marker lighting recessed into the rail fascia to avoid damage to the light in case of impact. The rub rail shall have an accessory mounting track integrated into the backside of the rail to allow mounting of accessories such as ground lighting.

3M™ Diamond Grade™ Conspicuity striping shall be provided in the rub rail. The striping shall be white in color.

FRONT PROTECTION PANELS

To protect areas subject to intensive wear, scuffing or abuse, protection panels shall be installed on the front vertical body panels and wrapped around to the front compartment door opening. The protection panels shall be fabricated from 1/8" aluminum treadplate.

ROOF ACCESS LADDER

The top of the body shall be accessible from the ground by a folding ladder. The ladder design will have a main ladder section, bolt on upper hand rail section and a folding lower step section for better angle of departure. Ladder stores in a folded position and then pulls out to a comfortable climbing angle. The ladder shall be parallel to the body when in the stored position.

Each cast aluminum step shall be 4-1/2" deep x 16" wide. Hand railing shall be 2-1/8" oval shaped aluminum tubing with a ribbed gripping surface.

The ladder shall be wired to the door ajar warning light in cab to warn the driver that the ladder is in the down position. Ladder shall be mounted to body with stainless steel bolts.

Ladder shall be located on rear streetside of the body.

WALKWAY/STEP LIGHTS

There shall be two (2) OnScene Solutions Rough-Service 9" LED lights provided to illuminate the walkway or step area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

Lighting shall provide illumination at a minimum level of 2 fc (20 lx) on all work surfaces, steps, and walkways. Lighting shall be switchable but activated automatically when the vehicle park brake is set.

Aspen Fire Protection District

Type III Engine, SVI #1080

WALKWAY EXTENSION STEP

A full walkway width x 8.5" deep, bolt-on type extension step shall be provided for safe transition from specified ladder to center walkway area. Step shall be fabricated from 3/16" NFPA compliant treadplate aluminum with side gusset supports to body. The specified center rear marker lights shall be located on rear facing edge. The underside of step shall have an 28" OnScene LED light to light the bumper or compartment area below.

REAR BODY HANDRAILS

There shall be two (2) 24" horizontal handrails on rear body. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

PUMP MODULE HANDRAILS

There shall be two (2) 24" handrails, one (1) each side of pump module for access to upper dunnage area. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

FOLDING STEP(S)

There shall be four (4) Innovative Controls polished cast aluminum folding step(s) provided and installed on completed vehicle. Each step shall be heavy duty with stainless steel spring and textured step surface meeting NFPA standards. Each step shall include an LED light.

Location(s): Front of body streetside.

LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC

General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125% of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10%. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

Aspen Fire Protection District

Type III Engine, SVI #1080

Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage over-current protective devices. Such devices shall be readily accessible and protected against heat in excess of the over-current device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- 1) SAE J156, *Fusible Links*
- 2) SAE J553, *Circuit Breakers*
- 3) SAE J554, *Electric Fuses (Cartridge Type)*
- 4) SAE J1888, *High Current Time Lag Electric Fuses*
- 5) SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125% of maximum current for which the circuit is protected.

Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

Aspen Fire Protection District

Type III Engine, SVI #1080

Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- 1) The propulsion engine and transmission
- 2) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- 3) The radio(s) at a duty cycle of 10 percent transmit and 90% receive (for calculation and testing purposes, a default value of 5 A continuous)
- 4) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- 5) The minimum optical warning system, where the apparatus is blocking the right-of way
- 6) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- 7) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

Aspen Fire Protection District

Type III Engine, SVI #1080

12 VOLT DIAGNOSTIC RELAY CONTROL CENTER

The 12 volt power distribution shall be conveniently located with easy access for service. All relays and circuit breakers shall be plug-in type allowing for removal for repairs without necessitating soldering or tools. The sockets mounts for both the relays and circuit breakers shall be of a design that permits the use of standard automotive type components.

The 12 volt distribution panel shall utilize printed circuit boards mounted in high strength enclosure. Each printed circuit board shall be provided with twelve (12) heavy duty independent switching relays. Each relay shall have the ability to be configured either normally open or normally closed and be protected by a 20 amp automatic reset breaker. Each circuit will be provided with a LED for visual diagnostic.

Power distribution panel shall be located in apparatus body within a protected enclosure with removable or hinged cover.

CAB CONSOLE

A center cab console shall be provided between the Driver's and Officer's seats. Console shall be as large as possible and fabricated of 1/8" smooth aluminum. A textured powder coat paint finish shall be provided for durability and finished appearance.

The rear portion of the console shall be provided with open top storage for notebooks or maps. Two (2) adjustable dividers shall be provided in the storage area. The forward portion of console shall be slanted for mounting of siren head, radio or 12 volt control panel, and etc, with easy access to both Driver and Officer.

The final design of console shall be determined by the Aspen Fire Protection District at the pre-construction meeting.

Console similar to Dallas #887 without cup holders.

The following options shall be provided in specified console. Final layout to be determined by Aspen Fire Protection District at pre-construction meeting.

There shall be one (1) communications radio and/or siren 3" recess mount(s) with black powdercoat paint finish in specified console.

There shall be one (1) 120 VAC, 20 amp, duplex straight-blade receptacle (NEMA 5-20R) outlet(s) provided in specified console, one (1) in front, and one (1) in rear connected to shore power inlet. Final location to be determined at prebuild.

There shall be two (2) Blue Sea 12 VDC USB port(s) provided in specified console, one (1) in front, and one (1) in rear.

Aspen Fire Protection District

Type III Engine, SVI #1080

ELECTRICAL SYSTEM MANAGER

LOAD MANAGEMENT

If the total continuous electrical load exceeds the minimum continuous electrical output rating of the installed alternator(s), an Innovative Controls automatic electrical load management system shall be required. The minimum continuous electrical loads shall not be subject to automatic load management.

The apparatus 12 volt electrical system shall be provided with a system manager for:

- Monitoring chassis battery voltage
- Shedding pre-determined electrical circuits
- Sequencing pre-determined electrical circuits
- Automatically controlling chassis engine fast-idle
- Monitor master switch and parking brake applications
- Automatically control warning light modes ("Calling-For" and "Blocking Right of Way")
- Provide low voltage alarm
- Programmable control circuits
- Remote system status indicator panel

System manager shall perform all electrical functions required by current NFPA 1901 Standards.

BATTERY MONITORING

The system manager shall monitor the vehicle battery voltage. When electrical loads exceed the alternator output and the voltage drops, the load manager shall start shutting down electrical outputs. The system shall shut down only as many outputs required to maintain the system voltage. A special indicator to show different states of the electrical system by flashing at rate proportional to the battery discharge.

LOAD SEQUENCING AND SHEDDING

The system shall be capable of sequentially switching and shedding 12 volt loads. The Master light switch starts the sequential switch when it is turned "On". Likewise turning the Master Switch "Off" will sequentially de-energize the loads.

BATTERY SYSTEM

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Aspen Fire Protection District

Type III Engine, SVI #1080

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

An onboard battery conditioner or charger or a polarized inlet shall be provided for charging all batteries. Where an onboard conditioner or charger is supplied, the associated line voltage electrical power system shall be installed in accordance with Chapter 22.

One of the following master disconnect switches shall be provided:

- 1) A master body disconnect switch that disconnects all electrical loads not provided by the chassis manufacturer
- 2) A master load disconnect switch that disconnects all electrical loads on the apparatus except the starter

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

A green "battery disconnect on" indicator light that is visible from the driver's position shall be provided.

Rechargeable hand lights, radios, and other similar devices shall be permitted to be connected to the electrical system ahead of the master disconnect switch.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within 5 seconds.

BATTERY SWITCH

The chassis ignition key shall activate a heavy duty relay to provide 12 volt battery power to the vehicle. There shall be a green "BATTERY ON" pilot light that is visible from the driver's position.

BATTERY SOLENOID

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

BATTERY CONDITIONER

One (1) Kussmaul model 091-9-1000 Pump-Plus 1000, single battery charger/air compressor, with 120 VAC input, and 15 amp 12 VDC amp output battery conditioner with a 12 volt, 80 psi air compressor shall be provided and installed. This system shall monitor the condition of battery(s) and provide an electrical current at variable rates to overcome battery failure. The air compressor shall maintain air pressure in the chassis air brake system. A Kussmaul bar graph type indicator panel shall be provided for showing status of battery conditioner.

Aspen Fire Protection District

Type III Engine, SVI #1080

SHORE POWER INLET

One (1) Kussmaul 120 VAC, 20 amp Super Auto-Eject shore power inlet(s) shall be provided. The shore power connection shall automatically disengage from vehicle when chassis ignition is engaged.

The protective ground from the shoreline inlet shall be bonded to the vehicle frame.

- The outlet cover shall be red.
- The shore power plug shall be located near the Driver door area.

INVERTER

A Tripp-Lite model PV700, 700 watt inverter with three (2) 120 VAC outlets shall be provided on back of front console with outlets facing upward (provide outlet protection if necessary).

inside console

ENGINE COMPARTMENT LIGHT

There shall be one (1) OnScene Severe Service LED light(s) mounted in the engine compartment with integral switch with a light output of at least 20 candlepower (250 lumens). The engine compartment light(s) shall operate only when the master battery switch is turned "On".

INTERIOR CAB LIGHT, LED

Two (2) OnScene Solution model #70152, 10" x 6" x 7/8", 10-30 VDC, surface mount dual red and white LED light(s) with clear lens shall be provided on cab ceiling. Each light shall be individually switched with a high/low intensity setting. In addition light(s) will be capable of a 5 second delay after switching off.

one centered; one centered back

CAB SPOTLIGHTS

Two (2) Unity model 335 cab spotlights shall be provided at the upper front cab door posts, one (1) on each side. Each spotlight shall be provided with a switch on the light handle.

CHASSIS HEADLIGHT WIG/WAG

A chassis headlight wig/wag flashing unit shall be provided. The headlight flasher shall shut down when the parking brake is engaged for "Blocking Mode".

The lights shall be controlled at the switch panel in cab.

Aspen Fire Protection District

Type III Engine, SVI #1080

CAB HAZARD WARNING LIGHT

A Truck-Lite red LED flashing light shall be provided and located in the driving compartment and be illuminated automatically whenever the vehicles parking brake is not fully engaged and any of the following conditions exist:

- Any passenger or equipment compartment door is not closed.
- Any ladder or equipment rack is not in the stowed position.
- Stabilizer system is not in its stowed position.
- Powered light tower is not stowed.
- Any other device permanently attached to the apparatus is open, extended, or deployed in a manner that is likely to cause damage to the apparatus if the apparatus is moved.

Compartments and equipment meeting all of the following conditions shall be permitted to be exempt from being wired to the hazard light:

- The volume is less than or equal to 4 ft³ (0.1 m³).
- The compartment has an opening less than or equal to 144 in.² (92,900 mm²).
- The open door does not extend sideways beyond the mirrors or up above the top of the fire apparatus.
- All equipment in the compartment is restrained so that nothing can fall out if the door is open while the apparatus is moving.
- Manually raised pole lights with an extension of less than 5 ft (1.5 m).

The hazard light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

An audible alarm shall be provided for the door ajar light.

BACK-UP ALARM

The body manufacturer shall furnish and install an automatic sound sensing electronic back-up alarm. The back-up alarm shall actuate automatically when the transmission gear selector is placed in reverse. The alarm automatically adjusts its sound output, maintaining a minimum of ten dB(A) above noise level, up to maximum rated output of 112 dB(A).

REAR VIEW CAMERA

There shall be one (1) Pioneer model ND-BC8 or equal rear observation camera provided and installed on completed unit. Camera will be wired into specified Pioneer dash mounted Multimedia display.

TAIL LIGHTS

Rear body tail lights shall be vertically mounted and located per Federal Motor Vehicle Safety Standards, FMVSS and Canadian Motor Vehicle Safety Standards CMVSS. The following lights shall be provided;

- Two (2) Whelen C6T amber LED sequential arrow turn signal lights, amber lens
- Two (2) Whelen C6BTT red LED brake and tail lights, red lens
- Two (2) Whelen C6LCC white LED back-up lights, clear lens

Each of the lights above shall be mounted in a C6FC, chrome finish bezels.

Aspen Fire Protection District

Type III Engine, SVI #1080

MIDSHIP MARKER/TURN SIGNAL

Two (2) Whelen model T0A00MAR 2" round amber LED midship body clearance marker/turn signal lights shall be provided and installed, one (1) light on each side of the body, in forward wheel well of rear axle. Midship marker/turn lights shall be wired to the headlight circuit of the chassis.

MARKER LIGHTS

The body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) and Canadian Motor Vehicle Safety Standards (CMVSS) regulations. All body clearance lights shall be Truck-Lite Model 18 LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

CAB STEP LIGHTS / GROUND LIGHTS

There shall be four (4) OnScene 8" Access LED light(s) installed on the vehicle capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting designed to provide illumination on areas under the driver and crew riding area exits shall be switchable but activated automatically when the exit doors are opened.

LICENSE PLATE LIGHT

One (1) Arrow #437 chrome plated LED license plate light shall be installed on the rear of the body. License plate light shall be wired to the headlight circuit of chassis. A fastener system shall be provided for license plate installation.

ELECTRONIC SIREN

One (1) Whelen model 295SLSA1 electronic siren control with selectable 100 or 200 watt output, hands-free operation, user selectable siren tones, park kill, and standard hard wired microphone shall be provided and installed in cab within easy reach of Driver. Siren power shall be wired through the master warning light switch.

SIREN SPEAKER

One (1) Whelen model SA314A 100 watt aluminum, 6.4" x 6.1" x 3.1" deep siren speaker shall be provided and located behind grill or front bumper with natural aluminum finish. The solid state siren speaker shall be vibration resistant. The SA314A shall comply with California Title XIII, Class A, and SAE J1849 requirements and with OSHA 1910.95 Guidelines regarding "Permissible Noise Exposure". All mounting hardware shall be stainless steel and covered by a two year factory warranty.

The siren speaker shall be located on the streetside of front bumper.

Aspen Fire Protection District

Type III Engine, SVI #1080

FRONT LED FLOODLIGHT

One (1) Rigid Industries E-Series model 130312, 30" combination spot/flood LED light(s) with white housing color and cradle mount brackets shall be provided on front of vehicle. The E-Series 30" LED light(s) shall have 13,800 lumen output each.

Each light shall be wired directly to the 12 VDC electrical system with stranded copper wire. The floodlights shall be protected with circuit breakers rated at the proper amperage and wire size.

Mount in the Brow location

The lights shall be controlled at the switch panel in cab.

SIDE LED SCENE LIGHTS

There shall be four (4) Whelen 900 Series Super-LED® model 9SC0ENZR, 9" x 7" surface mounted scene lights provided on the upper body. Light quantity shall be divided equally per side. The 900 configuration shall consist of 24 clear Super-LEDs and a clear gradien optic polycarbonate lens with chrome flange. The 900 series light shall have 6,500 useable lumens each. The scene light is covered by a five year factory warranty.

Two (2) switches shall be provided, one (1) for the streetside scene lights, and one (1) for the curbside scene lights.

The lights shall be controlled at the switch panel in cab.

REAR LED SCENE LIGHTS

Two (2) Whelen 900 Series Super-LED® model 9SC0ENZR, 9" x 7" surface mounted scene lights shall be provided on the upper rear body to light the work area immediately behind the vehicle. The 900 configuration shall consist of 24 clear Super-LEDs and a clear gradien optic polycarbonate lens with chrome flange. The 900 series light shall have 6,500 useable lumens each. The scene light is covered by a five year factory warranty.

The above scene lights shall light to a level of at least 3 fc (30 lx), measured at 25 equally spaced points on a 2.5 ft (750 mm) grid with in a 10 ft x 10 ft (3 m x 3m) square to the rear of vehicle.

The lights shall be controlled at the switch panel in cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

TRAFFIC DIRECTIONAL LIGHT

There shall be one (1) Whelen model TAL65 36.01" long x 2.84" high x 2.24" deep, amber LED traffic directional warning device with 30' control cable shall be located on upper rear body. The control head shall be located in the cab within easy reach of Driver.

The Whelen model TACTLD5 control head will be included with this installation. The auxiliary warning mode will be activated with the control head only.

The traffic directional light shall be surface mounted on upper rear body.

Aspen Fire Protection District

Type III Engine, SVI #1080

WARNING LIGHT PACKAGE

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four (4) warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four (4) zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two (2) separate signaling modes during emergency operations. One (1) mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One (1) mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two (2) signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

Steadily burning, non flashing optical sources shall be permitted to be used.

UPPER LEVEL OPTICAL WARNING DEVICES

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

Aspen Fire Protection District

Type III Engine, SVI #1080

ZONE A - FRONT WARNING LIGHTS

There shall be one (1) Whelen Freedom F4N0VLED LED 60" lightbar permanently mounted to the cab roof.

The lightbar configuration (streetside to curbside) shall be:

| <u>SECTION</u> | <u>INTERNAL COMPONENTS</u> | <u>LENS COLOR</u> |
|----------------|------------------------------|-------------------|
| 1 | Red Rear Corner LED | Clear |
| 2 | Red Front Corner LED | Clear |
| 3 | Blank | Clear |
| 4 | White Long Super-LED | Clear |
| 5 | Blank | Clear |
| 6 | Red Long Super-LED | Clear |
| 7 | Blank (Opticom if specified) | Clear |
| 8 | Blank (Opticom if specified) | Clear |
| 9 | Red Long Super-LED | Clear |
| 10 | Blank | Clear |
| 11 | White Long Super-LED | Clear |
| 12 | Blank | Clear |
| 13 | Red Front Corner LED | Clear |
| 14 | Red Rear Corner LED | Clear |

All clear lights shall shut down when the parking brake is set to comply with "Blocking" mode requirements as outlined in NFPA 1901.

The lightbar(s) shall be separately controlled at switch panel in the cab.

ZONES B AND D - SIDE WARNING LIGHTS

UPPER REAR CORNER WARNING LIGHTS

There shall be two (2) C6 SurfaceMax series (6" x 4") red Linear Super-LED with full-fill optic lights provided, one (1) each side. The self-contained flashing light shall have 75 Scan-Lock™ flash patterns including steady burn with hi/low power and covered by a five year factory warranty. Each light shall have a clear lens and chrome flange.

All blue on Passenger side red on Driver.
refer to drawing on one blue and one red light.

The lights shall be controlled at the switch panel in cab.

Aspen Fire Protection District

Type III Engine, SVI #1080

UPPER FORWARD CORNER WARNING LIGHTS

There shall be two (2) Whelen C6 SurfaceMax series (6" x 4") red Linear Super-LED with full-fill optic lights provided, one (1) each side. The self-contained flashing light shall have 75 Scan-Lock™ flash patterns including steady burn with hi/low power and covered by a five year factory warranty. Each light shall have a clear lens and chrome flange.

Refer to drawing for one Blue and one Red

The lights shall be controlled at the switch panel in cab.

ZONE C - REAR WARNING LIGHTS

There shall be two (2) Whelen C6 SurfaceMax series (6" x 4") red Linear Super-LED with full-fill optic lights provided, one (1) each side. The self-contained flashing light shall have 75 Scan-Lock™ flash patterns including steady burn with hi/low power and covered by a five year factory warranty. Each light shall have a clear lens and chrome flange.

Refer to drawing to one Blue and one Red

The lights shall be controlled at the switch panel in cab.

LOWER LEVEL OPTICAL WARNING DEVICES

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1600 mm) above level ground.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

ZONE A - FRONT WARNING LIGHTS

There shall be two (2) Whelen C6 SurfaceMax series (6" x 4") red Linear Super-LED with full-fill optic lights provided, one (1) each side. The self-contained flashing light shall have 75 Scan-Lock™ flash patterns including steady burn with hi/low power and covered by a five year factory warranty. Each light shall have a clear lens and chrome flange.

curbside blue/clear

refer to drawing for one Blue and one Red

The lights shall be controlled at the switch panel in cab.

Aspen Fire Protection District

Type III Engine, SVI #1080

ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

There shall be two (2) Whelen ION Wide Series (6" x 1 3/4") red Super-LED surface mount lights (WIONSMCR) provided, one (1) on each side. The wide angle warning light shall incorporate six red Super-LEDs. The self-contained flashing light shall have 75 Scan-Lock™ flash patterns including steady burn with hi/low power and covered by a five year factory warranty. Each light shall have a clear lens and chrome flange.

Refer to drawing one Blue and one Red

The lights shall be controlled at the switch panel in cab.

ZONES B AND D - BODY LIGHT (BODY WHEELWELL AREA)

There shall be two (2) Whelen ION Wide Series (6" x 1 3/4") red Super-LED surface mount lights (WIONSMCR) provided, one (1) on each side. The wide angle warning light shall incorporate six red Super-LEDs. The self-contained flashing light shall have 75 Scan-Lock™ flash patterns including steady burn with hi/low power and covered by a five year factory warranty. Each light shall have a clear lens and chrome flange.

refer to drawing one Blue and one Red

The lights shall be controlled at the switch panel in cab.

ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Whelen ION Wide Series (6" x 1 3/4") red Super-LED surface mount lights (WIONSMCR) provided, one (1) on each side. The wide angle warning light shall incorporate six red Super-LEDs. The self-contained flashing light shall have 75 Scan-Lock™ flash patterns including steady burn with hi/low power and covered by a five year factory warranty. Each light shall have a clear lens and chrome flange.

refer to drawing one Blue and one Red

The lights shall be controlled at the switch panel in cab.

ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Whelen C6 SurfaceMax series (6" x 4") red Linear Super-LED with full-fill optic lights provided, one (1) each side. The self-contained flashing light shall have 75 Scan-Lock™ flash patterns including steady burn with hi/low power and covered by a five year factory warranty. Each light shall have a clear lens and chrome flange.

refer to drawing one Blue and one Red

The lights shall be controlled at the switch panel in cab.

Aspen Fire Protection District

Type III Engine, SVI #1080

WILDLAND SIDE MOUNT PUMP MODULE

The 74" (measured laterally across vehicle width) x 36" wide side mount pump enclosure shall be removable and supported from the chassis frame rails with spring type body mounts. This enclosure shall allow independent flexing of the pump enclosure from the body and allow for quick removal. The support structure shall be constructed of extruded aluminum tubing and angle.

All pump suction and discharge controls are to be mounted on the driver side pump operator's panel so as to permit operation of the pump from a central location. The fire pump, valves and controls shall be accessible for service and maintenance as required by applicable sections of NFPA standards.

The "master" gauges shall be suitably enclosed and mounted on a full pump compartment width "hinged" gauge panel constructed of the same material as the pump operators control panel, allowing access to the backside of all gauges and gauge lines. The individual gauges shall be mounted inline with the control handle or adjacent to the control handle. Panel is to include a stainless steel piano hinge, flush mounted chrome plated trigger latch, and stainless steel cable end stops. Electrical wiring and all gauge lines shall be properly tie wrapped to prevent kinking or cutting of the lines when the panel is opened.

The following controls and equipment shall be provided on the pump panel or within the pump enclosure:

- 1) Electric primer.
- 2) Pump and plumbing area service lights.
- 3) Pressure control device and throttle control.
- 4) Fire pump and engine instruments.
- 5) Pump intakes and discharge controls.
- 6) Master intake and discharge gauges.
- 7) Tank fill control.
- 8) Tank suction control.
- 9) Water tank level gauge.
- 10) Pump panel lights.

PUMP PANEL - SIDE MOUNT

The pump operator's panel, along with the lower streetside and curbside pump panels shall be constructed of smooth plate aluminum with powder coated black paint finish, fastened to the pump enclosure with 1/4" stainless steel bolts.

The instrument area shall have a stainless steel continuous hinge that shall swing towards the front of the module for easy access to gauges.

STREETSIDE PUMP PANEL - BOLTED

The streetside pump panel shall be fastened to the pump enclosure with 1/4" stainless steel bolts and nutserts.

LOWER CURBSIDE PUMP PANEL - BOLTED

The curbside pump panel shall be fastened to the pump enclosure with 1/4" stainless steel bolts and nutserts.

Aspen Fire Protection District

Type III Engine, SVI #1080

PUMP MODULE EQUIPMENT STORAGE COMPARTMENT

There shall be one (1) equipment compartment located on the upper curbside of the pump module. It shall have dimensions of 22" wide x 26" high. The clear door compartment dimensions shall be 20.5" wide x 23" high x 12" deep with the door closed. An OnScene LED light shall illuminate the interior of the compartment when the door is open.

The equipment compartment shall be provided with a flush style hinged door. The doors shall be provided with a high quality, continuous double seal type weather stripping to prevent moisture and dust from entering the exterior compartment. The door shall be double pan design with the outer door material being 1/8" aluminum door with a 1/8" aluminum removable inner liner that shall have a natural finish to provide reflective qualities during night operations. The vertically hinged door shall have a gas shock and polished stainless steel 1/4" piano hinge.

The door latch shall be an Eberhard locking slam latch, with a chrome "D" ring with a 5-degree bend for easier grasping of each door handle with gloved hands. The door shall be provided with a keyed lock.

The exterior of the door shall be painted to match the lower job color. The interior shall be painted to match the compartment interior paint specified.

There shall be two (2) large removable panels provided on the inside of the compartment. These panels shall provide an opening for service access to the right side of the interior of the pump module and to the bottom side of the diesel pump.

WHEEL CHOCK COMPARTMENT

Behind rear wheels.

PUMP COMPARTMENT TOP OVERLAY

The top of the pump compartment shall be overlaid with materials of a non slip 1/8" NFPA compliant aluminum treadplate.

DUNNAGE AREA

A single wall 3/16" aluminum tread plate dunnage area shall be provided above the pump house compartment for equipment mounting and storage space. The dunnage area shall be as wide as possible from side to side, and as deep as allowed with the available space.

CURBSIDE PUMP MODULR COMPARTMENT

A compartment shall be provided on curbside pump module above pump panel. Compartment shall be made as large as possible.

This compartment shall have a R•O•M series IV roll-up door.

- The roll-up door shall have an unpainted satin aluminum finish on the door slats and the door trim components.
- The door shall be equipped with a CPI harsh environment mechanical type door ajar switch located inside compartment interior lower door track.
- There shall be NO keyed lock on this roll-up compartment door.

Aspen Fire Protection District

Type III Engine, SVI #1080

- One (1) aluminum drip pan/door guard shall be provided below door roll area. Drip pan/door guard shall have thumb nuts making it easily removable without tools with a maintenance-free, un-painted finish. A plastic drain line shall be provided on each end of the drip pan to lower door threshold.

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac welded to compartment walls for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- Two (2) OnScene Access LED, full height compartment lights, vertically mounted.

STREETSIDE RUNNING BOARD - SIDE MOUNT PANEL

The streetside pump panel shall be equipped with a side running board. The running board shall extend along the width of the pump module.

The running board stepping surface shall be constructed of aluminum NFPA compliant tread plate, bolted in place with stainless steel fasteners.

- One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.

CURBSIDE RUNNING BOARD - SIDE MOUNT PANEL

The curbside pump panel shall be equipped with a side running board. The running board shall extend along the width of the pump module.

The running board stepping surface shall be constructed of aluminum NFPA compliant tread plate, bolted in place with stainless steel fasteners.

- One (1) OnScene 8" Access LED ground light(s) shall be provided below the body.

PUMP MODULE FINISH

The pump module framework shall be painted body color choice.

PUMP MODULE HEATER

The pump module shall be provided with one (1) Red Dot 35,000 BTU hot water type heater(s). The heater(s) shall be connected to the chassis engine cooling system and have three-speed, 12 volt blower. The cooling system lines shall be insulated and be provided with 1/4 turn shut-off valves to isolate system, if required.

The pump operator's panel shall have an Innovative Controls switch panel for heat control switch with indicator light. Switch shall be constantly illuminated and labeled.

Aspen Fire Protection District

Type III Engine, SVI #1080

CROSS LAY

The specified pump module shall have three (3) cross lay(s). The cross lay hose bed(s) shall be located in the upper portion of the pump module.

The cross lay area shall be located at the front of side control pump module and at the rear of top control module. The cross lay area shall span the entire width of the pump module.

CROSS LAY TRIM

Brushed stainless steel trim shall be installed at the openings on each side of the cross lay hose bed area. The trim shall reduce the chaffing of the hose jacket on the edges of the bay area.

If divider(s) are required between the hose bed areas they shall be fabricated from 3/16" smooth aluminum and mounted in a channel on each end for adjustability.

Removable slotted aluminum flooring shall be provided for the hose bed area.

Each end of hose bed shall have a 2" black nylon covered with black 14 oz. vinyl style webbing covers. The covers will be mechanically fastened at the sides of the hose bed and secured using yellow pulls with reflective bungess and shoulder bolts.

Safety sign FAMA22, which warns of the need to secure hose, shall be visible to personnel at each side of hose storage area.

CROSS LAY BED COVER

A 1/8" aluminum tread plate hinged cover shall be provided over the lay beds complete with full length stainless steel piano hinge. Stops shall be provided to protect cab or other adjacent body components. The hinge shall be located on the forward section of the cover, closest to the chassis cab.

HALE MBP SINGLE STAGE FIRE PUMP

PUMP ASSEMBLY

1. The pump shall be of a size and design to mount on the chassis rails of commercial and or a custom truck chassis, and have the capacity of up to 1,000 GPM (4,000 LPM), NFPA 1901 rated performance.
2. The entire pump shall be assembled and tested at the pump manufacturer's factory.
3. The pump shall be driven by a the truck transmission mounted PTO. The engine shall provide sufficient horsepower and RPM to enable pump to meet and exceed its rated performance within the torque rating of the PTO, truck transmission and drive line components.
4. The entire pump shall be hydrostatically tested to a pressure of 600 PSI. The pump shall be fully tested at the pump manufacturer's factory to the performance spots as outlined by the latest NFPA Pamphlet No. 1901. Pump shall be free from objectionable pulsation and vibration.
5. The pump body and related parts shall be of fine grain alloy cast iron, with a minimum tensile strength of 30,000 PSI (2069 bar). All metal moving parts in contact with water shall be of high quality bronze or stainless steel. Pump utilizing castings made of lower tensile strength cast iron not acceptable.

Aspen Fire Protection District

Type III Engine, SVI #1080

6. Pump body shall be vertically split, on a single plane for easy removal of entire impeller assembly including clearance rings.
7. Pump shaft to be rigidly supported by two bearings for minimum deflection. The bearings shall be heavy-duty, deep groove ball bearings in the gearbox and they shall be splash lubricated.
8. The pump impeller shall be hard, fine grain bronze of the mixed flow design; accurately machines, hand-ground and individually balanced. The vanes of the impeller intake eye shall be hand ground and polished to a sharp edge, and be of sufficient size and design to provide ample reserve capacity utilizing minimum horsepower.
9. Impeller clearance rings shall be bronze, easily renewable without replacing impeller or pump volute body.
10. The pump shaft shall be heat-treated, electric furnace, corrosion resistant stainless steel. Pump shaft must be sealed with double-lip oil seal to keep road dirt and water out of gearbox.

ANODES

To reduce the effect of galvanic action, the fire pump shall be equipped with two (2) easily replaceable sacrificial catalytic action 3/4" magnesium anodes. One anode shall be installed on the inlet (suction) side of the system, and one anode shall be installed on the pressure (outlet) side of the main fire pump.

CERTIFICATION

The pump will perform and meet the following tests:

- 100% of rated capacity @ 150 PSI net pump pressure.
- 100% of rated capacity @ 165 PSI net pumps pressure.
- 70% of rated capacity @ 200 PSI net pump pressure.
- 50% of rated capacity @ 250 PSI net pump pressure

Pump shall be tested at manufacturer under full NFPA suction conditions.

Aspen Fire Protection District

Type III Engine, SVI #1080

GEARBOX

1. Pump gearbox shall be of sufficient size to withstand up to 16,000 lbs. ft. of torque of the engine. The drive unit shall be designed of ample capacity for lubrication reserve and to maintain the proper operating temperature..
2. The gearbox drive shafts shall be of heat-treated chrome nickel steel and at least 2-3/4 inches in diameter, on both the input and output drive shafts. They shall withstand the full torque of the engine.
3. All gears, both drive and pump, shall be of highest quality electric furnace chrome nickel steel. Bores shall be ground to size and teeth integrated and hardened, to give an extremely accurate gear for long life, smooth, quiet running, and higher load carrying capability. An accurately cut spur design shall be provided to eliminate all possible end thrust. (No exceptions.)
4. The pump ratio shall be selected by the apparatus manufacturer to give maximum performance with the engine and transmission selected.
5. If the gearbox is equipped with a power shift, the shifting mechanism shall be a heat treated, hard anodized aluminum power cylinder, with stainless steel shaft. An in-cab control for rapid shift shall be provided that locks in road or pump.
6. For automatic transmissions, three green warning lights shall be provided to indicate to the operator(s) when the pump has completed the shift from Road to Pump position. Two green lights to be located in the truck driving compartment and one green light on pump operators panel adjacent to the throttle control. For manual transmissions, one green warning light will be provided for the driving compartment. All lights to have appropriate identification/instruction plates.

PAINT FINISH

The pump manufacturer shall provide a black finish paint.

PUMP DRIVE SYSTEM - PUMP AND ROLL

The water system pump shall be driven by a Chelsea "Hot-Shift" transmission PTO and mounted directly to the transmission of the chassis. The drive line shall be hollow tube type, with heavy duty universals and splined shaft to allow movement of the chassis components and pump.

The engagement of the PTO shall be in the chassis cab with a rocker switch and red pilot light to note engagement of the PTO. The power supply to the PTO engagement control shall be wired to allow pump and roll operations.

The vehicle is designed to be used in both stationary pumping mode and "pump-and roll" pumping mode, an "OK to Pump-and-Roll" indicator shall be provided in the driving compartment to indicate that all of the following conditions have been met to safely operate the pump in pump-and-roll mode:

- 1) The pump shift is engaged.
- 2) The parking brake is released.

A "Throttle Ready" indicator shall be provided on the pump operator's panel. The "Throttle Ready" indicator shall indicate when The pump is in "OK to Pump" mode.

The "Throttle Ready" indicator at the pump operator's panel shall be permitted to indicate when the parking brake is engaged and, if the apparatus is equipped with an automatic transmission, when the chassis transmission is in neutral.

Aspen Fire Protection District

Type III Engine, SVI #1080

Model part number shall be Chelsea 280 series.

Double check the model number and ratio with engineering before ordering the PTO on the chassis.

MECHANICAL SEALS

The Hale pump shall be equipped with a mechanical seal in place of pump packing on the suction (inboard) side of the pump. The mechanical seal must be two (2) inches in diameter and shall be spring loaded, maintenance free and self-adjusting. Mechanical seal construction shall be a carbon sealing ring, stainless steel coil spring, Viton rubber cup, and a tungsten carbide seat with Teflon backup seal.

1/2" PUMP COOLER LINE

There shall be a 1/2" line installed from the discharge side of the pump to the water tank. The line shall be used to cool the pump during long periods of pumping when water is not being discharged. The pump cooler shall be controlled with a quarter-turn ball valve on main pump panel, and shall be clearly labeled "Pump Cooler".

PUMP COOLER CHECK VALVE

There shall be a check valve installed in the pump cooler line to prevent tank water from back flowing into the pump when it is not in use.

HALE FIVE YEAR PUMP WARRANTY

The fire pump shall be warranted by Hale for a period of five (5) years from the date of delivery to the Aspen Fire Protection District. Within this warranty period Hale shall cover parts and labor for the first two (2) years and parts only for years three (3) through five (5).

MANUFACTURER FIRE PUMP TEST

The pump shall undergo a manufacturer's test per applicable sections of NFPA 1901 standards, prior to delivery of the completed apparatus.

The test shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming device tests, and the vacuum test.

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 500 psi (3400 kPa) for a minimum for 10 min. The pump shall be fully tested at the pump manufacturer's factory to the performance specifications as outlined by applicable NFPA 1901 standards.

The results of this test shall be furnished with the vehicle on delivery.

Aspen Fire Protection District

Type III Engine, SVI #1080

FIRE PUMP TEST LABEL

A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve

The pump shall comply with the applicable requirements of "Standard for Fire Apparatus 1901, latest edition.

The pump shall be capable of producing fire streams that are free from objectionable pulsation under all normal operating conditions.

SAFETY SIGN

A safety sign FAMA25, which warns of the need for training prior to operating the apparatus, shall be located on the pump operators panel.

ALTITUDE REQUIREMENT

The apparatus shall be designed to meet the specified rating at 8,000 feet altitude.

PUMP DRAIN CONTROL

The pump drain shall be controlled at the pump operator's panel and identified as "Pump Drain". The control shall be a Class1 round 1/4 turn handle control that is easily actuated with a gloved hand.

AIR PRIMING PUMP CONTROL AT PUMP PANEL

The priming pump shall be a Trident Emergency Products compressed air powered, high efficiency, multi-stage venturi based AirPrime System.

The priming pump shall be rigidly attached to the pump transmission and utilizes air supplied from the chassis air system to operate the pump primer. The AirPrime is more efficient and reliable than the conventional electric motor driven primers, and virtually eliminates the impact load on the vehicles electrical system improving the reliability of the vehicle. AirPrime also improves performance in the elapsed time for establishing water supply resulting in improved fire ground operations and safety.

A manual rocker switch with Auto-Prime / Off / Manual-Prime shall be provided on main pump operator's panel.

The primer shall be capable of priming the pump through a 20' section of suction hose with a 10' lift within 30 seconds for pumps less than 1,500 gpm, and 45 seconds for pumps 1,500 gpm and larger.

DISCHARGE RELIEF VALVE

The discharge pressure relief shall be controlled by the electronic engine controlled device as specified.

6" SUCTION INLET - STREETSIDE

One (1) 6" (150 mm) un-gated suction intake shall be installed on the streetside pump panel to supply the fire pump from an external water supply. The threads shall be 6" NH male threads.

The intake shall be provided with a removable screen.

Aspen Fire Protection District

Type III Engine, SVI #1080

HALE 6" MIV ELECTRIC VALVE

There shall be one (1) Hale 6" Master Intake Valve (MIV) provided on specified master intake of the pump.

The inlet valve shall be a full flow butterfly type valve designed to mount on the fire pump between the suction tube extension and suction tube behind the pump compartment panel. The valve shall not interfere with other suction or discharge openings on the fire pump or with pump operating controls when properly mounted.

When the valve is installed in the fire pump suction the fire pump shall be capable of achieving an NFPA / UL test rating of 1,500 GPM through a single 6 inch NST suction hose. When two valves are installed on the fire pump, the pump shall be capable of achieving an NFPA/UL test rating of 2,000 GPM using dual 6" NST suction hoses.

The valve body and related components that are in contact with water shall be manufactured of fine grained corrosion resistant bronze. The butterfly disc shall be manufactured from 80,000 PSI minimum yield strength heat treated cast steel then coated with a durable nitrile rubber to provide a positive seal when the valve is closed.

Testing and rating of the valve shall be accomplished at the valve manufacturers factory. The valve, less relief valve, shall be hydrostatically tested to 600 PSIG. The valve shall then be vacuum tested to 26 inches Hg. A pressure relief valve shall be provided that is factory set to 125 PSI and field adjustable from 75 to 250 PSI . The pressure relief valve shall provide overpressure protection for the suction hose even when the intake valve is closed. An integral relief valve mounting pad shall be provided on the valve body.

This mounting pad shall provide a Hale type 115 4-3/8" bolt circle flange for normal installation. The mounting pad shall have 2-1/2" female NPT threads to permit remote mounting of the relief valve without special adapters. The outlet of the pressure relief valve shall have 2-1/2 inch NPT threads to allow directing the discharge flow away from the pump operator position.

Each valve shall be provided with panel placards indicating control operation. The placards shall have status lights to indicate whether the valve is open, closed or traversing from one position to another.

The inlet valve shall be operated by a 12 VDC electric motor with remote capabilities that will cycle the valve from OPEN to CLOSED position in no less than 3 seconds. The gear actuators shall be sealed units designed to provide reliable service in the harsh pump compartment environment. The ratio of the gear actuator shall be such that the handwheel will close the valve in no more than 10 complete turns.

The 12 VDC motor on the electric operated valve shall be provided with an automatic resetting, thermally compensated, over-current protection circuit breaker to protect the 12 VDC motor and apparatus electrical system. The electrical wiring for the valve shall be minimum 14 AWG, type SXL or GXL (SAE J1128) and shall be protected using 257 F minimum flame retardant, moisture resistant loom or braid. All electrical connections shall use sealed Packard Weather Pack connectors to provide extra protection from the harsh pump compartment environment to ensure long life and reliable operation.

The valve body shall have a 3/4" female NPT threaded port on the top to allow installation of an NFPA compliant large diameter hose air bleeder valve. The air bleeder valve shall be mounted on the operator panel and be controllable by the pump operator. Air bleeder valve connections shall have a restriction no larger than 3/4 inch to prevent water hammer when filling hose. The valve body shall have a 1/4" female NPT threaded port on the bottom to permit connection of an individual water drain valve.

A suction tube extension 7-1/4" wide shall be used to allow for the additional length of the inlet valve. The shorter suction tube extension, along with a 4, 6 or 9" suction tube, will keep the suction tube threads within the apparatus running boards while maintaining clearance for adapters.

Aspen Fire Protection District

Type III Engine, SVI #1080

A panel mounted manual override shall be provided to permit operation of the electric remote control valve in the event of abnormal operating conditions. The manual override shall be designed to permit operation of the valve without the use of special tools or disassembly of the pump compartment panel or valve.

The valve shall be equipped with o-ring seals for the mounting flanges. The o-ring seal groove shall be sized for proper squeeze of the o-ring for pressures in excess of 600 PSIG.

- The intake shall be provided with a 6" NHF swivel rocker lug x 5" Storz 30 degree down sweep elbow with hardcoat finish.
- The intake shall be provided with a 5" Storz blind cap with hardcoat finish and retaining chain.

6" SUCTION INLET - CURBSIDE

One (1) 6" (150 mm) un-gated suction intake shall be installed on the curbside pump panel to supply the fire pump from an external water supply. The threads shall be 6" NH male threads.

The intake shall be provided with a removable screen.

HALE 6" MIV ELECTRIC VALVE

There shall be one (1) Hale 6" Master Intake Valve (MIV) provided on specified master intake of the pump.

The inlet valve shall be a full flow butterfly type valve designed to mount on the fire pump between the suction tube extension and suction tube behind the pump compartment panel. The valve shall not interfere with other suction or discharge openings on the fire pump or with pump operating controls when properly mounted.

When the valve is installed in the fire pump suction the fire pump shall be capable of achieving an NFPA / UL test rating of 1,500 GPM through a single 6 inch NST suction hose. When two valves are installed on the fire pump, the pump shall be capable of achieving an NFPA/UL test rating of 2,000 GPM using dual 6" NST suction hoses.

The valve body and related components that are in contact with water shall be manufactured of fine grained corrosion resistant bronze. The butterfly disc shall be manufactured from 80,000 PSI minimum yield strength heat treated cast steel then coated with a durable nitrile rubber to provide a positive seal when the valve is closed.

Testing and rating of the valve shall be accomplished at the valve manufacturers factory. The valve, less relief valve, shall be hydrostatically tested to 600 PSIG. The valve shall then be vacuum tested to 26 inches Hg. A pressure relief valve shall be provided that is factory set to 125 PSI and field adjustable from 75 to 250 PSI . The pressure relief valve shall provide overpressure protection for the suction hose even when the intake valve is closed. An integral relief valve mounting pad shall be provided on the valve body.

This mounting pad shall provide a Hale type 115 4-3/8" bolt circle flange for normal installation. The mounting pad shall have 2-1/2" female NPT threads to permit remote mounting of the relief valve without special adapters. The outlet of the pressure relief valve shall have 2-1/2 inch NPT threads to allow directing the discharge flow away from the pump operator position.

Each valve shall be provided with panel placards indicating control operation. The placards shall have status lights to indicate whether the valve is open, closed or traversing from one position to another.

Aspen Fire Protection District

Type III Engine, SVI #1080

The inlet valve shall be operated by a 12 VDC electric motor with remote capabilities that will cycle the valve from OPEN to CLOSED position in no less than 3 seconds. The gear actuators shall be sealed units designed to provide reliable service in the harsh pump compartment environment. The ratio of the gear actuator shall be such that the handwheel will close the valve in no more than 10 complete turns.

The 12 VDC motor on the electric operated valve shall be provided with an automatic resetting, thermally compensated, over-current protection circuit breaker to protect the 12 VDC motor and apparatus electrical system. The electrical wiring for the valve shall be minimum 14 AWG, type SXL or GXL (SAE J1128) and shall be protected using 257 F minimum flame retardant, moisture resistant loom or braid. All electrical connections shall use sealed Packard Weather Pack connectors to provide extra protection from the harsh pump compartment environment to ensure long life and reliable operation.

The valve body shall have a $\frac{3}{4}$ " female NPT threaded port on the top to allow installation of an NFPA compliant large diameter hose air bleeder valve. The air bleeder valve shall be mounted on the operator panel and be controllable by the pump operator. Air bleeder valve connections shall have a restriction no larger than $\frac{3}{4}$ inch to prevent water hammer when filling hose. The valve body shall have a $\frac{1}{4}$ " female NPT threaded port on the bottom to permit connection of an individual water drain valve.

A suction tube extension 7- $\frac{1}{4}$ " wide shall be used to allow for the additional length of the inlet valve. The shorter suction tube extension, along with a 4, 6 or 9" suction tube, will keep the suction tube threads within the apparatus running boards while maintaining clearance for adapters.

A panel mounted manual override shall be provided to permit operation of the electric remote control valve in the event of abnormal operating conditions. The manual override shall be designed to permit operation of the valve without the use of special tools or disassembly of the pump compartment panel or valve.

The valve shall be equipped with o-ring seals for the mounting flanges. The o-ring seal groove shall be sized for proper squeeze of the o-ring for pressures in excess of 600 PSIG.

- The intake shall be provided with a 6" NHF swivel rocker lug x 5" Storz 30 degree down sweep elbow with hardcoat finish.
- The intake shall be provided with a 5" Storz blind cap with hardcoat finish and retaining chain.

HEAT EXCHANGER

A heat exchanger shall be provided on the pump driving engine cooling system that uses water from the discharge side of the pump to cool the engine coolant through the use of a closed heat exchanger. The water from the pump and the engine coolant shall not be intermixed. This cooling system shall be controlled by a 1/4 turn valve on the pump operator's panel.

INTAKE RELIEF VALVE

An Akron Brass model 53 intake pressure relief valve shall be provided. The intake pressure relief valve shall have a flange to allow mounting to a 4-bolt pump intake flange. The unit shall be adjustable from 50 to 250 psi and be factory set at 125 psi. Provisions for adjusting or servicing the valve {will/shall} be provided.

The relief outlet shall be directed below the pump with the discharge terminating in a 2-1/2" NSTM connection. The discharge shall be away from the pump operator and labeled "DO NOT CAP".

AUXILIARY PUMP

No auxiliary pump shall be provided with completed unit.

Aspen Fire Protection District

Type III Engine, SVI #1080

FOAM SYSTEM

The apparatus shall be equipped with a FoamPro 2001 electronic, fully automatic, variable speed, direct injection, discharge side foam proportioning system. The system shall be capable of handling Class A foam concentrates and most Class B foam concentrates. The foam proportioning operation shall be based on direct measurement of water flows, and remain consistent within the specified flows and pressures. System must be capable of delivering accuracy to within 5% of calibrated settings over the advertised operation range when installed according to factory standards. The system shall be equipped with a digital electronic control display suitable for installation on the pump panel. Incorporated within the control display shall be a microprocessor that receives input from the system flowmeter(s), while also monitoring foam concentrate pump output, comparing values to ensure that the operator preset proportional amount of foam concentrate is injected into the discharge side of the fire pump.

Paddlewheel-type flowmeter(s) shall be installed in the discharges specified to be "foam capable." When the use of more than one flowmeter is required, an interface electronics module will be provided to totalize these flows and send the flow total to the microprocessor in the computer control display.

The digital computer control display shall enable the pump operator to perform the following control and operation functions for the foam proportioning system:

- Provide push-button control of foam proportioning rates from 0.1% to 9.9%, in 0.1% increments
- Show current flow-per-minute of water
- Show total volume of water discharged during and after foam operations are completed
- Show total amount of foam concentrate consumed
- Simulate flow rates for manual operation
- Perform setup and diagnostic functions for the computer control microprocessor
- Flash a "low concentrate" warning when the foam concentrate tank(s) runs low
- Flash a "no concentrate" warning and shut the foam concentrate pump off, preventing damage to the pump, should the foam tank(s) empty

A 12-volt electric motor drive positive displacement foam concentrate pump, rated up to 2.5 gpm (9.5 L/min) @ 150 psi with operating pressures up to 400 psi (27.6 BAR), shall be installed in a suitable, accessible location. The system will draw a maximum of 40 amps @ 12 VDC. A pump motor electronic driver (mounted to the base of the pump) shall receive signals from the computer control display and power the 1/2 hp (0.40 kW) electric motor directly coupled to the concentrate pump in a variable speed duty cycle to ensure that the correct proportion of concentrate preset by the pump operator is injected into the water stream.

Full flow check valve shall be provided to prevent foam contamination of fire pump and water tank or water contamination of foam tank.

Components of the complete proportioning system shall include:

- Operator control and display
- Paddlewheel flowmeter(s)
- Pump and electric motor/motor driver
- Wiring harnesses
- Low level tank switch
- Foam injection check valve
- Main waterway check valve

Aspen Fire Protection District

Type III Engine, SVI #1080

An installation and operation manual shall be provided for the unit, along with a one-year limited warranty by the manufacturer. The system must be installed and calibrated by a Certified FoamPro Dealer.

The system design shall have passed environmental testing which simulates heavy use on off-road mobile apparatus. Testing shall have been conducted in accordance to SAE standards.

A means shall be provided to prevent water back flow into the foam proportioning system and the foam concentrate storage tank.

FOAM TANK REFILL SYSTEM

The apparatus shall be equipped with an electronic, automatic, concentrate refill system. System shall operate independently of the foam proportioner allowing simultaneous use. Refill operation shall not require apparatus or fire pump to be running. The system shall be capable of handling Class A or Class B foam concentrates, emulsifiers, gels and decontamination concentrates. The apparatus shall be plumbed from the externally accessed intake/flush ports to the concentrate cell following manufacturer's recommendations. External fill and flush connections to be quick-connect, cam-lock type. Internal piping to incorporate check valves to prevent back flow. Concentrate tank inlet shall be positioned to minimize agitation per manufacturer's recommendations. The refill operation shall be based on direct measurement of concentrate level in tank. System must be capable of automatically stopping when cell is full and include a manual override feature. The system shall be equipped with an electronic control suitable for installation on the pump panel. Incorporated within the control shall be a microprocessor that receives input from the system while controlling foam concentrate pump output. An all bronze three-way valve shall be included to allow the operator to flush system after use. Valve control, intake and flush ports shall be located within corresponding panel plate.

The system shall enable the operator to perform the following control/operation functions and status indicators for the refill operation:

- Provide push-button start/stop control of foam refill
- Solid green light advises operator concentrate cell is full
- Flashing green indicates system is running
- Green light off, system off
- Allow override of "full tank" condition
- Provide a means to flush the pump and intake piping

System shall include a 12 volt electric motor driven, positive displacement concentrate pump. Pump shall deliver minimum flow of 10 gpm (37.8 L/min) @ 20 psi with all concentrates currently utilized in fire apparatus. Pump body to be of all bronze construction and other wetted components and piping to be constructed of non-corrosive materials. The system will draw a maximum of 38 amps @ 12 VDC. A pump/motor solenoid (mounted to the base of the pump) shall receive signals from the computer control display and power the 1/2 hp (0.4 kW) electric motor directly coupled to the concentrate pump. The system shall receive readings when the concentrate tank is full and stop operation to prevent overflow.

Components of the complete refill system shall include:

- Operator control and display with Weather-Pac connectors
- Refill/flush quick-connect cam-lock fittings and cap
- Check valves
- Pump/motor assembly and solenoid
- Strainer
- Tank level switch
- Three-way fill/flush valve
- Stainless steel pick-up wand and 6' of reinforced suction hose, 1" diameter to allow maximum flow

Aspen Fire Protection District

Type III Engine, SVI #1080

- Panel placards

An installation and operation manual shall be provided, along with a one-year limited warranty by the manufacturer. The system must be installed and plumbed by a Certified FoamPro Dealer. When two types of concentrates are to be used, a separate refill system must be specified for each.

HOSE THREADS

Hose threads shall be National Standard (NST) on all base threads on the apparatus intakes and discharges, unless otherwise specified. (NST and NH are the same thread)

PLUMBING SPECIFICATIONS

The fire pump plumbing system shall be fabricated with rigid stainless steel and or flexible piping with stainless steel fittings. Victaulic couplings shall be installed to permit flexing of the plumbing system and allow for quick removal of piping or valves for service. Flexible hose couplings shall be threaded stainless steel or Victaulic connections.

The fire pump and plumbing shall be hydrostatically tested in compliance to applicable sections of NFPA standards, with test results submit with the delivery documentation.

STAINLESS STEEL INTAKE MANIFOLD

The suction manifold assembly shall be fabricated with Schedule 10 type 304 stainless steel. All threaded fittings shall be a minimum of Schedule 10 stainless steel. The suction manifold assembly shall have radiused sweep elbows to minimize water turbulence into the suction volute.

The suction manifold shall be welded and pressure tested prior to installation. The stainless steel manifold assembly shall be attached to the pump intake volute with a heavy-duty, flexible Victaulic coupling.

The entire intake piping system, valves, bleeder valves, and intake closures, excluding the tank-to-pump line on the tank side of the valve, shall be capable of withstanding a hydrostatic pressure of 250 psi (1700 kPa).

STAINLESS STEEL DISCHARGE MANIFOLD

The discharge manifold assembly shall be fabricated with Schedule #10 type 304 stainless steel. All threaded fittings shall be a minimum of Schedule 10 stainless steel. The discharge manifold assembly shall have radiused sweep elbows to minimize water turbulence into the discharge header.

The manifold shall be welded and pressure tested prior to installation. The stainless steel manifold assembly shall be attached to the pump intake volute with a heavy-duty, flexible Victaulic coupling.

The entire discharge piping system; valves; drain cocks; and outlet closures, excluding the tank fill line on the tank side of the valve and CAF system piping and components that include valves that permit isolation from discharge pressure, shall be capable of withstanding a hydrodynamic discharge pressure of 500 psi (3400 kPa) or 100 psi (700 kPa) over the maximum discharge pressure capability rating of the pump, whichever is greater.

PLUMBING SYSTEM FINISH

The plumbing system shall not be painted. The piping and valves shall remain natural color.

Aspen Fire Protection District

Type III Engine, SVI #1080

STAINLESS STEEL PLUMBING WARRANTY

The stainless steel plumbing shall be free of defects in material and workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

The contractor shall supply details of their warranty information with their bid submission.

INTAKES

The pump shall have a sufficient number and size of intakes to perform the apparatus pump system certification test. The intakes shall have male National Hose Threads (NST) if the apparatus is to be used in the United States.

If the couplings on the suction hose carried on the apparatus are of a different size from that of the pump intake(s) or have means of hose attachment other than that provided on the intake(s), an adapter(s) shall be provided to allow connection of the suction hose to the pump intake(s).

A sign shall be provided on the pump operator's panel that states the following:

WARNING: Death or serious injury might occur if proper operating procedures are not followed. The pump operator as well as individuals connecting supply or discharge hoses to the apparatus must be familiar with water hydraulics hazards and component limitations.

Each intake shall have a removable or accessible strainer inside the connection. The strainer(s) shall restrict spherical debris that is too large to pass through the pump.

At least one valved intake shall be provided that can be controlled from the pump operator's position. The valve and piping shall be a minimum 2-1/2 in. (65 mm) nominal size.

If the intake is 2-1/2 in. (65 mm) nominal size, the intake shall be equipped with a female swivel coupling with NH threads. Any 3 in. (75 mm) or larger intake valve except the tank-to-pump intake valve shall be a slow-operating valve.

Each valved intake shall be equipped with a bleeder valve having a minimum 3/4 in. (19 mm) pipe thread connection to bleed off air or water. The bleeder valve shall be operational without the operator having to get under the apparatus. If a valved appliance is attached to an intake, it shall be equipped with a 3/4 in. (19 mm) bleeder valve on each intake. Bleeder valves for valved intakes 4 in. (100 mm) and larger not located at the pump operator's panel shall be located where the bleeder valve controls are visible and operationally functional while the operator remains stationary at the valved intake position.

Each valved intake having a connection size larger than 3 in. (75 mm) shall be equipped with an adjustable automatic pressure relief device installed on the supply side of the valve to bleed off pressure from a hose connected to the valved intake.

All intakes shall be provided with caps or closures capable of withstanding a hydrostatic gauge pressure of 500 psi (3400 kPa). Intakes having male threads shall be equipped with caps; intakes having female threads shall be equipped with plugs. Where adapters for special threads or other means for hose attachment are provided on the intakes, closures shall be provided for the adapters in lieu of caps or plugs. Caps or closures for intake connections smaller than 4 in. (100 mm) shall remain secured to the apparatus when removed from the connection.

Aspen Fire Protection District

Type III Engine, SVI #1080

If the suction inlets are to be equipped with a valve, Siamese, or adapter that will remain in place while the apparatus is in motion, that valve, Siamese, or adapter shall not project beyond the apparatus running board. The purchaser shall specify if any valve, Siamese, or adapter is to be permanently installed on an intake and identify the brand and model of such item.

The completed apparatus shall have the following intake(s);

6" SUCTION INLET - REAR

One (1) 6" (150 mm) un-gated suction intake(s) shall be installed on the rear pump panel to supply the fire pump from an external water supply. The threads shall be 6" NH male threads.

The intake(s) shall be provided with a removable screen.

HALE 6" MIV ELECTRIC VALVE

There shall be one (1) Hale 6" Master Intake Valve (MIV) provided on specified master intake of the pump.

The inlet valve shall be a full flow butterfly type valve designed to mount on the fire pump between the suction tube extension and suction tube behind the pump compartment panel. The valve shall not interfere with other suction or discharge openings on the fire pump or with pump operating controls when properly mounted.

When the valve is installed in the fire pump suction the fire pump shall be capable of achieving an NFPA / UL test rating of 1,500 GPM through a single 6 inch NST suction hose. When two valves are installed on the fire pump, the pump shall be capable of achieving an NFPA/UL test rating of 2,000 GPM using dual 6" NST suction hoses.

The valve body and related components that are in contact with water shall be manufactured of fine grained corrosion resistant bronze. The butterfly disc shall be manufactured from 80,000 PSI minimum yield strength heat treated cast steel then coated with a durable nitrile rubber to provide a positive seal when the valve is closed.

Testing and rating of the valve shall be accomplished at the valve manufacturers factory. The valve, less relief valve, shall be hydrostatically tested to 600 PSIG. The valve shall then be vacuum tested to 26 inches Hg. A pressure relief valve shall be provided that is factory set to 125 PSI and field adjustable from 75 to 250 PSI . The pressure relief valve shall provide overpressure protection for the suction hose even when the intake valve is closed. An integral relief valve mounting pad shall be provided on the valve body.

This mounting pad shall provide a Hale type 115 4-3/8" bolt circle flange for normal installation. The mounting pad shall have 2-1/2" female NPT threads to permit remote mounting of the relief valve without special adapters. The outlet of the pressure relief valve shall have 2-1/2 inch NPT threads to allow directing the discharge flow away from the pump operator position.

Each valve shall be provided with panel placards indicating control operation. The placards shall have status lights to indicate whether the valve is open, closed or traversing from one position to another.

The inlet valve shall be operated by a 12 VDC electric motor with remote capabilities that will cycle the valve from OPEN to CLOSED position in no less than 3 seconds. The gear actuators shall be sealed units designed to provide reliable service in the harsh pump compartment environment. The ratio of the gear actuator shall be such that the handwheel will close the valve in no more than 10 complete turns.

Aspen Fire Protection District

Type III Engine, SVI #1080

The 12 VDC motor on the electric operated valve shall be provided with an automatic resetting, thermally compensated, over-current protection circuit breaker to protect the 12 VDC motor and apparatus electrical system. The electrical wiring for the valve shall be minimum 14 AWG, type SXL or GXL (SAE J1128) and shall be protected using 257 F minimum flame retardant, moisture resistant loom or braid. All electrical connections shall use sealed Packard Weather Pack connectors to provide extra protection from the harsh pump compartment environment to ensure long life and reliable operation.

The valve body shall have a ¾" female NPT threaded port on the top to allow installation of an NFPA compliant large diameter hose air bleeder valve. The air bleeder valve shall be mounted on the operator panel and be controllable by the pump operator. Air bleeder valve connections shall have a restriction no larger than ¾ inch to prevent water hammer when filling hose. The valve body shall have a ¼" female NPT threaded port on the bottom to permit connection of an individual water drain valve.

A suction tube extension 7-¼" wide shall be used to allow for the additional length of the inlet valve. The shorter suction tube extension, along with a 4, 6 or 9" suction tube, will keep the suction tube threads within the apparatus running boards while maintaining clearance for adapters.

A panel mounted manual override shall be provided to permit operation of the electric remote control valve in the event of abnormal operating conditions. The manual override shall be designed to permit operation of the valve without the use of special tools or disassembly of the pump compartment panel or valve.

The valve shall be equipped with o-ring seals for the mounting flanges. The o-ring seal groove shall be sized for proper squeeze of the o-ring for pressures in excess of 600 PSIG.

- The intake shall be provided with a 6" NHF swivel rocker lug x 5" Storz 30 degree down sweep elbow with hardcoat finish.
- The intake shall be provided with a 5" Storz blind cap with hardcoat finish and retaining chain.

2-1/2" INTAKE, STREETSIDE

There shall be one (1) 2-1/2" (65 mm) gated intake(s) located on pump panel. Each intake shall include:

- One (1) Akron Brass 8900 series Gen II, manual type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - Valve(s) shall be controlled with a chrome handle directly connected to valve.
- Each intake shall have a 2-1/2" (65 mm) NSTF chrome swivel adapter with strainer provided.
 - The specified adapter shall be provided with a 2-1/2" (65 mm) NSTM chrome plated plug with chain.
- One (1) Innovative Controls model 3003000, ¾" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

Aspen Fire Protection District

Type III Engine, SVI #1080

2-1/2" INTAKE, CURBSIDE

There shall be one (1) 2-1/2" (65 mm) gated intake(s) located on pump panel. Each intake shall include:

- One (1) Akron Brass 8900 series Gen II, manual type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - Valve(s) shall be controlled with a chrome handle directly connected to valve.
- Each intake shall have a 2-1/2" (65 mm) NSTF chrome swivel adapter with strainer provided.
 - The specified adapter shall be provided with a 2-1/2" (65 mm) NSTM chrome plated plug with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

TANK TO PUMP CHECK VALVE

There shall be a check valve between the pump suction and the booster tank valve. The check valve shall eliminate back flow into the water tank when the pump is connected to a pressurized source.

TANK TO PUMP VALVE

A 3" (75 mm) full flow ball valve shall be installed between the fire pump and the water tank. The connection between the tank and the pump shall be capable of the flow recommendations as set forth in the latest edition of NFPA 1901. The valve shall be flanged to bolt directly to the pump and shall incorporate a chromium plated bronze ball. The remaining internal moving parts shall be stainless steel for years of dependable service. A non collapsible flexible hose shall be incorporated into the tank to pump plumbing to allow movement in the line as the chassis flexes to avoid damage during normal road operation.

The tank to pump valve shall be controlled from the pump operator's panel.

- Valve(s) shall be controlled with a push/pull type chromed "T" handle connected to the valve. The control handle shall be located adjacent to the plumbing connection.

Aspen Fire Protection District

Type III Engine, SVI #1080

DISCHARGES

A minimum of two 2-1/2 in. (65 mm) outlets shall be provided on any pump rated at 750 gpm (3000 L/min) or greater, and a minimum of one 2-1/2 in. (65 mm) outlet shall be provided on any pump rated at less than 750 gpm (3000 L/min).

All 1-1/2" (65 mm) or larger discharge outlet connections shall be equipped with male National Hose Threads (NST). Adapters with special threads or other means for hose attachment shall be permitted to be attached to any outlets.

The piping and valves supplying any preconnected 1-1/2 in. (38 mm), 1-3/4 in. (45 mm), or 2 in. (52 mm) hose line, including the piping to the preconnected hose storage areas shall be at least 2 in. (52 mm) in size.

All discharge outlet connections, except connections to which a hose will be preconnected, shall be equipped with caps or closures capable of withstanding a hydrostatic gauge pressure of 100 psi (700 kPa) over the maximum pump close-off pressure or 500 psi (3400 kPa), whichever is greater.

Where adapters are provided on the discharge outlet connections, the closures shall fit on the adapters.

Caps or closures for outlet connections smaller than 4 in. (100 mm) shall remain secured to the apparatus when removed from the connection.

Each discharge outlet shall be equipped with a valve that can be opened and closed smoothly at pump discharge gauge pressures of 250 psi (1700 kPa).

The flow-regulating element of each valve shall not change its position under any condition of operation that involves discharge pressures to the maximum pressure of the pump; the means to prevent a change in position shall be incorporated in the operating mechanism and shall be permitted to be manually or automatically controlled.

Any 3 in. (75 mm) or larger discharge valve shall be a slow-operating valve.

All 1-1/2 in. (38 mm) or larger discharge outlets shall be equipped with a drain or bleeder valve having a minimum 3.4 in. (19 mm) pipe thread connection for draining or bleeding off pressure from a hose connected to the outlet.

Any 2 in. (52 mm) or larger discharge outlet that is located more than 42 in. (1070 mm) off the ground to which hose is to be connected and that is not in a hose storage area shall be supplied with a sweep elbow of at least 30 degrees downward.

The completed apparatus shall have the following discharge(s);

Aspen Fire Protection District

Type III Engine, SVI #1080

FRONT DISCHARGE

2" DISCHARGE

There shall be one (1) 2" (52 mm) gated discharge(s) with control located on pump panel. Each discharge shall include:

- One (1) of the discharge(s) shall flow water and foam.
- One (1) Akron Brass 9600 series Gen II, actuated type 2" (52 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
 - An Akron 9323 Navigator Pro electric valve position controller and wire harness with full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, and VMUX capable integration shall be located on the pump operator's panel.
- There shall be a 2" (52 mm) VFC x 1-1/2" (38 mm) NSTM brass or chrome plated 90 degree swivel elbow provided for each discharge.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- The discharge pressure shall be provided with the valve control system.

REMOTE CONTROL MONITOR

An Elkhart Brass Sidewinder #8494-01 electric monitor shall be provided on completed vehicle painted red. Monitor shall be constructed from durable, hard anodized, lightweight Elk-O-Lite® material with a variable cross-sectional and vaned waterway for flows up to 500 GPM. Monitor shall be constructed with thrust rods and thrust bearings on both horizontal and vertical rotational joints for improved product longevity with female 2" NPT style inlet connection and male 1.5" NHT or outlet connection. Unit shall have two (2) gear motors that allow for simultaneous vertical and horizontal adjustment, one motor shall control up to 334 degree horizontal rotation while the other motor shall control up to 135 degrees vertical travel (-45 degree to +90 degree vertical rotation from horizontal). Horizontal and vertical motors shall have a manual override device for use in the event of power failure. The electric control shall be compatible with both 12VDC and 24VDC power supply.

An Elkhart Brass 5000-24E, 1.5" FNH 150 GPM electric nozzle shall be provided with completed unit

A center console mounted joystick control box shall provide user interface for proportional monitor up/down, left/right rotation, stow, horizontal and vertical automatic oscillation, nozzle control functions, and, valve control functions including required harness to electric valve. Controller shall provide the user feedback for power on, valve open position, valve closed position, and valve preset position and provide programming capability for horizontal center position, horizontal stops, stow position, block-out zones, and motor speeds fast or slow.

Aspen Fire Protection District

Type III Engine, SVI #1080

A Class 1 high pressure flexible hose with stainless steel Victaulic couplers shall connect the discharge valve and monitor. Hose shall be secured to body and chassis frame with bolted "P" style clamps and protected from abrasion, sharp edges, or high heat.

- One (1) of the discharge(s) shall flow water and foam.
- One (1) Elkhart Brass Unibody bronze EB series, actuated type 2" (52 mm) valve(s) with stainless steel ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
- One (1) Innovative Controls model 3003000, ¾" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

CAB MOUNTED WATER TANK INDICATOR

There shall be one (1) Innovative mini 4-light, remote tank level gauge for indicating water level installed in cab. The tank level gauge shall indicate the liquid level or volume on an easy to read red LED display and show increments of 1/4 of a tank.

The Mini remote gauge will receive data from the same source as the Master Display. No additional transducers shall be required.

STREETSIDE DISCHARGE

2-1/2" DISCHARGE

There shall be two (2) 2-1/2" (65 mm) gated discharge(s) with control located on pump panel. Each discharge shall include:

- Two (2) of the discharge(s) shall flow water only.
- Two (2) Akron Brass 8900 series Gen II, actuated type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
 - An Akron 9323 Navigator Pro electric valve position controller and wire harness with full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, and VMUX capable integration shall be located on the pump operator's panel.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated 30 degree downsweep elbow provided.
 - The specified elbow shall be provided with a 2-1/2" (65 mm) NSTF chrome plated cap with chain.
- Two (2) Innovative Controls model 3003000, ¾" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.

Aspen Fire Protection District

Type III Engine, SVI #1080

- Two (2) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with blue (water) LED backlighting activated with pump engagement.
 - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
 - Gauge(s) shall have a range from 0 to 400 PSI.
 - The gauge shall have a die cast zinc, chrome plated bezel with color-coded labels insert and a color-coded gauge trim ring. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

CURBSIDE DISCHARGE

2-1/2" DISCHARGE

There shall be one (1) 2-1/2" (65 mm) gated discharge(s) with control located on pump panel. Each discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8900 series Gen II, actuated type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
- An Akron 9323 Navigator Pro electric valve position controller and wire harness with full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, and VMUX capable integration shall be located on the pump operator's panel.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated 30 degree downsweep elbow provided.
 - The specified elbow shall be provided with a 2-1/2" (65 mm) NSTF chrome plated cap with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with blue (water) LED backlighting activated with pump engagement.
 - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
 - Gauge(s) shall have a range from 0 to 400 PSI.
 - The gauge shall have a die cast zinc, chrome plated bezel with color-coded labels insert and a color-coded gauge trim ring. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

Aspen Fire Protection District

Type III Engine, SVI #1080

4" DISCHARGE

There shall be one (1) 4" (100 mm) gated discharge(s) with control located curbside. Each discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8900 series Gen II slow-operating, actuated type 4" (100 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
 - An Akron 9323 Navigator Pro electric valve position controller and wire harness with full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, and VMUX capable integration shall be located on the pump operator's panel.
- Each discharge shall have a 4" (100 mm) rocker lug NSTF swivel x 5" (125 mm) Storz hardcoat finish 30 degree downsweep elbow provided.
 - The specified elbow shall be provided with a 5" (125 mm) Storz cap hardcoat finish with chain.
- One (1) Innovative Controls model 3003000, ¾" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with blue (water) LED backlighting activated with pump engagement.
 - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
 - Gauge(s) shall have a range from 0 to 400 PSI.
 - The gauge shall have a die cast zinc, chrome plated bezel with color-coded labels insert and a color-coded gauge trim ring. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

Aspen Fire Protection District

Type III Engine, SVI #1080

REAR CURBSIDE DISCHARGE

Each discharge(s) shall have a stainless steel trim ring.

2-1/2" DISCHARGE

There shall be one (1) 2-1/2" (65 mm) gated discharge(s) with control located on pump panel. Each discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8900 series Gen II, actuated type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
 - An Akron 9323 Navigator Pro electric valve position controller and wire harness with full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, and VMUX capable integration shall be located on the pump operator's panel.
- Each discharge shall have a 2-1/2" (65 mm) NSTF x 2-1/2" (65 mm) NSTM chrome plated 30 degree downsweep elbow provided.
 - The specified elbow shall be provided with a 2-1/2" (65 mm) NSTF chrome plated cap with chain.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with blue (water) LED backlighting activated with pump engagement.
 - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
 - Gauge(s) shall have a range from 0 to 400 PSI.
 - The gauge shall have a die cast zinc, chrome plated bezel with color-coded labels insert and a color-coded gauge trim ring. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

Aspen Fire Protection District

Type III Engine, SVI #1080

MISCELLANEOUS DISCHARGE

2" CROSS LAY(S)

There shall be two (2) 2" cross lay(s) located in pump module, or per the itemized compartment list. The crosslay(s) shall be transverse of the pump module or body with access from either side.

Each cross lay shall have a minimum storage capacity of 200' of 1-3/4" double jacket hose and nozzle.

- Two (2) of the discharge(s) shall flow water and foam.
- Two (2) Akron Brass 9600 series Gen II, actuated type 2" (52 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
 - An Akron 9325 Navigator Pro electric valve position controller with wire harness and full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, flow meter (GPM or LPM), pressure meter (PSI or KPa), and VMUX capable integration shall be located on the pump operator's panel. A pressure and flow sensor shall be provided in discharge plumbing.
- There shall be a 2" (52 mm) VFC x 1-1/2" (38 mm) NSTM brass or chrome plated 90 degree swivel elbow provided for each discharge.
- Two (2) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- The discharge pressure shall be provided with the valve control system.

2-1/2" CROSS LAY(S)

There shall be one (1) 2-1/2" cross lay(s) located in pump module, or per the itemized compartment list. The crosslay(s) shall be transverse of the pump module or body with access from either side.

Each cross lay shall have a minimum storage capacity of 200' of 2-1/2" double jacket hose and nozzle.

- One (1) of the discharge(s) shall flow water and foam.
- One (1) Akron Brass 8900 series Gen II, actuated type 2-1/2" (65 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
 - An Akron 9325 Navigator Pro electric valve position controller with wire harness and full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, flow meter (GPM or LPM), pressure meter (PSI or KPa), and VMUX capable integration shall be located on the pump operator's panel. A pressure and flow sensor shall be provided in discharge plumbing.

Aspen Fire Protection District

Type III Engine, SVI #1080

- There shall be a 2-1/2" (65 mm) VFC x 2-1/2" (65 mm) NSTM brass or chrome plated 90 degree swivel elbow provided for each discharge.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- The discharge pressure shall be provided with the valve control system.

3" DECK GUN DISCHARGE

There shall be one (1) 3" (75 mm) gated discharge located on the upper deck above the pump compartment. Piping shall rise high enough for a mounted deluge gun to be operated in a 360 degree circle to a lower angle of 15 degrees without being impeded by any part of the apparatus or equipment.

The discharge plumbing shall terminate as required by deck gun model. The discharge shall include:

- One (1) of the discharge(s) shall flow water only.
- One (1) Akron Brass 8900 series Gen II slow-operating, actuated type 3" (75 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
- An Akron 9323 Navigator Pro electric valve position controller and wire harness with full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, and VMUX capable integration shall be located on the pump operator's panel.
- One (1) Innovative Controls model 3003000, 3/4" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with blue (water) LED backlighting activated with pump engagement.
 - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
 - Gauge(s) shall have a range from 0 to 400 PSI.
 - The gauge shall have a die cast zinc, chrome plated bezel with color-coded labels insert and a color-coded gauge trim ring. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

DECK GUN MONITOR

An Akron Apollo model 3423 lift-off style deck monitor with 1,250 GPM capacity, manually controlled deck gun shall be provided with completed unit with following features;

- Vertical travel from 90° above to 15° below horizontal, with built-in 35° safety stop
- 3" waterway with cast-in turning vanes for efficient flow
- Direct mount - a combination 3" NPT female and 3" flange

Aspen Fire Protection District

Type III Engine, SVI #1080

TELESCOPING WATERWAY

No deck gun riser shall be provided on completed unit.

MASTER STREAM TIP

The specified deck gun shall be provided with an Akron Akromatic model 5160 Pyrolite automatic, master stream tip capable of flowing 1,250 GPM.

STACKED TIPS

The specified deck gun shall be provided with an Akron model 2499 Pyrolite quad stacked deluge tips, and an Akron model 3488 Pyrolite, 3-1/2" F x 3" M cast discharge pipe.

GROUND BASE

The specified deck gun shall be provided with an Akron dual 2-1/2" inlet ground base.

BOOSTER REEL

There shall be one (1) Hannay SBEF30-23-24 polished aluminum booster hose reel discharge(s) with electric rewind motor located in upper pump module or lower compartment per itemized compartment layout. Reel shall be capable of holding 200' of 1" booster hose.

- Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and not be more than 72 in. (1830 mm) above the operator's standing position, and shall be marked with a label indicating its function.

Booster Reel will be located in RC-1

- There shall be one (1) male quick connector type air connection(s) to provide low pressure air blow-out of reel. Air inlet shall be located near reel rewind control and provided with a check valve.
- Each booster hose reel shall be equipped with a Hannay FH-3 hose guide rollers.
- Each booster reel shall be supplied with 100' x 1" of lightweight 100% polyester booster hose with 1" NST Pyrolite couplings. Hose color shall be red.
- No nozzle is required with specified booster hose reel(s).
- One (1) of the discharge(s) shall flow water only.
- One (1) of the discharge(s) shall flow water and foam.

Aspen Fire Protection District

Type III Engine, SVI #1080

- One (1) Akron Brass 9600 series Gen II, actuated type 2" (52 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
- An Akron 9323 Navigator Pro electric valve position controller and wire harness with full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, and VMUX capable integration shall be located on the pump operator's panel.
- One (1) Innovative Controls model 3003000, ¾" brass 90 degree ball type drain valve(s) with lift type handle which can be opened under pressure, with color coded label shall be provided. Valve(s) shall be located on bottom of pump panel and drain the lowest point in the plumbing.
- One (1) Innovative Controls/NoShok 2-1/2" liquid filled gauge(s) with blue (water) LED backlighting activated with pump engagement.
 - Gauge(s) shall have a white background with black text and blue (water) or red (foam) pie indicator.
 - Gauge(s) shall have a range from 0 to 400 PSI.
 - The gauge shall have a die cast zinc, chrome plated bezel with color-coded labels insert and a color-coded gauge trim ring. Labels shall be UV and scratch resistant and meet SAE standards where applicable.

TANK FILL VALVE

There shall be one (1) 2" (52 mm) tank fill valve plumbed with 2" plumbing from the pump to the tank. Installation shall be completed with 2" rubber hose and stainless steel hose couplings. The tank fill valve shall be controlled from the operator's control panel.

- One (1) Akron Brass 8900 series Gen II, manual type 2" (52 mm) valve(s) with Fusion CF composite ball. Each valve shall be equipped with a Class 1 stainless steel weld type valve adapter on inlet side, and discharge side with drain port.
 - The specified Akron valve(s) shall be configured for 12 VDC electric actuation.
- An Akron 9323 Navigator Pro electric valve position controller and wire harness with full color LCD display visible from all angles, true position feedback, user programmable presets, % open text shown on valve bar graph, and VMUX capable integration shall be located on the pump operator's panel.

PUMP PANEL

The side mount pump control panel shall be hinged, or bolted in place allowing it to be easily removed to gain access to plumbing components.

The pump controls shall be mounted on an aluminum control panel with a black powdercoat painted finish.

Aspen Fire Protection District

Type III Engine, SVI #1080

PUMP PANEL LOCATION

The pump control panel shall be side mounted.

The pump panel shall include the following items;

PUMP PANEL ACCESS

The pump panel shall be open to the side of the truck. The Pump Operator shall NOT be required to open a compartment door to access the pump control panel.

ENGINE GAUGES

The cab/chassis engine gauges shall be provided with the specified pump pressure governor system.

PRESSURE GOVERNOR and ENGINE MONITORING DISPLAY

A Fire Research PumpBoss series PBA401-D00 pressure governor and monitoring display kit shall be provided and installed for Cummins engine. The kit shall include a control module, intake pressure sensor, discharge pressure sensor, and cables. The control module case shall be waterproof and have dimensions not to exceed 6 3/4" high by 4 5/8". The control knob shall be 2" in diameter with no mechanical stops, have a serrated grip, and a red idle push button in the center. It shall not extend more than 1 3/4" from the front of the control module. Inputs for monitored engine information shall be from a J1939 data bus or independent sensors. Outputs for engine control shall be on the J1939 databus or engine specific wiring. Inputs from the pump discharge and intake pressure sensors shall be electrical.

The following continuous displays shall be provided:

- Engine RPM; shown with four daylight bright LED digits more than 1/2" high
- Check engine and stop engine warning LEDs
- Engine oil pressure; shown on a dual color (green/red) LED bar graph display
- Engine coolant temperature; shown on a dual color (green/red) LED bar graph display
- Transmission Temperature: shown on a dual color (green/red) LED bar graph display
- Battery voltage; shown on a dual color (green/red) LED bar graph display
- Pressure and RPM operating mode LEDs
- Pressure / RPM setting; shown on a dot matrix message display
- Throttle ready LED.

A dot-matrix message display shall show diagnostic and warning messages as they occur. It shall show monitored apparatus information, stored data, and program options when selected by the operator. All LED intensity shall be automatically adjusted for day and night time operation.

The program shall store the accumulated operating hours for the pump and engine to be displayed with the push of a button. It shall monitor inputs and support audible and visual warning alarms for the following conditions:

| | |
|--|---|
| • High Battery Voltage | • Low Engine Oil Pressure |
| • Low Battery Voltage (Engine Off) | • High Engine Coolant Temperature |
| • Low Battery Voltage (Engine Running) | • Out of Water (visual alarm only) |
| • High Transmission Temperature | • No Engine Response (visual alarm only). |

The program features shall be accessed via push buttons located on the front of the control module. There shall be a USB port located at the rear of the control module to upload future firmware enhancements.

Aspen Fire Protection District

Type III Engine, SVI #1080

The governor shall operate in two control modes, pressure and RPM. No discharge pressure or engine RPM variation shall occur when switching between modes. A throttle ready LED shall light when the interlock signal is recognized. The governor shall start in pressure mode and set the engine RPM to idle. In pressure mode the governor shall automatically regulate the discharge pressure at the level set by the operator. In RPM mode the governor shall maintain the engine RPM at the level set by the operator except in the event of a discharge pressure increase. The governor shall limit a discharge pressure increase in RPM mode to a maximum of 30 psi. Other safety features shall include recognition of no water conditions with an automatic programmed response and a push button to return the engine to idle.

MASTER INTAKE/PRESSURE GAUGES

There shall be one (1) Innovative Controls/NoShok 4" liquid filled gauge to display the Master Intake Pressure, and labeled "PUMP INTAKE".

There shall be one (1) Innovative Controls/NoShok 4" liquid filled gauge to display the Master Discharge Pressure. Gauge shall be labeled "PUMP DISCHARGE".

Both gauges shall have a die cast zinc, chrome plated bezel and color-coded. The left side (Pump Intake) bezel shall be color coded red, and the right side (Pump Discharge) bezel shall be colored black.

A test gauge port manifold shall be integrated into lower center bezel.

- Gauge(s) shall have a white background with black text.
- Gauge(s) shall have a range from -30" to 600 PSI.

PUMP SAFETY AND TEST LABELS

Safety, information, data, and instruction labels for apparatus shall be provided and installed at the operator's instrument panel.

The labels shall include rated capacities, pressure ratings, and engine speeds as determined by the certification tests. The no-load governed speed of the engine, as stated by the engine manufacturer, shall also be included.

The labels shall be provided with all information and be attached to the apparatus prior to delivery.

PUMP PANEL LIGHTING

All gauges and controls on the pump operator's panel shall be adequately illuminated by a full panel width shielded light assembly with full width OnScene Solutions LED light (each panel, if equipped). The light shall be activated by a weather-proof type switch on the pump operator's panel as well as automatically when pump is engaged. This switch shall also activate any area step lighting.

PUMP PANEL AIR HORN SWITCH

The pump operator's panel shall have an Innovative Controls switch panel to activate the cab/chassis air horn(s). Switch shall be constantly illuminated and labeled.

Aspen Fire Protection District

Type III Engine, SVI #1080

LOW PRESSURE AIR OUTLET

There shall be one (1) air outlet connection to supply low pressure air for general maintenance. The outlet shall terminate in a 1/4" NPT threaded port. Air outlet shall be located on lower pump operator's panel. The connector shall be supplied by the Aspen Fire Protection District.

BACK PACK FILLER VALVE

A brass, 3/4", quarter turn ball valve with chrome T-handle shall be supplied and labeled "Back Pack Filler". The valve shall be installed on the streetside lower forward side of the pump panel with the discharge hose terminating at the outside of the apparatus body. The valve plumbing shall be 3/4" I.D. properly routed and clamped from the tank sump to the filler valve.

POLY WATER TANK

The water tank capacity shall be approximately 750 US gallon or 416 Imperial gallons. Certification of the tank capacity shall be recorded on the manufacturer's record of construction and shall be provided to the purchaser upon delivery of the apparatus.

CONSTRUCTION

The tank must be designed and fabricated by a tank manufacturer that is ISO 9001:2008 certified. The ISO certification must be to the current standard in effect at the time of the design and fabrication of the tank.

The water tank shall be of a specific configuration and designed to be completely independent of the body and compartments. Joints and seams shall be fused using nitrogen gas as required and tested for maximum strength and integrity. The tank construction shall include PolyProSeal™ technology wherein a sealant shall be installed between the plastic components prior to being fusion welded. This sealing method will provide a liquid barrier offering leak protection in the event of a weld compromise. The top of the booster tank is fitted with removable lifting assembly designed to facilitate tank removal. The transverse and longitudinal swash partitions shall be manufactured of a minimum of 3/8" PT3™ polypropylene. All partitions shall be equipped with vent and air holes to permit movement of air and water between compartments. The partitions shall be designed to provide maximum water flow. All swash partitions interlock with one another and are completely fused to each other as well as to the walls of the tank. All partitions and spacing shall comply with NFPA 1901. The walls shall be welded to the floor of the tank providing maximum strength as part of the tank's unique Full Floor Design™. Tolerances in design allow for a maximum variation of 1/8" on all dimensions.

Aspen Fire Protection District

Type III Engine, SVI #1080

WATER FILL TOWER AND COVER

The tank shall have a combination vent and manual fill tower. The fill tower shall be constructed of 1/2" PT3™ polypropylene and shall be a minimum dimension of 8" x 8" outer perimeter. The fill tower shall be blue in color indicating that it is a water-only fill tower. The tower shall be located in the left front corner of the tank unless otherwise specified by the tank manufacturer to the purchaser. The tower shall have a 1/4" thick removable polypropylene screen and a PT3™ polypropylene hinged cover. The capacity of the tank shall be engraved on the top of the fill tower lid. Inside the fill tower there shall be a combination vent/overflow pipe. The vent overflow shall be a minimum of schedule 40 polypropylene pipe with a minimum I.D. of 4" that is designed to run through the tank, and shall be piped to discharge water behind the rear wheels as required in NFPA 1901 so as to not interfere with rear tire traction.

The tank cover shall be constructed of 1/2" thick PT3™ polypropylene and UV stabilized, to incorporate a multi-piece locking design, which allows for individual removal and inspection if necessary. The tank cover(s) shall be flush or recessed 3/8" from the top of the tank and shall be fused to the tank walls and longitudinal partitions for maximum integrity. Each one of the covers shall have hold downs consisting of 2" minimum polypropylene dowels spaced a maximum of 40" apart. These dowels shall extend through the covers and will assist in keeping the covers rigid under fast filling conditions. A minimum of two lifting dowels shall accommodate the necessary lifting hardware.

SUMP

There shall be one (1) sump standard per tank. The sump shall be constructed of a minimum of 1/2" PT3™ polypropylene and be located in the left front quarter of the tank, unless specified otherwise. On all tanks that require a front suction, a 3" schedule 40 polypropylene pipe shall be installed that will incorporate a dip tube from the front of the tank to the sump location. The sump shall have a minimum 3" N.P.T. threaded outlet on the bottom for a drain plug per NFPA. This shall be used as a combination clean-out and drain. All tanks shall have an anti-swirl plate located approximately 3" above the inside floor.

OUTLETS

There will be two (2) standard tank outlets: one for the tank-to-pump suction line, which shall be sized to provide adequate water flow to the pump; and, one for tank fill line, which shall be sized according to the NFPA minimum size chart for booster tanks. All tank fill couplings shall be backed with flow deflectors to break up the stream of water entering the tank, and be capable of withstanding sustained fill rates of up to 1000 G.P.M. The addition of rear suction fittings, nurse valve fittings, dump valve fittings, and through-the-tank sleeves to accommodate rear discharge piping must be specified. All auxiliary outlets and inlets must meet all NFPA guidelines in effect at the time of manufacture.

MOUNTING

The tank shall rest on the body cross members in conjunction with such additional cross members, spaced at a distance that would not allow for more than 530 square inches of unsupported area under the tank floor. In cases where overall height of the tank exceeds 40 inches, cross member spacing must be decreased to allow for not more than 400 square inches of unsupported area.

The tank must be isolated from the cross members through the use of hard rubber strips with a minimum thickness and width dimension of 1/4" x 1" and a Shore A Hardness of approximately 60 durometer. The rubber must be installed so it will not become dislodged during normal operation of the vehicle. Additionally, the tank must be supported around the entire bottom outside perimeter and captured both in the front and rear as well as side to side to prevent tank from shifting during vehicle operation.

A picture frame type cradle mount with a minimum of 2" x 2" x 1/4" mild steel, stainless steel, or aluminum angle shall be provided or the use of corner angles having a minimum dimension of 4" x 4" x 1/4" by 6" high are permitted for the purpose of capturing the tank.

Aspen Fire Protection District

Type III Engine, SVI #1080

Although the tank is designed on a free floating suspension principle, it is required that the tank have adequate vertical hold down restraints to minimize movement during vehicle operation. If proper retention has not been incorporated into the apparatus hose floor structure, an optional mounting restraint system shall be located on top of the tank, half way between the front and the rear on each side of the tank. These stops can be constructed of steel, stainless steel or aluminum angle having minimum dimensions of 3" x 3" x 1/4" and shall be approximately 6" to 12" long. These brackets must incorporate rubber isolating pads with a minimum thickness of 1/4" inch and a hardness of 60 durometer affixed on the underside of the angle. The angle should then be bolted to the body side walls of the vehicle while extending down to rest on the top outside edge of the upper side wall of the tank. Hose beds floors must be so designed that the floor slat supports extend full width from side wall to side wall and are not permitted to drop off the edge of the tank or in any way come in contact with the individual covers where a puncture could occur. Tank top must be capable of supporting loads up to 200 lbs per sq. foot when evenly distributed. Other equipment such as generators, portable pumps, etc. must not be mounted directly to the tank top unless provisions have been designed into the Poly-Tank® III for that purpose. The tank shall be completely removable without disturbing or dismantling the apparatus structure.

CENTER OF GRAVITY

A center of gravity calculation shall be determined for each tank and provided as requested in order to provide the apparatus manufacturer with the necessary data to design and certify the apparatus with respect to the NFPA requirements regarding rollover stability.

WATER TANK LEVEL GAUGE

There shall be one (1) Innovative Controls SL series 10-LED water tank level gauge(s) for indicating water tank level. The tank level gauge shall indicate the liquid level on an easy to read display.

Each tank level gauge system shall include:

- A pressure transducer that is mounted on the outside of the tank in an easily accessible area.
- A super bright LED bar graph display with a visual alarm at 1/4 of a tank. The display shall also provide an output to activate an audible alarm or secondary visual alarm at 1/4 of a tank.
- A set of weather resistant connectors to connect the digital display to the pressure transducer and to the apparatus power.

UPF POLY WATER TANK WARRANTY

The UPF poly water tank shall be provided with a lifetime material and workmanship limited warranty. The manufacturer shall supply details of their warranty information with their bid submission.

FILL TOWER PROTECTION

The fill tower(s) shall be boxed in with an aluminum panel for protection from damage.

Aspen Fire Protection District

Type III Engine, SVI #1080

CLASS A POLYPROPYLENE FOAM CELL

There shall be one (1) 20 US gallon or 16.6 Imperial gallons polypropylene foam cell incorporated into the polypropylene water tank. This foam tank capacity shall be deducted from water tank size specified.

There shall be one (1) pressure/vacuum vent installed on the foam tank.

A minimum 1 in. (25 mm) inside diameter full flow drain valve and piping shall be provided at the lowest point of any foam concentrate tank. The drain shall be piped to drain directly to the surface beneath the apparatus without contacting other body or chassis components.

A label shall be affixed to the foam tank fill indicating: "WARNING" Class A foam tank fill, do not mix brands or types of foam.

FOAM TANK LEVEL GAUGE

There shall be one (1) Innovative Controls SL series 10-LED foam tank level gauge(s) for indicating foam tank level. The gauge shall indicate the liquid level on an easy to read display.

Each tank level gauge system shall include:

- A pressure transducer that is mounted on the outside of the tank in an easily accessible area.
- A super bright LED bar graph display with a visual alarm at 1/4 of a tank. The display shall also provide an output to activate an audible alarm or secondary visual alarm at 1/4 of a tank.
- A set of weather resistant connectors to connect the digital display to the pressure transducer and to the apparatus power.

HOSE BED STORAGE AREA

Hose bed storage area shall be located over water tank and body, and shall exit at the rear of the apparatus. The interior of storage area shall be free from all projections such as nuts, sharp angles, or brackets that may damage equipment.

ALUMINUM HOSE BED DECKING

The hose bed deck shall be constructed from 3" x 3/4" hollow aluminum extrusions welded into a one-piece grid to allow ventilation and water drainage. The extrusions shall have a radiused ribbed top surface. The deck will be completely removable for easy access to the booster tank. The booster tank fill tower shall be protected as necessary to prevent damage from equipment located in the storage area.

FILL TOWER PROTECTION

The fill tower(s) shall be boxed in with an aluminum panel for protection from damage.

HOSE BED STORAGE

The following fire hose shall be stored in hose bed storage area;

- Thirteen (13) 100' lengths of 3" rubber hose, flat lay.

Aspen Fire Protection District

Type III Engine, SVI #1080

HOSE BED DIVIDER(S)

One (1) adjustable aluminum hose bed divider(s) shall be provided in the hose bed storage area. The dividers(s) shall be fabricated from 3/16" smooth aluminum with 1" round split aluminum tubing welded to the top and rear edges. A radiused hand-hold opening shall be provided on rear of divider to assist in access to hose bed area. Hose pay-out shall be unobstructed by the divider.

ALUMINUM HOSE BED COVER

A two-section hose bed cover shall be provided. Each door shall be fabricated from 1/8" NFPA aluminum treadplate with formed hat sections for bracing. Doors shall be hinged along each side of the hose body using stainless steel piano hinge. The top surface of each section shall slant down with the highest point in the center of the hose bed area and shall be supported from underneath by at least one (1) adjustable hose bed divider. Each section shall be constructed to support the weight of a 300 lb. person.

A flashing warning light signal shall be provided indicating when a hose bed door is not in a closed position as required by NFPA 1901.

There shall be one (1) 24" vertical handrail on each door to assist in raising and lowering hose bed door. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

Each door shall have a 36" OnScene LED light on the underside of the door that will be automatically activated when the door is opened.

A red cargo netting flap shall be provided with yellow pulls with reflective bungee attached to each door and extend downward to bottom of hose bed to protect hose and equipment from weather and dust. The center where both doors come together shall have a Velcro seam to join two-pieces of vinyl together. Bottom of each flap shall be weighted for quick deployment of hose. Vinyl color shall be color coordinated with upper vehicle colors unless specified otherwise.

AIR ASSIST

Each hose bed door shall have a single air actuator located in the front of hose bed utilized to open and close the hose bed doors.

A switch shall be located at the rear of the unit in a convenient location allowing the operator to view the hose bed doors while operating. The switch shall be interlocked with the parking brake and is only operable when the parking brake is applied. The doors are connected to the open door warning system when in the open condition. An audible alarm is located towards the front of the hosebed area designed to warn possible occupants of the hosebed area that door movement is occurring. The switch location shall be located no more than 72" off the ground level.

HOSE BED FULL WIDTH EXTENSION

A full width, bolt-on type hose bed extension step shall be provided. Step shall be fabricated from 3/16" NFPA compliant treadplate aluminum with side gusset supports to body. The specified center rear marker lights shall be located on rear facing edge. The underside of step shall have a 36" OnScene LED light to light the bumper or compartment area below.

Aspen Fire Protection District

Type III Engine, SVI #1080

EQUIPMENT PAYLOAD WEIGHT ALLOWANCE

In compliance with NFPA 1901 standards, the pumper shall be designed for an equipment loading allowance of 2,000 lbs. of Aspen Fire Protection District provided equipment based on the body having less than 250 cu. ft. of storage space.

SHELVING/TRAY ALLOWANCE

A shelving and tray allowance of \$5,000.00 is included in total bid amount. Layout to be determined at pre-construction meeting. Any un-used amount will be credited back to department at end of project build.

EQUIPMENT

The following equipment shall be furnished with the completed pumper vehicle;

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- There shall be two (2) Zico SAC-44-E NFPA approved folding aluminum wheel chocks provided for 44" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20 % grade, with the transmission in neutral, and the parking brake released.
 - The wheel chock(s) shall be mounted behind rear wheels in fender panels, one each side. Wheel chock compartment shall be provided with a door.
- One (1) Duo-Safety 900-A series 24' 2-section extension ladder(s) shall be provided with the completed unit.
 - The ladder(s) shall be mounted on specified ladder rack.
- One (1) Duo-Safety 775A series 14' aluminum roof ladder(s) shall be provided with the completed unit.
 - The ladder(s) shall be mounted on specified ladder rack.
- One (1) Duo-Safety 585-A 10' aluminum folding ladder(s) shall be provided with the completed unit.
 - The ladder(s) shall be mounted on specified ladder rack.
- One (1) Duo-Safety 6' fiberglass pike pole(s) shall be provided with the completed unit.
 - The above specified pike pole will not have a D handle attached
 - The pike pole(s) shall be mounted on vehicle, per itemized compartment list.
- One (1) Duo-Safety 8' fiberglass pike pole(s) shall be provided with the completed unit.
 - The above specified pike pole will not have a D handle attached
 - The pike pole(s) shall be mounted on vehicle, per itemized compartment list.

Aspen Fire Protection District

Type III Engine, SVI #1080

- One (1) 20 lb. ABC dry chemical aluminum fire extinguisher(s) shall be provided with the completed unit.
 - The above specified fire extinguisher(s) shall be installed on the completed unit, location to be determined by the Aspen Fire Protection District.
- One (1) 2-1/2 gallon pressurized water (Class A) fire extinguisher(s) shall be provided with the completed unit.
 - The above specified fire extinguisher(s) shall be installed on the completed unit, location to be determined by the Aspen Fire Protection District.
- Two (2) Streamlight FireBox LED flashlight(s) with shoulder strap shall be provided be provided with 540/330 lumen output and 7/15 hour run time.. Each flashlight shall be orange in color and have a 12 volt DC charger and vehicle mount kit. Each flashlight shall have a LED E-Spot spotlight style bulbs and reflectors with 2 ultra-bright LED taillights. The flashlight(s) shall be wired to battery direct unless otherwise specified by Aspen Fire Protection District.
 - The flashlight(s) shall be mounted on the completed unit in the cab area.
- Two (2) Kochek 6.0" x 10' Flexlite PVC flexible suction hose(s) shall be provided with completed unit. The hose shall have light weight Storz, 2-lug couplings provided.
- One (1) 6" barrel strainer(s) with foot valve shall be provided with completed unit. Barrell strainer hard suction end shall match provided hard suction(s).
 - The suction hose(s) shall be mounted on streetside above wheels in formed aluminum hard suction tray(s).
 - The suction hose(s) shall be mounted on the specified ladder rack.
- Aspen Fire Protection District supplied NFPA required fire hose and nozzles shall be provided on completed unit before placing vehicle in service.
- There shall be a Blitz Fire without nozzle located on the rear of truck.

REMAINING NFPA MINOR EQUIPMENT BY PURCHASER

All other minor equipment not specified above, but required by NFPA 1901 for pumpers, section 5.9.4 shall be supplied and mounted by Aspen Fire Protection District before the unit is placed in emergency service.